

The `pdfcolparcolumns` package

Heiko Oberdiek*
<heiko.oberdiek at googlemail.com>

2016/05/16 v1.4

Abstract

Since version 1.40 pdftEX supports several color stacks. This package uses them to fix color problems in package `parcolumns`.

Contents

1 Usage	2
1.1 Option <code>rulebetweencolor</code>	2
1.2 Future	2
2 Implementation	2
2.1 Identification	2
2.2 Load packages	3
2.2.1 Package <code>parcolumns</code>	3
2.2.2 Package <code>pdfcol</code>	3
2.2.3 Package <code>infwarerr</code>	3
2.3 Color stack macros	3
2.4 Patches	4
2.4.1 Init stacks	4
2.4.2 Switch stack	4
2.4.3 Set current stack color	4
3 Test	6
4 Installation	7
4.1 Download	7
4.2 Bundle installation	7
4.3 Package installation	8
4.4 Refresh file name databases	8
4.5 Some details for the interested	8
5 Catalogue	9
6 References	9

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

7 History	10
[2007/07/26 v1.0]	10
[2007/09/09 v1.1]	10
[2008/08/11 v1.2]	10
[2010/01/11 v1.3]	10
[2016/05/16 v1.4]	10
8 Index	10

1 Usage

```
\usepackage{pdfcolparcolumns}
```

The package `pdfcolparcolumns` loads package `parcolumns` [1]. If color stacks are available then the macros of `parcolumns` are patched to add support for color stacks.

1.1 Option `rulebetweencolor`

Package `pdfcolparcolumns` also fixes the color for the rule between columns (if `rulebetween` is set). Default color is `\normalcolor`. But this can be changed by using option `rulebetweencolor`. It takes a color specification as value. If the value is empty, then the default (`\normalcolor`) is used. Examples:

```
rulebetweencolor=blue,
rulebetweencolor={red},
rulebetweencolor={}, % \normalcolor is used
rulebetweencolor=[rgb]{1,0,.5} % see below
```

If used inside the optional argument of environment `parcolumns` and the value contains an optional argument, then whole value must be put in curly braces:

```
\begin{parcolumns}[
    rulebetween,
    rulebetweencolor={[rgb]{1,0,.5}},
]{2}
...
\end{parcolumns}
```

This option `rulebetweencolor` can also be set using `\setkeys`:

```
\setkeys{parcolumns}{rulebetweencolor=green}
```

1.2 Future

Currently package `parcolumns` does not seem to be maintained. Nevertheless if there will be a new version that adds support for color stacks, then this package may become obsolete.

2 Implementation

2.1 Identification

```
1 /*package*/
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{pdfcolparcolumns}%
```

```
4 [2016/05/16 v1.4 Color stacks for parcolumns (HO)]%
```

2.2 Load packages

2.2.1 Package `parcolumns`

Currently package `parcolumns` does not define options. Thus it is just a precaution that the options of package `pdfcolparcolumns` are passed to package `parcolumns`.

```
5 \DeclareOption*{%
6   \PassOptionsToPackage{\CurrentOption}{parcolumns}%
7 }
8 \ProcessOptions\relax
9 \RequirePackage{parcolumns}[2004/11/25]
```

2.2.2 Package `pdfcol`

```
10 \RequirePackage{pdfcol}[2007/09/09]
11 \ifpdfcolAvailable
12 \else
13   \PackageInfo{pdfcolparcolumns}{%
14     Loading aborted, because color stacks are not available%
15   }%
16   \expandafter\endinput
17 \fi
```

2.2.3 Package `infwarerr`

```
18 \RequirePackage{infwarerr}[2007/09/09]
```

2.3 Color stack macros

`\pcpc@MaxStack` Macro `\pcpc@MaxStack` holds the highest number of allocated stacks.

```
19 \global\chardef\pcpc@MaxStack=\z@
```

`\pcpc@InitStacks` Macro `\pcpc@InitStacks` takes the number of columns as argument and ensures that there are enough color stacks for all columns.

```
20 \def\pcpc@InitStacks#1{%
21   \ifnum#1>\pcpc@MaxStack
22     \begingroup
23       \count@\pcpc@MaxStack
24       \loop
25         \advance\count@\@ne
26         \pdfcolInitStack{\pcpc@\the\count@}%
27       \ifnum#1>\count@
28       \repeat
29       \global\chardef\pcpc@MaxStack=\count@
30     \endgroup
31   \fi
32 }
```

`\pcpc@SwitchStack`

```
33 \def\pcpc@SwitchStack#1{%
34   \pdfcolSwitchStack{\pcpc@\number#1}%
35 }
```

`\pcpc@SetCurrent`

```
36 \def\pcpc@SetCurrent#1{%
37   \pdfcolSetCurrent{\pcpc@\number#1}%
38 }
```

2.4 Patches

Now the color stack macros are patched into the macros of package `parcolumns`.

2.4.1 Init stacks

`\pcpc@InitStacks` should go into the definition of environment `parcolumns`. `\pc@alloccolumns` is executed there and nowhere else, thus we hook into it.

```
39 \g@addto@macro\pc@alloccolumns{%
40   \pcpc@InitStacks\pc@columncount
41 }
```

2.4.2 Switch stack

`\pcpc@SwitchStack` should be called by macro `\colchunk@`. However it is easier to patch `\pc@setcolumnwidth` that is executed in `\colchunk@` only.

```
42 \g@addto@macro\pc@setcolumnwidth{%
43   \pcpc@SwitchStack\pc@columnctr
44 }
```

2.4.3 Set current stack color

`\pcpc@SetCurrent` is set at the begin of each line. It must be inserted into `\pc@placeboxes`. Unhappily there is no easy way. Therefore we check and redefine `\pc@placeboxes`.

```
45 \begingroup
46   \def\x{%
47     \global\let\tempa\relax
48     \count@\z@
49     \hb@xt@\linewidth{%
50       \vfuzz30ex %
51       \vbadness\@M
52       \splittopskip\z@skip
53       \loop
54         \ifnum\count@<\pc@columncount
55           \advance\count@\@ne
56           \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
57             \hskip\csname pc@column@width@\number\count@\endcsname
58         \else
59           \expandafter\setbox\expandafter\@tempboxa\expandafter
60             \vsplit\csname pc@column@\number\count@\endcsname
61             to \dp\strutbox
62             \vbox{%
63               \unvbox\@tempboxa
64             }%
65         \fi
66         \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
67         \else
68           \global\let\tempa\pc@placeboxes
69         \fi
70         \ifnum\count@<\pc@columncount
71           \strut
72           \hfill
73           \ifpc@rulebetween
74             \vrule
75             \hfill
76           \fi
77     }
```

```

77      \fi
78      \repeat
79  }%
80  \tempa
81 }%
82 \ifx\x\pc@placeboxes
83 \else
84   \@PackageWarning{pdfcolparcolumns}{%
85     Command \string\pc@placeboxes\space has changed.\MessageBreak
86     Supported versions of package ‘parcolumns’: \MessageBreak
87     \space\space 2004/08/05.\MessageBreak
88     The redefinition of \string\pc@placeboxes\space may not%
89     \MessageBreak
90     behave correctly depending on the changes}%
91   }%
92 \fi
93 \endgroup

\pc@placeboxes
94 \renewcommand*{\pc@placeboxes}{%
95   \global\let\tempa\relax
96   \count@\z@
97   \hb@xt@\linewidth{%
98     \vfuzz30ex %
99     \vbadness\@M
100    \splittopskip\z@skip
101    \loop
102      \ifnum\count@<\pc@columncount
103        \advance\count@\@ne
104        \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
105          \hskip\csname pc@column@width@\number\count@\endcsname
106        \else
107          \expandafter\setbox\expandafter\tempboxa\expandafter
108          \vsplit\csname pc@column@\number\count@\endcsname
109            to \dp\strutbox
110          \vbox{%
111            \pcpc@SetCurrent\count@
112            \unvbox\tempboxa
113          }%
114        \fi
115        \expandafter\ifvoid\csname pc@column@\number\count@\endcsname
116        \else
117          \global\let\tempa\pc@placeboxes
118        \fi
119        \ifnum\count@<\pc@columncount
120          \strut
121          \hfill
122          \ifpc@rulebetween
123            \begingroup
124              \pcpc@RuleBetweenColor
125              \vrule
126            \endgroup
127            \hfill
128          \fi
129        \fi
130      \repeat
131    }%
132    \tempa

```

```

133 }

\pcpc@RuleBetweenColorDefault
134 \def\pcpc@RuleBetweenColorDefault{%
135   \normalcolor
136 }

\pcpc@RuleBetweenColor
137 \let\pcpc@RuleBetweenColor\pcpc@RuleBetweenColorDefault

138 \define@key{parcolumns}{rulebetweencolor}{%
139   \edef\pcpc@temp{\#1}%
140   \ifx\pcpc@temp\empty
141     \let\pcpc@RuleBetweenColor\pcpc@RuleBetweenColorDefault
142   \else
143     \edef\pcpc@temp{%
144       \noexpand\ifnextchar[{%
145         \def\noexpand\pcpc@RuleBetweenColor{%
146           \noexpand\color\pcpc@temp
147         }%
148         \noexpand\pcpc@GobbleNil
149       }{%
150         \def\noexpand\pcpc@RuleBetweenColor{%
151           \noexpand\color{\pcpc@temp}%
152         }%
153         \noexpand\pcpc@GobbleNil
154       }%
155       \pcpc@temp\noexpand\@nil
156     }%
157     \pcpc@temp
158   \fi
159 }

\pcpc@GobbleNil
160 \long\def\pcpc@GobbleNil#1\@nil{}

161 </package>

```

3 Test

The test file is a modified version of the file that Donald Goodman has posted in `comp.text.tex`: “Re: xcolor glitches”¹

```

162 {*test1}
163 \NeedsTeXFormat{LaTeX2e}
164 \AtEndDocument{%
165   \typeout{}%
166   \typeout{*****}%
167   \typeout{*** \space Check the PDF file manually! \space ***}%
168   \typeout{*****}%
169   \typeout{}%
170 }
171 \documentclass{article}
172 \usepackage{xcolor}
173 \usepackage{pdfcolparcolumns}
174

```

¹Url: <http://groups.google.com/group/comp.text.tex/msg/8eda74ed292012bb>

```

175 \newcommand{\instruct}[1]{%
176   \noindent
177   \footnotesize
178   \textcolor{red}{#1}%
179 }
180
181 \begin{document}
182   \begin{parcolumns}[colwidths={1=2.3in,2=2.3in},sloppy]{2}%
183     \colchunk[1]{%
184       \instruct{Et non dicitur versus} %
185       Fidelium anim\ae\ %
186       \instruct{%
187         sed immediate subiungitur antiphona finalis %
188         beat\ae\ Mari\ae\ Virginis%
189       } %
190       100.%
191     }%
192     \colchunk[2]{%
193       \instruct{%
194         And the verse %
195         \textcolor{black}{May the souls of the faithful} %
196         is not said, but the final antiphon of the %
197         Blessed Virgin Mary, %
198         \textcolor{black}{100,} %
199         is immediately joined.%
200       }%
201     }%
202   \end{parcolumns}%
203 \end{document}
204 </test1>

```

4 Installation

4.1 Download

Package. This package is available on CTAN²:

[CTAN:macros/latex/contrib/oberdiek/pdfcolparcolumns.dtx](http://ctan.org/pkg/pdfcolparcolumns) The source file.

[CTAN:macros/latex/contrib/oberdiek/pdfcolparcolumns.pdf](http://ctan.org/pkg/pdfcolparcolumns.pdf) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](http://ctan.org/pkg/oberdiek.tds.zip)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:tds/tds.pdf](http://ctan.org/pkg/tds.pdf)). Directories with `texmf` in their name are usually organized this way.

4.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

`unzip oberdiek.tds.zip -d ~/texmf`

²<http://ctan.org/pkg/pdfcolparcolumns>

Script installation. Check the directory `TDS:scripts/oberdiek/` for scripts that need further installation steps. Package `attachfile2` comes with the Perl script `pdfatfi.pl` that should be installed in such a way that it can be called as `pdfatfi`. Example (linux):

```
chmod +x scripts/oberdiek/pdfatfi.pl
cp scripts/oberdiek/pdfatfi.pl /usr/local/bin/
```

4.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TEX`:

```
tex pdfcolparcolumns.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>pdfcolparcolumns.sty</code>	→ <code>tex/latex/oberdiek/pdfcolparcolumns.sty</code>
<code>pdfcolparcolumns.pdf</code>	→ <code>doc/latex/oberdiek/pdfcolparcolumns.pdf</code>
<code>test/pdfcolparcolumns-test1.tex</code>	→ <code>doc/latex/oberdiek/test/pdfcolparcolumns-test1.tex</code>
<code>pdfcolparcolumns.dtx</code>	→ <code>source/latex/oberdiek/pdfcolparcolumns.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

4.4 Refresh file name databases

If your `TEX` distribution (`teTeX`, `mikTeX`, ...) relies on file name databases, you must refresh these. For example, `teTeX` users run `texhash` or `mktexlsr`.

4.5 Some details for the interested

Attached source. The PDF documentation on CTAN also includes the `.dtx` source file. It can be extracted by AcrobatReader 6 or higher. Another option is `pdftk`, e.g. unpack the file into the current directory:

```
pdftk pdfcolparcolumns.pdf unpack_files output .
```

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{pdfcolparcolumns.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the .dtx or the .drv to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex pdfcolparcolumns.dtx
makeindex -s gind.ist pdfcolparcolumns.idx
pdflatex pdfcolparcolumns.dtx
makeindex -s gind.ist pdfcolparcolumns.idx
pdflatex pdfcolparcolumns.dtx
```

5 Catalogue

The following XML file can be used as source for the [TeX Catalogue](#). The elements `caption` and `description` are imported from the original XML file from the Catalogue. The name of the XML file in the Catalogue is `pdfcolparcolumns.xml`.

```
205 (*catalogue)
206 <?xml version='1.0' encoding='us-ascii'?>
207 <!DOCTYPE entry SYSTEM 'catalogue.dtd'>
208 <entry datestamp='$Date$' modifier='$Author$' id='pdfcolparcolumns'>
209   <name>pdfcolparcolumns</name>
210   <caption>Fix colour problems in package 'parcolumns'.</caption>
211   <authorref id='auth:oberdiek' />
212   <copyright owner='Heiko Oberdiek' year='2007,2008,2010' />
213   <license type='lppl1.3' />
214   <version number='1.4' />
215   <description>
216     Since version 1.40 pdfTeX supports colour stacks.
217     This package uses them to fix colour problems in
218     package <xref refid='parcolumns'>parcolumns</xref>.
219     <p/>
220     The package is part of the <xref refid='oberdiek'>oberdiek</xref>
221     bundle.
222   </description>
223   <documentation details='Package documentation'
224     href='ctan:/macros/latex/contrib/oberdiek/pdfcolparcolumns.pdf' />
225   <ctan file='true' path=''/macros/latex/contrib/oberdiek/pdfcolparcolumns.dtx' />
226   <miktex location='oberdiek' />
227   <texlive location='oberdiek' />
228   <install path=''/macros/latex/contrib/oberdiek/oberdiek.tds.zip' />
229 </entry>
230 </catalogue>
```

6 References

- [1] Jonathan Sauer: *The parcolumns package*; 2004/11/25;
CTAN:macros/latex/contrib/sauerj/parcolumns.pdf.
- [2] Heiko Oberdiek: *The pdfcol package*; 2007/09/09;
CTAN:macros/latex/contrib/oberdiek/pdfcol.pdf.

7 History

[2007/07/26 v1.0]

- First version, published in the newsgroup `comp.text.tex` with the name `parcolumns-colorstacks`: “Re: `xcolor` glitches”³

[2007/09/09 v1.1]

- CTAN version, package name renamed to `pdfcolparcolumns`.
- Uses package `pdfcol`.
- Documentation added.
- Test file added.

[2008/08/11 v1.2]

- Code is not changed.
- URLs updated.

[2010/01/11 v1.3]

- Fix for rule color.
- New option `rulebetweencolor` for environment `parcolumns`.

[2016/05/16 v1.4]

- Documentation updates.

8 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	B
<code>\@M</code>	51, 99
<code>\@PackageWarningNoLine</code>	84
<code>\@empty</code>	140
<code>\@ifnextchar</code>	144
<code>\@ne</code>	25, 55, 103
<code>\@nil</code>	155, 160
<code>\@tempa</code>	47, 68, 80, 95, 117, 132
<code>\@tempboxa</code>	59, 63, 107, 112
<code>_l</code>	185, 188
A	C
<code>\advance</code>	25, 55, 103
<code>\ae</code>	185, 188
<code>\AtEndDocument</code>	164
D	
<code>\DeclareOption</code>	5
<code>\define@key</code>	138
<code>\documentclass</code>	171

³Url: <http://groups.google.com/group/comp.text.tex/msg/56bd897b11bca414>

\dp	61, 109	\pcpc@InitStacks	20, 40
		\pcpc@MaxStack	19, 21, 23, 29
		\pcpc@RuleBetweenColor	124, 137, 141, 145, 150
		\pcpc@RuleBetweenColorDefault	134, 137, 141
\end	202, 203	\pcpc@SetCurrent	36, 111
\endcsname	56, 57, 60, 66, 104, 105, 108, 115	\pcpc@SwitchStack	33, 43
\endinput	16	\pcpc@temp	139, 140, 143, 146, 151, 155, 157
		\pdfcolInitStack	26
		\pdfcolSetCurrent	37
		\pdfcolSwitchStack	34
F		\ProcessOptions	8
\footnotesize	177	\ProvidesPackage	3
G		R	
\g@addto@macro	39, 42	\renewcommand	94
		\repeat	28, 78, 130
H		\RequirePackage	9, 10, 18
\hb@xt@	49, 97		
\hfill	72, 75, 121, 127	S	
\hskip	57, 105	\setbox	59, 107
		\space	85, 87, 88, 167
I		\splittopskip	52, 100
\ifnum	21, 27, 54, 70, 102, 119	\strut	71, 120
\ifpc@rulebetween	73, 122	\strutbox	61, 109
\ifpdfcolAvailable	11		
\ifvoid	56, 66, 104, 115	T	
\ifx	82, 140	\textcolor	178, 195, 198
\instruct	175, 184, 186, 193	\the	26
		\typeout	165, 166, 167, 168, 169
L			
\linewidth	49, 97	U	
\loop	24, 53, 101	\unvbox	63, 112
		\usepackage	172, 173
M			
\MessageBreak	85, 86, 87, 89	V	
		\vbadness	51, 99
N		\vbox	62, 110
\NeedsTeXFormat	2, 163	\vfuzz	50, 98
\newcommand	175	\vrule	74, 125
\noindent	176	\vsplit	60, 108
\normalcolor	135		
\number	34,	X	
	37, 56, 57, 60, 66, 104, 105, 108, 115	\x	46, 82
P		Z	
\PackageInfo	13	\z@	19, 48, 96
\PassoptionsToPackage	6	\z@skip	52, 100
\pc@alloccolumns	39		
\pc@columncount	40, 54, 70, 102, 119		
\pc@columncctr	43		
\pc@placeboxes	68, 82, 85, 88, 94		
\pc@setcolumnwidth	42		
\pcpc@GobbleNil	148, 153, 160		