

# Producing slides with L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub>

Frank Mittelbach

2016/03/29

## 1 Introduction

With L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub>  it is now no longer necessary to maintain a special format for producing overhead slides. Instead the standard format may be used and internally only different font definition files come into play.

## 2 Usage

For producing slides you have to use `slides` as the document class. This class is very similar to the `slides` style that came with SL<sup>I</sup>T<sub>E</sub>X, in fact it is basically a copy changed to work under L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub> .<sup>1</sup> Thus you have to say something like

```
\documentclass[...]{slides}
```

and process this with L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub> .

## 3 Fonts

Note, that with NFSS you can easily produce slides with special fonts just by calling an appropriate style file (like `times`) in a `\usepackage` command. This works, for example, with all fonts that are defined to be scaleable (e.g., PostScript fonts) since they can be used at any size by NFSS.

However, packages like `pandora` won't work because the standard `.fd` files shipped with NFSS only contain small sizes. You can, of course, produce additional sizes and change the `.fd` files accordingly so that they would be useable for slides as well.

## 4 Invisible text and color separation

In the original SL<sup>I</sup>T<sub>E</sub>X it was possible to produce invisible text using the `\invisible` command, so that one was able to put several slides on top of each other (with each slides showing additional details, etc.). It was also possible to produce 'color' slides. This was done by producing individual slides one for each color and placing them on top of each other.

---

<sup>1</sup>Therefore you should compare the new class with old SL<sup>I</sup>T<sub>E</sub>X styles in case you have local slide classes to see what you have to change in order to use them with L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub> .

The availability of color printers and the `color` package make color separation obsolete, so it has been removed. Although the `color` has also made `\invisible` obsolete, the command is retained in the L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub>  implementation, but there are a few restrictions. Invisible fonts are implemented as special shapes where the shape names are build by prefixing the normal shape name with an uppercase I. For example, the ‘normal invisible shape’ would be `In`. When L<sup>A</sup>T<sub>E</sub>X is requested to typeset invisible it will thus change the current shape attribute in this manner. To make this work it is necessary that the resulting font shape group is defined. If not, the normal font substitution mechanism of L<sup>A</sup>T<sub>E</sub>X 2 <sub>$\varepsilon$</sub>  will change the attribute until it finds a usable font shape group with the result that the text may become visible.

As long as you use the standard fonts for slides this is not a problem because all the visible font shape groups have invisible counterparts. However, if you decide on using special fonts, e.g., PostScript fonts, your `\DeclareFontShape` settings may not contain invisible font shape groups and thus you may be unable to use these features without adding additional `\DeclareFontShape` commands to your `.fd` files or the preamble of your document.

## 5 The Implementation

**Warning:** The implementation is still very experimental and may change internally very much. It currently basically consists of a slightly modified copy of `slides.sty` (which then forms `slides.cls`) followed by a slightly changed copy of `slitex.tex`. Documentation is practically non-existing. Everybody is invited to help changing this!

The code is divided into two parts, we first implement the class related functions and declarations and then define lowlevel stuff that is necessary within every class. By placing such commands into a separate file it will be possible to share it with other slide classes.

### 5.1 The class code

At this point we input the redefinitions that are necessary for SLiTEx.

```
1 {*class}
2 \input{slides.def}
```

Now we are ready for setting up the font tables. As usual, we first look for a local configuration file `sfonts.cfg`. If there isn’t one, we fall back to the default one (`sfonts.def`).

```
3 \InputIfFileExists{sfonts.cfg}
4   {\typeout{*****^J%
5           *^J%
6           * Local config file sfonts.cfg used^J%
7           *^J%
8           *****}}%
9   {\input{sfonts.def}}
```

## 6 Declaration of Options

We declare a few options as illegal.

## 6.1 Setting Paper Sizes

The variables `\paperwidth` and `\paperheight` should reflect the physical paper size after trimming. For desk printer output this is usually the real paper size since there is no post-processing. Classes for real book production will probably add other paper sizes and additionally the production of crop marks for trimming.

```
10 \DeclareOption{a4paper}
11   {\setlength{\paperheight}{297mm}}
12   \setlength{\paperwidth}{210mm}
13 \DeclareOption{a5paper}
14   {\setlength{\paperheight}{210mm}}
15   \setlength{\paperwidth}{148mm}
16 \DeclareOption{b5paper}
17   {\setlength{\paperheight}{250mm}}
18   \setlength{\paperwidth}{176mm}
19 \DeclareOption{letterpaper}
20   {\setlength{\paperheight}{11in}}
21   \setlength{\paperwidth}{8.5in}
22 \DeclareOption{legalpaper}
23   {\setlength{\paperheight}{14in}}
24   \setlength{\paperwidth}{8.5in}
25 \DeclareOption{executivepaper}
26   {\setlength{\paperheight}{10.5in}}
27   \setlength{\paperwidth}{7.25in}
```

The option `landscape` switches the values of `\paperheight` and `\paperwidth`, assuming the dimensions were given for portrait paper.

```
28 \DeclareOption{landscape}
29   {\setlength{\@tempdima}{\paperheight}}
30   \setlength{\paperheight}{\paperwidth}
31   \setlength{\paperwidth}{\@tempdima}
```

## 6.2 The clock option

The option `clock` prints the time at the bottom of each note. We also define here the commands and counters used to keep track of time.

```
32 \newif\if@clock \clockfalse
33 \DeclareOption{clock}{\@clocktrue
34   \AtEndDocument{\typeout{@arabic\c@minutes\space minutes}}
35 }%
36 \newcounter{minutes}%
37 \newcounter{seconds}%
38 \newcommand*{\settime}[1]{\setcounter{seconds}{0}\addtime{#1}}%
39 \newcommand*{\addtime}[1]{\addtocounter{seconds}{#1}}%
40   \setcounter{minutes}{\value{seconds}}%
41   \global\divide\value{minutes} by 60\relax
42
```

## 6.3 Two-side or one-side printing

Two-sided printing is not allowed, so don't declare an option. But it is necessary to initialize the switch.

```
43 \twosidefalse
```

## 6.4 Draft option

If the user requests `draft` we show any overfull boxes. We could probably add some more interesting stuff to this option.

```
44 \DeclareOption{draft}{\setlength\overfullrule{5pt}}
45 \DeclareOption{final}{\setlength\overfullrule{0pt}}
```

## 6.5 Titlepage option

The default is for a `\maketitle` command to make a new page.

```
46 \newif\if@titlepage
47 \if@titlepage true
48 \DeclareOption{titlepage}{\if@titlepage true}
49 \DeclareOption{notitlepage}{\if@titlepage false}
```

## 6.6 Twocolumn printing

Two-column printing is again forbidden.

```
50 \DeclareOption{onecolumn}{}
51 \DeclareOption{twocolumn}{%
52     \ClassWarning{slides}{No 'twocolumn' layout for slides}}
```

## 6.7 Equation numbering on the left

The option `leqno` can be used to get the equation numbers on the left side of the equation.

```
53 \DeclareOption{leqno}{\input{leqno.clo}}
```

## 6.8 Flush left displays

The option `fleqn` redefines the displayed math environments in such a way that they come out flush left, with an indentation of `\mathindent` from the prevailing left margin.

```
54 \DeclareOption{fleqn}{\input{fleqn.clo}}
```

# 7 Executing Options

Here we execute the default options to initialize certain variables.

```
55 \ExecuteOptions{letterpaper,final}
```

The `\ProcessOptions` command causes the execution of the code for every option `FOO` which is declared and for which the `FOO` option in his `\documentclass` command. For every option `BAR` he typed, which is not declared, the option is assumed to be a global option. All options will be passed as document options to any `\usepackage` command in the document preamble.

```
56 \ProcessOptions
```

# 8 Loading Packages

The standard class files do not load additional packages.

## 9 Document Layout

In this section we are finally dealing with the nasty typographical details.

### 9.1 Fonts

```
57 % FMi:  
58 \def\rmdefault{lcms}          % no roman  
59 \def\sffontdefault{lcms}  
60 \def\ttdefault{lcmtt}  
61 \def\itdefault{s1}  
62 \def\sldefault{s1}  
63 \def\bfdefault{bx}
```

Since the number of parameters to set are very large it seems reasonable to set up one command `\@setfontsize@parms` which will do the work for us.

L<sup>A</sup>T<sub>E</sub>X offers the user commands to change the size of the font, relative to the ‘main’ size. Each relative size changing command `\size` executes the command `\@setfontsize\size<font-size>\baselineskip` where:

`<font-size>` The absolute size of the font to use from now on.

`<baselineskip>` The normal value of `\baselineskip` for the size of the font selected. (The actual value will be `\baselinestretch * <baselineskip>`.)

A number of commands, defined in the L<sup>A</sup>T<sub>E</sub>X kernel, shorten the following definitions and are used throughout. They are:

|                       |       |                      |    |                       |      |
|-----------------------|-------|----------------------|----|-----------------------|------|
| <code>\@vpt</code>    | 5     | <code>\@vipt</code>  | 6  | <code>\@viiipt</code> | 7    |
| <code>\@viiipt</code> | 8     | <code>\@ixpt</code>  | 9  | <code>\@xpt</code>    | 10   |
| <code>\@xipt</code>   | 10.95 | <code>\@xiipt</code> | 12 | <code>\@xivpt</code>  | 14.4 |
| ...                   |       |                      |    |                       |      |

|                                      |                                                                                                                                                                                                                                                                                           |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>\ifourteenpt</code>            | For SLI <sup>T</sup> E <sub>X</sub> , however, these are not sufficient, and we therefore need to add a few extra, larger, sizes.                                                                                                                                                         |
| <code>\iseventeenpt</code>           |                                                                                                                                                                                                                                                                                           |
| <code>\itwentypt</code>              | 64 <code>\def\ifourteenpt{13.82}</code>                                                                                                                                                                                                                                                   |
| <code>\itwentyfourpt</code>          | 65 <code>\def\iseventeenpt{16.59}</code>                                                                                                                                                                                                                                                  |
| <code>\itwenty ninept</code>         | 66 <code>\def\itwentypt{19.907}</code>                                                                                                                                                                                                                                                    |
| <code>\ithirtyfourpt</code>          | 67 <code>\def\itwentyfourpt{23.89}</code>                                                                                                                                                                                                                                                 |
| <code>\ifortyonept</code>            | 68 <code>\def\itwenty ninept{28.66}</code>                                                                                                                                                                                                                                                |
|                                      | 69 <code>\def\ithirtyfourpt{34.4}</code>                                                                                                                                                                                                                                                  |
|                                      | 70 <code>\def\ifortyonept{41.28}</code>                                                                                                                                                                                                                                                   |
| <br><code>\@setfontsize@parms</code> | This routine is used in SLI <sup>T</sup> E <sub>X</sub> to interface font size setting it is modeled after the settings I found in <code>slides.sty</code> , so it probably needs an update. But any class is free to redefine it, as it is used only as an abbreviation. It’s syntax is: |

```
\@setfontsize@parms  
<lineskip>  
<parskip>  
<abovedisplayskip>  
<belowdisplayskip>  
<abovedisplayshortskip>  
<belowdisplayshortskip>  
<strut ht> <strut dp> (without pt)
```

For NFSS1 a similar style existed which did run both with a SLT<sub>E</sub>X with old font selection or with NFSS1. But when no separate format is made this doesn't make much sense. So the following note is history and would only be true if all NFSS stuff would be removed from the file and placed into the format.

Note: To interface the old `sfonts.tex` the `(size)` must be hidden in commands denoting the size by its name prefixed with 'i', i.e. 20pt size is called `\itwentypt` at this point. The NFSS interface will define those sizes to expand to the internal size, e.g. 20 but for the old sfonts the command name, e.g. `\itwentypt`, will be used to construct the name `\twentypt` etc.

This is a crude interface to the old `sfonts.tex`. It will be a bit slower than the old one because it must define `\@tiny` etc. every time a size changes.

If classes are set up that are only for use with NFSS then the second argument may be an ordinary font size!

```

71 \def\@setfontsize@parms#1#2#3#4#5#6#7#8{%
72   \lineskip #1\relax%
73   \parskip #2\relax
74   \abovedisplayskip #3\relax
75   \belowdisplayskip #4\relax
76   \abovedisplayshortskip #5\relax
77   \belowdisplayshortskip #6\relax
78 %

```

I don't see a reason why the `\strutbox` has a dim different from `\baselineskip` but we will leave it for the moment

```

79  \setbox\strutbox=\hbox{\vrule \height#7\p@\depth#8\p@\width\z@\%
80  \baselineskip\baselinestretch\baselineskip
81  \normalbaselineskip\baselineskip}

```

Setting size relations for math scripts:

```

82 \DeclareMathSizes{13.82}{13.82}{10}{7}
83 \DeclareMathSizes{16.59}{16.59}{12}{7}
84 \DeclareMathSizes{19.907}{19.907}{16.59}{13.82}
85 \DeclareMathSizes{23.89}{23.89}{19.907}{16.59}
86 \DeclareMathSizes{28.66}{28.66}{23.89}{19.907}
87 \DeclareMathSizes{34.4}{34.4}{28.66}{23.89}
88 \DeclareMathSizes{41.28}{41.28}{34.4}{28.66}

```

```

\normalsize
89 \def\normalsize{%
90   \@setfontsize\normalsize\itwentypt{28\p@ plus3\p@ minus4\p@}%
91 %           {20}{30\p@ plus3\p@ minus3\p@}% made a bit shorter
92   \@setfontsize@parms
93   {2pt}%
94   {30\p@ plus18\p@ minus9\p@}%
95   {15\p@ plus3\p@ minus3\p@}%
96   {10\p@ plus3\p@ minus3\p@}%
97   {10\p@ plus3\p@}%
98   \abovedisplayshortskip
99   {17}{7}}

```

We initially choose the `normalsize` font.

```
100 \normalsize
```

```

\small
101 \def\small{\@setfontsize\small\iseventeenpt{19\p@ plus3\p@ minus\p@}%
102     \@setfontsize@parms
103     {2\p@}%
104     {15\p@ plus15\p@ minus7\p@}%
105     {12\p@ plus3\p@ minus3\p@}%
106     {9\p@ plus3\p@ minus3\p@}%
107     {6\p@ plus3\p@}%
108     \abovedisplayshortskip
109     {13.5}{5.6}}

\footnotesize
\scriptsize 110 \let\footnotesize=\small
111 \let\scriptsize=\small

\tiny
112 \def\tiny{\@setfontsize\tiny\ifourteenpt{16\p@ plus2\p@ minus\p@}%
113     \@setfontsize@parms
114     {2pt}%
115     {14\p@ plus3\p@ minus10\p@}%
116     {11\p@ plus3\p@ minus10\p@}%
117     \abovedisplayskip
118     {8\p@ plus3\p@ minus5\p@}%
119     {\z@ plus3\p@}%
120     {10}{4}}

```

Actually copying the code above would be better because this would correct the error message. Maybe one should remove the first argument of `\set@font@size@parms`.

```

\large
\Large 121 \def\large{\@setfontsize\large\itwentyfourpt{42\p@ plus8\p@ minus5\p@}%
\Large 122     \@setfontsize@parms
\huge 123     {2\p@}%
\Huge 124     {40\p@ plus20\p@ minus4\p@}%
125     {20\p@ plus8\p@ minus3\p@}%
126     \abovedisplayskip
127     {10\p@ plus5\p@}%
128     \abovedisplayshortskip
129     {20}{8.5}}
130

131 \def\Large{\@setfontsize\Large\itwentyneight{48\p@ plus10\p@ minus6\p@}%
132     \@setfontsize@parms
133     {2\p@}%
134     {48\p@ plus30\p@ minus6\p@}%
135     {24\p@ plus10\p@ minus6\p@}%
136     \abovedisplayskip
137     {12\p@ plus8\p@}%
138     \abovedisplayshortskip
139     {27}{11}}
140

141 \def\LARGE{\@setfontsize\LARGE\ithirtyfourpt{52\p@ plus10\p@ minus6\p@}%
142     \@setfontsize@parms

```

```

143 {2\p@}%
144 {52\p@ plus30\p@ minus6\p@}%
145 {24\p@ plus10\p@ minus6\p@}%
146 \abovedisplayskip
147 {12\p@ plus8\p@}%
148 \abovedisplayshortskip
149 {27}{11}}
150
151 \def\huge{\@setfontsize\huge\ifortyonept{60\p@ plus10\p@ minus6\p@}%
152     \@setfontsize@parms
153     {2\p@}%
154     {60\p@ plus30\p@ minus6\p@}%
155     {24\p@ plus10\p@ minus6\p@}%
156     \abovedisplayskip
157     {12\p@ plus8\p@}%
158     \abovedisplayshortskip
159     {27}{11}}
160
161 \let\Huge\huge

```

## 9.2 Paragraphing

- \baselinestretch** This is used as a multiplier for `\baselineskip`. The default is to *not* stretch the baselines.
- ```
162 \renewcommand\baselinestretch{}
```
- \parindent** `\parindent` is the width of the paragraph indentation.
- ```
163 \setlength\parindent{\z@}
```
- \@lowpenalty** **\@medpenalty** **\@highpenalty** The commands `\nopagebreak` and `\nolinebreak` put in penalties to discourage these breaks at the point they are put in. They use `\@lowpenalty`, `\@medpenalty` or `\@highpenalty`, dependent on their argument.
- ```
164 \@lowpenalty 51
165 \@medpenalty 151
166 \@highpenalty 301
```
- \clubpenalty** **\widowpenalty** These penalties are use to discourage club and widow lines. Because we use their default values we only show them here, commented out.
- ```
167 % \clubpenalty 150
168 % \widowpenalty 150
```
- \displaywidowpenalty** **\predisplaypenalty** **\postdisplaypenalty** Discourage (but not so much) widows in front of a math display and forbid breaking directly in front of a display. Allow break after a display without a penalty. Again the default values are used, therefore we only show them here.
- ```
169 % \displaywidowpenalty 50
170 % \predisplaypenalty 10000
171 % \postdisplaypenalty 0
```
- \interlinepenalty** Allow the breaking of a page in the middle of a paragraph.
- ```
172 % \interlinepenalty 0
```
- \brokenpenalty** We allow the breaking of a page after a hyphenated line.
- ```
173 % \brokenpenalty 0
```

## 9.3 Page Layout

All margin dimensions are measured from a point one inch from the top and lefthand side of the page.

### 9.3.1 Vertical spacing

- \headheight The \headheight is the height of the box that will contain the running head. The  
\headsep \headsep is the distance between the bottom of the running head and the top of  
\topskip \topskip is the \baselineskip for the first line on a page.

```
174 \setlength\headheight{14\p@}  
175 \setlength\headsep    {15\p@}  
176 \setlength\topskip   {30\p@}
```

- \footskip The distance from the baseline of the box which contains the running footer to  
the baseline of last line of text is controlled by the \footskip. Bottom of page:  
177 \setlength\footskip{25\p@} %

- \maxdepth The TeX primitive register \maxdepth has a function that is similar to that of  
\@maxdepth. The register \@maxdepth should always contain a copy of \maxdepth.  
In both plain TeX and L<sup>A</sup>T<sub>E</sub>X 2.09 \maxdepth had a fixed value of 4pt; in native  
L<sup>A</sup>T<sub>E</sub>X2e mode we let the value depend on the typesize. We set it so that \maxdepth  
+ \topskip = typesize  $\times$  1.5. As it happens, in these classes \topskip is equal  
to the typesize, therefor we set \maxdepth to half the value of \topskip.

```
178 \if@compatibility  
179   \setlength\maxdepth{4\p@}  
180 \else  
181   \setlength\maxdepth{.5\topskip}  
182 \fi  
183 \setlength\@maxdepth\maxdepth
```

### 9.3.2 The dimension of text

- \textwidth When we are in compatibility mode we have to make sure that the dimensions of  
the printed area are not different from what the user was used to see.

```
184 \if@compatibility  
185   \setlength\textwidth{460\p@}
```

When we are not in compatibility mode we can set some of the dimensions differently,  
taking into account the paper size for instance.

```
186 \else  
First, we calculate the maximum textwidth, which depends on the papersize. Then  
we calculate the approximate length of 65 characters, which should be the maxi-  
mum length of a line of text. The calculated values are stored in \@tempdima and  
\@tempdimb.
```

```
187 \setlength\@tempdima{\paperwidth}  
188 \addtolength\@tempdima{-2in}  
189 \setbox\@tempboxa\hbox{\rmfamily im}  
190 \setlength\@tempdimb{.5\wd\@tempboxa}  
191 \setlength\@tempdimb{65\@tempdimb}
```

Now we can set the `\textwidth`, depending on whether we will be setting one or two columns.

The text should not be wider than the minimum of the paperwidth (minus 2 inches for the margins) and the maximum length of a line as defined by the number of characters.

```
192 \ifdim\@tempdima>\@tempdimb\relax
193   \setlength\textwidth{\@tempdimb}
194 \else
195   \setlength\textwidth{\@tempdima}
196 \fi
197 \fi
```

Here we modify the width of the text a little to be a whole number of points.

```
198 \settowidth\textwidth
```

```
\columnwidth
\columnsep 199 \columnwidth \textwidth
\columnseprule 200 \columnsep 10pt
201 \columnseprule \z@
```

`\textheight` Now that we have computed the width of the text, we have to take care of the height. The `\textheight` is the height of text (including footnotes and figures, excluding running head and foot).

First make sure that the compatibility mode gets the same dimensions as we had with L<sup>A</sup>T<sub>E</sub>X2.09. The number of lines was calculated as the floor of the old `\textheight` minus `\topskip`, divided by `\baselineskip` for `\normalsize`. The old value of `\textheight` was 528pt.

```
202 \if@compatibility
203   \setlength\textheight{600\p@}
```

Again we compute this, depending on the papersize and depending on the `\baselineskip` that is used, in order to have a whole number of lines on the page.

```
204 \else
205   \setlength\@tempdima{\paperheight}
```

We leave at least a 1 inch margin on the top and the bottom of the page.

```
206   \addtolength\@tempdima{-2in}
```

We also have to leave room for the running headers and footers.

```
207   \addtolength\@tempdima{-1in}
```

Then we divide the result by the current `\baselineskip` and store this in the count register `\@tempcnta`, which then contains the number of lines that fit on this page.

```
208   \divide\@tempdima\baselineskip
209   \@tempcnta=\@tempdima
```

From this we can calculate the height of the text.

```
210   \setlength\textheight{\@tempcnta\baselineskip}
211 \fi
```

The first line on the page has a height of `\topskip`.

```
212 \advance\textheight by \topskip
```

### 9.3.3 Margins

\oddsidemargin First we give the values for the compatibility mode.

\evensidemargin Values for two-sided printing:

```

213 \if@compatibility
214   \setlength\oddsidemargin {17\p@}
215   \setlength\evensidemargin {17\p@}
216   \setlength\marginparwidth {20\p@}
217 \else

```

When we are not in compatibility mode we can take the dimensions of the selected paper into account.

We center the text on the page, by calculating the difference between `textwidth` and `\paperwidth - 2in`. Half of that difference is then used for the margin. The amount of space that can be used for marginal notes is at least 0.8 inch, to which we add any ‘leftover’ space.

```

218 \setlength\@tempdima {\paperwidth}
219 \addtolength\@tempdima {-2in}
220 \addtolength\@tempdima {-\textwidth}
221 \setlength\oddsidemargin {.5\@tempdima}
222 \setlength\marginparwidth {.8in}
223 \addtolength\marginparwidth {.5\@tempdima}

```

The `\evensidemargin` can now be computed from the values set above.

```

224 \setlength\evensidemargin {\paperwidth}
225 \addtolength\evensidemargin{-2in}
226 \addtolength\evensidemargin{-\textwidth}
227 \addtolength\evensidemargin{-\oddsidemargin}
228 \fi

```

\marginparsep The horizontal space between the main text and marginal notes is determined by `\marginparsep`, the minimum vertical separation between two marginal notes is controlled by `\marginparpush`.

```

229 \setlength\marginparsep {5\p@}
230 \setlength\marginparpush{5\p@}

```

\topmargin The `\topmargin` is the distance between the top of ‘the printable area’ –which is 1 inch below the top of the paper– and the top of the box which contains the running head.

It can now be computed from the values set above.

```

231 \if@compatibility
232   \setlength\topmargin{-10pt}
233 \else
234   \setlength\topmargin{\paperheight}
235   \addtolength\topmargin{-2in}
236   \addtolength\topmargin{-\headheight}
237   \addtolength\topmargin{-\headsep}
238   \addtolength\topmargin{-\textheight}
239   \addtolength\topmargin{-\footskip} % this might be wrong!

```

By changing the factor in the next line the complete page can be shifted vertically.

```

240 \addtolength\topmargin{-.5\topmargin}
241 \fi
242 \settopoint\topmargin

```

### 9.3.4 Footnotes

|              |                                                                                                                                                                                                      |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| \footnotesep | \footnotesep is the height of the strut placed at the beginning of every footnote. It equals the height of a normal \footnotesize strut in this class, thus no extra space occurs between footnotes. |
|              | 243 \setlength{\footnotesep}{20\p@}                                                                                                                                                                  |
| \footins     | \skip\footins is the space between the last line of the main text and the top of the first footnote.                                                                                                 |
|              | 244 \setlength{\skip\footins}{10\p@ \oplus 2\p@ \ominus 4\p@}                                                                                                                                        |

## 9.4 Page Styles

The page style *foo* is defined by defining the command \ps@*foo*. This command should make only local definitions. There should be no stray spaces in the definition, since they could lead to mysterious extra spaces in the output (well, that's something that should be always avoided).

|            |                                                                                                                                                                                                                                                                            |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| \@evenhead | The \ps@... command defines the macros \oddhead, \oddfoot, \@evenhead, and \evenfoot to define the running heads and feet—e.g., \oddhead is the macro to produce the contents of the heading box for odd-numbered pages. It is called inside an \hbox of width \textwidth. |
| \@oddhead  |                                                                                                                                                                                                                                                                            |

The page styles of slides is determined by the 'slide' page style, the slide environment executing a \thispagestyle{slide} command. The page styles of overlays and notes are similarly determined by 'overlay' and 'note' page styles. The command standard 'headings', 'plain' and 'empty' page styles work by redefining the 'slide', 'overlay', and 'note' styles.

```
\ps@headings
245 \if@compatibility
246 \def\ps@headings{%
247 \def\ps@slide{\def\oddfoot{\@mainsize +\hfil\hb@xt@3em{\theslide
248 \hss}}%
249 \def\oddhead{\@mainsize +\hfil +}%
250 \def\evenfoot{\@mainsize +\hfil\hb@xt@3em{\theslide\hss}}%
251 \def\evenhead{\@mainsize +\hfil +}%
252
253 \def\ps@overlay{\def\oddfoot{\@mainsize +\hfil\hb@xt@3em{\theoverlay
254 \hss}}%
255 \def\oddhead{\@mainsize +\hfil +}%
256 \def\evenfoot{\@mainsize +\hfil\hb@xt@3em{\theoverlay\hss}}%
257 \def\evenhead{\@mainsize +\hfil +}%
258 \def\ps@note{\def\oddfoot{\@mainsize \hbox{} \hfil\thenote}}%
259 \def\oddhead{}%
260 \def\evenfoot{\@mainsize \hbox{} \hfil\thenote}%
261 \def\evenhead{}}
262 %
263 \else %%if@compatibility
264 %
265 \def\ps@headings{%
266   \def\ps@slide{%
267     \def\oddfoot{\@mainsize \mbox{} \hfil\hb@xt@3em{\theslide\hss}}%
```

```

268     \def\@oddhead{}%
269     \def\@evenfoot{\@mainsize \mbox{}\hfil\hb@xt@3em{\theslide\hss}}%
270     \def\@evenhead{}%
271
272 \def\ps@overlay{%
273     \def\@oddfoot{\@mainsize \mbox{}\hfil\hb@xt@3em{\theoverlay\hss}}%
274     \def\@oddhead{}%
275     \def\@evenfoot{\@mainsize \mbox{}\hfil\hb@xt@3em{\theoverlay\hss}}%
276     \def\@evenhead{}%
277
278 \def\ps@note{%
279     \def\@oddfoot{%
280         \@mainsize
281         \if@clock
282             \fbox{\large \@arabic\c@minutes\space min}%
283         \else
284             \null
285         \fi
286         \hfil\thenote}%
287     \def\@oddhead{}%
288     \def\@evenfoot{%
289         \@mainsize
290         \if@clock
291             \fbox{\large \@arabic\c@minutes\space min}%
292         \else
293             \null
294         \fi
295         \hfil\thenote}%
296     \def\@evenhead{}%
297 \fi %% if@compatibility

\ps@plain
298 \def\ps@plain{\def\ps@slide{%
299     \def\@oddfoot{\@mainsize \mbox{}\hfil\hb@xt@3em{\theslide\hss}}%
300     \def\@oddhead{}%
301     \def\@evenfoot{\@mainsize \mbox{}\hfil\hb@xt@3em{\theslide\hss}}%
302     \def\@evenhead{}%
303     \def\ps@overlay{\def\@oddfoot{\@mainsize
304         \mbox{}\hfil\hb@xt@3em{\theoverlay\hss}}%
305     \def\@oddhead{}%
306     \def\@evenfoot{\@mainsize \mbox{}\hfil\hb@xt@3em{\theoverlay\hss}}%
307     \def\@evenhead{}%
308     \def\ps@note{\def\@oddfoot{\@mainsize \hbox{}\hfil\thenote}%
309     \def\@oddhead{}%
310     \def\@evenfoot{\@mainsize \hbox{}\hfil\thenote}%
311     \def\@evenhead{}%}

\ps@empty
312 \def\ps@empty{%
313     \def\ps@slide{\def\@oddhead{}\def\@oddfoot{}%
314     \def\@evenhead{}\def\@evenfoot{}%
315     \def\ps@overlay{\def\@oddhead{}\def\@oddfoot{}%
316     \def\@evenhead{}\def\@evenfoot{}%
317     \def\ps@note{\def\@oddhead{}\def\@oddfoot{}%

```

```

318 \def\@evenhead{}\def\@evenfoot{}}

Default definition the 'slide', 'overlay', and 'note' page styles.

319 \ps@headings
Set ordinary page style to 'empty'

320 \let\@oddhead\@empty\let\@oddfoot\@empty
321 \let\@evenhead\@empty\let\@evenfoot\@empty

```

## 9.5 Providing math *versions*

L<sup>A</sup>T<sub>E</sub>X provides two *versions*. We call them **normal** and **bold**, respectively. SL<sup>I</sup>T<sub>E</sub>X does not have a **bold** version. But we treat the invisible characters as a version. The only thing we have to take care of is to ensure that we have exactly the same fonts in both versions available.

```
322 \DeclareMathVersion{invisible}
```

Now we define the basic *math groups* used by L<sup>A</sup>T<sub>E</sub>X. Later on, in packages some other *math groups*, e.g., the AMS symbol fonts, will be defined.

As a default I used serif fonts for mathgroup 0 to get things like `\log` look right.

```

323 \SetSymbolFont{operators}{normal}
324             {OT1}{lcmss}{m}{n}
325
326 \SetSymbolFont{letters}{normal}
327             {OML}{lcmm}{m}{it}
328 \SetSymbolFont{symbols}{normal}
329             {OMS}{lcmsy}{m}{n}
330 \SetSymbolFont{largesymbols}{normal}
331             {OMX}{lcmex}{m}{n}
332
333 \SetSymbolFont{operators}{invisible}
334             {OT1}{lcmss}{m}{In}
335 \SetSymbolFont{letters}{invisible}
336             {OML}{lcmm}{m}{Iit}
337 \SetSymbolFont{symbols}{invisible}
338             {OMS}{lcmsy}{m}{In}
339 \SetSymbolFont{largesymbols}{invisible}
340             {OMX}{lcmex}{m}{In}
341
342
343 \def\@mainsize{\visible\tiny}

```

## 9.6 Environments

`titlepage` This environment starts a new page, with pagestyle *empty* and sets the page counter to 0.

```

344 \newenvironment{titlepage}
345     {\newpage
346      \thispagestyle{empty}%
347      \setcounter{page}{\z@}%
348      {\newpage}

```

### 9.6.1 General List Parameters

The following commands are used to set the default values for the list environment's parameters. See the L<sup>A</sup>T<sub>E</sub>X manual for an explanation of the meaning of the parameters.

```

\leftmargini
\leftmarginii 349 \setlength{\leftmargini} {38\p@}
\leftmarginiii 350 \setlength{\leftmarginii} {30\p@}
\leftmarginiv 351 \setlength{\leftmarginiii} {20\p@}
\leftmarginv 352 \setlength{\leftmarginiv} {15\p@}
\leftmarginvi 353 \setlength{\leftmarginv} {15\p@}
354 \setlength{\leftmarginvi} {10\p@}

@listi These commands set the values of \leftmargin, \parsep, \topsep, and \itemsep
@listii for the various levels of lists. It is even necessary to initialize \leftmargin in
@listiii \@listi, i.e. for a level one list, as a list environment may appear inside a
@listiv trivlist, for example inside a theorem environment.
@listv 355 \def@\listif{\leftmargin\leftmargini
@listvi 356           \parsep .5\parskip
357           \topsep \parsep
358           \itemsep\parskip
359           \partopsep \z@}
360
361 \def@\listii{\leftmargin\leftmarginii
362           \labelwidth\leftmarginii
363           \advance\labelwidth-\labelsep
364           \parsep .5\parskip
365           \topsep \parsep
366           \itemsep\parskip}
367 \def@\listiii{\leftmargin\leftmarginiii
368           \labelwidth\leftmarginiii
369           \advance\labelwidth-\labelsep}
370 \def@\listiv{\leftmargin\leftmarginiv
371           \labelwidth\leftmarginiv
372           \advance\labelwidth-\labelsep}
373 \def@\listv{\leftmargin\leftmarginv
374           \labelwidth\leftmarginv
375           \advance\labelwidth-\labelsep}
376 \def@\listvi{\leftmargin\leftmarginvi
377           \labelwidth\leftmarginvi
378           \advance\labelwidth-\labelsep}

```

Here we initialize \leftmargin and \labelwidth.

```

379 \leftmargin\leftmargini
380 \labelwidth\leftmargini\advance\labelwidth-\labelsep

```

### 9.6.2 Paragraph-formatting environments

**verse** Inside a `verse` environment, `\\"` ends a line, and line continuations are indented further. A blank line makes new paragraph with `\parskip` space.

```

381 \newenvironment{verse}{\let\\\=\@centercr
382           \list{}{\itemsep \z@}

```

```

383           \itemindent -15\p@  

384           \listparindent \itemindent  

385           \rightmargin \leftmargin  

386           \advance\leftmargin 15\p@)%  

387           \item[]}  

388       {\endlist}

quotation The quotation environment fills lines, indents paragraphs.  

389 \newenvironment{quotation}{\list{}{\listparindent 20\p@  

390                         \itemindent\listparindent  

391                         \rightmargin\leftmargin} %  

392                         \item[]}  

393       {\endlist}

quote The quote environment is the same as the quotation environment, except that  

there is no paragraph indentation.  

394 \newenvironment{quote}{\list{}{\rightmargin\leftmargin\item[]}  

395             {\endlist}}

```

### 9.6.3 List-making environments

**description** The **description** environment is defined here – while the **itemize** and **enumerate** environments are defined in **latex.dtx**.

```

396 \newenvironment{description}{\list{}{\labelwidth\z@  

397                         \itemindent-\leftmargin  

398                         \let\makelabel\descriptionlabel}  

399       {\endlist}

```

**\descriptionlabel** To change the formatting of the label, you must redefine **\descriptionlabel**.  
400 \newcommand\*{\descriptionlabel}[1]{\hspace\labelsep  
401 \normalfont\bfseries #1}  
402

### 9.6.4 Enumerate

The **enumerate** environment uses four counters: *enumi*, *enumii*, *enumiii* and *enumiv*, where *enumN* controls the numbering of the Nth level enumeration.

```

\theenumi The counters are already defined in latex.dtx, but their representation is changed  

\theenumii here.  

\theenumiii 403 \renewcommand{\theenumi}{\arabic{enumi}}  

\theenumiv 404 \renewcommand{\theenumii}{\alph{enumii}}  

405 \renewcommand{\theenumiii}{\roman{enumiii}}  

406 \renewcommand{\theenumiv}{\Alph{enumiv}}  

  

\labelenumi The label for each item is generated by the four commands \labelenumi ...  

\labelenumii  

\labelenumiii  

\labelenumiv 407 \newcommand{\labelenumi}{\theenumi.}  

408 \newcommand{\labelenumii}{(\theenumii)}  

409 \newcommand{\labelenumiii}{\theenumiii.}  

410 \newcommand{\labelenumiv}{\theenumiv.}

```

```

\p@enumii  The expansion of \p@enumN\theenumN defines the output of a \ref command
\p@enumiii when referencing an item of the Nth level of an enumerated list.
\p@enumiv  411 \renewcommand\p@enumii{\theenumi}
           412 \renewcommand\p@enumiii{\theenumi(\theenumii)}
           413 \renewcommand\p@enumiv{\p@enumiii\theenumiii}

```

### 9.6.5 Itemize

```

\labelitemi   Itemization is controlled by four commands: \labelitemi, \labelitemii,
\labelitemii  \labelitemiii, and \labelitemiv, which define the labels of the various item-
\labelitemiii ization levels.
\labelitemiv  414 \newcommand\labelitemi{$\cdot$}
           415 \newcommand\labelitemii{\normalfont\bfseries \textendash}
           416 \newcommand\labelitemiii{$\cdot$}
           417 \newcommand\labelitemiv{$\cdot$}

```

## 9.7 Setting parameters for existing environments

### 9.7.1 Array and tabular

```

\arraycolsep  The columns in an array environment are separated by 2\arraycolsep. Array
               and tabular environment parameters
               418 \setlength\arraycolsep{8\p@}

\tabcolsep    The columns in an tabular environment are separated by 2\tabcolsep.
               419 \setlength\tabcolsep{10\p@}

\arrayrulewidth The width of rules in the array and tabular environments is given by the length
                parameter\arrayrulewidth.
               420 \setlength\arrayrulewidth{.6\p@}

\doublerulesep The space between adjacent rules in the array and tabular environments is given
                 by \doublerulesep.
               421 \setlength\doublerulesep{3\p@}

```

### 9.7.2 Tabbing

```

\tabbingsep   This controls the space that the \' command puts in. (See LATEX manual for an
               explanation.)
               422 \labelsep 10pt
               423 \setlength\tabbingsep{\labelsep}

```

### 9.7.3 Minipage

```

\@minipagerestore The macro \@minipagerestore is called upon entry to a minipage environment
                   to set up things that are to be handled differently inside a minipage environment.
                   In the current styles, it does nothing.

\@mpfootins   Minipages have their own footnotes; \skip\@mpfootins plays same rôle for foot-
               notes in a minipage as \skip\footins does for ordinary footnotes.
               424 \skip\@mpfootins = \skip\footins

```

#### 9.7.4 Framed boxes

- \fboxsep The space left by \fbox and \framebox between the box and the text in it.
- \fboxrule The width of the rules in the box made by \fbox and \framebox.
 

```
425 \setlength\fboxsep{5\p@}
426 \setlength\fboxrule{.6\p@}
```
- \theequation The equation number will be typeset as arabic numerals.
 

```
427 \def\theequation{\@arabic\c@equation}
```
- \jot \jot is the extra space added between lines of an eqnarray environment. The default value is used.
 

```
428 % \setlength\jot{3pt}
```
- \eqnnum The macro \eqnnum defines how equation numbers are to appear in equations. Again the default is used.
 

```
429 % \def\eqnnum{(\theequation)}
```

## 9.8 Font changing

Here we supply the declarative font changing commands that were common in L<sup>A</sup>T<sub>E</sub>X version 2.09 and earlier. These commands work in text mode *and* in math mode. They are provided for compatibility, but one should start using the \text... and \math... commands instead. These commands are redefined using \DeclareOldFontCommand, a command with three arguments: the user command to be defined, L<sup>A</sup>T<sub>E</sub>X commands to execute in text mode and L<sup>A</sup>T<sub>E</sub>X commands to execute in math mode.

- \rm The commands to change the family. When in compatibility mode we select the ‘default’ font first, to get L<sup>A</sup>T<sub>E</sub>X2.09 behaviour.
- \sf
 

```
430 \DeclareOldFontCommand{\rm}{\normalfont\rmfamily}{\mathrm}
431 \DeclareOldFontCommand{\sf}{\normalfont\sffamily}{\mathsf}
432 \DeclareOldFontCommand{\tt}{\normalfont\ttfamily}{\mathtt}
```
- \bf The command to change to the bold series. One should use \mdseries to explicitly switch back to medium series.
 

```
433 \DeclareOldFontCommand{\bf}{\normalfont\bfseries}{\mathbf}
```
- \sl And the commands to change the shape of the font. The slanted and small caps \it shapes are not available by default as math alphabets, so those changes do nothing \sc in math mode. One should use \upshape to explicitly change back to the upright shape.
 

```
434 \DeclareOldFontCommand{\it}{\normalfont\itshape}{\mathit}
435 \DeclareOldFontCommand{\sl}{\normalfont\slshape}{\relax}
436 \DeclareOldFontCommand{\sc}{\normalfont\scshape}{\relax}
```
- \cal The commands \cal and \mit should only be used in math mode, outside math mode they have no effect. Currently the New Font Selection Scheme defines these commands to generate warning messages. Therefore we have to define them ‘by hand’.
 

```
437 \DeclareRobustCommand*\{\cal\}{\@fontswitch{\relax}{\mathcal}}
438 \DeclareRobustCommand*\{\mit\}{\@fontswitch{\relax}{\mathnormal}}
```

## 9.9 Footnotes

`\footnoterule` Usually, footnotes are separated from the main body of the text by a small rule. This rule is drawn by the macro `\footnoterule`. We have to make sure that the rule takes no vertical space (see `plain.tex`). The resulting rule will appear on all color layers, so it's best not to draw a rule.

```
439 \renewcommand\footnoterule{}  
440 % \let \footnoterule = \relax
```

`\c@footnote` Footnotes are numbered within slides, overlays, and notes and numbered with \*, †, etc.

```
441 % \newcounter{footnote}  
442 \def\thefootnote{\fnsymbol{footnote}}  
443 \Qaddtoreset{footnote}{slide}  
444 \Qaddtoreset{footnote}{overlay}  
445 \Qaddtoreset{footnote}{note}
```

`\@makefntext` The footnote mechanism of L<sup>A</sup>T<sub>E</sub>X calls the macro `\@makefntext` to produce the actual footnote. The macro gets the text of the footnote as its argument and should use `\@makefnmark` to produce the mark of the footnote. The macro `\@makefntext` is called when effectively inside a `\parbox` of width `\columnwidth` (i.e., with `\hsize = \columnwidth`).

An example of what can be achieved is given by the following piece of T<sub>E</sub>X code.

```
\long\def\@makefntext#1{  
    \setpar{\@par  
        \tempdima = \hsize  
        \advance\tempdima-10pt  
        \parshape \one 10pt \tempdima}%  
    \par  
    \parindent 1em\noindent  
    \hbox to \z@\{\hss\@makefnmark\#1}
```

The effect of this definition is that all lines of the footnote are indented by 10pt, while the first line of a new paragraph is indented by 1em. To change these dimensions, just substitute the desired value for '10pt' (in both places) or '1em'. The mark is flushright against the footnote.

In these document classes we use a simpler macro, in which the footnote text is set like an ordinary text paragraph, with no indentation except on the first line of a paragraph, and the first line of the footnote. Thus, all the macro must do is set `\parindent` to the appropriate value for succeeding paragraphs and put the proper indentation before the mark.

```
446 \long\def\@makefntext#1{  
447     \noindent  
448     \hangindent 10\p@  
449     \hb@xt@10\p@{\hss\@makefnmark\#1}}
```

`\@makefnmark` The footnote markers that are printed in the text to point to the footnotes should be produced by the macro `\@makefnmark`. We use the default definition for it.

```
450 %\def\@makefnmark{\hbox{$^{\{\@thefnmark\}\m@th}$}}
```

## 9.10 The title

The commands `\title`, `\author`, and `\date` are already defined, so here we just define `\maketitle`.

```
451 \newcommand{\maketitle}{\centering {\Large \@title \par}%
452     \author \par \@date\par}%
453     \if@titlepage \break \fi}
```

# 10 Initialisation

## 10.1 Date

`\today` This macro uses the TeX primitives `\month`, `\day` and `\year` to provide the date of the L<sup>A</sup>T<sub>E</sub>X-run.

```
454 \newcommand{\today}{\ifcase\month\or
455     January\or February\or March\or April\or May\or June\or
456     July\or August\or September\or October\or November\or December\fi
457     \space\number\day, \number\year}
```

Default initializations

```
458 \pagenumbering{arabic}
459 \onecolumn
460 </class>
```

## 10.2 Basic code

The code below is basically a copy of `slitex.tex` with some changes.

Global changes so far:

### 10.2.1 Hacks for slide macros

```
461 (*cmd)
462 \message{hacks,}
463
464 \outer\def\newifG#1{\count@`\\escapechar `\\m@ne
465     \expandafter\expandafter\expandafter
466     \edef\@ifG#1{true}{\global\let\noexpand#1\noexpand\iftrue}%
467     \expandafter\expandafter\expandafter
468     \edef\@ifG#1{false}{\global\let\noexpand#1\noexpand\iffalse}%
469     \@ifG#1{false}`\\escapechar`\count@} % the condition starts out false
470 \def\@ifG#1#2{\csname\expandafter\ifG@\string#1#2\endcsname}
471 {\uccode`1='i \uccode`2='f \uccode`3='G \uppercase{\gdef\ifG@123{G}}}
472 % 'ifG' is required
473
474 \def\@gobbletoend#1{\def\@argend{#1}@ggobtoend}
475
476 \long\def\@ggobtoend#1\end#2{\fi\def\reserved@a{#2}%
477 \ifx\reserved@a\@argend\else\@ggobtoend\fi}
```

FMi: I don't see any reason for this command since `\fi` is hidden anyway in the replacement text `\def\@xfi{\fi}`

```
478 \message{slides,}
```

### 10.2.2 Slide macros

Switches:

|                            |                                        |
|----------------------------|----------------------------------------|
| <code>@bw</code>           | true if making black and white slides  |
| <code>@visible</code>      | true if visible output to be produced. |
| <code>@makingslides</code> | true if making a slide/overlay/note    |

```
479 \newif\if@bw
480 \newif\if@visible
481 \newif\if@onlyslidesw \c@onlyslideswfalse
482 \newif\if@onlynotesw \c@onlynoteswfalse
483 \newif\if@makingslides
```

FMi: `\newifG` replaces `\gdef\@slidesw{T}` stuff

```
484 \newifG\ifG@slidesw
```

Counters

|                      |                            |
|----------------------|----------------------------|
| <code>slide</code>   | slide number               |
| <code>overlay</code> | overlay number for a slide |
| <code>note</code>    | note number for a slide    |

```
485 \countdef\c@slide=0 \c@slide=0
486 \def\cl@slide{}
487 \countdef\c@overlay=1 \c@overlay=0
488 \def\cl@overlay{}
489 \countdef\c@note=2 \c@note=0
490 \def\cl@note{}
```

Add these counters explicitly to the ‘ckpt list’ so that the `\include` mechanism works.

```
491 \g@addto@macro\cl@@ckpt{\@elt{slide}\@elt{overlay}\@elt{note}}
492 \c@addtoreset{overlay}{slide}
493 \c@addtoreset{note}{slide}
```

Redefine page counter to some other number. The page counter will always be zero except when putting out an extra page for a slide, note or overlay.

```
494 \c@definecounter{page}
495 \c@addtoreset{page}{slide}
496 \c@addtoreset{page}{note}
497 \c@addtoreset{page}{overlay}
498
499 \def\theslide{\c@arabic\c@slide}
500 \def\theoverlay{\theslide-\c@alph\c@overlay}
501 \def\thenote{\theslide-\c@arabic\c@note}
```

```
\c@setlimits \LIST \LOW \HIGH
```

Assumes that `\LIST = RANGE1, RANGE2, ..., Rangen` ( $n > 0$ )  
Where `RANGEi = j` or  $j-k$ .

Then `\c@setlimits` globally sets  
 (i) `\LIST := RANGE2, ..., Rangen`  
 (ii) `\LOW := p`  
 (iii) `\HIGH := q`  
 where either `RANGE1 = p-q` or `RANGE1 = p and q=p`.

```

502 \def\@sl@getargs#1-#2-#3\relax#4#5{\xdef#4{#1}\xdef#5{#2}}
503 \def\@sl@ccdr#1,#2\relax#3#4{\xdef#3{#1-#1-}\xdef#4{#2}}
504
505 \def\@setlimits #1#2#3{\expandafter\@sl@ccdr#1\relax\@sl@gtmp #1%
506 \expandafter\@sl@getargs\@sl@gtmp\relax#2#3}

\onlyslides{LIST} ::=
BEGIN
  @onlyslidesw := true
  \doglslidelist :=G LIST,999999,999999
  if @onlynotesw = true
    else @onlynotesw := true
      \doglnotelist :=G LIST,999999,999999
  fi
  message: Only Slides LIST
END

507 \def\onlyslides#1{\@onlyslideswtrue
508   \gdef\@doglslidelist{#1,999999,999999}%
509   \if@onlynotesw \else
510     \@onlynoteswtrue\gdef\@doglnotelist{999999,999999}\fi
511   \typeout{Only Slides #1}

\onlynotes{LIST} ::=
BEGIN
  @onlynotesw := true
  \doglnotelist :=G LIST,999999,999999
  if @onlyslidesw = true
    else \@onlyslidesw := true
      \doglslidelist{999999,999999}
  fi
  message: Only Notes LIST
END

512 \def\onlynotes#1{\@onlynoteswtrue
513   \gdef\@doglnotelist{#1,999999,999999}%
514   \if@onlyslidesw \else
515     \@onlyslideswtrue\gdef\@doglslidelist{999999,999999}\fi
516   \typeout{Only Notes #1}

\setupcounters ::= (similar to old \blackandwhite #1 ::=
\newpage
page counter := 0
@bw := T
@visible := T
if @onlyslidesw = true
  then \doslidelist := \doglslidelist
    \setlimits\doslidelist\doslidehigh\doslidehigh
  fi
if @onlynotesw = true
  then \donotelist := \doglnotelist
    \setlimits\donotelist\donotehigh\donotehigh
  fi
\normalsize % Note, this sets font to \rmfamily , which sets
            % \@currfont to \rmfamily

```

```

        counter slidenumber := 0
        counter note      := 0
        counter overlay   := 0
        @makingslides     := F %% \blackandwhite: @makingslides := T
                                %%           input #1
                                %%           @makingslides := F

517 \if@compatibility
518 % In compatibility mode, need to define \verb+\blackandwhite+, 
519 % \verb+\colors+, \verb+\colorslides+, etc.
520 \def\blackandwhite#1{\newpage\setcounter{page}{0}\@bwtrue\@visibletrue
521 \if@onlyslidesw \xdef\@doslidelist{\@doglslidelist}%
522 \@setlimits\@doslidelist\@doslidebelow\@doslidehigh\fi
523 \if@onlynotesw \xdef\@donotelist{\@doglnotelist}%
524 \@setlimits\@donotelist\@donotelow\@donotehigh\fi
525 \normalsize\setcounter{slide}{0}\setcounter{overlay}{0}%
526 \setcounter{note}{0}\@makingslidestrue\input #1\@makingslidesfalse}

\colors{COLORS} ::=
for \@colortemp := COLORS
  do \csname \@colortemp \endcsname == \color{\@colortemp} od
if \@colorlist = empty
  then \@colorlist := COLORS
  else \@colorlist := \@colorlist , COLORS
fi

527 \def\colors#1{\@for\@colortemp:=#1\do{\expandafter
528   \xdef\csname\@colortemp\endcsname{\noexpand\color{\@colortemp}}}\ifx
529   \@colorlist\empty \gdef\@colorlist{\#1}%
530   \else \xdef\@colorlist{\@colorlist,\#1}\fi}
531
532 \def\@colorlist{}

\colorslides{FILE} ::=
\newpage
page counter := 0
@bw := F
for \@currcolor := \@colorlist
  do @visible := T
    if @onlyslidesw = true
      then \@doslidelist := \@doglslidelist
            \@setlimits\@doslidelist\@doslidebelow\@doslidehigh
    fi
    if @onlynotesw = true
      then \@donotelist := \@doglnotelist
            \@setlimits\@donotelist\@donotelow\@donotehigh
    fi
  \normalsize
  counter slide := 0
  counter overlay := 0
  counter note   := 0
  type message
  generate color layer output page
  @makingslides := T
  input #1

```

```

@makingslides := F
od

533 \def\colorslides#1{\newpage\setcounter{page}{0}\@bwfalse
534 \@for\@currcolor:=\@colorlist\do
535 {\@visibletrue
536 \if@onlyslidesw \xdef\@doslidelist{\@doglslidelist}%
537 \@setlimits\@doslidelist\@doslidebelow\@doslidehigh\fi
538 \if@onlynotesw \xdef\@donotelist{\@doglnotelist}%
539 \@setlimits\@donotelist\@donotelow\@donotehigh\fi
540 \normalsize\setcounter{slide}{0}\setcounter{overlay}{0}%
541 \setcounter{note}{0}\typeout{color \@currcolor}%
542 \newpage
543 \begin{huge}%
544 \begin{center}%
545 COLOR LAYER\ [.75in]%
546 \@currcolor
547 \end{center}%
548 \end{huge}%
549 \newpage
550 \@makingslidestrue
551 \input #1
552 \@makingslidesfalse}
553 %
554 \else %% if@compatibility
555 %
556 \def\setupcounters{\newpage\setcounter{page}{0}\@bwtrue\@visibletrue
557 \if@onlyslidesw \xdef\@doslidelist{\@doglslidelist}%
558 \@setlimits\@doslidelist\@doslidebelow\@doslidehigh\fi
559 \if@onlynotesw \xdef\@donotelist{\@doglnotelist}%
560 \@setlimits\@donotelist\@donotelow\@donotehigh\fi
561 \normalsize\setcounter{slide}{0}\setcounter{overlay}{0}%
562 \setcounter{note}{0}\@makingslidesfalse}
563
564 \AtBeginDocument{\setupcounters}
565 \fi %% if@compatibility

\slide COLORS ::=
BEGIN
\changes{v2.3}{1994/03/16}{Moved \cs{newpage} up front, here and in
    \cs{note} and \cs{overlay}}
\par\break
\stepcounter{slide}
\setcounter{page}{0} % in case of non-slide pages
\@slidesw :=G T
if @onlyslidesw = true % set \@slidesw = T iff
    then % page to be output
        while \c@slide > \@doslidehigh
            do \@setlimits\@doslidelist\@doslidebelow\@doslidehigh od
        if \c@slide < \@doslidebelow
            then \@slidesw := F
        fi
    fi
if \@slidesw = T
then \@slidesw :=G F

```

```

\begingroup
  if @bw = true
    then \@slidesw := G T
    else \color{COLORS}
      \if@visible then \@slidesw := G T \fi
  fi
\endgroup
fi
if \@slidesw = T
  then @makingslides := T
    \thispagestyle{slide}
  else \end{slide}
    \gobbletoend{slide}
fi
END

\endslide ::=
BEGIN
  \par\break
END

566 \if@compatibility
567 \def\slide#1{\stepcounter{slide}\G@slideswtrue\if@onlyslidesw
568 \@whilenum \c@slide >\@doslidehigh\relax
569 \do{\@setlimits\@doslidelist\@doslidebelow\@doslidehigh}\ifnum
570 \c@slide <\@doslidebelow\relax\G@slideswfase\fi\fi
571 \ifG@slidesw
572   \G@slideswfase
573 % FMI this is only a hack at the moment to get things running.
574 % \begingroup
575   \if@bw\G@slideswtrue\else
576     \color{#1}\if@visible \G@slideswtrue \fi
577   \fi
578 % \endgroup
579 \fi
580 \ifG@slidesw \newpage\thispagestyle{slide}%

```

This will set up the last color specified in the argument to `\slide` as the current color. If only back and white slides are prepared `\last@color` will be empty and effectively `\relax` will be generated (hopefully).

We need to reset to a default font at the beginning of a slide. (not done yet).

```

581 \csname \last@color \endcsname
582 \else\end{slide}\gobbletoend{slide}\fi}
583 %
584 \else %% if@compatibility
585 %
586 \def\slide{\par\break
587 \stepcounter{slide}\setcounter{page}{0}\G@slideswtrue\if@onlyslidesw
588 \@whilenum \c@slide >\@doslidehigh\relax
589 \do{\@setlimits\@doslidelist\@doslidebelow\@doslidehigh}\ifnum
590 \c@slide <\@doslidebelow\relax\G@slideswfase\fi\fi
591 \ifG@slidesw
592   \G@slideswfase
593 % FMI this is only a hack at the moment to get things running.

```

```

594 % \begingroup
595   \if@bw\G@slideswtrue\else
596     \if@visible \G@slideswtrue \fi
597   \fi
598 % \endgroup
599 \fi
600 \ifG@slidesw \@makingslidestrue\thispagestyle{slide}%

```

This will set up the last color specified in the argument to `\slide` as the current color. If only back and white slides are prepared `\last@color` will be empty and effectively `\relax` will be generated (hopefully).

We need to reset to a default font at the beginning of a slide. (not done yet).

```

601 \csname \last@color \endcsname
602 \else\end{slide}\@gobbletoend{slide}\fi}
603 \fi %% if@compatibility
604
605 \let\last@color\empty
606
607 \def\endslide{\par\break}

\overlay COLORSS ::=
BEGIN
  \par\break
  \stepcounter{overlay}
  \setcounter{page}{0}                                % in case of non-slide pages
  \G@slidesw :=G T
  \if @onlyslidesw = T                               % set \G@slidesw = T iff
  then                                                 % page to be output
    \if \c@slide < \G@doslidelow
      \then \G@slidesw :=G F
    \fi
  \fi
  \if \G@slidesw = T
    \G@slidesw :=G F
    \begingroup
      \if @bw = true
        \then \G@slidesw :=G T
      \else \color{COLORS}
        \if@visible \then \G@slidesw :=G T \fi
      \fi
    \endgroup
  \fi
  \if \G@slidesw = T
    \then @makingslides := T
      \thispagestyle{overlay}
    \else \end{overlay}
      \@gobbletoend{overlay}
  \fi
END

\endoverlay ::=
BEGIN
  \par\break
END

```

```

608 \if@compatibility
609 \def\overlay{\stepcounter{overlay}\G@slideswtrue%
610 \if@onlyslidesw\ifnum \c@slide <\@doslidelow\relax
611 \G@slideswfalset\fi\fi
612 \ifG@slidesw \G@slideswfalset\begingroup\if@bw\G@slideswtrue%
613 \else\@color{#1}\if@visible \G@slideswtrue\fi\fi\endgroup\fi
614 \ifG@slidesw \newpage\thispagestyle{overlay}%
615 \else\end{overlay}\@gobbletoend{overlay}\fi}
616 %
617 \else %%if@compatibility
618 %
619 \def\overlay{\par\break
620   \stepcounter{overlay}%
621   \setcounter{page}{0}%
622   \G@slideswtrue%
623   \if@onlyslidesw\ifnum \c@slide <\@doslidelow\relax
624     \G@slideswfalset\fi\fi
625   \ifG@slidesw \G@slideswfalset
626     \begingroup\if@bw\G@slideswtrue%
627       \else\if@visible \G@slideswtrue\fi\fi
628     \endgroup\fi
629   \ifG@slidesw \@makingslidestrue\thispagestyle{overlay}%
630   \else\end{overlay}\@gobbletoend{overlay}\fi}
631 \fi %%if@compatibility
632
633 \def\endoverlay{\par\break}

\note ::=
BEGIN
  \par\break
  \stepcounter{note}
  \setcounter{page}{0} % in case of non-slide pages
  if @bw = T
  then
    \@slidesw :=G T
    if @onlynotesw = true % set \@notesw = T iff
    then % page to be output
      while \c@slide > \@donotehigh
        do \@setlimits\@donotelist\@donotelow\@donotehigh od
      if \c@slide < \@donotelow
        then \@slidesw :=G F
      fi
    fi
  else \@slidesw :=G F
  fi
  if \@slidesw = T
  then @makingslides := T
    \thispagestyle{note}
  else \end{note}
    \@gobbletoend{note}
  fi
END

\endnote ::=
BEGIN

```

```

    \par\break
END

634 \if@compatibility
635 \def\note{\stepcounter{note}%
636   \if@bw
637     \G@slideswtrue
638     \if@onlynotesw\whilenum \c@slide >\donotehigh\relax
639     \do{\@setlimits\donotelist\donotelow\donotehigh}\ifnum
640       \c@slide <\donotelow\relax \G@slideswfals\fi\fi
641     \else\G@slideswfals\fi
642     \ifG@slidesw \newpage\thispagestyle{note}\else
643     \end{note}\gobbletoend{note}\fi}
644 %
645 \else %%if@compatibility
646 %
647 \def\note{\par\break\stepcounter{note}\setcounter{page}{0}%
648   \if@bw
649     \G@slideswtrue
650     \if@onlynotesw\whilenum \c@slide >\donotehigh\relax
651     \do{\@setlimits\donotelist\donotelow\donotehigh}\ifnum
652       \c@slide <\donotelow\relax \G@slideswfals\fi\fi
653     \else\G@slideswfals\fi
654     \ifG@slidesw \@makingslidestrue\thispagestyle{note}\else
655     \end{note}\gobbletoend{note}\fi}
656 \fi %%if@compatibility
657
658 \def\endnote{\par\break}

\@color{COLORS} ::=
BEGIN
  if math mode
    then type warning
  fi
  if @bw
    then \visible
    else \invisible
    for \last@color := COLORS
      do if \last@color = \@currcolor
        then \visible
      fi
    od
  fi
  \ignorespaces
END

```

FMi: `\last@color` will be used in `\slide` to set up first color if no color is given. I suppose that this is much too complicated. `\else\@tempswafals` would produce the same effect I imagine.

```

659 \def\@color#1{\@mmode{test}
660 {\if@bw \@tempswatrue \else \@tempswafals
661   \@for \reserved@a :=#1\do{\ifx\reserved@a\@currcolor\@tempswatrue\fi
662     \let\last@color\reserved@a\fi
663   \if@tempswa \visible \else \invisible \fi

```

```

664   \ignorespaces}}
665
666 \def\@mmodetest#1{\ifmmode\ClassWarning{slides}{Color-changing command
667     in math mode has been ignored}\else #1\fi}
668
669 \def\invisible{\@mmodetest
670   {\if@visible
671     \@visiblefalse
672     \fontshape{f@shape}\selectfont
673     \mathversion{invisible}%
674   \fi
675   \ignorespaces}}
676
677 \def\visible{\@mmodetest
678   {\if@visible
679   \else
680     \@visibletrue
681     \fontshape{\expandafter\@gobble\f@shape}\selectfont
682     \mathversion{normal}%
683   \fi
684   \ignorespaces}}
685
686 \def\fontshape#1{\edef\f@shape{\if@visible \else I\fi #1}}

```

### 10.3 Macros for font handling

We let `\familydefault` point at `\sfdefault`, to make it easier to use the document class `slides` with packages that set up other fonts.

```
687 \renewcommand{\familydefault}{\sfdefault}
```

The `latsym` package, which is needed to be able to access the L<sup>A</sup>T<sub>E</sub>X symbol fonts (`lasy`), sets things up so that for sizes larger than 10 point magnifications of `lasy10` are used. For `slides` we want to use magnifications of `lasy8`, so we set up the `lasy` family here to prevent L<sup>A</sup>T<sub>E</sub>X from loading `Ulasy.fd`.

```

688 \DeclareFontFamily{U}{lasy}{}{}
689 \DeclareFontShape{U}{lasy}{m}{n}{%
690   <12><13.82><16.59><19.907><23.89><28.66><34.4><41.28>lasy8
691 }{}
692 \DeclareFontShape{U}{lasy}{m}{In}{%
693   <13.82><16.59><19.907><23.89><28.66><34.4><41.28>ilasy8
694 }{}
695 \message{picture,}

```

#### 10.3.1 Modifications to the picture environment

Below are the new definitions of the picture-drawing macros required for SLiTeX. Only those commands that actually draw something must be changed so that they do not produce any output when the `@visible` switch is false.

```

696 \def\line(#1,#2){\if@visible\@xarg #1\relax \@yarg #2\relax
697 \@linelen #3\unitlength
698 \ifnum\@xarg =\z@ \@vline
699   \else \ifnum\@yarg =\z@ \@hline \else \@sline\fi
700 \fi\fi}
701
702 \def\vector(#1,#2){\if@visible\@xarg #1\relax \@yarg #2\relax
703 \@linelen #3\unitlength
704 \ifnum\@xarg =\z@ \@vvector
705   \else \ifnum\@yarg =\z@ \@hvector \else \@svector\fi
706 \fi\fi}
707
708 \def\dashbox#1(#2,#3){%
709 \leavevmode\if@visible\hb@xt@\z@{\baselineskip \z@
710 \lineskip \z@
711 \dashdim #2\unitlength
712 \dashcnt \dashdim \advance\@dashcnt 200
713 \dashdim #1\unitlength\divide\@dashcnt \dashdim
714 \ifodd\@dashcnt\@dashdim\z@
715 \advance\@dashcnt \one \divide\@dashcnt \tw@
716 \else \divide\@dashdim \tw@ \divide\@dashcnt \tw@
717 \advance\@dashcnt \m@ne
718 \setbox\@dashbox \hbox{\vrule \height \halfwidth \depth \halfwidth
719 \width \dashdim}\put(0,0){\copy\@dashbox}%
720 \put(0,#3){\copy\@dashbox}%
721 \put(#2,0){\hskip-\dashdim\copy\@dashbox}%
722 \put(#2,#3){\hskip-\dashdim\box\@dashbox}%
723 \multiply\@dashdim \thr@@
724 \fi
725 \setbox\@dashbox \hbox{\vrule \height \halfwidth \depth \halfwidth
726 \width \#1\unitlength\hskip \#1\unitlength}\@tempcnta\z@
727 \put(0,0){\hskip\dashdim \whilenum \@tempcnta <\@dashcnt
728 \do{\copy\@dashbox\advance\@tempcnta \one }{}\@tempcnta\z@
729 \put(0,#3){\hskip\dashdim \whilenum \@tempcnta <\@dashcnt
730 \do{\copy\@dashbox\advance\@tempcnta \one }%}
731 \dashdim #3\unitlength
732 \dashcnt=\dashdim \advance\@dashcnt 200
733 \dashdim #1\unitlength\divide\@dashcnt \dashdim
734 \ifodd\@dashcnt \dashdim=\z@
735 \advance\@dashcnt \one \divide\@dashcnt \tw@
736 \else
737 \divide\@dashdim \tw@ \divide\@dashcnt \tw@
738 \advance\@dashcnt \m@ne
739 \setbox\@dashbox\hbox{\hskip -\halfwidth
740 \vrule \width \wholewidth
741 \height \dashdim}\put(0,0){\copy\@dashbox}%
742 \put(#2,0){\copy\@dashbox}%
743 \put(0,#3){\lower\dashdim\copy\@dashbox}%
744 \put(#2,#3){\lower\dashdim\copy\@dashbox}%
745 \multiply\@dashdim \thr@@
746 \fi
747 \setbox\@dashbox\hbox{\vrule \width \wholewidth
748 \height \#1\unitlength}\@tempcnta\z@
749 \put(0,0){\hskip -\halfwidth \vbox{\whilenum \@tempcnta <\@dashcnt

```

```

750 \do{\vskip #1\unitlength\copy\@dashbox\advance\@tempcnta \@ne }%
751 \vskip\@dashdim}\@tempcnta\z@
752 \put(#2,0){\hspace{-\@halfwidth} \vbox{\@whilenum \@tempcnta <\@dashcnt
753 \relax\do{\vskip #1\unitlength\copy\@dashbox\advance\@tempcnta \@ne }%
754 \vskip\@dashdim}}\fi\@makepicbox(#2,#3)}

(re)declare these booleans as they not defined in old format (or with latexrelease
package)
755 \newif\if@ovvline \@ovvlinetrue
756 \newif\if@ovhline \@ovhlinetrue

757 \def\@oval(#1,#2)[#3]{\if@visible\begingroup \boxmaxdepth \maxdimen
758   \@ovttrue \@ovbtrue \@ovltrue \@ovrtrue
759   \@ovvlinefalse \@ovhlinefalse
760   \@tfor\reserved@a :=#3\do
761     {\csname @ov\reserved@a false\endcsname}%
762   \@ovxx#1\unitlength \@ovyy #2\unitlength
763   \@tempdimb \ifdim \@ovyy >\@ovxx \@ovxx \@ovvlinetrue
764   \else \@ovyy \ifdim \@ovyy =\@ovxx \else \@ovhlinetrue \fi\fi
765   \advance \@tempdimb -2\p@
766   \@getcirc \@tempdimb
767   \@ovro \ht\@tempboxa \@ovri \dp\@tempboxa
768   \@ovdx\@ovxx \advance\@ovdx -\@tempdima \divide\@ovdx \tw@
769   \@ovdy\@ovyy \advance\@ovdy -\@tempdima \divide\@ovdy \tw@

770   \ifdim \@ovdx >\z@ \@ovhlinetrue \fi
771   \ifdim \@ovdy >\z@ \@ovvlinetrue \fi
772   \@circlefnt \setbox\@tempboxa
773   \hbox{\if@ovr \@ovvert32\kern -\@tempdima \fi
774   \if@ovl \kern \@ovxx \@ovvert01\kern -\@tempdima \kern -\@ovxx \fi
775   \if@ovt \@ovhorz \kern -\@ovxx \fi
776   \if@ovb \raise \@ovyy \@ovhorz \fi}\advance\@ovdx\@ovro
777   \advance\@ovdy\@ovro \ht\@tempboxa\z@ \dp\@tempboxa\z@
778   \@put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}%
779   \endgroup\fi}
780

781 \def\@circle#1{\if@visible \begingroup \boxmaxdepth \maxdimen
782   \@tempdimb #1\unitlength
783   \ifdim \@tempdimb >15.5\p@\relax \@getcirc\@tempdimb
784     \@ovro\ht\@tempboxa
785     \setbox\@tempboxa\hbox{\@circlefnt
786       \advance\@tempcnta\tw@ \char \@tempcnta
787       \advance\@tempcnta\m@ne \char \@tempcnta \kern -2\@tempdima
788       \advance\@tempcnta\tw@
789       \raise \@tempdima \hbox{\char\@tempcnta}\raise \@tempdima
790         \box\@tempboxa}\ht\@tempboxa\z@ \dp\@tempboxa\z@
791         \@put{-\@ovro}{-\@ovro}{\box\@tempboxa}%
792   \else \@circ\@tempdimb{96}\fi\endgroup\fi}
793

794 \def\@dot#1{%
795   \if@visible\@tempdimb #1\unitlength \@circ\@tempdimb{112}\fi}
796 \def\@frameb@x#1{%

```

```

797  \tempdima\fboxrule
798  \advance\tempdima\fboxsep
799  \advance\tempdima\dp\tempboxa
800  \leavevmode
801  \hbox{%
802    \lower\tempdima\hbox{%
803      \vbox{%
804        \if@visible\hrule\height\else\vskip\fi\fboxrule
805        \hbox{%
806          \if@visible\vrule\width\else\hskip\fi\fboxrule
807          #1%
808          \vbox{%
809            \vskip\fboxsep
810            \box\tempboxa
811            \vskip\fboxsep}%
812          #1%
813          \if@visible\vrule\width\else\hskip\fi\fboxrule}%
814        \if@visible\hrule\height\else\vskip\fi\fboxrule}}}}
815
816 \long\def\frame#1{\if@visible\leavevmode
817 \vbox{\vskip-\halfwidth\hrule\height\halfwidth\depth\halfwidth
818   \vskip-\halfwidth\hbox{\hskip-\halfwidth\vrule\width\wholewidth
819   \hskip-\halfwidth#1\hskip-\halfwidth\vrule\width\wholewidth
820   \hskip-\halfwidth}\vskip-\halfwidth\hrule\height\halfwidth
821   \depth\halfwidth\vskip-\halfwidth}\else#1\fi}
822 \message{mods,}

```

### 10.3.2 Other modifications to **TEX** and **LATEX** commands

```

\rule
823 \def\@rule[#1]#2#3{\tempdima#3\advance\tempdima #1\leavevmode
824 \hbox{\if@visible\vrule
825   \width#2\height\tempdima\depth#1\else
826   \vrule\width\z@\height\tempdima\depth#1\vrule
827   \width#2\height\z@\fi}}
828
829 % \_ (Added 10 Nov 86)
830
831 \def\_{\leavevmode \kern.06em \if@visible\vbox{\hrule\width.3em}\else
832   \vbox{\hrule\height\z@\width.3em}\vbox{\hrule\width\z@\fi}}
833
\overline, \underline, \frac and \sqrt
\@mathbox{STYLE}{BOX}{MTEXT} : Called in math mode, typesets MTEXT and
  stores result in BOX, using style STYLE.

\@bphant{BOX}   : Creates a phantom with dimensions BOX.
\@vphantom{BOX} : Creates a phantom with ht of BOX and zero width.
\@hphantom{BOX} : Creates a phantom with width of BOX
  and zero ht & dp.
\@hvsmash{STYLE}{MTEXT} : Creates a copy of MTEXT with zero height and
  width in style STYLE.

```

```

833 \def\@mathbox#1#2#3{\setbox#2\hbox{$\m@th#1{#3}$}}
834
835 \def\@vphantom#1{\setbox\tw@{\null \ht\tw@\ht #1\dp\tw@\dp #1%
836   \box\tw@}}
837
838 \def\@bphantom#1{\setbox\tw@{\null
839   \wd\tw@\wd #1\ht\tw@\ht #1\dp\tw@\dp #1%
840   \box\tw@}}
841
842 \def\@hbphantom#1{\setbox\tw@{\null \wd\tw@\wd #1\ht\tw@\z@ \dp\tw@\z@
843   \box\tw@}}
844
845 \def\@hvsmash#1#2{\@mathbox#1{z@{#2}\ht{z@{z@ \dp{z@{z@ \wd{z@{z@
846   \box{z@}}
847
848 \def\@underline#1{\relax\ifmmode
849   \Cxunderline{#1}\else $ \m@th\@xunderline{\hbox{#1}}$\relax\fi}
850
851 \def\@xunderline#1{\mathchoice{\@xyunderline\displaystyle{#1}}%
852   {\@xyunderline
853     \textstyle{#1}}{\@xyunderline\scriptstyle{#1}}{\@xyunderline
854       \scriptscriptstyle{#1}}}
855
856 \def\@xyunderline#1#2{%
857   \@mathbox#1\@smashboxa{#2}\@hvsmash#1{\copy\@smashboxa}%
858   \if@visible \@hvsmash#1{\@overline{\@bphantom\@smashboxa}}\fi
859   \@mathbox#1\@smashboxb{\@overline{\box\@smashboxa}}%
860   \@bphantom\@smashboxb}
861
862 \let\@overline=\overline
863
864 \def\@overline#1{\mathchoice{\@xoverline\displaystyle{#1}}{\@xoverline
865   \textstyle{#1}}{\@xoverline\scriptstyle{#1}}{\@xoverline
866     \scriptscriptstyle{#1}}}
867
868 \def\@xoverline#1#2{%
869   \@mathbox#1\@smashboxa{#2}\@hvsmash#1{\copy\@smashboxa}%
870   \if@visible \@hvsmash#1{\@overline{\@bphantom\@smashboxa}}\fi
871   \@mathbox#1\@smashboxb{\@overline{\box\@smashboxa}}%
872   \@bphantom\@smashboxb}

\@frac {STYLE}{DENOMSTYLE}{NUM}{DEN}{FONTSIZE} :
Creates \frac{NUM}{DENOM}
in style STYLE with NUM and DENOM in style DENOMSTYLE
FONTSIZE should be \textfont \scriptfont or \scriptscriptfont

```

Added a group around the first argument of `\frac` to prevent changes (for example font changes) to modify the contents of the second argument.

```

873 \def\frac#1#2{\mathchoice
874   {\@frac\displaystyle\textstyle{#1}{#2}\textfont{\@frac
875     \textstyle\scriptstyle{#1}{#2}\textfont{\@frac
876       \scriptstyle\scriptstyle{#1}{#2}\scriptfont{\@frac
877         \scriptstyle\scriptstyle{#1}{#2}\scriptfont}}}
878

```

```

879 \def\@frac#1#2#3#4#5{%
880   \mathbox#1\smashboxc{\begingroup\endgroup\over#4}}%
881   \setbox\tw@\null
882   \ht\tw@ \ht\smashboxc
883   \dp\tw@ \dp\smashboxc
884   \wd\tw@ \wd\smashboxc
885   \box@if@visible\smashboxc\else\tw@fi}
886
887 \def\r@@t#1#2{\setbox\z@\hbox{$\m@th#1\sqrt{#2}$}%
888   \dimen@\ht\z@ \advance\dimen@-\dp\z@
889   \mskip5mu\raise.6\dimen@\copy\rootbox \mskip-10mu\box\z@}
890 \def\sqrt{\ifnextchar[\sqrt{]}
891 \def\sqrt[#1]{\root #1\of}
892 \def\xsqrt{\mathchoice{\sqrt{\displaystyle{#1}}}{\sqrt{#1}}{\sqrt{#1}}{\sqrt{#1}}}
893   \textstyle{#1}}{\sqrt{\scriptstyle{#1}}}{\sqrt{\scriptscriptstyle{#1}}}}
894
895 \def\xsqrt{\mathchoice{\sqrt{\arrayrulewidth\hskip-.5\arrayrulewidth}}{\sqrt{\arrayrulewidth\hskip-.5\arrayrulewidth}}{\sqrt{\arrayrulewidth\hskip-.5\arrayrulewidth}}{\sqrt{\arrayrulewidth\hskip-.5\arrayrulewidth}}}\if@visible
896   \hphantom{\sqrt{\arrayrulewidth\hskip-.5\arrayrulewidth}}\fi
897   \phantom{\sqrt{\arrayrulewidth\hskip-.5\arrayrulewidth}}\box\smashboxa}
898
899 \newbox\smashboxa
900 \newbox\smashboxb
901 \newbox\smashboxc

```

array and tabular environments: changes to ‘|’, `\hline`, `\cline`, and `\vline`, added 8 Jun 88

```

902 \def\arrayrule{\if@visible\addtopreamble{\hspace{-.5\arrayrulewidth}
903   \vrule\@width\arrayrulewidth\hspace{-.5\arrayrulewidth}}\fi}
904 \def\cline#1{\if@visible\cline#1\@nil\fi}
905
906 \def\hline{\noalign{\ifnum0=\fi
907   \if@visible\hrule\@height\arrayrulewidth
908   \else\hrule\@width\z@\fi
909   \fi
910   \futurelet\reserved@a\@xhline}
911
912 \def\vline{\if@visible\vrule\@width\arrayrulewidth
913   \else\vrule\@width\arrayrulewidth\@height\z@\@depth\z@\fi}
914
915 \message{output,}

```

### 10.3.3 Changes to L<sup>A</sup>T<sub>E</sub>X output routine

```

\@makecol ==
BEGIN
% Following test added for slides to check if extra page
if @makingslides = T
then if \c@page > 0
    then if \c@note > 0
        then type 'Note \thenote too long.'
        else if \c@overlay > 0
            then type 'Overlay \theoverlay too long.'
            else type 'Slide \theslide too long'

```

```

        fi      fi      fi      fi
ifvoid \insert\footins
    then  \@outputbox := \box255
    else   \@outputbox := \vbox {\unvbox255
                                \vskip \skip\footins
                                \footnoterule
                                \unvbox\@footins
}
fi
\@freelist :=G \@freelist * \@midlist
\@midlist :=G empty
\@combinefloats
\@outputbox := \vbox to \@colht{\boxmaxdepth := \maxdepth
                                \vfil %%\vfil added for slides
                                \unvbox\@outputbox
                                \vfil } %%\vfil added for slides
\maxdepth :=G \@maxdepth
END

```

FMi simple hack to allow none centered slides Should be revised of course.

```

916 \let\@topfil\vfil
917
918 \def\@makecol{\if@makingslides\ifnum\c@page>\z@ \@extraside\fi\fi
919 \ifvoid\footins \setbox\@outputbox\box\cclv \let\@botfil\vfil
920 \else\let\@botfil\relax\setbox\@outputbox
921 \vbox{\unvbox\cclv\vfil
922 \vskip\skip\footins\footnoterule\unvbox\footins\vskip
923 \z@ plus.1fil\relax}\fi
924 \xdef\@freelist{@freelist\@midlist}\gdef\@midlist{}@\combinefloats
925 \setbox\@outputbox\vbox to \@colht{\boxmaxdepth\maxdepth
926 \atopfil\unvbox\@outputbox\@botfil}\global\maxdepth\@maxdepth}
927
928 \def\@extraside{\ifnum\c@note>\z@
929 \ClassWarning{slides}{Note \thenote\space too long}\else
930 \ifnum\c@overlay>\z@
931 \ClassWarning{slides}{Overlay \theoverlay\space too long}\else
932 \ClassWarning{slides}{Slide \theslide\space too long}\fi\fi}
933 \message{init}

```

### 10.3.4 Special SLiTeX initializations

FMi why not allow for ref's ?

```

934 % \nofiles
935
936 \@visibletrue
937 </cmd>

```