Lwarp

LaTeX HTML5

The lwarp package

LaTeX to HTML

v0.69 — 2019/03/21

© 2016–2019 Brian Dunn
bd@BDTechConcepts.com

Abstract

The lwarp package converts LaTeX to HTML by using LaTeX to process the user's document and directly generate HTML tags. External utility programs are only used for the final conversion of text and images. Math may be represented by SVG images or MathJax. Hundreds of LaTeX packages are supported.

Documents may be produced by DVI or PDF LaTeX, LuaLaTeX, XeLaTeX; by several CJK engines, classes, and packages; or by customized systems such as perltex and pythontex. A *texlua* script automates compilation, index, glossary, and batch image processing, and also supports *latexmk*. Configuration is semi-automatic at the first manual compile. Support files are self-generated. Print and HTML versions of each document may coexist.

Assistance is provided for HTML import into EPUB conversion software and word processors.

Requirements include the commonly-available Poppler utilities (included with MiKTeX) and Perl. Detailed installation instructions are included for each of the major operating systems and TeX distributions.

A quick-start tutorial is provided, as well as extensive documentation for special cases, a general index, and a troubleshooting index. Automatic testing of package load order and image generation offers useful advice for resolving errors.

SVG math and many other generated images include LaTeX expressions in the `alt` tags. MathJax may be used with advanced equation numbering under the direct control of lwarp.

Complicated tables are supported, which copy/paste well into LibreOffice Writer.

Supported classes and packages include memoir and koma-script, cleveref, caption, mdframed, siunitx, and many popular packages for tabulars, floats, graphics, theorems, the title page, bibliography, indexing, footnotes, and editorial work.

TeX is a self-modifying tokenized macro-expansion language. Since lwarp is written directly in LaTeX, it is able to interpret the document's meaning at a deeper level than external conversions which merely approximate TeX. HTML5 and CSS3 are leveraged to provide advanced features such as booktabs trim, multicolumns, side-by-side minipages, and JavaScript-free navigation.

For a list of supported features, see table 2: Supported packages and features.

To update existing projects, see section 2: Updates.

Lwarp is still in development. Changes are likely.

License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in http://www.latex-project.org/lppl.txt and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

1 Support TEX development

TEX and related projects:

- are mostly open-sourced and a volunteer effort;
- benefit students, academics, scientists, engineers, and businesses;
- help drive education, public and private research, and commercial activity;
- are used in the fields of mathematics, science, engineering, and humanities;
- are international in reach;
- span decades of development;
- are enduring — many older packages are still actively used and maintained;
- are largely backwards compatible;
- are portable across all the major computing platforms;
- are usable even on older computers and away from internet access;
- are continuing to maintain relevance with modern improvements;
- require no yearly subscription fees;
- and are supported by an active community of knowledgeable volunteers.

Please consider helping by joining and/or contributing to the TEX Users Group, a United States 501(c)(3) tax-exempt charitable organization. Contributions are accepted by credit card, check, or Pay Pal, via the United Way, or by USA or European bank transfer. Membership in TUG supports the development of TEXLive, the major TEX distribution.

Donations may be directed towards individual projects:

TUG Bursary Fund: Assistance for attending annual TUG meetings.
CTAN: The Comprehensive TEX Archive Network — Central storage for TEX.
TeX Development Fund: Support for specific projects.
EduTeX: Teaching and using TEX in schools and universities.
GUST e-foundry fonts: Enhanced for math and additional language groups.
LaTeX Project: Modernizing the LATEX core.
Libre Font Fund: Fonts, tools (FontForge), and distribution (the Open Font Library).
LuaTeX: Combining the pdfTEX engine and the Lua language.
MetaPost: Postscript graphics.
MacTeX: TEX for Mac.
PDF Accessibility: Modern PDF standards.
Other: Additional projects may be specified.

To make a contribution: https://www.tug.org/donate.html

For country-specific TEX users groups: http://tug.org/usergroups.html

For users of MiKTEX: https://miktex.org/donations.html

Contents

1 Support TEX development **2**

List of Figures **53**

List of Tables **53**

2 Updates **54**

3 Introduction **74**
3.1 Typesetting conventions 76
3.2 Supported packages and features 77

4 Alternatives **83**
4.1 internet class 83
4.2 TEX4HT 83
4.3 Translators 83
4.4 ASCIIDOC and ASCIIDOCTOR 84
4.4.1 ASCIIDOCTOR-LATEX 84
4.5 PANDOC 84
4.6 Word processors 84
4.7 Commercial systems 84
4.8 Comparisons 84

5 Installation **86**
5.1 Installing the lwarp package 88
5.2 Installing the *lwarpmk* utility 89
5.2.1 Using a local copy of *lwarpmk* 91
5.3 Installing additional utilities 91

6 Tutorial **93**
6.1 Starting a new project 93
6.2 Compiling the print version with *lwarpmk* 97
6.3 Compiling the HTML version with *lwarpmk* 98
6.4 Generating the SVG images 99
6.5 Using MATHJAX for math 100
6.6 Changing the CSS style 101
6.7 Customizing the HTML output 101
6.8 Using *latexmk* 102
6.9 Using XELATEX or LUALATEX 103
6.10 Using DVI LATEX 103
6.11 Using a glossary 104
6.11.1 gloss package 104
6.11.2 glossaries package 104
6.12 Cleaning auxiliary files 105
6.13 Cleaning auxiliary and output files 105
6.14 Cleaning the images from the `<project>-images` directory 105
6.15 Converting PDF or EPS images to SVG 105
6.16 Creating HTML from an incomplete compile 105
6.17 Processing multiple projects in the same directory 105
6.18 Using the *make* utility 106

7 Converting an existing document 107

8 Additional details 108
8.1 Shell escape . . . 108
8.2 Font and UTF-8 support . . . 108
8.2.1 Indexes, glossaries, and encoding . . . 109
8.3 lwarp package loading and options . . . 110
8.4 Customizing the HTML output . . . 114
8.4.1 Example HTML file naming . . . 119
8.5 Customizing the CSS . . . 120
8.6 Selecting the operating system . . . 121
8.7 Selecting actions for print or HTML output . . . 121
8.8 Commands to be placed into the `warpprint` environment . . . 122
8.9 Title page . . . 123
8.10 HTML page meta descriptions . . . 124
8.11 HTML homepage meta title . . . 124
8.12 HTML page meta author . . . 124

9 Special cases and limitations 124
9.1 Things to avoid . . . 125
9.1.1 Invalid HTML . . . 125
9.2 Formatting . . . 125
9.2.1 Text formatting . . . 125
9.2.2 Horizontal space . . . 126
9.2.3 Text alignment . . . 126
9.2.4 Accents . . . 126
9.2.5 textcomp package . . . 126
9.2.6 Superscripts and other non-math uses of math mode . . . 126
9.2.7 Empty `\item` followed by a new line of text or a nested list: . . . 127
9.2.8 Filenames and URLs in lists or footnotes . . . 127
9.2.9 relsize package . . . 127
9.3 Boxes and minipages . . . 127
9.3.1 Marginpars . . . 127
9.3.2 Save Boxes . . . 127
9.3.3 Minipages . . . 127
9.3.4 Side-by-side minipages . . . 128
9.3.5 Framed minipages and other environments . . . 128
9.3.6 fancybox package . . . 130
9.3.7 mdframed package . . . 131
9.4 Section names . . . 132
9.5 Cross-references . . . 132
9.5.1 Page references . . . 133
9.5.2 cleveref and varioref packages . . . 133
9.5.3 Hyperlinks, hyperref, and url . . . 133
9.5.4 Footnotes and page notes . . . 133
9.6 Front and back matter . . . 135
9.6.1 Custom classes with multiple authors and affiliations . . . 135
9.6.2 Starred chapters and sections . . . 135
9.6.3 abstract package . . . 136
9.6.4 titling and authblk . . . 136
9.6.5 tocloft package . . . 136

9.6.6 appendix package . . . 136
9.6.7 pagenote package . . . 136
9.6.8 endnotes package . . . 136
9.6.9 BibTeX . . . 137
9.6.10 gloss package . . . 137
9.6.11 glossaries package . . . 137
9.6.12 nomencl package . . . 138
9.6.13 Indexing overview . . . 138
9.6.14 Indexing with basic LaTeX and makeidx . . . 139
9.6.15 Indexing with index . . . 140
9.6.16 Indexing with splitidx . . . 140
9.6.17 Indexing with imakeidx . . . 142
9.6.18 Indexes with memoir . . . 145
9.6.19 Using a custom *makeindex* style file . . . 148
9.6.20 Using a custom *xindy* style file . . . 149
9.6.21 Additional indexing limitations . . . 149
9.6.22 Index positions, toc, tocbibind . . . 150
9.7 Math . . . 151
9.7.1 Math in section names . . . 151
9.7.2 Rendering tradeoffs . . . 151
9.7.3 svg option . . . 152
9.7.4 MathJax option . . . 152
9.7.5 Customizing MathJax . . . 153
9.7.6 MathJax limitations . . . 153
9.7.7 Catcode changes . . . 154
9.7.8 Complicated inline math objects . . . 154
9.7.9 Complicated display math objects . . . 154
9.7.10 ntheorem package . . . 154
9.7.11 siunitx package . . . 155
9.7.12 units and nicefrac packages . . . 155
9.7.13 newtxmath package . . . 155
9.8 Graphics . . . 155
9.8.1 tikz package . . . 157
9.8.2 grffile package . . . 157
9.8.3 color package . . . 157
9.8.4 xcolor package . . . 157
9.8.5 epstopdf package . . . 158
9.8.6 pstricks package . . . 158
9.8.7 pdftricks package . . . 158
9.8.8 psfrag package . . . 158
9.8.9 pstool package . . . 159
9.8.10 asymptote package . . . 159
9.8.11 overpic package . . . 159
9.9 Tabbing . . . 159
9.10 Tabular . . . 160
9.10.1 `tabular` environment . . . 160
9.10.2 multirow package . . . 162
9.10.3 longtable package . . . 162
9.10.4 threeparttablex package . . . 163
9.10.5 supertabular and xtab packages . . . 163
9.10.6 colortbl package . . . 164

9.10.7 ctable package . . . 164
9.10.8 bigdelim package . . . 164
9.11 Floats . . . 164
9.11.1 Float contents alignment . . . 164
9.11.2 float, trivfloat, and/or algorithmicx together . . . 165
9.11.3 caption and subcaption packages . . . 165
9.11.4 subfig package . . . 165
9.11.5 floatrow package . . . 165
9.11.6 keyfloat package . . . 166
9.12 KOMA-SCRIPT classes . . . 166
9.13 MEMOIR class . . . 166
9.14 International languages . . . 167
9.15 Miscellaneous packages . . . 167
9.15.1 verse and memoir . . . 167
9.15.2 newclude package . . . 168
9.15.3 babel package . . . 168
9.15.4 polyglossia package . . . 168
9.15.5 todonotes and luatodonotes packages . . . 169
9.15.6 fixme . . . 169
9.15.7 chemfig package . . . 169
9.15.8 chemformula package . . . 169
9.15.9 mhchem package . . . 169
9.15.10 xparse package . . . 170
9.15.11 kotex package . . . 170

10 Compiling using custom shell commands 171
10.1 Command options . . . 171
10.2 Literal character macros . . . 171
10.3 *latexmk* . . . 172
10.4 perltex package . . . 173
10.5 pythontex package . . . 173
10.6 Other packages . . . 173
10.7 *make* program . . . 174
10.8 UTF-8 locale . . . 174

11 EPUB conversion 175

12 Word-processor conversion 177
12.1 Activating word-processor conversion . . . 177
12.2 Additional modifications . . . 178
12.3 Recommendations . . . 180
12.4 Limitations . . . 181

13 Modifying lwarp 182
13.1 Creating a development system . . . 182
13.2 Modifying a package for lwarp . . . 183
13.2.1 Adding a package to the lwarp.dtx file . . . 184
13.3 Modifying a class for lwarp . . . 184
13.4 Testing lwarp . . . 185
13.5 Modifying *lwarpmk* . . . 185

14 Troubleshooting 187

14.1 Using the lwarp.sty package 187
14.1.1 Debug tracing output 190
14.2 Compiling the lwarp.dtx file 190

15 Trademarks 192

1 lwarp.sty 193

16 Implementation 193

17 Section depths and HTML headings 194

18 Source code 195

19 Detecting the TEX engine — *pdflatex*, *lualatex*, *xelatex* 196

20 Early package requirements 196

21 Package load order 196
21.1 Tests of package load order 197
21.2 Error for disallowed packages and classes loaded before lwarp 199
21.3 Enforcing package loading after lwarp 200

22 MD5 hashing 208

23 pdfLATEX T1 and UTF-8 encoding 209

24 Unicode input characters 209

25 Upright quotes 210

26 Miscellaneous tools 210

27 Operating-System portability 211
27.1 Literal characters 212
27.2 Common portability code 213
27.3 UNIX, LINUX, and MAC OS 213
27.4 MS-WINDOWS 213

28 Package options 214
28.1 Additional options support 218
28.2 Conditional compilation 220

29 Required packages 221

30 Loading packages 225

31 Additional required packages 230

32 File handles 230

33 Include a file 230

34 Copying a file **231**

35 Debugging messages **232**

36 Defining print and HTML versions of macros and environments **233**

37 HTML-conversion output modifications **237**
37.1 User-level controls 237
37.2 Heading adjustments 239

38 Remembering original formatting macros **241**

39 Accents **243**

40 Configuration files **244**
40.1 Decide whether to generate configuration files 244
40.2 `<project>_html.tex` 245
40.3 *lwarpmk* configuration files 245
40.3.1 Helper macros 245
40.3.2 `lwarpmk.conf` 251
40.3.3 `<project>.lwarpmkconf` 251
40.4 `lwarp.css` 251
40.5 `lwarp_sagebrush.css` 280
40.6 `lwarp_formal.css` 285
40.7 `sample_project.css` 288
40.8 `lwarp.ist` 289
40.9 `lwarp.xdy` 289
40.10 `lwarp_one_limage.cmd` 290
40.11 `lwarp_mathjax.txt` 291
40.12 `lwarpmk.lua` — `lwarpmk` option 293

41 Stacks **310**
41.1 Assigning depths 310
41.2 Closing actions 311
41.3 Closing depths 311
41.4 Pushing and popping the stack 312

42 Data arrays **313**

43 Localizing catcodes **313**

44 Localizing dynamic math **314**

45 HTML entities **315**

46 HTML filename generation **316**

47 Homepage link **319**

48 `\LWRPrintStack` diagnostic tool **320**

49 Closing stack levels **320**

50 PDF pages and styles **321**

51 HTML tags, spans, divs, elements 322
51.1 Mapping LaTeX sections to HTML sections . . . 323
51.2 Babel-French tag modifications . . . 323
51.3 HTML output formatting . . . 324
51.4 HTML tags . . . 324
51.5 Block tags and comments . . . 326
51.6 Div class and element class . . . 327
51.7 Single-line elements . . . 328
51.8 HTML5 semantic elements . . . 329
51.9 High-level block and inline classes . . . 329
51.10 Closing HTML tags . . . 331

52 Paragraph handling 332

53 Paragraph start/stop handling 335

54 Indentfirst 338

55 Page headers and footers 338

56 CSS 339

57 Title, HTML meta author, HTML meta description 339

58 Footnotes 340
58.1 Regular page footnotes . . . 341
58.2 Minipage footnotes . . . 341
58.3 Titlepage thanks . . . 341
58.4 Regular page footnote implementation . . . 342
58.5 Minipage footnote implementation . . . 344
58.6 Printing pending footnotes . . . 345

59 Marginpars 346

60 Splitting HTML files 348
60.1 Customizing MathJax . . . 352

61 Sectioning 357
61.1 User-level starred section commands . . . 358
61.2 Book class commands . . . 358
61.3 Sectioning support macros . . . 359
61.4 Pre- and post- sectioning names . . . 366
61.5 `\section` and friends . . . 366

62 Starting a new file 368

63 Starting HTML output 372

64 Ending HTML output 375

65 Title page 377
65.1 Setting the title, etc. . . . 377
65.2 `\if@titlepage` . . . 378

65.3 Changes for \affiliation . . . 378
65.4 Printing the thanks . . . 379
65.5 Printing the title, etc. in HTML . . . 380
65.6 Printing the title, etc. in print form . . . 381
65.7 \maketitle for HTML output . . . 381
65.8 \published and \subtitle . . . 384

66 Abstract 385

67 Quote and verse 386
67.1 Attributions . . . 386
67.2 Quotes, quotations . . . 387
67.3 Verse . . . 387
67.3.1 LaTeX core verse environment . . . 388
67.3.2 verse and memoir . . . 388

68 Verbatim and tabbing 388

69 Theorems 391

70 Lists 392
70.1 List environment . . . 392
70.2 Itemize . . . 396
70.3 Enumerate . . . 396
70.4 Description . . . 397
70.5 Patching the lists . . . 398

71 Tabular 399
71.1 Limitations . . . 399
71.2 Temporary package-related macros . . . 401
71.2.1 arydshln . . . 401
71.3 Token lookahead . . . 401
71.4 Tabular variables . . . 402
71.5 Handling &, @, !, and bar . . . 405
71.5.1 Handling & . . . 406
71.5.2 Filling an unfinished row . . . 407
71.6 Handling \\ . . . 409
71.7 Looking ahead in the column specifications . . . 410
71.8 Parsing @, >, <, !, bar columns . . . 410
71.9 Parsing ‘l’, ‘c’, or ‘r’ columns . . . 414
71.10 Parsing ‘p’, ‘m’, or ‘b’ columns . . . 415
71.11 Parsing ‘w’ columns . . . 415
71.12 Parsing ’*’ columns . . . 415
71.13 Parsing ‘D’ columns . . . 416
71.14 Parsing the column specifications . . . 416
71.15 colortbl and xparse tabular color support . . . 421
71.16 Starting a new row . . . 422
71.17 Printing vertical bar tags . . . 423
71.18 Printing at or bang tags . . . 423
71.19 Data opening tag . . . 424
71.20 Midrules . . . 426
71.21 Cell colors . . . 432

71.22 Multicolumns . . . 436
71.22.1 Parsing multicolumns . . . 436
71.22.2 Multicolumn factored code . . . 439
71.22.3 Multicolumn . . . 442
71.22.4 Longtable captions . . . 443
71.22.5 Counting HTML tabular columns . . . 445
71.23 Multirow if not loaded . . . 446
71.24 Multicolumnrow . . . 447
71.25 Utility macros inside a table . . . 448
71.26 Special-case tabular markers . . . 448
71.27 Checking for a new table cell . . . 449
71.28 `\mrowcell` . . . 452
71.29 `\mcolrowcell` . . . 452
71.30 HTML `tabular` environment . . . 453

72 Cross-references 459
72.1 Setup . . . 460
72.2 New lwarp labels. . . . 460
72.3 Labels . . . 463
72.4 References . . . 464
72.5 Hyper-references . . . 466

73 Floats 470
73.1 Float environment . . . 470
73.2 Float tracking . . . 472
73.3 Caption inside a float environment . . . 474
73.4 Caption and LOF linking and tracking . . . 474

74 Table of Contents, LOF, LOT 477
74.1 Reading and printing the TOC . . . 478
74.2 High-level TOC commands . . . 480
74.3 Side TOC . . . 481
74.4 Low-level TOC line formatting . . . 482

75 Index and glossary 485

76 Bibliography presentation 489

77 Restoring original formatting 490

78 Math 491
78.1 Limitations . . . 491
78.1.1 Math in section names . . . 491
78.1.2 Rendering tradeoffs . . . 492
78.1.3 SVG option . . . 492
78.1.4 MathJax option . . . 493
78.1.5 Customizing MathJax . . . 493
78.1.6 MathJax limitations . . . 493
78.1.7 Catcode changes . . . 494
78.1.8 Complicated inline math objects . . . 494
78.1.9 Complicated display math objects . . . 495
78.2 HTML `alt` tag names . . . 495

78.3 Inline and display math . . . 495
78.4 MathJax support . . . 506
78.5 Equation environment . . . 508
78.6 \displaymathnormal and \displaymathother . . . 511
78.7 AMS Math environments . . . 512
78.7.1 Support macros . . . 512
78.7.2 Environment patches . . . 514

79 Lateximages 516
79.1 Description . . . 516
79.2 Support counters and macros . . . 517
79.3 Font size . . . 518
79.4 Sanitizing math expressions for HTML . . . 518
79.5 Equation numbers . . . 520
79.6 HTML alt tags . . . 521
79.7 lateximage environment . . . 522

80 center, flushleft, flushright 527

81 Preloaded packages 529

82 siunitx 530

83 Graphics print-mode modifications 531
83.1 General limitations . . . 531
83.2 Print-mode modifications . . . 533

84 xcolor boxes 533

85 chemmacros environments 536

86 cleveref 537

87 picture environment 540

88 Minipages and Boxes 540
88.1 Counters and lengths . . . 541
88.2 Footnote handling . . . 541
88.3 Minipage handling . . . 541
88.4 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox . . . 545

89 Direct formatting 551

90 Skips, spaces, font sizes 562

91 \phantomsection 569

92 \LaTeX and other logos 569
92.1 HTML logos . . . 570
92.2 Print logos . . . 572

93 \AtBeginDocument, \AtEndDocument 573

94 Loading Koma-Script class patches 573

95 Loading MEMOIR class patches 573

96 ut* class patches 574

97 CTEX patches 575

98 kotexutf patches 576

2 lwarp-2in1.sty 577

99 2in1 577

3 lwarp-2up.sty 577

100 2up 577

4 lwarp-a4.sty 577

101 a4 577

5 lwarp-a4wide.sty 578

102 a4wide 578

6 lwarp-a5comb.sty 578

103 a5comb 578

7 lwarp-abstract.sty 578

104 abstract 578

8 lwarp-academicons.sty 580

105 academicons 580

9 lwarp-accsupp.sty 581

106 accsupp 581

10 lwarp-acro.sty 581

107 acro 581

11 lwarp-acronym.sty 583

108 acronym 583

12 lwarp-adjmulticol.sty 584

109 adjmulticol 584

13 lwarp-addlines.sty 585

110 addlines 585

14 lwarp-afterpage.sty 585

111 afterpage 585

15 lwarp-algorithm2e.sty 585

112 algorithm2e 585

16 lwarp-algorithmicx.sty 589

113 algorithmicx 589

17 lwarp-alltt.sty 590

114 alltt 590

18 lwarp-amsmath.sty 590

115 amsmath 590

19 lwarp-amsthm.sty 597

116 amsthm 597

20 lwarp-anonchap.sty 600

117 anonchap 600

21 lwarp-anysize.sty 601

118 anysize 601

22 lwarp-appendix.sty 601

119 appendix 601

23 lwarp-ar.sty 602

120 ar 602

24 lwarp-arabicfront.sty 603

121 arabicfront 603

25 lwarp-array.sty 603

122 array 603

26 lwarp-arydshln.sty 604

123 arydshln 604

27 lwarp-asymptote.sty 606

124 asymptote 606

28 lwarp-atbegshi.sty 607

125 atbegshi 607

29 lwarp-attachfile.sty 607

126 attachfile 607

30 lwarp-attachfile2.sty 608

127 attachfile2 608

31 lwarp-authblk.sty 610

128 authblk 610

32 lwarp-axessibility.sty 611

129 axessibility 611

33 lwarp-axodraw2.sty 611

130 axodraw2 611

34 lwarp-backref.sty 612

131 backref 612

35 lwarp-balance.sty 612

132 balance 612

36 lwarp-bbding.sty 612

133 bbding 612

37 lwarp-biblatex.sty 617

134 biblatex 617

38 lwarp-bibunits.sty 618

135 bibunits 618

39 lwarp-bigdelim.sty 618

136 bigdelim 618

40 lwarp-bigfoot.sty 619

137 bigfoot 619

41 lwarp-bigstrut.sty 620

138 bigstrut 620

42 lwarp-bitpattern.sty 620

139 bitpattern 620

43 lwarp-blowup.sty 621

140 blowup 621

44 lwarp-booklet.sty 621

141 booklet 621

45 lwarp-bookmark.sty 621

142 bookmark 621

46 lwarp-booktabs.sty 622

143 booktabs 622

47 lwarp-bophook.sty 623

144 bophook 623

48 lwarp-bounddvi.sty 624

145 bounddvi 624

49 lwarp-boxedminipage2e.sty 624

146 boxedminipage2e 624

50 lwarp-breakurl.sty 624

147 breakurl 624

51 lwarp-breqn.sty 625

148 breqn 625

52 lwarp-bsheaders.sty 626

149 bsheaders 626

53 lwarp-bxpapersize.sty 627

150 bxpapersize 627

54 lwarp-bytefield.sty 627

151 bytefield 627

55 lwarp-cancel.sty 627

152 cancel 627

56 lwarp-canoniclayout.sty 628

153 canoniclayout 628

57 lwarp-caption.sty 628

154 caption 628

58 lwarp-cases.sty 631

155 cases 631

59 lwarp-changebar.sty 632

156 changebar 632

60 lwarp-changepage.sty 632

157 changepage 632

61 lwarp-changes.sty 633

158 changes 633

62 lwarp-chappg.sty 634

159 chappg 634

63 lwarp-chapterbib.sty 634

160 chapterbib 634

64 lwarp-chemfig.sty 634

161 chemfig 634

65 lwarp-chemformula.sty 636

162 chemformula 636

66 lwarp-chemgreek.sty 640

163 chemgreek **640**

67 lwarp-chemmacros.sty 641

164 chemmacros **641**

164.1 Changes to the user's document . . . 641
164.2 Code . . . 642
164.3 Loading modules . . . 642
164.4 New environments . . . 642
164.5 Acid-base . . . 642
164.6 Charges . . . 644
164.7 Nomenclature . . . 645
164.8 Particles . . . 647
164.9 Phases . . . 647
164.10 Mechanisms . . . 648
164.11 Newman . . . 650
164.12 Orbital . . . 650
164.13 Reactions . . . 651
164.14 Redox . . . 652
164.15 Scheme . . . 652
164.16 Spectroscopy . . . 653
164.17 Thermodynamics . . . 657

68 lwarp-chemnum.sty 659

165 chemnum **659**

69 lwarp-chkfloat.sty 660

166 chkfloat **660**

70 lwarp-chngpage.sty 660

167 chngpage **660**

71 lwarp-cite.sty 660

168 cite **660**

72 lwarp-CJK.sty 661

169 CJK **661**

73 lwarp-CJKutf8.sty 661

170 CJKutf8 661

74 lwarp-clrdblpg.sty 661

171 clrdblpg 661

75 lwarp-cmdtrack.sty 661

172 cmdtrack 661

76 lwarp-color.sty 662

173 color 662

77 lwarp-colortbl.sty 662

174 colortbl 662

78 lwarp-continue.sty 664

175 continue 664

79 lwarp-copyrightbox.sty 664

176 copyrightbox 664

80 lwarp-crop.sty 665

177 crop 665

81 lwarp-ctable.sty 665

178 ctable 665

82 lwarp-cuted.sty 668

179 cuted 668

83 lwarp-cutwin.sty 668

180 cutwin 668

84 lwarp-dblfloatfix.sty 669

181 dblfloatfix 669

85 lwarp-dblfnote.sty 669

182 dblfnote 669

86 lwarp-dcolumn.sty 669

183 dcolumn 669

87 lwarp-diagbox.sty 670

184 diagbox 670

88 lwarp-dingbat.sty 671

185 dingbat 671

89 lwarp-dprogress.sty 672

186 dprogress 672

90 lwarp-draftcopy.sty 672

187 draftcopy 672

91 lwarp-draftfigure.sty 673

188 draftfigure 673

92 lwarp-draftwatermark.sty 673

189 draftwatermark 673

93 lwarp-easy-todo.sty 674

190 easy-todo 674

94 lwarp-ebook.sty 674

191 ebook 674

95 lwarp-ed.sty 675

192 ed 675

96 lwarp-ellipsis.sty 676

193 ellipsis 676

97 lwarp-embrac.sty 676

194 embrac 676

98 lwarp-emptypage.sty 677

195 emptypage 677

99 lwarp-endfloat.sty 677

196 endfloat 677

100 lwarp-endheads.sty 677

197 endheads 677

101 lwarp-endnotes.sty 678

198 endnotes 678

102 lwarp-enumerate.sty 679

199 enumerate 679

103 lwarp-enumitem.sty 679

200 enumitem 679

104 lwarp-epigraph.sty 680

201 epigraph 680

105 lwarp-epsfig.sty 681

202 epsfig 681

106 lwarp-epstopdf.sty 681

203 epstopdf 681

107 lwarp-epstopdf-base.sty 682

204 epstopdf-base 682

108 lwarp-eqlist.sty 683

205 eqlist 683

109 lwarp-eqparbox.sty 683

206 eqparbox 683

110 lwarp-errata.sty 684

207 errata 684

111 lwarp-eso-pic.sty 685

208 eso-pic 685

112 lwarp-eurosym.sty 686

209 eurosym 686

113 lwarp-everypage.sty 686

210 everypage 686

114 lwarp-everyshi.sty 687

211 everyshi 687

115 lwarp-extramarks.sty 687

212 extramarks 687

116 lwarp-fancybox.sty 687

213 fancybox 687

117 lwarp-fancyhdr.sty 692

214 fancyhdr 692

118 lwarp-fancyref.sty 693

215 fancyref 693

119 lwarp-fancytabs.sty 694

216 fancytabs 694

120 lwarp-fancyvrb.sty 695

217 fancyvrb 695

121 lwarp-figcaps.sty 700

218 figcaps 700

122 lwarp-figsize.sty 701

219 figsize 701

123 lwarp-fitbox.sty 701

220 fitbox 701

124 lwarp-fix2col.sty 702

221 fix2col 702

125 lwarp-fixme.sty 702

222 fixme 702

126 lwarp-fixmetodonotes.sty 703

223 fixmetodonotes 703

127 lwarp-flafter.sty 704

224 flafter 704

128 lwarp-flippdf.sty 704

225 flippdf 704

129 lwarp-float.sty 704

226 float 704

130 lwarp-floatflt.sty 706

227 floatflt 706

131 lwarp-floatpag.sty 707

228 floatpag 707

132 lwarp-floatrow.sty 707

229 floatrow 707

133 lwarp-fltrace.sty 712

230 fltrace 712

134 lwarp-flushend.sty 712

231 flushend 712

135 lwarp-fnbreak.sty 713

232 fnbreak 713

136 lwarp-fncychap.sty 713

233 fncychap 713

137 lwarp-fnlineno.sty 714

234 fnlineno 714

138 lwarp-fnpara.sty 714

235 fnpara 714

139 lwarp-fnpos.sty 714

236 fnpos 714

140 lwarp-fontawesome.sty 714

237 fontawesome 714

141 lwarp-fontawesome5.sty 716

238 fontawesome5 716

142 lwarp-fontenc.sty 717

239 fontenc 717

143 lwarp-footmisc.sty 717

240 footmisc 717

144 lwarp-footnote.sty 718

241 footnote 718

145 lwarp-footnotebackref.sty 719

242 footnotebackref 719

146 lwarp-footnotehyper.sty 719

243 footnotehyper 719

147 lwarp-footnoterange.sty 719

244 footnoterange 719

148 lwarp-footnpag.sty 720

245 footnpag 720

149 lwarp-foreign.sty 720

246 foreign 720

150 lwarp-forest.sty 720

247 forest 720

151 lwarp-framed.sty 721

248 framed 721

152 lwarp-ftcap.sty 723

249 ftcap 723

153 lwarp-ftnright.sty 723

250 ftnright 723

154 lwarp-fullminipage.sty 724

251 fullminipage 724

155 lwarp-fullpage.sty 724

252 fullpage 724

156 lwarp-fullwidth.sty 724

253 fullwidth 724

157 lwarp-fwlw.sty 725

254 fwlw 725

158 lwarp-gentombow.sty 725

255 gentombow 725

159 lwarp-geometry.sty 725

256 geometry 725

160 lwarp-gloss.sty 726

257 gloss 726

161 lwarp-glossaries.sty 726

258 glossaries **726**

162 lwarp-gmeometric.sty 728

259 gmeometric **728**

163 lwarp-graphics.sty 729

260 graphics **729**

260.1 Graphics extensions 729
260.2 Length conversions and graphics options 730
260.3 Printing HTML styles 732
260.4 `\includegraphics` 733
260.5 Boxes 738

164 lwarp-graphicx.sty 741

261 graphicx **741**

165 lwarp-grffile.sty 741

262 grffile **741**

166 lwarp-grid.sty 742

263 grid **742**

167 lwarp-grid-system.sty 742

264 grid-system **742**

168 lwarp-gridset.sty 742

265 gridset **742**

169 lwarp-hang.sty 743

266 hang **743**

170 lwarp-hanging.sty 744

267 hanging **744**

171 lwarp-hypcap.sty 745

268 hypcap 745

172 lwarp-hypdestopt.sty 745

269 hypdestopt 745

173 lwarp-hypernat.sty 746

270 hypernat 746

174 lwarp-hyperref.sty 746

271 hyperref 746

175 lwarp-hyperxmp.sty 751

272 hyperxmp 751

176 lwarp-hyphenat.sty 751

273 hyphenat 751

177 lwarp-idxlayout.sty 752

274 idxlayout 752

178 lwarp-ifoddpage.sty 753

275 ifoddpage 753

179 lwarp-imakeidx.sty 753

276 imakeidx 753

180 lwarp-index.sty 757

277 index 757

181 lwarp-intopdf.sty 759

278 intopdf 759

182 lwarp-karnaugh-map.sty 759

279 karnaugh-map 759

183 lwarp-keyfloat.sty 762

280 keyfloat 762

184 lwarp-layaureo.sty 768

281 layaureo 768

185 lwarp-layout.sty 768

282 layout 768

186 lwarp-layouts.sty 768

283 layouts 768

187 lwarp-leading.sty 771

284 leading 771

188 lwarp-letterspace.sty 771

285 letterspace 771

189 lwarp-lettrine.sty 772

286 lettrine 772

190 lwarp-lineno.sty 772

287 lineno 772

191 lwarp-lips.sty 775

288 lips 775

192 lwarp-listings.sty 775

289 listings 775

193 lwarp-listliketab.sty 779

290 listliketab 779

194 lwarp-lltjext.sty 780

291 lltjext 780

195 lwarp-longtable.sty 781

292 longtable 781

196 lwarp-lscape.sty 783

293 lscape 783

197 lwarp-ltablex.sty 784

294 ltablex 784

198 lwarp-ltcaption.sty 784

295 ltcaption 784

199 lwarp-ltxgrid.sty 785

296 ltxgrid 785

200 lwarp-ltxtable.sty 785

297 ltxtable 785

201 lwarp-lua-check-hyphen.sty 785

298 lua-check-hyphen 785

202 lwarp-lua-visual-debug.sty 786

299 lua-visual-debug 786

203 lwarp-luacolor.sty 786

300 luacolor 786

204 lwarp-luatodonotes.sty 786

301 luatodonotes 786

205 lwarp-magaz.sty 788

302 magaz 788

206 lwarp-makeidx.sty 788

303 makeidx 788

207 lwarp-manyfoot.sty 789

304 manyfoot 789

208 lwarp-marginal.sty 791

305 marginal 791

209 lwarp-marginfit.sty 791

306 marginfit 791

210 lwarp-marginfix.sty 791

307 marginfix 791

211 lwarp-marginnote.sty 792

308 marginnote 792

212 lwarp-marvosym.sty 792

309 marvosym 792

213 lwarp-mcaption.sty 793

310 mcaption 793

214 lwarp-mdframed.sty 793

311 mdframed **793**
311.1 Limitations 793
311.2 Package loading 794
311.3 Patches 794
311.4 Initial setup 795
311.5 Color and length HTML conversion 795
311.6 Environment encapsulation 795
311.7 Mdframed environment 797
311.8 Titles and subtitles 798
311.9 New environments 800

215 lwarp-memhfixc.sty **802**

312 memhfixc **802**

216 lwarp-metalogo.sty **802**

313 metalogo **802**

217 lwarp-mhchem.sty **803**

314 mhchem **803**

218 lwarp-microtype.sty **805**

315 microtype **805**

219 lwarp-midfloat.sty **806**

316 midfloat **806**

220 lwarp-midpage.sty **806**

317 midpage **806**

221 lwarp-minitoc.sty **806**

318 minitoc **806**

222 lwarp-morefloats.sty **807**

319 morefloats **807**

223 lwarp-moreverb.sty **807**

320 moreverb **807**

224 lwarp-mparhack.sty 808

321 mparhack **808**

225 lwarp-multicap.sty 808

322 multicap **808**

226 lwarp-multicol.sty 809

323 multicol **809**

227 lwarp-multicolrule.sty 810

324 multicolrule **810**

228 lwarp-multirow.sty 810

325 multirow **810**
325.1 Multirow 811
325.2 Combined multicolumn and multirow 813

229 lwarp-multitoc.sty 814

326 multitoc **814**

230 lwarp-musicography.sty 814

327 musicography **814**

231 lwarp-nameauth.sty 816

328 nameauth **816**

232 lwarp-nameref.sty 817

329 nameref **817**

233 lwarp-natbib.sty 817

330 natbib **817**

234 lwarp-nccfancyhdr.sty 818

331 nccfancyhdr 818

235 lwarp-needspace.sty 819

332 needspace 819

236 lwarp-nextpage.sty 819

333 nextpage 819

237 lwarp-nicefrac.sty 820

334 nicefrac 820

238 lwarp-niceframe.sty 820

335 niceframe 820

239 lwarp-nomencl.sty 821

336 nomencl 821

240 lwarp-nonfloat.sty 821

337 nonfloat 821

241 lwarp-nonumonpart.sty 822

338 nonumonpart 822

242 lwarp-nopageno.sty 822

339 nopageno 822

243 lwarp-notes.sty 822

340 notes 822

244 lwarp-notespages.sty 823

341 notespages 823

245 lwarp-nowidow.sty 823

342 nowidow **823**

246 lwarp-ntheorem.sty 824

343 ntheorem **824**

343.1 Limitations . . . 824
343.2 Options . . . 824
343.3 Remembering the theorem style . . . 825
343.4 HTML cross-referencing . . . 828
343.5 `\newtheoremstyle` . . . 828
343.6 Standard styles . . . 828
343.7 Additional objects . . . 830
343.8 Renewed standard configuration . . . 830
343.9 amsthm option . . . 831
343.10 Ending a theorem . . . 833
343.11 `\NoEndMark` . . . 834
343.12 List-of . . . 834
343.13 Symbols . . . 834
343.14 Cross-referencing . . . 835

247 lwarp-octave.sty 835

344 octave **835**

248 lwarp-overpic.sty 836

345 overpic **836**

249 lwarp-pagegrid.sty 837

346 pagegrid **837**

250 lwarp-pagenote.sty 837

347 pagenote **837**

251 lwarp-pagesel.sty 837

348 pagesel **837**

252 lwarp-paralist.sty 837

349 paralist **837**

253 lwarp-parnotes.sty 838

350 parnotes 838

254 lwarp-parskip.sty 839

351 parskip 839

255 lwarp-pbox.sty 839

352 pbox 839

256 lwarp-pdfcomment.sty 840

353 pdfcomment 840

257 lwarp-pdflscape.sty 840

354 pdflscape 840

258 lwarp-pdfmarginpar.sty 840

355 pdfmarginpar 840

259 lwarp-pdfpages.sty 841

356 pdfpages 841

260 lwarp-pdfprivacy.sty 843

357 pdfprivacy 843

261 lwarp-pdfrender.sty 843

358 pdfrender 843

262 lwarp-pdfsync.sty 844

359 pdfsync 844

263 lwarp-pdftricks.sty 844

360 pdftricks 844

264 lwarp-pdfx.sty 845

361 pdfx 845

265 lwarp-perpage.sty 845

362 perpage 845

266 lwarp-pfnote.sty 846

363 pfnote 846

267 lwarp-phfqit.sty 846

364 phfqit 846

268 lwarp-pifont.sty 847

365 pifont 847

269 lwarp-placeins.sty 847

366 placeins 847

270 lwarp-plarydshln.sty 848

367 plarydshln 848

271 lwarp-plext.sty 848

368 plext 848

272 lwarp-plextarydshln.sty 849

369 plextarydshln 849

273 lwarp-plextcolortbl.sty 849

370 plextcolortbl 849

274 lwarp-prelim2e.sty 849

371 prelim2e 849

275 lwarp-prettyref.sty 850

372 prettyref 850

276 lwarp-preview.sty 850

373 preview 850

277 lwarp-psfrag.sty 850

374 psfrag 850

278 lwarp-psfragx.sty 851

375 psfragx 851

279 lwarp-pst-eps.sty 851

376 pst-eps 851

280 lwarp-pstool.sty 852

377 pstool 852

281 lwarp-pstricks.sty 853

378 pstricks 853

282 lwarp-pxatbegshi.sty 853

379 pxatbegshi 853

283 lwarp-pxeveryshi.sty 853

380 pxeveryshi 853

284 lwarp-pxftnright.sty 853

381 pxftnright 853

285 lwarp-pxjahyper.sty 854

382 pxjahyper 854

286 lwarp-quotchap.sty 854

383 quotchap 854

287 lwarp-quoting.sty 855

384 quoting 855

288 lwarp-ragged2e.sty 855

385 ragged2e 855

289 lwarp-realscripts.sty 856

386 realscripts 856

290 lwarp-refcheck.sty 857

387 refcheck 857

291 lwarp-register.sty 857

388 register 857

292 lwarp-relsize.sty 858

389 relsize 858

293 lwarp-repeatindex.sty 859

390 repeatindex 859

294 lwarp-resizegather.sty 860

391 resizegather 860

295 lwarp-rmpage.sty 860

392 rmpage 860

296 lwarp-romanbar.sty 861

393 romanbar 861

297 lwarp-romanbarpagenumber.sty 861

394 romanbarpagenumber 861

298 lwarp-rotating.sty 861

395 rotating 861

299 lwarp-rotfloat.sty 862

396 rotfloat 862

300 lwarp-rviewport.sty 863

397 rviewport 863

301 lwarp-savetrees.sty 863

398 savetrees 863

302 lwarp-scalefnt.sty 863

399 scalefnt 863

303 lwarp-schemata.sty 863

400 schemata 863

304 lwarp-scrextend.sty 864

401 scrextend 864

305 lwarp-scrhack.sty 867

402 scrhack 867

306 lwarp-scrlayer.sty 867

403 scrlayer 867

307 lwarp-scrlayer-notecolumn.sty 868

404 scrlayer-notecolumn 868

308 lwarp-scrlayer-scrpage.sty 869

405 scrlayer-scrpage 869

309 lwarp-scrpage2.sty 870

406 scrpage2 870

310 lwarp-section.sty 871

407 section 871

311 lwarp-sectionbreak.sty 872

408 sectionbreak 872

312 lwarp-sectsty.sty 872

409 sectsty 872

313 lwarp-semantic-markup.sty 873

410 semantic-markup 873

314 lwarp-setspace.sty 874

411 setspace 874

315 lwarp-shadow.sty 875

412 shadow 875

316 lwarp-showidx.sty 875

413 showidx 875

317 lwarp-showkeys.sty 875

414 showkeys 875

318 lwarp-showtags.sty 876

415 showtags 876

319 lwarp-sidecap.sty 876

416 sidecap 876

320 lwarp-sidenotes.sty 877

417 sidenotes 877

321 lwarp-SIunits.sty 878

418 SIunits 878

322 lwarp-siunitx.sty 879

419 siunitx 879

323 lwarp-soul.sty 884

420 soul 884

324 lwarp-soulpos.sty 885

421 soulpos 885

325 lwarp-soulutf8.sty 886

422 soulutf8 886

326 lwarp-splitidx.sty 886

423 splitidx 886

327 lwarp-srcltx.sty 888

424 srcltx 888

328 lwarp-srctex.sty 888

425 srctex 888

329 lwarp-stabular.sty 888

426 stabular 888

330 lwarp-stfloats.sty 889

427 stfloats 889

331 lwarp-struktex.sty 889

428 struktex 889

332 lwarp-subcaption.sty 890

429 subcaption 890

333 lwarp-subfig.sty 891

430 subfig 891

334 lwarp-subfigure.sty 895

431 subfigure 895

335 lwarp-supertabular.sty 896

432 supertabular 896

336 lwarp-syntonly.sty 897

433 syntonly 897

337 lwarp-tablefootnote.sty 898

434 tablefootnote 898

338 lwarp-tabls.sty 898

435 tabls 898

339 lwarp-tabularx.sty 898

436 tabularx 898

340 lwarp-tabulary.sty 899

437 tabulary 899

341 lwarp-tascmac.sty 899

438 tascmac **899**

342 lwarp-textarea.sty 901

439 textarea **901**

343 lwarp-textcomp.sty 901

440 textcomp **901**
440.1 Limitations . . . 901
440.2 Package loading . . . 902
440.3 HTML symbols . . . 902
440.3.1 pdfLaTeX symbols . . . 902
440.3.2 XeLaTeX and LuaLaTeX symbols . . . 902
440.4 HTML diacritics . . . 903

344 lwarp-textfit.sty 905

441 textfit **905**

345 lwarp-textpos.sty 905

442 textpos **905**

346 lwarp-theorem.sty 906

443 theorem **906**
443.1 Remembering the theorem style . . . 906
443.2 CSS patches . . . 908

347 lwarp-thinsp.sty 910

444 thinsp **910**

348 lwarp-threadcol.sty 910

445 threadcol **910**

349 lwarp-threeparttable.sty 910

446 threeparttable **910**

350 lwarp-threeparttablex.sty 911

447 threeparttablex 911

351 lwarp-thumb.sty 912

448 thumb 912

352 lwarp-thumbs.sty 912

449 thumbs 912

353 lwarp-tikz.sty 913

450 tikz 913

354 lwarp-titleps.sty 914

451 titleps 914

355 lwarp-titleref.sty 917

452 titleref 917

356 lwarp-titlesec.sty 917

453 titlesec 917

357 lwarp-titletoc.sty 919

454 titletoc 919

358 lwarp-titling.sty 921

455 titling 921

359 lwarp-tocbasic.sty 925

456 tocbasic 925

360 lwarp-tocbibind.sty 926

457 tocbibind 926

361 lwarp-tocdata.sty 927

458 tocdata 927

362 lwarp-tocenter.sty 929

459 tocenter 929

363 lwarp-tocloft.sty 929

460 tocloft 929

364 lwarp-tocstyle.sty 935

461 tocstyle 935

365 lwarp-todo.sty 935

462 todo 935

366 lwarp-todonotes.sty 936

463 todonotes 936

367 lwarp-topcapt.sty 938

464 topcapt 938

368 lwarp-tram.sty 938

465 tram 938

369 lwarp-transparent.sty 939

466 transparent 939

370 lwarp-trimclip.sty 939

467 trimclip 939

371 lwarp-trivfloat.sty 940

468 trivfloat 940

468.1 Combining \newfloat, \trivfloat, and algorithmicx 940

372 lwarp-truncate.sty 941

469 truncate 941

373 lwarp-turnthepage.sty 941

470 turnthepage 941

374 lwarp-twoup.sty 941

471 twoup 941

375 lwarp-typearea.sty 942

472 typearea 942

376 lwarp-typicons.sty 942

473 typicons 942

377 lwarp-ulem.sty 943

474 ulem 943

378 lwarp-umoline.sty 944

475 umoline 944

379 lwarp-underscore.sty 945

476 underscore 945

380 lwarp-units.sty 945

477 units 945

381 lwarp-unitsdef.sty 946

478 unitsdef 946

382 lwarp-upref.sty 947

479 upref 947

383 lwarp-url.sty 947

480 url 947

384 lwarp-uspace.sty 948

481 uspace 948

385 lwarp-verse.sty 948

482 verse 948

386 lwarp-versonotes.sty 949

483 versonotes 949

387 lwarp-vertbars.sty 950

484 vertbars 950

388 lwarp-vmargin.sty 950

485 vmargin 950

389 lwarp-vowel.sty 951

486 vowel 951

390 lwarp-vpe.sty 951

487 vpe 951

391 lwarp-vwcol.sty 952

488 vwcol 952

392 lwarp-wallpaper.sty 954

489 wallpaper 954

393 lwarp-watermark.sty 954

490 watermark **954**

394 lwarp-widows-and-orphans.sty 955

491 widows-and-orphans **955**

395 lwarp-wrapfig.sty 955

492 wrapfig **955**

396 lwarp-xbmks.sty 956

493 xbmks **956**

397 lwarp-xcolor.sty 956

494 xcolor **956**

494.1 Limitations . . . 957
494.2 xcolor definitions: location and timing . . . 957
494.3 Package loading . . . 959
494.4 Remembering and restoring original definitions . . . 959
494.5 HTML color style . . . 959
494.6 HTML border . . . 960
494.7 High-level macros . . . 961
494.8 Row colors . . . 965

398 lwarp-xechangebar.sty 967

495 xechangebar **967**

399 lwarp-xellipsis.sty 967

496 xellipsis **967**

400 lwarp-xetexko-vertical.sty 968

497 xetexko-vertical **968**

401 lwarp-xfakebold.sty 968

498 xfakebold **968**

402 lwarp-xfrac.sty 968

499 xfrac 968

403 lwarp-xltabular.sty 971

500 xltabular 971

404 lwarp-xltxtra.sty 971

501 xltxtra 971

405 lwarp-xmpincl.sty 972

502 xmpincl 972

406 lwarp-xpiano.sty 972

503 xpiano 972

407 lwarp-xpinyin.sty 973

504 xpinyin 973

408 lwarp-xtab.sty 973

505 xtab 973

409 lwarp-xunicode.sty 975

506 xunicode 975

410 lwarp-xurl.sty 976

507 xurl 976

411 lwarp-xy.sty 976

508 xy 976

412 lwarp-zhlineskip.sty 977

509 zhlineskip 977

413 lwarp-zwpagelayout.sty 977

510 zwpagelayout 977

414 lwarp-patch-komascript.sty 978

511 patch-komascript 978

415 lwarp-patch-memoir.sty 980

512 patch-memoir 980

512.1 Packages . . . 981
512.2 Preliminary setup . . . 982
512.3 Laying out the page . . . 983
512.4 Text and fonts . . . 985
512.5 Titles . . . 986
512.6 Abstracts . . . 986
512.7 Docment divisions . . . 986
512.8 Pagination and headers . . . 989
512.9 Paragraphs and lists . . . 990
512.10 Contents lists . . . 991
512.11 Floats and captions . . . 995
512.12 Page notes . . . 998
512.13 Decorative text . . . 999
512.14 Poetry . . . 999
512.15 Boxes, verbatims and files . . . 1000
512.16 Cross referencing . . . 1001
512.17 Back matter . . . 1001
512.18 Miscellaneous . . . 1003
512.19 ccaption emulation . . . 1003
512.20 Final patchwork . . . 1005

Change History 1006

513 Chg Hist 1006

Index of Objects 1032

General Index 1052

Troubleshooting Index 1056

Index of Indexes 1061

List of Figures

1 tutorial.tex listing 94

List of Tables

1 Typesetting conventions 76
2 LaTeX lwarp package — Supported features 77
3 Required software programs 87
4 Configuration files created by print version 96
5 lwarp package options 111
6 HTML settings 115
7 Literal character macros 172
8 Section HTML headings for word-processor conversion 180
9 Section depths and HTML headings 194
10 Tabular baseline 416
11 Tabular HTML column conversions 417
12 Cross-referencing data structures 461
13 Float data structures 470
14 amsthm package — CSS styling of theorems and proofs 597
15 Ntheorem package — CSS styling of theorems and proofs 824
16 Theorem package — CSS styling of theorems and proofs 906

2 Updates

The following is a summary of updates to lwarp, highlighting new features and any special changes which must be made due to improvements or modifications in lwarp itself.

For a detailed list of the most recent changes, see the end of the Change History on page 1031.

v0.69: Error handling, many fixes, improved keyfloat / tocdata.

- Fix for HTML corruption of `lateximage` displays.
- `\makebox`, `\framebox`: Fix for (⟨*width,height*⟩) arguments.
- `fminipage`: Honors `\minipagefullwidth`.

packages

- array, longtable: Fix for `\tabularnewline`.
- tabularx, tabulary: Fix to require the array package.
- supertabular, xtab: Fix to clear caption after use.
- graphics: Added a warning if used the `\includegraphics scale` option.
- multirow: Added an error if didn't use `\mrowcell` or `\mcolrowcell` when using `\multirow` or `\multicolumnrow`.
- keyfloat: Updated for v2.00, additional improvements.
- Added ctable, eqlist, eqparbox, ftcap, listliketab, minitoc, tocdata, topcapt.

v0.68: Error handling, tabulars, footnotes.

lwarpmk

- *lwarpmk*: Improved error handling for image generation if compile was incomplete.
- `tabular`: Fix for `\warpprintonly`.

packages

- longtable: Improved flexibility for `\endhead`, etc. Improved error reporting if `\endhead`, etc. incorrect for lwarp.
- threeparttable: Fix for caption type.
- hyperref: Fix for options with braces.
- morefloats: Fix to be loaded early for print output.
- listings: Updated for v1.7.
- Added bigfoot, fnpara, footnotebackref, manyfoot, tablefootnote, threeparttablex.
- Added layouts, niceframe, perpage, showtags.
- Prevented alg, algorithmic, pdfcprot, fncylab.

v0.67: Filename generation, symbol fonts.

docs

- Documentation fix for `<project>-images`, `<project>-images.txt`.
- Added discussion regarding section names. See section 9.4.

filenames

- Added `\FilenameNullify` and `\FilenameSimplify` for filename generation. See section 9.4.

- Core, textcomp, xunicode: Nullified additional symbols during filename generation.

packages

- color: Fix for version number warnings.
- Added academicons, bbding, dingbat, eurosym, fontawesome, fontawesome5, marvosym, pifont, typicons.
- Added changes, easyReview, fitbox, foreign, gloss, karnaugh-map, multicap, nomencl, notes, struktex, umoline, xfakebold.
- Tested to work as-is with askmaps, curves, euro, karnaughmap, tikz-karnaugh.

v0.66: xr, multiple projects, image names/directory, HTML formatting

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

`lateximage`

- Adds options `ImagesDirectory` and `ImagesName` to assign directory and name prefixes for `lateximage` images. The new defaults include the jobname, allowing the image directories for multiple projects to coexist.

⚠ existing projects

- To reuse existing `lateximage` directories, add lwarp options

```
\usepackage[
  ImagesDirectory={lateximages},
  ImagesName={lateximage-}
]{lwarp}
```

  If not reused, the existing `lateximages` directory and `lateximages.txt` file may be removed.

filenames

- Added `\FilenameLimit` to control the maximum length of the filenames generated by lwarp.

⚠ Possible filename changes

- Improved filename generation when special characters or macros are used in section names.

WINDOWS

- Fix for **`lwarpmk cleanlimages`** with WINDOWS.

floats

- Fixes for floats in the home page.

lists, table notes

- Improved CSS for definition lists, table notes.

`tabular`

- `tabular`: Fixes for `\par` in column specifier, minipage inside `tabular`.

indexing

- Indexing: Fix for a long line of multiple entries.

`minipage`

- `\minipagefullwidth`: Fix for global changes.
- Added `\UseMinipageWidths` and `\IgnoreMinipageWidths`. See section 9.3.3.

colors

- Improved `\fbox`, `\fboxBlock`, `\fminipage` to use current text color.

HTML

- Improved HTML output formatting.

docs

- Added discussion regarding invalid HTML. See section 9.1.1.
- Added discussion regarding math in section names, `\imagegraphics scale` option. See section 7.
- Added discussion regarding international languages in section names. See section 9.14.

packages

- caption: Fix for options clash.
- xr, xr-hyper: Now compatible.

- subcaption: Improved horizontal spacing.
- multicol: Fix for minipage inside `multicols`.
- multicolrule: Updated for v1.2.
- tocbasic: Minor update.
- acronym: Fix for acronym in float caption.
- kotexutf: Patch with *pdflatex* and new lwarp labels.
- extramarks, fancyhdr: Updated for v3.10.
- memoir: Added docs regarding version numbers. See section 9.13.
- zref: No longer required.
- Added ar, ed, indentfirst, nameauth, truncate.
- Verified to work as-is with changelog.
- Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs.

v0.65: CSS layout, `alt` tags, Japanese.

page layout
- Moved the sideTOC to the left side, allowing improved CSS for margin notes.
- Improved page layout CSS.

image `alt` tags
- graphicx `\includegraphics`: Added the `alt` key to assign an `alt` tag to an image. Default is "`(image)`", assigned to pass validation.

duplicate HTML files
- Detects and causes an error if duplicate HTML file names are generated, caused by identical or similar sectioning names.

fixes
- Fix for `tabular*`.
- Fix for tabular border colors.
- Fixes `\quad`, `\enskip`, and figure captions to pass validation.

Japanese
- Added ltj* classes, bounddvi, gentombow, lltjext, plarydshln, plext, plextarydshln, plextcolortbl, pxatbegshi, pxeveryshi, pxftnright, pxjahyper, tascmac.
- Verified to work with plarray, plautopatch, plextarray, plextdelarray, pxgentombow, plsiunitx, pxpdfpages, pxpgfrcs, pxpgfmark.

packages
- Added support for fontspec `\textsi` and `\sishape`.
- Added multicol's `\docolaction`.
- Added embrac, footnoterange, multicolrule, versonotes.

v0.64: Koma-Script, Japanese, Chinese.

Japanese
- Added utarticle and related classes.
- Improved ujarticle and related classes.

Chinese
- Fix for biblatex with CTEX and other classes.

Koma-Script
- Fixes for scrlayer, scrlayer-scrpage.

packages
- addlines: Updated to v0.3.
- Added bsheaders, gmeometric, marginal, rmpage, scrpage2.

v0.63: mdframed, Chinese, Japanese, Korean

localization
- Added `\linkhomename`: A user-definable name for the **Home** link.
- Documented `\sidetocname`: A user-definable name for the sideTOC.

fixes
- Fix: `\LinkHome` for print output.

optimizations
- Moved package load checks to the lwarp core to reduce the number of `lwarp-*` files.

packages
- mdframed: Fix with amsthm, improved titles and font control. Improved rule widths.

Chinese
- Fixes for xeCJK.
- Added xpinyin, zhlineskip.
- Verified to work with cjkpunct, upzhkinsoku, zhspacing.

Japanese
- Verified to work with zxjatype, luatexja, luatexja-fontspec.
- Added bxjsarticle and related classes.
- Added ltjsarticle and related classes.
- Added pLaTeX, upLaTeX, ujarticle and related classes.
- Prevented utarticle and related classes.
- Prevented bxcjkatype.

Korean
- Verified to work with kotex, xetexko, luatexko.

v0.62: MiKTeX docs, HTML title, CTeX, xeCJK, bitpattern.

docs
- Docs: Setting a UTF-8 locale. See section 10.8.

MiKTeX
- MiKTeX: Docs for *MiKTeX Console* and miktex-poppler-bin.

HTML `<title>`
- HTML subpage titles: Added `\HTMLTitleBeforeSection` and `\HTMLTitleAfterSection` to select whether the HTML `<title>` displays the website name before or after the section name. See section 8.4.

fixes
- Fix for package options handling.
- Fixes for horizontal white space between `fminipage`, `fcolorminipage`, `colorboxBlock`, `fcolorboxBlock`.
- Logos: Fix for XeTeX logo, improved CSS, made robust, improved search-engine optimization.
- `\\[$1]`: Additional HTML `<br>` if $1 > 0 pt.
- Fixes for `\includgraphics` filename, and with `FormatWP`.
- Fix: CSS for `\textup`.
- Fix: Added `\slshape`.

Chinese
- Added ctex package and related classes, xeCJK.
- Prevented CJK, CJKutf8 unless xeCJK, ctex are used.

packages
- chemfig: Docs for new macro `\polymerdelim`.
- asymptote: Docs for compilation.
- chngpage: Fix to load lwarp-changepage.
- algorithm2e: Fix with non-book classes.

- register: Updated to v1.8.
- nicefrac: Improved font control and CSS, honors `nice` and `ugly`.
- units: Improved font control and CSS, honors `tight` and `loose`.
- xfrac: Improved CSS.
- textcomp and xunicode: Fix conflicts with `\textcircled`.
- ulem: Improved compatibility with CJKulem, `lateximage`.
- MathJax and siunitx: Removed inoperable extension.
- Added bitpattern, pdfcomment, pdfmarginpar, tram, unitsdef, xechangebar.
- Added musicography, octave, semantic-markup.
- Added 2in1, flippdf, notespages, rviewport, twoup.

v0.61: Custom compilation, EPS-related packages, documentation, indexes.

docs
- Split index into multiple indexes. See page 1061.
- Improved documentation regarding font selection. See section 8.2.
- Added documentation regarding debugging options. See section 35.
- Added documentation regarding HTML entities inside program listings. See section 9.2.1.

custom compiling
- Added options to specify the shell commands to execute for **`lwarpmk print`** and **`lwarpmk html`**, allowing the use of lwarp with perltex, pythontex, etc. If not specified, these are set automatically depending on the LaTeX engine, `--shell-escape`, and lwarp options. See section 10.

⚠ changed names
- Changed macro names to match `\displaymathother`, `\displaymathnormal`:

Old	New
`\StartDynamicMath`	`\inlinemathother`
`\StopDynamicMath`	`\inlinemathnormal`

fixes
- Fix: Paragraph tags in a `tabular`.
- Fix: supertabular and xtab captions.
- Fix: DVI LaTeX `\includegraphics` EPS images.
- Fix: newfloat lists.
- Fix: CSS footnotes text align, minipage tabular and footnote margins.

packages
- Added epsfig, psfrag, psfragx, pstool.
- Added copyrightbox, pdfprivacy, thinsp, threadcol, uspace.
- Added chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.

v0.60: Fixes for longtable, listings.

fixes
- longtable, etc.: Fixes for slowdown and memory management for very long tables.
- listings: Fix for HTML entities, and also when used inside a list.
- diagbox: Fix for incorrect HTML par tags.

packages
- Added 2up, booklet.

- Added bophook, draftfigure, fullminipage, grid-system, layaureo.
- Added leading, widows-and-orphans.
- Added fancytabs, thumb, thumbs.

v0.59: DVI *latex*, MATHJAX, asymptote, pdftricks and pstricks, epstopdf, brqen.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- Added an error if `lwarpmk.conf`'s format has changed and the document must be recompiled.
- Added a warning if the `lwarpmk.conf` configuration file appears to be for the wrong operating system, in case files are transferred between systems.
- Added

  ```
  lwarpmk epstopdf <list-of-EPS-files>
  ```

  to quickly convert a document's EPS images to PDF or SVG. See section 9.8.

DVI *latex*

- Added support for DVI *latex*. See section 8.3.

latexmk

- Fix for `--shell-escape` with *latexmk*.

math

- Updated MathJax script to v2.7.4.
- Fix: Mathjax chapter number removed from non-numeric tagged equations.
- Added MathJax support for nicefrac, units.
- Fix for `\[` and `\]` with `\displaymathnormal`.

images

- Fix for `\includegraphics` filename expansion.
- `\includegraphics` now works with `.pdf` and `.eps` filename extensions.

packages

- Moved amsmath out of the lwarp core.
- Fix for chemformula `\NMR`.
- Added asymptote, pdftricks, pstricks, pst-eps.
- Added breqn, SIunits.
- Added bxpapersize, canoniclayout, draftcopy, fnbreak, nccfancyhdr.
- Added accsupp, axessibility.
- Added xunicode.
- Improved and now supports epstopdf.
- Tested to work as-is: eepic, sepfootnotes.

docs

- Added information about setting up a development version of lwarp.

v0.58: Extensive improvements in indexing, glossaries. Adds PDF-inclusion packages.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- *lwarpmk*: Added the `-p` option to specify the project name.

glossaries

- *lwarpmk*: Now uses *makeglossaries* for glossary generation, allowing the processing of multiple glossaries at once.

- Added lwarp option `GlossaryCmd` to specify the shell command used by **`lwarpmk printglossary`** and **`lwarpmk htmlglossary`**. Defaults to **`makeglossaries`**.

index and glossary

- Docs: Extra indexing options. See section 9.6.13.
- Added support for *makeindex*. (Previously supported only *xindy*.) Also added indexing packages listed below.
- Added lwarp options `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to specify shell commands used by **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, and *latexmk*. May be preset with the `makeindex` or `xindy` lwarp options. See section 8.3.
- Added lwarp options `makeindex` and `xindy` to set `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to sensible values for a typical single index. See section 8.3.
- Added lwarp option `makeindexStyle` to tell *lwarpmk* to use a custom style instead of `lwarp.ist`. See section 9.6.19.
- Fix for index entries with `\see`, `\seealso`, `\emph`, `\textbf`, etc.

misc. fixes

- Replaced each `\csuse` with `\@nameuse` for improved error detection.
- Additional internal print/HTML macro selection improvements.
- Fix: `\printindex` finishes pending `\index` writes first.

packages

- Fixes for memoir: makeidx, ccaption, multiple indexes, `\specialindex`.
- Fixes for komascript: Indexing improvements.
- Added imakeidx, index, repeatindex, splitidx.
- Added attachfile, attachfile2, intopdf, pdfpages, pdfx.
- Added cases.
- Tested to work as-is: notes2bib, hvindex.

v0.57: algorithm2e, float styles, tabular packages, internal improvements.

MathJax

- Added support for MathJax equations with `\footnote`, `\footnotemark`.

math macros

- Added `\StartDefiningMath` and `\StopDefiningMath` for use when defining macros in the preamble which contain $. See section 9.7.7.

dynamic math

- Added `\inlinemathother` and `\inlinemathnormal` to delimit math expressions which depend on a variable condition such as a counter. Such expressions will not be hashed for reuse, and will be converted to SVG math images even when MathJax is enabled. See section 9.7.8.

⚠ new name

- Renamed `\EndDefiningTabulars` to `\StopDefiningTabulars`.

`lateximage alt` tags

- Improved localization for `lateximage` HTML `alt` tags. For SVG math images, the `alt` tag under some conditions will be set to `\mathimagename`, which defaults to "math image". For packages, the `alt` tag is set using the package name followed by `\packagediagramname`, which defaults to "diagram". Ex:

  `(-xy- diagram)`

  See section 8.4.
- Fix: Improved print/HTML macro selection.

misc. fixes

- Fix: `\href` text catcodes.
- Fix: `\subref` text.

- Fixes: Colored `\rule` and `\boxframe`.

packages

- float, rotfloat: Adds support for float styles `ruled` and `boxed`.
- float: Fix: Do not create `\l@<type>` until `\listof` is used.
- marginnote: Fix: Long optional argument.
- ellipsis: Adds `\midwordellipsis`.
- breakurl: Fix for text catcodes.
- Added algorithm2e, register, ltablex, xltabular, xellipsis, trimclip, errata, vowel, xpiano.
- Prevents glossary.
- Tested to work as-is with gauss, phonrule, piano, SIunits, tikzcodeblocks.

v0.56: Shell escape, tabular packages.

lwarpmk

- Added

  ```
  lwarpmk pdftosvg <list-of-PDF-files>
  ```

  to quickly convert a document's PDF images to SVG, for use with HTML. See section 9.8.
- Added support for `--shell-escape`. See section 8.1.

`tabular`

- Added support for array `w` and `W` columns.
- Fix: `\multicolumn` parameter handling.
- Added support for double `\hlines`, `\midrules`, and vertical rules.
- Added support for arydshln dashed lines with HTML `tabular`, but reverts to plain rules for `lateximage` and SVG math `array`.

misc. fixes

- Fix: `\thinspace`.
- Fix: paralist compact environments.

packages

- Added parnotes, quoting, lua-check-hyphen, tocenter, underscore.
- Tested to work as-is with babelbib, bibunits, bodegraph, fast-diagram, nicematrix, structmech.

v0.55: Various fixes.

misc fixes

- Fix: Extraneous space in file links, which also prevented *Calibre* EPUB conversions.
- Fix: Float optional argument regression.
- Fix: `\ForceHTMLTOC` with `\phantomsection`.
- Fix: Overfull boxes in `lateximages`.
- Fix: QED symbols in `lateximage`.

packages

- koma-script: Fix: Figure with `\centering`, etc.
- Added clrdblpg.

v0.54: Float `\centering`, improved image checks.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- `lwarpmk limages` checks for the presence of the HTML version of the document and valid image references before attempting to create the `lateximages`.
- *lwarpmk*: Improved error message if configuration file does not exist.

BibTeX

- Added documentation for avoiding error with BibTeX and `\etalchar`. See section 9.6.9.

polyglossia

- Added documentation regarding polyglossia. See section 9.15.4.

macros in section names

- Added documentation regarding the use of macros in section names. See section 9.1.

document encoding

⚠ New and revised encoding options

- Renamed and added package options:

Old Package Option	New Package Option
`xdyFilename`	`xindyStyle`
`IndexLanguage`	`xindyLanguage`
---	`xindyCodepage`
---	`pdftotextEnc`

  Use these options along with inputenc or inputenx to process documents in an encoding other than UTF-8. See section 8.2.

floats with `\centering`, etc.

- Floats now honor `\centering`, `\raggedright`, `\raggedleft`, and their ragged2e equivalents, when placed directly after:

```
\begin{floattype}
\centering
```

misc. fixes

- tikz: `\pgfpicture`, fit, align, font.
- ragged2e: `\centering` etc.
- hyperref: `\hypertarget` was creating duplicate of `\label`.
- hyperref: Active chars inside `\hyperref`, `\hyperlink`.
- hyperref: `\ref` inside `\hyperlink` caused a nested HTML link.
- glossaries: Fix when not using babel or polyglossia.
- textcomp: `\textperthousand`.
- LaTeX core `verse` environment: line spacing.

⚠ packages

- Removed `\citetitle`, adjusted `\attribution`.
- memoir: Minor update for v3.7g.
- Added inputenx, bibunits, chngpage, forest, magaz, gridset.
- Prevents loading ae, aecc, t1enc, and wasysym.

v0.53: Improved image checks.

lwarpmk

- *lwarpmk*: Added a warning about corrupted images due to the need to recompile the document one more time.
- *lwarpmk*: Added the **`lwarpmk cleanlimages`** command.
- Added documentation for **`lwarpmk cleanlimages`** and **`lwarpmk pdftohtml`**.

v0.52: Improved footnotes, SVG math.

documentation

- Improved install instructions regarding `lwarp_baseline_marker.png`.
- Added documentation regarding footnotes in section headings, and footnotes with `\VerbatimFootnotes` from fancybox, fancyvrb. See section 9.5.4.
- Added documentation regarding font selection when using XƎLaTeX or LuaLaTeX with fontspec and traditional font packages. See section 8.2.

SVG math

- Fix: Limit the number of background tasks when generating `lateximages`.
- Added user-adjustable SVG math font scaling. See section 79.3.
- Added warnings if `lwarp_baseline_marker.png` is not present, or if graphicx or graphics is not loaded.
- Improved `\ensuremath` hashing expansion.
- Fix: `equation*` with `split`.
- `tabbing` now works inside a `lateximage`. Use for math in `tabbing`.

MathJax

- Fix: MathJax script was not executing in some conditions.
- Added `\CustomizeMathJax` to add custom functions. See section 9.7.

footnotes

- Fix: Footnote numbering when using `HTMLDebugComments`.
- Fix: Footnote paragraph tags.
- Fix: `FootnoteDepth` defaults to `\subsubsection`.

misc. fixes

- Fix: `\kill` in a `lateximage`.
- Fix: `\FileDepth`, misc. others, when input encoding is not `utf8`.
- Fix: `\texorpdfstring` in a section name.

packages

- hyperref emulation: Fix for #, %, &, ~, _ characters in URLs.
- fancybox, fancyvrb: Initial support for `\VerbatimFootnotes`.
- nicefrac: Added with fix for `\ensuremath`.
- graphicx: Fix for option defaults. Added v1.1a/b options.
- endfloat: Updated for v2.6.
- url: Fixes for active characters.

v0.51: Improved SVG math, added numerous chemistry packages.

documentation

- Docs: Added Things to avoid.
- Docs: Added to Converting an existing document.
- Docs: Multiple authors and affiliations with custom classes. See section 9.6.1.
- Docs: tikz with matrices. See section 9.8.1.

SVG math

- Improved SVG math baseline.
- Improved SVG math font and color.
- Faster SVG math rendering.
- Improved support for display math containing complicated math objects, such as tikz-cd. See section 9.7.9.
- Fix: `\addcontentsline` inside SVG math.

- Fix: SVG math containing an embedded `lateximage`.

MathJax
- MathJax now handles `\ensuremath` in expressions.

misc. fixes
- Fix: Added `alignat` environment.
- Fix: afterpackage no longer required, which conflicted with scrlfile.
- Fix: titling `\thanks` mark.
- Fix: fancybox improvements.
- Fix: tikz `\tikz` macro. (Previously only the `tikzpicture` environment worked.)
- Fix: tikz with optional argument.

packages
- Added mhchem, chemfig, chemformula, chemmacros, chemnum, chemgreek, epstopdf-base, grid, ltxgrid.

v0.50: Improved SVG math.

SVG math
- SVG math and other `lateximages` now are converted to SVG using parallel background tasks, utilizing all available CPU cores.
- Inline SVG math image file names now are MD5 hashes made from their source LaTeX code. Identical inline math expressions, such as multiple instance of x, now share a single image file. This reduces the number of images to store, transmit, process, and display. Each image file is only converted to SVG a single time, and reused if it already exists. Display math and other forms of SVG image such as `picture` and Ti*k*z still use individual image files which are recreated each time **`lwarpmk limages`** is run.
- Fixes: SVG math and/or `\underline` in a sectioning file name.
- Improved SVG display math and tags.
- Improved SVG math and siunitx `alt` tags.
- Improved siunitx units.
- Fix: `\ensuremath` with MathJax now creates a `lateximage`.
- Fix: `\centering`, etc. in SVG math, `lateximage`, Ti*k*z.

misc. fixes
- Fix: Made various macros robust, additionally fixing authblk.
- Fix: ntheorem if neither `standard` nor `amsthm` selected.
- Fix: listings: Improved column alignment.
- Fix: Load fontspec if necessary.

packages
- Added xy, epstopdf, diagbox, pbox, bytefield, axodraw2, phfqit, schemata, dblfloatfix, nonfloat, morefloats.

v0.49:

tabular
- Added xcolor `\rowcolors`.
- Fix: `\noalign` inside a `tabular`.

math
- Fix: `\eqref` in a caption.

misc fixes
- Fix: Incorrect PDF font size changes caused occasional HTML corruption.
- Fix: printlen changes are now grouped for HTML output.

packages
- Added vwcol, vertbars, hyphenat, lineno, fnlineno, figsize, hypdestopt, pagegrid, pdfrender, luacolor, resizegather.

v0.48:

documentation
- Added some documentation regarding converting an existing document. See section 7.

cleveref
- Updated compatibility for new cleveref v0.21.

tabular
- Fix: Ignores optional tabular column arguments.

minor updates
- Added `\leftline`, `\centerline`, `\rightline`.
- Lists have improved font control via `\makelabel`.
- Print-mode `lateximage` now boxed to the natural width of its multiline contents.
- `abstract` now allows an optional name, as required by some classes.

math
- Fix: Improved spacing, `\mbox`, and font sizes with SVG math, Ti*k*z.
- siunitx: Improved SVG math, fraction compatibility, color output.

misc. fixes
- Fix: LOF/LOT links.
- Fix: Virtual page size grouping caused excessive PDF page breaks.
- Fix: Parsing similar package names in a single `\usepackage`.
- Fix: Adapts to classes without `\part`.
- Fix: `\newline` in `\title` was causing `<br>` in window title.
- Fix: `\maketitle` with `\cr`, `\crcr`, `\noalign`, for IEEEtran class.
- Fix: xfrac neutralized `BlockClass` and others.
- Fix: todonotes and luatodonotes: Improved `\todototoc`.

packages
- Added colortbl, chapterbib, acro, acronym, hypernat, hypcap, stfloats, vmargin, fancyheadings.
- fancyref: Now directly supported.

v0.47:

math
- Improved SVG math baseline and sizing.
- Fixes: SVGmath in captions, subcaptions, `\nameref`.
- Fixes: Line wrap at hyphen in HTML output.

packages
- Added endheads, multitoc, sectionbreak, blowup, xurl.

v0.46:

⚠ name change
- `\PrintStack` changed to `\LWRPrintStack`.

misc. fixes
- Fix: Empty lines between `tabular` rows.
- Fix: Stack unnesting.
- Fix: SVG math and `lateximages` in numerous situations.
- Fix: Spaces in `\usepackage`.
- Fix: Now allows MathJax inside `verse`.

v0.45:

documentation
- Improved *MiKTeX* install instructions.
- Improved graphics and epstopdf instructions.
- Updates to the Introduction.

memoir
- Added memoir, memhfixc. See section 9.13.

cross-references
- Fix: Now allows underscores in labels.
- Fix: _ and \<blank> in section/file names.

math
- Fix: Now allows MathJax inside tabbing.

bibliography
- Fix: Bibliography \em names.
- Added cite, natbib, backref. (Also works as-is with biblatex.)

misc. fixes
- Fix: Empty lines between tabular rows.
- Fix: "Improper \prevdepth" with minipages, lists.
- Fix: Incorrect SVG math and lateximages with subfig.
- Fix: Lateximages from incorrect pages with Mathjax.
- Fix: Missing sidetoc if using listings.
- Fix: Added an array emulation package.

packages
- Added subfigure, prettyref, hanging, midpage, flafter, fltrace, changebar, endfloat, continue, fwlw, turnthepage, footnpag, pagesel, textfit, titleref.

v0.44:

koma-script
- Added koma-script classes (except scrlttr2, scrjura).
- Added scrextend, scrlayer, scrlayer-notecolumn, scrlayer-scrpage, scrhack, tocstyle, tocbasic.

HTML title and author
- Added \HTMLTitle. Fixed web page title if \HTMLTitle empty and no \title given and not using titling package.
- Fixed web page author if \HTMLauthor is empty and \author is not given.

encodings
- If using *pdflatex*, automatically loads T1 and UTF-8 encodings. (Additional fontenc encodings may be loaded after lwarp.)

lists
- Added list and trivlist environments, hang.

tabular
- Fix: \multicolumn alignment if formatting for a word processor.
- Added ltxtable.

math
- Fix: MathJax combined with lateximages.
- algorithmicx: Improved comment symbol and floating.

packages
- Completed todonotes and luatodonotes.
- Added todo, easy-todo, fixmetodonotes, fixme.
- Added soulutf8, soulpos, cancel.
- Added section, fancyref, ifoddpage.
- Added preview, atbegshi, watermark.
- Improved tocloft \newlistof and \newlistentry.

v0.43:

- Docs: Reorganized HTML customization, added an HTML settings table. See section 8.4.

footnotes
- Added `FootnoteDepth` to control the placement of pending footnotes before section breaks. By default, pending footnotes are printed before each `\subparagraph` or higher.

sectioning
- Fix: Expansion in section name.

tabular
- Fix: Ignore spaces in tabular column specification.
- Fix: Tabular rules at bottom or when finishing incomplete rows.
- Fix: `\multicolumn` at/bang/before/after specifications, trim, and vertical rules.
- Fix: supertabular and xtab column misalignment.

math
- Fix: `equation*`.
- Fix: SVG math in a section name.
- Fix: `\ref` and `\eqref` in SVG math.

packages
- Added todonotes and luatodonotes (but only `disabled`).
- Added breakurl.
- hyperref: Fix: Several macros were made robust, `\Gauge` added.

v0.42:

Support TEX!
- Added TEX development support page, Support TEX development.

word-processor conversion
- Improved assitance for word-processor conversions when boolean `FormatWP` is set `true`. See section 12.

⚠ name change
  - The boolean `FormatWordProcessor` has been renamed `FormatWP`.

⚠ name change
  - The boolean `HTMLMarkFloats` has been renamed `WPMarkFloats`.
  - New booleans control whether to place additional marks around minipages, at the table of contents, at the LOF and LOT, and whether to print math as LATEX source for copy/paste into the *LibreOffice Writer TeXMaths* extension.
  - Improved formatting for numerous objects. See section 12.

tabbing
- Add: `tabbing` environment.

overpic
- Add: overpic package. See section 345.

math
- Fix: Text copy/paste of $\mathcal{AMS}$ math environment numbers and names.
- Improved `\ensuremath`.
- MATHJAX with siunitx: Updated script and documentation.

symbols
- textcomp: Improved `\interrobangdown`.
- realscripts: Fix for subscripts in a `lateximage`.

load order
- morewrites: Enforces loading before lwarp.

v0.41:

tabular

- Added tabular vertical rules, subject to some limitations. See the rules section of section 9.10.1.
- Improved booktabs: Width and trim are honored.

⚠ new syntax

- Added \mcolrowcell for empty cells inside a \multicolumnrow. Use \mcolrowcell instead of \mrowcell for two-dimensional cells created by \multicolumnrow. Continue to use \mrowcell for empty cells in a \multirow. See section 325.2 on page 813.
- Fix: Unfinished tabular rows are automatically filled.
- Fix for tabular column specifiers while using babel-french. (\NoAutoSpacing is activated then nullified inside the tabular, due to a conflict with the tabular column parsing code.)

v0.40:

graphics, graphicx

- graphics and graphicx have been moved from the lwarp core, and are only loaded if requested with \usepackage.

\includegraphics path

⚠ image file extensions

- Improved graphics \graphicspath support. Multiple image directories may now be used. Refer to .pdf files without a file extension to allow the HTML version to use a .svg, .png, .jpg, or .gif version instead. See section 9.8.
- grffile is now directly supported instead of emulated.

bigdelim

- Fix for bigdelim, and improved documentation. See section 136.

symbols

- Improved LaTeX and textcomp symbols.

fixes

- Fix for LaTeX logos and \InlineClass, etc. inside a lateximage.
- Fix for xltxtra with XeLaTeX.
- Fixes for tocbibind with \simplechapter, etc.
- Fixes for \multicolumnrow and \nullfonts with older versions of multirow and xparse.
- Added \underline.

margins

- Added adjmulticol.

columns

- Added cuted, midfloat.

footnotes

- Added pfnote, fnpos, dblfnote.

tabular

- Added stabular, tabls.

sectioning

- Added sectsty, anonchap, quotchap.

v0.39:

title pages

- Improved the titlepage HTML code, \thanks notes, and \maketitle. titling is no longer required, but is still supported. The \published and \subtitle fields are no longer provided, but \AddSubtitlePublished replicates them using titling. See section 65.8. authblk is added, and should be loaded before titling. See section 65.

⚠ \published and \subtitle

⚠ load order

tabular

- \multirow now supports the new optional vpos argument.

multi column/row cell

- Added \multicolumnrow for combined \multicolumn and \multirow. See section 325.2.

- Tabular special cases:
  - Added `\TabularMacro` to mark custom macros inside tabular data cells, avoiding row corruption. See section 9.10.1.
  - Added `\ResumeTabular` for use when a `tabular` environment is defined inside another environment. See section 9.10.1.

⚠ macros inside tabular

⚠ tabular defined inside another environment

tabular
- Added supertabular, xtab, bigstrut, bigdelim.

margins
- Added fullwidth.

page layout
- Added addlines, anysize, a4, a4wide, a5comb, textarea, zwpagelayout, typearea, ebook.

v0.38:

forced single-pass compile
- Added **`lwarpmk print1`** and **`lwarpmk html1`** actions to force a compile of the project a single time. Useful when multiple passes are not needed, or changes were not detected.

starred sections
- Added `\ForceHTMLPage` and `\ForceHTMLTOC` to force a starred sectional unit onto its own HTML page and with its own TOC entry. See section 9.6.2.

updated tutorial
- Modified the tutorial to use the new `\ForceHTMLPage` and `\ForceHTMLTOC` macros.

packages
- Added appendix, tocbibind, fncychap, fix2col.

font size
- Added relsize, scalefnt.
- Added realscripts, metalogo, xltxtra.
- Added grffile, romanbar.

page numbering
- Added arabicfront, chappg, nonumonpart, nopageno, romanbarpagenumber.

front & back matter
- Docs: Improved description of the use of front/back matter. See section 9.6.
- Fix: color requests xcolor.
- Fix: `\part` for article class.

v0.37:

`\include` for HTML
- `\include` now maintains independent `.aux` files for HTML versions.

latexmk
- comment, used by lwarp, now maintains independent cut files for print and HTML versions, helping *latexmk* to better know whether to recompile.

accents and symbols
- Improved support for LaTeX accents, textcomp, siunitx symbols.

babel-french
- Improved babel-french handling for load order and ~ tilde.

v0.36:

- Recorganized the documentation section regarding special cases and limitations. (Section 9)
- Improved source formatting.

boxes and frames
- `\fbox` and related now use `\fboxsep` and `\fboxrule`.
- `\makebox` and `\framebox` now use width and position.
- `\fcolorbox` and related now work inside a `lateximage`.

babel-french
- babel-french: Improvements for French variants, load order, footnotes, ellipses.

footnotes

- Improved footnote numbering. `lateximage` footnotes now appear as regular footnotes to match the numbering of the print version. Also fixed a regression with MathJax.

siunitx

- Improved siunitx units.
- Fix for filenames while using MathJax.
- Fix for `\rule` when xcolor is not loaded.
- Added transparent, upref.

v0.35: Fix: `\textbf` and related.

v0.34:

⚠ Optional arguments

- `BlockClass`'s optional argument has been moved in front of the mandatory argument:

  `BlockClass[style]{class}` (NEW)

  instead of:

  `BlockClass{class}[style]` (OLD)

  This change makes it more consistent with LaTeX standards, and avoids problems with space between arguments.

⚠ Optional arguments

- Likewise, `\InlineClass`'s optional argument now comes before the mandatory arguments:

  `\InlineClass[style]{class}{text}`

spans with minipages

- Improved compatibility between spans, minipages, lists, frames, and math. Handles minipages and lists inside an HTML span, such as an `\fbox` containing a minipage, although with minimal HTML fomatting. See section 9.3.3.

framing minipages

- `\fboxBlock` is added to frame minipages, tables, and lists with full HTML formatting but no longer inline, and behaves as `\fbox` for print output. The `fminipage` environment is added for framed minipages, as an environment with full HTML formatting, and draws a framed minipage in print output. See section 9.3.5. `\fbox` and minipages now often work in SVG math and `lateximages`. MathJax supports `\fbox`, but not `\fboxBlock` nor `fminipage`.

`lateximage`, SVG math, `tabular`

- Improved compatibility between `lateximage` and `minipage`, `\parbox`, `\makebox`, `\fbox`, `\framebox`, `\raisebox`, `\scalebox`, `\reflectbox`, `tabular`, booktabs.
- Improved font control for `lateximagees` and SVG math.

`eqnarray`

- Added the `eqnarray` environments.

verbatim packages

- fancyvrb is no longer required (preloaded), but is still supported.
- Added verbatim and moreverb.

framing packages

- Added fancybox, boxedminipage2e and shadow.

list packages

- enumitem is no longer required, but is still supported.
- Added enumerate and paralist.
- titleps is no longer required, but is still supported.
- Added crop.
- Added rotfloat, marginfit, and several minor packages; see the change log.

babel-french

- Adds fixed-width HTML spaces around punctuation when using babel-french. LuaTeX does not yet use the extra punctuation spacing.

v0.33:

- Tabular `@` and `!` columns now havetheir own HTML columns.
- `&` catcode changes are localized, perhaps causing errors about the tab alignment character `&`, so any definitions of macros or environments which themselves contain `tabular` and `&` must be enclosed within `\StartDefiningTabulars` and `\StopDefiningTabulars` (previously called `\EndDefiningTabulars`. See section 43. This change is not required for the routine use of tables, but only when a table is defined inside another macro or environment, and while also using the `&` character inside the definition. This may include the use inside conditional expressions.
- Several math environments were incorrectly placed inline. Also, for amsmath with SVG math, the `fleqn` option has been removed, resulting in improved spacing for aligned equations.
- Bug fixes; see the changelog.

v0.32: Bug fixes; no source changes needed:

- *lwarpmk* has been adjusted to work with the latest *luatex*.
- Spaces in the `\usepackage` and `\RequirePackage` package lists are now accepted and ignored.
- Fix for the glossaries package and `\glo@name`.

v0.31: Bug fix; no source changes needed:

- Improved compatibility with keyfloat, including the new `keywrap` environment.

v0.30:

⚠ lwarp-newproject

- lwarp-newproject has been removed, and its functions have been combined with lwarp.

  To modify existing documents, remove from the document source:

  ```
  \usepackage{lwarp-newproject}
  ```

  The lwarp package now produces the configuration files during print output, and also accepts the option `lwarpmk` if desired.

⚠ HTML setup changes.

- A number of macros related to HTML settings have been converted to options, and other macros and options have been renamed to create a consistent syntax:

Old Macro	New Package Option
\HomeHTMLFileName	HomeHTMLFilename
\HTMLFileName	HTMLFilename
\useLatexmk	latexmk
\warpOSwindows	OSWindows

Old Package Option	New Package Option
lwarpmklang	xindyLanguage
(new)	xindyStyle

Old Macro	New Macro
\MetaLanguage	\HTMLLanguage
\HTMLauthor	\HTMLAuthor
\NewHTMLdescription	\HTMLDescription
\SetFirstPageTop	\HTMLFirstPageTop
\SetPageTop	\HTMLPageTop
\SetPageBottom	\HTMLPageBottom
\NewCSS	\CSSFilename

- Per the above changes, in existing documents, modify the package load of lwarp, such as:

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={},
    xindyLanguage=english
]{lwarp}
```

- The file lwarp_html.xdy has been renamed lwarp.xdy. To update each document's project:
  1. Make the changes shown above.
  2. Recompile the document in print mode. This updates the project's configuration files, and also generates the new file lwarp.xdy.
  3. The old file lwarp_html.xdy may be deleted.
- The new lwarp package option xindyStyle may be used to tell *lwarpmk* to use a custom .xdy file instead of lwarp.xdy. See section 9.6.20.
- Improvements in index processing:
  - *xindy*'s language is now used for index processing as well as glossary.
  - Print mode without *latexmk* now uses *xindy* instead of *makeindex*.
  - *texindy*/*xindy* usage depends on *pdflatex* vs *xelatex*, *lualatex*.
  - For *pdflatex* and *texindy*, the -C utf8 option is used. This is supported in modern distributions, but a customized lwarpmk.lua may need to be created for use with older distributions.

v0.29:

- Add: lwarpmklang option for lwarp-newproject and lwarp. Sets the language to use while processing the glossary. (As of v0.30, this has been changed to the IndexLanguage option.) (As of v0.54, this has been changed to the xindyLanguage option.)

- Fix: `\includegraphics` when no optional arguments.

v0.28:

- `\HTMLAuthor` {⟨*name*⟩} assigns HTML meta author if non-empty. Defaults to `\theauthor`.
- Booean `HTMLDebugComments` controls whether HTML comments are added for closing `<div>`s, opening and closing sections, etc.
- Boolean `FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.
- Boolean `FormatWordProcessor` changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Name changed to `FormatWP` as of v0.42.
- Boolean `HTMLMarkFloats` adds text marks around floats only if the boolean `FormatWordProcessor` is `true`. These make it easier to identify float boundaries, which are to be manually converted to word-processor frames. Name changed to `WPMarkFloats` as of v0.42.
- Updated for the new MathJax CDN repository.
- Adds tabulary.
- Supports the options syntax for graphics.
- Improved index references, now pointing exactly to their target.
- Adds glossaries. *lwarpmk* is modified to add `printglosssary` and `htmlglossary` actions.

3 Introduction

The lwarp project aims to allow a rich LaTeX document to be converted to a reasonable HTML5 interpretation, with only minor intervention on the user's part. No attempt has been made to force LaTeX to provide for every HTML-related possibility, and HTML cannot exactly render every possible LaTeX concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the HTML conversion.

Several "modern" features of HTML5, CSS3, and SVG are employed to allow a fairly feature-rich document without relying on the use of JAVASCRIPT. Limited testing on older browsers shows that these new features degrade gracefully.

---

lwarp is a native LaTeX package, and operates by either patching or emulating various functions. Source-level compatibility is a major goal, but occasional user intervention is required in certain cases.

As a package running directly in LaTeX, lwarp has some advantages over other methods of HTML conversion. TeX itself is still used, allowing a wider range of TeX trickery to be understood. Lua expressions are still available with LuaTeX. Entire categories of LaTeX packages work as-is when used with lwarp: definitions, file handling, utilities, internal data structures and calculations, specialized math-mode typesetting for various fields of science and engineering, and anything generating plain-text output. Blocks of PDF output may be automatically converted to SVG images while using the same font and spacing as the original print document, directly supporting Ti*k*z and `picture`. Numerous packages are easily adapted for HTML versions, either by loading and patching the originals, or by creating nullified or emulated replacements, and all without resorting to external programming. As a result, several hundred packages have already been adapted (table 2), and an uncounted number more work as-is.

Packages have been selected according to several criteria: perceived importance, popularity lists, recent CTAN updates, CTAN topics, mention in other packages, support by other HTML conversion methods, and from sample documents taken from public archives. These include some "obsolete" packages as well.[1]

Assistance is also provided for modifying the HTML output to suit the creation of EPUB documents, and for modifying the HTML output to ease import into a word processor.

---

pdflatex, *xelatex*, or *lualatex* may be used, allowing lwarp to process the usual image formats. While generating HTML output, SVG files are used in place of PDF. Other formats such as PNG and JPG are used as-is.

[1] An amazing number of decades-old packages are still in use today.

SVG images may be used for math, and are also used for `picture`, Ti*k*z, and similar environments. The SVG format has better browser and e-book support than MathML (as of this writing), while still allowing for high-quality display and printing of images (again, subject to potentially bug-ridden[2] browser support).

Furthermore, SVG images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by `<alt>` tags holding the LaTeX source for the expression, allowing it to be copy/pasted into other documents.[3] Custom LaTeX macros may be used as-is in math expressions, since the math is evaluated entirely inside LaTeX. An MD5 hash is used to combine multiple instances of the same inline math expression into a single image file, which then needs to be converted to SVG only a single time.

The MathJax JavaScript display engine may be selected for math display instead of using SVG images. Subject to browser support and Internet access, MathJax allows an HTML page to display math without relying on a large number of external image files.[4] lwarp maintains LaTeX control for cross-referencing and equation numbering, and attempts to force MathJax to tag equations accordingly.

A *texlua* program called *lwarpmk* is used to process either the print or HTML version of the document. A few external utility programs are used to finish the conversion from a LaTeX-generated PDF file which happens to have HTML5 tags, to a number of HTML5 plain-text files and accompanying images.

lwarp automatically generates the extra files necessary for the HTML conversion, such as CSS and `.xdy` files, and configuration files for the utility *lwarpmk*. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects HTML output and then inputs the user's own source. This process allows both the printed and HTML versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during HTML conversion, lwarp first looks to see if it has its own modified version to use instead of the standard LaTeX version. These `lwarp-packagename.sty` files contain code used to emulate or replace functions for HTML output.

[2] Firefox has had an on-again/off-again bug for quite some time regareding printing SVGs at high resolution.

[3] There seems to be some debate as to whether MathML is actually an improvement over LaTeX for sharing math. The author has no particular opinion on the matter, except to say that in this case LaTeX is much easier to implement!

[4] One SVG image file per math expression, except that duplicate inline math expressions are combined into a single file according to the MD5 hash function of its contents. A common scientific paper can easily include several thousand files, and in one case the MD5 hash cut the number of files in half and the rendering time by 30%.

3.1 Typesetting conventions

Font weight, family, and style are used to indicate various objects:

Table 1: Typesetting conventions

package	LaTeX package.
program	Program's executable name.
`option`	Program or package option.
`filename`	File name in the operating system.
Brand Name	Proper name for a program, operating system, etc.
`commands`	Commands to be entered by the user.
`code`	Program code.
`\macroname`	LaTeX macro.
`environment`	LaTeX environment.
`counter`	LaTeX counter.
`boolean`	LaTeX boolean.
`<element>`	HTML element.
`attribute`	HTML attribute.
User Interface	A user-interface item.
ACRO	Acronym.

3.2 Supported packages and features

Table 2 lists some of the various LaTeX features and packages which may be used. Many are tested to work as-is, some are patches for the original packages, and some are emulations written for source-level compatibility. Many are nullified as being irrelevent to HTML output.

Table 2: LaTeX lwarp package — Supported features

Category	Status and supported features.
Engines:	DVI LaTeX, pdfLaTeX, XeLaTeX, LuaLaTeX, upLaTeX
Compiling:	latexmk, perltex, pythontex, *make*, etc.
Classes:	article, book, report, scrartcl, scrbook, scrreprt, memoir, CJK-related as listed below.
Koma-script:	scrextend, scrhack, scrlayer. Others as listed below.
Memoir:	memhfixc
Languages:	babel, polyglossia. cjkpunct, xeCJK.
Chinese:	CTeX, ctex, upzhkinsoku, xpinyin, zhlineskip, zhspacing.
Japanese:	upLaTeX, LuaTeX-ja, gentombow, lltjext, plarray, plarydshln, plautopatch, plext, plextarray, plextarydshln, plextcolortbl, plextdelarray, pxatbegshi, pxeveryshi, pxftnright, pxgentombow, pxjahyper, pxpdfpages, pxpgfrcs, pxpgfmark, tascmac, zxjatype. bxjsarticle and related, ltjsarticle and related, luatexja, luatexja-fontspec, ujarticle and related, utarticle and related.
Korean:	kotex, luatexko, xetexko.

lwarp Supported Functions — continued

Category	Status
Page layout:	2in1, 2up, a4, a4wide, a5comb, addlines, anysize, atbegshi, blowup, booklet, bophook, bounddvi, bxpapersize, canoniclayout, changepage, chngpage, clrdblpg, continue, draftcopy, draftfigure, draftwatermark, ebook, everyshi, fancyhdr, fancytabs, flippdf, fullminipage, fullpage, fwlw, geometry, gmeometric, grid, grid-system, gridset, layaureo, layout, layouts, leading, ltxgrid, nccfancyhdr, notespages, nowidow, pagegrid, pdfprivacy, pagesel, preview, rmpage, scrlayer-scrpage, scrpage2, textarea, threadcol, thumb, thumbs, titleps, tocenter, turnthepage, twoup, typearea, vmargin, watermark, widows-and-orphans, zwpagelayout. Tested to work as-is: underlin.
Sectioning:	Adds `FileDepth` for splitting the HTML output. Files may be numbered sequentially or named according to section name. Common short words and punctuation are removed from the filenames. anonchap, bsheaders, fncychap, indentfirst, quotchap, section, sectionbreak, sectsty, titlesec. Tested to work as-is: secdot.
Table of contents, figures, tables:	Supported, with hyperlinks. minitoc, multitoc, shorttoc, titletoc, tocbasic, tocbibind, tocdata, tocloft, tocstyle.
Title page:	`\maketitle`, `titlepage`, authblk, titling.
Front & back matter:	abstract, appendix.
Indexing:	*makeindex* and *xindy* are supported, with hyperlinks. idxlayout, imakeidx, index, makeidx, repeatindex, splitidx. Tested to work as-is: hvindex.
Glossary:	gloss, glossaries and *xindy*, nomencl.
Bibliography:	babelbib, backref, biblatex, bibunits, chapterbib, cite, hypernat, natbib, showtags. Tested to work as-is: notes2bib.
Cross-references:	bookmark, breakurl, cleveref, fancyref, hypdestopt, hyperref, perpage, prettyref, titleref, url, varioref, xr, xr-hyper, xurl.
Margin notes:	marginal, marginfit, marginfix, scrlayer-notecolumn, versonotes.

lwarp Supported Functions — continued

Category	Status
Footnotes:	Adds `FootnoteDepth` to print footnotes at section breaks. bigfoot, dblfnote, endheads, endnotes, fnbreak, fnpara, fnpos, footmisc, footnote, footnotebackref, footnoterange, footnpag, manyfoot, marginnote, pagenote, parnotes, pfnote, sidenote, tablefootnote. Tested to work as-is: fixfoot, nccfoots, sepfootnotes.
Math:	Converted to SVG images with HTML `<alt>` tags containing the LaTeX source for the math expression. MathJax supported as an alternative. amsmath: $\mathcal{AMS}$ environments are supported. User-defined macros are available during converson, due to native LaTeX processing.
Theorems:	Native LaTeX theorems, amsthm, ntheorem, theorem.
Additional math:	Math fonts via SVG images, breqn, cases, resizegather, xfakebold, xy. Tested to work as-is: amscd, bm, braket, delarray, guass, nicematrix, pb-diagram, tikz-cd, etc.
Display math with `\displaymathother`:	Complicated math objects in display math, such as tikz-cd, etc.
Units and fractions:	nicefrac, SIunits, siunitx, units, unitsdef, xfrac. Tested to work as-is: SIunits.
Floats:	Appear where declared. capt-of, caption, cutwin, dblfloatfix, endfloat, fix2col, flafter, float, floatflt, floatrow, fltrace, ftcap, hypcap, keyfloat, morefloats, multicap, newfloat, nonfloat, placeins, rotfloat, stfloats, subcaption, subfig, subfigure, subfloat, topcapt, trivfloat, wrapfig.
Tabular:	`tabular` environment, array, arydshln, bigdelim, booktabs, colortbl, ctable, diagbox, longtable, ltablex, ltxtable, multirow, supertabular, tabularx, tabulary, threeparttable, threeparttablex, xltabular, xtab.

lwarp Supported Functions — continued

Category	Status
Graphics:	graphics and graphicx. `\includegraphics` supports `width`, `height`, `origin`, `angle`, and `scale` tags, and adds `class`. References to PDF files are changed to SVG, other image types are accepted as well. `\rotatebox` and `\scalebox` are supported as well as HTML can handle. rotating is emulated but all objects are unrotated. picture, tikz, and xy are converted to an SVG image. asymptote, epsfig, epstopdf, figsize, fitbox, grffile, overpic, psfrag, psfragx, pst-eps, pstool, pstricks, rviewport. Tested to work as-is: curves, eepic, tikz-3dplot.
xcolor:	Full package color names, any color models, and mixing. `\textcolor`, `\colorbox`, `\fcolorbox`. Enhanced for HTML compatibility.
Lists:	Standard LaTeX environments, enumerate, enumitem, eqlist, hang, listliketab, paralist.
Environments:	Standard LaTeX environments.
`minipage`, `\parbox`:	Some HTML5-imposed limitations. Nested minipages are supported. eqparbox, pbox.
Quotations:	copyrightbox, csquotes, epigraph, quoting, verse.
Verbatim:	fancyvrb, moreverb, shortvrb, verbatim.
Frames:	boxedminipage2e, fancybox, framed, mdframed, niceframe, shadow, vertbars.
Multi-columns:	adjmulticol, multicol, multicolrule, vwcol.
Margins:	fullwidth, hanging, midpage.
Line numbering:	fnlineno, lineno.
Direct formatting:	`\emph`, `\textsuperscript`, `\textbf`, etc are supported. `\bfseries`, etc. are only supported in some cases. cancel, ellipsis, embrac, enparen, hyphenat, lettrine, lips, lua-check-hyphen, luacolor, magaz, pdfrender, realscripts, relsize, scalefnt, soul, soulpos, soulutf8, textfit, thinsp, trimclip, truncate, ulem, umoline, underscore, uspace, xellipsis.
Acronyms:	acro, acronym.
Ordinals:	engord, fmtcount, nth.

lwarp Supported Functions — continued

Category	Status
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for thin-unbreakable, unbreakable, `\enskip`, `\quad`, `\qquad`, `\hspace`.
Rules:	`\rule` with width, height, raise, text color.
HTML reserved characters:	`\&`, `\textless`, and `\textgreater` are converted to HTML entities.
Fonts:	Used as-is. Appear in SVG math expressions or embedded image environments.
Symbols:	Native LaTeX diacriticals, academicons, bbding, chemgreek, dingbat, eurosym, fontawesome, fontawesome5, marvosym, pifont, textalpha, textcomp, textgreek, typicons, xunicode. Tested to work as-is: euro, gensymb.
Files:	attachfile, attachfile2, hyperxmp, intopdf, pdfpages, pdfx, xmpincl.
Science and engineering:	algorithm2e, algorithmicx, ar, axodraw2, bitpattern, bytefield, chemfig, chemformula, chemgreek, chemmacros, chemnum, karnaugh-map, listings, mhchem, phfqit, register, struktex. Tested to work as-is: askmaps, blochsphere, bodegraph, bohr, circuitikz, elements, engtlc, fast-diagram, hepnicenames, heppennames, karnaughmap, linop, pgfgantt, physics, simpler-wick, slashed, structmech, tikz-karnaugh, tikzcodeblocks.
Arts and humanities:	foreign, forest, musicography, nameauth, octave, schemata, semantic-markup, vowel, xpiano. Tested to work as-is: phonrule, piano, tikz-dependency.
Admonitions:	notes.
Editorial:	changebar, changes, easy-todo, ed, errata, fixme, fixmetodonotes, pdfcomment, pdfmarginpar, todo, todonotes, tram, xechangebar. Tested to work as-is: changelog, easyReview.

lwarp Supported Functions — continued

Category	Status
Accessibility:	accsupp, axessibility.
Debug:	chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.
Working as-is:	Various utility, calculation, file, and text-only packages, such as calc, fileerr, somedefs, trace, xspace. Also, most math-only packages, including specialized typesetting for various fields of science and engineering.

4 Alternatives

Summarized below are several other ways to convert a LaTeX or other document to HTML. Where an existing LaTeX document is to be converted to HTML, lwarp may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

4.1 internet class

Cls internet The closest to lwarp in design principle is the `internet` class by Andrew Stacey — an interesting project which directly produces several versions of markdown, and also HTML and EPUB. https://github.com/loopspace/latex-to-internet

4.2 TeX4ht

Prog TeX4ht http://tug.org/tex4ht/

Prog htlatex

This system uses native LaTeX processing to produce a DVI file containing special commands, and then uses additional post-processing for the HTML conversion by way of numerous configuration files. In some cases lwarp provides a better HTML conversion, and it supports a different set of packages. TeX4ht produces several other forms of output beyond HTML, including ODT and a direct path to EPUB, and is still being developed.

4.3 Translators

These systems use external programs to translate a subset of LaTeX syntax into HTML. Search for each on CTAN (http:\ctan.org).

Prog Hevea **HEvEa:** http://hevea.inria.fr/ (not on CTAN)

Prog TtH **TtH:** http://hutchinson.belmont.ma.us/tth/

Prog GELLMU **GELLMU:** http://www.albany.edu/~hammond/gellmu/

Prog LaTeXML **LaTeXML:** http://dlmf.nist.gov/LaTeXML/

Prog Plastex **PlasTeX:** https://github.com/tiarno/plastex

Prog LaTeX2HTML **LaTeX2HTML:** http://www.latex2html.org/ and http://ctan.org/pkg/latex2html.

Prog TeX2page **TeX2page:** http://ds26gte.github.io/tex2page/index.html

Finally, GladTeX may used to directly insert LaTeX math into HTML:

Prog GladTeX **GladTeX:** http://humenda.github.io/GladTeX/

4.4 AsciiDoc and Asciidoctor

AsciiDoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes LaTeX and HTML.

Prog AsciiDoc **Asciidoctor:** http://asciidoctor.org/ (More active.)

Prog AsciiDoctor **AsciiDoc:** http://asciidoc.org/ (The original project.)

4.4.1 Asciidoctor-LaTeX

The Asciidoctor-LaTeX project is developing additional LaTeX-related features.

Asciidoctor-LateX:
http://www.noteshare.io/book/asciidoctor-latex-manual
Prog Asciidoctor-LaTeX https://github.com/asciidoctor/asciidoctor-latex

4.5 Pandoc

Prog Pandoc A markup system which also reads and writes LaTeX and HTML.

Pandoc: http://pandoc.org/

(Watch for improvements in cross-references to figures and tables.)

4.6 Word processors

Prog Word
Prog LibreOffice
Prog OpenOffice

It should be noted that the popular word processors have advanced through the years in their abilities to represent math with a LaTeX-ish input syntax, unicode math fonts, and high-quality output, and also generate HTML with varying success. See recent developments in Microsoft® *Word*® and LibreOffice™ *Writer*.

4.7 Commercial systems

Prog Adobe
Prog FrameMaker
Prog InDesign
Prog Flare
Prog Madcap

Likewise, several professional systems exist whose abilities have been advancing in the areas of typesetting, cross-referencing, and HTML generation. See Adobe® *FrameMaker*®, Adobe *InDesign*®, and Madcap *Flare*™.

4.8 Comparisons

AsciiDoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to

require many combinations of special characters, resulting in a complicated mess of syntax. By contrast, LaTeX spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that LaTeX is comparably easy to learn, while LaTeX provides many more advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of LaTeX vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a LaTeX back end, yielding high-quality results especially when the LaTeX template is adjusted, but they lose the ability to use LaTeX macros and other LaTeX source-document features.

The effort required to customize the output of each markup system varies. For print output, LaTeX configuration files are usually used. For HTML output, a CSS file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of lwarp, CSS is used, and much HTML output is adjusted through the usual LaTeX optional macro parameters, but further customization may require patching LaTeX code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

5 Installation

Table 3 shows the tools which are used for the LaTeX to HTML conversion. In most cases, these will be available via the standard package-installation tools.

Detailed installation instructions follow.

Table 3: Required software programs

Provided by your LaTeX distribution:

From TeXLive: http://tug.org/texlive/.

LaTeX: *pdflatex*, *xelatex*, or *lualatex*.

The lwarp package: This package.

The *lwarpmk* utility: Provided along with this package. This should be an operating-system executable in the same way that *pdflatex* or *latexmk* is. It is possible to have the lwarp package generate a local copy of *lwarpmk* called `lwarpmk.lua`. See table 4.

***luatex*:** Used by the *lwarpmk* program to simplify and automate document generation.

***xindy*:** The *xindy* program is used by lwarp to create indexes. On a MiKTeX system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

***latexmk*:** Optionally used by *lwarpmk* to compile LaTeX code. On a MiKTeX system, *Perl* may need to be installed first.

***pdfcrop*:** Used to pull images out of the LaTeX PDF.

Poppler PDF utilities:

***pdftotext*:** Used to convert PDF to text.

***pdfseparate*:** Used to pull images out of the LaTeX PDF.

***pdftocairo*:** Used to convert images to SVG.

These might be provided by your operating-system package manager, and MiKTeX provides miktex-poppler-bin-* packages.

From Poppler: poppler.freedesktop.org.

For MacOS®, see https://brew.sh/, install *Homebrew*, then

Enter ⇒ **`brew install poppler`**

For Windows, see MikTeX miktex-poppler-bin-*, or:
https://sourceforge.net/projects/poppler-win32/ and:
http://blog.alivate.com.au/poppler-windows/

***Perl*:**

This may be provided by your operating-system package manager, and may be required for some of the Poppler PDF utilities.

strawberryperl.com (recommended), perl.org

Automatically downloaded from the internet as required:

MathJax: Optionally used to display math. From: mathjax.org

5.1 Installing the lwarp package

There are several ways to install lwarp. These are listed here with the preferred methods listed first:

Pre-installed: Try entering into a command line:

Enter ⇒ **`kpsewhich lwarp.sty`**

If a path to `lwarp.sty` is shown, then lwarp is already installed and you may skip to the next section.

TEX Live: If using a TEX Live distribution, try installing via *tlmgr*:

Enter ⇒ **`tlmgr install lwarp`**

MiKTEX:

1. For newer versions of MiKTEX, install or update lwarp using the *MiKTeX Console* program.
2. For older versions of MiKTEX, to install lwarp the first time, use the *MiKTeX Package Manager (Admin)*. To update lwarp, use *MiKTeX Update (Admin)*.
3. Either way, also update the package miktex-misc, which will install and update the *lwarpmk* executable.

Operating-system package: The operating-system package manager may already have lwarp, perhaps as part of a set of TEX-related packages.

CTAN TDS archive: lwarp may be downloaded from the Comprehensive TEX Archive:

1. See http://ctan.org/pkg/lwarp for the lwarp package.
2. Download the TDS archive: `lwarp.tds.zip`
3. Find the TEX `local` directory:

   TEX Live:

   Enter ⇒ **`kpsewhich -var-value TEXMFLOCAL`**

   MiKTEX:

   In the **Settings** window, **Roots** tab, look for a local TDS root.

   This should be something like:

   `/usr/local/texlive/texmf-local/`
4. Unpack the archive in the TDS local directory.
5. Renew the cache:

   Enter ⇒ **`mktexlsr`**

   — or —

   Enter ⇒ **`texhash`**

   Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.

CTAN `.dtx` and `.ins` files: Another form of TEX package is `.dtx` and `.ins` source files. These files are used to create the documentation and `.sty` files.

1. See http://ctan.org/pkg/lwarp for the lwarp package.
2. Download the zip archive `lwarp.zip` into your own `lwarp` directory.
3. Unpack `lwarp.zip`.
4. Locate the contents `lwarp.dtx` and `lwarp.ins`
5. Create the `.sty` files:

   Enter ⇒ **`pdflatex lwarp.ins`**
6. Create the documentation:

```
pdflatex lwarp.dtx  (several times)
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
makeindex -s gind.ist lwarp.idx
pdflatex lwarp.dtx  (several times)
```

7. Copy the `.sty` files somewhere such as the TEX Live local tree found in the previous CTAN TDS section, under the subdirectory:

   `<texlocal>/tex/latex/local/lwarp`
8. Copy `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` to the same place as the `.sty` files.
9. Copy the documentation `lwarp.pdf` to a `source` directory in the local tree, such as:

   `<texlocal>/doc/local/lwarp`
10. Renew the cache:

    Enter ⇒ **`mktexlsr`**

    — or —

    Enter ⇒ **`texhash`**

    Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.
11. See section 5.2.1 to generate your local copy of *lwarpmk*.
12. Once the local version of `lwarpmk.lua` is installed, it may be made available system-wide as per section 5.2.

Project-local CTAN `.dtx` and `.ins` files: The `.dtx` and `.ins` files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant `*.sty` and `lwarpmk.lua` files may be used as-is, so long as they are in the same directory as the document source. The files `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` must also be copied as well. This approach is especially useful if you would like to temporarily test lwarp before deciding whether to permanently install it.

Just testing!

5.2 Installing the *lwarpmk* utility

(Note: If *lwarpmk* is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 5.2.1.)

After the lwarp package is installed, you may need to setup the *lwarpmk* utility:

1. At a command line, try executing **`lwarpmk`**. If the *lwarpmk* help message appears, then *lwarpmk* is already set up. If not, it is easiest to generate and use a local copy. See section 5.2.1.

2. For MiKTEX, try updating the miktex-misc package. This may install the *lwarpmk* executable for you.

   Otherwise, continue with the following:

3. Locate the file `lwarpmk.lua`, which should be in the `scripts` directory of the TDS tree. On a TEX Live or MiKTEX system you may use

   Enter ⇒ **`kpsewhich lwarpmk.lua`**

   (If the file is not found, you may also generate a local copy and use it instead. See section 5.2.1.)

4. Create *lwarpmk*:

   Unix: Create a symbolic link and make it executable:

   (a) Locate the TEX Live binaries:

   Enter ⇒ **`kpsewhich -var-value TEXMFROOT`**

   This will be something like:

   `/usr/local/texlive/<year>`

   The binaries are then located in the `bin/<arch>` directory under the root:

   `/usr/local/texlive/<year>/bin/<architecture>/`

   In this directory you will find programs such as *pdflatex* and *makeindex*.

   (b) In the binaries directory, create a new symbolic link from the binaries directory to `lwarpmk.lua`:

   Enter ⇒ **`ln -s <pathtolwarpmk.lua> lwarpmk`**

   (c) Make the link executable:

   Enter ⇒ **`chmod 0755 lwarpmk`**

   WINDOWS TEX Live: Create a new `lwarpmk.exe` file:

   (a) Locate the TEX Live binaries as shown above for UNIX.

   (b) In the binaries directory, make a *copy* of `runscript.exe` and call it `lwarpmk.exe` This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

   WINDOWS MiKTEX: Create a new `lwarpmk.bat` file:

   (a) Locate the MiKTEX binaries. These will be in a directory such as:

   `C:\Program Files\MiKTeX 2.9\miktex\bin\x64`

   In this directory you will find programs such as `pdflatex.exe` and `makeindex.exe`.

   (b) Create a new file named `lwarpmk.bat` containing:

   ```
   texlua "C:\Program Files\MiKTeX 2.9\scripts\lwarp\lwarp.texlua" %*
   ```

   This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

5.2.1 Using a local copy of *lwarpmk*

It is also possible to use a local version of *lwarpmk*:

1. When compiling the tutorial in section 6, use the `lwarpmk` option for the lwarp package:

   ```
   \usepackage[lwarpmk]{lwarp}
   ```

2. When the tutorial is compiled with *pdflatex*, the file `lwarpmk.lua` will be generated along with the other configuration files.

3. `lwarpmk.lua` may be used for this project:

   Unix:

   (a) Make `lwarpmk.lua` executable:

   Enter ⇒ **`chmod 0755 lwarpmk.lua`**

   (b) Compile documents with

   Enter ⇒ **`./lwarpmk.lua html`**

   Enter ⇒ **`./lwarpmk.lua print`**

   etc.

   (c) It may be useful to rename or link to a version without the `.lua` suffix.

   Windows:

   Compile documents with either of the following, depending on which command shell is being used:

   Enter ⇒ **`texlua lwarpmk.lua html`**

   Enter ⇒ **`texlua lwarpmk.lua print`**

   etc.

   Or:

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk print`**

   etc.

5.3 Installing additional utilities

To test for the existence of the additional utilities:

Enter the following in a command line. If each programs' version is displayed, then that utility is already installed. See table 3 on page 87.

Enter ⇒ **`luatex --version`**

Enter ⇒ **`xindy --version`**

Enter ⇒ **`latexmk --version`**

Enter ⇒ **`perl --version`**

Enter ⇒ **`pdfcrop --version`**

Enter ⇒ **`pdftotext -v`**

Enter ⇒ **`pdfseparate --version`**

Enter ⇒ **`pdftocairo -v`**

To install *xindy*, *latexmk*, and *pdfcrop*:

The TEX utilities *xindy*, *latexmk*, and *pdfcrop* may be installed in *TexLive* with *tlmgr*, installed by *MiKTeX*, provided by your operating system's package manager, or downloaded from the *CTAN* archive:

http://ctan.org/pkg/xindy
http://ctan.org/pkg/latexmk
http://ctan.org/pkg/pdfcrop

Prog [requirement] `pdftotext`
Prog [requirement] `pdfseparate`
Prog [requirement] `pdftocairo`

To install the POPPLER utilities to a UNIX/LINUX system:

The tools from the POPPLER project should be provided by your operating system's package manager.

To install the POPPLER utilities to a MACOS machine:

1. Install *Homebrew* from https://brew.sh/:

```
/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"
```

2. Install the POPPLER utilities:

Enter ⇒ `brew install poppler`

To install the POPPLER utilities to a WINDOWS machine:

If using MikTEX, install a miktex-poppler-bin-* package. Otherwise:

1. See table 3 on page 87.
2. Download and extract the POPPLER utilities *pdftotext*, *pdfseparate*, and *pdfseparate* to a directory, such as `Poppler`.
3. In the **Start** window, type "Path" to search for results related to Path. Or, open the control panel and search for "Path".
4. Choose **Edit the system environment variables** in the control panel.
5. Choose the **Environment Variables** button.
6. Choose the **Path** variable, then the **Edit** button.
7. Choose the **New** button to make an additional entry.
8. Enter the `bin` directory of the POPPLER utilities, such as:

   `C:\Users\<myname>\Desktop\Poppler\poppler-0.5_x86\poppler-0.5\bin`

   Be sure to include `\bin`.
9. Click **Ok** when done.

Prog [requirement] `perl`

To install PERL to a WINDOWS machine:

1. Download and install a version of PERL, such as STRAWBERRY PERL, to a directory without a space in its name, such as `C:\Strawberry`.
2. Edit the **Path** as seen above for the POPPLER utilities.
3. Enter the `bin` directory of the *perl* utility, such as:

   `C:\Strawberry\perl\bin`

   Be sure to include `\bin`.
4. Click **Ok** when done.

Any utilities installed by hand must be added to the `PATH`.

6 Tutorial

This section shows an example of how to create an lwarp document.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

6.1 Starting a new project

1. Create a new project directory called `tutorial`.

File `tutorial.tex`

2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

   Copy from the documentation PDF:

   A listing is in fig. 1, which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

   Copy from the lwarp documentation directory:

File `lwarp_tutorial.txt`

⚠ Note: `.txt` suffix!

   Another copy may be found by entering into a command line:

   Enter ⇒ **`texdoc -l lwarp_tutorial.txt`**

   This should be in the `doc/latex/lwarp/` directory along with this PDF documentation. Copy `lwarp_tutorial.txt` directly into your `tutorial` directory, renamed as `tutorial.tex`.

⚠ Bad formatting!

   When using WINDOWS, use an editor other than NOTEPAD, since NOTEPAD does not accept the end-of-line from a UNIX text file.

3. Compile the project:

   Enter ⇒ **`pdflatex tutorial.tex`**

   (several times)

   (*xelatex* or *lualatex* may be used as well. lwarp also supports DVI *latex* for use with `.eps` images.)

4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in table 4. These files are created by the `lwarp` package.

(Two of the new files are configuration files for the helper program *lwarpmk*. Whenever a print version of the document is created, the configuration files for *lwarpmk* are updated to record the operating system, LaTeX engine (*latex*, *pdflatex*, *xelatex*, or *lualatex*), the filenames of the source code and HTML output, and whether the additional helper program *latexmk* will be used to compile the document.)

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarp package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern}            % pdflatex or dvi latex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec}           % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
%   HomeHTMLFilename=index,     % Filename of the homepage.
%   HTMLFilename={node-},       % Filename prefix of other pages.
%   IndexLanguage=english,      % Language for xindy index, glossary.
%   latexmk,                    % Use latexmk to compile.
%   OSWindows,                  % Force Windows. (Usually automatic.)
%   mathjax,                    % Use MathJax to display math.
]{lwarp}
% \boolfalse{FileSectionNames}  % If false, numbers the files.

% --- LOAD PDFLATEX MATH FONTS HERE ---

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor}             % (Demonstration purposes only.)
\usepackage{hyperref,cleveref}  % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarp Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2}        % Include subsections in the \TOC.
\setcounter{secnumdepth}{2}     % Number down to subsections.
\setcounter{FileDepth}{1}       % Split \HTML\ files at sections
\booltrue{CombineHigherDepths}  % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1}    % Include subsections in the side\TOC
\HTMLTitle{Webpage Title}       % Overrides \title for the web page.
\HTMLAuthor{Some Author}        % Sets the HTML meta author tag.
\HTMLLanguage{en-US}            % Sets the HTML meta language.
\HTMLDescription{A description.}% Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSFilename{lwarp_sagebrush.css}
```

```
\begin{document}

\maketitle                      % Or titlepage/titlingpage environment.

% An article abstract would go here.

\tableofcontents                % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math: $r = r_0 + vt - \frac{1}{2}at^2$
followed by display math:
\begin{equation}
a^2 + b^2 = c^2
\end{equation}


\begin{warpprint}   % For print output ...
\cleardoublepage    % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage      % HTML index will be on its own page.
\ForceHTMLTOC       % HTML index will have its own toc entry.
\printindex

\end{document}
```

Table 4: Configuration files created by print version

`tutorial.pdf`: The PDF output from LaTeX. The print version of the document.

`tutorial_html.tex`: A small `.tex` file used to create a parallel HTML version of the document, which co-exists with usual the PDF version, and which will have its own auxiliary files. In this way, both PDF and HTML documents may co-exist side-by-side.

Auxiliary files: The usual LaTeX files `.aux`, `.log`, `.out`, `.toc`, `.lof`, `.idx`. When an HTML version of the document is created, `_html` versions of the auxiliary files will also be generated.

`lwarpmk.conf`: A configuration file for *lwarpmk*, which is used to automate the compilation of PDF or HTML versions of the document.

`tutorial.lwarpmkconf`: Another configuration file used by *lwarpmk*, which is only useful if you wish to have several projects residing in the same directory.

`.css` files: `lwarp.css`, `lwarp_formal.css`, `lwarp_sagebrush.css` These files are standard for lwarp, and are not meant to be modified by the user.

`sample_project.css`: An example of a user-customized CSS file, which may be used for project-specific changes to the lwarp defaults.

`lwarp.ist`: Used by lwarp while creating an index using *makeindex*. This file should not be modified by the user. A custom file may be used instead, if necessary.

`lwarp.xdy`: Used by lwarp while creating an index using *xindy*. This file should not be modified by the user. A custom file may be used instead, if necessary.

`lwarp_one_limage.txt`: For WINDOWS only. Used to process SVG images in the background. Copied to `lwarp_one_limage.cmd` when images are generated.

`lwarp_mathjax.txt`: Inserted into the HTML files when MATHJAX is used to display math. This file should not be modified by the user.

`comment.cut`: A temporary file used by lwarp to conditionally process blocks of text. This file may be ignored.

When the `lwarpmk` option is given to the lwarp package:

`lwarpmk.lua`: A local copy of the *lwarpmk* utility.

On UNIX-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

6.2 Compiling the print version with *lwarpmk*

The *lwarpmk* utility program is used to compile either the printed or the HTML version of the document.

`lwarpmk print` is used to recompile a printed version of the document.

1. Re-compile the print version:

   Enter ⇒ **`lwarpmk print`**

   lwarpmk prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then *lwarpmk* informs you of that fact and then exits.

2. Make a small change in the original document, such as adding a space character.

3. Recompile again.

   Enter ⇒ **`lwarpmk print`**

   The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

4. Force a recompile to occur.

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk print`**

   `lwarpmk again` updates the date code for the file, triggering a recompile the next time the document is made.[5]

5. Process the index.[6] [7]

   Enter ⇒ **`lwarpmk printindex`**

6. Recompile again to include the index.

   Enter ⇒ **`lwarpmk print`**

7. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk print1`**

Note that the HTML customization commands are ignored while making the print version.

[5] Although, when using the utility *latexmk* (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

[6] The command **`lwarpmk printglossary`** is also available to process a glossary produced with the glossaries package. See section 9.6.11.

[7] Also see section 9.6.14 for index options.

6.3 Compiling the HTML version with *lwarpmk*

`lwarpmk html` is used to recompile an HTML version of the document.

1. Compile the HTML version:

   Enter ⇒ **`lwarpmk html`**

   (a) *lwarpmk* uses LaTeX to process `tutorial_html.tex` to create `tutorial_html.pdf`.

   (b) *pdftotext* is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.

   (c) *lwarpmk* manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`[8], `Some-math.html`, and the document's index in `_Index.html`.[9]

2. View the HTML page in a web browser.

   Open the file `tutorial.html` in a web browser.

math Note that math is still displayed as its `alt` tag, which is the plain-text LaTeX source, until the images of the math expressions have been generated. Math may be displayed as SVG images or by a MathJax script, as seen in sections 6.4 and 6.5.

3. Force a recompile:

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk print`**

4. Process the HTML index and recompile:[10][11]

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   `_Index.html` is updated for the new LaTeX index.

5. Reload the web page to see the added index.

6. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk html1`**

[8] `First-chapter.html` also contains the first section, even though the second section is its own HTML page. This behavior is controlled by the boolean `CombineHigherDepths`.

[9] `index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

[10] The command **`lwarpmk htmlglossary`** is also available to process a glossary produced with the glossaries package. See section 9.6.11.

[11] Also see section 9.6.14 for index options.

6.4 Generating the SVG images

math as SVG images

By default lwarp represents math as SVG images, with the LaTeX source included in `alt` attributes. In this way, the math is displayed as it was drawn by LaTeX, and the LaTeX source may be copied and pasted into other documents.

`picture` and Ti*k*z

lwarp uses the same mechanism for `picture` and Ti*k*z environments.

1. Create the SVG images:

   Enter ⇒ **`lwarpmk images`**

   Enter ⇒ **`lwarpmk html`**

2. Move to the tutorial's HTML math page and reload the document in the browser.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the LaTeX source.

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk images`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[12] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ HTML instead of images

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect SVG images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

⚠ Lots of files!

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 6.5 to use MathJax instead.

[12] This becomes important when dealing with a document containing thousands of images.

6.5 Using MathJax for math

math with MathJax

Math may also be represented using the MathJax Javascript project.

1. In the tutorial's source code, uncomment the `mathjax` package option for lwarp:

   ```
   mathjax, % Use MathJax to display math.
   ```

2. Recompile

   Enter ⇒ **`lwarpmk html`**

3. Reload the math page.

⚠ MathJax requirements

MathJax requires web access unless a local copy of MathJax is available, and it also requires that Javascript is enabled for the web page. The math is rendered by MathJax. Right-click on math to see several options for rendering, and for copying the LaTeX source.

While using MathJax has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as LaTeX, and it may not support some math-related packages.

6.6 Changing the CSS style

For a formal CSS style, add to the preamble:

```
\usepackage{lwarp}
. . .
\CSSFilename{lwarp_formal.css}
. . .
\begin{document}
```

For a modern CSS style, `lwarp_sagebrush.css` is also provided:

```
\CSSFilename{lwarp_sagebrush.css}
```

See section 8.5 for more information about modifying the CSS styling of the document.

6.7 Customizing the HTML output

A number of settings may be made to control the HTML output, including filename generation, automatic compilation, math output, document splitting, meta data, and page headers and footers.

See section 8.4 for more information.

6.8 Using *latexmk*

latexmk is a LaTeX utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the `latexmk` option for the lwarp package:

   ```
   latexmk, % Use latexmk to compile.
   ```

2. Recompile the printed version of the document.

   Enter ⇒ **`lwarpmk print`**

   lwarp updates its own configuration files (`lwarpmk.conf` and `tutorial.lwarpmkconf`) whenever the printed version of the document is compiled. These configuration files remember that *lwarpmk* should use *latexmk* to compile the document.

3. Recompile the document.

   Enter ⇒ **`lwarpmk print`**

   and/or

   Enter ⇒ **`lwarpmk html`**

Changes are detected by comparing checksums rather than modification times, so `lwarpmk again` will not trigger a recompile, but *latexmk* has a much better awareness of changes than the *lwarpmk* utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source, and a single recompile may be forced with:

forced single-pass recompile

Enter ⇒ **`lwarpmk print1`**

and/or

Enter ⇒ **`lwarpmk html1`**

6.9 Using XƎLaTeX or LuaLaTeX

XƎLaTeX or LuaLaTeX may be used instead of LaTeX.

1. Remove the auxiliary files for the project:

   Enter ⇒ **`lwarpmk cleanall`**

2. Use *xelatex* or *lualatex* to compile the printed version a single time.

   Enter ⇒ **`xelatex tutorial.tex`**

   -or-

   Enter ⇒ **`lualatex tutorial.tex`**

   When the compile occurs, the configuration files for *lwarpmk* are modified to remember which TeX engine was used. XƎLaTeX or LuaLaTeX will be used for future runs of *lwarpmk*.

3. To recompile the document:

   Enter ⇒ **`lwarpmk print`**

   -and-

   Enter ⇒ **`lwarpmk html`**

4. Also remember to update the indexes and recompile again:

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk printindex`**

   Enter ⇒ **`lwarpmk print`**

6.10 Using DVI LaTeX

Traditional DVI LaTeX may also be used along with `.eps` image files. An SVG version of each image must also be provided. *lwarpmk* may be used to convert image formats.

To convert EPS files to PDF:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

To convert PDF files to SVG:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

⚠ bitmapped fonts See section 8.2 regarding font selection to avoid the use of bitmapped fonts.

6.11 Using a glossary

lwarp supports the gloss and glossaries packages, although this tutorial does not supply an example.

6.11.1 gloss package

See section 9.6.10.

6.11.2 glossaries package

To process the glossary for the print version:

Enter ⇒ **`lwarpmk printglossary`**

⚠ (If **`makeglossaries`** is not found, see section 9.6.11.)

To process the glossary for the HTML version:

Enter ⇒ **`lwarpmk htmlglossary`**

In each case, the document will have to be recompiled afterwards:

Enter ⇒ **`lwarpmk html1`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk print1`**

Enter ⇒ **`lwarpmk print`**

See section 9.6.11 to set options for processing glossaries.

6.12 Cleaning auxiliary files

To remove the auxiliary files `.aux`, `.toc`, `.lof`, `.lot`, `.idx`, `.ind`, `.log`, and `.gl*`:

Enter ⇒ **`lwarpmk clean`**

6.13 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the `.pdf` and `.html` files:

Enter ⇒ **`lwarpmk cleanall`**

6.14 Cleaning the images from the `<project>-images` directory

The `<project>-images` directory contains SVG images automatically generated for inline and display math, tikz, etc. To remove all the images from the `lateximages` directory:

Enter ⇒ **`lwarpmk cleanlimages`**

6.15 Converting PDF or EPS images to SVG

HTML cannot display PDF or EPS images, so any external PDF graphics images must be converted to SVG format. *pdftocairo* and *epstopdf* may be used one image at a time, but *lwarpmk* also provides a way to convert PDF or EPS images in bulk:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

Be sure to always provide SVG files for HTML output.

6.16 Creating HTML from an incomplete compile

During testing it may be useful to finish the HTML conversion even when the document had errors and did not compile successfully. To attempt an HTML conversion of an incomplete document:

Enter ⇒ **`lwarpmk pdftohtml [-p project]`**

6.17 Processing multiple projects in the same directory

It is possible to have several projects in the same directory. *lwarpmk* has an optional parameter which is the document to compile.

To create each project:

Enter ⇒ **pdflatex project_a**

Enter ⇒ **pdflatex project_b**

Each project is given its own configuration file:

`project_a.lwarpmkconf, project_b.lwarpmkconf`

To compile each project with `lwarkmk`:

Enter ⇒ **lwarpmk print -p project_a**

Enter ⇒ **lwarpmk html -p project_b**

6.18 Using the *make* utility

lwarpmk has an action which may be useful for integration with the common *make* utility:

```
lwarpmk pdftohtml [-p project]
```

make may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then *lwarpmk* may be used to convert each target to HTML files.

7 Converting an existing document

To convert an existing document for use with lwarp:

1. Arrange the document in the following order:
   (a) Declare the `\documentclass`.
   (b) Load text fonts.
   (c) Load inputenc or inputenx, fontenc, and/or fontspec.
   (d) Load lwarp.
   (e) Load remaining packages.
2. Modify the document:

⚠ math in section names

   (a) If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:
   ```
   \section{A name with math
       \texorpdfstring{$1+2=3$}{text description}}
   ```

⚠ scale

   (b) Avoid using the `\includegraphics` `scale` option. Change:
   ```
   \includegraphics[scale=<xx>]{ . . . }
   ```
   to:
   ```
   \includegraphics[width=<yy>\linewidth]{ . . . }
   ```
   (c) Possible changes to `tabular` environments include: `*` columns, multirow, longtable, supertabular, xtab, bigdelim. See section 9.10.1.
   (d) Possible option clashes with memoir. See section 9.13.
   (e) If using indexes, see section 9.6.14.
   (f) If using many indexes, glossaries, `.aux` files, etc., see section 9.6.14 regarding morewrites. If morewrites is already used, be sure to add the setup with `allocate=10`.
   (g) Other changes as per Special cases and limitations, section 9.
3. Convert any PDF images to SVG. See section 9.8.
4. Manually compile the print version with *latex*, *pdflatex*, *lualatex*, or *xelatex*.
5. `lwarpmk print` to finish the print version.
6. `lwarpmk html` to create the HTML version.
7. `lwarpmk limages` to create the SVG images of any SVG math, `lateximage`, Ti*k*z, etc.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

8 Additional details

8.1 Shell escape

Opt `--shell-escape`

Some documents require the use of an external program, which is allowed when using the `--shell-escape` command-line option. When the document is first compiled manually, and also whenever the print version is recompiled, lwarp detects and remembers whether shell escape is enabled. If so, it will also be enabled when the document is recompiled with *lwarpmk*.

8.2 Font and UTF-8 support

⚠ type 3 bitmapped fonts

lwarp uses *pdftotext* to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which may prevent the use of older "type 3" bit-mapped fonts, and of older packages such as ae. The lwarp option `pdftotextEnc` may be useful in some situations. See section 8.3.

vector fonts

Computer Modern

⚠ *pdflatex*

⚠ DVI *latex*

Pkg `cm-super`

While using DVI *latex* or PDF *pdflatex*, if no font-related package is specified then the default Computer Modern font is used, which may be a "type 3" bit-mapped font which may not convert well to plain text. A "type 1" vector font is required.

To use the updated cm-super's type 1 fonts instead of Computer Modern, install the cm-super font package.

Pkg `lmodern`

To use Latin Modern instead, add

```
usepackage{lmodern}
```

to the preamble.

Pkg `dejavu`

Another useful option is the Deja Vu series of fonts, which have an increased coverage of language and glyphs:

```
\usepackage{dejavu}
```

latex, *pdflatex*, T1, UTF8

While using DVI *latex* or PDF *pdflatex*, lwarp automatically loads fontenc with T1 encoding. fontenc may be loaded with an additional encoding after lwarp. inputenc is automatically loaded with UTF8 encoding if if has not yet been loaded, but may also be specified with another encoding such as `latin1`. See the next section regarding index encoding.

⚠ *xelatex* and *lualatex*

XeLaTeX and LuaLaTeX users must use the fontspec package. Do NOT use fontenc!

Place fontspec or fontenc, xunicode, and other font and UTF-8 related commands after the `\documentclass` command and before `\usepackage{lwarp}`.

⚠ package conflicts

In some cases, a package conflict may require that a font package be loaded after lwarp, which should work as well:

1. `documentclass{article/book/report}` comes first, followed by any of:

2. Font and UTF-8 related commands:

   - For XƎLaTeX or LuaLaTeX:

     Pkg fontspec

     – fontspec and font choices

     ligatures

     lwarp sets the following to turn off TeX ligatures during the generation of HTML tags, and turn off common ligatures in regular text, since older browsers may not display them correctly and newer browsers can automatically re-create them.

     ```
     \defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
     \defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
     \defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
     ```

   - For *pdflatex*:

     Pkg lmodern

     Pkg fontenc

     Pkg inputenc

     Pkg inputenx

     Pkg newunicodechar

     File glyphtounicode.tex

     Pkg cmap

     Pkg textcomp

     (a) `\usepackage{lmodern}`, or other font-related packages
     (b) `\usepackage[T1]{fontenc}`
     (c) `\usepackage[utf8]{inputenc}`, or `latin1`, etc. Or use inputenx.
     (d) `\usepackage{newunicodechar}` along with related definitions.
     (e) To assist with the PDF-HTML conversion:
        i. `\input glyphtounicode.tex`
        ii. `\input glyphtounicode-cmr.tex% from the pdfx package`
        iii. `\pdfgentounicode=1`
     (f) Another option to assist with the PDF-HTML conversion:
        – `\usepackage{cmap}`
     (g) `\usepackage{textcomp}`

3. `\usepackage{lwarp}` (section 8.3) goes after any of the above, followed by:

4. `\usepackage{newtxmath}` or other math-related font packages. Many of these load amsmath, which must be loaded after lwarp, so they must also be loaded after lwarp.

⚠ fontspec with traditional font packages

5. `\setmonofont{TeX Gyre Cursor}` or similar may be required if using XƎLaTeX or LuaLaTeX and fontspec along with traditional font packages such as txfonts, newtxtext, etc. This is required to turn off the monospaced font's ligatures with fontspec after loading the traditional font packages. Monospaced output ligatures must be turned off to produce the correct HTML characters.

6. … the rest of the preamble and the main document.

⚠ UTF-8 locale

In some cases, an external program may require a UTF-8 "locale". See section 10.8.

8.2.1 Indexes, glossaries, and encoding

lwarp uses the *xindy* program to processes indexes. *xelatex* and *lualatex* use *xindy* and *pdflatex* uses *texindy*.

The lwarp option `xindyLanguage` may be used to set the language option for xindy, and the `xindyCodepage` option may be used to set the codepage option for xindy. These are used for index generation.

8.3 lwarp package loading and options

lwarp supports book, report, and article classes, as well as the equivalent Koma-script classes and memoir.

Load the lwarp package immediately after the font and UTF-8 setup commands.

Package options may be set while loading lwarp, or later with

```
\lwarpsetup{⟨key=value, . . . ⟩}
```

Pkg lwarp

lwarp package options are as follows:

Opt mathsvg
Opt mathjax

mathsvg, mathjax: For math display, select mathsvg (default) or mathjax. For more information about the math options, see section 9.7.

Opt latexmk
Default: false

latexmk: Tells *lwarpmk* to use *latexmk* to recompile the document several times if necessary. Otherwise, *lwarpmk* attempts to determing for itself whether to recompile. See section 8.4.

Opt dvips
Default: false

dvips: Tells *lwarpmk* to use *dvips* and *ps2pdf* to convert DVI output to PDF.

Opt dvipdfm
Default: false

dvipdfm: Tells *lwarpmk* to use *dvipdfm* to convert DVI output to PDF.

Opt dvipdfmx
Default: false

dvipdfmx: Tells *lwarpmk* to use *dvipdfmx* to convert DVI output to PDF.

Opt HomeHTMLFilename
Default: {}

HomeHTMLFilename: See section 8.4.

Opt HTMLFilename
Default: {}

HTMLFilename: See section 8.4.

Opt PrintLatexCmd
Default: <automatic>

PrintLatexCmd: Sets the shell commands executed by **lwarpmk print**. If not specified, will automatically be set according to the detected LaTeX engine and the use of --shell-escape.

Opt HTMLLatexCmd
Default: <automatic>

HTMLLatexCmd: Sets the shell commands executed by **lwarpmk html**. If not specified, will automatically be set according to the detected LaTeX engine and the use of --shell-escape.

Opt makeindex
Default: makeindex

makeindex: Sets PrintIndexCmd, HTMLIndexCmd, and LatexmkImageCmd to use *makeindex* when generating indexes with **lwarpmk printindex**, **lwarpmk htmlindex**, or *latexmk*. If neither makeindex nor xindy is used, makeindex is assumed.

Opt xindy
Default: makeindex

xindy: Sets PrintIndexCmd, HTMLIndexCmd, and LatexmkImageCmd to use *xindy* when generating indexes with **lwarpmk printindex**, **lwarpmk htmlindex**, or *latexmk*.

Opt makeindexStyle
Default: lwarp.ist

makeindexStyle: If you wish to use a custom .ist file for index generation, see section 28.

Opt xindyStyle
Default: lwarp.xdy

xindyStyle: If you wish to use a custom .xdy file for index generation, see section 28.

Opt xindyLanguage
Default: english

xindyLanguage: If using an index or glossary, see section 28.

Opt xindyCodepage
Default: utf8

xindyCodepage: If using an index, see section 28.

Opt PrintIndexCmd
Default: <automatic>

PrintIndexCmd: Sets the shell commands executed by **lwarpmk printindex**. If not specified, will be set by the selection of makeindex or xindy. May be used to specify the creation of multiple indexes. See section 9.6.14.

Table 5: lwarp package options

Option	Description
`mathsvg`	Show math using SVG images.
`mathjax`	Show math using MATHJAX.
`latexmk`	Use *latexmk* for compiling documents.
`dvips`	Use *dvips* and *ps2pdf* to convert DVI documents.
`dvipdfm`	Use *dvipdfm* to convert DVI documents.
`dvipdfmx`	Use *dvipdfmx* to convert DVI documents.
`HomeHTMLFilename`	The filename of the home page.
`HTMLFilename`	A prefix for the filenames of the remaining web pages.
`PrintLatexCmd`	The shell commands for **`lwarpmk print`**.
`HTMLLatexCmd`	The shell commands for **`lwarpmk html`**.
For indexing (section 9.6.14) and glossaries (section 9.6.11):	
`makeindex`	Use *makeindex* to generate indices.
`xindy`	Use *xindy* to generate indices.
`makeindexStyle`	Set a custom style for *makeindex*.
`xindyStyle`	Set a custom style for *xindy*.
`xindyLanguage`	The *xindy* language option used for index generation.
`xindyCodepage`	The *xindy* codepage option used for index generation.
`PrintIndexCmd`	Shell commands executed by **`lwarpmk printindex`**.
`HTMLIndexCmd`	Shell commands executed by **`lwarpmk htmlindex`**.
`LatexmkIndexCmd`	Shell commands executed by *latexmk*.
`GlossaryCmd`	Shell command executed by **`lwarpmk printglossary`** and **`lwarpmk htmlglossary`**.
Seldom necessary:	
`OSWindows`	Force compatibility with MS-WINDOWS.
`pdftotextEnc`	Set the encoding for *pdftotext*.
`lwarpmk`	Generate a local copy of `lwarpmk.lua`.
Used internally by lwarp:	
`warpprint`	Generate print output, and also generate configuration files.
`warpHTML`	Generate HTML output.
`BaseJobname`	The `\jobname` to use. Set to the `\jobname` of the printed version even while generating HTML.

Examples:

```
makeindex -s lwarp.ist projectname.idx                (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname.idx      (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `PrintIndexCmd` to sensible values for each of those programs while compiling a single index. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified.

⚠ xindy

If specifying `PrintIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C` *xindy* options, as the lwarp `xindyLanguage` and `xindyCodepage` options are not used for the `PrintIndexCmd` option when it is set manually.

This option is stored in the configuration files `lwarpmk.conf` and `*.lwarpmkconf`, and is then passed by the **`lwarpmk printindex`** command to the operating system to compile the print indexes. Since the command string is parsed by TEX, written to a file, read from the file by LuaTEX, and finally passed to the operating system, any attempt at quoting will be problematic. For complicated commands, it would be best to create a shell script, and simply refer to the script with the lwarp `PrintIndexCmd` option.

Opt `HTMLIndexCmd`
Default: `<automatic>`

`HTMLIndexCmd`: Sets the shell commands executed by **`lwarpmk htmlindex`**. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 9.6.14.

⚠ filenames

Example settings are similar to `PrintIndexCmd`, but append `_html` to the filenames:

```
makeindex -s lwarp.ist projectname_html.idx           (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname_html.idx  (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `HTMLIndexCmd` to sensible values for each of those programs while compiling a single index. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified.

⚠ xindy

If specifying `HTMLIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C` *xindy* options, as the lwarp `xindyLanguage` and `xindyCodepage` options are not used for the `HTMLIndexCmd` option when it is set manually.

As with `PrintIndexCmd`, to generate complicated indexes it may be worthwhile to use a shell script, then refer to that script with `HTMLIndexCmd`.

Opt `LatexmkIndexCmd`
Default: `<automatic>`

`LatexmkIndexCmd`: Sets the shell commands executed by *latexmk*. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `LatexmkIndexCmd` does not include any filenames, which will be provided instead by *latexmk*. See section 9.6.14.

Example settings are similar to `PrintIndexCmd`, but without a filename:

```
makeindex -s lwarp.ist                                (makeindex)
xindy -M lwarp.xdy -L english -C utf8                      (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `LatexmkIndexCmd` to either of the two settings show above. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, *latexmk* uses either of the single-line settings of `LatexmkIndexCmd` shown above to compile each of multiple indexes if necessary.

⚠ xindy

If specifying `LatexmkIndexCmd` manually, be sure to assign an *xindy* language

and codepage with the -L and -C *xindy* options, as the lwarp xindyLanguage and xindyCodepage options are not used for the LatexmkIndexCmd option when it is set manually.

Opt GlossaryCmd
Default: **makeglossaries**

GlossaryCmd: Sets the shell command executed by **lwarpmk printglossary** and **lwarpmk htmlglossary**. The print or HTML glossary filename is appended to this command. See section 9.6.11.

Opt OSWindows

OSWindows: lwarp attempts to automatically sense WINDOWS, but it may be forced with this option. See section 8.6.

Opt pdftotextEnc
Default: UTF-8

pdftotextEnc: Used to specify the encoding used by *pdftotext* during the PDF-HTML conversion. In most situations, the default is the correct choice.

Opt lwarpmk

lwarpmk: If you wish to have lwarp generate a local copy of lwarpmk.lua for archival or local-installation purposes, compile the print version with the lwarpmk option set. See section 28.

The following options are used internally by lwarp, and usually are not used in the user's document:

Opt warpprint
Opt warpHTML

warpprint and warpHTML: Usually controlled by *lwarpmk*, and not set in the document. Select the warpprint option to generate print output (default), or the warpHTML option to generate HTML5 output. The default is print output, so the print version may be compiled with the usual *pdflatex*, etc. When lwarp is loaded in print mode, it creates <project>_html.tex, which sets the warpHTML option before calling the user's source code <project>.tex. In this way, <project>.tex can \usepackage{lwarp} without any options to create a printed version, while <project>_html.tex will create an HTML version.

Opt BaseJobname
Default: \jobname

BaseJobname: Not intended for the user. Used internally by lwarp when creating the *_html.tex file used to compile the HTML version. See section 28.

8.4 Customizing the HTML output

Table 6 shows several settings may be used to customize the HTML output. Watch for the correct placement of each!

⚠ Placement!

⚠ Changes! Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:

   Enter ⇒ **`lwarpmk clearall`**

2. Recompile the print version in order to recreate the configuration files for *lwarpmk*:

   Enter ⇒ **`lwarpmk print`**

3. Finally, recompile the HTML version with the new settings:

   Enter ⇒ **`lwarpmk html`**

Options for the lwarp package:

Use the following as options for `\usepackage[<options>]{lwarp}`:

Opt `HomeHTMLFilename`
Default: `\BaseJobname`

`HomeHTMLFilename`: Filename of the homepage, without the "`.html`" suffix. Defaults to the `\BaseJobname`. A common setting is:

```
HomeHTMLFilename=index
```

causing the homepage to be the file `index.html`. Underscores are allowed in `HomeHTMLFilename` and `HTMLFilename` options, but may need to be escaped elsewhere, such as when appearing in a list:

filename underscores

```
\item [\href{file\_name.pdf}{text}] \
```

See section 8.4.1 for examples of naming and numbering HTML files.

Opt `HTMLFilename`
Default: `<empty>`

`HTMLFilename`: A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty. See section 8.4.1 for examples of naming and numbering HTML files.

Opt `latexmk`
Default: `false`

`latexmk`: Controls whether lwarp uses *latexmk* to compile the document. This setting is written to *lwarpmk*'s configuration files.

Opt `mathsvg`
Default: `true`

`mathsvg`: Selects SVG display for math output. (The default.)

Opt `mathjax`
Default: `false`

`mathjax`: Selects MATHJAX for math output.

Opt `makeindex`
Default: `makeindex`

`makeindex`: Selects *makeindex* for index generation by *lwarpmk*.

Opt `xindy`
Default: `makeindex`

`xindy`: Selects *xindy* for index generation by *lwarpmk*.

Placed in the preamble before `\begin{document}`:

`\linkhomename`
Default: `Home`

`\linkhomename`: Name of the link to the home page. Paragraphs are allowed.

Table 6: HTML settings

Macro/Cntr/Bool	Description
\linkhomename	Name of the link to the homepage.
SideTOCDepth	Sectioning depth of the sideTOC.
\sidetocname	Name of the sideTOC.
FileDepth	Sectioning depth of the file splits.
CombineHigherDepths	Combine higher section levels.
FileSectionNames	Use section names for file names, else use numbers.
\FilenameLimit	Maximum length of the generated filenames.
FootnoteDepth	Sectioning depth of footnotes.
\abstractname	The name of the abstract.
\mathimagename	The SVG math image lateximage alt tag.
\packagediagramname	The suffix for a package's lateximage alt tags.
\CSSFilename	The CSS for the following files.
\HTMLLanguage	The HTML lang tag.
\HTMLTitle	The homepage's <title>, overriding \title.
\HTMLTitleBeforeSection	Set subpage <title>s to \HTMLTitle - sectionname
\HTMLTitleAfterSection	Set subpage <title>s to sectionname - \HTMLTitle
\HTMLAuthor	The HTML author meta tag, overriding \author.
\HTMLDescription	The HTML description meta tag.
\HTMLFirstPageTop	Heading for the home page.
\HTMLPageTop	Heading for the other pages.
\HTMLPageBottom	Footing for all pages.
HTMLDebugComments	Boolean to generate HTML comments.

Ctr tocdepth

tocdepth: Sectioning depth of the table of contents. See section 17 for a list of LaTeX stack depths.

Ctr SideTOCDepth
Default: 1

SideTOCDepth: Sectioning depth of the sideTOC. Defaults to 1, causing the sideTOC to show sections but not subsections.

sideTOC

Each subpage of the website has its own small table of contents on the side (the "sideTOC"). Its depth is set by SideTOCDepth. This sideTOC is only shown if the web page is wide enough. When using a narrow web browser window, "responsive web design" is used to show the sideTOC at the top of the page and a link back to **Home** at the bottom.

It is recommended to set:

```
SideTOCDepth = FileDepth
```

or

```
SideTOCDepth = FileDepth+1
```

⚠ inaccessible pages

If SideTOCDepth < FileDepth, web pages will be inaccessible via the sideTOC.

\sidetocname
Default: Contents

\sidetocname: Name of the sideTOC. Paragraphs are allowed.

Ctr FileDepth
Default: -5

FileDepth: Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.

- To place the entire file into one HTML page, use:
  \setcounter{FileDepth}{-5}
- To split the HTML file at \section depth, use:
  \setcounter{FileDepth}{1}
- ⚠ To ensure that the HTML pages/files are accessible:
  Place a \tableofcontents somewhere before the first section break (therefore in the "home page"), and set
  tocdepth >= FileDepth

Bool CombineHigherDepths
Default: true

CombineHigherDepths: Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

⚠ Inaccesible pages!

⚠ Lost in an old page!

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (lwarpmk cleanall), change FileDepth and/or CombineHigherDepths, then finally recompile and renavigate to the desired page using the new file structure.

Bool FileSectionNames
Default: true

⚠ Unique filename!

FileSectionNames: If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the HTMLFilename option is used as a prefix. See section 8.4.1 for examples of naming and numbering HTML files. The user must ensure that filenames are unique after begin sanitized. For example, math in the section name is removed before creating the filename, so the rest of the filename must be sufficiently unique to avoid name collisions.

\FilenameLimit
Default: 80

\FilenameLimit: The maximum length of the filenames generated by lwarp. ".html" is added to this length. Redefine with \newcommand.

Ctr FootnoteDepth
Default: 3

FootnoteDepth: Determines where to place pending footnotes. 3 places footnotes before each break down to the \subsubsection level. 1 places footnotes before each \section break. Any pending footnotes are also placed at the bottom of each page before each file break.

Bool HTMLDebugComments
Default: false

HTMLDebugComments: Set true to generate HTML comments, such as which section or is being opened or closed.

\abstractname
Default: Abstract

\abstractname: The name of the abstract. This may also be over-written by the babel package. Defaults to "Abstract".

Placed before \begin{document}, or before any sectioning command which causes a file break:

\CSSFilename
Default: lwarp.css

\CSSFilename: {⟨*filename.css*⟩} Sets the CSS file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The CSS styles of the web pages are set by the \CSSFilename command. If \CSSFilename is not used, a default plain style is used to mimic printed LaTeX output. lwarp_sagebrush.css is a semi-fancy colored style as shown in this tutorial. Change it to lwarp_formal.css for a more formal look, or comment out the \CSSFilename command to see the default. \CSSFilename may be used before each file break to set the CSS for individual pagess of the website.

\HTMLLanguage
Default: en-US

\HTMLLanguage: {⟨*langauge*⟩} The HTML file's HTML lang meta tag. Defaults to en-US.

\HTMLTitle
Default: \thetitle

\HTMLTitle: {⟨*title*⟩} Overrides \title for the HTML header's meta title. Defaults to \thetitle, which is set by \title, or empty otherwise. Unlike the author, \thetitle is set by \title even if not using the titling package.

\HTMLTitleBeforeSection
Default: \HTMLTitleBeforeSection

\HTMLTitleBeforeSection: Sets subpage <title> tags to show the website title followed by the section name.

\HTMLTitleAfterSection

\HTMLTitleAfterSection: Sets subpage <title> tags to show the section name followed by the website title.

custom <title>

To customize subpage <title>s, redefine \theHTMLTitleSection, which defaults to:

```
\def\theHTMLTitleSection{%
  \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
}
```

\HTMLAuthor
Default: \theauthor

\HTMLAuthor: {⟨*author*⟩} The HTML header's meta author. Defaults to \theauthor, which is set by \author if using the titling package, but is empty otherwise. There are several ways to represent the author and affiliations, especially if using the authblk package, most of which do not result in a sensible \theauthor, so \HTMLAuthor is useful to create a list of authors without their affiliations.

\HTMLDescription
Default: <empty>

\HTMLDescription: {⟨*description*⟩} Sets the HTML description tag for the following files. May be changed before each each sectioning command which would cause a file split.

\HTMLFirstPageTop
Default: <empty>

\HTMLFirstPageTop: {⟨*contents*⟩} A user-definable custom action applied to the top of the home page. Useful for logos, etc. Defaults empty. Ignored in print output.

\HTMLPageTop
Default: <empty>

\HTMLPageTop: {⟨*contents*⟩} A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.

\HTMLPageBottom
Default: <empty>

\HTMLPageBottom: {⟨*contents*⟩} A user-definable custom action applied to the bottom of each web page. Useful for authors, copyright notices, contact information, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.

Placed in the home page before the first sectioning command which causes a file break:

\tableofcontents
⚠ TOC on the homepage!

\tableofcontents: Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage.

Links to each chapter/section are provided, as selected by tocdepth.

Placed in the document wherever necessary:

\mathimagename
Default: math image

\mathimagename: When creating an SVG math image, its alt tag may be set to the math expression, which may be hashed for image reuse. In the case of \ensuremath or after \inlinemathother, where the contents require a unique image for each instance of the same expression, the alt tag is set to \mathimagename, and the image is not reused.

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "math image", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

\packagediagramname
Default: diagram

\packagediagramname: For many packages, the output is placed inside a lateximage with an HTML alt tag set to the package name followed by \packagediagramname. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `lateximages`.

Env warpprint

warpprint: An environment which is only used while generating print output. Place inside anything which does not apply to HTML and which may cause problems with lwarp. If lwarp knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won't have to be placed inside a `warpprint` environment, but unknown packages may cause problems which may be isolated from lwarp using this environment.

⚠ *Do not place anything else on the same line as* `\end{warpprint}`.

Env warpHTML

warpHTML: An environment which is only used while generating HTML output. This is useful for website logos and other items which have no purpose in printed output.

⚠ *Do not place anything else on the same line as* `\end{warpHTML}`.

\warpprintonly

\warpprintonly: {⟨*contents*⟩} A macro version of the `warpprint` environment.

\warpHTMLonly

\warpHTMLonly: {⟨*contents*⟩} A macro version of the `warpHTML` environment.

8.4.1 Example HTML file naming

Examples of ways to name or number HTML files:

Numbered HTML nodes:

Example: Homepage `index.html`, and `node-1`, `node-2`. [13]

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={node-}
]{lwarp}
\boolfalse{FileSectionNames}
```

Named HTML sections, no prefix:

Example: `index.html`, and `About.html`, `Products.html`

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={}
]{lwarp}
\booltrue{FileSectionNames}
```

[13] See `\SetHTMLFileNumber` to number in groups by chapter, for example.

Named HTML sections, with prefix:

Example: Homepage `mywebsite.html`, and additional pages such as `mywebsite-About.html`, `mywebsite-Products`, etc.

```
\usepackage[
    HomeHTMLFilename=mywebsite,
    HTMLFilename={mywebsite-}
]{lwarp}
\booltrue{FileSectionNames}
```

8.5 Customizing the css

`\CSSFilename`
Default: `lwarp.css`

`\CSSFilename` may be used to choose which `.css` file is used to display each page of the web site. Use `\CSSFilename` before `\begin{document}` to assign the style of the home page. If different parts of the website should have different styles, call `\CSSFilename` again before each section heading which creates a new file. This may be changed numerous times throughout the file, resulting in different HTML pages having different css files assigned:

```
...
\CSSFilename{myCSS.css}
\chapter{Another Chapter}
...
```

The styles provided by lwarp include:

`lwarp.css`: A default style if `\CSSFilename` is not used. This style is comparable to a plain LaTeX document. To set this style, you may use `\CSSFilename{lwarp.css}`, or no `\CSSFilename` call at all.

`lwarp_formal.css`: A formal style with a serif fonts and a traditional look.

`lwarp_sagebrush.css`: A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the `\CSSFilename` entry in the tutorial, `lwarpmk html` again, and then reload the tutorial webpage.

Custom css

A customized style may also be created. For each new project a file called `sample_project.css` is generated. This may be renamed to `<project>.css` then used by assigning `\CSSFilename{<project>.css}`.

⚠ Rename it!

Note that `sample_project.css` is overwritten whenever lwarp is loaded in print mode. It is therefore important to rename the file to something like `<project>.css` before using it, so that your own changes are not overwritten.

`<project>.css` has an entry which loads `lwarp.css`, and this entry may be changed to load `lwarp_formal.css` or `lwarp_sagebrush.css` if desired. Additional changes to the css may be made by making entries later in the `<project>.css` file.

File lwarp.css
File project.css
File sample_project.css

It is best to make a local project-specific CSS file such as `project.css`, containing only things which are different from `lwarp.css`. The file `project.css` should refer to `lwarp.css` as follows:

```
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
```

Finally use `\CSSFilename{<project>.css}` in the document to activate the custom CSS.

8.6 Selecting the operating system

Prog Unix
Prog Mac OS
Prog Linux
Prog MS-Windows
Prog Windows
Opt OSWindows

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.

If MS-WINDOWS is not correctly detected, use the lwarp option `OSWindows`.

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean `usingOSWindows` is set `true`. This boolean may be tested by the user for later use.

8.7 Selecting actions for print or HTML output

The following environments and macros are used to select actions which only apply to either traditional LaTeX print-formatted PDF generation, or to HTML generation.

For most of built-in LaTeX and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which lwarp does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

Env warpHTML

Anything which is to be done only for HTML5 output is surrounded by a `warpHTML` environment:

```
\begin{warpHTML}
 ... something to be done only during \HTML\ generation
\end{warpHTML}
```

⚠ `\end{warpHTML}` Do *not* place anything else on the same line as `\end{warpHTML}`. The exact phrase is used to mark the end of the environment.

Env `warpprint` Anything which is to be done only for print output is surrounded by a `warpprint` environment:

```
\begin{warpprint}
 ... something to be done only during traditional \PDF\ generation
\end{warpprint}
```

⚠ `\end{warpprint}` As above, do not place anything else on the line with `\end{warpprint}`.

Env `warpall` Anything which is to be done for any output may be surrounded by a `warpall` environment. Doing so is optional.

```
\begin{warpall}
 ... something to be done during print \PDF\ or \HTML\ output
\end{warpall}
```

As above, do not place anything else on the line with `\end{warpall}`.

Macros are also provided for print-only or HTML-only code:

`\warpprintonly` {⟨*actions*⟩}

Performs the given actions only when print output is being generated.

`\warpHTMLonly` {⟨*actions*⟩}

Performs the given actions only when HTML output is being generated.

8.8 Commands to be placed into the `warpprint` environment

Certain print-related commands should always be placed inside a `warpprint` environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: `\parindent` `\parskip`
- Manual page positions such as the textpos package, which is emulated but only in a limited way.

- Anything changing the page counter. lwarp requires that the page counter not be adjusted during HTML output.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 14: Troubleshooting.

8.9 Title page

In the preamble, place an additional block of code to set the following:

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
    Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

The title is used in the meta tags in the HTML files, unless overridden by `\HTMLTitle`, and the rest are used in `\maketitle`. To use a `\subtitle` or `\published` field, see section 65.8.

`\maketitle` Use `\maketitle` just after the `\begin{document}`, as this will establish the title of the homepage. Optionally, use a `titlepage` environment instead.

Env `titlepage` The `titlepage` environment may be used to hold a custom title page. The titlepage will be set in a `<div>` class `titlepage`, and `\printtitle`, etc. may be used inside this environment.

Env `titlingpage` Another form of custom title page, where `\maketitle` is allowed, and additional information may be included as well.

`\title` {⟨*title*⟩}

⚠ newlines Avoid newlines in the `\title`; these will interfere with the file break and CSS detection. Use a `\subtitle` command instead (section 65.8). The title will appear in the document `\maketitle` as a heading `<h1>`. The HTML meta `title` tag will also have this title, unless `\HTMLTitle` is used to set the meta title to something else instead.

`\author` {⟨*author*⟩}

In `\author`, `\protect` may be needed before some formatting commands. In HTML, the author will appear in a `<div>` of class `author` in the `\maketitle`. If the titling package is used, the author will also appear in a HTML meta tag, but `\HTMLAuthor` may be necessary to create a plain list of names if `\author` had affiliations added. `\affiliation` is a new addition to lwarp.

`\date` {⟨*date*⟩}

`\date` works as expected. In HTML, this will appear in a `<div>` class `titledate`.

`\thanks` {⟨*text*⟩}

\thanks are allowed in the titlepage fields, and will be rendered as HTML notes at the bottom of the title page.

8.10 HTML page meta descriptions

\HTMLDescription {⟨*A description of the web page.*⟩} The default is no description.

limitations Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character (").

placement Use \HTMLDescription just before \begin{document} to set the description of the home page, and also just before each sectioning command such as \chapter or \section where a new file will be generated, depending on FileDepth. For example, if FileDepth is 1, use \HTMLDescription just before each \section command, and that description will be placed inside the HTML page for that \section. The same descrition will be used for all following HTML files as well, until reset by a new \HTMLDescription. It is best to use a unique description for each HTML file.

disabling To disable the generation of HTML description meta tags, use:

```
\HTMLDescription{}
```

8.11 HTML homepage meta title

\HTMLTitle {⟨*title*⟩} Sets the contents of the web page <meta name="title"> element. Defaults to \HTMLtitle{\thetitle}. May be set empty to cancel the meta title tag.

See section 8.4 for \HTMLTitleBeforeSection and \HTMLTitleAfterSection, used to set the title for HTML subpages.

8.12 HTML page meta author

\HTMLAuthor {⟨*author*⟩} Sets the contents of the web page <meta name="author"> element. Defaults to \HTMLAuthor{\theauthor}. May be set empty to cancel the meta author tag.

\author may be used to create a list of authors and their affiliations, in several formats if using authblk, and these may not successfully parse properly into a sensible list for \theauthor. \HTMLAuthor may be used to set the meta tag to a simple list of names.

9 Special cases and limitations

Some commonly-used LaTeX expressions should be modified as follows to allow for a smooth conversion to both HTML and print-formatted outputs.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

9.1 Things to avoid

In the document, avoid the following:

page counter: Do not adjust the page counter. If doing so is required for the print version, place the adjustment inside a `warpprint` environment.

Custom math environment macros: Do not use expressions such as `\beq` as a replacement for `\begin{equation}`.

Custom macros in section, figure, table names: Custom macros which appear in sectioning commands or float captions then appear in the `.toc`, `.lof`, and `.lot` lists, and should be made robust using `\newrobustcmd` or `\robustify` from etoolbox, xparse, etc.

When setting `FileSectionNames` to `true` to name the HTML files from the section names, the file names are created from sanitized versions of the chapter or section names, but the section names must be plain text or something which expands into plain text. Robust macros will not work at the sectioning level which is used for file names, but a robust macro or other complicated name may be used for the manditory argument of `\chapter`, `\section`, etc., if a plain-text version is also included in the optional argument:

```
\chapter[Plain Name]{\ARobustMacro{Fancy Name}}
```

9.1.1 Invalid HTML

Additionally, some objects are valid LaTeX, but invalid HTML. An example is a tabular inside `\textbf`, since HTML does not allow a table inside a span. lwarp will create the table, and the browser may support it, but the result is technically invalid.

9.2 Formatting

9.2.1 Text formatting

⚠ `\bfseries`, etc.

`\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ HTML special chars

&, <, and > have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings

For program listings, the listings package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.

verbatim The various verbatim-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

9.2.2 Horizontal space

\hspace \hspace is converted to an inline HTML span of the given width, except that 0 width is ignored, a width of .16667em is converted to an HTML thin breakable space (U+2009), and a \fill is converted to a \qquad.

\, ~ and \, are converted to HTML entities.

\kern \hskip \kern and \hskip are entered into the HTML PDF output as-is, then interpreted by *pdftotext*, and thus usually appear as a single space.

9.2.3 Text alignment

Use the environments center, flushright, flushleft instead of the macros \centering, \raggedright, \raggedleft.

⚠ figure & table alignment \centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

9.2.4 Accents

Native LaTeX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX.

9.2.5 textcomp package

Pkg textcomp Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols Many textcomp symbols are not supported by many system / browser fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

9.2.6 Superscripts and other non-math uses of math mode

Use ^{x} instead of ^{x}

9.2.7 Empty \item followed by a new line of text or a nested list:

lists Use a trailing backslash: `\item[label] \`

9.2.8 Filenames and URLs in lists or footnotes

filename underscore Escape underscores in the filenames:

```
\item[\href{file\_name.pdf}{text}]
```

9.2.9 relsize package

Pkg relsize For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small The HTML browser's setting for minumum font size may limit how small the output will be displayed.

9.3 Boxes and minipages

9.3.1 Marginpars

`\marginpar` [⟨*left*⟩] {⟨*right*⟩} `\marginpar` may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `<br />` tags.

`\marginparBlock` [⟨*left*⟩] {⟨*right*⟩} To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a `<span>`. A line break will occur in the text where the `\marginBlock` occurs.

9.3.2 Save Boxes

TEX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. lwarp uses methods which help avoid this problem.

9.3.3 Minipages

⚠ inline A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox`

placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

placement

`minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side

Side-by-side `minipages` may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span

There is limited support for `minipages` inside an HTML `<span>`. An HTML `<div>` cannot appear inside a `<span>`. While in a `<span>`, `minipages`, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an "inline" format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

⚠ minipage size

When using `\linewidth`, `\textwidth`, and `\textheight`, widths and heights in HTML are scaled proportionally to a 6×9 inch text area, and inside a `multicols` `\linewidth` is divided by the specified number of columns.

if width is `\linewidth`

If a `minipage` or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML

A new macro `\minipagefullwidth` requests that, during HTML output, the next single `minipage` or `\parbox` be generated without an HTML `width` attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ `tabular`, `multicols`

`\UseMinipageWidths`
`\IgnoreMinipageWidths`

Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every `minipage` or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell lwarp to honor the specified widths of all following `minipages` and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell lwarp to ignore the specified widths.

⚠ text alignment

Nested `minipages` adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a `flushleft` or similar environment in the child `minipage` to force a text alignment.

9.3.4 Side-by-side minipages

Place side-by-side minipages inside a `center` environment, with horizontal space between them, such as `\quad`, `\qquad`, `\hspace`, or `\hfill`. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

9.3.5 Framed minipages and other environments

`\fbox` can only be used around inline `<span>` items during HTML output, but HTML cannot place a block element such as a `<div>` for a minipage or a list inside of a `<span>`.

Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

\fbox
\fboxBlock
Env fminipage

For a framed object, options include:

To remove the frame in HTML output: Place the \fbox command and its closing brace inside warpprint environments. This will nullify the frame for HTML output.

For inline text:

To frame the contents inline with some formatting losses in HTML: This is the default action of \fbox when enclosing a minipage. During HTML output, \fbox nullifies the HTML tags for minipage, \parbox, and lists. The contents are included as inline text inside the \fbox's of class framebox. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.

For inline minipage and lists:

To frame the contents on their own line with improved formatting in HTML: A new command \fboxBlock is included, intended to be a direct replacement for \fbox for cases where the \fbox surrounds a minipage, table, or list. For print output, this behaves as \fbox. For HTML output, the contents are placed inside an HTML with the class framed, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and minipages look nicer, and valid HTML is created for a tabular. While an \fbox containing a tabular is valid LaTeX code, the result in HTML is problematic since a table is a not a , so use \fboxBlock around a tabular, or else place the tabular inside a minipage, or use fminipage, described next. Also see below regarding the "Misplaced alignment tab character &." error.

For display tabular, minipages, and lists:

To create a framed minipage in both print and HTML: A new environment fminipage is included. For print output, this is identical to minipage, except that it is also framed. For HTML output, this forms a of class framed, the contents preserve their HTML formatting, and valid HTML is created for a tabular. Also see section 84 for a new environment fcolorminipage. Also see below regarding the "Misplaced alignment tab character &." error.

colored boxes and frames:

To create colored frames and boxes: See section 494 for xcolor's \colorbox and \fcolorbox, and lwarp's additional \colorboxBlock and \fcolorboxBlock.

⚠ Misplaced alignment tab character &

To frame tables or verbatim environments: Place the contents inside a fminipage, or perhaps a \fboxBlock for a tabular. Also, if using \fboxblock with tabular, you will have to use \StartDefiningTabulars before the start of the macro which uses \fboxBlock and the tabular, and \StopDefiningTabulars afterwards. Also see the lwarp documentation for the fancybox package.

To frame equations: See section 213 for the fancybox package.

For fancy framed minipages: See packages boxedminipage, shadow, fancybox, framed, mdframed.

Custom environments: Use a custom environment to create a sidebar, containing a BlockClass environment with custom css formatting, and \warpprintonly{\hrule} command:

```
\begin{BlockClass}{frameminipage}% ignored in print output
  % use \CSS\ to format div class ``framedminipage''
\warpprintonly{\hrule} % only appears in print output
Contents
\warpprintonly{\hrule} % only appears in print output
\end{BlockClass}
```

9.3.6 fancybox package

Pkg fancybox

framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives

\fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example

The fancybox documentation's example framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method loses HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim

lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \beginVerbatim
}{
  \endVerbatim
  \endfminipage
}
```

framed \VerbBox — fancybox's \VerbBox may be used inside \fbox.

indented alignment — LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

9.3.7 mdframed package

Pkg mdframed support — Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading — When used, lwarp loads mdframed in HTML with framemethod=none.

font — For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where \textbf must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support \bfseries and friends, only one font selection may be made at a time.

theoremtitlefont — theoremtitlefont is not supported, since the following text is not in braces in the mdframed source.

ignored options — userdefinedwidth and align are currently ignored.

css classes — Environments created or encapsulated by mdframed are enclosed in a of class mdframed, and also class md<environmentname> for new environments.

Frame titles are placed in a of class |mdframedtitle|. Subtitles are in a of class |mdframedsubtitle|, and likewise for subsubtitles.

9.4 Section names

If using named HTML files, by selecting `\booltrue{FileSectionNames}`:

`\FilenameSimplify` To remove common short words from the automatically-generated filenames, replacing each with a single hyphen "-", use `\FilenameSimplify`:

```
\FilenameSimplify*{-in-}
\FilenameSimplify*{A-}
```

The first example removes the word "in" in the middle of a filename, and the second example removes "A" at the start of the filename. The star forces the arguments to be detokenized, which is required for a plain-text comparison. (The unstarred form is used for a token-sensitive comparison, which is seldom required by the user.) After simplfication, repeated hyphen characters will be further simplified to a single hyphen "-". Finally, single hyphens at the start or end of the filename are removed.

`\FilenameNullify` ⚠ macros in section names

Macro names may appear in the automatically-generated file names. To remove these, create *non-robust* nullified versions of the macros, ensuring that each line ends with a percent character % as shown below. These are placed inside `\FilenameNullify`, which adds them to the list of macros which are nullfiied during filename generation. Low-level macros such as `\begingroup` will cause problems when nullfied. Many macros such as `\textbf` are already nullfied. lwarp also already nullifies built-in symbol and textcomp macros, including if defined by xunicode, but not all xunicode macros. See the definition of `\LWR@nullfonts` for a complete list.

```
\FilenameNullify{%
  \renewcommand*{\macroname}[1]{#1}%
  \renewcommand*{\anothermacro}{}%
}
```

⚠ duplicate filename

Avoid duplicate file names. Section names at levels which result in HTML file splits must be unique. lwarp will generate an error if a duplicate HTML filename is generated. Use the optional TOC caption entry parameter for formatting. Remember to `\protect` LaTeX commands which appear in section names and TOC captions.

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

9.5 Cross-references

labels ⚠ label characters

Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).

`\nameref` ⚠ empty link

`\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

9.5.1 Page references

⚠ LaTeX page numbers

The printed page does not translate to the HTML page, so `\pageref` references are converted to parentheses containing `\pagerefPageFor`, which defaults to "see ", followed by a hyperlink to the appropriate object.

Ex:

```
\ref{sec:name} on page \pageref{sec:name}
```

in HTML becomes:

"Sec. 1.23 on page (**see** sec. 1.23)".

`\pagerefPageFor` may be redefined to "page for ", empty, etc. See page 466.

9.5.2 cleveref and varioref packages

Pkg cleveref
Pkg varioref

⚠ cleveref page numbers

cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to "for".

Ex:

```
\cpageref{tab:first,tab:second}
in html becomes:
```

"pages **for** table 4.1 and **for** table 4.2"

See `\cpagerefFor` at page 538 to redefine the message which is printed for page number references.

9.5.3 Hyperlinks, hyperref, and url

Pkg hyperref
Pkg url

lwarp emulates hyperref, including the creation of active hyperlinks, but does not require that hyperref be loaded by the document.

⚠ comments between arguments

Do not place a comment with a `%` character between arguments for `\hyperref`, etc., as it is neutralized for inclusion in HTML URLs.

lwarp can also load url, but url should not be used at the same time as hyperref, since they both define the `\url` command. lwarp does not (yet) attempt to convert url links into hyperlinks during HTML output, nor does the print version of url create hyperlinks.

⚠ backref

When generating HTML, lwarp's emulation of hyperref does not automatically load backref, so backref must be loaded explicitly.

9.5.4 Footnotes and page notes

lwarp uses native LaTeX footnote code, although with its own `\box` to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering

To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

footmisc

The footmisc `stable` option is emulated by lwarp.

⚠ sectioning commands

When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the `stable` option, provide a short TOC entry, and `\protect` the `\footnote`:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc

⚠ memoir

If using memoir class, with which lwarp preloads footmisc, the `stable` option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

fancybox, fancyvrb

⚠ `\VerbatimFootnotes`

⚠ sectioning or displaymath

If using fancybox or fancyvrb with `\VerbatimFootnotes`, and using footnotes in a sectioning command or display math, use `\footnotemark` and `\footnotetext`:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when `\VerbatimFootnotes` are selected. The browser usually compensates.

pfnote

⚠ pfnote numbers

While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

bigfoot, manyfoot

⚠ verbatim

Verbatim footnotes are not yet supported.

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has

been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XƎLaTeX or LuaLaTeX instead of pdfLaTeX.

9.6 Front and back matter

9.6.1 Custom classes with multiple authors and affiliations

Some classes allow multiple authors and affiliations. Often it is possible to emulate these using a standard class along with authblk:

```
%\documentclass{customclass} % for print document
\documentclass{article} % for html document

\usepackage{lwarp}
\begin{warpHTML}
\usepackage{authblk}
\let\affiliation\affil % maybe required
\end{warpHTML}
```

9.6.2 Starred chapters and sections

The following describes `\ForceHTMLPage` and `\ForceHTMLTOC`, which may be used for endnotes, glossaries, tocbibind, bibliographies, and the index. See the following sections where applicable. Continue here if interested in the reason for adding these commands to lwarp.

Some packages use `\chapter*` or `\section*` to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own HTML pages, and they are not given TOC entries.

lwarp provides a method to cause a starred section to be on its own HTML page, subject to `FileDepth`, and also a method to cause the starred section to have its own TOC entry during HTML output.

`\ForceHTMLPage` To place a starred section on its own HTML page, use `\ForceHTMLPage` just before the `\chapter*` or `\section*`. lwarp will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using `\phantomsection` and `\addcontentsline` works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created, or when creating an EPUB where the TOC entry will point to the page before the starred section. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is

⚠ inaccessible HTML page

created.

\ForceHTMLTOC

To automatically force the HTML version of the document to have a TOC entry for a starred section, use \ForceHTMLTOC just before the \chapter* or \section*, and place \phantomsection and \addcontentsline inside a warpprint environment.

For print output, \ForceHTMLTOC and \ForceHTMLPage have no effect.

9.6.3 abstract package

Pkg abstract

⚠ missing TOC

If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

9.6.4 titling and authblk

Pkg titling

Pkg authblk

package support

⚠ load order

\published and \subtitle

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 65.8.

9.6.5 tocloft package

Opt [tocloft] titles

Pkg tocloft

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its titles option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

9.6.6 appendix package

Pkg appendix

⚠ incorrect TOC link

During HTML conversion, the option toc without the option page results in a TOC link to whichever section was before the appendices environment. It is recommended to use both toc and also page at the same time.

9.6.7 pagenote package

Pkg pagenote

pagenote works as-is, but the page option is disabled.

9.6.8 endnotes package

Pkg endnotes

table of contents

To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

HTML page

To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

9.6.9 BibTeX

`\etalchar`

Displays a superscript "+" to indicate "and others".

⚠ Modify *.bib

When enough authors are cited for a source, BibTeX may use the `\etalchar` command to display a math superscript with a + character to indicate "and others". Without modification, this will result in an "Improper `\prevdepth`" error. At present, lwarp requires that `\etalchar` be replaced by a text superscript. To do so, add to the start of the `.bib` file the following:

```
@PREAMBLE{"\let\etalchar\relax \newcommand{\etalchar}[1]{\textsuperscript{#1}}"}
```

9.6.10 gloss package

Pkg gloss

⚠ compiling

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

9.6.11 glossaries package

Pkg glossaries

processing glossaries

Opt GlossaryCmd

Default: makeglossaries

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

lwarpmk has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

The shell command to execute is set by the lwarp option `GlossaryCmd`, which defaults to **`makeglossaries`**. The print or HTML glossary filename is appended to this command.

⚠ *makeglossaries* not found

In some situations it may be required to modify the default command, such as to add the **`perl`** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and TOC options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style

The default `style=item` option for glossaries conflicts with lwarp, so the style is forced to `index` instead.

⚠ number list

The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions

The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

9.6.12 nomencl package

Pkg nomencl

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

9.6.13 Indexing overview

There are many ways to process indexes for a LaTeX document, including native LaTeX capabilities, a number of packages and classes, the possible availability of shell escape and *latexmk*, and the need to process print and HTML versions. lwarp attempts to provide easy recompilation of indexes along with the rest of the document, but the various indexing options must be set correctly. Numerous examples are given below. Some differ in minor details, so the important parts are highlighted in red, and options are in green.

Once set up properly, the entire document may be recompiled with **`lwarpmk print`** and **`lwarpmk html`**. In some cases, it will also be necessary to compile the indexes

with **`lwarpmk printindex`** and **`lwarpmk htmlindex`**. A recompile may then be forced with **`lwarpmk print1`** and **`lwarpmk html1`**.

manual processing

The user may continue to process indexes manually or by shell script without the use of *lwarpmk*, but adjustments will be required to process HTML indexes as well. In general, `*.idx` and `*.ind` files will be accompanied by `*_html.idx` and `*_html.ind` files.

custom index style

If using a custom indexing style file, see sections 9.6.19 and 9.6.20.

source code

See section 75 for lwarp's core index and glossary code, section 277 for index, section 423 for splitidx, section 276 for imakeidx, section 457 for tocbibind, and section 512.17 for memoir's indexing patches.

9.6.14 Indexing with basic LaTeX and makeidx

lwarpmk processing

The following allow the user to process indexes automatically, or using *lwarpmk*'s commands:

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

For a single index using *makeindex*:

```
\usepackage[makeindex,latexmk] {lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.ist` style file. When creating the HTML index, "`_html`" is automatically appended to each of the names.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For a single index using *xindy*:

```
\usepackage[
    xindy,
    xindyLanguage=english,                <optional>
    xindyCodepage=utf8,                   <optional>
    latexmk                               <optional>
]{lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

9.6.15 Indexing with index

lwarp is told how to use *makeindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

For multiple indexes using *makeindex* and index:

(Assuming that the second index has file extensions `.sist` and `.sind`)

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist
      -o <projectname>.sind <projectname>.sidx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist
      -o <projectname>_html.sind <projectname>_html.sidx
  }
]{lwarp}
\usepackage{index}
. . .
\makeindex
\newindex{secondname}{sidx}{sind}{Second Index}
```

⚠ WINDOWS *For WINDOWS, replace the two ";" characters with "&".*

When creating the HTML index, "`_html`" is automatically appended to the index filenames.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

If the `latexmk` option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **`lwarpmk printindex`** and **`lwarpmk htmlindex`** will still be required.

9.6.16 Indexing with splitidx

lwarp is told how to use *splitindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

If the `latexmk` option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **`lwarpmk printindex`** and **`lwarpmk htmlindex`** will still be required.

⚠ `\thepage` When using `\AtWriteToIndex` or `\AtNextWriteToIndex`, the user must not refer to

\thepage during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 512.17 in the lwarp-patch-memoir package for the \@@wrspindexhyp macro as an example.

For multiple indexes using *makeindex* and splitidx:

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    splitindex <projectname> -- -s lwarp.ist
  },
  HTMLIndexCmd={
    splitindex <projectname>_html -- -s lwarp.ist
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "_html" is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

For multiple indexes using *xindy* and splitidx:

```
\usepackage[
  xindy, latexmk,
  PrintIndexCmd={
    splitindex -m xindy <projectname> -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  },
  HTMLIndexCmd={
    splitindex -m xindy <projectname>_html -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "`_html`" is automatically appended to each of the names.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

9.6.17 Indexing with imakeidx

Due to the number of methods which may be used to process multiple indexes, the options for style file and *xindy* language and codepage must be specified in one of several different ways. These are described in detail later in this section, but are summarized here.

If shell escape is used, imakeidx will automatically compile the indexes by itself. Options specifying a custom style file and *xindy* language and codepage must be specified for each `\makeindex` command using its `options=` option, which must include lwarp's special `lwarp.ist` or `lwarp.xdy` file, or a file based on them. If using a custom indexing style file, see sections 9.6.19 and 9.6.20. The `splitindex` option is also available of shell escape is used, in which case the splitidx package and *splitindex* program will also be used.

If shell escape is not possible, *latexmk* may be used to automatically compile the indexes. The style, language, and codepage options are specified with lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options. These are passed to *latexmk* by *lwarpmk*'s **`lwarpmk printindex`** and **`lwarpmk htmlindex`** commands.

Where shell escape and *latexmk* are not possible, *lwarpmk* may be used to manually compile the indexes. lwarp's `PrintIndexCmd` and `HTMLIndexCmd` options are used.

For a single or multiple indexes using *makeindex* and imakeidx:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

imakeidx will automatically compile the indexes. Shell escape is not required while using *makeindex*. `latexmk` may be specified, and if so it will be used for **`lwarpmk print`** and **`lwarpmk html`**, but *imakeidx* will actually create the indexes.

For a single or multiple indexes using *makeindex* and *splitindex* with imakeidx:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

⚠ enable shell escape

Shell escape is required while using *splitindex*. For the first compile, use

Enter ⇒ **`pdflatex --shell-escape projectname.tex`**

Enter ⇒ **`pdflatex --enable-write18 projectname.tex`** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex*, and will also use *makeindex* to compile the indexes.

`latexmk` may be specified, and if so it will be used for **`lwarpmk print`** and **`lwarpmk html`**, but *imakeidx* will actually create the indexes.

For multiple indexes using *xindy* and imakeidx, using shell escape:

Options may be given to imakeidx's `\makeindex` command. The style file `lwarp.xdy` is automatically used for HTML output, and is not necessary for print output since the output will be similar. If language or codepage must be set, they should be specified as options for `\makeindex`, since imakeidx will process the indexes.

```
\usepackage[xindy,latexmk] {lwarp}
\usepackage[xindy,splitindex]{imakeidx}
. . .
\makeindex[
  options={ -M lwarp.xdy -L english -c utf8 }
]
\makeindex[
  name=secondname,
  options={ -M lwarp.xdy -L english -c utf8 }
]
```

⚠ enable shell escape

For the first compile, use

Enter ⇒ **pdflatex --shell-escape projectname.tex**

Enter ⇒ **pdflatex --enable-write18 projectname.tex** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex* if selected, and will also use *xindy* to compile the indexes.

If selected, *latexmk* will automatically recompile the entire document as necessary.

For indexes using *xindy* and *imakeidx*, without shell escape, but *with* *latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\usepackage[
  xindy,
  xindyLanguage=english,                    <optional>
  xindyCodepage=utf8,                       <optional>
  latexmk,
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

latexmk will create the indexes automatically when **lwarpmk print** and **lwarpmk html** are executed.

For indexes using *xindy* and *imakeidx*, without shell escape, and *without* *latexmk*:

lwarpmk must be told how to create the indexes:

```
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
\usepackage[xindy]{imakeidx}
. . .
\makeindex
\makeindex[name=secondname]
```

⚠ WINDOWS *For WINDOWS, replace the two ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

9.6.18 Indexes with memoir

For a single index with memoir and makeindex:

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.ist` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes with memoir and makeindex, using *latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically when the user executes **`lwarpmk print`** and **`lwarpmk html`**.

For multiple indexes with memoir and makeindex, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  makeindex,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist secondname.idx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist secondname_html.idx
  }
]{lwarp}
. . .
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS *For WINDOWS, replace the two ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For a single index with memoir and xindy:

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk                                   <optional>
]{lwarp}
. . .
\xindyindex
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes with memoir and xindy, using latexmk:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk
]{lwarp}
. . .
\xindyindex
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically.

For multiple indexes with memoir and xindy, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
. . .
\xindyindex
\makeindex
\makeindex[secondname]
```

⚠ WINDOWS *For WINDOWS, replace the four ";" characters with "&".*

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

9.6.19 Using a custom *makeindex* style file

Prog `makeindex`
File `lwarp.ist`

When using *makeindex*, *lwarpmk* uses the file `lwarp.ist` to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *makeindex* style file:

1. Copy `lwarp.ist` to a new filename such as `projectname.ist`
2. Make changes to `projectname.ist`. Keep the lines which refer to `\hyperindexref`. These lines creates the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

Opt `makeindexStyle`

3. In the document source use the `makeindexStyle` option for lwarp:

```
\usepackage[
    ... other options ...
```

```
    \textred{makeindexStyle=projectname.ist},
]{lwarp}
```

Likewise, refer to the custom style file if using \PrintIndexCmd, \HTMLIndexCmd, or \LatexmkIndexCmd.

4. Recompile the print version, which causes lwarp to rewrite the lwarpmk.conf configuration file. This tells *lwarpmk* to use the custom projectname.ist file instead of lwarp.ist.

9.6.20 Using a custom *xindy* style file

Prog xindy
File lwarp.xdy

When using *xindy*, *lwarpmk* uses the file lwarp.xdy to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *xindy* style file:

1. Copy lwarp.xdy to a new filename such as projectname.xdy
2. Make changes to projectname.xdy.

   Keep the lines which refer to \hyperindexref:

   ```
   (define-attributes (("hyperindexref")))
   (markup-locref :open "\hyperindexref{" :close "}")
   ...
   (markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
   ```

   These lines create the hyperlinks for the HTML index. During print output \hyperindexref becomes a null function.

   To create custom styles, refer to the lines for \textbf and \textit.

Opt xindyStyle

3. In the document source use the xindyStyle option for lwarp:

   ```
   \usepackage[
       ... other options ...
       \textred{xindyStyle=projectname.xdy},
   ]{lwarp}
   ```

   Likewise, refer to the custom style file if using \PrintIndexCmd, \HTMLIndexCmd, or \LatexmkIndexCmd.

4. Recompile the print version, which causes lwarp to rewrite the lwarpmk.conf configuration file. This tells *lwarpmk* to use the custom projectname.xdy file instead of lwarp.xdy.

9.6.21 Additional indexing limitations

⚠ xindy with hyperref

xindy and hyperref may not work well together for print output with “see”, “see also”, reference ranges, or stylized index references. It may be necessary to turn off hyper-referencing for indexes:

```
\usepackage[hyperindex=false]{hyperref}
```

⚠ empty index

If an HTML index is empty, it may be necessary to add the following before lwarp is loaded:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
. . .
\usepackage{lwarp}
```

makeindex custom display styles

When using *makeindex*, custom display styles are possible:

```
\begin{warpprint}
\newcommand{\notesstyle}[1]{#1nn}
\end{warpprint}

\begin{warpHTML}
\makeatletter
\newcommand{\notesstyle}[1]{\LWR@doindexentry{#1} notes }
\makeatother
\end{warpHTML}
. . .
A sentence.\index{key|notesstyle}
```

xindy custom display styles

For custom styles with *xindy*, see `lwarp.xdy` for `\textbf` and `\textit` as examples.

9.6.22 Index positions, TOC, tocbibind

placement and TOC options

An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind

On its own HTML page, with an automatic TOC entry:

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex

numbered index section

Use the tocbibind numindex option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

9.7 Math

9.7.1 Math in section names

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

9.7.2 Rendering tradeoffs

Math rendering

Math may be rendered as SVG graphics or using the MathJax JavaScript display engine.

SVG files

Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline

The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files

Others LaTeX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML

Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 11 regarding EPUB output with MathJax.

9.7.3 SVG option

SVG math option

For SVG math, math is rendered as usual by LaTeX into the initial PDF file using the current font[14], then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LaTeX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the LaTeX code which generated the math, allowing copy/paste of the LaTeX math expression into other documents.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

SVG math copy/paste

For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the LaTeX code for the math expression. For $\mathcal{AMS}$ environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred $\mathcal{AMS}$ environment, although the `\tag` macro will still appear inside the LaTeX math expression.

⚠ SVG math in TeX boxes

SVG math does not work inside TeX boxes, since a `\newpage` is required before and after each image.

9.7.4 MathJax option

MathJax math option

Prog MathJax

The popular MathJax alternative (`mathjax.org`) may be used to display math.

When MathJax is enabled, math is rendered twice:

1. As regular LaTeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LaTeX, and

[14] See section 499 regarding fonts and fractions.

2. As detokenized printed LaTeX commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current LaTeX values, and the MathJax cross-referencing system is ignored in favor of the LaTeX internal system, seamlessly integrating with the rest of the LaTeX code.

9.7.5 Customizing MathJax

MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

9.7.6 MathJax limitations

MathJax limitations
Prog MathJax

Limitations when using MathJax include:

subequations

- MathJax itself does not support subequations. This may be improved by parsing the LaTeX math expression to manually insert tags, but this has not yet been done.

footnotes in math

- Footnotes inside equations are not yet supported while using MathJax.

lateximage

- Math appearing inside a lateximage, and therefore also inside a Ti*k*z or `picture` environment, is rendered as SVG math even if MathJax is used in the rest of the document.

siunitx

⚠ siunitx inside an equation

- Usage of siunitx inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

  https://github.com/burnpanck/MathJax-siunitx

  Also see section 9.7.11.

tabbing

- A `tabbing` environment is emulated using an HTML `<pre>`.While MathJax is enabled inside `tabbing`, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

⚠ other macros and packages

- Other math-related macros and packages are not supported by MathJax, including `\ensuremath` and bigdelim, along with occasionally-used macros such as `\relax`. lwarp emulates footnotes, units, and nicefrac for MathJax.

9.7.7 Catcode changes

preamble macros with math

The math shift character $ is not set for HTML output until after the preamble. Macros defined in the preamble which contain $ must be enclosed between \StartDefiningMath and \StopDefiningMath to temporarily change to the HTML meaning of $:

```
\StartDefiningMath
\newcommand{. . . }
\StopDefiningMath
```

As an alternative, use \(and \) instead of $, in which case \StartDefiningMath and \StopDefiningMath are not necessary.

If a package defines macros using $, it may be nessary to use \StartDefiningMath and \StopDefiningMath before and after loading the package.

9.7.8 Complicated inline math objects

\inlinemathnormal
\inlinemathother

changing contents

complicated alt tag

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as $x+1$, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an alt tag. The macro \inlinemathother may be used before a dynamic math expression, and \inlinemathnormal after. Doing so tells lwarp to use an unhashed SVG math image, even if MathJax is in use. See section 44.

9.7.9 Complicated display math objects

\displaymathnormal

By default, or when selecting \displaymathnormal, MATHJAX math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother

MathJax unsupported

complicated alt tag

When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MATHJAX and will not make sense as an HTML alt tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

9.7.10 ntheorem package

Pkg ntheorem

⚠ Font control

This conversion is not total. Font control is via CSS, and the custom LaTeX font settings are ignored.

⚠ Equation numbering

ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environmentswhen the option `thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's `thref` option.

9.7.11 siunitx package

Pkg siunitx

fractions

Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required

Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first.

⚠ tabular

Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

9.7.12 units and nicefrac packages

Pkg units

Pkg nicefrac

units and nicefrac work with lwarp, but MathJax does not have an extension for units or nicefrac. These packages do work with lwarp's option `svgmath`.

9.7.13 newtxmath package

Pkg newtxmath

⚠ loading sequence

The proper load order is:

```
...
\usepackage{lwarp}
...
\usepackage{amsthm}
\usepackage{newtxmath}
...
```

9.8 Graphics

Pkg graphics

Pkg graphicx

⚠ scale

Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

`\includegraphics` file formats

For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps`

image file for use in print mode, and also a .svg, .png, or .jpg version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the .pdf or .eps format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf or .eps image is referred to with its file extension, the extension will be changed to .svg for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo

PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **pdftocairo -svg filename.pdf**

Prog lwarpmk pdftosvg

For a large number of images, use *lwarpmk*:

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

Prog lwarpmk epstopdf

Prog epstopdf

epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **lwarpmk pdftosvg *.PDF**

to convert to SVG images.

DVI latex

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **lwarpmk epstopdf *.eps** **(or a list of filenames)**

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

PNG and JPG

For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF

GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities

If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx

⚠ viewport

⚠ viewport units

If using the older graphics syntax, use both optional arguments for \includegraphics. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

For \includegraphics, avoid px and % units for width and height, or enclose them inside warpHTML environments. For font-proportional image sizes, use ex or em. For fixed-sized images, use cm, mm, in, pt, or pc. Use the keys width=.5\linewidth, or similar for \textwidth or \textheight to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the scale option, since it is not well supported by HTML browsers.

options

\includegraphics accepts width and height, origin, rotate and scale, plus new class and alt keys.

HTML class

With HTML output, \includegraphics accepts an optional class=xyz keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML alt tags

Likewise, the \includegraphics alt key adds an HTML alt tag to an image, and is ignored for print output. If not assigned, each image is given an alt tag of "(image)".

\rotatebox

\rotatebox accepts the optional origin key.

⚠ browser support

\rotatebox, \scalebox, and \reflectbox depend on modern browser support. The css3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

9.8.1 tikz package

Pkg tikz

⚠ displaymath and matrices

If using display math with tikzpicture or \tikz, along with matrices with the & character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of & in the tikz expression must be replaced with \&.

9.8.2 grffile package

Pkg grffile

⚠ matching PDF and SVG

grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

9.8.3 color package

Pkg color

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

9.8.4 xcolor package

Pkg xcolor

\colorboxBlock and \fcolorboxBlock

\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a instead of a . These s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none

\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes required.

colored tables

\rowcolors is supported, except that the optional argument is ignored so far.

colored text and boxes

\textcolor, \colorbox, and \fcolorbox are supported.

\color and \pagecolor

\color and \pagecolor are ignored. Use CSS or \textcolor where possible.

9.8.5 epstopdf package

Pkg epstopdf

⚠ convert to .svg

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

9.8.6 pstricks package

Pkg pstricks

⚠ use pspicture

All pstricks content should be contained inside a pspicture environment.

9.8.7 pdftricks package

Pkg pdftricks

⚠ convert image files

The pdftricks image files <jobname>-fig*.pdf must be converted to .svg, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **lwarpmk pdftosvg <jobname>-fig*.pdf**

9.8.8 psfrag package

Pkg psfrag

⚠ use psfrags

The psfrags environment is modified to use lateximage to encapsulate the image. Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

9.8.9 pstool package

Pkg pstool

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename

The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

9.8.10 asymptote package

Pkg asymptote

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

9.8.11 overpic package

Pkg overpic

⚠ scaling

The macros \overpicfontsize and \overpicfontskip are used during HTML generation. These are sent to \fontsize to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the overpic and Overpic environments.

9.9 Tabbing

The tabbing environment works, except that SVG math and lateximages do not yet work inside the environment.

⚠ math in tabbing

If math is used inside tabbing, place tabbing inside a lateximage environment, which

will render the entire environment as a single SVG image.

9.10 Tabular

9.10.1 `tabular` environment

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, * column specifiers, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include `tabular` and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDeferingTabulars
<define macros or environments using tabular and & here>
\StopDeferingTabulars
```

⚠ floatrow

This includes before and after defining any macro which used `\ttabbox` from floatrow.

⚠ `tabular` inside another environment

- When creating a new environment which contains a `tabular` environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDeferingTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDeferingTabulars
```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use `\TabularMacro` just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

⚠ * column specification

- * in a column specification is not used (so far). Repeat the column type the correct number of times.

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

⚠ \newcolumntype

- \newcolumntype is ignored; unknown column types are set to l.

Rules:

- Doubled \hlines, \midrules, and vertical rules are supported.

vertical rules

- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

full-width rules

- \toprule, \midrule, \bottomrule, and \hline ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional -2ex is ignored in HTML, but improves the visual formatting in the print output.

⚠ \warpprintonly
⚠ Misplaced \noalign

- For \toprule and \bottomrule, when combined with a warpprint or warpHTML environment, if a "Misplaced \noalign" error occurs, change

```
This & That \endhead
```

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevent to HTML output.

Other:

- tabularx ignores the width, but X columns do produce paragraph columns or multicolumns.

longtable headings

- For longtable, place headings and footings which do not apply to HTML inside \warpprintonly{}.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as \multirow. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

9.10.2 multirow package

vposn

- Note that recent versions of multirow include a new optional vposn argument.

multirow cells

- For multirow, insert \mrowcell into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
. . . &   \multirow{2}{.5in}{text}   & . . .
. . . &   \mrowcell                  & . . .
```

colored cells

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.

with \multicolumn

- See section 325.2 for \multicolumrow.

⚠ \multicolumn & \multirow

lwarp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

⚠ skipped cells

⚠ empty cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines, \mcolrowcell must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```
. . . &   \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}   & . . .
. . . &   \mcolrowcell          &          \mcolrowcell   & . . .
. . . &   \mcolrowcell          &          \mcolrowcell   & . . .
```

9.10.3 longtable package

Pkg longtable

Use one of either \endhead or \endfirsthead for both print and HTML, and use a \warpprintonly macro to disable the other head phrase, and also the \endfoot and \endfirstfoot phrases. (See section 9.10.4 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{         % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced \noalign

Use the \warpprintonly macro instead of the warpprint environment. Doing so helps avoid "Misplaced \noalign." when using \begin{warpprint}.

⚠ \kill

\kill is ignored, place a \kill line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside \warpprintonly.

⚠ lateximage

longtable is not supported inside a lateximage.

9.10.4 threeparttablex package

Pkg threeparttablex

threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{         % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width

The table notes are created using a \multicolumn. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use \UseMinipageWidths before \insertTableNotes. The width is then specified, and in many cases the result is an improvement in overall table layout.

9.10.5 supertabular and xtab packages

Pkg supertabular

Pkg xtab

⚠ Misplaced alignment tab character &

For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 9.10.1.

⚠ lateximage

supertabular and xtab are not supported inside a lateximage.

9.10.6 colortbl package

Pkg colortbl

⚠ row/cell color

Only use \rowcolor and \cellcolor at the start of a row, in that order.

colortbl ignores the overhang arguments.

9.10.7 ctable package

⚠ Misplaced alignment tab character &

Use \StartDefiningTabulars before one or more \ctables, and \StopDefiningTabulars after. These change the meaning of the ampersand & character.

9.10.8 bigdelim package

Pkg bigdelim

⚠ use \mrowcell

\ldelim and \rdelim use \multirow, so \mrowcell must be used in the proper number of empty cells in the same column below \ldelim or \rdelim, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

<->	a	b
left	c	d
	e	f
	g	h
<->	i	j

9.11 Floats

9.11.1 Float contents alignment

⚠ figure & table alignment

\centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

9.11.2 float, trivfloat, and/or algorithmicx together

Pkg float
Pkg trivfloat
Pkg algorithmicx
⚠ package conflicts

If using \newfloat, trivfloat, and/or algorithmicx together, see section 468.1.

9.11.3 caption and subcaption packages

Pkg caption
Pkg subcaption
⚠ options

To pass options to caption, select the options before loading lwarp:

```
\documentclass{article}
. . .
\PassOptionsToPackage{options_list}{caption}
. . .
\usepackage{lwarp}
. . .
\usepackage{caption}
```

⚠ numbering

To ensure proper float numbering, set caption positions such as:

```
\captionsetup[figure]{position=bottom}
\captionsetup[subfigure]{position=bottom}
\captionsetup[table]{position=top}
\captionsetup[subtable]{position=top}
```

Similarly for longtable. These positions depend on where the user places the \caption command inside each float.

9.11.4 subfig package

Pkg subfig

⚠ lof/lotdepth

At present, the package options for lofdepth and lotdepth are not working. These counters must be set separately after the package has been loaded.

In the document source, use \hfill and \hspace* subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

9.11.5 floatrow package

Pkg floatrow
⚠ Misplaced alignment tab character &
⚠ subfig package

Use \StartDefiningTabulars and \StopDefiningTabulars before and after defining macros using \ttabbox with a tabular inside. See section 9.10.1.

When combined with the subfig package, while inside a subfloatrow \ffigbox and \ttabbox must have the caption in the first of the two of the mandatory arguments.

⚠ \FBwidth, \FBheight

The emulation of floatrow does not support \FBwidth or \FBheight. These values are pre-set to .3\linewidth and 2in. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use warpprint and warpHTML environments to select appropriate values for each case.
- Inside a warpHTML environment, manually change \FBwidth or \FBheight before the \ffigbox or \ttabbox. Use \FBwidth or \FBheight normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

9.11.6 keyfloat package

Pkg keyfloat

⚠ keywrap

If placing a \keyfig[H] inside a keywrap, use an absolute width for \keyfig, instead of lw-proportional widths. (The [H] option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the lw option.)

9.12 Koma-Script classes

Cls komascript

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

\titlehead, \subject, \captionformat, \figureformat, and \tableformat are not yet emulated.

⚠ Not fully tested! Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

9.13 Memoir class

Cls memoir

⚠ options clash

While emulating memoir, lwarp pre-loads a number of packages (section 512.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

\verbfootnote is not supported.

\newfootnoteseries, etc. are not supported.

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in \pagenotesubhead and related macros.

Poem numbering is not supported.

The verbatim environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

9.14 International languages

⚠ section and file names

If using *pdflatex* with the setting \booltrue{FileSectionNames}, non-ASCII text in section names can result in corrupted HTML file names. *pdflatex* may be used if setting \boolfalse{FileSectionNames}, in which case HTML file numbers will be generated.

For correct HTML file names, use *xelatex*, *lualatex*, or dedicated document classes / engines.

(As of this writing, this warning is only relevent to the kotex package.)

9.15 Miscellaneous packages

9.15.1 verse and memoir

Pkg verse

When using verse or memoir, always place a \\ after each line.

Cls memoir

\attrib

The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip

Len \vleftmargini

Len \HTMLvleftskip

Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of

\HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

9.15.2 newclude package

Pkg newclude

⚠ loading

newclude modifies \label in a non-adaptive way, so newclude must be loaded before lwarp is loaded:

```
\documentclass{article}
. . . <font setup>
\usepackage{newclude}
\usepackage[warpHTML]{lwarp}
. . .
```

9.15.3 babel package

Pkg babel

⚠ \CaptionSeparator

When French is used, the caption separator is changed to a dash. The following may be used to restore it to a colon:

```
\renewcommand*{\CaptionSeparator}{:~}
```

punctuation spaces

⚠ customized spacing

Also when French is used, lwarp creates fixed-width space around punctuation by patching \FBcolonspace, \FBthinspace, \FBguillspace, \FBmedkern, \FBthickkern, \FBtextellipsis, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a warpprint environment so that the user's changes do not affect the HTML output.

9.15.4 polyglossia package

Pkg polyglossia

lwarp uses cleveref, which has some limitations when using polyglossia, possibly resulting in the error

```
! Undefined control sequence. . . . \@begindocumenthook
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by cleveref, then select other languages using \setotherlanguages.

Once the print version works with cleveref and polyglossia, the HTML version should work as well using lwarp.

9.15.5 todonotes and luatodonotes packages

Pkg todonotes
Pkg luatodonotes

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

9.15.6 fixme

Pkg fixme

External layouts (\fxloadlayouts) are not supported.

⚠ external layouts

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

9.15.7 chemfig package

If using \polymerdelim to add delimiters to a \chemfig, wrap both inside a single lateximage:

```
\begin{lateximage}[(-chemfig-~\packagediagramname)]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

9.15.8 chemformula package

⚠ chemformula with MathJax

chemformula works best without MathJax. If MathJax is used, \displaymathother must be used before array, and then \displaymathnormal may be used after. (The chemformula package adapts to array, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, \displaymathother may also be used for other forms of display and inline math which contain chemformula expressions.

9.15.9 mhchem package

See section 314.

9.15.10 xparse package

Pkg xparse To remove from the log any warnings about redeclaring objects, place the following before lwarp is loaded:

```
\usepackage[log-declarations=false]{xparse}
```

9.15.11 kotex package

Pkg kotex See section 9.14 regarding *pdflatex* and Korean section names.

⚠ Korean section names

10 Compiling using custom shell commands

lwarp and *lwarpmk* try to make it easy to process print and HTML compilation tasks in most situations. Depending on the operating system, command-line options, TEX engine, and lwarp options, the commands **`lwarpmk print`** and **`lwarpmk html`** are automatically set up to correctly recompile the project. These actions may be overridden using lwarp options, thus allowing the use of packages such as perltex and pythontex.

10.1 Command options

Opt `PrintLatexCmd`
Opt `HTMLLatexCmd`

The lwarp options `PrintLatexCmd` and `HTMLLatexCmd` are used to set customized commands to be executed by **`lwarpmk print`** and **`lwarpmk html`**.

`PrintLatexCmd` should be set to shell commands which take `project.tex` and generate `project.pdf`.

`HTMLLatexCmd` should be set to take `project_html.tex` and generate `project_html.pdf`. *lwarpmk* will then take `project_html.pdf` and automatically convert it and generate `project.html`.

10.2 Literal character macros

The lwarp package options are parsed by TEX, and so some characters require the use of a special macro to represent them. See table 7. `\LWRopquote` and `\LWRopseq` may be used to increase operating-system portability. `\jobname` must have `_html` appended for processing HTML. `\space` may be necessary between other macros.

⚠ macro not found

To use these macros, either kvoptions-patch must be loaded before lwarp:

```
\usepackage{kvoptions-patch}
\usepackage[
    PrintLatexCmd={ ... } ,
    HTMLLatexCmd={ ... }
]{lwarp}
```

Table 7: Literal character macros

Character	Macro	Comment
%	\LWRpercent	
$	\LWRdollar	
&	\LWRamp	
%	\LWRhash	
\	\LWRbackslash	
' or "	\LWRopquote	Depends on the operating system.
& or &&	\LWRopseq	Depends on the operating system.
(space)	\space	Forces an extra space.
(jobname)	\jobname	Without file extension.

or \lwarpsetup must be used to set PrintLatexCmd and HTMLLatexCmd:

```
\usepackage[...]{lwarp}
\lwarpsetup{
  PrintLatexCmd=
      {
          latex tm \LWRopseq
          dvips -o tm-pics.ps tm.dvi \LWRopseq
          ps2pdf tm-pics.ps \LWRopseq
          pdflatex tm.tex
      } ,
  HTMLLatexCmd=
      {
          latex tm_html \LWRopseq
          dvips -o tm_html-pics.ps tm_html.dvi \LWRopseq
          ps2pdf tm_html-pics.ps \LWRopseq
          pdflatex tm_html.tex
      }
}
```

10.3 *latexmk*

Prog latexmk If *latexmk* is used for a project, it may be easiest to continue using it.

latexmk project.tex would create project.pdf as normal.

latexmk project_html.tex would create project_html.pdf, then

lwarpmk pdftohtml project_html.pdf would take project_html.pdf and convert it to project.html.

Pkg sagetex *latexmk* may simplify the use of packages such as sagetex.

10.4 perltex package

Pkg perltex The lwarp package option settings to use perltex would be similar to:

```
\usepackage[
  . . .
  PrintLatexCmd={perltex -latex=pdflatex project.tex} ,
  HTMLLatexCmd={perltex -latex=pdflatex project_html.tex} ,
  . . .
]{lwarp}
```

⚠ "impure" math Place perltex math expressions between `\displaymathother` and `\displaymathnormal`, or `\inlinemathother` and `\inlinemathnormal`. See section 9.7.9.

10.5 pythontex package

Pkg pythontex An example using pythontex:

```
\usepackage[
  . . .
  PrintLatexCmd={
    pdflatex project.tex \LWRopseq
    pythontex project \LWRopseq
    pdflatex project.tex
  } ,
  HTMLLatexCmd={
    pdflatex project_html.tex \LWRopseq
    pythontex project_html \LWRopseq
    pdflatex project_html.tex
  } ,
  . . .
]{lwarp}
```

Another possibility is to use *latexmk*, placing the **`latexmk . . .`** commands in the `PrintLatexCmd` and `HTMLLatexCmd` options. While using these options, the lwarp option `latexmk` would not be used.

⚠ "impure" math ⚠ HTML look-alike No attempt has yet been made to make pythontex robust with HTML output. Some math objects must be surrounded by `\displaymathother` ... `\displaymathnormal`, or `\inlinemathother` ... `\inlinemathnormal`. Displays of code may have to be enclosed inside a `lateximage` environment to prevent <, > and similar from being interpreted by the browser as HTML entities.

10.6 Other packages

Pkg sympytex Pkg rterface Other packages such as sympytex and rterface would be set up similar to pythontex,

and the same warnings would apply.

10.7 *make* program

Prog make

To use lwarp with the *make* program, have the `makefile` take `project.tex` and generate the print version `project.pdf`, as normal. `\usepackage{lwarp}` must be used, and it generates `lwarpmk.conf` when the print version is created.

To generate HTML, first have `project_html.tex` be compiled to generate `project_html.pdf`. This must be in PDF format. Finally, have `project_html.pdf` be converted to HTML using **`lwarpmk pdftohtml project_html.pdf`**, and convert SVG math with **`lwarpmk limages`**.

10.8 UTF-8 locale

⚠ UTF-8 locale

lwarpmk uses the *texlua* program, which sets the "locale" to "C", including for external operating-system calls such as when executing **`lwarpmk html`**. In some cases, an external program called from the user's document may require the use of a UTF-8 "locale". For UNIX-related operating systems, it may be required to use lwarp's custom compilation options to add a locale change:

```
\usepackage{lwarp}[
  PrintLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex --shell-escape project.tex
  }
  HTMLLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex --shell-escape project_html.tex
  }
]
```

Pkg ditaa

The only example seen so far where this is required is the ditaa package, where the locale change allows the use of UTF-8 with XeLaTeX and ditaa. To use LuaLaTeX instead, the locale change would have to be made inside the ditaa package where its calls the *ditaa* program.

11 EPUB conversion

lwarp does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

<meta> author

To assign the author's name for regular lwarp HTML files, and also for the EPUB, use `\HTMLAuthor {⟨name⟩}`. This assigns the name to the `<meta>` author element. It may be set empty, and it defaults to `\theauthor`.

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

`FormatEPUB`

Bool `FormatEPUB`
Default: `false`

`FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

To help convert lwarp HTML output to EPUB, add

```
\booltrue{FormatEPUB}
```

to the project's source preamble after `\usepackage{lwarp}`. The EPUB version of the document cannot co-exist with the regular HTML version, so

Enter ⇒ **`lwarpmk cleanall`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk limages`**

to recompile with the `FormatEPUB` boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.

Calibre

The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program *Calibre* (`https://calibre-ebook.com/`).

⚠ search order

The EPUB conversion program must know what order the files are included. For lwarp projects, set the EPUB conversion software to do a breadth-first search of the files. For *Calibre*, this option is found in

Preferences → Plugins → File type plugins → HTML to Zip

⚠ encoding

Check the box Add linked files in breadth first order. Set the document encoding as `utf-8`, which is what lwarp generates for HTML, even if the original printed document uses some other encoding.

⚠ section breaks

The EPUB-conversion program must also know where the section breaks are located. For a list of lwarp's section headings, see table 9. For example, an `article` class document would break at `\section`, which is mapped to HTML heading level `<h4>`, whereas a `book` class document would break at `\chapter`, which is HTML heading level `<h3>`. For *Calibre*, this option is found in

Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)

Select the "magic wand" to the right of this entry box, and set the first entry

Match HTML tags with tag name:

to "h4". (Or "h3" for document classes with `\chapters`.) The Detect chapters at field should then show

//h:h4 — or — **//h:h3**

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the lwarp-generated HTML files may be loaded by *Calibre*, and then converted to an EPUB.

MATHJAX support

MATHJAX may be used in EPUB documents. Some e-readers include MATHJAX, but any given reader may or may not have a recent version, and may or may not include extensions such as support for siunitx.

lwarp adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader's version of MATHJAX, so lwarp requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn't work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MATHJAX, especially for equations numbered by chapter, or where siunitx support is important.

12 Word-processor conversion

lwarp may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LibreOffice works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. lwarp provides some assistance in locating these frame boundaries, as shown below.

12.1 Activating word-processor conversion

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

`FormatWP`

Bool `FormatWP`
Default: `false`

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Additionally, honors the booleans `WPMarkFloats`, `WPMarkMinipages`, `WPMarkTOC`, and `WPMarkLOFT`.

To help modify lwarp HTML output for easier import to a word processor, add

```
\booltrue{FormatWP}
```

to the project's source preamble after lwarp is loaded. The following changes are then made to the HTML output:

formatting adjustments

- If using a class without chapters, `\section` and lower are shifted up in level for the HTML heading tags. The CSS has not been changed, so the section heading formats will not match the normal HTML output, but when imported to *LibreOffice Writer* the higher section headings will import as **Heading 1** for the title, **Heading 2** for `\section`, etc.
- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and `<div>`s, but they are no longer useful when the document has been imported into a word processor.
- An additional `<div>` with an `id` encapsulates each float and minipage, which on import into *LibreOffice Writer* causes a thin frame to appear around the text block for each.
- Float captions are given an explicit italic formatting.

- Tabular rule borders are made explicit for *LibreOffice Writer*. LibreOffice displays a light border around each cell while editing, even those which have no border when printed, and lwarp also uses a light border for thin rules, so it will be best to judge the results using the print preview instead of while editing in LibreOffice.
- `\includegraphics` and svg math width and height are made explicit for LibreOffice.
- `\hspace` is approximated by a number of `\quad`s, and rules are approximated by a number of underscores.
- Explicit html styles are given to:
  - `\textsc`, etc.
  - `\underline`, soul and ulem markup.
  - `center`, `flushleft`, `flushright`.
  - `\marginpar`, keyfloat, sidenotes, floatflt, and wrapfig.
  - fancybox `\shadowbox`, etc.
  - The LaTeX and TeX logos.
- Honors several booleans:

  WPMarkFloats: Marks the begin and end of floats.

  WPMarkMinipages: Marks the begin and end of minipages.

  WPMarkTOC: Marks the location of the Table of Contents.

  WPMarkLOFT: Marks the locations of the List of Figures/Tables.

  WPMarkMath: Prints LaTeX math instead of using images.

  WPTitleHeading: Adjusts title and section headings.

  Several of these may be used to add markers to the html text which help determine where to adjust the word processor document after import.

12.2 Additional modifications

`WPMarkFloats`

Bool `WPMarkFloats`
Default: `false`

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.

WPMarkMinipages

Bool WPMarkMinipages
Default: false

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

WPMarkTOC

Bool WPMarkTOC
Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set `false`*, the actual TOC is printed instead.*

WPMarkLOFT

Bool WPMarkLOFT
Default: false

While formatting for word processors, adds

```
=== list of figures ===
=== list of tables ===
```

and/or

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

WPMarkMath

siunitx
Bool WPMarkMath
Default: false
Prog TeXMaths

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

When using the siunitx package, enter

```
\usepackage{siunitx}
```

in the *TeXMaths* preamble. Equation numbering is problematic for $\mathcal{AMS}$ math environments.

Table 8: Section HTML headings for word-processor conversion

	HTML headings*			
	With \chapter		Without \chapter	
	WPTitleHeading		WPTitleHeading	
Section	true	false	true	false
Title	<h1>	plain	<h1>	plain
\part	<h2>	<h1>	<h2>	<h1>
\chapter	<h3>	<h2>	—	—
\section	<h4>	<h3>	<h3>	<h2>
\subsection	<h5>	<h4>	<h4>	<h3>
\paragraph	<h6>	<h5>	<h5>	<h4>
\subparagraph	span	<h6>	<h6>	<h5>

* For default depths when not FormatWP, see table 9 on page 194.

WPTitleHeading

Bool WPTitleHeading
Default: false
section headings

While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 180.

12.3 Recommendations

TOC, LOF, LOT

For use with *LibreOffice Writer*, it is recommended to:

1. Set \booltrue{FormatWP}
2. Set \booltrue{WPMarkTOC} and \boolfalse{WPMarkLOFT}
3. Use lwarp to generate the HTML document.
4. Copy/paste from the HTML document into an empty *LibreOffice Writer* document.
5. Manually insert a LibreOffice TOC in the LibreOffice document.
6. Manually add frames around each float, adding a caption which is cut/pasted from each float's simulated caption.
7. Manually create cross references.

This process yields a document with an actual LibreOffice Table of Contents, but a simulated List of Figures and List of Tables.

siunitx

For siunitx, remember to adjust the preamble as mentioned above.

LO view border options

LibreOffice has options in the **View** menu to turn on/off the display of thin borders around table cells and text objects.

12.4 Limitations

Floats and captions are not explicitly converted to LibreOffice floats with their own captions. Floats are surrounded by a thin frame in the LibreOffice editor, and may be marked with `WPMarkFloats`, but are not given a proper LibreOffice object frame. Captions are given an explicit italic formatting, but not a proper LibreOffice paragraph style.

Cross references are not actual LibreOffice linked cross references.

The List of Figures and List of Tables are not linked. The pasted pseudo LOF and LOT match the numbering of the LaTeX and HTML versions.

Equation numbering is not automatic, but the equation numbers in SVG math will match the LaTeX and HTML output. SVG math is recommended when using the $\mathcal{AMS}$ environments, which may have multiple numbered equations per object.

As of when last checked, LibreOffice ignores the following:

- Minipage alignment.
- Tabular cell vertical alignment.
- Image rotation and scaling.
- Rounded border corners, which are also used by:
  - `\textcircled`
  - booktabs trim
- `\hspace` and rules, also used by algorithmic.
- Coloring of text decorations, used by soul and ulem.
- Overline text decoration, used by romanbar.

LibreOffice also has limitations with frames and backgrounds:

- Multiple lines in an object are framed individually instead of as a whole.
- Nested frames are not handled correctly.
- Images inside boxes are not framed correctly.
- Spans with background colors and frames are not displayed correctly.

13 Modifying lwarp

locating something

To quickly find the source for a package in `lwarp.dtx`, search for `*packagename`, such as `*siunitx`.

Likewise, to quickly find the source for a file in `lwarp.dtx`, search for `*filename`, such as `*lwarp.css`.

Purely text-based packages probably will work as-is when generating HTML.

Look to existing code for ideas on how to expand into new code.

image of TEX output

An environment may be converted to a `lateximage` then displayed with an image of the resulting LATEX output. See section 87 for an example of the `picture` environment.

CSS classes

To create a custom HTML block or inline CSS class, see section 51.9.

print/HTML macros

To create print and HTML versions of the same macro or environment, see section 36.

⚠ TEX boxes

Any TEX boxes must be undone, as SVG math or `lateximages` require `\newpage`, which will not work in a TEX box.

index recreation

To recreate the index for the lwarp documentation:

```
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
splitindex lwarp.idx -- -s gind.ist
```

13.1 Creating a development system

The following creates a local development system for lwarp on a TeXLive system in a UNIX-like environment. Doing so allows anything requesting lwarp to use the development version instead of whichever version is installed in TeXLive.

Create a development directory:

Place into this directory `lwarp.dtx` and `lwarp.ins`.

To create `lwarp.sty`, execute

Enter ⇒ **`pdflatex lwarp.ins`**

which creates `lwarp.sty` and several hundred additional `lwarp-*.sty` files for the various packages which are supported.

To create the documentation `lwarp.pdf`, execute

Enter ⇒ **`pdflatex lwarp.dtx`**

To make the development files visible to other projects:

Create the directory

`/usr/local/texlive/texmf-local/tex/latex/local/lwarp`

Inside this directory, create the file update, containing:

```
ln -s /path_to_dev_directory/lwarp*.sty .
ln -s /path_to_dev_directory/lwarp_baseline_marker.png .
ln -s /path_to_dev_directory/lwarp_baseline_marker.eps .
mktexlsr
```

Run ./update now, and whenever a new lwarp-* package is added.

To make the development version of *lwarpmk* visible to other projects:

```
cd /opt
ln -s /usr/local/texlive/texmf-local/bin/x86_64-linux texbin_local
cd texbin_local
ln -s ../../scripts/lwarp/lwarpmk.lua lwarpmk
cd /usr/local/texlive/texmf-local/scripts/
mkdir lwarp
cd lwarp
ln -s /path_to_dev_directory/lwarpmk.lua lwarpmk
```

Verify that the correct version is found with

Enter ⇒ **`which lwarpmk`**

To make the local versions visible to the shell:

Paths must be set by the shell startup, such as in .bashrc and .cshrc:

In .bashrc:

```
PATH=/opt/texbin_local:/opt/texbin:$PATH
```

In .cshrc:

```
setenv PATH ${HOME}/bin:/opt/texbin_local:/opt/texbin:${PATH}
```

13.2 Modifying a package for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

When creating HTML, lwarp redefines the \usepackage and \RequirePackage macros such that it first looks to see if a lwarp-<packagename>.sty version exists. If so, the lwarp version is used instead. This modular system allows users to create their own versions of packages for lwarp to use for HTML, simply by creating a new package with

a lwarp- prefix. If placed in the local directory along with the source code, it will be seen by that project alone. If placed alongside the other lwarp- packages where TEX can see it, then the user's new package will be seen by any documents using lwarp. (Remember mktexlsr or texhash.)

An lwarp-<packagename>.sty package is only used during HTML generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful HTML conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing lwarp- packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new lwarp- package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a "local" prefix according to the package name, and @ characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for HTML output. Only the "user-facing" macros need to be nullified or emulated.

Each lwarp-* package should first call either of:

```
\LWR@ProvidesPackageDrop
  -or-
\LWR@ProvidesPackagePass
```

If "Drop"ped, the original print-version package is ignored, and only the lwarp- version is used. Use this where the original print version is useless for HTML. If "Pass"ed, the original package is loaded first, with the user-supplied options, then the lwarp- version continues loading as well. See section 343 (ntheorem) for an example of selectively disabling user options for a package. Use this when HTML output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a lwarp- version.

13.2.1 Adding a package to the lwarp.dtx file

When adding a package to lwarp.dtx for permanent inclusing in lwarp, provide the lwarp-<packagename> code in lwarp.dtx, add its entry into lwarp.ins, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to lwarp.dtx in section 21.1. This causes lwarp to stop with an error if packagename is loaded before lwarp. Finally, add an entry in table 2, Supported packages and features, and also the Updates section.

13.3 Modifying a class for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

13.4 Testing lwarp

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

Remember that the configuration files are only rewritten when compiling the printed version of the document.

When changing the source to *lwarpmk* or a CSS file in `lwarp.dtx`:

1. Change the source in `lwarp.dtx`.
2. `pdflatex lwarp.ins`
3. `pdflatex lwarp.dtx`
4. If modifying *lwarpmk* the new version should now be active.
5. If modifying CSS files:
   (a) For the document, `lwarpmk print` to update the CSS files in the project.
   (b) Reload the HTML document to see the effect of the new CSS files.

Sometimes it is worth checking the `<project>_html.pdf` file, which is the PDF containing HTML tags. Also, `<project>_html.html` has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and CSS code.

13.5 Modifying *lwarpmk*

Prog `lwarpmk`
File `lwarpmk.lua`

In most installations, `lwarpmk.lua` is an executable file located somewhere the operating system knows about, and it is called by typing **`lwarpmk`** into a terminal.

A project-local copy of `lwarpmk.lua` may be generated, modified, and then used to compile documents:

1. Add the `lwarpmk` option to the lwarp package.
2. Recompile the printed version of the document. The `lwarpmk` option causes lwarp to create a local copy of `lwarpmk.lua`
3. The `lwarpmk` option may now be removed from the lwarp package.
4. Copy and rename `lwarpmk.lua` to a new file such as `mymake.lua`.

5. Modify `mymake.lua` as desired.
6. If necessary, make `mymake.lua` executable.
7. Use `mymake.lua` instead of `lwarpmk.lua`.

14 Troubleshooting

14.1 Using the lwarp.sty package

Also see:
Section 8.8: Commands to be placed into the `warpprint` environment
Section 9: Special cases and limitations

Text is not converting correctly / corrupted HTML tags:

- Font-related UTF-8 information must be embedded in the PDF file. See section 8.2 regarding bitmapped vs. vector fonts.
- See section 9.2.1 regarding HTML entities and the characters &, <, and >.

Undefined HTML settings:

- See the warning regarding the placement of the HTML settings at section 8.4.

Tabular problems: See section 9.10.1.

Obscure error messages:

Print first: Be sure that a print version of the document compiles and that your document's LaTeX code is correct, before attempting to generate an HTML version.

`\end{warpHTML}`, `\end{warpprint}`, `\end{warpall}`: Each of these must be without any other characters on the same line.

Options clash: If using memoir, see section 9.13.

"No room for a new `\write`.": Before `\usepackage{lwarp}`, add:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
```

"Missing $ inserted.": If using a filename or URL in a footnote or `\item`, escape underscores with `\_`.

"Label(s) may have changed. Rerun to get cross-references right.":

This warning may repeat endlessly if a math expression is used in a caption. Simple math expressions such as $X=1$ may be replaced with

```
\textit{X}\,=\,1
```

"Leaders not followed by proper glue": This can be caused by a missing `l@<floattype>` or `l@<sectiontype>` definition. See lwarp's definitions for examples.

"Improper `\prevdepth`": `lateximages` and SVG math require `\newpage`, which cannot work inside TeX boxes or `\ensuremath`. Anything using `\newsavebox`, `\newbox`, `lrbox`, `\savebox`, `\hbox`, `\vbox`, `\usebox`, `\sbox`, etc., must be modified to work without box commands.

If you find something using `\ensuremath`, have it temporarily set:

```
\LetLtxMacro\@ensuredmath\LWR@origensuredmath
```

inside a group first.

⚠ macros in section,table,figure names

Also, custom macros which appear inside a section, figure, or table name should be made robust since they appear inside the `.toc`, `.lof`, or `.lot` files. Use `\newrobustcmd` or `\robustify` from etoolbox, xparse, etc.

⚠ BibTeX

If using BibTeX, see section 9.6.9.

⚠ polyglossia

"! Undefined control sequence. . . . \@begindocumenthook'': See section 9.15.4 if using polyglossia.

⚠ custom macros for environments

"\begin{equation} ended by \end{document}": Do not use custom macros such as `\beq` and `\eeq` to replace

```
\begin{equation}
. . .
\end{equation}
```

⚠ `\LWR@formatted`

"Misplaced \omit": If using `\LWR@formatted` to define new macros for print and HTML modes, see section 36 regarding `\LWR@expandableformatted`.

⚠ "impure" math objects

Complicated objects inside math: Some objects, such as Ti*k*z, may not compile in lwarp's normal math emulation. Insert

```
\displaymathother -or- \inlinemathother
```

before the math, and then

```
\displaymathnormal -or- \inlinemathnormal
```

when displaying "normal" math. See section 9.7.9.

Slow compliation of math objects: Complicated math objects can also cause problems with `alt` tags, resulting in very slow compilation, large `alt` tags, and possible crashes. Use `\inlinemathother` ...`\inlinemathnormal` or `\displaymathother` ...`\displaymathnormal` around the math expression.

⚠ MathJax
⚠ MathJax

Incorrect MathJax: Some objects do not convert to MathJax. Use `\displaymathother` before these objects, then `\displaymathnormal` to return to "normal" display math. See section 9.7.9.

Missing sections: See section 8.4 regarding the `FileDepth` and `SideTOCDepth` counters, and the use of `\tableofcontents` in the home page.

Misnumbered footnotes from section headings: See section 9.5.4.

Missing HTML files:

- See the warning regarding changes to the HTML settings at section 8.4.
- Ensure that the filenames are unique after math and short words are removed. See `FileSectionNames` at section 8.4.

Missing / incorrect cross-references:

- Use `lwarpmk again` followed by `lwarpmk html` or `lwarpmk print` to compile the document one more time.
- Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).

  labels
  ⚠ label characters
  `\nameref`
  ⚠ empty link

  `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

⚠ cleveref page numbers

- cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to "for".

  Ex:
  ```
  \cpageref{tab:first,tab:second}
  ```
  in html becomes:
  "pages **for** table 4.1 and **for** table 4.2"

  See `\cpagerefFor` at page 538 to redefine the message which is printed for page number references.

BibTeX errors with `\etalchar`: See section 9.6.9.

Malformed URLs: Do not use the `%` character between arguments of `\hyperref`, etc., as this character is among those which is neutralized for inclusion in HTML URLs.

Em-dashes or En-dashes in listing captions and titles:

Use XƎLaTeX or LuaLaTeX.

Floats out of sequence:

Mixed "Here" and floating: Floats [H]ere and regular floats may become out of order. `\clearpage` if necessary.

Caption setup: With `\captionsetup` set the positions for the captions `above` or `below` to match their use in the source code.

Images are appearing in strange places:

- Enter **`lwarpmk limages`** to refresh the `lateximage` images.

SVG images:

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk limages`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[15] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ HTML instead of images

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect SVG images will also occur if the document changes the `page` counter:

```
\setcounter{page}{<value>}
```

The `page` counter must *not* be adjusted by the user.

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file

⚠ Lots of files!

for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 6.5 to use MathJax instead.

Plain-looking document:

- The document's CSS stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFilename` statements point to a valid CSS file.

Broken fragments of HTML:

- Check the PDF file used to create HTML to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

Changes do not seem to be taking effect:

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the HTML settings at section 8.4.
- Verify that the proper CSS is actually being used.
- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

Un-matched conditional compiles:

- Verify the proper `begin`/`end` of `warpprint`, `warpHTML`, and `warpall` environments.

14.1.1 Debug tracing output

`\tracinglwarp` When `\tracinglwarp` is used, lwarp will add extra tracing messages to the `.log` file. The last several messages may help track down errors.

Place `\tracinglwarp` just after `\usepackage{lwarp}` to activate tracing.

14.2 Compiling the `lwarp.dtx` file

`lwarp_tutorial.tex`: Copy or link `lwarp_tutorial.txt` from the TDS `doc` directory to the `source` directory, or wherever you wish to compile the documentation. This file is included verbatim in the documentation, but is in the `doc` directory so that it may be found by *texdoc* and copied by the user.

Illogical error messages caused by an out-of-sync `lwarp.sty` file:

1. Delete the `lwarp.sty` file.

[15] This becomes important when dealing with a document containing thousands of images.

2. Enter **`pdflatex lwarp.ins`** to generate a new `lwarp.sty` file.
3. Enter **`pdflatex lwarp.dtx`** to recompile the `lwarp.pdf` documentation.

Un-nested environments:

Be sure to properly nest:

- `\begin{macrocode}` and `\end{macrocode}`
- `\begin{macro}` and `\end{macro}`
- `\begin{environment}` and `\end{environment}`

15 Trademarks

- TEX is a trademark of American Mathematical Society.
- ADOBE® and ADOBE *Framemaker*® are either registered trademarks or trademarks of ADOBE SYSTEMS INCORPORATED in the United States and/or other countries.
- LINUX® is the registered trademark of Linus Torvalds in the U.S. and other countries.
- MAC OS® is a trademark of APPLE INC.
- MADCAP FLARE™ is the property of MADCAP SOFTWARE, INC.
- MATHJAX is copyright 2009 and later. The MATHJAX CONSORTIUM is a joint venture of the AMERICAN MATHEMATICAL SOCIETY (AMS) and the SOCIETY FOR INDUSTRIAL AND APPLIED MATHEMATICS (SIAM) to advance mathematical and scientific content on the web.
- MICROSOFT®, ENCARTA, MSN, and WINDOWS® are either registered trademarks or trademarks of MICROSOFT CORPORATION in the United States and/or other countries.
- UNIX® is a registered trademark of THE OPEN GROUP.

File 1 **lwarp.sty**

16 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of ~~crude hacks~~ clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include xcolor with its color models and conversion to HTML color output, and siunitx which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by *pdftotext*.

Packages were emulated where their primary purpose was visual formatting which is not relevent to HTML output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in HTML output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a `lateximage` environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

Table 9: Section depths and HTML headings

Section	LaTeX depth	HTML headings *
title of the entire website		`<h1>`
none	-5	new for this package
book	-2	**not yet used**
part	-1	`<h2>`
chapter	0	`<h3>`
section	1	`<h4>`
subsection	2	`<h5>`
subsubsection	3	`<h6>`
paragraph	4	`<span class = "paragraph">`
subparagraph	5	`<span class = "subparagraph">`
listitem	7	new for this package, used for list items

* If `FormatWP` is true, section headings may be adjusted, depending on `WPTitleHeading`. See table 8 on page 180.

17 Section depths and HTML headings

Stacks are created to track depth inside the LaTeX document structure. This depth is translated to HTML headings as shown in table 9. "Depth" here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the LaTeX document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Support for the memoir package will require the addition of a `book` level, which may push the HTML headings down a step, and also cause `subsubsection` to become a `<div>` due to a limit of six HTML headings.

It is possible to use HTML5 `<section>` and `<h1>` for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the CSS to remain fixed as well.

18 Source code

This is where the documented source code for lwarp begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the lwarp package.

line numbers — The small numbers at the left end of a line refer to line numbers in the `lwarp.sty` file.

subjects — Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph.

objects — Black-colored tags in the left marign are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are command macros. Each of these also appears in the index as individual entries, and are also listed together under "files", "packages", "environments", "booleans", and "counters".

index entries

⚠ warnings — Special warnings are marked with a warning icon.

for HTML output:
for PRINT output:
for HTML & PRINT:

Green-colored tags in the left margin show which sections of source code apply to the generation of HTML, print, or both forms of output.

— lwarp source code begins on the following page —

19 Detecting the TEX engine — *pdflatex*, *lualatex*, *xelatex*

See: http://tex.stackexchange.com/a/47579.

Detects XƎTEX and LuaLATEX:

```
\RequirePackage{iftex}
\newif\ifxetexorluatex
\ifXeTeX
    \xetexorluatextrue
\else
    \ifLuaTeX
        \xetexorluatextrue
    \else
        \xetexorluatexfalse
    \fi
\fi

\ifLuaTeX
\RequirePackage{luatex85}% until the geometry package is updated
\fi

\RequirePackage{ifpdf}
```

```
\RequirePackage{ifptex}
```

20 Early package requirements

Pkg etoolbox Provides \ifbool and other functions.

Pkg xpatch Patches macros with optional arguments.

```
\RequirePackage{etoolbox}[2011/01/03]% v2.6 for \BeforeBeginEnvironment, etc.
\RequirePackage{xpatch}
```

Pkg ifplatform Provides \ifwindows to try to automatically detect WINDOWS OS.

```
\RequirePackage{ifplatform}% sense op-system platform
```

Pkg letltxmacro

```
\RequirePackage{letltxmacro}
```

21 Package load order

Several packages must never be used with lwarp, others should only be loaded before lwarp, and others should only be loaded after. The lwarp core checks most of these

cases. In some lwarp-* packages, \LWR@loadbefore is used to trigger an error if they are loaded after lwarp, while additional code provides necessary patches for when they are loaded before.

Packages which must be loaded after lwarp are enfoced by a large number of \LWR@loadafter statements, below. Some packages are emulated by memoir, and so these are tested by \LWR@notmemoirloadafter, which does not cause an error if memoir is used.

\LWR@checkloadfilename is used to check each filename to see if it must never be loaded, or must always be loaded before lwarp.

21.1 Tests of package load order

\LWR@loadafter {⟨*packagename*⟩} Error if this package was loaded before lwarp.

```
\newcommand*{\LWR@loadafter}[1]{%
\@ifpackageloaded{#1}
{
    \PackageError{lwarp}
        {%
            Package #1,\MessageBreak
            or one which uses #1,\MessageBreak
            must be loaded after lwarp
        }
        {Move \detokenize{\usepackage}{#1} after
        \detokenize{\usepackage}{lwarp}.\MessageBreak
        Package #1 may also be loaded by something else,\MessageBreak
        which must also be moved after lwarp.}
}
{}
}
```

\LWR@notmemoirloadafter {⟨*packagename*⟩} Error if not memoir class and this package was loaded before lwarp.

memoir emulates many packages, and pretends that they have already been loaded.

```
\@ifclassloaded{memoir}
{\newcommand*{\LWR@notmemoirloadafter}[1]{}}
{\LetLtxMacro\LWR@notmemoirloadafter\LWR@loadafter}
```

\LWR@notltjloadafter {⟨*packagename*⟩} Error if not a ltjs* class and this package was loaded before lwarp.

```
\LetLtxMacro\LWR@notltjloadafter\LWR@loadafter

\@ifclassloaded{ltjarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

```
\@ifclassloaded{ltjsreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjspf}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjskiyou}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

`\LWR@loadbefore` {⟨*packagename*⟩} Error if this package is loaded after lwarp.

```
\newcommand*{\LWR@loadbefore}[1]{%
\@ifpackageloaded{#1}
{}
{
\PackageError{lwarp}
{Package #1 must be loaded before lwarp}
{Move \detokenize{\usepackage}{#1} before \detokenize{\usepackage}{lwarp}.}
}
}
```

`\LWR@checkloadbefore` {⟨*thispackagename*⟩} {⟨*packagename*⟩}

If package names match, error if it is loaded after lwarp.

```
\newcommand*{\LWR@checkloadbefore}[2]{%
    \edef\LWR@tempone{#1}%
    \ifdefstring{\LWR@tempone}{#2}{%
        \LWR@loadbefore{#1}%
    }{}%
}
```

`\LWR@loadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

The first packages is not supported, so tell the user to use the second instead.

```
\newcommand*{\LWR@loadnever}[2]{%
\PackageError{lwarp}
{%
    Package #1 is not supported\MessageBreak
    by lwarp's HTML conversion.\MessageBreak
    Package(s) #2 may be useful instead
}
{%
    Package #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another package.\MessageBreak
    For a possible alternative, see package(s) #2.
}
}
```

`\LWR@checkloadnever` {⟨*thispackagename*⟩} {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

If this package name is the bad packagename, suggest the replacements instead.

```
\newcommand*{\LWR@checkloadnever}[3]{%
    \edef\LWR@tempone{#1}%
    \ifdefstring{\LWR@tempone}{#2}{%
        \LWR@loadnever{#2}{#3}%
    }{}%
}
```

\LWR@earlyloadnever {⟨*badpackagename*⟩} {⟨*replacementpkgname*⟩}

The first package is not supported, so tell the user to use the second instead. This version checks immediately for packages which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyloadnever}[2]{%
\@ifpackageloaded{#1}{%
\PackageError{lwarp}
{%
    Package #1 is not supported\MessageBreak
    by lwarp's HTML conversion.\MessageBreak
    Package(s) #2 may be useful instead
}
{%
    Package #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another package.\MessageBreak
    For a possible alternative, see package(s) #2.
}
}{}%
}
```

\LWR@earlyclassloadnever {⟨*badclassname*⟩} {⟨*replacementclassname*⟩}

The first class is not supported, so tell the user to use the second instead. This version checks immediately for classes which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyclassloadnever}[2]{%
\@ifclassloaded{#1}{%
\PackageError{lwarp}
{%
    Class #1 is not supported\MessageBreak
    by lwarp's HTML conversion.\MessageBreak
    Class(es) #2 may be useful instead
}
{%
    Class #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another class.\MessageBreak
    For a possible alternative, see class(es) #2.
}
}{}%
}
```

21.2 Error for disallowed packages and classes loaded before lwarp

```
\LWR@earlyclassloadnever{jarticle}{ujarticle}
\LWR@earlyclassloadnever{jbook}{ujbook}
\LWR@earlyclassloadnever{jreport}{ujreport}
\LWR@earlyclassloadnever{tarticle}{utarticle}
\LWR@earlyclassloadnever{tbook}{utbook}
\LWR@earlyclassloadnever{treport}{utreport}
\LWR@earlyloadnever{ae}{cm-super, lmodern}
\LWR@earlyloadnever{aecompl}{cm-super, lmodern}
\LWR@earlyloadnever{aecc}{cm-super, lmodern}
\LWR@earlyloadnever{alg}{algorithm2e, algorithmicx}
\LWR@earlyloadnever{algorithmic}{algorithm2e, algorithmicx}
\LWR@earlyloadnever{boxedminipage}{boxedminipage2e}
\LWR@earlyloadnever{caption2}{caption}
% \LWR@earlyloadnever{ccaption}{caption}% might be preloaded by memoir
```

The older CJK and CJKutf8 only work with xeCJK:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@earlyloadnever{CJK}{ctex, xeCJK}
    \LWR@earlyloadnever{CJKutf8}{ctex, xeCJK}
}
```

bxcjkatype is based on CJK:

```
\LWR@earlyloadnever{bxcjkjatype}{upLaTeX, bxjsarticle, ujarticle, utarticle}
```

hangul is not in TeXLive, and is not tested:

```
\LWR@earlyloadnever{hangul}{kotex, xetexko, luatexko}
```

Others:

```
\LWR@earlyloadnever{colortab}{colortbl}
\LWR@earlyloadnever{epsf}{graphicx}
\LWR@earlyloadnever{fancyheadings}{fancyhdr}
\LWR@earlyloadnever{fncylab}{cleveref}
\LWR@earlyloadnever{glossary}{glossaries}
\LWR@earlyloadnever{hyper}{hyperref}
\LWR@earlyloadnever{pdfcprot}{microtype}
\LWR@earlyloadnever{picinpar}{floatflt, wrapfig}
\LWR@earlyloadnever{picins}{floatflt, wrapfig}
\LWR@earlyloadnever{sistyle}{siunitx}
\LWR@earlyloadnever{t1enc}{fontenc, inputenc, inputenx}
\LWR@earlyloadnever{ucs}{inputenc, inputencx}
\LWR@earlyloadnever{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

21.3 Enforcing package loading after lwarp

Packages which should only be loaded after lwarp are tested here to trip an error of they have already been loaded.

The following packages must be loaded after lwarp:

```
\LWR@loadafter{2in1}
```

```
\LWR@loadafter{2up}
\LWR@loadafter{a4}
\LWR@loadafter{a4wide}
\LWR@loadafter{a5comb}
\LWR@notmemoirloadafter{abstract}
\LWR@loadafter{academicons}
\LWR@loadafter{accsupp}
\LWR@loadafter{acro}
\LWR@loadafter{acronym}
\LWR@loadafter{adjmulticol}
\LWR@loadafter{addlines}
\LWR@loadafter{ae}
\LWR@loadafter{aecc}
\LWR@loadafter{afterpage}
\LWR@loadafter{algorithm2e}
\LWR@loadafter{algorithmicx}
\LWR@loadafter{alltt}
\LWR@loadafter{amsmath}
\LWR@loadafter{amsthm}
\LWR@loadafter{anonchap}
\LWR@loadafter{anysize}
\LWR@notmemoirloadafter{appendix}
\LWR@loadafter{ar}
\LWR@loadafter{arabicfront}
\LWR@notmemoirloadafter{array}
\LWR@loadafter{arydshln}
\LWR@loadafter{asymptote}
% \LWR@loadafter{atbegshi}% used by morewrites
\LWR@loadafter{attachfile}
\LWR@loadafter{attachfile2}
\LWR@loadafter{authblk}
\LWR@loadafter{axessibility}
\LWR@loadafter{axodraw2}
\LWR@loadafter{backref}
\LWR@loadafter{balance}
\LWR@loadafter{bbding}
\LWR@loadafter{bigdelim}
\LWR@loadafter{bigfoot}
\LWR@loadafter{bigstrut}
\LWR@loadafter{bitpattern}
\LWR@loadafter{blowup}
\LWR@loadafter{booklet}
\LWR@loadafter{bookmark}
\LWR@notmemoirloadafter{booktabs}
\LWR@loadafter{bophook}
\LWR@loadafter{bounddvi}
\LWR@loadafter{boxedminipage}
\LWR@loadafter{boxedminipage2e}
\LWR@loadafter{breakurl}
\LWR@loadafter{breqn}
\LWR@loadafter{bsheaders}
\LWR@loadafter{bxpapersize}
\LWR@loadafter{bytefield}
\LWR@loadafter{cancel}
\LWR@loadafter{canoniclayout}
```

```
\LWR@loadafter{caption}
\LWR@loadafter{caption2}
\LWR@loadafter{cases}
% \LWR@loadafter{ccaption}% may be preloaded by memoir
\LWR@loadafter{changebar}
\LWR@notmemoirloadafter{changepage}
\LWR@loadafter{changes}
\LWR@loadafter{chappg}
\LWR@loadafter{chapterbib}
\LWR@loadafter{chemfig}
\LWR@loadafter{chemformula}
\LWR@loadafter{chemgreek}
\LWR@loadafter{chemmacros}
\LWR@loadafter{chemnum}
\LWR@loadafter{chkfloat}
\LWR@notmemoirloadafter{chngpage}
\LWR@loadafter{cite}
\LWR@loadafter{cmdtrack}
\LWR@loadafter{color}
\LWR@loadafter{colortbl}
\LWR@loadafter{continue}
\LWR@loadafter{copyrightbox}
\LWR@notmemoirloadafter{crop}
% ctex must be loaded before lwarp
\LWR@loadafter{ctable}
\LWR@loadafter{cuted}
\LWR@loadafter{cutwin}
\LWR@loadafter{dblfloatfix}
\LWR@loadafter{dblfnote}
\LWR@notmemoirloadafter{dcolumn}
\LWR@loadafter{diagbox}
\LWR@loadafter{dingbat}
\LWR@loadafter{dprogress}
\LWR@loadafter{draftcopy}
\LWR@loadafter{draftfigure}
\LWR@loadafter{draftwatermark}
\LWR@loadafter{easy-todo}
\LWR@loadafter{ebook}
\LWR@loadafter{ed}
\LWR@loadafter{ellipsis}
\LWR@loadafter{embrac}
\LWR@loadafter{emptypage}
\LWR@loadafter{endfloat}
\LWR@loadafter{endheads}
\LWR@loadafter{endnotes}
\LWR@notmemoirloadafter{enumerate}
\LWR@loadafter{enumitem}
\LWR@notmemoirloadafter{epigraph}
\LWR@loadafter{epsfig}
\LWR@loadafter{epstopdf}
\LWR@loadafter{epstopdf-base}
\LWR@loadafter{eqlist}
\LWR@loadafter{eqparbox}
\LWR@loadafter{errata}
\LWR@loadafter{eso-pic}
```

```
\LWR@loadafter{eurosym}
\LWR@loadafter{everypage}
\LWR@loadafter{everyshi}
\LWR@loadafter{extramarks}
\LWR@loadafter{fancybox}
\LWR@loadafter{fancyhdr}
\LWR@loadafter{fancyheadings}
\LWR@loadafter{fancyref}
\LWR@loadafter{fancytabs}
\LWR@loadafter{fancyvrb}
\LWR@loadafter{figcaps}
\LWR@loadafter{figsize}
\LWR@loadafter{fitbox}
\LWR@loadafter{fix2col}
\LWR@loadafter{fixme}
\LWR@loadafter{fixmetodonotes}
\LWR@loadafter{flafter}
\LWR@loadafter{flippdf}
\LWR@loadafter{float}
\LWR@loadafter{floatflt}
\LWR@loadafter{floatpag}
\LWR@loadafter{floatrow}
\LWR@loadafter{fltrace}
\LWR@loadafter{flushend}
\LWR@loadafter{fnbreak}
\LWR@loadafter{fncychap}
\LWR@loadafter{fnlineno}
\LWR@loadafter{fnpara}
\LWR@loadafter{fnpos}
\LWR@loadafter{fontawesome}
\LWR@loadafter{fontawesome5}
% fontenc must be loaded before lwarp
% fontspec must be loaded before lwarp
\LWR@loadafter{footmisc}
\LWR@loadafter{footnote}
\LWR@loadafter{footnotebackref}
\LWR@loadafter{footnotehyper}
\LWR@loadafter{footnoterange}
\LWR@loadafter{footnpag}
\LWR@loadafter{foreign}
\LWR@loadafter{forest}
\LWR@loadafter{framed}
\LWR@loadafter{ftcap}
\LWR@loadafter{ftnright}
\LWR@loadafter{fullminipage}
\LWR@loadafter{fullpage}
\LWR@loadafter{fullwidth}
\LWR@loadafter{fwlw}
\LWR@loadafter{gentombow}
% geometry is always loaded by lwarp, and lwarp-geometry is AtBeginDocument
\LWR@loadafter{gmeometric}
\LWR@loadafter{glossaries}
% \LWR@loadafter{graphics}% pre-loaded by xunicode
% \LWR@loadafter{graphicx}% pre-loaded by xunicode
\LWR@loadafter{gloss}
```

```
\LWR@loadafter{glossary}
\LWR@loadafter{grffile}
\LWR@loadafter{grid}
\LWR@loadafter{grid-system}
\LWR@loadafter{gridset}
\LWR@loadafter{hang}
\LWR@loadafter{hanging}
\LWR@loadafter{hypcap}
\LWR@loadafter{hypdestopt}
\LWR@loadafter{hypernat}
\LWR@loadafter{hyperref}
\LWR@loadafter{hyperxmp}
\LWR@loadafter{hyphenat}
\LWR@loadafter{idxlayout}
\LWR@loadafter{ifoddpage}
\LWR@loadafter{imakeidx}
\LWR@notmemoirloadafter{index}
% inputenc must be loaded before lwarp
% inputenx must be loaded before lwarp
\LWR@loadafter{intopdf}
\LWR@loadafter{karnaugh-map}
\LWR@loadafter{keyfloat}
\LWR@loadafter{layaureo}
\LWR@loadafter{layout}
\LWR@loadafter{layouts}
\LWR@loadafter{leading}
\LWR@loadafter{letterspace}
\LWR@loadafter{lettrine}
\LWR@loadafter{lineno}
\LWR@loadafter{lips}
\LWR@loadafter{listings}
\LWR@loadafter{listliketab}
\LWR@loadafter{longtable}
\LWR@loadafter{lscape}
\LWR@loadafter{ltablex}
\LWR@loadafter{ltcaption}
\LWR@loadafter{ltxgrid}
\LWR@loadafter{ltxtable}
\LWR@loadafter{lua-check-hyphen}
\LWR@loadafter{lua-visual-debug}
\LWR@loadafter{luacolor}
\LWR@loadafter{luatodonotes}
\LWR@loadafter{magaz}
\LWR@notmemoirloadafter{makeidx}
\LWR@loadafter{manyfoot}
\LWR@loadafter{marginfit}
\LWR@loadafter{marginfix}
\LWR@loadafter{marginnote}
\LWR@loadafter{marvosym}
\LWR@loadafter{mcaption}
\LWR@loadafter{mdframed}
\LWR@loadafter{memhfixc}
\LWR@loadafter{metalogo}
\LWR@loadafter{mhchem}
\LWR@loadafter{microtype}
```

```
\LWR@loadafter{midfloat}
\LWR@loadafter{midpage}
\LWR@loadafter{minitoc}
% morefloats must be allowed early for print mode
\LWR@notmemoirloadafter{moreverb}
% morewrites must be loaded before lwarp
\LWR@notmemoirloadafter{mparhack}
\LWR@loadafter{multicap}
%\LWR@loadafter{multicol}% loaded by ltxdoc
\LWR@loadafter{multicolrule}
\LWR@loadafter{multirow}
\LWR@loadafter{multitoc}
\LWR@loadafter{musicography}
\LWR@loadafter{nameauth}
\LWR@loadafter{nameref}
\LWR@loadafter{natbib}
\LWR@notmemoirloadafter{nccfancyhdr}
\LWR@notmemoirloadafter{needspace}
% newclude must be loaded before lwarp
\LWR@loadafter{newtxmath}
% newunicodechar must be loaded before lwarp
\LWR@notmemoirloadafter{nextpage}
\LWR@loadafter{nicefrac}
\LWR@loadafter{niceframe}
\LWR@loadafter{nomencl}
\LWR@loadafter{nonfloat}
\LWR@loadafter{nonumonpart}
\LWR@loadafter{nopageno}
\LWR@loadafter{notes}
\LWR@loadafter{notespages}
\LWR@loadafter{nowidow}
\LWR@loadafter{ntheorem}
\LWR@loadafter{octave}
\LWR@loadafter{overpic}
\LWR@loadafter{pagegrid}
\LWR@notmemoirloadafter{pagenote}
\LWR@loadafter{pagesel}
\LWR@loadafter{paralist}
\LWR@loadafter{parnotes}
\LWR@notmemoirloadafter{parskip}
\LWR@loadafter{pbox}
\LWR@loadafter{pdfcomment}
\LWR@loadafter{pdflscape}
\LWR@loadafter{pdfmarginpar}
\LWR@loadafter{pdfpages}
\LWR@loadafter{pdfprivacy}
\LWR@loadafter{pdfrender}
\LWR@loadafter{pdfsync}
\LWR@loadafter{pdftricks}
\LWR@loadafter{pdfx}
\LWR@loadafter{perpage}
\LWR@loadafter{pfnote}
\LWR@loadafter{phfqit}
\LWR@loadafter{pifont}
\LWR@loadafter{placeins}
```

```
\LWR@loadafter{plarray}
\LWR@loadafter{plarydshln}
\LWR@loadafter{plextarray}
\LWR@loadafter{plextarydshln}
\LWR@loadafter{plcolortbl}
\LWR@loadafter{plextdelarray}
\LWR@loadafter{prelim2e}
\LWR@loadafter{prettyref}
\LWR@loadafter{preview}
\LWR@loadafter{psfrag}
\LWR@loadafter{psfragx}
\LWR@loadafter{pst-eps}
\LWR@loadafter{pstool}
\LWR@loadafter{pstricks}
% \LWR@loadafter{pxatbegshi}% may be used by morewrites
\LWR@loadafter{pxeveryshi}
\LWR@loadafter{pxftnright}
\LWR@loadafter{pxjahyper}
\LWR@loadafter{quotchap}
\LWR@loadafter{quoting}
\LWR@loadafter{ragged2e}
\LWR@loadafter{realscripts}
\LWR@loadafter{refcheck}
\LWR@loadafter{register}
\LWR@loadafter{relsize}
\LWR@loadafter{repeatindex}
\LWR@loadafter{resizegather}
\LWR@loadafter{rmpage}
\LWR@loadafter{romanbar}
\LWR@loadafter{romanbarpagenumber}
\LWR@loadafter{rotating}
\LWR@loadafter{rotfloat}
\LWR@loadafter{rviewport}
\LWR@loadafter{savetrees}
% scalefnt is loaded by babel-french
\LWR@loadafter{schemata}
\LWR@loadafter{scrextend}
\LWR@loadafter{scrhack}
\LWR@loadafter{scrlayer}
\LWR@loadafter{scrlayer-notecolumn}
\LWR@loadafter{scrlayer-scrpage}
\LWR@loadafter{scrpage2}
\LWR@loadafter{section}
\LWR@loadafter{sectionbreak}
\LWR@loadafter{sectsty}
\LWR@loadafter{semantic-markup}
\LWR@notmemoirloadafter{setspace}
\LWR@loadafter{shadow}
\LWR@notmemoirloadafter{showidx}
\LWR@loadafter{showkeys}
\LWR@loadafter{showtags}
\LWR@loadafter{sidecap}
\LWR@loadafter{sidenotes}
\LWR@loadafter{SIunits}
\LWR@loadafter{siunitx}
```

```
\LWR@loadafter{soul}
\LWR@loadafter{soulpos}
\LWR@loadafter{soulutf8}
\LWR@loadafter{splitidx}
\LWR@loadafter{srcltx}
\LWR@loadafter{srctex}
\LWR@loadafter{stabular}
\LWR@notltjloadafter{stfloats}
\LWR@loadafter{struktex}
\LWR@loadafter{subcaption}
\LWR@loadafter{subfig}
\LWR@loadafter{subfigure}
\LWR@loadafter{supertabular}
\LWR@loadafter{t1inc}
\LWR@loadafter{tabls}
\LWR@loadafter{tablefootnote}
\LWR@notmemoirloadafter{tabularx}
\LWR@loadafter{tabulary}
\LWR@loadafter{tascmac}
\LWR@loadafter{textarea}
% \LWR@loadafter{textcomp}% maybe before lwarp with font packages
\LWR@loadafter{textfit}
\LWR@loadafter{textpos}
\LWR@loadafter{theorem}
\LWR@loadafter{thinsp}
\LWR@loadafter{threadcol}
\LWR@loadafter{threeparttable}
\LWR@loadafter{threeparttablex}
\LWR@loadafter{thumb}
\LWR@loadafter{thumbs}
\LWR@loadafter{tikz}
\LWR@loadafter{titleps}
\LWR@loadafter{titlesec}
\LWR@loadafter{titletoc}
\LWR@notmemoirloadafter{titling}
% \LWR@loadafter{tocbasic}% preloaded by koma-script classes
\LWR@notmemoirloadafter{tocbibind}
\LWR@loadafter{tocdata}
\LWR@loadafter{tocenter}
\LWR@notmemoirloadafter{tocloft}
\LWR@loadafter{tocstyle}
\LWR@loadafter{todo}
\LWR@loadafter{todonotes}
\LWR@loadafter{topcapt}
\LWR@loadafter{tram}
\LWR@loadafter{transparent}
\LWR@loadafter{trimclip}
\LWR@loadafter{trivfloat}
\LWR@loadafter{truncate}
\LWR@loadafter{turnthepage}
\LWR@loadafter{twoup}

% \LWR@loadafter{typearea}% preloaded by koma-script classes
\LWR@loadafter{typicons}
% \LWR@loadafter{ulem}% preloaded by ctexart and related classes
```

```
\LWR@loadafter{umoline}
\LWR@loadafter{underscore}
\LWR@loadafter{units}
\LWR@loadafter{unitsdef}
\LWR@loadafter{upref}
\LWR@loadafter{url}
\LWR@loadafter{uspace}
\LWR@loadafter{varioref}% no lwarp package provided
\LWR@notmemoirloadafter{verse}
\LWR@loadafter{versonotes}
\LWR@loadafter{vertbars}
\LWR@loadafter{vmargin}
\LWR@loadafter{vowel}
\LWR@loadafter{vpe}
\LWR@loadafter{vwcol}
\LWR@loadafter{wallpaper}
\LWR@loadafter{watermark}
\LWR@loadafter{widows-and-orphans}
\LWR@loadafter{wrapfig}
\LWR@loadafter{xbmks}
\LWR@loadafter{xcolor}
\LWR@loadafter{xechangebar}
\LWR@loadafter{xellipsis}
% xetexko-vertical must be loaded before lwarp
\LWR@loadafter{xfakebold}
\LWR@loadafter{xfrac}
\LWR@loadafter{xltabular}
\LWR@loadafter{xltxtra}
\LWR@loadafter{xmpincl}
\LWR@loadafter{xpiano}
\LWR@loadafter{xpinyin}
\LWR@loadafter{xtab}
% xunicode must be loaded before lwarp
\LWR@loadafter{xurl}
\LWR@loadafter{xy}
\LWR@loadafter{zwpagelayout}
```

22 MD5 hashing

The MD5 hash is used for `latexmimage` filenames for SVG math.

```
\newcommand{\LWR@mdfive}[1]{%
\PackageError{lwarp}
{No MD5 macro was found}
{Lwarp must find the macros pdfmdfivesum or mdfivesum.}
}
```

The default for pdfLaTeX, DVILaTeX, upLaTeX, etc:

```
\let\LWR@mdfive\pdfmdfivesum
```

For LuaLaTeX:

```
\ifLuaTeX
\RequirePackage{pdftexcmds}
\let\LWR@mdfive\pdf@mdfivesum
\fi
```

For XeLaTeX:

```
\ifXeTeX
\@ifundefined{pdffivesum}{}
    {\let\LWR@mdfive\pdfmdfivesum}
\@ifundefined{mdfivesum}{}
    {\let\LWR@mdfive\mdfivesum}
\fi
```

23 pdfLaTeX T1 and UTF-8 encoding

When using pdfLaTeX, lwarp requires T1 encoding, and recommends UTF-8 encoding.

If some other input encoding is already defined, lwarp will try to use it instead, and hope for the best.

XeLaTeX and LuaLaTeX are both UTF-8 by nature.

`\LWR@pdfencoding` Sets T1, and also utf8 if not already set.

```
\newcommand*{\LWR@pdfencoding}{%
    \RequirePackage[T1]{fontenc}

    \@ifpackageloaded{inputenc}{}{
        \@ifpackageloaded{inputenx}{}{
            \RequirePackage[utf8]{inputenc}
        }
    }
}
```

```
\ifPDFTeX% pdflatex or dvi latex
    \LWR@pdfencoding
\fi

\ifpTeX
    \LWR@pdfencoding
\fi
```

24 Unicode input characters

for HTML & PRINT:

If using *pdflatex*, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be `\texttimes`.

The first arguments of `\newunicodechar` below are text ligatures in the source code, even though they are not printed in the following listing.

```
\ifpTeX
\else
\RequirePackage{newunicodechar}

\newunicodechar{×}{\texttimes}

\ifPDFTeX% pdflatex or dvi latex
\newunicodechar{ff}{ff}% the first arguments are ligatures
\newunicodechar{fi}{fi}
\newunicodechar{fl}{fl}
\newunicodechar{ffi}{ffi}
\newunicodechar{ffl}{ffl}
\newunicodechar{---}{---}
\newunicodechar{--}{--}
\fi

\fi
```

25 Upright quotes

In PDFTEX, preserve upright quotes in verbatim text. upquote also loads textcomp.

```
\ifPDFTeX
\RequirePackage{upquote}
\fi

\ifpTeX
    \RequirePackage{upquote}
\fi
```

26 Miscellaneous tools

`\LWR@providelength` {⟨`\lengthname`⟩} Provides the length if it isn't defined yet.

Used to provide source compatibility for lengths which will be ignored, but might or might not be already provided by other packages.

```
\newcommand*\LWR@providelength[1]{%
    \ifdeflength{#1}{}{\newlength{#1}}%
}
```

Prints a length in the given units, without printing the unit itself.

\LWR@convertto {⟨*dest unit*⟩} {⟨*length*⟩}

```
\newcommand*{\LWR@convertto}[2]{\strip@pt\dimexpr #2*65536/\number\dimexpr 1#1}
```

\LWR@patcherror {⟨*packagename*⟩} {⟨*macroname*⟩}

Prints an error if could not patch a macro.

```
\newcommand*{\LWR@patcherror}[2]{%
\PackageError{lwarp}
{Unable to patch package #1, macro #2}
{Please contact the author of the lwarp package.}
}
```

\LWR@isolate {⟨*text*⟩} Isolates Chinese characters from the surrounding text. This is required to avoid extra spaces on either side of the Chinese characters, especially when written to a file.

```
\newcommand{\LWR@isolate}[1]{#1}%

\@ifpackageloaded{ctexpatch}{
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
}{}

\@ifpackageloaded{xeCJK}{
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
}{}
```

\LWR@firstoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@secondoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@thirdoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@fourthoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

Expands to the nth of the four arguments. Used for extra cross referencing.

```
\long\def\LWR@firstoffour#1#2#3#4{#1}
\long\def\LWR@secondoffour#1#2#3#4{#2}
\long\def\LWR@thirdoffour#1#2#3#4{#3}
\long\def\LWR@fourthoffour#1#2#3#4{#4}
```

27 Operating-System portability

Prog Unix
Prog Mac OS
Prog Linux

lwarp tries to detect which operating system is being used. Unix / Mac OS / Linux

is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.

Prog MS-Windows

If MS-WINDOWS is not correctly detected, use the lwarp option `OSWindows`.

Prog Windows

Opt OSWindows

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean `usingOSWindows` is set `true`. This boolean may be tested by the user for later use.

27.1 Literal characters

Literal characters to be used in `PrintLatexCmd` and `HTMLLatexCmd`. These are defined without `@` to easily allow their inclusion in the user's document.

The literal `%` character:

```
\let\LWRpercent\@percentchar
```

The literal `$` character:

```
\catcode`\$=12
\def\LWRdollar{$}
\catcode`\$=3
```

The literal `&` character:

```
\catcode`\&=12
\def\LWRamp{&}
\catcode`\&=4
```

The literal `\` character. The ampersand is temporarily set to the escape character during the definition of the backslash macro.

```
\catcode`\&=0
&catcode`&\=12
&def&LWRbackslash{\}
&catcode`&\=0
\catcode`\&=4
```

The literal `{` character. The ampersand is temporarily set to the begin group character during the definition of the leftbrace macro.

```
\catcode`\&=1
\catcode`\{=12
\def\LWRleftbrace&{}
\catcode`\{=1
\catcode`\&=4
```

The literal `}` character. The ampersand is temporarily set to the end group character during the definition of the leftbrace macro.

```
\catcode`\&=2
```

```
\catcode`\}=12
\def\LWRrightbrace{}&
\catcode`\}=2
\catcode`\&=4
```

The literal # character:

```
\catcode`\#=12
\def\LWRhash{#}
\catcode`\#=6
```

\LWRopquote The operating system's quote mark, Unix default. For Windows, see \LWR@setOSWindows, below.

```
\def\LWRopquote{'}
```

\LWRopseq The operating system's sequential execution command, Unix default. For Windows, see \LWR@setOSWindows, below.

```
\def\LWRopseq{\space\LWRamp\LWRamp\space\space}
```

27.2 Common portability code

Bool usingOSWindows Set if the OSWindows option is used, or if Windows is automatically detected.

```
\newbool{usingOSWindows}
\boolfalse{usingOSWindows}
```

27.3 Unix, Linux, and Mac OS

\OSPathSymbol Symbol used to separate directories in a path.

```
\newcommand*{\OSPathSymbol}{/}
```

27.4 MS-Windows

For MS-Windows:

\LWR@setOSWindows Set defaults for the MS-Windows operating system. lwarp attempts to auto-detect the operatings system, and the OSWindows option may also be used to force MS-Windows compatibility.

```
\newcommand*{\LWR@setOSWindows}
{
```

```
\booltrue{usingOSWindows}
\renewcommand*{\OSPathSymbol}{\@backslashchar}
\def\LWRopquote{"}
\def\LWRopseq{\space\LWRamp\space\space}
}
```

Test for windows during compile. The user may also specify `OSWindows` package option in case this test fails.

```
\ifwindows
\LWR@setOSWindows
\fi
```

28 Package options

Pkg `kvoptions` Allows key/value package options.

```
\RequirePackage{kvoptions}
\SetupKeyvalOptions{family=LWR,prefix=LWR@}
```

`\lwarpsetup` A user interface to set the keys:

```
\newcommand{\lwarpsetup}[1]{\setkeys{LWR}{#1}}
```

Bool `warpingprint`
Bool `warpingHTML`
Bool `mathjax`
Bool `LWR@origmathjax`

Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax.

`LWR@origmathjax` remembers the original setting to be restored by `\displaymathnormal`.

```
\newbool{warpingprint}
\newbool{warpingHTML}
\newbool{mathjax}
\newbool{LWR@origmathjax}
```

defaults The default is print output, and SVG math if the user chose HTML output.

```
\booltrue{warpingprint}%
\boolfalse{warpingHTML}%
\boolfalse{mathjax}%
```

Opt `warpprint` If the `warpprint` option is given, boolean `warpingprint` is true and boolean `warpingHTML` is false, and may be used for `\ifbool` tests.

```
\DeclareVoidOption{warpprint}{%
\PackageInfo{lwarp}{Using option 'warpprint'}
\booltrue{warpingprint}%
\boolfalse{warpingHTML}%
}
```

Opt warpHTML

Anything in the warpHTML environment will be generated for HTML output only.

Opt warpHTML

If the warpHTML option is given, boolean warpingHTML is true and boolean warpingprint is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{warpHTML}{%
\PackageInfo{lwarp}{Using option 'warpHTML'}%
\booltrue{warpingHTML}%
\boolfalse{warpingprint}%
}
```

Opt mathsvg

Option mathsvg selects SVG math display: If the mathsvg option is given, boolean mathjax is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{mathsvg}{%
\PackageInfo{lwarp}{Using option 'mathsvg'}
\boolfalse{mathjax}%
\boolfalse{LWR@origmathjax}%

}
```

Opt mathjax

Option mathjax selects MATHJAX math display: If the mathjax option is given, boolean mathjax is true, may be used for \ifbool tests.

```
\DeclareVoidOption{mathjax}{%
\PackageInfo{lwarp}{Using option 'mathjax'}
\booltrue{mathjax}%
\booltrue{LWR@origmathjax}%

}
```

Opt BaseJobname
Default: \jobname

Option BaseJobname sets the \BaseJobname for this document.

This is the \jobname of the printed version, even if currently compiling the HTML version. I.e. this is the \jobname without _html appended. This is used to set \HomeHTMLFilename if the user did not provide one.

```
\DeclareStringOption[\jobname]{BaseJobname}
```

Opt ImagesDirectory
Default: \jobname-images

Option ImagesDirectory sets the name of the directory to use for the lateximage images.

```
\DeclareStringOption[\BaseJobname-images]{ImagesDirectory}
```

Opt ImagesName
Default: image-

Option ImagesName sets the prefix to use for the lateximage images.

```
\DeclareStringOption[image-]{ImagesName}
```

Opt makeindexStyle
Default: lwarp.ist

Selects a custom .ist file. A customized file should be based on lwarp.ist, and must retain the lines related to \hyperindexref.

```
\DeclareStringOption[lwarp.ist]{makeindexStyle}
```

Opt xindyStyle
Default: lwarp.xdy

Selects a custom .xdy file. A customized file should be based on lwarp.xdy, and must retain the line

```
(markup-locref :open "\hyperindexref{" :close "}")
```

```
\DeclareStringOption[lwarp.xdy]{xindyStyle}
```

Opt xindyLanguage
Default: english

Sets the xindy language to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index and glossary.

```
\DeclareStringOption[english]{xindyLanguage}
```

Opt xindyCodepage
Default: utf8

Sets the xindy codepage to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index.

```
\DeclareStringOption[utf8]{xindyCodepage}
```

Opt pdftotextEnc
Default: UTF-8

The option pdftotextEnc sets the encoding used by *pdftotext*. This is passed to *pdftotext* using its -enc option, and is used when converting LaTeX PDF output with HTML tags into a plain-text file with HTML tags.

```
\DeclareStringOption[UTF-8]{pdftotextEnc}
```

Opt lwarpmk

Tells lwarp to generate a local copy of *lwarpmk* called lwarpmk.lua. Useful for archiving for future use. This file may be made executable and acts just like *lwarpmk*.

If lwarpmk option, creates a local copy of lwarpmk.lua:

```
\newbool{LWR@creatinglwarpmk}
\boolfalse{LWR@creatinglwarpmk}

\DeclareVoidOption{lwarpmk}{
\PackageInfo{lwarp}{Using option 'lwarpmk'}
\booltrue{LWR@creatinglwarpmk}
}
```

Opt OSWindows

Tells lwarp to use MS-Windows compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated lwarpmk.conf file to find out whether the operating system was detected correctly.

```
\DeclareVoidOption{OSWindows}{
\PackageInfo{lwarp}{Using option 'OSWindows'}
\LWR@setOSWindows
}
```

Opt HomeHTMLFilename
Default: \BaseJobname

The filename of the homepage. The default is the jobname. This option is stored into \LWR@HomeHTMLFilename, and later transferred into \HomeHTMLFilename for internal use.

```
\DeclareStringOption[]{HomeHTMLFilename}
```

Opt HTMLFilename
Default: <empty>

The filename prefix of web pages after the homepage. The default is empty, no prefix. This option is stored into \LWR@HTMLFilename, and later transferred into \HTMLFilename for internal use.

```
741 \DeclareStringOption[]{HTMLFilename}
```

Opt PrintLatexCmd
Default: <automatic>

The shell commands to use to compile the print document.

```
742 \DeclareStringOption[]{PrintLatexCmd}
```

Opt HTMLLatexCmd
Default: <automatic>

The shell commands to use to compile the HTML document.

```
743 \DeclareStringOption[]{HTMLLatexCmd}
```

Opt PrintIndexCmd
Default: <empty>

The shell commands to use to compile the print indexes.

```
744 \DeclareStringOption[]{PrintIndexCmd}
```

Opt HTMLIndexCmd
Default: <empty>

The shell commands to use to compile the HTML indexes.

```
745 \DeclareStringOption[]{HTMLIndexCmd}
```

Opt LatexmkIndexCmd
Default: <empty>

The shell commands to by used by *latexmk* to compile the print indexes. Unlike PrintIndexCmd and HTMLIndexCmd, LatexmkIndexCmd does not include the filename, which will be provided by *latexmk*.

```
746 \DeclareStringOption[]{LatexmkIndexCmd}
```

Opt makeindex

Tells lwarp to use makeindex for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *makeindex* with a single index file.

```
747 \DeclareBoolOption[false]{makeindex}
```

Opt xindy

Tells lwarp to use xindy for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *xindy* with a single index file.

```
748 \DeclareBoolOption[false]{xindy}
```

Opt GlossaryCmd
Default: makeglossaries

The shell command to use to compile the glossary. The print or HTML version of the glossary filename will be appended to this command.

```
749 \DeclareStringOption[makeglossaries]{GlossaryCmd}
```

Opt latexmk

Option latexmk tells *lwarpmk* to use *latexmk* when compiling documents.

```
750 \DeclareBoolOption[false]{latexmk}
```

Opt dvips Option dvips tells *lwarpmk* to use *dvips* when compiling DVI *latex* documents.

```
751 \DeclareBoolOption[false]{dvips}
```

Opt dvipdfm Option dvipdfm tells *lwarpmk* to use *dvipdfm* when compiling DVI *latex* documents.

```
752 \DeclareBoolOption[false]{dvipdfm}
```

Opt dvipdfmx Option dvipdfmx tells *lwarpmk* to use *dvipdfmx* when compiling DVI *latex* documents.

```
753 \DeclareBoolOption[false]{dvipdfmx}
```

Execute options Execute the package options, with the defaults which have been set just above:

```
754 \ProcessKeyvalOptions*\relax
```

28.1 Additional options support

Assign the \BaseJobname if the user hasn't provided one:

```
755 \providecommand*{\BaseJobname}{\LWR@BaseJobname}
```

Defaults unless already over-ridden by the user:

```
756 \ifcsempty{LWR@HomeHTMLFilename}{
757     \newcommand*{\HomeHTMLFilename}{\BaseJobname}
758 }{
759     \csedef{HomeHTMLFilename}{\LWR@HomeHTMLFilename}
760 }
761
762 \csedef{HTMLFilename}{\LWR@HTMLFilename}
```

Special handling for underscores in labels and filenames.

\LWR@sanitized The sanitized version of what was given to \LWR@sanitize. Characters are set to their detokenized versions. Required for underscores in labels and filenames.

```
763 \newcommand*{\LWR@sanitized}{}
```

\LWR@sanitize {⟨*text*⟩}

Sanitizes the text and returns the result in \LWR@sanitized.

```
764 \newcommand*{\LWR@sanitize}[1]{%
765 \edef\LWR@sanitized{#1}%
766 \edef\LWR@sanitized{\detokenize\expandafter{\LWR@sanitized}}%
767 }
```

Sanitize some string options to neutralize underscores.

```
\LWR@sanitize{\LWR@BaseJobname}
\edef\LWR@BaseJobname{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesDirectory}
\edef\LWR@ImagesDirectory{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesName}
\edef\LWR@ImagesName{\LWR@sanitized}
```

`\LWR@PrintIndexCmd` and `\LWR@HTMLIndexCmd` are tested to see if they are empty. If so, they are set to a reasonable defaults for a single index using *makeindex*, then possibly set to defaults for *xindy* if the lwarp `xindy` option was selected.

```
\ifdefempty{\LWR@PrintIndexCmd}{
    \renewcommand{\LWR@PrintIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname.idx%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@PrintIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
            \jobname.idx%
        }
    }{}
}{}

\ifdefempty{\LWR@HTMLIndexCmd}{
    \renewcommand{\LWR@HTMLIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname_html.idx%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@HTMLIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
            \jobname_html.idx%
        }
    }{}
}{}

\ifdefempty{\LWR@LatexmkIndexCmd}{
    \renewcommand{\LWR@LatexmkIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@LatexmkIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage%
```

```
        }
    }{}
}{}
```

28.2 Conditional compilation

\warpprintonly {⟨*contents*⟩}

Only process the contents if producing printed output.

```
\newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{}}
```

\warpHTMLonly {⟨*contents*⟩}

Only process the contents if producing HTML output.

```
\newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{}}
```

Pkg comment Provides conditional code blocks.

Attempts to use versions or verbatim fail in some cases, and do not provide much of a speed benefit even when they do work.

```
\RequirePackage{comment}
```

Use `comment_print.cut` for print mode, and `comment_html.cut` for HTML mode. This helps *latexmk* to more reliably know whether to recompile.

```
\ifbool{warpingHTML}{
\def\DefaultCutFileName{\def\CommentCutFile{comment_html.cut}}
}{}

\ifbool{warpingprint}{
\def\DefaultCutFileName{\def\CommentCutFile{comment_print.cut}}
}{}
```

Env warpall Anything in the `warpall` environment will be generated for print or HTML outputs.

```
\includecomment{warpall}
```

Env warpprint
Env warpHTML

Anything in the `warpprint` environment will be generated for print output only.

For HTML output:

```
\ifbool{warpingHTML}
{\includecomment{warpHTML}}
{\excludecomment{warpHTML}}%
```

```
\ifbool{warpingprint}
{\includecomment{warpprint}}
{\excludecomment{warpprint}}
```

Optionally generate a local copy of *lwarpmk*. Default to no.

```
\ifbool{LWR@creatinglwarpmk}
{\includecomment{LWR@createlwarpmk}}
{\excludecomment{LWR@createlwarpmk}}
```

29 Required packages

These packages are automatically loaded by lwarp when generating HTML output. Some of them are also automatically loaded when generating print output, but some are not.

for HTML output:

```
\begin{warpHTML}
```

Load fontspec if necessary:

```
\ifxetexorluatex
\@ifpackageloaded{fontspec}{}{
    \usepackage[no-math]{fontspec}
}
```

The monospaced font is used for HTML tags, so turn off its TeX ligatures and common ligatures:

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
\else
```

pdflatex only: Only pre-loaded if *pdflatex* is being used.

Pkg microtype

ligatures Older browsers don't display ligatures. Turn off letter ligatures, keeping LaTeX dash and quote ligatures, which may fail on older browers but at least won't corrupt written words.

```
\RequirePackage {microtype}

\microtypesetup{
    protrusion=false,
    expansion=false,
    tracking=false,
    kerning=false,
    spacing=false}

\DisableLigatures[f,q,t,T,Q]{encoding = *,family = *}
```

```
\fi
```

```
\end{warpHTML}
```

Pkg geometry

Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

for HTML output:

```
\begin{warpHTML}
```

```
\RequirePackage{geometry}
```

Avoid class and option conflict by changing settings after package load:

```
\geometry{
    paperheight=190in,%
    paperwidth=20in,%
    left=2in,right=6in,%
    top=1in,bottom=1in,%
}
```

ltjtarticle and other classes may require these to be reset by lwarp:

```
\setlength{\textheight}{0.8\paperheight}
\setlength{\textwidth}{0.7\paperwidth}

\@twosidefalse
\@mparswitchfalse

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xparse

LaTeX3 command argument parsing

```
\RequirePackage{xparse}
```

Pkg calc

```
\RequirePackage{calc}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg expl3

LaTeX3 programming

```
\RequirePackage{expl3}
```

Pkg gettitlestring

Used to emulate \nameref.

```
\RequirePackage{gettitlestring}
```

Pkg everyhook

everyhook is used to patch paragraph handling.

```
\@ifundefined{bxjs@everypar}{}{\let\everypar\bxjs@everypar}

\RequirePackage{everyhook}
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg filecontents

Used to write helper files, done in print mode.

Patched to work with morewrites, per https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910

```
\RequirePackage{filecontents}

\@ifpackagelater{filecontents}{2011/10/09}%
{}
{
\newwrite\fcwrite
\let\LWR@origfilec@ntents\filec@ntents
\def\filec@ntents{\def\chardef##1\write{\let\reserved@c\fcwrite}\LWR@origfilec@ntents}
}

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg xifthen

```
\RequirePackage{xifthen}
```

Pkg verbatim

```
\RequirePackage{verbatim}
```

Pkg refcount

Provides \setcounterref, \setcounterpageref, etc.

```
\RequirePackage{refcount}
```

Pkg newfloat

```
\RequirePackage{newfloat}
```

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xstring

⚠ index

There was a short-term bug in xstring regarding \IfInteger which affected lwarp's index generation. The updated version is requested here.

```
\RequirePackage{xstring}[2019/02/01]
```

Pkg environ

Used to encapsulate math environments for re-use in HTML <alt> text.

```
\RequirePackage{environ}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg printlen

Used to convert lengths for image width/height options.

```
\RequirePackage{printlen}
```

\LWR@printlength {⟨*length*⟩}

Prints a length using a locally-controlled unit and space. Rounding is used unless the length is small.

```
\newrobustcmd*{\LWR@printlength}[1]{%
\begingroup%
\uselengthunit{PT}%
\renewcommand*{\unitspace}{}%
\ifdimless{#1}{10pt}{%
    \printlength{#1}%
}{%
    \rndprintlength{#1}%
}%
\endgroup%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Pkg varwidth Used for print-mode lateximage.

```
\RequirePackage{varwidth}
```

```
\end{warpprint}
```

30 Loading packages

for HTML & PRINT:

```
\begin{warpall}
```

Remember the original \RequirePackage:

```
\LetLtxMacro\LWR@origRequirePackage\RequirePackage
```

\LWR@requirepackagenames Stores the list of required package names.

```
\newcommand*{\LWR@requirepackagenames}{}
```

\LWR@parsedrequirepackagenames Stores the parsed list of required package names after spaces are removed and lwarp- is prepended.

```
\newcommand*{\LWR@parsedrequirepackagenames}{}
```

\LWR@nullifycomment Remove the preexisting comment environment. Certain packages define it for their own use.

```
\newcommand*{\LWR@nullifycomment}{%
    \PackageInfo{lwarp}%
        {Nullifying the comment environment before loading \LWR@strresulttwo,}%
    \let\comment\relax%
    \let\endcomment\relax%
}
```

\LWR@findword [⟨*1: separator*⟩] {⟨*2: list*⟩} {⟨*3: index*⟩} [⟨*4: destination*⟩]

Note that argument 4 is passed directly to \StrBetween.

```
\newcommand*\LWR@findword[3][,]{%
    \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}{#1}%
}
```

\LWR@checkloadfilename {⟨*filename*⟩} Checks if this filename should be loaded after lwarp, or never at all.

The following should never be loaded:

```
\newcommand*{\LWR@checkloadfilename}[1]{%
\LWR@checkloadnever{#1}{ae}{latinmodern}
\LWR@checkloadnever{#1}{aecc}{latinmodern}
```

```
\LWR@checkloadnever{#1}{alg}{algorithm2e, algorithmicx}
\LWR@checkloadnever{#1}{algorithmic}{algorithm2e, algorithmicx}
\LWR@checkloadnever{#1}{bitfield}{bytefield}
\LWR@checkloadnever{#1}{boxedminipage}{boxedminipage2e}
\LWR@checkloadnever{#1}{caption2}{caption}
\LWR@checkloadnever{#1}{ccaption}{caption}
\LWR@checkloadnever{#1}{colortab}{colortbl}
\LWR@checkloadnever{#1}{doublespace}{setspace}
\LWR@checkloadnever{#1}{epsf}{graphicx}
\LWR@checkloadnever{#1}{fancyheadings}{fancyhdr}
\LWR@checkloadnever{#1}{fncylab}{cleveref}
\LWR@checkloadnever{#1}{glossary}{glossaries}
\LWR@checkloadnever{#1}{hyper}{hyperref}
\LWR@checkloadnever{#1}{newthm}{ntheorem}
\LWR@checkloadnever{#1}{pdfcprot}{microtype}
\LWR@checkloadnever{#1}{picinpar}{floatflt, wrapfig}
\LWR@checkloadnever{#1}{picins}{floatflt, wrapfig}
\LWR@checkloadnever{#1}{rplain}{fancyhdr}
\LWR@checkloadnever{#1}{si}{siunitx}
\LWR@checkloadnever{#1}{sistyle}{siunitx}
\LWR@checkloadnever{#1}{t1enc}{fontenc, inputenc, inputenx}
\LWR@checkloadnever{#1}{ucs}{inputenc, inputencx}
\LWR@checkloadnever{#1}{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

The following should only be loaded before lwarp:

```
\LWR@checkloadbefore{#1}{ctex}
\LWR@checkloadbefore{#1}{fontspec}
\LWR@checkloadbefore{#1}{inputenc}
\LWR@checkloadbefore{#1}{inputenx}
\LWR@checkloadbefore{#1}{kotex}
\LWR@checkloadbefore{#1}{luatexja}
\LWR@checkloadbefore{#1}{luatexja-fontspec}
\LWR@checkloadbefore{#1}{luatexko}
\LWR@checkloadbefore{#1}{morewrites}
\LWR@checkloadbefore{#1}{newclude}
\LWR@checkloadbefore{#1}{newunicodechar}
\LWR@checkloadbefore{#1}{plext}
\LWR@checkloadbefore{#1}{xeCJK}
\LWR@checkloadbefore{#1}{xetexko}
\LWR@checkloadbefore{#1}{zxjatype}
}
```

`\LWR@lookforpackagename` {⟨*index*⟩}

If HTML, and if this is an lwarp-supported package name, re-direct it to the lwarp version by renaming it `lwarp-` followed by the original name.

Looks `index` deep into the list of package names, `\LWR@requirepackagenames`, and builds `\LWR@parsedrequirepackagenames` which is the modified list of names.

```
\newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the index'th package name from the list:

```
\LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in LWR@strresult and the final name with no blanks goes into LWR@strresulttwo.

```
\StrSubstitute[100]{\LWR@strresult}{ }{}[\LWR@strresulttwo]%
```

See if the package name was found:

```
\IfStrEq{\LWR@strresulttwo}{}%
{}% no filename
{% yes filename was found
```

Possible adjustments before loading the package. Maybe nullify the comment environment if the new package will be redefining it for a new purpose.

```
    \ifdefstring{\LWR@strresulttwo}{easyReview}{\LWR@nullifycomment}{}%
```

If HTML, check if the package should be loaded before lwarp, or never at all:

```
    \ifbool{warpingHTML}{\LWR@checkloadfilename{\LWR@strresulttwo}}{}%
```

If HTML, and if found, and if an lwarp-equivalent name exists, use lwarp-* instead.

```
    \ifboolexpr{
        bool{warpingHTML} and
        test{\IfFileExists{lwarp-\LWR@strresulttwo.sty}}
    }%
    {% lwarp-* file found
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
            \edef\LWR@parsedrequirepackagenames{lwarp-\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,lwarp-\LWR@strresulttwo%
            }%
        }%
    }%
    {%
```

Otherwise, use the current package name.

```
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
            \edef\LWR@parsedrequirepackagenames{\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,\LWR@strresulttwo%
            }%
        }%
    }% no lwarp-* file
}% yes filename
}
```

\RequirePackage [⟨*1: options*⟩] {⟨*2: package names*⟩} [⟨*3: version*⟩]

For each of many package names in a comma-separated list, if an lwarp version of a package exists, select it instead of the LaTeX version.

```
\RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to twenty names:[16]

```
\renewcommand*{\LWR@requirepackagenames}{#2}%
\renewcommand*{\LWR@parsedrequirepackagenames}{}%
\LWR@lookforpackagename{1}%
\LWR@lookforpackagename{2}%
\LWR@lookforpackagename{3}%
\LWR@lookforpackagename{4}%
\LWR@lookforpackagename{5}%
\LWR@lookforpackagename{6}%
\LWR@lookforpackagename{7}%
\LWR@lookforpackagename{8}%
\LWR@lookforpackagename{9}%
\LWR@lookforpackagename{10}%
\LWR@lookforpackagename{11}%
\LWR@lookforpackagename{12}%
\LWR@lookforpackagename{13}%
\LWR@lookforpackagename{14}%
\LWR@lookforpackagename{15}%
\LWR@lookforpackagename{16}%
\LWR@lookforpackagename{17}%
\LWR@lookforpackagename{18}%
\LWR@lookforpackagename{19}%
\LWR@lookforpackagename{20}%
```

\RequirePackage depending on the options and version:

```
\IfValueTF{#1}%
{% options given
    \IfValueTF{#3}% version given?
    {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}[#3]}%
    {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}}%
}%
{% no options given
    \IfValueTF{#3}% version given?
    {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}[#3]}%
    {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}}%
}%
}
\LetLtxMacro\usepackage\RequirePackage
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

[16] This was originally nine names, but then I came across a package which used twelve...

\LWR@ProvidesPackagePass {⟨*pkgname*⟩} [⟨*version*⟩]

Uses the original package, including options.

```
\NewDocumentCommand{\LWR@ProvidesPackagePass}{m o}{
\PackageInfo{lwarp}{%
    Using package ‘#1’ and adding lwarp modifications,\MessageBreak
    including options,}%
\IfValueTF{#2}
{\ProvidesPackage{lwarp-#1}[#2]}
{\ProvidesPackage{lwarp-#1}}
\DeclareOption*{\PassOptionsToPackage{\CurrentOption}{#1}}
\ProcessOptions\relax
\IfValueTF{#2}
{\LWR@origRequirePackage{#1}[#2]}
{\LWR@origRequirePackage{#1}}
```

In some cases, the following seems to be required to avoid an “unknown option” error, such as when loading xcolor with options.

```
\DeclareOption*{}%
\ProcessOptions\relax
}
```

\LWR@ProvidesPackageDrop {⟨*pkgname*⟩} [⟨*version*⟩]

Ignores the original package and uses lwarp’s version instead. Drops/discards all options.

```
\NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o}{
\PackageInfo{lwarp}{%
    Replacing package ‘#1’ with the lwarp version,\MessageBreak
    and discarding options,%
}%
\IfValueTF{#2}
{\ProvidesPackage{lwarp-#1}[#2]}
{\ProvidesPackage{lwarp-#1}}
```

Ignore all options.

```
\DeclareOption*{}
```

Nullifies then processes the options. Seems to be required when options contain curly braces, which were causing “`Missing \begin{document}`”.

```
% \ProcessOptions\relax% original LaTeX code
\let\ds@\@empty%         from the original \ProcessOptions
\edef\@curroptions{}%    lwarp modification to \ProcessOptions
\@process@ptions\relax%  from the original \ProcessOptions
}
```

```
\end{warpHTML}
```

31 Additional required packages

for HTML output:
```
\begin{warpHTML}
```

Pkg caption

```
\LWR@origRequirePackage{caption}
\AtBeginDocument{\RequirePackage{lwarp-caption}}%

\end{warpHTML}
```

32 File handles

Defines file handles for writes.

for HTML & PRINT:
```
\begin{warpall}
```

`\LWR@quickfile` For quick temporary use only. This is reused in several places.

```
\newwrite\LWR@quickfile%

\end{warpall}
```

for HTML output:
```
\begin{warpHTML}
```

`\LWR@lateximagesfile` For `<project>-images.txt`:

```
\newwrite\LWR@lateximagesfile

\end{warpHTML}
```

33 Include a file

During HTML output, `\include{<filename>}` causes the following to occur:

1. lwarp creates `<filename>_html_inc.tex` whose contents are:
   `\input <filename>.tex`
2. `<filename>_html_inc.tex` is then `\included` instead of `<filename>.tex`.
3. `<filename>_html_inc.aux` is automatically generated and used by LaTeX.

for HTML output:
```
\begin{warpHTML}
```

\include {⟨*filename*⟩}

\@include {⟨*filename*⟩} Modified to load _html_inc files.

```
\def\@include#1 {%
\immediate\openout\LWR@quickfile #1_html_inc.tex% lwarp
\immediate\write\LWR@quickfile{\string\input{#1.tex}}% lwarp
\immediate\closeout\LWR@quickfile% lwarp
\LWR@origclearpage% \changed
\if@filesw
    \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
\fi
\@tempswatrue
\if@partsw
    \@tempswafalse
    \edef\reserved@b{#1}%
    \@for\reserved@a:=\@partlist\do
    {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
\fi
\if@tempswa
    \let\@auxout\@partaux
    \if@filesw
        \immediate\openout\@partaux #1_html_inc.aux % changed
        \immediate\write\@partaux{\relax}%
    \fi
    \@input@{#1_html_inc.tex}% changed
    \LWR@origclearpage% changed
    \@writeckpt{#1}%
    \if@filesw
        \immediate\closeout\@partaux
    \fi
\else
    \deadcycles\z@
    \@nameuse{cp@#1}%
\fi
\let\@auxout\@mainaux%
}
```

```
\end{warpHTML}
```

34 Copying a file

for HTML output:

```
\begin{warpHTML}
```

\LWR@copyfile {⟨*source filename*⟩} {⟨*destination filename*⟩}

Used to copy the .toc file to .sidetoc to re-print the TOC in the sideTOC navigation pane.

```
\newwrite\LWR@copyoutfile  % open the file to write to
\newread\LWR@copyinfile      % open the file to read from
```

```

\newcommand*{\LWR@copyfile}[2]{%
\LWR@traceinfo{LWR@copyfile: copying #1 to #2}

\immediate\openout\LWR@copyoutfile=#2
\openin\LWR@copyinfile=#1
\begingroup\endlinechar=-1
\makeatletter

\LWR@traceinfo{LWR@copyfile: about to loop}

\loop\unless\ifeof\LWR@copyinfile
  \LWR@traceinfo{LWR@copyfile: one line}
  \read\LWR@copyinfile to\LWR@fileline  % Read one line and store it into \LWR@fileline
%   \LWR@fileline\par                   % print the content into the pdf
% print the content:
  \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
\repeat
\immediate\closeout\LWR@copyoutfile
\LWR@traceinfo{LWR@copyfile: done}
\endgroup
}

\end{warpHTML}
```

35 Debugging messages

HTML comments — To have the HTML output include additional HTML comments, such as which is closing, use

```
\booltrue{HTMLDebugComments}
```

debugging information — To have debug information written to the log, use

```
\tracinglwarp
```

for HTML & PRINT:

```
\begin{warpall}
```

Bool `LWR@tracinglwarp` — True if tracing is turned on.

```
\newbool{LWR@tracinglwarp}
```

`\tracinglwarp` — Turns on the debug tracing messages.

```
\newcommand{\tracinglwarp}{\booltrue{LWR@tracinglwarp}}
```

`\LWR@traceinfo` {⟨*text*⟩} — If tracing is turned on, writes the text to the `.log` file.

```
\newcommand{\LWR@traceinfo}[1]{%
\ifbool{LWR@tracinglwarp}%
```

```
{%
    \typeout{*** lwarp: #1}%
}%
{}%
}
```

Bool HTMLDebugComments Add comments in HTML about closing s, sections, etc.

Default: false

```
\newbool{HTMLDebugComments}
\boolfalse{HTMLDebugComments}
```

If \tracinglwarp, show where preamble hooks occur:

```
\AfterEndPreamble{
\LWR@traceinfo{AfterEndPreamble}
}

\AtBeginDocument{
\LWR@traceinfo{AtBeginDocument}
}
```

```
\end{warpall}
```

36 Defining print and HTML versions of macros and environments

The following refers to defining objects inside lwarp, and is not for the user's document.

Many macros and environments must be provided as both print and HTML versions.

While generating the print version of a document, the original macros as defined by LaTeX and its packages are used as-is.

While generating the HTML version of a document, the original macro or environment is redefined to call a new HTML version or a copy of the original print version. The new HTML versions of macros and environments are used most of the time. Copies of the print versions are used inside a lateximage environment, which draws and remembers an image of the printed output, and also several other places. The copies of the print versions may also be used by the HTML versions, such as when the HTML version merely encloses the print version inside HTML tags.

The general structure for providing print and HTML versions of a macro or environment is as follows:

For a preexisting macro, not defined with xparse: An HTML version is provided with a special name, inside a warpHTML environment, then \LWR@formatted is used to redefine and patch various macros:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may also use xparse

\LWR@formatted{name}
\end{warpHTML}
```

`\LWR@formatted{name}` copies the original print version, then redefines `\name` to use either the print or HTML version depending on which mode lwarp is using. xparse may be used to define the new HTML version, even if the original did not use xparse.

For a preexisiting environment, not defined with xparse: The process is similar. Note the use of `\LWR@formattedenv` instead of `\LWR@formatted`.

```
\begin{warpHTML}
\newenvironment{LWR@HTML@name}{...}% may also use xparse

\LWR@formattedenv{name}
\end{warpHTML}
```

If the original used xparse: A copy must be made using a new name:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@name}{..}{..}% copy the original

\NewDocumentCommand{\LWR@HTML@name}{..}{..}% or use \newcommand

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment, using `\LWR@formattedenv`. (`\LWR@formatted` and `\LWR@formattedenv` use `\LetLtxMacro` to copy the original print definiton, which may not work with macros and environments created by xparse, so the print version must be manually recreated in the lwarp source.)

For a new macro or environment, not using xparse for the print version:

```
\begin{warpall}
\newcommand{\name}{...}% NOT xparse!
\end{warpall}

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may use xparse for HTML

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment. The plain `\name` or environment `name` is used for the printed version, and is placed inside `warpall`. xparse may be used for the `\LWR@HTML@<name>` version.

For a new macro or environment, using xparse: It is possible to use xparse for an entirely new macro or environment by defining the \LWR@print@<name> version with xparse, along with \name defined without xparse to refer directly to the \LWR@print version:

```
\begin{warpall}
\NewDocumentCommand{\LWR@print@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@print@name}{...} {...} {...}

% Simply a call to \LWR@print@name:
\newcommand{\name}{\LWR@print@name}%        -or-
\newenvironment{name}{\LWR@print@name}{\endLWR@print@name}
\end{warpall}

\begin{warpHTML}
\NewDocumentCommand{\LWR@HTML@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@HTML@name}{...} {...} {...}

\LWR@formatted{name}%    -or-
\LWR@formattedenv{name}
\end{warpHTML}
```

In general, \LWR@formatted or \LWR@formattedenv are placed inside a warpHTML environment, and while producing an HTML document they do the following:

- Macros are modified:
  1. The pre-existing print version \name is saved as \LWR@print@<name>, unless \LWR@print@<name> is already defined.
  2. The original \name is redefined to call either the print or HTML version depending on which format is in use at the moment, as set by \LWR@formatting, which is defined as either "print" or "HTML".
- When lwarp is producing a print document, the original definitions are used, as well as any new definitions defined in warpall above.
- When lwarp is generating HTML output, \LWR@formatting is set to "HTML", and \name is directed to \LWR@HTML@<name>.
- When lwarp is generating HTML output but enters a lateximage environment, or for some other reason needs to draw images using the original print defintions, \LWR@formatting is changed to "print" and \name is then redirected to \LWR@print@<name>, which was the original \name.

Since arguments are not handled by the new \name, any star and other arguments are processed by the print or HTML version.

Expandable versions are also provided as well. These usually are necessary for anything which could appear inside a tabular, without which a "Misplaced \omit" error may occur.

⚠ Misplaced \omit error

```
\LWR@expandableformatted
\LWR@expandableformattedenv
```

(Older versions of lwarp used \LetLtxMacro for everything, but this could fail when using macros defined by xparse. This older system is still in use for many definitions.)

for HTML output:

```
\begin{warpHTML}
```

\LWR@formatting Remembers if selected print/HTML formatting.

Used while \LWR@restoreorigformatting, such as in an lateximage. May be set to either "print" or "HTML".

```
\newcommand*{\LWR@formatting}{HTML}
```

\LWR@formatted {⟨*macroname*⟩} No backslash in the macro name.

If not yet defined, defines \LWR@print@<name> as the original print-mode \<name>. Also redefines \<name> to use \LWR@<format>@<name>, where <format> is set by \LWR@formatting, and is print or HTML.

```
\newcommand*{\LWR@formatted}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
        \expandafter\newrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }%
}
```

\LWR@expandableformatted {⟨*macroname*⟩} No backslash in the macro name.

An expandable version of \LWR@formatted.

```
\newcommand*{\LWR@expandableformatted}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
        \expandafter\newcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
```

```
    }%
}
```

\LWR@formattedenv {⟨*environmentname*⟩}

If not yet defined, defines the environment LWR@print@<name> as the original print-mode <name>. Also redefines the environment <name> to use environment LWR@<format>@<name>, where <format> is set by \LWR@formatting, and is print or HTML.

```
\newcommand*{\LWR@formattedenv}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareDocumentEnvironment{#1}{}%
    {\@nameuse{LWR@\LWR@formatting @#1}}%
    {\@nameuse{endLWR@\LWR@formatting @#1}}%
}
```

\LWR@expandableformattedenv {⟨*environmentname*⟩}

An expandable version of LWR@formattedenv.

```
\newcommand*{\LWR@expandableformattedenv}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareExpandableDocumentEnvironment{#1}{}%
    {\@nameuse{LWR@\LWR@formatting @#1}}%
    {\@nameuse{endLWR@\LWR@formatting @#1}}%
}
```

```
\end{warpHTML}
```

37 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

for HTML & PRINT:

```
\begin{warpall}
```

37.1 User-level controls

Bool FormatEPUB
Default: false

Changes HTML output for easy EPUB conversion via an external program. Removes

per-file headers, footers, and nav. Adds footnotes per chapter/section.

```
\newbool{FormatEPUB}
\boolfalse{FormatEPUB}
```

Bool FormatWP
Default: false

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.

```
\newbool{FormatWP}
\boolfalse{FormatWP}
```

Bool WPMarkFloats
Default: false

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions. [17]

```
\newbool{WPMarkFloats}
\boolfalse{WPMarkFloats}
```

Bool WPMarkMinipages
Default: false

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

```
\newbool{WPMarkMinipages}
\boolfalse{WPMarkMinipages}
```

Bool WPMarkTOC
Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set `false`*, the actual TOC is printed instead.*

```
\newbool{WPMarkTOC}
\booltrue{WPMarkTOC}
```

[17] Perhaps some day word processors will have HTML import options for identifying `<figure>` and caption tags for figures and tables.

Bool WPMarkLOFT
Default: false

While formatting for word processors, adds

```
=== list of figures ===
=== list of tables ===
```

and/or

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

```
\newbool{WPMarkLOFT}
\boolfalse{WPMarkLOFT}
```

Bool WPMarkMath
Default: false

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

```
\newbool{WPMarkMath}
\boolfalse{WPMarkMath}
```

Bool WPTitleHeading
Default: false

While formatting for word processors, `true` sets the document title to `<h1>`, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to `false` to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 180.

```
\newbool{WPTitleHeading}
\boolfalse{WPTitleHeading}
```

```
\end{warpall}
```

37.2 Heading adjustments

If formatting the HTML for a word processor, adjust heading levels.

If `WPTitleHeading` is true, adjust so that `part` is **Heading 1**.

If `WPTitleHeading` is false, use `<h1>` for the title, and set `part` to **Heading 2**.

for HTML output:

```
\begin{warpHTML}
```

```
\AtBeginDocument{
\ifbool{FormatWP}{
\@ifundefined{chapter}{
\ifbool{WPTitleHeading}{% part and section starting at h2
\renewcommand*{\LWR@tagtitle}{h1}
\renewcommand*{\LWR@tagtitleend}{/h1}
\renewcommand*{\LWR@tagpart}{h2}
\renewcommand*{\LWR@tagpartend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
```

```
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
\renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% WPTitleHeading
{% not WPTitleHeading, part and section starting at h1
\renewcommand*{\LWR@tagtitle}{div class="title"}
\renewcommand*{\LWR@tagtitleend}{/div}
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagsection}{h2}
\renewcommand*{\LWR@tagsectionend}{/h2}
\renewcommand*{\LWR@tagsubsection}{h3}
\renewcommand*{\LWR@tagsubsectionend}{/h3}
\renewcommand*{\LWR@tagsubsubsection}{h4}
\renewcommand*{\LWR@tagsubsubsectionend}{/h4}
\renewcommand*{\LWR@tagparagraph}{h5}
\renewcommand*{\LWR@tagparagraphend}{/h5}
\renewcommand*{\LWR@tagsubparagraph}{h6}
\renewcommand*{\LWR@tagsubparagraphend}{/h6}
}% not WPTitleHeading
}% chapter undefined
{% chapter defined
\ifbool{WPTitleHeading}{}
{% not WPTitleHeading, part and chapter starting at h1
\renewcommand*{\LWR@tagtitle}{div class="title"}
\renewcommand*{\LWR@tagtitleend}{/div}
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagchapter}{h2}
\renewcommand*{\LWR@tagchapterend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
\renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% not WPTitleHeading
}% chapter defined
}{}% FormatWP
}% AtBeginDocument

\end{warpHTML}
```

38 Remembering original formatting macros

for HTML output:

```
\begin{warpHTML}
```

Remember original definitions of formatting commands. Will be changed to HTML commands for most uses. Will be temporarily restored to original meaning inside any lateximage environment. Also nullify unused commands.

Some packages redefine \#, which is used to generate HTML, so the original must be remembered here.

```
\chardef\LWR@origpound=`\#
```

```
\let\LWR@origcomma\,
\let\LWR@origthinspace\thinspace
\let\LWR@orignegthinspace\negthinspace
\let\LWR@origtilde~
\let\LWR@origenskip\enskip
\let\LWR@origquad\quad
\let\LWR@origqquad\qquad
\let\LWR@orighfil\hfil
\let\LWR@orighss\hss
\let\LWR@origllap\llap
\let\LWR@origrlap\rlap
\let\LWR@orighfilneg\hfilneg
\let\LWR@orighspace\hspace

\let\LWR@origrule\rule

\let\LWR@origmedskip\medskip
\let\LWR@origbigskip\bigskip

\let\LWR@origtextellipsis\textellipsis
\let\LWR@orig@textquotedbl\textquotedbl

\LetLtxMacro\LWR@origrmfamily\rmfamily
\LetLtxMacro\LWR@origsffamily\sffamily
\LetLtxMacro\LWR@origttfamily\ttfamily
\LetLtxMacro\LWR@origbfseries\bfseries
\LetLtxMacro\LWR@origmdseries\mdseries
\LetLtxMacro\LWR@origupshape\upshape
\LetLtxMacro\LWR@origslshape\slshape
\LetLtxMacro\LWR@origscshape\scshape
```

```
\@ifundefined{sishape}{
    \LetLtxMacro\LWR@origsishape\scshape
}{
    \LetLtxMacro\LWR@origsishape\sishape
}
```

```
\LetLtxMacro\LWR@origitshape\itshape
\LetLtxMacro\LWR@origem\em
\LetLtxMacro\LWR@orignormalfont\normalfont
```

```

\let\LWR@origonecolumn\onecolumn

\let\LWR@origsp\sp
\let\LWR@origsb\sb
\LetLtxMacro\LWR@origtextsuperscript\textsuperscript
\LetLtxMacro\LWR@orig@textsuperscript\@textsuperscript

\AtBeginDocument{
\LetLtxMacro\LWR@origtextsubscript\textsubscript
\LetLtxMacro\LWR@orig@textsubscript\@textsubscript
}

\LetLtxMacro\LWR@origunderline\underline

\let\LWR@orignewpage\newpage

\let\LWR@origpagestyle\pagestyle
\let\LWR@origthispagestyle\thispagestyle
\LetLtxMacro\LWR@origpagenumbering\pagenumbering

\let\LWR@orignewline\newline


\AtBeginDocument{% in case packages change definition
\let\LWR@orig@trivlist\@trivlist
\let\LWR@origtrivlist\trivlist
\let\LWR@origendtrivlist\endtrivlist
\LetLtxMacro\LWR@origitem\item
\LetLtxMacro\LWR@origitemize\itemize
\LetLtxMacro\LWR@endorigitemize\enditemize
\LetLtxMacro\LWR@origenumerate\enumerate
\LetLtxMacro\LWR@endorigenumerate\endenumerate
\LetLtxMacro\LWR@origdescription\description
\LetLtxMacro\LWR@endorigdescription\enddescription
\let\LWR@orig@mklab\@mklab
\let\LWR@origmakelabel\makelabel
\let\LWR@orig@donoparitem\@donoparitem
\LetLtxMacro\LWR@orig@item\@item
\let\LWR@orig@nbitem\@nbitem
}

\let\LWR@origpar\par

\LetLtxMacro\LWR@origfootnote\footnote
\let\LWR@orig@mpfootnotetext\@mpfootnotetext

\let\LWR@origclearpage\clearpage


\AtBeginDocument{% in case packages change definition
\LetLtxMacro\LWR@orighline\hline%
\LetLtxMacro\LWR@origcline\cline%
}
```

```
\end{warpHTML}
```

39 Accents

Native LaTeX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX.

for HTML output:

```
\begin{warpHTML}
```

Without \AtBeginDocument, \t was being re-defined somewhere.

```
\AtBeginDocument{
```

The following are restored for print when inside a lateximage.

For Unicode engines, only \t needs to be redefined:

```
\LetLtxMacro\LWR@origt\t
```

For pdfLaTeX, additional work is required:

```
\ifPDFTeX% pdflatex or dvi latex
\LetLtxMacro\LWR@origequalaccent\=
\LetLtxMacro\LWR@origdotaccent\.
\LetLtxMacro\LWR@origu\u
\LetLtxMacro\LWR@origv\v
\LetLtxMacro\LWR@origc\c
\LetLtxMacro\LWR@origd\d
\LetLtxMacro\LWR@origb\b
```

The HTML redefinitions follow.

For pdfLaTeX, Unicode diacritical marks are used:

```
\renewcommand*{\=}[1]{#1\HTMLunicode{0305}}
\renewcommand*{\.}[1]{#1\HTMLunicode{0307}}
\renewcommand*{\u}[1]{#1\HTMLunicode{0306}}
\renewcommand*{\v}[1]{#1\HTMLunicode{030C}}
\renewcommand*{\c}[1]{#1\HTMLunicode{0327}}
\renewcommand*{\d}[1]{#1\HTMLunicode{0323}}
\renewcommand*{\b}[1]{#1\HTMLunicode{0331}}
\fi
```

For all engines, a Unicode diacritical tie is used:

```
\def\LWR@t#1#2{#1\HTMLunicode{0361}#2}
\renewcommand*{\t}[1]{\LWR@t#1}
```

\LWR@restoreorigaccents Called from \restoreoriginalformatting when a lateximage is begun.

```
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@restoreorigaccents}{%
\LetLtxMacro\=\LWR@origequalaccent%
\LetLtxMacro\.\LWR@origdotaccent%
\LetLtxMacro\u\LWR@origu%
\LetLtxMacro\v\LWR@origu%
\LetLtxMacro\t\LWR@origt%
\LetLtxMacro\c\LWR@origc%
\LetLtxMacro\d\LWR@origd%
\LetLtxMacro\b\LWR@origb%
}%
\else% XeLaTeX, LuaLaTeX:
\newcommand*{\LWR@restoreorigaccents}{%
\LetLtxMacro\t\LWR@origt%
}%
\fi%
}% AtBeginDocument
```

```
\end{warpHTML}
```

40 Configuration files

40.1 Decide whether to generate configuration files

Configuration files are only written if processing the print version of the document, and not processing a pstool image. pstool uses an additional compile for each image using the original document's preamble, which includes lwarp, so the lwarp configuration files are turned off if `-pstool` is part of the `\jobname`.

Default to no configuration files:

```
\excludecomment{LWRwriteconf}
```

Generate configuration files if print mode and not `-pstool`:

for PRINT output:

```
\begin{warpprint}
\fullexpandarg%
\IfSubStr*{\jobname}{-pstool}
    {
        \typeout{lwarp: jobname with -pstool is found,}%
        \typeout{lwarp: \space\space not generating configuration files.}%
    }
    {
        \typeout{lwarp: generating configuration files}
        \includecomment{LWRwriteconf}
    }
\end{warpprint}
```

40.2 <project>_html.tex

File *_html.tex Used to allow an HTML version of the document to exist alongside the print version.

Config file:
```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=\jobname_html.tex
\immediate\write\LWR@quickfile{%
\detokenize{\PassOptionsToPackage}%
{warpHTML,BaseJobname=\jobname}{lwarp}%
}
\immediate\write\LWR@quickfile{%
\detokenize{\input}\string{\jobname.tex\string }%
}
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.3 *lwarpmk* configuration files

Config file:
```
\begin{LWRwriteconf}
```

\LWR@lwarpconfversion The version number of the configuration file, allowing *lwarpmk* to detect an obsolete configuration file format. Incremented by one each time the configuration file format changes. (This is NOT the same as the lwarp version number.)

```
\newcommand*{\LWR@lwarpconfversion}{2}% also in lwarpmk.lua
```

40.3.1 Helper macros

\LWR@shellescapecmd The LaTeX compile option for shell escape, if used.

```
\ifshellescape
    \def\LWR@shellescapecmd{--shell-escape }
\else
    \def\LWR@shellescapecmd{}
\fi
```

\LWR@compilecmd {⟨*engine*⟩} {⟨*suffix*⟩}

Used to form the basic compilation command for a document, adding the optional shell escape.

Engine is *pdflatex*, etc. Suffix is empty or _html

```
\newcommand*{\LWR@compilecmd}[2]{%
    #1 \LWR@shellescapecmd \jobname#2%
}
```

\LWR@addcompilecmd {⟨*cmd*⟩} {⟨*suffix*⟩}

Adds to the compilation command.

Cmd is *dvipdfmx*, etc. Suffix is empty or `_html`

```
\newcommand*{\LWR@addcompilecmd}[2]{%
    \LWRopseq
    #1 \jobname#2%
}
```

`\LWR@unknownengine` Error message if not sure which LaTeX engine is being used.

```
\newcommand*{\LWR@unknownengine}{%
    \PackageError{lwarp}
    {Unknown LaTeX engine.}
   {Lwarp only knows about pdflatex, dvi latex, xelatex, lualatex, and upLateX.}
}
```

`\LWR@latexmkvar` {⟨*varname*⟩} {⟨*value*⟩}

Adds a *latexmk* variable assignment.

```
\newcommand*{\LWR@latexmkvar}[2]{%
    -e
    \LWRopquote%
    \LWRdollar #1=q/#2/%
    \LWRopquote
}
```

`\LWR@latexmkcmd` {⟨*latexmk options*⟩}

Sets a call to *latexmk* with the given options, possibly adding `--shell-escape`, and also adding the indexing program.

```
\newcommand*{\LWR@latexmkcmd}[1]{%
    latexmk  \space \LWR@shellescapecmd \space  #1 \space
    -recorder \space
    \LWR@latexmkvar{makeindex}{\LWR@LatexmkIndexCmd}
}
```

`\LWR@latexmkdvipdfm` {⟨*dvipdfm or dvipdfmx*⟩}

Adds the options settings for *dvipdfm* or *dvipdfmx*.

```
\newcommand*{\LWR@latexmkdvipdfm}[1]{%
    -pdfdvi \space
    \LWR@latexmkvar{dvipdf}{%
        #1
        \@percentchar O
        -o \@percentchar D
        \@percentchar S%
    }
}
```

\LWR@compileuplatex Sets compile options for upLaTeX with ujarticle or related classes.

```
\newcommand*{\LWR@compileuplatex}{
    \def\LWR@tempprintlatexcmd{%
        \LWR@compilecmd{uplatex}{}
        \LWR@addcompilecmd{dvipdfmx}{}
    }
    \def\LWR@tempHTMLlatexcmd{%
        \LWR@compilecmd{uplatex}{_html}
        \LWR@addcompilecmd{dvipdfmx}{_html}
    }
}
```

\LWR@PrintLatexCmd
\LWR@HTMLLatexCmd

If not set by the user, the following sets the command to use to compile the source to PDF form.

If using *latexmk*, a complicated string is created, eventually resulting in something such as:

For *xelatex* with `--shell-escape`:

```
[[latexmk   -xelatex   --shell-escape  -recorder
    -e '$makeindex = q/makeindex -s lwarp.ist/'  <jobname>_html]]
```

For *dvipdfmx*:

```
[[latexmk   -pdfdvi  -e '$dvipdf=q/dvipdfmx %O -o %D %S/'
    -recorder
    -e '$makeindex=q/makeindex -s lwarp.ist/'   <jobname>_html]]
```

For the following, temporary values are computed, but the permanent values are only set if the originals were not assigned by the user.

```
\ifbool{LWR@latexmk}{
```

For *latexmk* with *pdflatex* or *lualatex*:

```
    \ifpdf
```

For *latexmk* with *pdflatex*:

```
        \ifPDFTeX
            \def\LWR@latexcmd{\LWR@latexmkcmd{-pdf -dvi- -ps-}}
        \else
```

For *latexmk* with *lualatex*:

```
            \ifLuaTeX
```

```
                \def\LWR@latexcmd{\LWR@latexmkcmd{-lualatex}}
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For *latexmk* with *xelatex* or DVI *latex*:

```
        \ifXeTeX
```

For *latexmk* with *xelatex*:

```
            \def\LWR@latexcmd{\LWR@latexmkcmd{-xelatex}}
        \else% \ifXeTeX
```

For *latexmk* with DVI *latex*:

```
            \ifbool{LWR@dvipdfm}{
                \def\LWR@latexcmd{%
                    \LWR@latexmkcmd{%
                        \LWR@latexmkdvipdfm{dvipdfm}%
                    }
                }
            }{
                \ifbool{LWR@dvipdfmx}{
                    \def\LWR@latexcmd{%
                        \LWR@latexmkcmd{%
                            \LWR@latexmkdvipdfm{dvipdfmx}%
                        }
                    }
                }{
                    \def\LWR@latexcmd{\LWR@latexmkcmd{-pdfps}}
                }
            }
        \fi
    \fi% \ifpdf
```

The final assignment if *latexmk*:

```
    \def\LWR@tempprintlatexcmd{\LWR@latexcmd \space \jobname}
    \def\LWR@tempHTMLlatexcmd{\LWR@latexcmd \space \jobname_html}
}% latexmk
```

Without *latexmk*, the compiling command is simply the compiler name and the optional shell escape:

```
{% not latexmk
    \ifpdf
```

For *pdflatex* or *lualatex*:

```
        \ifPDFTeX
```

For *pdflatex*:

```
            \def\LWR@tempprintlatexcmd{\LWR@compilecmd{pdflatex}{}}
            \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{pdflatex}{_html}}
        \else
            \ifLuaTeX
```

For *lualatex*:

```
                \def\LWR@tempprintlatexcmd{\LWR@compilecmd{lualatex}{}}
                \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{lualatex}{_html}}
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For DVI *latex* or *xelatex*:

```
        \ifXeTeX
```

For *xelatex*:

```
            \def\LWR@tempprintlatexcmd{\LWR@compilecmd{xelatex}{}}
            \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{xelatex}{_html}}
        \else
```

For DVI *latex*. Default to *dvips*, unless told to use *dvipdfm* or *dvipdfmx*:

```
            \ifbool{LWR@dvipdfm}{
```

For DVI *latex* with *dvipdfm*:

```
                \def\LWR@tempprintlatexcmd{%
                    \LWR@compilecmd{latex}{}
                    \LWR@addcompilecmd{dvipdfm}{}
                }
                \def\LWR@tempHTMLlatexcmd{%
                    \LWR@compilecmd{latex}{_html}
                    \LWR@addcompilecmd{dvipdfm}{_html}
                }
            }{
                \ifbool{LWR@dvipdfmx}{
```

For DVI *latex* with *dvipdfmx*:

```
                    \def\LWR@tempprintlatexcmd{%
                        \LWR@compilecmd{latex}{}
                        \LWR@addcompilecmd{dvipdfmx}{}
                    }
                    \def\LWR@tempHTMLlatexcmd{%
                        \LWR@compilecmd{latex}{_html}
                        \LWR@addcompilecmd{dvipdfmx}{_html}
                    }
```

```
                }{% dvips
```

For DVI *latex* with *dvips* and *ps2pdf*:

```
                    \def\LWR@tempprintlatexcmd{%
                        \LWR@compilecmd{latex}{}
                        \LWR@addcompilecmd{dvips}{}
                        \LWR@addcompilecmd{ps2pdf}{}.ps
                    }
                    \def\LWR@tempHTMLlatexcmd{%
                        \LWR@compilecmd{latex}{_html}
                        \LWR@addcompilecmd{dvips}{_html}
                        \LWR@addcompilecmd{ps2pdf}{_html}.ps
                    }
                }
            }
        \fi% \ifXeTeX
    \fi% \ifpdf
}% latexmk
```

For ujarticle, utarticle, and related, using upLaTeX and *dvipdfmx*:

```
\@ifclassloaded{ujarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{ujbook}{\LWR@compileuplatex}{}
\@ifclassloaded{ujreport}{\LWR@compileuplatex}{}
\@ifclassloaded{utarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{utbook}{\LWR@compileuplatex}{}
\@ifclassloaded{utreport}{\LWR@compileuplatex}{}
```

Only make the setting permanent if the original was empty:

```
\ifdefempty{\LWR@PrintLatexCmd}{
    \def\LWR@PrintLatexCmd{\LWR@tempprintlatexcmd}
}{}
\ifdefempty{\LWR@HTMLLatexCmd}{
    \def\LWR@HTMLLatexCmd{\LWR@tempHTMLlatexcmd}
}{}
```

`\LWR@writeconf` {⟨*filename*⟩}

Common code for each of `lwarpmk.conf` and `<project>.lwarpmkconf`. Each entry is a variable name, the equal sign, and a quoted string inside `[[` and `]]`, which are *lua*'s long quote characters, allowing the use of single and double quotes inside.

```
\newcommand{\LWR@writeconf}[1]{
\ifcsdef{LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
\immediate\openout\LWR@quickfile=#1
\immediate\write\LWR@quickfile{confversion = [[\LWR@lwarpconfversion]]}
\ifbool{usingOSWindows}{
    \immediate\write\LWR@quickfile{opsystem = [[Windows]]}
}{
    \immediate\write\LWR@quickfile{opsystem = [[Unix]]}
}
\immediate\write\LWR@quickfile{sourcename = [[\jobname]]}
```

```
\immediate\write\LWR@quickfile{homehtmlfilename = [[\HomeHTMLFilename]]}
\immediate\write\LWR@quickfile{htmlfilename = [[\HTMLFilename]]}
\immediate\write\LWR@quickfile{imagesdirectory = [[\LWR@ImagesDirectory]]}
\immediate\write\LWR@quickfile{imagesname = [[\LWR@ImagesName]]}
\immediate\write\LWR@quickfile{latexmk = [[\ifbool{LWR@latexmk}{true}{false}]]}
\immediate\write\LWR@quickfile{printlatexcmd = [[\LWR@PrintLatexCmd]]}
\immediate\write\LWR@quickfile{HTMLlatexcmd = [[\LWR@HTMLLatexCmd]]}
\immediate\write\LWR@quickfile{printindexcmd = [[\LWR@PrintIndexCmd]]}
\immediate\write\LWR@quickfile{HTMLindexcmd = [[\LWR@HTMLIndexCmd]]}
\immediate\write\LWR@quickfile{latexmkindexcmd = [[\LWR@LatexmkIndexCmd]]}
\immediate\write\LWR@quickfile{glossarycmd = [[\LWR@GlossaryCmd]]}
\immediate\write\LWR@quickfile{pdftotextenc = [[\LWR@pdftotextEnc]]}
\immediate\closeout\LWR@quickfile
}

\end{LWRwriteconf}
```

40.3.2 lwarpmk.conf

File lwarpmk.conf

lwarpmk.conf is automatically (re-)created by the lwarp package when executing

```
pdflatex <project.tex>,
```

or similar for *xelatex* or *lualatex*, in print-document generation mode, which is the default unless the warpHTML option is given. lwarpmk.conf is then used by the utility *lwarpmk*.

Config file:

```
\begin{LWRwriteconf}

\AtBeginDocument{\LWR@writeconf{lwarpmk.conf}}

\end{LWRwriteconf}
```

40.3.3 <project>.lwarpmkconf

File project.lwarpmkconf

A project-specific configuration file for *lwarpmk*.

The makeindex and xindy options have already been handled for lwarp.conf.

Config file:

```
\begin{LWRwriteconf}

\AtBeginDocument{\LWR@writeconf{\jobname.lwarpmkconf}}

\end{LWRwriteconf}
```

40.4 lwarp.css

File lwarp.css

This is the base CSS layer used by lwarp.

This must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.css}
/*
  CSS stylesheet for the LaTeX lwarp package
  Copyright 2016-2018 Brian Dunn --- BD Tech Concepts LLC
*/


/* a fix for older browsers: */
header, section, footer, aside, nav, main,
    article, figure { display: block; }


A:link {color:#000080 ; text-decoration: none ; }
A:visited {color:#800000 ; }
A:hover {color:#000080 ; text-decoration: underline ;}
A:active {color:#800000 ; }

a.tocpart {display: inline-block ; margin-left: 0em ;
    font-weight: bold ;}
a.tocchapter {display: inline-block ; margin-left: 0em ;
    font-weight: bold ;}
a.tocsection {display: inline-block ; margin-left: 1em ;
    text-indent: -.5em ; font-weight: bold ; }
a.tocsubsection {display: inline-block ; margin-left: 2em ;
    text-indent: -.5em ; }
a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
    text-indent: -.5em ; }
a.tocparagraph {display: inline-block ; margin-left: 4em ;
    text-indent: -.5em ; }
a.tocsubparagraph {display: inline-block ; margin-left: 5em ;
    text-indent: -.5em ; }
a.tocfigure {margin-left: 0em}
a.tocsubfigure {margin-left: 2em}
a.toctable {margin-left: 0em}
a.tocsubtable {margin-left: 2em}
a.toctheorem {margin-left: 0em}
a.toclstlisting {margin-left: 0em}

body {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
        "Lucida Bright", Georgia, serif;
    background: #FAF7F4 ;
    color: black ;
    margin:0em ;
    padding:0em ;
    font-size: 100% ;
    line-height: 1.2 ;
}

p {margin: 1.5ex 0em 1.5ex 0em ;}
table p {margin: .5ex 0em .5ex 0em ;}

/* Holds a section number */
span.sectionnumber { margin-right: 0em }

```

```
/* Inserted in front of index lines */
span.indexitem {margin-left: 0em}
span.indexsubitem {margin-left: 2em}
span.indexsubsubitem {margin-left: 4em}

div.hidden, span.hidden { display: none ; }

kbd, span.texttt {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
    font-size: 100% ;
}

pre { padding: 3pt ; }

span.strong, span.textbf, div.strong, div.textbf { font-weight: bold; }

span.textit, div.textit { font-style: italic; }

span.textmd, div.textmd { font-weight: normal; }

span.textsc, div.textsc {
    font-variant: small-caps;
    font-variant-numeric: oldstyle-nums ;
}

span.textsi, div.textsi {
    font-style: italic ;
    font-variant: small-caps;
    font-variant-numeric: oldstyle-nums ;
}

span.textsl, div.textsl { font-style: oblique; }

span.textup, div.textup {
    font-style: normal;
    font-variant: normal;
    font-variant-numeric: normal ;
}

span.textrm, div.textrm {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
    "Lucida Bright", Georgia, serif;
}

span.textsf, div.textsf {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
}

span.textcircled { border: 1px solid black ; border-radius: 1ex ; }

span.underline {
    text-decoration: underline ;
```

```
    text-decoration-skip: auto ;
}

span.overline {
    text-decoration: overline ;
    text-decoration-skip: auto ;
}


/* for vertical text: */
div.verticalrl { writing-mode: vertical-rl }
div.horizontaltb { writing-mode: horizontal-tb }


/* for diagbox */
div.diagboxtitleN { border-bottom: 1px solid gray }
div.diagboxtitleS { border-top: 1px solid gray }

div.diagboxE {
    padding-left: 2em ;
    text-align: right ;
}

div.diagboxW {
    padding-right: 2em ;
    text-align: left ;
}



/* For realscripts */
.supsubscript {
    display: inline-block;
    text-align:left ;
}

.supsubscript sup,
.supsubscript sub {
    position: relative;
    display: block;
    font-size: .5em;
    line-height: 1;
}

.supsubscript sup {
    top: .5em;
}

.supsubscript sub {
    top: .5em;
}

div.attribution p {
    text-align: right ;
    font-size: 80%
```

```
}

span.poemtitle {
  font-size: 120% ; font-weight: bold;
}

pre.tabbing {
    font-family: "Linux Libertine Mono O", "Lucida Console",
        "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
        "Liberation Mono", "FreeMono", "Andale Mono",
        "Nimbus Mono L", "Courier New", monospace;
}

blockquote {
    display: block ;
    margin-left: 2em ;
    margin-right: 2em ;
}

blockquotation {
    display: block ;
    margin-left: 2em ;
    margin-right: 2em ;
}

/* quotchap is for the quotchap package */
div.quotchap {
    display: block ;
    font-style: oblique ;
    overflow-x: auto ;
    margin-left: 2em ;
    margin-right: 2em ;
}

blockquote p, blockquotation p, div.quotchap p {
    line-height: 1.5;
    text-align: left ;
    font-size: .85em ;
}

/* qauthor is for the quotchap package */
div.qauthor {
  display: block ;
  text-align: right ;
  margin-left: auto ;
  margin-right: 2em ;
  font-size: 80% ;
  font-variant: small-caps;
}

div.qauthor p {
  text-align: right ;
}

div.epigraph, div.dictum {
```

```
  line-height: 1.2;
    text-align: left ;
    padding: 3ex 1em 0ex 1em ;
/*     margin: 3ex auto 3ex auto ; */ /* Epigraph centered */
    margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
/*    margin: 3ex 1em 3ex 1em ; */ /* Epigraph to the left */
    font-size: .85em ;
    max-width: 27em ;
}

div.epigraphsource, div.dictumauthor {
    text-align:right ;
    margin-left:auto ;
/*     max-width: 50% ; */
    border-top: 1px solid #A0A0A0 ;
    padding-bottom: 3ex ;
    line-height: 1.2;
}

div.epigraph p, div.dictum p { padding: .5ex ; margin: 0ex ;}
div.epigraphsource p, div.dictumauthor p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
div.dictumauthor { font-style:italic }


/* copyrightbox package */
div.copyrightbox { margin: .5ex .5em }
div.copyrightbox p {margin: 0px .5em ; padding: 0px}
div.copyrightboxnote {text-align: left ; font-size: 60%}


/* lettrine package: */
span.lettrine { font-size: 4ex ; float: left ; }
span.lettrinetext { font-variant: small-caps ; }

/* ulem, soul, umoline packages: */
span.uline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
}

span.uuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: double ;
}

span.uwave {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: wavy ;
}

span.sout {
    text-decoration: line-through ;
}
```

```

span.oline {
    text-decoration: overline ;
    text-decoration-skip: auto ;
}

span.xout {
    text-decoration: line-through ;
}

span.dashuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: dashed ;
}

span.dotuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: dotted ;
}

span.letterspacing { letter-spacing: .2ex ; }

span.capsspacing {
    font-variant: small-caps ;
    letter-spacing: .1ex ;
}

span.highlight { background: #F8E800 ; }



html body {
  margin: 0 ;
  line-height: 1.2;
}


body div {
  margin: 0ex;
}


h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}
```

```

h1 {    /* title of the entire website, used on each page */
    text-align: center ;
    font-size: 2.5em ;
    padding: .4ex 0em 0ex 0em ;
}
h2 { font-size: 2.25em }
h3 { font-size: 2em }
h4 { font-size: 1.75em }
h5 { font-size: 1.5em }
h6 { font-size: 1.25em }
span.paragraph {font-size: 1em ; font-variant: normal ;
    margin-right: 1em ; }
span.subparagraph {font-size: 1em ; font-variant: normal ;
    margin-right: 1em ;  }

div.minisec {
    font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}

h1 {
  margin: 0ex 0em 0ex 0em ;
  line-height: 1.3;
  text-align: center ;
}

h2 {
  margin: 1ex 0em 1ex 0em ;
  line-height: 1.3;
  text-align: center ;
}

h3 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h4 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h5 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h6 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}
```

```
div.titlepage {
  text-align: center ;
}

.footnotes {
    text-align: left ;
    font-size: .85em ;
    margin: 3ex 2em 0ex 2em ;
    border-top: 1px solid silver ;
}

.marginpar, .marginparblock {
    max-width: 50%;
    float: right ;
    clear: both ;
    text-align: left ;
    margin: 1ex 0.5em 1ex 1em ;
    padding: 1ex 0.5em 1ex 0.5em ;
    font-size: 85% ;
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
    overflow-x: auto ;
}

.marginpar br { margin-bottom: 2ex ; }

div.marginblock, div.marginparblock {
    max-width:50%;
    min-width: 10em; /* room for caption */
    float:right;
    text-align:left;
    margin: 1ex 0.5em 1ex 1em ;
    padding: 1ex 0.5em 1ex 0.5em ;
    overflow-x: auto;
}

div.marginblock div.minipage,
div.marginparblock div.minipage {
    display: block ;
    margin: 0pt auto 0pt auto ;
}

div.marginblock div.minipage p ,
div.marginparblock div.minipage p
    { font-size: 85%}

div.marginblock br ,
div.marginparblock br
    { margin-bottom: 2ex ; }

div.bodycontainer {
    float: left ;
    width: 80% ;
```

```
}

div.bodywithoutsidetoc div.bodycontainer {
    float: none ;
    width: 100% ;
}

section.textbody div.footnotes{
    margin: 3ex 2em 0ex 2em ;
    border-bottom: 2px solid silver ;
}

.footnoteheader {
    border-top: 2px solid silver ;
    margin-top: 3ex ;
    padding-top: 1ex ;
    font-weight: bold ;
}

.mpfootnotes {
    text-align: left ;
    font-size: .85em ;
    margin-left: 1em ;
    border-top: 1px solid silver ;
}

/* Remove footnote top border in the title page. */
div.titlepage div.mpfootnotes {
    border-top: none ;
}



ul, ol {
  margin: 1ex 1em 1ex 0em;
  line-height: 1.2;
}

body dir, body menu {
  margin: 3ex 1em 3ex 0em;
  line-height: 1.2;
}

li { margin: 0ex 0em 1ex 0em; }

html {
  margin: 0;
  padding: 0;
}

.programlisting {
  font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
  margin: 1ex 0ex 1ex 0ex ;
```

```
  padding: .5ex 0pt .5ex 0pt ;
  overflow-x: auto;
}

section.textbody>pre.programlisting {
border-top: 1px solid silver ;
border-bottom: 1px solid silver ;
}


div.displaymath {
    text-align: center ;
}

div.displaymathnumbered {
    text-align: right ;
    margin-left: 5% ;
    margin-right: 5% ;
    min-width: 2.5in ;
}

@media all and (min-width: 400px) {
    div.displaymathnumbered {
        margin-left: 10% ;
        margin-right: 10% ;
    }
}

@media all and (min-width: 800px) {
    div.displaymathnumbered {
        margin-right: 20% ;
    }
}

@media all and (min-width: 1200px) {
    div.displaymathnumbered {
        margin-right: 30% ;
    }
}


.inlineprogramlisting {
  font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
  overflow-x: auto;
}

span.listinglabel {
    display: inline-block ;
    font-size: 70% ;
    width: 4em ;
    text-align: right ;
    margin-right: 2em ;
}
```

```
div.abstract {
  margin: 2em 5% 2em 5% ;
  padding: 1ex 1em 1ex 1em ;
/*  font-weight: bold ; */
  font-size: 90% ;
    text-align: left ;
}

div.abstract dl {line-height:1.5;}
div.abstract dt {color:#304070;}

div.abstracttitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-size:1.25em;
    text-align: center ;
}

span.abstractrunintitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
}


.verbatim {
    overflow-x: auto ;
}

.alltt {
    overflow-x: auto ;
}


.bverbatim {
    margin: 1ex 0pt 1ex 0pt ;
    padding: .5ex 0pt .5ex 0pt ;
    overflow-x: auto ;
}

.lverbatim {
    margin: 1ex 0pt 1ex 0pt ;
    padding: .5ex 0pt .5ex 0pt ;
    overflow-x: auto ;
}

.fancyvrb {
    font-size:.85em ;
    margin: 3ex 0pt 3ex 0pt
}

```

```
.fancyvrblabel {
    font-weight:bold;
    text-align: center ;
}


.verse {
    font-family: "Linux Libertine Mono O", "Lucida Console",
        "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
        "Liberation Mono", "FreeMono", "Andale Mono",
        "Nimbus Mono L", "Courier New", monospace;
    margin-left: 1em ;
}


div.singlespace { line-height: 1.2 ; }
div.onehalfspace { line-height: 1.5 ; }
div.doublespace { line-height: 2 ; }


/* Word processor format output: */
div.wpfigure { border: 1px solid red ; margin: .5ex ; padding: .5ex ; }
div.wptable { border: 1px solid blue ; margin: .5ex ; padding: .5ex ; }
div.wpminipage { border: 1px solid green ; margin: .5ex ; padding: .5ex ;}




/* Minipage environments, vertically aligned to top, center, bottom: */
.minipage, .fminipage, .fcolorminipage {
    /* display: inline-block ; */
        /* Mini pages which follow each other will be tiled. */
    margin: .25em .25em .25em .25em;
    padding: .25em .25em .25em .25em;
    display: inline-flex;
    flex-direction: column ;
    overflow: auto;
}

/* Paragraphs in the flexbox did not collapse their margins. */
/* Have not yet researched this. */
.minipage p {margin: .75ex 0em .75ex 0em ;}

.fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
.fcolorbox .minipage, .fcolorboxBlock .minipage
    {border: none ; background: none;}

.fbox, .fboxBlock { border: 1px solid black ; }

.fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
.fminipage, .fcolorminipage
    {display: inline-block}

.shadowbox, .shabox {
   border: 1px solid black;
```

```
    box-shadow: 3px 3px 3px #808080 ;
     border-radius: 0px ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.doublebox {
   border: 3px double black;
     border-radius: 0px ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.ovalbox, .Ovalbox {
   border: 1px solid black;
     border-radius: 1ex ;
    padding: .4ex .3em .4ex .3em ;
    margin: 0pt .3ex 0pt .3ex ;
  display: inline-block ;
}

.Ovalbox { border-width: 2px ; }

.framebox {
   border: 1px solid black;
     border-radius: 0px ;
    padding: .3ex .2em 0ex .2em ;
    margin: 0pt .1ex 0pt .1ex ;
  display: inline-block ;
}


.mdframed {
    padding: 0ex ;
    margin: 2ex 0em 2ex 0em ;
}

.mdframed p { padding: 0ex .5em 0ex .5em ; }

.mdframed dl { padding: 1ex .5em 0ex .5em ; }

.mdframedtitle {
    padding: .5ex 0pt 0pt 0pt ;
    border-radius: 10pt 10pt 0pt 0pt ;
    display: block ;
    margin-bottom: 1ex ;
}

.mdframedsubtitle {
    display: block ;
}

.mdframedsubsubtitle {
```

```
    display: block ;
}

.mdtheorem {
    padding: 0ex .5em 0ex .5em ;
    margin: 3ex 5% 3ex 5% ;
}


/* framed package */
.framed, pre.boxedverbatim, fcolorbox {
    margin: 3ex 0em 3ex 0em ;
   border: 1px solid black;
     border-radius: 0px ;
    padding: .3ex 1em 0ex 1em ;
  display: block ;
}

.shaded {
    margin: 3ex 0em 3ex 0em ;
    padding: .3ex 1em .3ex 1em ;
    display: block ;
}

.snugframed {
    margin: 3ex 0em 3ex 0em ;
   border: 1px solid black;
     border-radius: 0px ;
  display: block ;
}

.framedleftbar {
    margin: 3ex 0em 3ex 0em ;
   border-left: 3pt solid black;
     border-radius: 0px ;
    padding: .3ex .2em .3ex 1em ;
  display: block ;
}

.framedtitle {
    margin: 0em ;
    padding: 0em ;
    font-size: 130%
}

.framedtitle p { padding: .3em }


/* For the niceframe package: */

div.niceframe, div.curlyframe, div.artdecoframe, div.generalframe {
    padding: 1ex ;
    margin: 2ex auto ;
    border-radius: 2ex ;
}
```

```
div.niceframe {
    border: 6px groove black ;
}

div.curlyframe {
    border-left: 3px dotted black ;
    border-right: 3px dotted black ;
    border-radius: 6ex ;
}

div.artdecoframe {
    border-left: 10px double black ;
    border-right: 10px double black ;
    border-radius: 6ex ;
}

div.generalframe {
    border: 6px groove black ;
}



dl {
  margin: 1ex 2em 1ex 0em;
  line-height: 1.3;
}

dl dt {
    display: block ;
    float:left ;
    font-weight: bold;
    padding-right: 1em ;
}

dl dd { display: block ; }

dl dd:after { content: "" ; display: block ; clear: both }

dl dd p { margin-top: 0em; }

dd ul, dd ol, dd dl { clear: both ; padding-top: 1ex }


nav {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    margin-bottom: 4ex ;
}

nav p {
    line-height: 1.2 ;
    margin-top:.5ex ;
    margin-bottom:.5ex;
```

```
    font-size: .9em ;
}



img, img.hyperimage, img.borderimage {
    max-width: 600px;
    border: 1px solid silver;
    box-shadow: 3px 3px 3px #808080 ;
    padding: .5% ;
    margin: .5% ;
    background: none ;
}

img.inlineimage{
    padding: 0px ;
    box-shadow: none ;
    border: none ;
    background: none ;
    margin: 0px ;
    display: inline-block ;
    border-radius: 0px ;
}

img.logoimage{
    max-width: 300px ;
    box-shadow: 3px 3px 3px #808080 ;
    border: 1px solid black ;
    background:none ;
    padding:0 ;
    margin:.5ex ;
    border-radius: 10px ;
}


.section {
/*
    To have each section float relative to each other:
*/
/*
    display: block ;
    float: left ;
    position: relative ;
    background: white ;
    border: 1px solid silver ;
    padding: .5em ;
*/
    margin: 0ex .5em 0ex .5em ;
    padding: 0 ;
}


figure {
    margin: 5ex auto 5ex auto ;
    padding: 1ex 1em 1ex 1em ;
```

```
    overflow-x: auto ;
}


/* To automatically center images in figures: */
/*
figure img.inlineimage {
    margin: 0ex auto 0ex auto ;
    display: block ;
}
*/

/* To automatically center minipages in figures: */
/*
figure div.minipage, figure div.minipage div.minipage {
    margin: 1ex auto 1ex auto ;
    display: block ;
}
*/

figure figure { margin: 0pt }

figure div.minipage p { font-size: 85% ; }

figure.subfigure, figure.subtable  {
    display: inline-block ; margin: 3ex 1em 3ex 1em ;
}

div.figurecaption .minipage { margin:0 ; padding: 0 }

div.minipage figure { border: none ; box-shadow: none ; }
div.minipage figure.table { margin: 0ex }
div.minipage div.footnotes { margin: 1ex 2em 0ex 2em }

div.floatrow { text-align: center; }

div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }

div.floatfoot { font-size: .85em ;
    border-top: 1px solid silver ; line-height: 1.2 ; }

div.figurecaption , .lstlistingtitle {
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
    margin-top: 1ex ;
    margin-bottom: 1ex ;
}

figure.subfigure div.figurecaption, figure.subtable div.figurecaption  {
    border-bottom: none ; background: none ;
}

div.nonfloatcaption {
    margin: 1ex auto 1ex auto ;
```

```
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
}

/* For a \RawCaption inside a minipage inside a figure's floatrow: */
figure div.floatrow div.minipage div.figurecaption {
    border: none ;
    background: none ;
}


/* For packages such as float, rotfloat, and algorithm2e: */

figure.boxed, figure.boxruled {
    border: 1px solid black ;
}

figure.ruled {
    border-top: 1px solid black ;
    border-bottom: 1px solid black ;
    border-left: 0px ;
    border-right: 0px ;
    border-radius: 0px ;
    background: none ;
    box-shadow: none ;
}

figure.ruled div.figurecaption, figure.boxruled div.figurecaption {
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
}


table {
    margin: 1ex auto 1ex auto ;
    border-collapse: separate ;
    border-spacing: 0px ;
    line-height: 1.3 ;
    }

tr.hline td {border-top: 1px solid #808080 ; margin-top: 0ex ;
    margin-bottom: 0ex ; } /* for \hline */

tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;
    margin-bottom: 0ex ; } /* for \toprule, \bottomrule */

td {padding: .5ex .5em .5ex .5em ;}

table td.tdl { text-align: left ; vertical-align: middle ; }
table td.tdc { text-align: center ; vertical-align: middle ; }
table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }
table td.tdbang { text-align: center ; vertical-align: middle ; }
table td.tdr { text-align: right ; vertical-align: middle ; }
table td.tdp { text-align: left ; vertical-align: bottom ; }
```

```
table td.tdm { text-align: left ; vertical-align: middle ; }
table td.tdb { text-align: left ; vertical-align: top ; }
table td.tdP { text-align: center ; vertical-align: bottom ; }
table td.tdM { text-align: center ; vertical-align: middle ; }
table td.tdB { text-align: center ; vertical-align: top ; }

table td.tvertbarl { border-left: 1px solid black }
table td.tvertbarldouble { border-left: 4px double black }
table td.tvertbarr { border-right: 1px solid black }
table td.tvertbarrdouble { border-right: 4px double black }

table td.tvertbarldash { border-left: 1px dashed black }
table td.tvertbarldoubledash { border-left: 2px dashed black }
table td.tvertbarrdash { border-right: 1px dashed black }
table td.tvertbarrdoubledash { border-right: 2px dashed black }


/* for cmidrules: */
table td.tdrule {
    border-top: 1px solid #A0A0A0 ;
}

table td.tdrulel {
    border-top-left-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}

table td.tdruler {
    border-top-right-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}

table td.tdrulelr {
    border-top-left-radius:.5em ;
    border-top-right-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}


/* Margins of paragraphs inside table cells: */
td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }
td.tdm p , td.tmbrule p , td.tdM p , td.tdMrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }
td.tdb p , td.tdbrule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }

td.tdp , td.tdprule , td.tdP , td.tdPrule
    { padding: 0ex .5em 0ex .5em ; }
td.tdm , td.tdmrule , td.tdM , td.tdMrule
    { padding: 0ex .5em 0ex .5em ; }
td.tdb , td.tdbrule , td.tdB , td.tdBrule
    { padding: 0ex .5em 0ex .5em ; }
```

```
/* table notes: */
.tnotes {
    margin: 0ex 5% 1ex 5% ;
    padding: 0.5ex 1em 0.5ex 1em;
    font-size:.80em;
    text-align: left ;
}

.minipage .tnotes {
    margin: 0pt ;
    padding: 0pt ;
}

.tnotes dl dt p {margin-bottom:0px;}

.tnoteitemheader {margin-right: 1em;}


/* for colortbl and cell color */
div.cellcolor {
    width: 100% ;
    padding: .5ex .5em .5ex .5em ;
    margin: -.5ex -.5em -.5ex -.5em ;
}


/* for bigdelim */
.ldelim, .rdelim { font-size: 200% }


/* center, flushleft, flushright environments */
div.center{text-align:center;}
div.center table {margin-left:auto;margin-right:auto;}
div.flushleft{text-align:left;}
div.flushleft table {margin-left:0em ; margin-right:auto;}
div.flushright{text-align:right;}
div.flushright table {margin-left:auto ; margin-right: 0em ;}


/* Fancybox */
div.Btrivlist table tr td {
    padding: .2ex 0em ;
}


/* program listing callouts: */
span.callout {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    border-radius: .5em;
    background-color:black;
    color:white;
    padding:0px .25em 0px .25em;
    margin: 0 ;
    font-weight: bold;
```

```
    font-size:.72em ;
}

div.programlisting pre.verbatim span.callout{
    font-size: .85em ;
}

span.verbatim {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
}



div.published
{
    text-align: center ;
    font-variant: normal ;
    font-style: italic ;
    font-size: 1em ;
    margin: 1ex 0em 1ex 0em ;
}

div.subtitle
{
    text-align: center ;
    font-variant: normal ;
    font-style: italic ;
    font-size: 1.25em ;
    margin: 1ex 0em 1ex 0em ;
}

div.subtitle p { margin: 1ex ; }

div.author
{
    font-variant: normal ;
    font-style: normal ;
    font-size: 1em ;
    margin: 1ex 0em 1ex 0em ;
}

div.oneauthor {
    display: inline-block ;
    margin: 0ex 1em 0ex 1em ;
}

/*
div.author table {
    margin: 1ex auto 0ex auto ;
    background: none ;
}

div.author table tbody tr td { padding: .25ex ; }
```

```
*/

span.affiliation {font-size: .85em ; font-variant: small-caps; }

div.titledate {
    text-align: center ;
    font-size: .85em ;
    font-style: italic;
    margin: 1ex 0em 1ex 0em ;
}


nav.topnavigation{
    text-align: left ;
    padding: 0.5ex 1em 0.5ex 1em ;
/*     margin: 2ex 0em 3ex 0em ; */
    margin: 0 ;
    border-bottom: 1px solid silver ;
    border-top: 1px solid silver ;
    clear:both ;
}

nav.botnavigation{
    text-align: left ;
    padding: 0.5ex 1em 0.5ex 1em ;
/*     margin: 3ex 0em 2ex 0em ; */
    margin: 0 ;
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
    clear:both ;
}


header {
    line-height: 1.2 ;
    font-size: 1em ;
    border-bottom: 1px solid silver ;
    margin: 0px ;
    padding: 2ex 1em 2ex 1em ;
    text-align:left ;
}


footer {
    font-size: .85em ;
    line-height: 1.2 ;
    margin-top: 1ex ;
    border-top: 1px solid silver ;
    padding: 2ex 1em 2ex 1em ;
    clear:both ;
    text-align:left ;
}


a.linkhome { font-weight:bold ; font-size: 1em ;}
```

```
div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }

img.lateximage{
    padding: 0pt ;
    margin: 0pt ;
    box-shadow: none ;
    border: none ;
    background: none ;
    max-width: 100% ;
    border-radius: 0ex ;
    border: none ;
}


/* The -1px right margin compensates for the 1px right border. */
/* Without this -1px margin, the body container appears below instead */
/* of floating to the side. */
div.sidetoccontainer {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
        "Lucida Bright", Georgia, serif;
    float: left ;
    width: 20%;
    margin: 0pt -1px 3ex 0pt ;
    border-right: 1px solid silver;
    border-bottom: 1px solid silver;
    background: #FAF7F4 ;
    font-size:.9em ;
    border-radius: 0px 0px 20px 0px ;
}

div.sidetoccontents {
    overflow-y: auto ;
    width: 100% ;
    text-align: left ;
}


nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;
    text-indent: 0 ; }

nav.sidetoc p a {color:black ; font-size: .7em ;}

div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;
    border-bottom: 1px solid silver ;    }

nav.sidetoc a:hover {text-decoration: underline ; }



section.textbody { margin: 0ex 1em 0ex 1em ;}


div.multicolsheading { -webkit-column-span: all;
```

```
    -moz-column-span: all; column-span: all; }
div.multicols { -webkit-columns: 3 380px ;
    -moz-columns: 3 380px ; columns: 3 380px ; }
div.multicols p {margin-top: 0ex}


/* Used for xfrac and nicefrac: */
span.numerator {
    font-size: 60% ;
    vertical-align: .4em ;
}

span.denominator {
    font-size: 60%
}


/* Used for algorithm2e: */
div.alg2evline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
    border-radius: 0px 0px 0px 1ex ;
}

div.alg2evsline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
}

div.alg2enoline{
    margin-left: 1em ;
    padding-left: 1em ;
}

span.alg2elinenumber{
    margin-right: .5em ;
    font-size: 50% ;
    color: red ;
}


/* Used for algorithmicx: */
span.floatright { float: right ; }


/* keyfloat and tocdata: */
.floatnotes {
    margin: 0ex 5% 0ex 5% ;
    padding: 0ex 1em 0ex 1em ;
    font-size:.80em ;
    text-align: left ;
}

```

```
.authorartist{
    font-size:.70em ;
    font-style: italic;
}



/* Native LaTeX theorems: */

.theoremcontents { font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ; }
.theoremlabel { font-style: normal; font-weight: bold ; margin-right: .5em ; }


/* theorem, amsthm, and ntheorem packages */

span.theoremheader,
span.theoremheaderplain,
span.theoremheaderdefinition,
span.theoremheaderbreak,
span.theoremheadermarginbreak,
span.theoremheaderchangebreak,
span.theoremheaderchange,
span.theoremheadermargin
{
    font-style:normal ; font-weight: bold ; margin-right: 1em ;
}

span.amsthmnameplain,
span.amsthmnamedefinition,
span.amsthmnumberplain,
span.amsthmnumberdefinition
{
    font-style:normal ; font-weight: bold ;
}


span.amsthmnameremark,
span.amsthmnumberremark
{font-style:italic ; font-weight: normal ; }


span.amsthmnoteplain,
span.amsthmnotedefinition
{font-style:normal ;}


span.theoremheaderremark,
span.theoremheaderproof,
span.amsthmproofname
{font-style:italic ; font-weight: normal ; margin-right: 1em ; }

span.theoremheadersc
{
    font-style:normal ;
    font-variant: small-caps ;
```

```
    font-weight: normal ;
    margin-right: 1em ;
}

.theoremendmark {float:right}

div.amsthmbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
div.theorembodybreak, div.theorembodynonumberbreak,
div.theorembodymarginbreak,
div.theorembodychangebreak,
div.theorembodychange,
div.theorembodymargin
{
    font-style:italic;
    margin-top: 3ex ; margin-bottom: 3ex ;
}

div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
div.theorembodyplainupright, nonumberplainuprightsc,
div.amsthmbodydefinition, div.amsthmbodyremark,
div.amsthmproof
{
    font-style: normal ;
    margin-top: 3ex ; margin-bottom: 3ex ;
}

span.amsthmnoteremark {}


/* For the notes package: */
div.notesimportantnote, div.noteswarningnote, div.notesinformationnote {
    clear: both ;
    margin: 2ex 2em 2ex 2em ;
    border: 1px solid silver ;
}

div.notesicon {
    float:left ;
    display: inline-block ;
    background: gold ;
    padding: 0ex 1em 0ex 1em ;
    margin-right: 1em ;
    font-weight: bold ;
}

div.notescontents { font-style: italic }


/*
For CSS LaTeX and related logos:
Based on spacing demonstrated by the metafont package.
*/

.latexlogofont {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
```

```
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-variant: normal ;
}

.latexlogo {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-size: 1.1em;
}

.latexlogosup {
  text-transform: uppercase;
  letter-spacing: .03em ;
  font-size: 0.7em;
  vertical-align: 0.25em;
  margin-left: -0.4em;
  margin-right: -0.15em;
}

.latexlogosub {
  text-transform: uppercase;
  vertical-align: -0.27ex;
  margin-left: -0.08em;
  margin-right: -0.07em;
  font-size: 1em;
}

.latexlogotwoe {
  text-transform: none ;
  font-variant-numeric: oldstyle-nums ;
}

.latexlogotwoesub {
  font-style:italic ;
  vertical-align: -0.27ex;
  margin-left: -0.11em;
  margin-right: -0.1em;
  font-size: 1em;
}

.xelatexlogo {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    letter-spacing: .03em ;
    font-size: 1.1em;
}

.xelatexlogosub {
  vertical-align: -0.27ex;
  margin-left: -0.0667em;
  margin-right: -.05em;
  font-size: 1em;
  letter-spacing: .03em ;
}

```

```
.amslogo {
    font-family: "TeXGyreChorus","URW Chancery L",
        "Apple Chancery","ITC Zapf Chancery","Monotype Corsiva",
        "Linux Libertine O", "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif ;
    font-style: italic ;
}

.lyxlogo {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "DejaVu Sans", "Bitstream Vera Sans", Geneva,
        Verdana, sans-serif ;
}


/* Only display top and bottom navigation if a small screen: */
/* Hide the sidetoc if a small screen: */
nav.topnavigation { display:none; }
nav.botnavigation { display:none; }

/* Only display the sidetoc's webpage title if a small screen */
span.sidetocthetitle { display: none }

@media screen and (max-width: 50em) {
    div.sidetoccontainer {
        float: none ;
        width: 100% ;
        padding: 0 ;
        border-radius: 0 ;
        border-bottom: 1px solid black ;
        border-top: 1px solid black ;
        box-shadow: none ;
    }
    span.sidetocthetitle { display: inline }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
    .marginpar {
        max-width: 100%;
        float: none;
        display:block ;
        margin: 1ex 1em 1ex 1em ;
    }
}

@media print {
    body {
        font-family: "Linux Libertine O",
        "DejaVu Serif", "Bitstream Vera Serif",
        "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    }
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display: none; }
    nav.botnavigation { display: none; }
    div.bodycontainer { width: 100% }
```

```
}

@media handheld {
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display:block }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
}

@media projection {
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display:block }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
}
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.5 lwarp_sagebrush.css

File lwarp_sagebrush.css

An optional CSS which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_sagebrush.css}
@import url("lwarp.css") ;


A:link {color:#105030 ; text-decoration: none ; }
A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}
A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}
A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}



h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif",
        "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif;
    font-variant: small-caps ;
    font-weight: normal ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
}

h1 {    /* title of the entire website, used on each page */
    font-variant: small-caps ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
```

```
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);
}

h1 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
}

h2 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #DAD0C0);
}



div.abstract {
    background: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

  border: 1px solid silver;
    border-radius: 1em ;
}

div.abstract dl {line-height:1.5;}
div.abstract dt {color:#304070;}

div.abstracttitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    font-size:1.5em;
    border-bottom: 1px solid silver ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}

span.abstractrunintitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
}


div.epigraph, div.dictum {
    background: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

    border: 1px solid silver ;
```

```
    border-radius: 1ex ;
    box-shadow: 3px 3px 3px #808080 ;
}


.example {
    background-color: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

}

div.exampletitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    border-bottom: 1px solid silver ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}


.sidebar {
    background-color: #f5f5eb ;
    background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);

}

div.sidebartitle{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    border-bottom: 1px solid silver ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}


.fancyvrblabel {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    font-weight:bold;
    font-variant: small-caps ;
    font-size: 1.5em ;
    color: #304070 ;
    text-align: center ;
    text-shadow: 1px 1px 2px #808080;
}

```

```
div.minipage {
    background-color: #eeeee7 ;
    border: 1px solid silver ;
    border-radius: 1ex ;
}

table div.minipage { background: none ; border: none ; }

div.framebox div.minipage {border:none ; background:none}

section.textbody > div.minipage {
    box-shadow: 3px 3px 3px #808080 ;
}

div.fboxBlock div.minipage { box-shadow: none ; }

.framed .minipage , .framedleftbar .minipage {
    border: none ;
    background: none ;
    padding: 0ex ;
    margin: 0ex ;
}

figure.figure .minipage, div.figurecaption .minipage { border: none; }

div.marginblock div.minipage ,
div.marginparblock div.minipage
    { border: none; }

figure , div.marginblock {
    background-color: #eeeee7 ;
    border: 1px solid silver ;
    border-radius: 1ex ;
    box-shadow: 3px 3px 3px #808080 ;
}

figure figure {
    border: 1px solid silver ;
    margin: 0em ;
    box-shadow: none ;
}

/*
div.figurecaption {
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
    background-color: #e8e8e8 ;
}
*/


div.table {
    box-shadow: 3px 3px 3px #808080 ;
}

```

```
/*
.tnotes {
    background: #e8e8e8;
    border: 1px solid silver;
}
*/


nav.topnavigation{
    background-color: #b0b8b0 ;
    background-image: linear-gradient(to bottom,#e0e0e0,#b0b8b0) ;
}

nav.botnavigation{
    background-color: #b0b8b0 ;
    background-image: linear-gradient(to top,#e0e0e0,#b0b8b0) ;
}



header{
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
}

footer{
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
}



div.sidetoccontainer {
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
    box-shadow: 3px 3px 3px #808080 ;
    }

div.sidetoctitle {color: #304070 ; }

nav.sidetoc a:hover {
    color:#006000 ;
    text-decoration: none ;
    text-shadow:0px 0px 2px #a0a0a0;
}


@media screen and (max-width: 45em) {
    div.sidetoccontainer { border-radius: 0 ; }
}


\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.6 lwarp_formal.css

File lwarp_formal.css An optional CSS which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_formal.css}
@import url("lwarp.css") ;



A:link {color:#802020 ; text-decoration:none; }
A:visited {color:#802020 ; text-shadow:none ;}
A:hover {color:#400000 ; text-shadow:none ;}
A:active {color:#C00000 ; text-shadow:none ;}


body {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    background: #fffcf5;
}

span.textrm {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
}

span.textsf {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
}



h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
}

h1, h2 {
    background-color: #fffcf5 ;
    background-image: none ;
    border-bottom: 1px solid #808080;
```

```
/*    border-top: 2px solid #808080; */
}

div.abstracttitle {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: black ;
    text-shadow: none ;
}

span.abstractrunintitle {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: black ;
    text-shadow: none ;
}

div.abstract { font-size: 100% }

.sidebar {
    background: #fffcf5;
    background-image: none ;
  margin: 2em 5% 2em 5%;
  padding: 0.5em 1em;
  border: none ;
  border-top : 1px solid silver;
  border-bottom : 1px solid silver;
  font-size: 90% ;
}

div.sidebartitle{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}

.example {
    background: #fffcf5;
    background-image: none ;
  margin: 2em 5% 2em 5%;
  padding: 0.5em 1em;
  border: none ;
  border-top : 1px solid silver;
  border-bottom : 1px solid silver;
}

div.exampletitle{
```

```
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}

div.fancyvrblabel{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}



figure {
    margin: 5ex 5% 5ex 5% ;
    padding: 1ex 1em 1ex 1em ;
    background-color: #fffcf5 ;
    overflow-x: auto ;
    border: none ;
/*     border-top: 1px solid silver; */
/*     border-bottom: 1px solid silver; */
}


div.figurecaption , .lstlisting {
    border: none ;
/*     border-top: 1px solid silver ; */
/*     border-bottom: 1px solid silver ; */
    background-color: #fffcf5 ;
}

.tnotes {
    background: #fffcf5 ;
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
}

.theorem {
        background: none ;
}

.minipage {
    background-color: #fffcf5 ;
    border: none ;
}

div.floatrow figure { border: none ; }
```

```

figure figure { border: none ; }


nav.toc, nav.lof, nav.lot, nav.lol {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
}

div.sidetoccontainer {
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    background-image: linear-gradient(to bottom, #fffcf5, #C0C0C0);
}

div.sidetoctitle{
    color: #800000 ;
}

header{
    background-color: #e0e0e0 ;
    background-image: linear-gradient(to top, #fffcf5, #b0b0b0);
    text-align:center ;
}

footer{
    background-color: #e0e0e0 ;
    background-image: linear-gradient(to bottom, #fffcf5, #b0b0b0);
    padding: 2ex 1em 2ex 1em ;
    text-align:left ;
}

nav.botnavigation {
    background: #dedcd5 ;
    border-top: 1px solid black ;
}
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.7 sample_project.css

File `sample_project.css` The project-specific CSS file. Use with `\CSSFilename`.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{sample_project.css}
/* ( --- Start of project.css --- ) */
```

```
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.8 lwarp.ist

File lwarp.ist Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The page compositor line is for memoir's \specialindex.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.ist}
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
      \\par\\textbf{#1}\\par
      \\nopagebreak
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 ", \\hyperindexref{"
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"
page_compositor "."
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.9 lwarp.xdy

File lwarp.xdy Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

See:
https://tex.stackexchange.com/questions/80300/
how-can-i-convince-hyperref-and-xindy-to-play-together-nicely

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.xdy}
(require "tex/inputenc/latin.xdy")
(merge-rule "\\PS *" "Postscript")
(require "texindy.xdy")
(require "page-ranges.xdy")
(require "book-order.xdy")
(define-location-class "arabic-page-numbers"
    ("arabic-numbers") :min-range-length 1)
(require "makeindex.xdy")
(define-attributes (("hyperindexref")))
(markup-locref :open "\hyperindexref{" :close "}")
(markup-locref :open "\hyperindexref{" :close "}" :attr "hyperpage")
(markup-locref :open "\textbf{\hyperindexref{" :close "}}" :attr "textbf")
(markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
(define-location-class-order ("roman-page-numbers"
                  "arabic-page-numbers"
                  "alpha-page-numbers"
                  "Roman-page-numbers"
                  "Alpha-page-numbers"
                  "see"
                  "seealso"))
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.10 lwarp_one_limage.cmd

File `lwarp_one_limage.cmd`

Used by lwarp to help make `lateximages` when using WINDOWS.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The arguments are each of the three fields from `<project>-images.txt`, and also the base name of the source file.

MiKTeX does not allow file `lwarp_one_limage.cmd` to be created directly by *lwarpmk*, so `lwarp_one_limage.txt` is created instead, then copied to `lwarp_one_limage.cmd` by *lwarpmk*. This occurs each time *lwarpmk* used to create `lateximages`.

Config file:

```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=lwarp_one_limage.txt
\immediate\write\LWR@quickfile{%
    pdfseparate -f \LWRpercent 1 -l \LWRpercent 1 \LWRpercent 4_html.pdf %
   \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent\LWRpercent d.pdf%
}
```

```
\immediate\write\LWR@quickfile{%
  pdfcrop --hires \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
  pdftocairo -svg -noshrink \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.svg%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf%
}
\immediate\write\LWR@quickfile{exit}
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.11 lwarp_mathjax.txt

File lwarp_mathjax.txt

Used by lwarp when using MathJax.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_mathjax.txt}
<!-- https://groups.google.com/forum/#!topic/
                                mathjax-users/jUtewUcE2bY -->
<script type="text/x-mathjax-config">
MathJax.Hub.Register.StartupHook("TeX AMSmath Ready",function () {
    var seteqsectionDefault = {name: "", num: 0};
    var seteqsections = {}, seteqsection = seteqsectionDefault;
    var TEX = MathJax.InputJax.TeX, PARSE = TEX.Parse;
    var AMS = MathJax.Extension["TeX/AMSmath"];
    TEX.Definitions.Add({
    macros: {
        seteqsection: "mySection",
        seteqnumber: "mySetEqNumber"
    }
    });

    PARSE.Augment({
    mySection: function (name) {
        seteqsection.num = AMS.number;
        var n = this.GetArgument(name);
        if (n === "") {
            seteqsection = seteqsectionDefault;
        } else {
            if (!seteqsections["_"+n])
                seteqsections["_"+n] = {name:n, num:0};
            seteqsection = seteqsections["_"+n];
        }
        AMS.number = seteqsection.num;
```

```
    },
    mySetEqNumber: function (name) {
        var n = this.GetArgument(name);
        if (!n || !n.match(/^ *[0-9]+ *$/))
            n = "";
        else
            n = parseInt(n)-1;
        <!-- $ syntax highlighting -->
        if (n === "" || n < 1)
            TEX.Error
            ("Argument to "+name+" should be a positive integer");
        AMS.number = n;
    }
    });
    MathJax.Hub.Config({
    TeX: {
        equationNumbers: {
            formatTag: function (n) {
                <!-- if not numeric, don't include the chapter -->
                if (!n.match(/^ *[0-9]+ *$/ ))
                <!-- $ syntax highlighting -->
                    return "("+(n).replace(/^\./,"")+")" ;
                else
                  return "("+(seteqsection.name+"."+n).replace(/^\./,"")+")" ;
            },
            formatID: function (n) {
                n = (seteqsection.name+'.'+n).replace
                    (/[:"'<>&]/g,"").replace(/^\./,"");
                return 'mjx-eqn-' + n;
            }
        }
    }
    });
});
</script>

<!-- http://docs.mathjax.org/en/latest/options/ThirdParty.html -->
<script type="text/x-mathjax-config">
  MathJax.Ajax.config.path["Contrib"] =
    "https://cdn.mathjax.org/mathjax/contrib";
</script>

<script type="text/x-mathjax-config">
MathJax.Hub.Config({
    TeX: {
    equationNumbers: {
        autoNumber: "AMS"
    }
    }
});
</script>

<!-- Alternative CDN provider: -->
<script type="text/javascript" async
src="https://cdnjs.cloudflare.com/ajax/libs/mathjax/2.7.4/MathJax.js?config=TeX-AMS_HTML-full">
```

```
</script>

<!-- No longer supported after April 30, 2017: -->
<!--
<script
 src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-AMS_HTML-full">
</script>
-->

\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.12 `lwarpmk.lua` — `lwarpmk` option

Opt `lwarpmk` Creates a local copy of *lwarpmk*.

Prog `lwarpmk` Command-line utility to process lwarp files and images.

parallel processing `lateximages` and SVG math images are generated using multiple processes in parallel. For UNIX and LINUX, every 32 images the `wait` command is issued to wait for the previous batch of images to finish processing before starting a new batch. For WINDOWS, every 32 images one task is dispatched with

```
START /B /WAIT /BELOWNORMAL
```

which causes the operating system to wait until this lesser-priority tasks finishes, hopefully also waiting for the normal priority tasks which were already in progress to also complete. Afterwards, the next batch of images is started.

The following is only generated if the `lwarpmk` option was given to lwarp.

```
\begin{LWR@createlwarpmk}

\begin{filecontents*}{lwarpmk.lua}
#!/usr/bin/env texlua

-- Copyright 2016-2018 Brian Dunn


printversion = "v0.69"
requiredconfversion = "2" -- also at *lwarpmk.conf

function printhelp ()
print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help.") ;
end


function printusage ()
--
-- Print the usage of the lwarpmk command:
--
print ( [[
```

```

lwarpmk print [-p project]: Compile the print version if necessary.
lwarpmk print1 [-p project]: Forced single compile of the print version.
lwarpmk printindex [-p project]: Process print indexes.
lwarpmk printglossary [-p project]: Process the glossary for the print version.
lwarpmk html [-p project]: Compile the HTML version if necessary.
lwarpmk html1 [-p project]: Forced single compile of the HTML version.
lwarpmk htmlindex [-p project]: Process HTML indexes.
lwarpmk htmlglossary [-p project]: Process the glossary for the html version.
lwarpmk again [-p project]: Touch the source code to trigger recompiles.
lwarpmk limages [-p project]: Process the "lateximages" created by lwarp.sty.
lwarpmk pdftohtml [-p project]:
    For use with latexmk or a Makefile:
    Converts project_html.pdf to project_html.html and individual HTML files.
    Finishes the HTML conversion even if there was a compile error.
lwarpmk pdftosvg <list of file names>: Converts each PDF file to SVG.
lwarpmk epstopdf <list of file names>: Converts each EPS file to PDF.
lwarpmk clean [-p project]: Remove *.aux, *.toc, *.lof/t,
    *.idx, *.ind, *.log, *_html_inc.*, .gl*
lwarpmk cleanall [-p project]: Remove auxiliary files, project.pdf, *.html
lwarpmk cleanlimages: Removes all image from the "lateximages" directory.
lwarpmk -h: Print this help message.
lwarpmk --help: Print this help message.

]] )
-- printconf ()
end


function splitfile (destfile,sourcefile)
--
-- Split one large sourcefile into a number of files,
-- starting with destfile.
-- The file is split at each occurance of <!--|Start file|newfilename|*
--
print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
local sfile = io.open(sourcefile)
io.output(destfile)
for line in sfile:lines() do
i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*)|") ;
if ( (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then
    -- split the file
    io.output(newfilename) ;
else
    -- not a splitpoint
    io.write (line .. "\n") ;
end
end -- do
io.close(sfile)
end -- function


function cvalueerror ( line, linenum , cvalue )
--
-- Incorrect value, so print an error and exit.
```

```
--
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. linenum .. " : " .. line ) ;
    print (
        "lwarpmk: incorrect variable value \"" .. cvalue ..
        "\" in lwarpmk.conf.\n"
    ) ;
    print ("lwarpmk: ===")
--    printconf () ;
    os.exit(1) ;
end


function ignoreconf ()
-- Global argument index
argindex = 2
end

function loadconf ()
--
-- Load settings from the project's "lwarpmk.conf" file:
--
-- Default configuration filename:
local conffile = "lwarpmk.conf"
local confroot = "lwarpmk"
-- Global argument index
argindex = 2
-- Optional configuration filename:
if ( arg[argindex] == "-p" ) then
    argindex = argindex + 1
    confroot = arg[argindex]
    conffile = confroot..".lwarpmkconf"
    argindex = argindex + 1
end
-- Additional defaults:
confversion = "0"
opsystem = "Unix"
imagesdirectory = "lateximages"
imagesname = "image-"
latexmk = "false"
printlatexcmd = ""
HTMLlatexcmd = ""
printindexcmd = ""
HTMLindexcmd = ""
latexmkindexcmd = ""
-- to be removed:
-- indexprog = "makeindex"
-- makeindexstyle = "lwarp.ist"
-- xindylanguage = "english"
-- xindycodepage = "utf8"
-- xindystyle = "lwarp.xdy"
-- pdftotextenc = "UTF-8"
glossarycmd = "makeglossaries"
-- Verify the file exists:
if (lfs.attributes(conffile,"mode")==nil) then
```

```
    -- file not exists
    print ("lwarpmk: ===")
    print ("lwarpmk: File \"" .. conffile .."\" does not exist.")
    print ("lwarpmk: Move to the project's source directory,")
    print ("lwarpmk: recompile using pdflatex, xelatex, or lualatex,")
    print ("lwarpmk: then try using lwarpmk again.")
    if ( arg[argindex] ~= nil ) then
        print (
            "lwarpmk: (\"" .. confroot ..
            "\" does not appear to be a project name.)"
        )
    end
    print ("lwarpmk: ===")
    printhelp () ;
    os.exit(1) -- exit the entire lwarpmk script
else -- file exists
-- Read the file:
print ("lwarpmk: Reading " .. conffile ..".")
local cfile = io.open(conffile)
-- Scan each line, parsing each line as: name = [[string]]
local linenum = 0
for line in cfile:lines() do -- scan lines
linenum = linenum + 1
i,j,cvarname,cvalue = string.find (line,"([%w-_]*)%s*=%s*%[%[([^%]]*)%]%]") ;
-- Error if incorrect enclosing characters:
if ( i == nil ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: " ..  linenum .. " : " .. line ) ;
    print ("lwarpmk: Incorrect entry in " .. conffile ..".\n" ) ;
    print ("lwarpmk: ===")
--    printconf () ;
    os.exit(1) ;
end -- nil
if ( cvarname == "confversion" ) then
    confversion = cvalue
elseif ( cvarname == "opsystem" ) then
    -- Verify choice of opsystem:
    if ( (cvalue == "Unix") or (cvalue == "Windows") ) then
        opsystem = cvalue
    else
        cvalueerror ( line, linenum , cvalue )
    end
elseif ( cvarname == "sourcename" ) then sourcename = cvalue
elseif ( cvarname == "homehtmlfilename" ) then homehtmlfilename = cvalue
elseif ( cvarname == "htmlfilename" ) then htmlfilename = cvalue
elseif ( cvarname == "imagesdirectory" ) then imagesdirectory = cvalue
elseif ( cvarname == "imagesname" ) then imagesname = cvalue
elseif ( cvarname == "latexmk" ) then latexmk = cvalue
elseif ( cvarname == "printlatexcmd" ) then printlatexcmd = cvalue
elseif ( cvarname == "HTMLlatexcmd" ) then HTMLlatexcmd = cvalue
elseif ( cvarname == "printindexcmd" ) then printindexcmd = cvalue
elseif ( cvarname == "HTMLindexcmd" ) then HTMLindexcmd = cvalue
elseif ( cvarname == "latexmkindexcmd" ) then latexmkindexcmd = cvalue
elseif ( cvarname == "glossarycmd" ) then glossarycmd = cvalue
elseif ( cvarname == "pdftotextenc" ) then pdftotextenc = cvalue
```

```
else
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. linenum .. " : " .. line ) ;
    print (
        "lwarpmk: Incorrect variable name \"" .. cvarname .. "\" in " ..
        conffile ..".\n"
    ) ;
    print ("lwarpmk: ===")
--    printconf () ;
os.exit(1) ;
end -- cvarname
end -- do scan lines
io.close(cfile)
end -- file exists
-- Error if sourcename is "lwarp".
-- This could happen if a local copy of lwarp has recently been recompiled.
if sourcename=="lwarp" then
    print ("lwarpmk: ===")
    print ("lwarpmk: lwarp.sty has recently been recompiled in this directory,")
    print ("lwarpmk: and \"lwarpmk.conf\" is no longer set for your own project.")
    print ("lwarpmk: Recompile your own project using pdf/lua/xelatex <projectname>.")
    print ("lwarpmk: After a recompile, \"lwarpmk.conf\" will be set for your project,")
    print ("lwarpmk: and you may again use lwarpmk.")
    print ("lwarpmk: ===")
    os.exit(1)
end -- sourcename of "lwarp"
-- Select some operating-system commands:
if opsystem=="Unix" then  -- For Unix / Linux / Mac OS:
    rmname = "rm"
    mvname = "mv"
    cpname = "cp"
    touchnamepre = "touch"
    touchnamepost = ""
    newtouchname = "touch"
    dirslash = "/"
    opquote= "\'"
    cmdgroupopenname = " ( "
    cmdgroupclosename = " ) "
    seqname = " && "
    bgname = " &"
elseif opsystem=="Windows" then -- For Windows
    rmname = "DEL"
    mvname = "MOVE"
    cpname = "COPY"
    touchnamepre = "COPY /b"
    touchnamepost = "+,,"
    newtouchname = "echo empty >"
    dirslash = "\\"
    opquote= "\""
    cmdgroupopenname = ""
    cmdgroupclosename = ""
    seqname = " & "
    bgname = ""
else
    print ("lwarpmk: ===")
```

```
    print ("lwarpmk: Select Unix or Windows for opsystem." )
    print ("lwarpmk: ===")
    os.exit(1)
end --- for Windows
-- Warning if the operating system does not appear to be correct,
-- in case files were transferred to another system.
if ( (package.config:sub(1,1)) ~= dirslash ) then
    print ("lwarpmk: ===")
   print ("lwarpmk: It appears that lwarpmk.conf is for a different operating system." )
    print ("lwarpmk: To adjust lwarpmk.conf for the current operating system," )
    print ("lwarpmk:   recompile the original document using xe/lua/pdflatex." )
    print ("lwarpmk: ")
    print ("lwarpmk: lwarpmk shall attempt to continue...")
    print ("lwarpmk: ===")
end
-- Error if the configuration file's version is not current:
if ( confversion ~= requiredconfversion ) then
    print ("lwarpmk: ===")
   print ("lwarpmk: The configuration files lwarpmk.conf and "..sourcename..".lwarpmkconf" )
    print ("lwarpmk:   must be updated.  To update the configuration files," )
    print ("lwarpmk:   recompile "..sourcename..".tex using xe/lua/pdflatex," )
    print ("lwarpmk:   then use lwarpmk again.")
    print ("lwarpmk: ===")
    os.exit(1)
end
end -- loadconf


function executecheckerror ( executecommands , errormessage )
--
-- Execute an operating system call,
-- and maybe exit with an error message.
--
local err
err = os.execute ( executecommands )
if ( err ~= 0 ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. errormessage )
    print ("lwarpmk: ===")
    os.exit(1)
end
end -- executecheckerror


function refreshdate ()
os.execute(touchnamepre .. " " .. sourcename .. ".tex " .. touchnamepost)
end



function reruntoget (filesource)
--
-- Scan the LaTeX log file for the phrase "Rerun to get",
-- indicating that the file should be compiled again.
-- Return true if found.
```

```
--
local fsource = io.open(filesource)
for line in fsource:lines() do
if ( string.find(line,"Rerun to get") ~= nil ) then
    io.close(fsource)
    return true
end -- if
end -- do
io.close(fsource)
return false
end



function onetime (latexcmd, fsuffix)
--
-- Compile one time, return true if should compile again.
-- fsuffix is "" for print, "_html" for HTML output.
--
print("lwarpmk: Compiling with: " .. latexcmd)
executecheckerror (
    latexcmd ,
    "Compile error."
)
return (reruntoget(sourcename .. fsuffix .. ".log") ) ;
end


function manytimes (latexcmd, fsuffix)
--
-- Compile up to five times.
-- fsuffix is "" for print, "_html" for HTML output
--
if onetime(latexcmd, fsuffix) == true then
if onetime(latexcmd, fsuffix) == true then
if onetime(latexcmd, fsuffix) == true then
if onetime(latexcmd, fsuffix) == true then
if onetime(latexcmd, fsuffix) == true then
end end end end end
end


function verifyfileexists (filename)
--
-- Exit if the given file does not exist.
--
if (lfs.attributes ( filename , "modification" ) == nil ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. filename .. " not found." ) ;
    print ("lwarpmk: ===")
    os.exit (1) ;
end
end


```

```

function pdftohtml ()
--
-- Convert <project>_html.pdf into HTML files:
--
-- Convert to text:
print ("lwarpmk: Converting " .. sourcename
    .."_html.pdf to " .. sourcename .. "_html.html")
os.execute("pdftotext  -enc " .. pdftotextenc .. "  -nopgbrk  -layout "
    .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
-- Split the result into individual HTML files:
splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
end


function removeaux ()
--
-- Remove auxiliary files:
-- All .aux files are removed since there may be many bbl*.aux files.
--
os.execute ( rmname .. " *.aux " ..
    sourcename ..".toc " .. sourcename .. "_html.toc " ..
    sourcename ..".lof " .. sourcename .. "_html.lof " ..
    sourcename ..".lot " .. sourcename .. "_html.lot " ..
    " *.idx " ..
    " *.ind " ..
    sourcename ..".ps " .. sourcename .."_html.ps " ..
    sourcename ..".log " .. sourcename .. "_html.log " ..
    sourcename ..".gl* " .. sourcename .. "_html.gl* " ..
    " *_html_inc.* "
    )
end

function checkhtmlpdfexists ()
--
-- Error if the HTML document does not exist.
-- The lateximages are drawn from the HTML PDF version of the document,
-- so "lwarpmk html" must be done before "lwarpmk limages".
--
local htmlpdffile = io.open(sourcename .. "_html.pdf", "r")
if ( htmlpdffile == nil ) then
    print ("")
    print ("lwarpmk: ===")
    print ("lwarpmk: The HTML version of the document does not exist.")
    print ("lwarpmk: Enter \"lwarpmk html\" to compile the HTML version.")
    print ("lwarpmk: ===")
    os.exit(1)
end
io.close (htmlpdffile)
end -- checkhtmlpdfexists


function warnlimages ()
--
-- Warning of a missing <sourcename>-images.txt file:
```

```
    print ("lwarpmk: ===")
    print ("lwarpmk: \"" .. sourcename .. "-images.txt\" does not exist.")
    print ("lwarpmk: Your project does not use SVG math or other lateximages,")
    print ("lwarpmk: or the file has been deleted somehow.")
    print ("lwarpmk: Use \"lwarpmk html\" to recompile your project")
    print ("lwarpmk: and recreate \"" .. sourcename .. "-images.txt\".")
    print ("lwarpmk: If your project does not use SVG math or other lateximages,")
    print ("lwarpmk: then \"" .. sourcename .. "-images.txt\" will never exist, and")
    print ("lwarpmk: \"lwarpmk limages\" will not be necessary.")
    print ("lwarpmk: ===")
end -- warnlimages


function warnlimagesrecompile ()
-- Warning if must recompile before creating limages:
    print ("")
    print ("lwarpmk: ===")
    print ("lwarpmk: The document must be recompiled before creating the lateximages.")
    print ("lwarpmk: Enter \"lwarpmk html\" again, then try \"lwarpmk limages\" again.")
    print ("lwarpmk: ===")
end --warnlimagesrecompile


function checklimages ()
--
-- Check <sourcename>.txt to see if need to recompile first.
-- If any entry has a page number of zero, then there were incorrect images.
--
print ("lwarpmk: Checking for a valid " .. sourcename .. "-images.txt file.")
local limagesfile = io.open(sourcename .. "-images.txt", "r")
if ( limagesfile == nil ) then
    warnlimages ()
    os.exit(1)
end
-- Track warning to recompile if find a page 0
local pagezerowarning = false
-- Scan <sourcename>.txt
for line in limagesfile:lines() do
    -- lwimgpage is the page number in the PDF which has the image
    -- lwimghash is true if this filename is a hash
    -- lwimgname is the lateximage filename root to assign for the image
    i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
    -- For each entry:
    if ( (i~=nil) ) then
        -- If the page number is 0, image references are incorrect
        --  and must recompile the soure document:
        if ( lwimgpage == "0" ) then
            pagezerowarning = true
        end
    end -- if i~=nil
end -- do
-- The last line should be |end|end|end|.
-- If not, the compile must have aborted, and the images are incomplete.
if ( lwimgpage ~= "end" ) then
    warnlimagesrecompile()
```

```
    os.exit(1) ;
end
if ( pagezerowarning ) then
    warnlimagesrecompile()
    os.exit(1) ;
end -- pagezerowarning
end -- checklimages


function createuniximage ( lwimgfullname )
--
-- Create one lateximage for Unix / Linux / Mac OS.
--
executecheckerror (
    cmdgroupopenname ..
    "pdfseparate -f " .. lwimgpage .. " -l " .. lwimgpage .. " " ..
        sourcename .."_html.pdf " ..
        imagesdirectory .. dirslash .."lateximagetemp-%d" .. ".pdf" ..
        seqname ..
    -- Crop the image:
    "pdfcrop  --hires  " .. imagesdirectory .. dirslash .. "lateximagetemp-" ..
        lwimgpage .. ".pdf " ..
        imagesdirectory .. dirslash .. lwimgname .. ".pdf" ..
        seqname ..
    -- Convert the image to svg:
   "pdftocairo -svg  -noshrink  " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf " ..
        imagesdirectory .. dirslash .. lwimgname ..".svg" ..
        seqname ..
    -- Remove the temporary files:
   rmname .. " " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf" .. seqname ..
   rmname .. " " .. imagesdirectory .. dirslash .. "lateximagetemp-" .. lwimgpage .. ".pdf" ..
    cmdgroupclosename .. " >/dev/null " .. bgname
    ,
    "File error trying to convert " .. lwimgfullname
)
-- Every 32 images, wait for completion at below normal priority,
--  allowing other image tasks to catch up.
numimageprocesses = numimageprocesses + 1
if ( numimageprocesses > 32 ) then
    numimageprocesses = 0
    print ( "lwarpmk: waiting" )
    executecheckerror ( "wait" , "File error trying to wait.")
end
end -- createuniximage


function createwindowsimage ( lwimgfullname )
--
-- Create one lateximage for Windows.
--
-- Every 32 images, wait for completion at below normal priority,
--  allowing other image tasks to catch up.
numimageprocesses = numimageprocesses + 1
if ( numimageprocesses > 32 ) then
    numimageprocesses = 0
```

```
    thiswaitcommand = "/WAIT /BELOWNORMAL"
    print ( "lwarpmk: waiting" )
else
    thiswaitcommand = ""
end
-- Execute the image generation command
executecheckerror (
    "start /B " .. thiswaitcommand .. " \"\" lwarp_one_limage " ..
    lwimgpage .. " " ..
    lwimghash .. " " ..
    lwimgname .. " " ..
    sourcename .. " <nul >nul"
    ,
    "File error trying to create image."
)
end -- createwindowsimage


function createonelateximage ( line )
--
-- Given the next line of <sourcename>.txt, convert a single image.
--
-- lwimgpage is the page number in the PDF which has the image
-- lwimghash is true if this filename is a hash
-- lwimgname is the lateximage filename root to assign for the image
i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
-- For each entry:
if ( (i~=nil) ) then
    -- Skip if the page number is 0:
    if ( lwimgpage == "0" ) then
        pagezerowarning = true
    -- Skip if the page number is "end":
    else if ( lwimgpage == "end" ) then
    else
        -- Skip is this image is hashed and already exists:
       local lwimgfullname = imagesdirectory .. dirslash .. lwimgname .. ".svg"
        if (
            (lwimghash ~= "true") or
            (lfs.attributes(lwimgfullname,"mode")==nil) -- file not exists
        )
        then -- not hashed or not exists:
            -- Print the name of the file being generated:
            print ( "lwarpmk: " .. lwimgname )
          -- Touch/create the dest so that only once instance tries to build it:
            executecheckerror (
                newtouchname .. " " .. lwimgfullname ,
                "File error trying to touch " .. lwimgfullname
            )
            -- Separate out the image into its own single-page pdf:
            if opsystem=="Unix" then
                createuniximage (lwimgfullname)
            elseif opsystem=="Windows" then
                createwindowsimage (lwimgfullname)
            end
        end -- not hashed or not exists
```

```
    end -- not page "end"
    end -- not page 0
end -- not nil
end -- createonelateximage


function createlateximages ()
--
-- Create lateximages based on <sourcename>-images.txt:
--
-- See if the document must be recompiled first:
checklimages ()
-- See if the print version exists:
checkhtmlpdfexists ()
-- Attempt to create the lateximages:
print ("lwarpmk: Creating lateximages.")
local limagesfile = io.open(sourcename .. "-images.txt", "r")
if ( limagesfile == nil ) then
    warnlimages ()
    os.exit(1)
end
-- Create the lateximages directory, ignore error if already exists
err = os.execute("mkdir " .. imagesdirectory)
-- For Windows, create lwarp_one_limage.cmd from lwarp_one_limage.txt:
if opsystem=="Windows" then
    executecheckerror (
        cpname .. " lwarp_one_limage.txt lwarp_one_limage.cmd" ,
       "File error trying to copy lwarp_one_limage.txt to lwarp_one_limage.cmd"
    )
end -- create lwarp_one_limage.cmd
-- Track the number of parallel processes
numimageprocesses = 0
-- Track warning to recompile if find a page 0
pagezerowarning = false
-- Scan <sourcename>.txt
for line in limagesfile:lines() do
    createonelateximage ( line )
end -- do
io.close(limagesfile)
print ( "lwarpmk limages: ===")
print ( "lwarpmk limages: Wait a moment for the images to complete" )
print ( "lwarpmk limages:   before reloading the page." )
print ( "lwarpmk limages: ===")
print ( "lwarpmk limages: Done." )
if ( pagezerowarning == true ) then
    print ( "lwarpmk limages: WARNING: Images will be incorrect." )
    print ( "lwarpmk limages:   Enter \"lwarpmk cleanlimages\", then" )
    print ( "lwarpmk limages:   recompile the document one more time, then" )
    print ( "lwarpmk limages:   repeat \"lwarpmk images\" again." )
end -- pagezerowarning
end -- function


function convertepstopdf ()
--
```

```
-- Converts EPS files to PDF files.
-- The filenames are arg[argindex] and up.
-- arg[1] is the command "pdftosvg".
--
ignoreconf ()
for i = argindex , #arg do
    if (lfs.attributes(arg[i],"mode")==nil) then
        print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
    else
        print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
        os.execute ( "epstopdf " .. arg[i] )
    end -- if
end -- do
end --function


function convertpdftosvg ()
--
-- Converts PDF files to SVG files.
-- The filenames are arg[argindex] and up.
-- arg[1] is the command "pdftosvg".
--
ignoreconf ()
for i = argindex , #arg do
    if (lfs.attributes(arg[i],"mode")==nil) then
        print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
    else
        print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
        os.execute ( "pdftocairo -svg " .. arg[i] )
    end -- if
end -- do
end --function


-- Force an update and conclude processing:
function updateanddone ()
print ("lwarpmk: Forcing an update of " .. sourcename ..".tex.")
refreshdate ()
print ("lwarpmk: " .. sourcename ..".tex is ready to be recompiled.")
print ("lwarpmk: Done.")
end -- function


-- Start of the main code: --


-- lwarpmk --version :

if (arg[1] == "--version") then
print ( "lwarpmk: " .. printversion )

else -- not --version


-- print intro:
```

```

print ("lwarpmk: " .. printversion .. "  Automated make for the LaTeX lwarp package.")


-- lwarpmk print:

if arg[1] == "print" then
loadconf ()
if ( latexmk == "true" ) then
    print ("lwarpmk: Compiling with: " .. printlatexcmd)
    executecheckerror (
        printlatexcmd ,
        "Compile error."
    )
    print ("lwarpmk: Done.")
else -- not latexmk
    verifyfileexists (sourcename .. ".tex") ;
    -- See if up to date:
    if (
        ( lfs.attributes ( sourcename .. ".pdf" , "modification" ) == nil ) or
        (
            lfs.attributes ( sourcename .. ".tex" , "modification" ) >
            lfs.attributes ( sourcename .. ".pdf" , "modification" )
        )
    ) then
        -- Recompile if not yet up to date:
        manytimes(printlatexcmd, "")
        print ("lwarpmk: Done.") ;
    else
        print ("lwarpmk: " .. sourcename .. ".pdf is up to date.") ;
    end
end -- not latexmk


-- lwarpmk print1:

elseif arg[1] == "print1" then
    loadconf ()
    verifyfileexists (sourcename .. ".tex") ;
    onetime(printlatexcmd, "")
    print ("lwarpmk: Done.") ;


-- lwarpmk printindex:
-- Compile the index then touch the source
-- to trigger a recompile of the document:

elseif arg[1] == "printindex" then
loadconf ()
os.execute ( printindexcmd )
print ("lwarpmk: -------")
updateanddone ()


-- lwarpmk printglossary:
```

```
-- Compile the glossary then touch the source
-- to trigger a recompile of the document:

elseif arg[1] == "printglossary" then
loadconf ()
print ("lwarpmk: Processing the glossary.")

os.execute(glossarycmd .. " " .. sourcename)
updateanddone ()


-- lwarpmk html:

elseif arg[1] == "html" then
loadconf ()
if ( latexmk == "true" ) then
    print ("lwarpmk: Compiling with: " .. HTMLlatexcmd)
    executecheckerror (
        HTMLlatexcmd ,
        "Compile error."
    )
    pdftohtml ()
    print ("lwarpmk: Done.")
else -- not latexmk
    verifyfileexists ( sourcename .. ".tex" ) ;
    -- See if exists and is up to date:
    if (
      ( lfs.attributes ( homehtmlfilename .. ".html" , "modification" ) == nil ) or
        (
            lfs.attributes ( sourcename .. ".tex" , "modification" ) >
            lfs.attributes ( homehtmlfilename .. ".html" , "modification" )
        )
    ) then
        -- Recompile if not yet up to date:
        manytimes(HTMLlatexcmd, "_html")
        pdftohtml ()
        print ("lwarpmk: Done.")
    else
        print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
    end
end -- not latexmk


-- lwarpmk html1:

elseif arg[1] == "html1" then
    loadconf ()
    verifyfileexists ( sourcename .. ".tex" ) ;
    onetime(HTMLlatexcmd, "_html")
    pdftohtml ()
    print ("lwarpmk: Done.")


-- lwarpmk pdftohtml:
elseif arg[1] == "pdftohtml" then
```

```
    loadconf ()
    pdftohtml ()


-- lwarpmk htmlindex:
-- Compile the index then touch the source
-- to trigger a recompile of the document:

elseif arg[1] == "htmlindex" then
loadconf ()
os.execute ( HTMLindexcmd )
print ("lwarpmk: -------")
updateanddone ()


-- lwarpmk htmlglossary:
-- Compile the glossary then touch the source
-- to trigger a recompile of the document.
-- The <sourcename>.xdy file is created by the glossaries package.

elseif arg[1] == "htmlglossary" then
loadconf ()
print ("lwarpmk: Processing the glossary.")
os.execute(glossarycmd .. " " .. sourcename .. "_html")
updateanddone ()


-- lwarpmk limages:
-- Scan the <sourcename>.txt file to create lateximages.

elseif arg[1] == "limages" then
loadconf ()
print ("lwarpmk: Processing images.")
createlateximages ()
print ("lwarpmk: Done.")


-- lwarpmk again:
-- Touch the source to trigger a recompile.

elseif arg[1] == "again" then
loadconf ()
updateanddone ()


-- lwarpmk clean:
-- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*

elseif arg[1] == "clean" then
loadconf ()
removeaux ()
print ("lwarpmk: Done.")


-- lwarpmk cleanall
```

```
-- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
--    and also project.pdf, project.dvi, *.html

elseif arg[1] == "cleanall" then
loadconf ()
removeaux ()
os.execute ( rmname .. " " ..
    sourcename .. ".pdf " .. sourcename .. "_html.pdf " ..
    sourcename .. ".dvi " .. sourcename .. "_html.dvi " ..
    "*.html"
    )
print ("lwarpmk: Done.")


-- lwarpmk cleanlimages
-- Remove images from the imagesdirectory.

elseif arg[1] == "cleanlimages" then
loadconf ()
os.execute ( rmname .. " " .. imagesdirectory .. dirslash .. "*" )
print ("lwarpmk: Done.")

-- lwarpmk epstopdf <list of file names>
-- Convert EPS files to PDF using epstopdf
elseif arg[1] == "epstopdf" then
convertepstopdf ()
print ("lwarpmk: Done.")


-- lwarpmk pdftosvg <list of file names>
-- Convert PDF files to SVG using pdftocairo
elseif arg[1] == "pdftosvg" then
convertpdftosvg ()
print ("lwarpmk: Done.")


-- lwarpmk with no argument :

elseif (arg[1] == nil) then
printhelp ()


-- lwarpmk -h or lwarpmk --help :

elseif (arg[1] == "-h" ) or (arg[1] == "--help") then
printusage ()


-- Unknown command:

else
printhelp ()
print ("\nlwarpmk: ****** Unknown command \""..arg[1].."\". ******\n")
end

```

```
end -- not --version
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting

\end{LWR@createlwarpmk}
```

41 Stacks

for HTML output:

```
\begin{warpHTML}
```

Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (un-nested) in proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new `\section` would close any currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an enumerate, for example. Depths to be recorded in `\LWR@closedepthone`, etc.

41.1 Assigning depths

initial depths for empty stack entries:

```
\newcommand*{\LWR@depthnone}{-5}
```

all sectioning depths are deeper than `LWR@depthfinished`:

```
\newcommand*{\LWR@depthfinished}{-4}
\newcommand*{\LWR@depthpart}{-1}
\newcommand*{\LWR@depthchapter}{0}
\newcommand*{\LWR@depthsection}{1}
\newcommand*{\LWR@depthsubsection}{2}
\newcommand*{\LWR@depthsubsubsection}{3}
\newcommand*{\LWR@depthparagraph}{4}
\newcommand*{\LWR@depthsubparagraph}{5}
```

used by `\itemize`, `\enumerate`, `\description`:

```
\newcommand*{\LWR@depthlist}{6}
```

used by `\item`:

```
\newcommand*{\LWR@depthlistitem}{7}
```

41.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to \pushclose and \popclose as well.

```
\newcommand*{\LWR@closeone}{}% top of the stack
\newcommand*{\LWR@closetwo}{}
\newcommand*{\LWR@closethree}{}
\newcommand*{\LWR@closefour}{}
\newcommand*{\LWR@closefive}{}
\newcommand*{\LWR@closesix}{}
\newcommand*{\LWR@closeseven}{}
\newcommand*{\LWR@closeeight}{}
\newcommand*{\LWR@closenine}{}
\newcommand*{\LWR@closeten}{}
\newcommand*{\LWR@closeeleven}{}
\newcommand*{\LWR@closetwelve}{}
```

41.3 Closing depths

A stack to record the depth of each level:

⚠ Note that nested LaTeX structures may push depths which are non-sequential.

Ex:

```
\begin{itemize}
   \item{A}
   \begin{description}
      \item{B}
   \end{description}
\end{itemize}
```

```
\newcommand*{\LWR@closedepthone}{\LWR@depthnone}% top of the stack
\newcommand*{\LWR@closedepthtwo}{\LWR@depthnone}
\newcommand*{\LWR@closedepththree}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfour}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfive}{\LWR@depthnone}
\newcommand*{\LWR@closedepthsix}{\LWR@depthnone}
\newcommand*{\LWR@closedepthseven}{\LWR@depthnone}
\newcommand*{\LWR@closedeptheight}{\LWR@depthnone}
\newcommand*{\LWR@closedepthnine}{\LWR@depthnone}
\newcommand*{\LWR@closedepththen}{\LWR@depthnone}
\newcommand*{\LWR@closedeptheleven}{\LWR@depthnone}
\newcommand*{\LWR@closedepththwelve}{\LWR@depthnone}
```

41.4 Pushing and popping the stack

\pushclose {⟨*action*⟩} {⟨*depth*⟩}

Pushes one return action and its LaTeX depth onto the stacks.

```
\NewDocumentCommand{\pushclose}{m m}
{
\global\let\LWR@closetwelve\LWR@closeeleven
\global\let\LWR@closeeleven\LWR@closeten
\global\let\LWR@closeten\LWR@closenine
\global\let\LWR@closenine\LWR@closeeight
\global\let\LWR@closeeight\LWR@closeseven
\global\let\LWR@closeseven\LWR@closesix
\global\let\LWR@closesix\LWR@closefive
\global\let\LWR@closefive\LWR@closefour
\global\let\LWR@closefour\LWR@closethree
\global\let\LWR@closethree\LWR@closetwo
\global\let\LWR@closetwo\LWR@closeone
\global\let\LWR@closeone#1
\global\let\LWR@closedepthtwelve\LWR@closedeptheleven
\global\let\LWR@closedeptheleven\LWR@closedepthten
\global\let\LWR@closedepthten\LWR@closedepthnine
\global\let\LWR@closedepthnine\LWR@closedeptheight
\global\let\LWR@closedeptheight\LWR@closedepthseven
\global\let\LWR@closedepthseven\LWR@closedepthsix
\global\let\LWR@closedepthsix\LWR@closedepthfive
\global\let\LWR@closedepthfive\LWR@closedepthfour
\global\let\LWR@closedepthfour\LWR@closedepththree
\global\let\LWR@closedepththree\LWR@closedepthtwo
\global\let\LWR@closedepthtwo\LWR@closedepthone
\global\let\LWR@closedepthone#2
}
```

\popclose Pops one action and its depth off the stacks.

```
\newcommand*{\popclose}
{
\global\let\LWR@closeone\LWR@closetwo
\global\let\LWR@closetwo\LWR@closethree
\global\let\LWR@closethree\LWR@closefour
\global\let\LWR@closefour\LWR@closefive
\global\let\LWR@closefive\LWR@closesix
\global\let\LWR@closesix\LWR@closeseven
\global\let\LWR@closeseven\LWR@closeeight
\global\let\LWR@closeeight\LWR@closenine
\global\let\LWR@closenine\LWR@closeten
\global\let\LWR@closeten\LWR@closeeleven
\global\let\LWR@closeeleven\LWR@closetwelve
\global\let\LWR@closedepthone\LWR@closedepthtwo
\global\let\LWR@closedepthtwo\LWR@closedepththree
\global\let\LWR@closedepththree\LWR@closedepthfour
\global\let\LWR@closedepthfour\LWR@closedepthfive
\global\let\LWR@closedepthfive\LWR@closedepthsix
```

```
\global\let\LWR@closedepthsix\LWR@closedepthseven
\global\let\LWR@closedepthseven\LWR@closedeptheight
\global\let\LWR@closedeptheight\LWR@closedepthnine
\global\let\LWR@closedepthnine\LWR@closedepthten
\global\let\LWR@closedepthten\LWR@closedeptheleven
\global\let\LWR@closedeptheleven\LWR@closedepthtwelve
}
```

```
\end{warpHTML}
```

42 Data arrays

These macros are similar to the arrayjobx package, except that `\LWR@setexparray`'s argument is expanded only once when assigned.

`name` has no backslash, `index` can be a number or a text name, and an empty `value` must be `\relax` instead of empty.

To assign an empty value:

```
\LWR@setexparray{name}{index}{}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@setexparray` {⟨*name*⟩} {⟨*index*⟩} {⟨*contents*⟩}

```
\NewDocumentCommand{\LWR@setexparray}{m m m}{%
    \begingroup%
    \let\par\relax%
    \xdef\LWR@thisexparrayname{#1#2}%
    \ifstrempty{#3}%
    {\csgdef{\LWR@thisexparrayname}{}}%
    {\csxdef{\LWR@thisexparrayname}{#3}}%
    \endgroup%
}
```

`\LWR@getexparray` {⟨*name*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@getexparray}[2]{%
    \@nameuse{#1#2}%
}
```

```
\end{warpHTML}
```

43 Localizing catcodes

for HTML & PRINT:

```
\begin{warpall}
```

⚠ Misplaced alignment tab character &

Place \StartDefiningTabulars and \StopDefiningTabulars before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error

```
Misplaced alignment tab character &.
```

\StartDefiningTabulars

Place before defining something with & in it.

```
\newcommand{\StartDefiningTabulars}{%
\LWR@traceinfo{StartDefiningTabulars}%
\warpHTMLonly{\catcode`\&=\active}%
}
```

\StopDefiningTabulars

Place after defining something with & in it.

```
\newcommand{\StopDefiningTabulars}{%
\LWR@traceinfo{StopDefiningTabulars}%
\warpHTMLonly{\catcode`\&=4}%
}
```

Bool LWR@mathmacro

True if currently defining math macros. Used to disable SVG math hashing and MathJax math contents while defining a macro using inline math. Begin a macro, it is not guaranteed that the contents are static, and so the image must be unique. The contents also almost certainly will not be parsed correctly by MathJax.

```
\newbool{LWR@mathmacro}
\boolfalse{LWR@mathmacro}
```

\StartDefiningMath

Place before defining something with $ in it.

```
\newcommand{\StartDefiningMath}{%
\LWR@traceinfo{StartDefiningMath}%
\warpHTMLonly{\catcode`\$=\active}%
}
```

\StopDefiningMath

Place after defining something with $ in it.

```
\newcommand{\StopDefiningMath}{%
\LWR@traceinfo{StopDefiningMath}%
\warpHTMLonly{\catcode`\$=3}% math shift
}
```

```
\end{warpall}
```

44 Localizing dynamic math

Inline SVG math usually uses a hash of its contents to generate latexmages which are reusable for multiple instances with the same contents. If the contents may change for

each use, such as depending on the current value of a counter, then `\inlinemathother` must be used before the inline math expression, and `\inlinemathnormal` must be used after.

For MathJax, the inline math expression is usually printed for MathJax to interpret. When marked as dynamic math, the following inline math expression will be displayed as an unhashed inline SVG image instead.

For existing code and packages, it may be possible to patch macros after they have been defined, using the xpatch package, which is pre-loaded by lwarp:

```
\xpatchcmd{\macroname}
    {$math expression$}
    {\inlinemathother$math expression$\inlinemathnormal}
    {}
    {\typeout{Error patching macroname.}}
```

for HTML & PRINT:

```
\begin{warpall}
```

Bool `LWR@dynamicmath` Default: `false`

True to mark inline math which is dynamic in nature, thus should not be hashed for reuse.

```
\newbool{LWR@dynamicmath}
\boolfalse{LWR@dynamicmath}
```

`\inlinemathother`

Place before using `$ ... $` or `\( ... \)` if the contents of the math are not static, depending on counters or dynamic macros.

```
\newcommand{\inlinemathother}{%
\LWR@traceinfo{inlinemathother}%
\booltrue{LWR@dynamicmath}%
}
```

`\inlinemathnormal`

Place after using `$ ... $` or `\( ... \)` with dynamic contents.

```
\newcommand{\inlinemathnormal}{%
\LWR@traceinfo{inlinemathnormal}%
\boolfalse{LWR@dynamicmath}%
}
```

```
\end{warpall}
```

45 HTML entities

for HTML output:

```
\begin{warpHTML}
```

HTML Unicode entities:

```
\let\LWR@origampersand\&
```

\HTMLentity {⟨*entitytag*⟩}

```
\newcommand*{\HTMLentity}[1]{%
% \LWR@traceinfo{HTMLentity \detokenize{#1}}%
\begingroup%
\LWR@FBcancel%
\LWR@origampersand#1;%
\endgroup%
% \LWR@traceinfo{HTMLentity done}%
}
```

\HTMLunicode {⟨*hex_unicode*⟩}

```
\newcommand*{\HTMLunicode}[1]{\HTMLentity{\LWR@origpound{}x#1}}
```

\&

```
\renewrobustcmd*{\&}{\HTMLentity{amp}}
```

\textless

```
\let\LWR@origtextless\textless
\renewrobustcmd*{\textless}{\HTMLentity{lt}}
```

\textgreater

```
\let\LWR@origtextgreater\textgreater
\renewrobustcmd*{\textgreater}{\HTMLentity{gt}}
```

```
\end{warpHTML}
```

46 HTML filename generation

The filename of the homepage is set to `\HomeHTMLFilename.html`. The filenames of additional sections start with `\HTMLFilename`, to which is appended a section number or a simplified section name, depending on `FileSectionNames`.

for HTML & PRINT:

```
\begin{warpall}
```

\BaseJobname The `\jobname` of the printed version, even if currently compiling the HTML version. I.e. this is the `\jobname` without `_html` appended. This is used to set `\HomeHTMLFilename` if the user did not provide one.

```
\providecommand*{\BaseJobname}{\jobname}
```

\HTMLFilename The prefix for all generated HTML files other than the home page, defaulting to empty. See section 8.4.1.

```
\providecommand*{\HTMLFilename}{}
```

\HomeHTMLFilename The filename of the home page, defaulting to the \BaseJobname. See section 8.4.1.

```
\providecommand*{\HomeHTMLFilename}{\BaseJobname}
```

\SetHTMLFileNumber {⟨*number*⟩}

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
\newcommand*{\SetHTMLFileNumber}[1]{%
\setcounter{LWR@htmlfilenumber}{#1}%
}
```

Bool FileSectionNames Selects how to create HTML file names.

Defaults to use section names in the filenames.

```
\newbool{FileSectionNames}
\booltrue{FileSectionNames}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@htmlfilenumber Records the number of each HTML file as it is being created. Number 0 is the home page.

```
\newcounter{LWR@htmlfilenumber}
\setcounter{LWR@htmlfilenumber}{0}
```

\LWR@htmlsectionfilename {⟨*htmlfilenumber or name*⟩}

Prints the filename for a given section: \HTMLFilename{}filenumber/name.html

```
\newcommand*{\LWR@htmlsectionfilename}[1]{%
\LWR@traceinfo{LWR@htmlsectionfilename A !\detokenize{#1}!}%
```

Section 0 or empty is given the home filename. The filename must be detokenized for underscores.

```
% \LWR@traceinfo{about to assign temp}%
\LWR@sanitize{#1}%
\LWR@traceinfo{about to compare with ??}%
\ifthenelse{\equal{\LWR@sanitized}{??}}%
```

```
    {\LWR@traceinfo{found ??}}%
    {\LWR@traceinfo{not found ??}}%
\LWR@traceinfo{about to compare with zero or empty}%
\ifthenelse{%
    \equal{\LWR@sanitized}{0}%
    \OR \equal{\LWR@sanitized}{}%
    \OR \equal{\LWR@sanitized}{??}%
}%
{%
    \LWR@traceinfo{LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
    \HomeHTMLFilename.html%
}%
```

For a LaTeX section named “Index” or “index” without a prefix, create a filename with a leading underscore to avoid colliding with the HTML filename `index.html`:

```
{%
    \LWR@traceinfo{LWR@htmlsectionfilename C \LWR@sanitized}%
    \ifthenelse{%
        \equal{\HTMLFilename}{} \AND
        \equal{\LWR@sanitized}{Index} \OR
        \equal{\LWR@sanitized}{index}%
    }%
    {%
        \LWR@traceinfo{Prefixing the index name with an underscore.}%
        \_\LWR@sanitized.html%
    }%
```

Otherwise, create a filename with the chosen prefix:

```
    {%
        \HTMLFilename\LWR@isolate{\LWR@sanitized}.html%
    }%
}%
\LWR@traceinfo{LWR@htmlsectionfilename Z}%
}
```

`\LWR@htmlrefsectionfilename` {⟨*label*⟩}

Prints the filename for the given label

```
\newcommand*{\LWR@htmlrefsectionfilename}[1]{%
\LWR@traceinfo{LWR@htmlrefsectionfilename: !\detokenize{#1}!}%
```

`\LWR@nullfonts` to allow math in a section name.

```
\begingroup%
\LWR@nullfonts%
\LWR@htmlsectionfilename{\LWR@htmlfileref{#1}}%
\endgroup%
\LWR@traceinfo{LWR@htmlrefsectionfilename: done}%
}
```

```
\end{warpHTML}
```

47 Homepage link

for HTML & PRINT:

```
\begin{warpall}
```

\linkhomename Holds the default name for the home link.

```
\newcommand{\linkhomename}{Home}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LinkHome May be used wherever you wish to place a link back to the homepage. The filename must be detokenized for underscores.

```
\newcommand*{\LinkHome}{%
\LWR@subhyperrefclass{\HomeHTMLFilename.html}{\linkhomename}{linkhome}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\LinkHome May be used wherever you wish to place a link back to the homepage. For print output, if hyperref is available a hyperlink to the first page is used, named by \linkhomename. If hyperref is not available, a pageref is used instead.

\BaseJobname is included in the link label in case multiple documents are cross-referenced.

```
\AtBeginDocument{
\@ifundefined{hyperref}{
    \newcommand*{\LinkHome}{%
        \linkhomename\ --- page \pageref{\BaseJobname-page-LWRfirstpage}%
    }
}{
    \newcommand*{\LinkHome}{%
        \hyperref[\BaseJobname-page-LWRfirstpage]{\linkhomename}%
    }
}
}

\AfterEndPreamble{\label{\BaseJobname-page-LWRfirstpage}}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@topnavigation Creates a link to the homepage at the top of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@topnavigation}{
\LWR@htmlelementclassline{nav}{topnavigation}{\LinkHome}
}
```

\LWR@botnavigation Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@botnavigation}{
\LWR@htmlelementclassline{nav}{botnavigation}{\LinkHome}
}

\end{warpHTML}
```

48 \LWRPrintStack diagnostic tool

⚠ Diagnostics tool: Prints the LaTeX nesting depth values for the stack levels. \LWR@startpars is used before printing the stack, so that \LWRPrintStack may be called from anywhere in the normal text flow.

for HTML output:

```
\begin{warpHTML}
```

\LWRPrintStack Prints the closedepth stack.

```
\newcommand*{\LWR@subprintstack}{
\LWR@closedepthone\ \LWR@closedepththwo\ \LWR@closedepththree\
\LWR@closedepthfour\ \LWR@closedepthfive\ \LWR@closedepthsix\
\LWR@closedepthseven\ \LWR@closedeptheight\ \LWR@closedepthnine\
\LWR@closedepthten\ \LWR@closedeptheleven\ \LWR@closedepthtwelve\
}

\newcommand*{\LWRPrintStack}{
\LWR@startpars
\LWR@subprintstack
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}

\newcommand*{\LWRPrintStack}{}

\end{warpprint}
```

49 Closing stack levels

for HTML output:

```
\begin{warpHTML}
```

Close one nested level:

```
\newcommand*{\LWR@closeoneprevious}{%

\LWR@closeone

\popclose
}
```

\LWR@closeprevious {⟨*depth*⟩} Close everything up to the given depth:

```
\newcommand*{\LWR@closeprevious}[1]{
\LWR@traceinfo{LWR@closeprevious to depth #1, depths are \LWR@subprintstack}%
```

Close any pending paragraph:

```
\LWR@stoppars%
```

Close anything nested deeper than the desired depth. First close anything deeper, then at most one of the same level.

```
\whileboolexpr{test{\ifnumcomp{\LWR@closedepthone}{>}{#1}}}%
{%
    \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
    \LWR@closeoneprevious%
}%
\ifboolexpr{test{\ifnumcomp{\LWR@closedepthone}{=}{#1}}}%
{%
    \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
    \LWR@closeoneprevious%
}{}%
\LWR@traceinfo{LWR@closeprevious: done, depths are \LWR@subprintstack}%
}

\end{warpHTML}
```

50 PDF pages and styles

for HTML output:

```
\begin{warpHTML}
```

\LWR@forcenewpage New PDF page a before major environment.

This is used just before major environments, such as `verse`. Reduces the chance of an environment overflowing the HTML PDF output page.

```
\newcommand{\LWR@forcenewpage}{%
\LWR@traceinfo{LWR@forcenewpage}%
\ifinner\else%
\LWR@stoppars\LWR@orignewpage\LWR@startpars%
\fi%
}
```

\pagestyle, etc. are nullified for HTML output.

\pagestyle {⟨*style*⟩}

```
\renewcommand*{\pagestyle}[1]{}
```

\thispagestyle {⟨*style*⟩}

```
\renewcommand*{\thispagestyle}[1]{}
```

\markboth {⟨*left*⟩} {⟨*right*⟩}

```
\renewcommand*{\markboth}[2]{}
```

\markright {⟨*right*⟩}

```
\renewcommand*{\markright}[1]{}
```

\raggedbottom

```
\renewcommand*{\raggedbottom}{}
```

\flushbottom

```
\renewcommand*{\flushbottom}{}
```

\sloppy

```
\renewcommand*{\sloppy}{}
```

\fussy

```
\renewcommand*{\fussy}{}
```

\pagenumbering * {⟨*commands*⟩}

```
\RenewDocumentCommand{\pagenumbering}{s m}{}
\end{warpHTML}
```

51 HTML tags, spans, divs, elements

for HTML output:

```
\begin{warpHTML}
```

51.1 Mapping LaTeX sections to HTML sections

```
\newcommand*{\LWR@tagtitle}{h1}
\newcommand*{\LWR@tagtitleend}{/h1}
\newcommand*{\LWR@tagpart}{h2}
\newcommand*{\LWR@tagpartend}{/h2}
\newcommand*{\LWR@tagchapter}{h3}
\newcommand*{\LWR@tagchapterend}{/h3}
\newcommand*{\LWR@tagsection}{h4}
\newcommand*{\LWR@tagsectionend}{/h4}
\newcommand*{\LWR@tagsubsection}{h5}
\newcommand*{\LWR@tagsubsectionend}{/h5}
\newcommand*{\LWR@tagsubsubsection}{h6}
\newcommand*{\LWR@tagsubsubsectionend}{/h6}
\newcommand*{\LWR@tagparagraph}{span class="paragraph"}
\newcommand*{\LWR@tagparagraphend}{/span}
\newcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\newcommand*{\LWR@tagsubparagraphend}{/span}

\newcommand*{\LWR@tagregularparagraph}{p}
```

51.2 Babel-French tag modifications

Adjust babel-french for HTML spaces. So far, this only works for *pdflatex* and *xelatex*.

(*Emulates or patches code by* Daniel Flipo.)

```
\providecommand*{\LWR@FBcancel}{}

\AtBeginDocument{%
\@ifundefined{frenchbsetup}%
{}%
{%
    \frenchbsetup{FrenchFootnotes=false}%

%
    \LetLtxMacro\LWR@FBcancel\NoAutoSpacing%
    \renewrobustcmd*{\FBcolonspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;%
        \endgroup%
    }%
    \renewrobustcmd*{\FBthinspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \renewrobustcmd*{\FBguillspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;% ~,  for \og xyz \fg{}
        \endgroup%
```

```
    }%
    \DeclareDocumentCommand{\FBmedkern}{}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \DeclareDocumentCommand{\FBthickkern}{}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;% ~
        \endgroup%
    }%
    \renewrobustcmd*{~}{\HTMLentity{nbsp}}% was overwritten by babel-french
    \ifFBunicode%
    \else%
        \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
        \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
    \fi%
}%
}
```

51.3 HTML output formatting

Helps format the output HTML code for human readability.

\LWR@indentHTML Newline and indent the output HTML code.

```
\newcommand*{\LWR@indentHTML}{%
    \LWR@orignewline\LWR@origrule{2em}{0pt}%
}
```

51.4 HTML tags

\LWR@htmltagc {⟨*tag*⟩} Break ligatures and use upright apostrophes in HTML tags.

\protect is in case the tag appears in TOC, LOF, LOT.

```
\newcommand*{\LWR@htmltagc}[1]{%
\LWR@traceinfo{LWR@htmltagc !\detokenize{#1}!}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\protect\LWR@origtextless%
\LWR@isolate{#1}%
\protect\LWR@origtextgreater%
\endgroup%
}
```

Env LWR@nestspan Disable minipage, \parbox, and HTML s inside a .

⚠ \begin{LWR@nestspan} must follow the opening tag to allow a paragraph to start if the span is at the beginning of a new paragraph.

⚠ \end{LWR@nestspan} must follow the or a <p> may appear inside the span.

```
\newcommand*{\LWR@nestspanitem}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
\LWR@origitem%
}

\newenvironment*{LWR@nestspan}
{%
\LWR@traceinfo{LWR@nestspan starting}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{%
    \LWR@traceinfo{LWR@nestspan: inside a lateximage}%
}%
{% not in a lateximage
    \LWR@traceinfo{LWR@nestspan: NOT inside a lateximage}%
    \addtocounter{LWR@spandepth}{1}%
    \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{}%
    \RenewDocumentEnvironment{BlockClass}{o m}{}{}%
    \renewcommand{\BlockClassSingle}[2]{##2}%
    \renewcommand{\LWR@forcenewpage}{}%
    \renewcommand{\LWR@liststart}{%
        \let\item\LWR@nestspanitem%
    }%
    \renewcommand{\LWR@listend}{\LWR@htmltagc{br /}\LWR@htmltagc{br /}}%
}% not in a lateximage
\LWR@traceinfo{LWR@nestspan starting: done}%
}% starting env
{% ending env
\LWR@traceinfo{LWR@nestspan ending}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{\addtocounter{LWR@spandepth}{-1}}%
\LWR@traceinfo{LWR@nestspan ending: done}%
}

\AfterEndEnvironment{LWR@nestspan}{\global\let\par\LWR@closeparagraph}
```

\LWR@htmlspan {⟨*tag*⟩} {⟨*text*⟩}

⚠ \LWR@spandepth is used to ensure that paragraph tags are not generated inside a span. The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```
\NewDocumentCommand{\LWR@htmlspan}{m +m}{%
\LWR@ensuredoingapar%
\LWR@htmltagc{#1}%
\begin{LWR@nestspan}%
#2%
\LWR@htmltagc{/#1}%
```

```
\end{LWR@nestspan}%
}
```

\LWR@htmlspanclass [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlspanclass}{o m +m}{%
\LWR@traceinfo{LWR@htmlspanclass |#1|#2|}%
\LWR@ensuredoingapar%
\LWR@subhtmlelementclass{span}[#1]{#2}%
\begin{LWR@nestspan}%
#3%
\LWR@htmltagc{/span}%
\LWR@traceinfo{LWR@htmlspanclass done}%
\end{LWR@nestspan}%
}
```

\LWR@htmltag {⟨*tag*⟩}

Print an HTML tag: <tag>

```
\newcommand*{\LWR@htmltag}[1]{%
% \LWR@traceinfo{LWR@htmltagb !\detokenize{#1}!}%
\LWR@htmltagc{#1}%
% \LWR@traceinfo{LWR@htmltagb: done}%
}
```

51.5 Block tags and comments

In the following, \origttfamily breaks ligatures, which may not be used for HTML codes:

\LWR@htmlopencomment
\LWR@htmlclosecomment

```
\newcommand*{\LWR@htmlopencomment}{%
{%
% \LWR@traceinfo{LWR@htmlopencomment}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\LWR@print@mbox{\LWR@origtextless{}!-\/-}%
\endgroup%
}%
}

\newcommand*{\LWR@htmlclosecomment}{%
{%
% \LWR@traceinfo{LWR@htmlclosecomment}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
```

```
\LWR@print@mbox{-\/-\LWR@origtextgreater}%
\endgroup%
}%
}
```

\LWR@htmlcomment {⟨*comment*⟩}

```
\newcommand{\LWR@htmlcomment}[1]{%
\LWR@htmlopencomment{}%
{%
\LWR@origttfamily% break ligatures
#1%
}%
\LWR@htmlclosecomment{}}
```

\LWR@htmlblockcomment {⟨*comment*⟩}

```
\newcommand{\LWR@htmlblockcomment}[1]
{\LWR@stoppars\LWR@htmlcomment{#1}\LWR@startpars}
```

\LWR@htmlblocktag {⟨*tag*⟩} print a stand-alone HTML tag

```
\newcommand*{\LWR@htmlblocktag}[1]{%
\LWR@stoppars%
\LWR@htmltag{#1}%
\LWR@startpars%
}
```

51.6 Div class and element class

\LWR@subhtmlelementclass {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩}

Factored and reused in several places.

The trailing spaces allow more places for a line break.

The use of `\textquotedbl` instead of " provides improved compatibility with xeCJK.

```
\NewDocumentCommand{\LWR@subhtmlelementclass}{m O{} m}{%
\LWR@traceinfo{LWR@subhtmlelementclass !#1!#2!#3!}%
\ifblank{#2}%
{% empty option
    \LWR@htmltag{%
        #1 % space
        class=\textquotedbl#3\textquotedbl\ % space
    }%
}%
{% non-empty option
    \LWR@htmltag{%
        #1\LWR@indentHTML%
```

```
        class=\textquotedbl#3\textquotedbl\LWR@indentHTML%
        style=\textquotedbl#2\textquotedbl\LWR@orignewline%
    }%
}%
\LWR@traceinfo{LWR@subhtmlelementclass done}%
}
```

\LWR@htmlelementclass {⟨*element*⟩} {⟨*class*⟩} [⟨*style*⟩]

```
\NewDocumentCommand{\LWR@htmlelementclass}{m o m}{%
\LWR@stoppars%
\LWR@subhtmlelementclass{#1}[#2]{#3}%
\LWR@startpars%
}
```

\LWR@htmlelementclassend {⟨*element*⟩} {⟨*class*⟩}

```
\newcommand*{\LWR@htmlelementclassend}[2]{%
\LWR@stoppars%
\LWR@htmltag{/#1}%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{End of #1 ‘‘#2’’}%
}{}%
\LWR@startpars%
}
```

\LWR@htmldivclass [⟨*style*⟩] {⟨*class*⟩}

```
\NewDocumentCommand{\LWR@htmldivclass}{o m}{%
\LWR@htmlelementclass{div}[#1]{#2}%
}
```

\LWR@htmldivclassend {⟨*class*⟩}

```
\newcommand*{\LWR@htmldivclassend}[1]{%
\LWR@htmlelementclassend{div}{#1}%
}
```

51.7 Single-line elements

A single-line element, without a paragraph tag for the line of text:

\LWR@htmlelementclassline {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlelementclassline}{m o m +m}{%
\LWR@stoppars
\LWR@subhtmlelementclass{#1}[#2]{#3}%
#4%
```

```
\LWR@htmltag{/#1}
\LWR@startpars
}
```

51.8 HTML5 semantic elements

\LWR@htmlelement {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelement}[1]{%
\LWR@htmlblocktag{#1}
}
```

\LWR@htmlelementend {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelementend}[1]{%
\LWR@stoppars
\LWR@htmltag{/#1}
\LWR@startpars
}

\end{warpHTML}
```

51.9 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with css.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section 89.

Env BlockClass [⟨*style*⟩] {⟨*class*⟩} High-level interface for classes.

Ex: \begin{BlockClass}{class} text \end{BlockClass}

for PRINT output:

```
\begin{warpprint}
\NewDocumentEnvironment{BlockClass}{o m}{}{}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentEnvironment{LWR@print@BlockClass}{o m}{}{}%
\NewDocumentEnvironment{LWR@HTML@BlockClass}{o m}%
{%
    \LWR@origpar%
    \LWR@htmldivclass[#1]{#2}%
}
{\LWR@htmldivclassend{#2}}

```

```
\LWR@formattedenv{BlockClass}
\end{warpHTML}
```

\BlockClassSingle {⟨*class*⟩} {⟨*text*⟩} A single-line , without a paragraph tag for the line of text.

for HTML & PRINT:

```
\begin{warpall}
\newcommand{\BlockClassSingle}[2]{#2}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@BlockClassSingle}[2]{%
\LWR@origpar%
\LWR@htmlelementclassline{div}{#1}{#2}%
}

\LWR@formatted{BlockClassSingle}
\end{warpHTML}
```

\InlineClass (⟨*WP style*⟩) [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

High-level interface for inline span classes.

(⟨*WP style*⟩) is css styling to add when formatting for a word processor import.

[⟨*style*⟩] is the css styling to add when not formatting for a word processor.

for PRINT output:

```
\begin{warpprint}
\NewDocumentCommand{\InlineClass}{D{(}{)}{} o m +m}{#4}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@InlineClass}{D{(}{)}{} o m +m}{#4}%

\NewDocumentCommand{\LWR@HTML@InlineClass}{D{(}{)}{} o m +m}{%
\ifbool{FormatWP}{%
    \LWR@htmlspanclass[#1]{#3}{#4}%
}{%
    \LWR@htmlspanclass[#2]{#3}{#4}%
}%
}

\LWR@formatted{InlineClass}
\end{warpHTML}
```

Env LWR@BlockClassWP {⟨*WPstyle*⟩} {⟨*HTMLstyle*⟩} {⟨*class*⟩} Low-level interface for classes with an automatic float ID. These are often used when \ifbool{FormatWP}.

The use of \textquotedbl instead of " provides improved compatibility with xeCJK.

for PRINT output:

```
\begin{warpprint}
\NewDocumentEnvironment{LWR@BlockClassWP}{m m m}{}{}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentEnvironment{LWR@print@LWR@BlockClassWP}{m m m}{}{}%
\NewDocumentEnvironment{LWR@HTML@LWR@BlockClassWP}{m m m}%
{%
\LWR@stoppars%
\ifbool{FormatWP}%
{%
    \addtocounter{LWR@thisautoidWP}{1}%

    \LWR@htmltag{%
        div class=\textquotedbl#3\textquotedbl\ % space
        id=\textquotedbl%
            \LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}%
        \textquotedbl%
        \ifblank{#1}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
}% FormatWP
{% not FormatWP
    \LWR@htmltag{%
        div class=\textquotedbl#3\textquotedbl%
        \ifblank{#2}{}{ style=\textquotedbl#2\textquotedbl}%
    }%
}% not FormatWP
\LWR@startpars%
}
{\LWR@htmldivclassend{#3}}

\LWR@formattedenv{LWR@BlockClassWP}
\end{warpHTML}
```

51.10 Closing HTML tags

for HTML output:

```
\begin{warpHTML}
```

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```
\newcommand*{\LWR@printclosepart}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
\newcommand*{\LWR@printclosechapter}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
\newcommand*{\LWR@printclosesection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
\newcommand*{\LWR@printclosesubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
\newcommand*{\LWR@printclosesubsubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsubsection}}{}}
\newcommand*{\LWR@printcloseparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
\newcommand*{\LWR@printclosesubparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}
```

Lists require closing HTML tags:

```
\newcommand*{\LWR@printcloselistitem}
    {\LWR@htmltag{/li}}
\newcommand*{\LWR@printclosedescitem}
    {\LWR@htmltag{/dd}}
\newcommand*{\LWR@printcloseitemize}
    {\LWR@htmltag{/ul}}
\newcommand*{\LWR@printcloseenumerate}
    {\LWR@htmltag{/ol}}
\newcommand*{\LWR@printclosedescription}
    {\LWR@htmltag{/dl}}

\end{warpHTML}
```

52 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 53 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (`\LWR@doingstartpars`), tags are not generated until a LaTeX paragraph is being used (`\LWR@doingapar`). `LWR@lateximagedepth` is used to prevent nesting tags inside a `lateximage`. `LWR@spandepth` is used to prevent nesting paragraph tags inside a paragraph, which became important inside `\fbox` commands and other spans.

for HTML output:

```
\begin{warpHTML}
```

Ctr `LWR@spandepth` Do not create paragraph tags inside of an HTML span.

```
\newcounter{LWR@spandepth}
\setcounter{LWR@spandepth}{0}
```

Bool `LWR@doingstartpars` Tells whether paragraphs may be generated.

```
\newbool{LWR@doingstartpars}
\boolfalse{LWR@doingstartpars}
```

Bool `LWR@doingapar` Tells whether have actually generated and are currently processing paragraph text.

```
\newbool{LWR@doingapar}
\global\boolfalse{LWR@doingapar}
```

`\LWR@ensuredoingapar` If are about to print something visible, and if allowed to start a new paragraph, ensure that are `LWR@doingapar`, so that paragraph tags are placed:

```
\newcommand*{\LWR@ensuredoingapar}{%
\ifbool{LWR@doingstartpars}%
{\global\booltrue{LWR@doingapar}}%
{}%
}
```

\PN@parnotes@auto Redefined by parnotes to print paragraph notes at the end of each paragraph.

```
\def\PN@parnotes@auto{}%
```

\LWR@openparagraph

```
\newcommand*{\LWR@openparagraph}
{%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingstartpars}%
{% handling pars
```

See if have already started a lateximage or a . If so, do not generate nested paragraph tags.

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }% nested par tags?
```

If so: Do nothing if already started a lateximage page. Cannot nest a lateximage. Also do nothing if already inside a . Do not nest paragraph tags inside a .

```
    {}% no nested par tags
```

Else: No lateximage or has been started yet, so it's OK to generate paragraph tags.

```
    {% yes nest par tags
```

If parnotes is used, paragraph notes are inserted before starting the next paragraph:

```
        \PN@parnotes@auto%
```

The opening paragraph tag:

```
        \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%
```

Now have started a paragraph.

```
        \global\booltrue{LWR@doingapar}%
```

At the endof each paragraph, generate closing tag and do regular /par stuff. (Attempting to use the everyhook cr hook for \LWR@closeparagraph does not work well.)

```
        \let\par\LWR@closeparagraph%
    }% end of yes nest par tags
}% end of handling pars
{}% not handling pars
}
```

\LWR@closeparagraph@br

Add an HTML break if in a span, and not in a lateximage, and not in tabular metadata. Factored from \LWR@closeparagraph.

```
\newcommand*{\LWR@closeparagraph@br}
{%
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}} and
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}} and
        not bool {LWR@intabularmetadata}
    }%
        {\unskip\LWR@htmltagc{br /}}%
        {}%
}
```

\LWR@closeparagraph

```
\newcommand*{\LWR@closeparagraph}
{%
% \LWR@traceinfo{LWR@closeparagraph}%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingapar}%
```

If currently in paragraph mode:

```
{% handling pars
```

See if already started a lateximage or a :

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }%
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
    {% no nested par tags
        \LWR@closeparagraph@br%
    }% no nested par tags
```

If have not already started a lateximage or a :

```
    {% yes nest par tags
```

Print a closing tag and some extra vertical space.

```
        \leavevmode\LWR@orignewline%
        \LWR@htmltagc{/\LWR@tagregularparagraph}%
        \LWR@orignewline%
```

No longer doing a paragraph:

```
        \global\boolfalse{LWR@doingapar}%
```

Disable the special minipage & \hspace interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}%
```

If parnotes is used, paragraph notes are inserted after ending the previous paragraph:

```
        \PN@parnotes@auto%
    }% end of yes nest par tags
}% end of handling pars
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
{% not handling pars
    \LWR@closeparagraph@br%
}% not handling pars
```

In most cases, finish with a LaTeX \par, but in the case of paragraphs between lines in a tabular fetch the next token instead:

```
\ifboolexpr{%
    not bool {LWR@doingapar} and
    test {\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}} and
    test {
        \ifnumcomp{\value{LWR@tabulardepth}}{=}{\value{LWR@tabularpardepth}}
    } and
    bool {LWR@intabularmetadata} and
    not bool {LWR@tableparcell} and
    test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
}%
{%
    \LWR@getmynexttoken%
}{%
    \LWR@origpar%
}%
}
```

```
\end{warpHTML}
```

53 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 52 has the commands which actually generate the tags.

The everyhook package is used to generate the opening paragraph tags. The closing tags are generated by \par.

for HTML output:

```
\begin{warpHTML}
```

\LWR@startpars Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```
\newcommand*{\LWR@startpars}%
{%
% \LWR@traceinfo{LWR@startpars}%
```

Ignore if inside a span:

```
\ifnumcomp{\value{LWR@spandepth}}{>}{0}%
{}%
{%
```

See if currently handling HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If already in paragraph mode, do nothing.

```
    {}%
```

If not currently in paragraph mode:

```
    {%
```

At the start of each paragraph, generate an opening tag:

```
        \PushPreHook{par}{\LWR@openparagraph}%
```

At the end of each paragraph, generate closing tag then do regular /par actions:

```
        \let\par\LWR@closeparagraph

    }% an intentionally blank line
```

Are now handling paragraphs, but have not yet actually started one:

```
    \global\setbool{LWR@doingstartpars}{true}%
```

No <par> tag yet to undo:

```
    \global\boolfalse{LWR@doingapar}%
}% nestspan
% \LWR@traceinfo{LWR@startpars: done}%
}
```

\LWR@stoppars Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```
\newcommand*{\LWR@stoppars}%
{%
```

Ignore if inside a span:

```
\ifnumcomp{\value{LWR@spandepth}}{>}{0}%
{}%
{%
```

See if currently handling HTML paragraphs:

```
    \ifbool{LWR@doingapar}%
```

if currently in an HTML paragraph:

```
    {%
```

Print a closing tag:

```
        \leavevmode\LWR@orignewline%
        \LWR@htmltagc{/\LWR@tagregularparagraph}%
        \LWR@orignewline%
```

No longer have an open HTML paragraph:

```
        \global\boolfalse{LWR@doingapar}%
```

Disable the special `minipage` & `\hspace` interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}

    }% an intentionally blank line
```

If was not in an HTML paragraph:

```
    {}%
```

See if currently allowing HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If so: clear the `par` hook to no longer catch paragraphs:

```
        {\ClearPreHook{par}}%
```

Else: Do nothing:

```
        {}%
```

No longer in paragraph mode:

```
    \global\setbool{LWR@doingstartpars}{false}%
```

No <p> tag to undo:

```
    \global\boolfalse{LWR@doingapar}%
}% nestspan
}
```

```
\end{warpHTML}
```

54 Indentfirst

Pkg indentfirst

indentfirst redefines `\@afterindentfalse` to be `\@afterindenttrue`. This is reversed `\AtBeginDocument` here.

for HTML output:

```
\begin{warpHTML}
```

```
\AtBeginDocument{
\def\@afterindentfalse{\let\if@afterindent\iffalse}
\@afterindentfalse
}
\let\LWR@afterindent@syntaxhighlight\fi% syntax highlighting
```

```
\end{warpHTML}
```

55 Page headers and footers

for HTML & PRINT:

```
\begin{warpall}
```

In the following, catcode is manually changed back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
\newcommand{\LWR@firstpagetop}{} % for the home page alone
\newcommand{\LWR@pagetop}{} % for all other pages
\newcommand{\LWR@pagebottom}{}
```

`\HTMLFirstPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLFirstPageTop}[1]{%
    \renewcommand{\LWR@firstpagetop}{#1}%
}
```

`\HTMLPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageTop}[1]{%
    \renewcommand{\LWR@pagetop}{#1}%
}
```

`\HTMLPageBottom` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageBottom}[1]{%
    \renewcommand{\LWR@pagebottom}{#1}%
}

\end{warpall}
```

56 CSS

for HTML output:

```
\begin{warpHTML}
```

`\LWR@currentcss` The CSS filename to use. This may be changed mid-document using `\CSSFilename`, allowing different CSS files to be used for different sections of the document.

```
\newcommand*{\LWR@currentcss}{lwarp.css}
```

`\CSSFilename` {⟨*new-css-filename.css*⟩} Assigns the CSS file to be used by the following HTML pages.

```
\newcommand*{\CSSFilename}[1]{%
\renewcommand*{\LWR@currentcss}{#1}%
\@onelevel@sanitize\LWR@currentcss%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\CSSFilename}[1]{}
\end{warpprint}
```

57 Title, HTML meta author, HTML meta description

for HTML output:

```
\begin{warpHTML}
```

`\title` {⟨*title*⟩} Modified to remember `\thetitle`, which is used to set the HTML page titles.

```
\let\LWR@origtitle\title

\renewcommand*{\title}[1]{%
    \LWR@origtitle{#1}%
    \begingroup%
        \renewcommand{\thanks}[1]{}%
        \protected@xdef\thetitle{#1}%
    \endgroup%
}

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

`\HTMLTitle` {⟨*Titlename*⟩} The Title to place into an HTML meta tag. The default is to use the document `\title`'s setting.

```
\providecommand{\thetitle}{}

\newcommand{\theHTMLTitle}{\thetitle}

\newcommand{\HTMLTitle}[1]{\renewcommand{\theHTMLTitle}{#1}}
```

`\HTMLAuthor` {⟨*authorname*⟩} The author to place into an HTML meta tag. If none given, the default is `\theauthor`, which is empty unless the titling package is used.

```
\providecommand{\theauthor}{}

\newcommand{\theHTMLAuthor}{\theauthor}

\newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}
```

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using `\HTMLDescription`, allowing different HTML descriptions to be used for different sections of the document.

⚠ HTML author Do not use double quotes, and do not exceed 150 characters.

`\HTMLDescription` {⟨*New HTML meta description.*⟩} Assigns the HTML file's description meta tag.

```
\newcommand{\LWR@currentHTMLDescription}{}

\newcommand{\HTMLDescription}[1]{%
\renewcommand{\LWR@currentHTMLDescription}{#1}
}

\end{warpall}
```

58 Footnotes

lwarp uses native LaTeX footnote code, although with its own `\box` to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

footmisc

The footmisc `stable` option is emulated by lwarp.

⚠ sectioning commands

When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the `stable` option, provide a short TOC entry, and `\protect` the `\footnote`:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc

⚠ memoir

If using memoir class, with which lwarp preloads footmisc, the `stable` option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust `\secnumdepth` instead.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handle differently.

58.1 Regular page footnotes

In HTML documents, footnotes are placed at the bottom of the web page or the section, depending on `FootnoteDepth`, using the LaTeX box `\LWR@footnotebox`. Using this instead of the original `\footins` box avoids having footnotes be printed by the output routine, since footnotes should be printed per HTML page instead of per PDF page.

See section 58.4 for the implementation.

58.2 Minipage footnotes

See section 58.5 for how minipage footnotes are gathered. See section 88.3 for how minipage footnotes are placed into the document.

58.3 Titlepage thanks

See section 65.7 for titlepage footnotes.

58.4 Regular page footnote implementation

for HTML & PRINT:

```
\begin{warpall}
```

Ctr `FootnoteDepth` Default: 3

Determines how deeply to place footnotes in the HTML files, similar to `tocdepth`. The default of 3 places footnotes before each `\subsubsection` or higher. See table 9 for a table of LaTeX section headings.

```
\newcounter{FootnoteDepth}
\setcounter{FootnoteDepth}{3}
```

Ctr `footnoteReset` Default: 0

If non-zero, the `footnote` counter is reset to this value each time the footnotes are printed, as controlled by `FootnoteDepth`. For the manyfoot and bigfoot packages, additional counters such as `footnote<suffix>Reset` will be defined as well. These counters may be set non-zero by the user, and are also set if the perpage's `\MakePerPage` or `\MakeSortedPerPage` macros are used for the `footnote` or `footnote<suffix>` counters.

(The name is not capitalized because it is made from the counter's name with "Reset" appended.)

```
\newcounter{footnoteReset}
\setcounter{footnoteReset}{0}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@footnotebox`

Patch LaTeX footnotes to use a new `\box` instead of an insert for lwarp footnotes. This avoids having the original `\footins` appear at the bottom of a `lateximage`, which is on its own new page.

```
\newbox\LWR@footnotebox
```

Much of the following has unneeded print-mode formatting removed.

`\@makefntext` {⟨*text*⟩}

```
\long\def\@makefntext#1{\textsuperscript{\@thefnmark}~#1}
```

`\@makefnmark`

```
\def\@makefnmark{%
    \textsuperscript{\@thefnmark}%
}
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or `lateximage`, in which case paragraph tags must be added manually.

In a lateximage during HTML output, the lateximage is placed inside a print-mode minipage, but the footnotes are broken out by:

```
\def\@mpfn{footnote}
\def\thempfn{\thefootnote}
\let\@footnotetext\LWR@footnotetext
```

\LWR@@footnotetext {⟨*text*⟩} {⟨*footnote box name*⟩}

Factored to allow multiple footnote boxes for manyfoot.

```
\long\def\LWR@@footnotetext#1#2{%
\LWR@traceinfo{LWR@footnotetext}%
\global\setbox\csname #2\endcsname=\vbox{%
```

Add to any current footnotes:

```
    \unvbox\csname #2\endcsname%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Open a group:

```
    \color@begingroup%
```

Use HTML superscripts in the footnote even inside a lateximage:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{#1}%
```

Closing paragraph tag:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {\par}%
```

```
        {%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@orignewline%
        }%
```

Close the group:

```
    \color@endgroup%
}% vbox
```

Paragraph handling:

```
\LWR@ensuredoingapar%
}%
```

\LWR@footnotetext {⟨*text*⟩}

```
\long\def\LWR@footnotetext#1{\LWR@@footnotetext{#1}{LWR@footnotebox}}
```

\@footnotetext {⟨*text*⟩}

```
\LetLtxMacro\@footnotetext\LWR@footnotetext
```

58.5 Minipage footnote implementation

Patch LaTeX minipage footnotes to use a new \box instead of an insert for lwarp minipage footnotes. This avoids having the original \@mpfootins appear at the bottom of a lateximage, which is on its own new page.

```
\newbox\LWR@mpfootnotes
```

\@mpfootnotetext {⟨*text*⟩}

```
\long\def\@mpfootnotetext#1{%
\LWR@traceinfo{@mpfootnotetext}%
\global\setbox\LWR@mpfootnotes\vbox{%
    \unvbox\LWR@mpfootnotes%
    \reset@font\footnotesize%
    \hsize\columnwidth%
    \@parboxrestore%
    \protected@edef\@currentlabel%
        {\csname p@mpfootnote\endcsname\@thefnmark}%
    \color@begingroup%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
```

```
    }%
    {}%
    {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%

    \@makefntext{%
        \ignorespaces#1%
    }%
```

Don't add the closing paragraph tag if are inside a `lateximage`:

```
    \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}{>}{0}}%
        {}%
        {%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@orignewline%
        }%
    \color@endgroup%
}% vbox
```

Paragraph handling:

```
\LWR@ensuredoingapar%
\LWR@traceinfo{@mpfootnotetext: done}%
}
```

`\thempfootnote` Redefined to remove the `\itshape`, which caused an obscure compiling error in some situations.

```
\AtBeginDocument{
\def\thempfootnote{\@alph\c@mpfootnote}
}
```

58.6 Printing pending footnotes

`\LWR@@printpendingfootnotes` {⟨*footnote counter name*⟩}

```
\newcommand*{\LWR@@printpendingfootnotes}[1]{%
\expandafter\ifvoid\csname LWR@#1box\endcsname\else
    \LWR@forcenewpage
    \begin{BlockClass}{footnotes}
    \LWR@origmedskip
    \unvbox\csuse{LWR@#1box}
    \setbox\csuse{LWR@#1box}=\vbox{}
    \end{BlockClass}
    \ifltxcounter{#1Reset}{%
        \ifnumgreater{\value{#1Reset}}{0}{%
            \setcounter{#1}{\value{#1Reset}}%
            \addtocounter{#1}{-1}%
        }{}%
    }{}%
\fi
```

```
}
```

\LWR@printpendingfootnotes Enclose the footnotes in a class, print, then clear. For manynotes, new footnotes may be added via \appto.

```
\newcommand*{\LWR@printpendingfootnotes}{%
    \LWR@@printpendingfootnotes{footnote}%
}
```

LWR@maybeprintpendingfootnotes {⟨*depth*⟩} Used to print footnotes before sections only if formatting for an EPUB or word processor:

```
\newcommand*{\LWR@maybeprintpendingfootnotes}[1]{%
\ifboolexpr{
    not test{\ifnumcomp{#1}{>}{\value{FootnoteDepth}}} or
    bool{FormatEPUB} or
    bool{FormatWP}
}%
{\LWR@printpendingfootnotes}%
{}%
}
```

\LWR@printpendingmpfootnotes Enclose the minipage footnotes in a class, print, then clear.

```
\newcommand*{\LWR@printpendingmpfootnotes}{%
\ifvoid\LWR@mpfootnotes\else
    \LWR@forcenewpage
    \begin{BlockClass}{footnotes}
    \LWR@print@vspace*{\baselineskip}
    \unvbox\LWR@mpfootnotes
    \setbox\LWR@mpfootnotes=\vbox{}
    \end{BlockClass}
\fi
}
```

```
\end{warpHTML}
```

59 Marginpars

\marginpar [⟨*left*⟩] {⟨*right*⟩} \marginpar may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the \marginpar. Paragraph breaks are converted to <br /> tags.

\marginparBlock [⟨*left*⟩] {⟨*right*⟩} To include block-related macros, use \marginparBlock, which takes the same arguments but creates a instead of a . A line break will occur in the text where the \marginBlock occurs.

for HTML output:

```
\begin{warpHTML}
```

\marginpar [⟨*left*⟩] {⟨*right*⟩}

```
\renewcommand{\marginpar}[2][]{%
\ifbool{FormatWP}%
{%
\begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{marginblock}
#2
\end{LWR@BlockClassWP}
}%
{%
    \LWR@htmlspanclass{marginpar}{#2}%
}%
}
```

\marginparBlock [⟨*left*⟩] {⟨*right*⟩}

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

HTML version.

```
\newcommand{\marginparBlock}[2][]{%
\ifbool{FormatWP}%
{%
\begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{marginblock}
#2
\end{LWR@BlockClassWP}
}%
{%
\begin{BlockClass}[width:2in; float:right; margin:10pt]{marginparblock}
#2
\end{BlockClass}
}%
}
```

\reversemarginpar

```
\renewcommand*{\reversemarginpar}{}
```

\normalmarginpar

```
\renewcommand*{\normalmarginpar}{}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\marginparBlock [⟨*left*⟩] {⟨*right*⟩}

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

Print version.

```
\LetLtxMacro\marginparBlock\marginpar
```

```
\end{warpprint}
```

60 Splitting HTML files

- Files are split according to `FileDepth` and `CombineHigherDepths`.
- Filenames are sanitized by `\LWR@filenamenoblanks`.
- `\LWR@newhtmlfile` finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

for HTML & PRINT:

```
\begin{warpall}
```

Ctr `FileDepth` {⟨*section depth*⟩} determines how deeply to break into new HTML files, similar to `tocdepth`. The default of -5 produces one large HTML file.

```
\newcounter{FileDepth}
\setcounter{FileDepth}{-5}
```

Bool `CombineHigherDepths` Combile higher-level sections together into one file?

```
\newbool{CombineHigherDepths}
\booltrue{CombineHigherDepths}
```

`\FilenameLimit` Maximum length of the generated filenames.

```
\newcommand*{\FilenameLimit}{80}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@thisfilename` The currently-active filename or number. At first, this is the homepage.

```
\AtBeginDocument{
\ifbool{FileSectionNames}%
    {\newcommand*{\LWR@thisfilename}{\HomeHTMLFilename}}
    {\newcommand*{\LWR@thisfilename}{0}}
}
```

`\LWR@thisnewfilename` The filename being sanitized.

```
\newcommand*{\LWR@thisnewfilename}{}
```

\LWR@simplifyname * {⟨*expression*⟩} Simplify \LWR@thisnewfilename.

If starred, detokenizes the input expression. If found, changes the expression to a single detokenized dash.

```
\NewDocumentCommand{\LWR@simplifyname}{s m}{%
\IfBooleanTF{#1}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {\detokenize{#2}}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {#2}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}
}
```

\LWR@simplifycustom User-defined filename simplifications. Redefine with \newcommand.

```
\newcommand*{\LWR@simplifycustom}{}
```

\FilenameSimplify * {⟨*phrase*⟩} Assign a user-defined filename simplification. Appends to \LWR@simplifycustom.

```
\NewDocumentCommand{\FilenameSimplify}{s m}{%
\IfBooleanTF{#1}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname*{#2}%
    }%
}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname{#2}%
    }%
}%
}
```

\LWR@filenamenoblanks {⟨*filename*⟩}

Convert blanks into dashes, removes short words, store result in \LWR@thisfilename.

Also see \LWR@nullfonts for nullified macros.

```
\newcommand*{\LWR@filenamenoblanks}[1]{%
\begingroup
```

Locally temporarily disable direct-formatting commands, not used in filenames:

```
\LWR@nullfonts%
\renewcommand*{\LWR@htmltagc}[1]{}%
```

```
\edef\LWR@thisnewfilename{#1}%
```

Replaces common macros with hyphens. (\& is done by \LWR@nullfonts.)

```
\RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
\LWR@simplifyname{\_}
\LWR@simplifyname{\#}
\LWR@simplifyname{\textbackslash}
\LWR@simplifyname{\protect}
\LWR@simplifyname{\ }
\LWR@simplifyname{\textless}
\LWR@simplifyname{\textgreater}
```

```
\edef\LWR@thisnewfilename{\detokenize\expandafter{\LWR@thisnewfilename}}%
```

```
\LWR@traceinfo{LWR@filenamenoblanks edef: !\LWR@thisnewfilename!}%
\fullexpandarg%
```

Convert spaces into hyphens:

```
\LWR@simplifyname*{ }
```

Convert punctutation into hyphens:

```
\LWR@simplifyname*{!}
\LWR@simplifyname*{,}
\LWR@simplifyname*{'}
\LWR@simplifyname*{+}
\LWR@simplifyname*{,}
\LWR@simplifyname*{/}
\LWR@simplifyname*{:}
\LWR@simplifyname*{;}
\LWR@simplifyname*{=}
\LWR@simplifyname*{?}
\LWR@simplifyname*{@}
\LWR@simplifyname*{^}
\LWR@simplifyname*{&}
\LWR@simplifyname*{"}
\LWR@simplifyname*{<}
\LWR@simplifyname*{>}
```

```
\LWR@simplifyname{\LWRbackslash}
```

Braces are removed entirely to avoid extra dashes in the result.

```
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRleftbrace}{}[\LWR@thisnewfilename]%
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRrightbrace}{}[\LWR@thisnewfilename]%
```

```
\LWR@simplifyname{\LWRpercent}
\LWR@simplifyname{\LWRdollar}
```

```
\LWR@simplifyname*{|}
```

```
\LWR@simplifyname*{^}
\LWR@simplifyname*{~}
\LWR@simplifyname*{[}
\LWR@simplifyname*{]}
\LWR@simplifyname*{`}
```

Convert short words:

```
\LWR@simplifyname*{-s-}
\LWR@simplifyname*{-S-}
\LWR@simplifyname*{-a-}
\LWR@simplifyname*{-A-}
\LWR@simplifyname*{-an-}
\LWR@simplifyname*{-AN-}
\LWR@simplifyname*{-to-}
\LWR@simplifyname*{-TO-}
\LWR@simplifyname*{-by-}
\LWR@simplifyname*{-BY-}
\LWR@simplifyname*{-of-}
\LWR@simplifyname*{-OF-}
\LWR@simplifyname*{-and-}
\LWR@simplifyname*{-AND-}
\LWR@simplifyname*{-for-}
\LWR@simplifyname*{-FOR-}
\LWR@simplifyname*{-the-}
\LWR@simplifyname*{-THE-}
```

Convert custom words:

```
\LWR@simplifycustom%
```

Convert multiple hyphens:

```
\LWR@simplifyname*{-----}
\LWR@simplifyname*{----}
\LWR@simplifyname*{---}
\LWR@simplifyname*{--}
```

If pdfLaTeX and not `utf8` encoding, don't try to convert emdash, endash:

```
\ifPDFTeX% pdflatex or dvi latex
\ifdefstring{\inputencodingname}{utf8}{%
\LWR@simplifyname*{---}
%     emdash
\LWR@simplifyname*{--}
%     endash
}{}%
\else% not PDFTeX
\LWR@simplifyname*{---}
\LWR@simplifyname*{--}
\fi%
```

If starts with a dash, remove the leading dash:

```
\IfBeginWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleLeft{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

If ends with a dash, remove the trailing dash:

```
\IfEndWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleRight{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

Limits the length of the filename:

```
\StrLeft{\LWR@thisnewfilename}{\FilenameLimit}[\LWR@thisnewfilename]%
```

Return the global result:

```
\global\let\LWR@thisfilename\LWR@thisnewfilename%
\endgroup%
\LWR@traceinfo{LWR@filenamenoblanks: result is \LWR@thisfilename}%
}
```

Ctr `LWR@previousautopagelabel` Remembers which autopage label was most recently generated. Used to avoid duplicates.

```
\newcounter{LWR@previousautopagelabel}
\setcounter{LWR@previousautopagelabel}{-1}
```

File `*_html.aux` A new entry in the `*_html.aux` file is used to help cross-references:

```
\newlabel{autopage-<nnn>}{{<x>}{<y>}}
```

`\LWR@newautopagelabel` {⟨*pagenumber counter*⟩}

```
\newcommand*{\LWR@newautopagelabel}[1]{%
\ifnumequal{\value{LWR@previousautopagelabel}}{\value{page}}%
{}% no action if this autopage label has already been defined
{%
    \label{autopage-\arabic{#1}}%
    \setcounter{LWR@previousautopagelabel}{\value{page}}
}%
}
```

60.1 Customizing MathJax

`\LWR@customizedMathJax` Additional MathJax definitions to be added to the start of each HTML page.

```
\newcommand*{\LWR@customizedMathJax}{}
```

\CustomizeMathJax MATHJAX does not have preexisting support every possible math function. Additional MATHJAX function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

```
\newcommand*{\CustomizeMathJax}[1]{%
    \appto{\LWR@customizedMathJax}{%
        \(#1\)\par
    }%
}
```

\LWR@customizeMathJax

```
\newcommand{\LWR@customizeMathJax}{%
\ifbool{mathjax}{

\LWR@stoppars
\LWR@htmlcomment{Nullify \textbackslash{}ensuremath, footnotes for MathJax:}

\(\newcommand\ensuremath[1]{##1}\)

\(\newcommand\footnote[2][]{\text{( Footnote ##1 )}}\)

\(\newcommand\footnotemark[1][]{\text{( Footnote ##1 )}}\)

\LWR@htmlcomment{Additional customizations for MathJax:}

\LWR@customizedMathJax

\LWR@startpars
}{}
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\CustomizeMathJax The print-mode version:

```
\newcommand*{\CustomizeMathJax}[1]{}
```

\FilenameSimplify * {⟨*expression*⟩}

```
\NewDocumentCommand{\FilenameSimplify}{s m}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@newhtmlfile` {⟨*section name*⟩}

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and CSS are, then adds navigation, side TOC, header, and starts the text body.

```
\newcommand*{\LWR@newhtmlfile}[1]{
\LWR@traceinfo{LWR@newhtmlfile}
```

At the bottom of the ending file:

```
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{div}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}

\LWR@printpendingfootnotes

```

No footer between files if EPUB:

```
\ifbool{FormatEPUB}
{}
{
    \LWR@htmlelement{footer}

    \LWR@pagebottom

    \LWR@htmlelementend{footer}
}
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}}
```

End of this HTML file:

```
\LWR@stoppars
\LWR@htmltag{/body}\LWR@orignewline
\LWR@htmltag{/html}\LWR@orignewline
\LWR@traceinfo{LWR@newhtmlfile: about to LWR@orignewpage}
\LWR@orignewpage

\addtocounter{LWR@htmlfilenumber}{1}%
```

If using a filename based on section name, create a version without blanks. The filename without blanks will be placed into `\LWR@thisfilename`. Duplicates will be detected using MD5 hashes.

If not using a filename, the file number will be used instead.

```
\ifbool{FileSectionNames}%
{%
```

Convert the section name to a filename with blanks and common words removed. The resulting filename is in `\LWR@thisfilename`.

```
    \LWR@filenamenoblanks{#1}%
```

Create a macro name from the MD5 hash of the file name, to detect duplicates:

```
    \edef\LWR@hashedname{\LWR@mdfive{\LWR@thisfilename}}%
```

If the macro name is not yet defined, this filename is unique.

```
    \ifcsundef{LWR@filename\LWR@hashedname}{%
```

If the filename is unique, create a macro using the hashed name, to be used to test for additional duplicates in the future.

```
        \csdef{LWR@filename\LWR@hashedname}{}%
    }{%
```

If the filename is not unique, create an error.

```
        \PackageError{lwarp}
            {%
                Section name\MessageBreak
                ``#1'',\MessageBreak
                at the line number listed below,\MessageBreak
                generates the filename\MessageBreak
                ``\LWR@thisfilename'',\MessageBreak
                which appears to be a duplicate.\MessageBreak
                There is a previous section with an\MessageBreak
                identical or similar name%
            }
            {%
                Lwarp sanitizes most symbols and a few common short words
                when generating file names, and this may cause a conflict.
            }
    }
}
```

If using file numbers instead of names, the name is set to the next file number.

```
{\renewcommand*{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}
```

Include an HTML comment to instruct lwarpmk where to split the files apart. Uses pipe-separated fields for `split_html.gawk`. Uses monospaced font with ligatures disabled for everything except the title.

```
\LWR@traceinfo{LWR@newhtmlfile: about to print start file}%
```

\LWR@nullfonts to allow math in a section name.

```
\begingroup%
\LWR@nullfonts%
\LWR@htmlblockcomment{%
|Start file|%
\LWR@htmlsectionfilename{\LWR@thisfilename}|%
}
\endgroup%
```

At the top of the starting file:

```
\LWR@stoppars

```

Start a new file with the given section name:

```
\LWR@filestart[#1]

```

Track the page numbers:

```
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@latestautopage}%
```

No navigation between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\LWR@topnavigation}

```

No header if between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {
        \LWR@htmlelement{header}

        \LWR@pagetop

        \LWR@htmlelementend{header}
    }

```

The container for the sidetoc and text body:

```
\LWR@htmlelementclass{div}{bodyandsidetoc}
```

No sideTOC if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\LWR@sidetoc}
```

Start of the <textbody>:

```
\LWR@htmlelementclass{div}{bodycontainer}
\LWR@htmlelementclass{section}{textbody}
```

Print title only if there is one. Skip if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}%
    {}%
    {%
        \ifcsvoid{thetitle}{}{%
            \LWR@printthetitle%
        }%
    }%
```

Keep paragraph tags disabled for now:

```
\LWR@stoppars
```

If using MathJax, disable \ensuremath by printing a nullified definition at the start of each file, and add further customizations:

```
\LWR@customizeMathJax
```

```
\LWR@traceinfo{LWR@newhtmlfile: done}
}
```

```
\end{warpHTML}
```

61 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing LaTeX code and packages. Formatting is handled by css, so the emulated code has much less work to do than the print versions.

Unicode

⚠ accents in filenames

Section names and the resulting filenames with accented characters are partially supported, depending on the ability of *pdflatex* to generate characters and *pdftotext* to read them. If extra symbols appear in the text, it may be that *pdflatex* is actually producing a symbol over or under a character, resulting in *pdftotext* picking up the accent symbol separately.

XeLaTeX and LuaLaTeX directly support accented section and file names.

for HTML output:

```
\begin{warpHTML}
```

61.1 User-level starred section commands

\ForceHTMLPage For HTML output, forces the next section to be on its own HTML page, if FileDepth allows, even if starred. For use with \printindex and others which generate a starred section which should be on its own HTML page. Also see \ForceHTMLTOC.

For print output, no effect.

```
\newbool{LWR@forcinghtmlpage}
\boolfalse{LWR@forcinghtmlpage}

\newcommand*{\ForceHTMLPage}{%
\global\booltrue{LWR@forcinghtmlpage}%
}
```

\ForceHTMLTOC For HTML output, forces the next section to have a TOC entry, even if starred. For use with \printindex and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with tocbibind. Also see \ForceHTMLPage.

For print output, no effect.

```
\newbool{LWR@forcinghtmltoc}
\boolfalse{LWR@forcinghtmltoc}

\newcommand*{\ForceHTMLTOC}{%
\global\booltrue{LWR@forcinghtmltoc}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\ForceHTMLPage}{}
\newcommand*{\ForceHTMLTOC}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

61.2 Book class commands

\mainmatter ⚠ Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```
\newbool{LWR@mainmatter}
\DeclareDocumentCommand{\mainmatter}{}{%
\booltrue{LWR@mainmatter}%
}
```

\frontmatter Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```
\DeclareDocumentCommand{\frontmatter}{}{%
\boolfalse{LWR@mainmatter}%
}
```

\backmatter Declare the back matter section of the document. Does not reset the page number.

```
\DeclareDocumentCommand{\backmatter}{}{%
\boolfalse{LWR@mainmatter}
}
```

61.3 Sectioning support macros

\LWR@sectionumber {⟨*section type*⟩}

Typeset a section number and its trailing space with CSS formatting:

```
\newcommand*{\LWR@sectionnumber}[1]{%
\InlineClass{sectionnumber}{#1}%
}
```

autosec A tag used by the TOC and index.

\LWR@createautosec {⟨*section type*⟩}

Create an autosection tag.

```
\newcommand*{\LWR@createautosec}[1]{%
\LWR@htmltag{%
    #1 % space
    id=\textquotedbl\LWR@print@mbox{autosec-\arabic{page}}\textquotedbl%
}%
}
```

\LWR@pushoneclose {⟨*depth*⟩} {⟨*printclose*⟩} Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

⚠ \LWR@stoppars must be executed first.

```
\NewDocumentCommand{\LWR@pushoneclose}{m m}{%
\LWR@traceinfo{LWR@pushoneclose #1}%
    \pushclose{#2}{#1}%
}
```

\LWR@startnewdepth {⟨*depth*⟩} {⟨*printclose*⟩}

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

⚠ \LWR@stoppars must be executed first.

```
\NewDocumentCommand{\LWR@startnewdepth}{m m}{%
```

Close any stacked sections up to this new one.

```
\LWR@closeprevious{#1}%
```

Push a new section depth:

```
\LWR@pushoneclose{#1}{#2}%
}
```

Ctr `LWR@prevFileDepth` Remembers the previous `LWR@FileDepth`.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
\newcounter{LWR@prevFileDepth}
\setcounter{LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

`\@seccntformat` {⟨*sectiontype*⟩}

```
\def\@seccntformat#1{\csname the#1\endcsname\quad}
```

`\simplechapterdelim` Used by tocbibind and anonchap.

```
\newcommand*{\simplechapterdelim}{}
```

`\@chapcntformat` {⟨*sectiontype*⟩}

`\let` to `\@seccntformat` by default, but may be redefined by `\simplechapter` and `\restorechapter` from tocbibind or anonchap.

```
\let\@chapcntformat\@seccntformat
```

`\@partcntformat` {⟨*sectiontype*⟩}

`\let` to `\@seccntformat` by default, but may be redefined by ctex.

```
\let\@partcntformat\@seccntformat
```

`\@partnameformat` Prints “Part” for part sections.

Nullified by ctex.

```
\newcommand*{\@partnameformat}{\LWR@isolate{\partname}~}%
```

Ctr `LWR@currentautosec` Records the page number when the section was created. If a math expression is included in the section name, and SVG math is used, the corresponding `lateximage`

will cause the page number to change by the time the following autosec label is created.

```
\newcounter{LWR@currentautosec}
\setcounter{LWR@currentautosec}{1}
```

\LWR@section * [⟨*TOC name*⟩] {⟨*name*⟩} {⟨*sectiontype*⟩}

The common actions for the high-level sectioning commands.

```
\DeclareDocumentCommand{\LWR@section}{m m m m}{%
\LWR@traceinfo{LWR@section: starting}%
\LWR@stoppars%
```

Cancel special minipage horizontal space interaction:

```
\global\boolfalse{LWR@minipagethispar}%
```

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for \part*, for appendix.

Generate a new LaTeX page so that TOC and index page number points to the section:

```
\LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%
\IfBooleanT{#1}{\LWR@traceinfo{LWR@section: starred}}%
\ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}}{}%
\ifthenelse{%
    \(%
        \(\NOT\equal{#1}{\BooleanTrue}\)\OR%
        \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)\OR%
        \(\boolean{LWR@forcinghtmlpage}\)%
    \)%
    \AND%
    \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{FileDepth}}%
    \AND%
    \(%
        \NOT\boolean{CombineHigherDepths}\OR%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}%
    \)%
    \AND%

    \(% phantomsection
        \NOT\isempty{#3}%
        \OR%
        \(\NOT\equal{#1}{\BooleanTrue}\)%
    \)%
}%
```

If so: start a new HTML file:

```
{% new file
    \LWR@traceinfo{LWR@section: new HTML file}%
```

See if there was an optional TOC name entry:

```
    \IfNoValueTF{#2}%
```

If no optional entry

```
        {\LWR@newhtmlfile{#3}}%
```

If yes an optional entry

```
        {\LWR@newhtmlfile{#2}}%
}% new file
```

Else: No new HTML file:

```
{% not new file
```

Generate a new LaTeX page so that TOC and index page number points to the section:

```
    \LWR@traceinfo{LWR@section: not a new HTML file, about to LWR@orignewpage}%
    \LWR@orignewpage%
}% not new file

```

Remember this section's name for `\nameref`:

```
\IfValueT{#3}{%
    \LWR@traceinfo{LWR@section: about to LWR@setlatestname}%
    \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
}%
```

Print an opening comment with the level and the name; ex: "section" "Introduction" Footnotes may be used in section names, which would also appear in the HTML section opening comments, so the short TOC entry is used if possible, and a limited opening comment is made if the sectional unit is starred.

```
\ifbool{HTMLDebugComments}{%
    \begingroup%
    \LWR@nullfonts%
    \IfBooleanTF{#1}% starred
    {\LWR@htmlcomment{Opening #4*}}%
    {%
        \IfNoValueTF{#2}% short TOC
            {\LWR@htmlcomment{Opening #4 ``#3''}}%
            {\LWR@htmlcomment{Opening #4 ``#2''}}%
    }\LWR@orignewline%
    \endgroup%
}{}
```

For inline sections paragraph and subparagraph, start a new paragraph now:

```
\ifthenelse{%
    \cnttest{\@nameuse{LWR@depth#4}}{>=}{\LWR@depthparagraph}%
```

```
}%
    {\LWR@startpars}%
    {}%
```

Create the opening tag with an autosec:

```
\LWR@traceinfo{LWR@section: about to LWR@createautosec}%
\LWR@createautosec{\@nameuse{LWR@tag#4}}%

\setcounter{LWR@currentautosec}{\value{page}}%
```

Check if starred:

```
\IfBooleanTF{#1}%
{%
    \LWR@traceinfo{LWR@section: starred}%
```

Starred, but also forcing a TOC entry, so add unnumbered TOC name or regular name:

```
    \ifbool{LWR@forcinghtmltoc}%
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
    }%
    {}%
}% starred
```

Not starred, so step counter and add to TOC:

```
{% not starred
```

Only add a numbered TOC entry if section number is not too deep:

```
    \ifthenelse{%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
    }%
    {% if secnumdepth
```

If in the main matter, step the counter and add the TOC entry. For `article` class, lwarp assumes that all is mainmatter.

```
        \LWR@traceinfo{LWR@section: about to test main matter}%
        \ifbool{LWR@mainmatter}%
        {%
            \LWR@traceinfo{LWR@section: yes mainmatter}%
            \refstepcounter{#4}%
```

Add main matter numbered TOC entry with the TOC name or the regular name:

```
            \LWR@traceinfo{LWR@section: about to addcontentsline}%
            \addcontentsline{toc}{#4}%
            {%
```

```
                \protect\numberline{%
                    \@nameuse{pre#4name}%
                    \@nameuse{the#4}%
                    \@nameuse{post#4name}%
                }%
                {%
                    \ignorespaces%
             \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
                }%
            }%
            \LWR@traceinfo{LWR@section: finished addcontentsline}%
        }% end of if main matter
```

If not main matter, add unnumbered TOC name or regular name:

```
        {% not main matter
            \LWR@traceinfo{LWR@section: no main matter}%
            \addcontentsline{toc}{#4}{%
                \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
            }%
        }% end of not main matter
    }% end of secnumdepth
```

Deeper than secnumdepth, so add an unnumbered TOC entry:

```
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
    }%
```

For part, print “Part”:

```
    \ifbool{LWR@mainmatter}%
    {%
        \ifthenelse{%
            \(\cnttest{\@nameuse{LWR@depth#4}}{<=}%
                {\value{secnumdepth}}\) \AND%
            \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)%
        }%
            {\@partnameformat}%
            {}%
```

Print the section number:

```
        \LWR@traceinfo{LWR@section: about to print section number}%
        \ifthenelse{%
            \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
        }%
            {%
                \ifstrequal{#4}{part}%
                {\protect\LWR@sectionnumber{\@partcntformat{#4}}}%
                {%
                    \ifstrequal{#4}{chapter}%
                        {\protect\LWR@sectionnumber{\@chapcntformat{#4}}}%
```

```
                        {\protect\LWR@sectionnumber{\@seccntformat{#4}}}%
                }%
            }%
            {}%
        \LWR@traceinfo{LWR@section: finished print section number}%
    }{}%
}% end of not starred
```

Print the section name:

```
\LWR@traceinfo{LWR@section: about to print the section name}%
\LWR@isolate{#3}%
```

Close the heading tag, such as /H2:

```
\LWR@traceinfo{LWR@section: about to close the heading tag}%
\LWR@htmltag{\@nameuse{LWR@tag#4end}}%
\LWR@orignewline%
```

Generate a LaTeX label:

```
\LWR@traceinfo{LWR@section: about to create the LaTeX label}%
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosec}\LWR@orignewline%
```

Start paragraph handing unless is an inline paragraph or subparagraph:

```
\ifthenelse{%
    \cnttest{\@nameuse{LWR@depth#4}}{<}{\LWR@depthparagraph}%
}%
    {\LWR@startpars}%
    {}%
```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a `\part*` to start a new HTML page. This is used by appendix.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a `\listoftables` was tested in the middle of the document. The `\chapter*` for the list was not allowing a new HTML page for the section following it while `CombineHigherDepths` was true.

```
\ifthenelse{%
    \NOT\equal{#1}{\BooleanTrue}\OR%
    \cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}%
}%
    {% not starred
        \setcounter{LWR@prevFileDepth}{\@nameuse{LWR@depth#4}}%
    }% not starred
    {}%
```

Reset to defaults if not a phantomsection:

```
\ifstrempty{#3}%
```

```
    {}%
    {%
        \global\boolfalse{LWR@forcinghtmlpage}%
        \global\boolfalse{LWR@forcinghtmltoc}%
    }%
%
\LWR@traceinfo{LWR@section: done}%
}
```

61.4 Pre- and post- sectioning names

\prepartname
\postpartname

Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prepartname}{}
\providecommand*{\postpartname}{}
```

\prechaptername
\postchaptername

Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prechaptername}{}
\providecommand*{\postchaptername}{}
```

\presectionname
\postsectionname

Always null, but provided here for algorithmic simplicity in \LWR@section.

```
\providecommand*{\presectionname}{}
\let\postsectionname\presectionname

\let\presubsectionname\presectionname
\let\postsubsectionname\postsectionname

\let\presubsubsectionname\presectionname
\let\postsubsubsectionname\postsectionname

\let\preparagraphname\presectionname
\let\postparagraphname\postsectionname

\let\presubparagraphname\presectionname
\let\postsubparagraphname\postsectionname
```

61.5 \section and friends

\part * [⟨*TOC name*⟩] {⟨*name*⟩}

```
\newcommand{\part@preamble}{}% for koma-script

\DeclareDocumentCommand{\part}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthpart}%
\LWR@stoppars%

```

```
\LWR@startnewdepth{\LWR@depthpart}{\LWR@printclosepart}%

\LWR@section{#1}{#2}{#3}{part}%

\part@preamble% for koma-script
\renewcommand{\part@preamble}{}%
}
```

\chapter * [⟨*TOC name*⟩] [⟨*heading name*⟩] {⟨*name*⟩}

```
\let\@printcites\relax% for quotchap package

\newcommand{\chapter@preamble}{}% for koma-script

\@ifundefined{chapter}
{}
{%
\DeclareDocumentCommand{\chapter}{s o o m}{%
\IfValueTF{#2}{
\LWR@traceinfo{chapter #2}%
}{
\LWR@traceinfo{chapter #4}%
}
\LWR@maybeprintpendingfootnotes{\LWR@depthchapter}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthchapter}{\LWR@printclosechapter}%

\LWR@section{#1}{#2}{#4}{chapter}%

\@printcites% for quotchap package

\chapter@preamble% for koma-script
\renewcommand{\chapter@preamble}{}%
}
}
```

\section * [⟨*TOC name*⟩] [⟨*heading name*⟩] {⟨*name*⟩}

```
\DeclareDocumentCommand{\section}{s o o m}{%
\LWR@traceinfo{section: starting}%
\LWR@maybeprintpendingfootnotes{\LWR@depthsection}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthsection}{\LWR@printclosesection}%

\LWR@section{#1}{#2}{#4}{section}%
}
```

\subsection * [⟨*TOC name*⟩] {⟨*name*⟩}

```
\DeclareDocumentCommand{\subsection}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthsubsection}%
```

```
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthsubsection}{\LWR@printclosesubsection}%

\LWR@section{#1}{#2}{#3}{subsection}%
}
```

\subsubsection * [⟨*TOC name*⟩] {⟨*name*⟩}

```
\DeclareDocumentCommand{\subsubsection}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthsubsubsection}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthsubsubsection}%
{\LWR@printclosesubsubsection}%

\LWR@section{#1}{#2}{#3}{subsubsection}%
}
```

\paragraph * [⟨*TOC name*⟩] {⟨*name*⟩}

```
\DeclareDocumentCommand{\paragraph}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthparagraph}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthparagraph}{\LWR@printcloseparagraph}%

\LWR@section{#1}{#2}{#3}{paragraph}%
}
```

\subparagraph * [⟨*TOC name*⟩] {⟨*name*⟩}

```
\DeclareDocumentCommand{\subparagraph}{s o m}{%
\LWR@maybeprintpendingfootnotes{\LWR@depthsubparagraph}%
\LWR@stoppars%

\LWR@startnewdepth{\LWR@depthsubparagraph}{\LWR@printclosesubparagraph}%

\LWR@section{#1}{#2}{#3}{subparagraph}%
}
```

```
\end{warpHTML}
```

62 Starting a new file

for HTML & PRINT:

```
\begin{warpall}
```

\HTMLLanguage Default language for the HTML lang tag.

```
\newcommand*{\LWR@currentHTMLLanguage}{en-US}

\newcommand*{\HTMLLanguage}[1]{%
\renewcommand*{\LWR@currentHTMLLanguage}{#1}%
}
```

\theHTMLTitleSeparator

May be used inside \theHTMLTitleSection to separate the website's overall HTML title and the particular page's section name.

```
\ifPDFTeX% pdflatex or dvi latex
    \ifdefstring{\inputencodingname}{utf8}{%
        \newcommand*{\theHTMLTitleSeparator}{ --- }% EMdash
    }{%
        \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
    }%
\else%
    \ifpTeX
        \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
    \else
        \newcommand*{\theHTMLTitleSeparator}{ --- }% EMdash
    \fi%
\fi%
```

\HTMLTitleBeforeSection

Sets the HTML page's meta title tag to show the website title before the section name.

```
\newcommand*{\HTMLTitleBeforeSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
    }%
}
```

\HTMLTitleAfterSection

Sets the HTML page's meta title tag to show the section name before the website title.

```
\newcommand*{\HTMLTitleAfterSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLSection\theHTMLTitleSeparator\theHTMLTitle%
    }%
}
```

\theHTMLTitleSection

Forms the HTML page's meta title tag. The default is to show the website title before the section name.

```
\HTMLTitleBeforeSection
```

\theHTMLSection

The section name is passed to \LWR@filestart, which then sets \theHTMLSection for use inside \theHTMLTitleSection to create an HTML meta title tag.

```
\newcommand*{\theHTMLSection}{}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@filestart` [⟨*sectionname*⟩] Creates the opening HTML tags.

```
\newcommand*{\LWR@filestart}[1][]{%
\LWR@traceinfo{LWR@filestart !#1!}%
```

Locally temporarily disable direct-formatting commands:

```
\begingroup%
\LWR@nullfonts%
```

Save the section name for use while creating the HTML meta `title` tag:

```
\edef\theHTMLSection{#1}%
```

Create the page's HTML header:

```
\LWR@htmltag{!DOCTYPE html}\LWR@orignewline
```

The language is user-adjustable:

```
\LWR@htmltag{%
  html lang=\LWR@orig@textquotedbl\LWR@currentHTMLLanguage\LWR@orig@textquotedbl%
}\LWR@orignewline
```

Start of the meta data:

```
\LWR@htmltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
\LWR@htmltag{%
    meta charset=\LWR@orig@textquotedbl{}UTF-8\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

Author:

```
\ifthenelse{\equal{\theHTMLAuthor}{}}%
    {}%
    {%
        \LWR@htmltag{%
        meta name=\LWR@orig@textquotedbl{}author\LWR@orig@textquotedbl\ % space
         content=\LWR@orig@textquotedbl\theHTMLAuthor\LWR@orig@textquotedbl\ /%
        }\LWR@orignewline%
    }%
```

lwarp is the generator:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}generator\LWR@orig@textquotedbl\ % space
```

```
  content=\LWR@orig@textquotedbl{}LaTeX lwarp package\LWR@orig@textquotedbl\ /%
}\LWR@orignewline%
```

If there is a description, add it now:

```
\ifdefempty{\LWR@currentHTMLDescription}{}{%
    \LWR@htmltag{%
      meta name=\LWR@orig@textquotedbl{}description\LWR@orig@textquotedbl\ % space
      content=\LWR@orig@textquotedbl\LWR@currentHTMLDescription\LWR@orig@textquotedbl\ /%
    }\LWR@orignewline
}%
```

Mobile-friendly viewport:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}viewport\LWR@orig@textquotedbl\ % space
  content=\LWR@orig@textquotedbl{}width=device-width, initial-scale=1.0\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

IE patch:

```
\LWR@htmltag{!-\/-[if lt IE 9]}\LWR@orignewline
\LWR@htmltag{%
    script % space
    src=\LWR@orig@textquotedbl{}%
        http://html5shiv.googlecode.com/svn/trunk/html5.js%
    \LWR@orig@textquotedbl%
}%
\LWR@htmltag{/script}\LWR@orignewline
\LWR@htmltag{![endif]-\/-}\LWR@orignewline
```

The page's title, if there is one. A section name is also added if given.

```
\ifthenelse{\equal{\theHTMLTitle}{}}%
    {}%
    {%
        \LWR@htmltag{title}%
        \ifdefempty{\theHTMLSection}%
            {\theHTMLTitle}%
            {\theHTMLTitleSection}%
        \LWR@htmltag{/title}\LWR@orignewline%
    }%
```

The page's stylesheet:

```
\LWR@htmltag{%
    link % space
    rel=\LWR@orig@textquotedbl{}stylesheet\LWR@orig@textquotedbl\ % space
    type=\LWR@orig@textquotedbl{}text/css\LWR@orig@textquotedbl\ % space
    href=\LWR@orig@textquotedbl\LWR@currentcss\LWR@orig@textquotedbl\ /%
}%
\LWR@orignewline
```

Optional MathJax support. The HTML tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```
\ifbool{mathjax}%
{%
    \begingroup%
    \LWR@restoreoriglists%
    \boolfalse{LWR@verbtags}%

        \verbatiminput{lwarp_mathjax.txt}%

    \booltrue{LWR@verbtags}%
    \endgroup%
    \LWR@stoppars%
}% end of mathjax
{}%
```

End of the header:

```
\LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```
\LWR@htmltag{body}\LWR@orignewline
\endgroup
\LWR@traceinfo{LWR@filestart: done}
}

\end{warpHTML}
```

63 Starting HTML output

for HTML output:

```
\begin{warpHTML}
```

`\LWR@LwarpStart` Executed at the beginning of the entire document.

The use of `\textquotedbl` instead of " improves compatibility with xeCJK.

```
\catcode`\$=\active
\newcommand*{\LWR@LwarpStart}
{%
\LWR@traceinfo{LWR@lwarpStart}
```

If formatting for a word processor, force filedepth to single-file only, force HTML debug comments off.

```
\ifbool{FormatWP}{%
    \setcounter{FileDepth}{-5}%
    \boolfalse{HTMLDebugComments}%
}{}
```

Expand and detokenize \HomeHTMLFilename and \HTMLFilename:

```
\edef\LWR@strresult{\HomeHTMLFilename}
\edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
\edef\LWR@strresult{\HTMLFilename}
\edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}
```

Force onecolumn and empty page style:

```
\LWR@origonecolumn%
\LWR@origpagestyle{empty}%
```

No black box for overfull lines:

```
\overfullrule=0pt
```

Reduce chance of line overflow when HTML tags are added:

```
\LWR@print@footnotesize%
```

In PDF output, don't allow line breaks to interfere with HTML tags:

```
\LWR@print@raggedright%
\LetLtxMacro{\\}{\LWR@endofline}%
```

Spread the lines for *pdftotext* to read them well:

```
\linespread{1.3}%
```

For *pdftotext* to reliably identify paragraph splits:

```
\setlength{\parindent}{0pt}
\setlength{\parskip}{2ex}
```

For the lateximage record file:

```
\immediate\openout\LWR@lateximagesfile=\BaseJobname-images.txt
```

Removes space around the caption in the HTML:

```
\setlength{\belowcaptionskip}{0ex}
\setlength{\abovecaptionskip}{0ex}
```

Redefine the plain page style to be empty when used by index pages:

```
\renewcommand{\ps@plain}{}
```

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Float captions:

```
\let\LWR@origcaption\caption
```

Labels: \ltx@label is used in amsmath environments and is also patched by cleveref.

Label in HTML

```
\let\LWR@origltx@label\ltx@label
\let\ltx@label\LWR@htmlmathlabel
```

Logos:

```
\LetLtxMacro\TeX\LWR@TeX
\LetLtxMacro\LaTeX\LWR@LaTeX
\LetLtxMacro\LuaTeX\LWR@LuaTeX
\LetLtxMacro\LuaLaTeX\LWR@LuaLaTeX
\LetLtxMacro\XeTeX\LWR@XeTeX
\LetLtxMacro\XeLaTeX\LWR@XeLaTeX
\LetLtxMacro\ConTeXt\LWR@ConTeXt
```

Not yet started any paragraph handling:

```
\global\boolfalse{LWR@doingapar}
\global\boolfalse{LWR@doingstartpars}
```

Document and page settings:

```
\mainmatter
\LWR@origpagenumbering{arabic}
```

Start a new HTML file and a header:

```
\LWR@traceinfo{LWR@lwarpStart: Starting new file.}
\LWR@filestart
\LWR@traceinfo{LWR@lwarpStart: Generating first header.}
\LWR@htmltag{header}\LWR@orignewline
\LWR@startpars
\LWR@firstpagetop
\LWR@stoppars
\LWR@htmltag{/header}\LWR@orignewline
```

```
\LWR@htmlelementclass{div}{bodywithoutsidetoc}
\LWR@htmlelementclass{div}{bodycontainer}
\LWR@traceinfo{LWR@lwarpStart: Generating textbody.}
\LWR@htmlelementclass{section}{textbody}
```

Patch the itemize, enumerate, and description environments and \item. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\LWR@patchlists
```

Ensure that math mode is active to call lwarp's patches:

```
\catcode`\$=\active
```

Required for \nameref to work with SVG math:

```
\immediate\write\@mainaux{\catcode`\string$\active}%
\LetLtxMacro\LWR@syntaxhighlightone$% balance for editor syntax highlighting
```

Allow HTML paragraphs to begin:

```
\LWR@startpars
```

If using MathJax, disable \ensuremath by printing a nullified definition at the start of each file, and add further customizations:

```
\LWR@customizeMathJax
```

First autopage label in case a figure occurs early.

```
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosec}%

\LWR@traceinfo{LWR@lwarpStart: done}
}
\catcode`\$=3% math shift until lwarp starts

\end{warpHTML}
```

64 Ending HTML output

for HTML output:

```
\begin{warpHTML}
```

\LWR@requesttoc {⟨*boolean*⟩} {⟨*suffix*⟩} Requests that a TOC, LOF, or LOTbe generated.

```
\newcommand*{\LWR@requesttoc}[2]{%
\ifbool{#1}
{
    \expandafter\newwrite\@nameuse{tf@#2}
    \immediate\openout \@nameuse{tf@#2} \jobname.#2\relax
}{}
}
```

\LWR@LwarpEnd Final stop of all HTML output:

```
\newcommand*{\LWR@LwarpEnd}
{
\LWR@stoppars
\LWR@closeprevious{\LWR@depthfinished}
```

At the bottom of the ending file:

Close the textbody:

```
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{div}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}
```

Print any pending footnotes:

```
\LWR@printpendingfootnotes
```

Create the footer:

```
\LWR@htmlelement{footer}

\LWR@pagebottom

\LWR@htmlelementend{footer}
```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {
        \ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}
    }
```

```
\LWR@stoppars% final stop of all paragraphs
```

Finish the HTML file:

```
\LWR@htmltag{/body}\LWR@orignewline
\LWR@htmltag{/html}\LWR@orignewline
```

Seems to be required sometimes:

```
\LWR@orignewpage
```

For `lateximage` commands:

```
\immediate\write\LWR@lateximagesfile{%
    |end|end|end|%
}%
\immediate\closeout\LWR@lateximagesfile
}
```

```
\end{warpHTML}
```

65 Title page

package support
⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 65.8.

affiliation

lwarp provides for the \author macro an additional \affiliation macro to provide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using titlingpage's \theauthor in the main text.

reusing titlepage information

⚠ \theauthor, authblk

The titling package maintains the definitions of \thetitle, \theauthor, etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the \thanks and \affiliation removed, and for \author the \and is replaced to generate a simple inline list of authors separated by commas. Note: \theauthor does not work well with authblk unless the traditional LaTeX syntax is used.

custom titlepages

\printtitle, \printauthor, etc., are provided for use inside a custom titlepage or titlingpage environment, and these retain the \thanks and \affiliation.

\printthanks

\printthanks has been added to force the printing of thanks inside a titlingpage environment when \maketitle is not used.

⚠ \thanks

Inside a \titlepage or \titlingpage environment, use \thanks instead of \footnote for acknowledgements, etc.

65.1 Setting the title, etc.

The following provide setting commands for both HTML and print outputs.

\author
\and

{⟨*author*⟩} While using \maketitle and print mode, the author is treated as a single-column tabular and the \and feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as

```
\author{Name \\ Affiliation \and Second Name \\ Second Affiliation}
```

For HTML, the entire author block is placed inside a of class author, and each individual author is inside a of class oneauthor.

\@title
\@author
\@date

\@title, \@author, etc. store the values as originally assigned, including any \thanks, \and, or \affiliation. These are low-level macros intended to be used by other macros only inside a titlepage or titlingpage, and are used by \maketitle. The author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For HTML, these tabulars become side-by-side s of class oneauthor, all of which are combined into one of class author.

\printtitle
\printauthor
\printdate

\printtitle, etc. are user-level macros intended to be used in custom titlepage or titlingpage environments in cases where \maketitle is not desired. These commands preserve the \thanks, etc., and should not be used in the main text.

\thetitle
\theauthor
\thedate

\thetitle, \theauthor, and \thedate are available if titling has been loaded, and are sanitized user-level versions from which have been removed the \thanks and \affiliation, and \and is changed for inline text usage. The author is printed inline without \affiliation or \thanks, with \and placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each HTML page, such as:

\HTMLPageBottom {⟨*text*⟩}

```
\HTMLPageBottom{
\begin{center}\textcopyright~2016 \theauthor\end{center}
}
```

⚠ \theauthor, authblk

\theauthor does not work well if authblk is used. If \theauthor is important, it is recommended to use the standard LaTeX syntax for \author, optionally with lwarp's \affiliation macro as well.

⚠ affiliations

After \maketitle has completed, \theauthor retains the definition of the author, but \and is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

\affiliation

A solution, provide here, is to define a macro \affiliation which, during \maketitle, starts a new row and adds the affiliation, but after \maketitle is finished \affiliation is re-defined to discard its argument, thus printing only the author names when \author is later used inline.

65.2 \if@titlepage

for HTML & PRINT:

```
\begin{warpall}
```

\if@titlepage

Some classes do not provide \if@titlepage. In this case, provide it and force it false.

```
\ifcsvoid{@titlepagefalse}{
    \newif\if@titlepage
    \@titlepagefalse
}{}

\end{warpall}
```

65.3 Changes for \affiliation

\affiliation {⟨*text*⟩}

Adds the affiliation to the author for use in \maketitle.

Inside titlepage, this macro prints its argument. Outside, it is null.

for HTML & PRINT:

```
\begin{warpall}
\providerobustcmd{\affiliation}[1]{}
\end{warpall}
```

for PRINT output:

```
\begin{warpprint}

\AtBeginEnvironment{titlepage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}

\AtBeginDocument{
\@ifpackageloaded{titling}{
\AtBeginEnvironment{titlingpage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}
}{}% titling loaded
}% AtBeginDocument

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

Env titlepage — Sets up a of class titlepage. Provided even for memoir class, since it is used by \maketitle.

```
\DeclareDocumentEnvironment{titlepage}{}
{
\renewrobustcmd{\affiliation}[1]{\\ \InlineClass{affiliation}{##1}}
\LWR@printpendingfootnotes
\LWR@forcenewpage
\BlockClass{titlepage}
}
{
\endBlockClass
\LWR@printpendingfootnotes
}

\end{warpHTML}
```

65.4 Printing the thanks

for HTML & PRINT:

```
\begin{warpall}
```

\printthanks — Forces the \thanks to be printed.

This is necessary in a titlingpage environment when \maketitle was not used.

```
\newcommand*{\printthanks}{\@thanks}
```

```
\end{warpall}
```

65.5 Printing the title, etc. in HTML

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in HTML:

for HTML output:

```
\begin{warpHTML}
```

`\printtitle`

```
\newcommand*{\printtitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

`\LWR@printthetitle` A private version which prints the title without footnotes, used to title each HTML page.

```
\newcommand*{\LWR@printthetitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \thetitle%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

`\printauthor` HTML version.

```
\newcommand*{\printauthor}{
```

The entire author block is contained in a `<div>` named `author`:

```
\begin{BlockClass}{author}
```

`\and` finishes one author and starts the next:

```
\renewcommand{\and}{%
\end{BlockClass}
\begin{BlockClass}{oneauthor}
}
```

Individual authors are contained in a `<div>` named `oneauthor`:

```
\begin{BlockClass}{oneauthor}
\@author
\end{BlockClass}
```

```
\end{BlockClass}
}
```

\printdate

```
\newcommand*{\printdate}{%
\begin{BlockClass}{titledate}
\@date
\end{BlockClass}
}
```

```
\end{warpHTML}
```

65.6 Printing the title, etc. in print form

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in print form:

for PRINT output:

```
\begin{warpprint}
```

\printtitle

```
\newcommand*{\printtitle}{{\Huge\@title}}
```

\printauthor

Print mode.

```
\newcommand*{\printauthor}
    {{\large\begin{tabular}[t]{c}\@author\end{tabular}}}
```

\printdate

```
\newcommand*{\printdate}{{\small\textit{\@date}}}
```

```
\end{warpprint}
```

65.7 \maketitle for HTML output

An HTML of class `titlepage` is used.

`\thanks` are a form of footnotes used in the title page. See section 58 for other kinds of footnotes.

See `\thanksmarkseries{series}`, below, to set the style of the footnote marks.

for HTML output:

```
\begin{warpHTML}
```

```
\@ifclassloaded{memoir}
{
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
}{% not memoir
\if@titlepage
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
\else
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
}
\fi
}% not memoir
```

`\LWR@maketitlesetup` Patches `\thanks` macros.

```
\newcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
\LWR@setfootnoteseries%
\def\@makefnmark{\textsuperscript{\thefootnote}}
```

`\thefootnote` ⇒ `\nameuse`{arabic}{footnote}, or
`\thefootnote` ⇒ `\nameuse`{fnsymbol}{footnote}

Redefine the footnote text:

```
\long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
\textsuperscript{\@thefnmark}~%
```

`\makethanksmark` ⇒ `\thanksfootmark` ⇒ `\tamark` ⇒ `\@thefnmark` ⇒ `\itshape` a (or similar)

Print the text:

```
##1%
}%
}
```

`\@fnsymbol` {⟨*counter*⟩}

Re-defined to use an HTML entity for the double vertical bar symbol. The original definition used `\|` which was not being seen by *pdftotext*.

```
\def\@fnsymbol#1{\ifcase#1\or *\or \HTMLentity{dagger}\or \HTMLentity{Dagger}\or
   \HTMLentity{sect}\or \HTMLentity{para}\or \text{\HTMLunicode{2016}}\or
   **\or \HTMLentity{dagger}\HTMLentity{dagger} \or
   \HTMLentity{Dagger}\HTMLentity{Dagger} \else\@ctrerr\fi}
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage is used for all classes.

```
\begin{titlepage}
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\@thanks
```

Close the HTML titlepage div and cleanup:

```
\end{titlepage}
\setcounter{footnote}{0}%
\global\let\thanks\relax
\global\let\maketitle\relax
\global\let\@maketitle\relax
\global\let\@thanks\@empty
\global\let\@author\@empty
\global\let\@date\@empty
\global\let\@title\@empty
\global\let\title\relax
\global\let\author\relax
\global\let\date\relax
\global\let\and\relax
}
```

\@maketitle HTML mode. Typesets the title, etc.:

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
    \begin{BlockClass}{author}%
```

For IEEEtran class:

```
    \renewcommand*{\cr}{}%
    \renewcommand*{\crcr}{}%
    \renewcommand*{\noalign}{}%

        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }%
        \begin{BlockClass}{oneauthor}%
            \@author%
        \end{BlockClass}%
    \end{BlockClass}%
    \begin{BlockClass}{titledate}%
    \@date%
    \end{BlockClass}%
}
```

\LWR@titlingmaketitle

\maketitle for use inside an HTML titlingpage environment.

```
\newcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\@thanks
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\@thanks
}

\end{warpHTML}
```

65.8 \published and \subtitle

\subtitle and \published

To add \subtitle and \published to the titlepage, load the titling package and use \AddSubtitlePublished in the preamble.

The default lwarp.css has definitions for the published and subtitle classes.

If titling is loaded, \AddSubtitlePublished creates a number of additional macros, and also assigns some of the titling hooks. If titling is not loaded, \AddSubtitlePublished creates null macros.

⚠ titling hooks Do not use \AddSubtitlePublished if the user has patched the titling hooks for some other reason. Portions are marked \warpprintonly to reduce extra tags in HTML. Similarly, BlockClass has no effect in print mode. Thus, the following may be marked warpall.

for HTML & PRINT:
```
\begin{warpall}
```

\AddSubtitlePublished Adds \published and \subtitle, and related.

```
\newcommand*{\AddSubtitlePublished}{%
\@ifpackageloaded{titling}{% yes titling package
    \newcommand{\@published}{}%
    \newcommand{\published}[1]{\gdef\@published{##1}}%
    \renewcommand*{\maketitlehooka}{\printpublished}%
    \newcommand*{\printpublished}{%
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{published}%
        \warpprintonly{\large\itshape}%
        \@published%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
    \newcommand{\@subtitle}{}%
    \newcommand{\subtitle}[1]{\gdef\@subtitle{##1}}%
    \renewcommand*{\maketitlehookb}{\printsubtitle}%
    \newcommand*{\printsubtitle}{%
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{subtitle}%
        \warpprintonly{\Large\itshape}%
        \@subtitle%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
}% yes titling package
{% no titling package
    \newcommand{\published}[1]{}%
    \newcommand*{\printpublished}{}%
    \newcommand{\subtitle}{}%
    \newcommand*{\printsubtitle}%
}% no titling package
}% \AddSubtitlePublished
```

```
\end{warpall}
```

66 Abstract

The following code replaces the LaTeX default, and will itself be replaced later if the abstract package is loaded.

for HTML output:
```
\begin{warpHTML}
```

\abstractname User-redefinable title for the abstract.

Also over-written by the babel package.

```
\providecommand*{\abstractname}{Abstract}
```

Some classes allow an optional name, so it is allowed here.

Env abstract

```
\DeclareDocumentEnvironment{abstract}{O{\abstractname}}
{
\LWR@forcenewpage
\BlockClass{abstract}
\BlockClassSingle{abstracttitle}{#1}
}
{
\endBlockClass
}
```

```
\end{warpHTML}
```

67 Quote and verse

67.1 Attributions

\attribution For use with quote, quotation, verse:

Ex: "A quotation." \attribution{\textsc{Author Name}\\\textsl{Book Title}}

for HTML output:

```
\begin{warpHTML}
\newcommand{\attribution}[1]{%
    \begin{BlockClass}{attribution}
    #1
    \end{BlockClass}
}
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand{\attribution}[1]{
    \begin{flushright}
    \unskip
    #1
    \end{flushright}%
}
\end{warpprint}
```

67.2 Quotes, quotations

for HTML output:

```
\begin{warpHTML}
```

Env quote

```
\renewenvironment*{quote}
{
\LWR@forcenewpage
\LWR@htmlblocktag{blockquote}
}
{\LWR@htmlblocktag{/blockquote}}

\renewenvironment*{quotation}
{
\LWR@forcenewpage
\LWR@htmlblocktag{blockquotation}
}
{\LWR@htmlblocktag{/blockquotation}}

\end{warpHTML}
```

67.3 Verse

When using verse or memoir, always place a \\ after each line.

\attrib

The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

67.3.1 LaTeX core verse environment

for HTML output:

```
\begin{warpHTML}
```

Env verse

```
\renewenvironment{verse}
               {\let\\\newline% lwarp
                \list{}{\itemsep      \z@
                        \itemindent   -1.5em%
                        \listparindent\itemindent
                        \rightmargin  \leftmargin
                        \advance\leftmargin 1.5em}%
                \item\relax}
               {\endlist}

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

67.3.2 verse and memoir

The following lengths are used by verse and memoir. They may be set in either print or HTML output, but are only used in HTML. This allows the user to set \vleftskip and \leftmargini for print output, and optionally select different values for HTML.

Len \HTMLvleftskip

Sets \vleftskip inside a verse environment in HTML.

```
\newlength{\HTMLvleftskip}
\setlength{\HTMLvleftskip}{1em}
```

Len \HTMLleftmargini

Sets \leftmargini inside a verse environment in HTML.

```
\newlength{\HTMLleftmargini}
\setlength{\HTMLleftmargini}{4.5em}

\end{warpall}
```

68 Verbatim and tabbing

for HTML & PRINT:

```
\begin{warpall}
```

Len \VerbatimHTMLWidth

Width to use in HTML Verbatim environment.

This width is used when placing line numbers to the right. Ignored during print output.

```
\newlength{\VerbatimHTMLWidth}
\setlength{\VerbatimHTMLWidth}{4in}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Bool LWR@verbtags

Used to temporarily turn off verbatim tags while doing \verbatiminput in the HTML head.

```
\newbool{LWR@verbtags}
\booltrue{LWR@verbtags}
```

\LWR@atbeginverbatim [⟨*1: style*⟩] {⟨*2: negative* \baselineskip \vspace⟩} {⟨*3: class*⟩}

Encloses a verbatim environment with the given CSS class.

The use of \textquotedbl instead of " improves compatibility with xeCJK.

```
\newcommand*{\LWR@atbeginverbatim}[3][]
{%
```

Avoid excessive space between lines:

```
\setlength{\parskip}{0ex}%
```

Stop generating HTML paragraph tags:

```
\LWR@stoppars%
```

Create a new pre of the given class. The tags may temporarily be turned off for internal use, such as loading the MathJax script.

```
\ifbool{LWR@verbtags}{%
    \LWR@htmltag{pre class=\textquotedbl#3\textquotedbl%
        \ifthenelse{\equal{#1}{}}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
    \LWR@orignewline% pre
    \leavevmode\unskip\LWR@print@vspace*{-#2\baselineskip}%
}{}%
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the CSS for the verse class.

```
\begingroup%
```

```
% \LWR@print@normalsize%
\LWR@origttfamily%
\LWR@print@small%
```

Since inside a <pre>, restore the original list processing:

```
\LWR@restoreoriglists%
```

Turn off babel-french extra space before punctuation:

```
\LWR@FBcancel%
```

Do not produce HTML tags for \hspace inside a verse par. Restore plain LaTeX \hspace functionality:

```
\LWR@select@print@hspace%
}
```

\LWR@afterendverbatim {⟨*negative* \baselineskip \vspace⟩}

Finishes enclosing a verbatim environment.

```
\newcommand*{\LWR@afterendverbatim}[1]{%
\endgroup%
\par%
```

At the end of the environment, close the pre:

```
\ifbool{LWR@verbtags}{%
    \LWR@print@vspace*{-#1\baselineskip}%
    \noindent\LWR@htmltag{/pre}\LWR@orignewline% pre
}{}%
```

Resume regular paragraph handling:

```
\LWR@startpars%
}
```

\verbatiminput {⟨*filename*⟩}

Patch \verbatiminput to add HTML tags:

```
\let\LWRV@origverbatim@input\verbatim@input

\renewcommand{\verbatim@input}[2]{%
\ifbool{LWR@verbtags}{\LWR@forcenewpage}{}%
\LWR@atbeginverbatim{2.5}{Verbatim}%
\LWRV@origverbatim@input{#1}{#2}%
\LWR@afterendverbatim{1.5}%
}
```

Env verbatim

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verbatim.}
\AtBeginEnvironment{verbatim}{%
\LWR@forcenewpage%
\LWR@atbeginverbatim{2.5}{verbatim}%
}
\AfterEndEnvironment{verbatim}{%
    \LWR@afterendverbatim{1}%
}
}
```

Env tabbing The tabbing environment works, except that SVG math and lateximages do not yet work inside the environment.

⚠ math in tabbing If math is used inside tabbing, place tabbing inside a lateximage environment, which will render the entire environment as a single SVG image.

```
\newcommand*{\LWR@HTML@tabbing}{%
\LWR@forcenewpage%
\LWR@atbeginverbatim{3}{tabbing}%
\LWR@print@tabbing%
}

\newcommand*{\LWR@HTML@endtabbing}{%
    \LWR@print@endtabbing%
    \LWR@afterendverbatim{1}%
}

\LWR@formatted{tabbing}
\LWR@formatted{endtabbing}
```

```
\end{warpHTML}
```

69 Theorems

\newtheorem {⟨*text*⟩} [⟨*counter*⟩] -or- [⟨*oldname*⟩] {⟨*text*⟩}

A few minor changes are made to supply HTML tags.

- The entire theorem is placed into a of class theoremcontents.
- The label for each theorem is placed inside a of class theoremlabel.
- The contents are placed inside a of class theoremcontents.

for HTML output:

```
\begin{warpHTML}
```

\@begintheorem {⟨*name*⟩} {⟨*number*⟩}

```
\renewcommand{\@begintheorem}[2]{%
\LWR@forcenewpage
\BlockClass{theoremcontents}
\trivlist
\item[\InlineClass{theoremlabel}{#1\ #2\ }]\itshape
}
```

\@opargbegintheorem {⟨*name*⟩} {⟨*number*⟩} {⟨*oparg*⟩}

```
\renewcommand{\@opargbegintheorem}[3]{%
\LWR@forcenewpage
```

```
\BlockClass{theoremcontents}
\trivlist
\item[\InlineClass{theoremlabel}{#1\ #2\ (#3)\ }]\itshape
}
```

\@endtheorem

```
\renewcommand*{\@endtheorem}{%
\endtrivlist
\endBlockClass% theoremcontents
}
```

```
\end{warpHTML}
```

70 Lists

The environments `itemize`, `enumerate`, and `description` are patched when lwarp is started. These patches support the standard LaTeX environments, as well as those of enumerate, enumitem, and paralist, and at least the French version of babel. Additional patches are done on a package-specific basis.

The LaTeX source for `itemize` and `enumerate` are found in `source2e`, but the source for `description` is found in `article.cls`, etc.

empty item

To have an empty item,use `\mbox{}` or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

```
begin{itemize}
item \mbox{}
    \begin{itemize}
...
    \end{itemize}
item \
    \begin{itemize}
  ...
    \end{itemize}
```

`\makelabel`

While inside a list environment, lwarp nullifies a number of TeX horizontal skip and fill commands, allowing the user to define `\makelabel` for print mode while HTML mode ignores those commands.

⚠ label font

When defining `\makelabel` in a `list` environment, use `\textbf` etc. instead of `\bfseries`.

70.1 List environment

for HTML output:

```
\begin{warpHTML}
```

\LWR@printcloselist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
```

\LWR@printopenlist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
```

\@mklab Removes PDF spacing.

```
\AtBeginDocument{
\def\@mklab#1{%
%     \hfil %
    #1}
\let\makelabel\@mklab
}
```

\@donoparitem Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
\def\@donoparitem{%
  \@noparitemfalse
%   \global\setbox\@labels\hbox{\hskip -\leftmargin
%                                \unhbox\@labels
%                                 \hskip \leftmargin}%
%   \if@minipage\else
%     \@tempskipa\lastskip
%     \vskip -\lastskip
%     \advance\@tempskipa\@outerparskip
%     \advance\@tempskipa -\parskip
%     \vskip\@tempskipa
%   \fi
}
```

\@item Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
\def\LWR@HTML@item[#1]{%
\LWR@traceinfo{@item}
  \if@noparitem
    \@donoparitem
  \else
%     \if@inlabel
%       \indent
        \par
%     \fi
    \ifhmode
%       \unskip\unskip
        \par
```

```
    \fi
    \if@newlist
      \if@nobreak
        \@nbitem
      \else
%         \addpenalty\@beginparpenalty
%         \addvspace\@topsep
%         \addvspace{-\parskip}%
      \fi
    \else
%       \addpenalty\@itempenalty
%       \addvspace\itemsep
    \fi
    \global\@inlabeltrue
  \fi
%   \everypar{%
    \@minipagefalse
    \global\@newlistfalse

%     \if@inlabel
%       \global\@inlabelfalse

%       {\setbox\z@\lastbox
%        \ifvoid\z@
%          \kern-\itemindent
%        \fi}%

%       \box\@labels
%       \penalty\z@
%     \fi

%     \if@nobreak
%       \@nobreakfalse
%       \clubpenalty \@M
%     \else
%       \clubpenalty \@clubpenalty
%       \everypar{}%
%     \fi}%

  \if@noitemarg
    \@noitemargfalse
    \if@nmbrlist

      \refstepcounter\@listctr
    \fi
  \fi


    \makelabel{#1} % extra space
%   \sbox\@tempboxa{\makelabel{#1}%
%   \global\setbox\@labels\hbox{%
%     \unhbox\@labels
%     \hskip \itemindent
%     \hskip -\labelwidth
```

```
%     \hskip -\labelsep
%     \ifdim \wd\@tempboxa >\labelwidth
%       \box\@tempboxa

%     \else
%       \hbox to\labelwidth {\unhbox\@tempboxa}%
%     \fi
%     \hskip \labelsep}%
  \ignorespaces%
}
```

`\@nbitem`

```
\def\@nbitem{%
%   \@tempskipa\@outerparskip
%   \advance\@tempskipa -\parskip
%   \addvspace\@tempskipa
}
```

`\LWR@listitem` [⟨*label*⟩]

Handles `\item` inside a `list`, `itemize`, or `enumerate`.

See `\LWR@openparagraph` where extra `\hspace` is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@listitem}{%
\LWR@stoppars%
\LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printcloselistitem}%
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

`\LWR@nulllistfills` Nullifies various TEX fill commands, in case they are used inside `\makelabel`. Problems are caused when these are nullified all the time.

```
\newcommand*{\LWR@nulllistfills}{%
\renewcommand*{\hss}{}%
\renewcommand*{\llap}[1]{##1}%
\renewcommand*{\rlap}[1]{##1}%
\renewcommand*{\hfil}{}%
\renewcommand*{\hfilneg}{}%
\renewcommand*{\hfill}{}%
}
```

Env `list` {⟨*label*⟩} {⟨*commands*⟩}

```
\newcommand*{\LWR@liststart}{%
\LWR@traceinfo{LWR@liststart}%
\LWR@stoppars%
\LWR@pushoneclose{\LWR@depthlist}{\LWR@printcloselist}%
```

```
\LWR@htmltag{\LWR@printopenlist}\LWR@orignewline%
\LWR@startpars%
\setlength{\topsep}{0pt}%
\setlength{\partopsep}{0pt}%
\setlength{\itemsep}{0pt}%
\setlength{\parsep}{0pt}%
\setlength{\leftmargin}{0pt}%
\setlength{\rightmargin}{0pt}%
\setlength{\listparindent}{0pt}%
\setlength{\itemindent}{0pt}%
\setlength{\labelsep}{1em}%
\LWR@nulllistfills%
}
```

```
\newcommand*{\LWR@listend}{%
\LWR@traceinfo{LWR@listend}%
\LWR@stoppars%
\LWR@closeprevious{\LWR@depthlist}%
\LWR@startpars%
}
```

70.2 Itemize

`\LWR@itemizeitem` [⟨*label*⟩]

Handles `\item` inside an itemize or enumerate.

See `\LWR@openparagraph` where extra `\hspace` is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@itemizeitem}{%
\LWR@stoppars%
\LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printcloselistitem}%
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

Env `itemize` [⟨*options*⟩]

```
\newcommand*{\LWR@itemizestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

70.3 Enumerate

An HTML unordered list is used with customized LaTeX-generated labels.

Env `enumerate` [⟨*options*⟩]

```
\newcommand*{\LWR@enumeratestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

70.4 Description

`\LWR@descitem` [⟨*label*⟩] Handles an `\item` inside a description.

```
\newcommand*{\LWR@descitem}[1][]%
{%
\LWR@stoppars%
\LWR@setlatestname{#1}%
\LWR@startnewdepth{\LWR@depthlistitem}{\LWR@printclosedescitem}%
```

Temporarily disable `\hspace`, which `article.cls`, etc. use per `\item` for `descriptions` only. This causes lwarp to mistakenly place an empty span between HTML list tags.

```
\LWR@select@html@nohspace%
```

Process the original `\item` code:

```
\LWR@origitem[]%
```

Restore `\hspace` for use in the item text:

```
\LWR@select@html@hspace%
```

```
\LWR@htmltag{dt}#1\LWR@htmltag{/dt}%
\LWR@orignewline%
\LWR@htmltag{dd}%
\LWR@startpars%
}
```

Env `description` [⟨*options*⟩]

```
\newcommand*{\LWR@descriptionstart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printclosedescription}
\renewcommand*{\LWR@printopenlist}{dl}
\let\item\LWR@descitem%
\LWR@nulllistfills%
}
```

70.5 Patching the lists

\LWR@patchlists Patches list environments.

\LWR@patchlists remembers \item as defined by whatever packages have been loaded, then patches the itemize, enumerate, and description environments and \item. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\newcommand*{\LWR@patchlists}{%
    \LetLtxMacro\item\LWR@listitem%
    \LetLtxMacro\@item\LWR@HTML@item%
    \renewcommand*{\@trivlist}{%
        \LWR@traceinfo{@trivlist start}%
        \LWR@liststart%
        \LWR@orig@trivlist%
        \LWR@traceinfo{@trivlist done}%
    }%
    \renewcommand*{\trivlist}{%
        \LWR@traceinfo{trivlist}%
        \LWR@origtrivlist%
    }%
    \renewcommand*{\endtrivlist}{%
        \LWR@traceinfo{endtrivlist start}%
        \LWR@origendtrivlist\LWR@listend%
        \LWR@traceinfo{endtrivlist done}%
    }%
    \renewcommand*{\itemize}{%
        \LWR@itemizestart\LWR@origitemize%
    }%
    \renewcommand*{\enumerate}{%
        \LWR@enumeratestart\LWR@origenumerate%
    }%
    \renewcommand*{\description}{%
        \LWR@descriptionstart\LWR@origdescription%
    }%
}
```

\LWR@restoreoriglists Restores the original trivlist environment.

```
\newcommand*{\LWR@restoreoriglists}{%
\LWR@traceinfo{LWR@restoreoriglists}%
\LetLtxMacro\item\LWR@origitem%
\LetLtxMacro\@item\LWR@orig@item%
\let\@trivlist\LWR@orig@trivlist%
\let\trivlist\LWR@origtrivlist%
\let\endtrivlist\LWR@origendtrivlist%
\LetLtxMacro\itemize\LWR@origitemize%
\LetLtxMacro\enditemize\LWR@endorigitemize%
\LetLtxMacro\enumerate\LWR@origenumerate%
\LetLtxMacro\endenumerate\LWR@endorigenumerate%
\LetLtxMacro\description\LWR@origdescription%
\LetLtxMacro\enddescription\LWR@endorigdescription%
\let\@mklab\LWR@orig@mklab%
```

```
\let\makelabel\LWR@origmakelabel%
\let\@donoparitem\LWR@orig@donoparitem%
\let\@nbitem\LWR@orig@nbitem%
}
```

```
\end{warpHTML}
```

71 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax of the LaTeX core and the various tabular-related packages.

71.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, * column specifiers, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include `tabular` and instances of the & character, it may be necessary to make & active before the environment or macro is defined, then restore & to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

⚠ floatrow

This includes before and after defining any macro which used `\ttabbox` from floatrow.

⚠ `tabular` inside another environment

- When creating a new environment which contains a `tabular` environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use `\TabularMacro` just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

⚠ * column specification

- * in a column specification is not used (so far). Repeat the column type the correct number of times.

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

`\multirow`

- In `\multirow` cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the `\multirow` which do not appear in the HTML version.

⚠ `\newcolumntype`

- `\newcolumntype` is ignored; unknown column types are set to `l`.

Rules:

- Doubled `\hlines`, `\midrules`, and vertical rules are supported.

vertical rules

- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

full-width rules

- `\toprule`, `\midrule`, `\bottomrule`, and `\hline` ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

⚠ `\warpprintonly`
⚠ Misplaced `\noalign`

- For `\toprule` and `\bottomrule`, when combined with a `warpprint` or `warpHTML` environment, if a "Misplaced `\noalign`" error occurs, change

```
This & That \endhead
```

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevent to HTML output.

Other:

- tabularx ignores the width, but `X` columns do produce paragraph columns or multicolumns.

`longtable` headings

- For longtable, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

for HTML output:

```
\begin{warpHTML}
```

71.2 Temporary package-related macros

These macros are temporary placeholders for macros defined by various packages. If the relevent package is not loaded, these placeholders are used instead.

71.2.1 arydshln

Emualated by the original LaTeX non-dashed versions.

```
\LetLtxMacro\hdashline\hline
\LetLtxMacro\cdashline\cline
\LetLtxMacro\firsthdashline\hline
\LetLtxMacro\lasthdashline\hline
```

71.3 Token lookahead

Used by `\LWR@futurenonspacelet` to look at the next token.

`\LWR@mynexttoken`

```
\newcommand\LWR@mynexttoken\relax
```

`\futurelet` copies the next token then executes a function to analyze

`\LWR@futurenonspacelet` does the same, but ignores intervening white space

Based on the booktabs style:

`\LWR@futurenonspacelet`

```
\def\LWR@futurenonspacelet#1{\def\LWR@cs{#1}%
\afterassignment\LWR@fnslone\let\nexttoken= }
\def\LWR@fnslone{\expandafter\futurelet\LWR@cs\LWR@fnsltwo}
\def\LWR@fnsltwo{%
```

```
\expandafter\ifx\LWR@cs\@sptoken\let\next=\LWR@fnslthree%
\else\let\next=\nexttoken\fi\next}
\def\LWR@fnslthree{\afterassignment\LWR@fnslone\let\next= }
```

\LWR@getmynexttoken Looks ahead and copies the next token into \LWR@mynexttoken.

```
\newcommand*{\LWR@getmynexttoken}{%
\LWR@traceinfo{LWR@getmynexttoken}%
% nothing must follow this next line
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@tabledatacolumntag
}
```

71.4 Tabular variables

Bool LWR@startedrow True if should print a row tag before this column.

```
\newbool{LWR@startedrow}
\boolfalse{LWR@startedrow}
```

Bool LWR@tabularcelladded True if have added a data cell for this position.

```
\newbool{LWR@tabularcelladded}
\boolfalse{LWR@tabularcelladded}
```

Ctr LWR@hlines Number of \hlines or \midrules above the next row.

```
\newcounter{LWR@hlines}
```

Ctr LWR@hdashedlines Number of arydshln dashed lines above the next row.

```
\newcounter{LWR@hdashedlines}
```

Bool LWR@doingtbrule True if the next row will have a top/bottom rule above it.

```
\newbool{LWR@doingtbrule}
\boolfalse{LWR@doingtbrule}
```

Bool LWR@doingcmidrule True if the next row will have a cmidrule above it.

This is used by \LWR@tabularfinishrow to force a final empty row to create the border for the \cmidrule.

```
\newbool{LWR@doingcmidrule}
\boolfalse{LWR@doingcmidrule}
```

Bool LWR@tableparcell True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

```
\newbool{LWR@tableparcell}
```

Bool LWR@skippingmrowcell

True if are doing an empty \multirow cell, and thus there is no data tag to close.

```
\newbool{LWR@skippingmrowcell}
```

Bool LWR@skippingmcolrowcell

True if are doing an empty \multicolumnrow cell, and thus there is no data tag to close, and do not print @ and ! columns.

```
\newbool{LWR@skippingmcolrowcell}
```

Bool LWR@usedmultirow

Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
\newbool{LWR@usedmultirow}
```

Bool LWR@foundmrowcell

Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
\newbool{LWR@foundmrowcell}
```

Bool LWR@skipatbang

True if just finished a \multicolumn so should not create the trailing @ or ! columns table data cells.

```
\newbool{LWR@skipatbang}
```

Bool LWR@emptyatbang

True if finishing a row and should print empty @ or ! column table data cells.

```
\newbool{LWR@emptyatbang}
```

Bool LWR@intabularmetadata

True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.

```
\newbool{LWR@intabularmetadata}
\boolfalse{LWR@intabularmetadata}
```

Ctr LWR@tabularDepth

Tracks whether & is being used inside a tabular.

```
\newcounter{LWR@tabulardepth}
\setcounter{LWR@tabulardepth}{0}
```

Ctr LWR@tabularpardepth

Tracks whether should look ahead at the next token when encountering a \par while processing tabular contents.

When LWR@tabularpardepth is deeper than LWR@tabulardepth then lwarp has started looking at the contents of the tabular, and thus any \pars encountered must be followed by another token lookahead.

```
\newcounter{LWR@tabularpardepth}
\setcounter{LWR@tabularpardepth}{0}
```

```
\newcommand*{\LWR@colsresult}{}%temp storage for column format results
\newcommand*{\LWR@pposition}{}
\newcommand*{\LWR@pleft}{}
\newcommand*{\LWR@pright}{}
```

LWR@tablecolspec

Holds the parsed column specification, of total width LWR@tabletotalLaTeXcols, not counting @ and ! columns.

Will contain a string such as llrrccpc, exactly one letter per LaTeX table column, without @, !, >, <, or the vertical bar.

\LWR@strresult

Holds the result of Str functions.

```
\providecommand*{\LWR@strresult}{}
\providecommand*{\LWR@strresulttwo}{}
```

\LWR@origcolspec

Holds the original column specs given to tabular.

```
\newcommand*{\LWR@origcolspec}{}
```

Ctr LWR@tablecolspecwidth

Holds the number of tokens in the table columns specification.

This is includes one for each @, !, <, > column, and also one for each of the parameters of p, @, !, <, > columns, and three for each D column.

(This is not the total # of LaTeX columns in the table.)

```
\newcounter{LWR@tablecolspecwidth}
```

Ctr LWR@tablecolspecindex

While parsing the LaTeX table column specification, starts at 1 and is incremented per token of the specification.

```
\newcounter{LWR@tablecolspecindex}
```

Ctr LWR@tableLaTeXcolindex

While producing the table, resets to 1 at the start of the table and also at each end of line, and is incremented by 1 by each ampersand.

```
\newcounter{LWR@tableLaTeXcolindex}
```

Ctr LWR@tabletotalLaTeXcols

While parsing a table column specification, begins at 0 and increments by 1 per LaTeX table column. Eventually holds the final number of LaTeX table columns in each row, not counting @ and ! columns. (In HTML, @ and ! cells become their own columns, but are not included in LWR@tabletotalLaTeXcols.)

```
\newcounter{LWR@tabletotalLaTeXcols}
```

Ctr LWR@tabletotalLaTeXcolsnext

Holds the next LaTeX table column index while parsing, equal to one more than LWR@tabletotalLaTeXcols.

```
\newcounter{LWR@tabletotalLaTeXcolsnext}
```

LWR@colatspec

A data array of specifications for @ columns. The leftmost's index is leftedge, the others are counter values. See section 42.

LWR@colbangspec

A data array of specifications for ! columns. The leftmost's index is leftedge, the others are counter values. See section 42.

LWR@colbeforespec A data array of specifications for > columns.

LWR@colafterspec A data array of specifications for < columns.

LWR@colbarspec A data array of specifications for vertical rules.

71.5 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:
http://tex.stackexchange.com/questions/11638/
where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860

\LWR@instertatbangcols

```
\newcommand*{\LWR@insertatbangcols}{%
\ifbool{LWR@skipatbang}%
{}%
{%
    \LWR@printatbang{at}{\arabic{LWR@tableLaTeXcolindex}}%
    \LWR@printatbang{bang}{\arabic{LWR@tableLaTeXcolindex}}%
}%
}
```

\LWR@closetabledatacell If LWR@skippingmrowcell or LWR@skippingmcolrowcell then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
\newcommand*{\LWR@closetabledatacell}{%
\LWR@stoppars%
\global\booltrue{LWR@intabularmetadata}%
\ifbool{LWR@exitingtabular}{}%
{% not exiting tabular
    \ifboolexpr{bool{LWR@skippingmrowcell} or bool{LWR@skippingmcolrowcell}}%
    {%
```

If not skipping a \multicolumnrow cell, insert the @ and ! columns after this non-existant column.

```
        \ifbool{LWR@skippingmcolrowcell}%
            {}%
            {\LWR@insertatbangcols}%
    }%
    {% not skippingmrowcell
```

Insert any < then any @ and ! column contents, unless muted for the \bottomrule or a \multicolumn:

```
        \unskip%
        \ifboolexpr{%
            bool{LWR@tabularmutemods} or
            bool{LWR@skipatbang} or
            bool{LWR@emptyatbang}
```

```
        }%
        {}%
        {\LWR@getexparray{LWR@colafterspec}{\arabic{LWR@tableLaTeXcolindex}}}%
```

Close paragraphs:

```
        \ifbool{LWR@tableparcell}{\LWR@stoppars}{}%
        \global\boolfalse{LWR@tableparcell}%
```

Close the table data cell.

Close any color s.

```
        \whileboolexpr{test {\ifnumcomp{\value{LWR@cellcolordepth}}{>}{0}}}{%
            \LWR@htmltag{/div}\LWR@orignewline%
            \addtocounter{LWR@cellcolordepth}{-1}%
        }%
```

Skip the @ and ! cells if are closing a multicolumn cell.

```
        \leavevmode\unskip\LWR@htmltag{/td}\LWR@orignewline%
        \global\booltrue{LWR@tabularcelladded}%
        \LWR@insertatbangcols%
    }% not skipping mrowcell
}% not exiting tabular
\global\boolfalse{LWR@skippingmrowcell}%
\global\boolfalse{LWR@skippingmcolrowcell}%
\global\boolfalse{LWR@skipatbang}%
```

Color control. Column is set by >{} for each cell, so it must be cleared here.

```
\gdef\LWR@cellHTMLcolor{}
\gdef\LWR@columnHTMLcolor{}
\setcounter{LWR@cellcolordepth}{0}
}
```

When not used inside a tabular, & performs its original function as recorded here (with catcode 4).

```
\let\LWR@origampmacro&
```

```
\end{warpHTML}
```

71.5.1 Handling &

for HTML output:

```
\begin{warpHTML}
```

& Will behave depending on whether it is being used inside tabular.

& is redefined to test whether it is inside a tabular environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```
\newcommand*{\LWR@tabularampersand}{%
\LWR@traceinfo{LWR@tabularampersand}%
\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}%
{%
```

If not skipping a multirow cell, close the current data cell.

```
    \unskip%
    \LWR@closetabledatacell%
```

Move to the next column.

```
    \addtocounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
    \global\boolfalse{LWR@tabularcelladded}%
```

Look at the next token to decide multi or single column data tag.

```
    \LWR@getmynexttoken%
}%
```

If not inside a tabular, performs the original action:

```
{\LWR@origampmacro}%
}
```

& is left with its original catcode for now.

tikz package seems to require & be left alone until after tikz has been loaded. Also, cleveref uses the ampersand in one of its options.

& is made active inside a `tabular`.

& is left alone when in math alignments.

71.5.2 Filling an unfinished row

`\LWR@tabularfinishrow` Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
\newcommand*{\LWR@tabularfinishrow}{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
\ifboolexpr{%
    not bool {LWR@exitingtabular} or%
    bool{LWR@doingtbrule} or%
```

```
    bool{LWR@doingcmidrule} or%
    test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
    test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
    bool{LWR@startedrow}%
}{%
```

To temporarily turn off `LWR@exitingtabular` so that table data tags will still be generated:

If generating a final row for the `\bottomrule` borders, turn off the `@`, `!`, <, and > column output:

```
\ifbool{LWR@exitingtabular}{%
    \global\booltrue{LWR@tabularmutemods}%
}{%
    \global\boolfalse{LWR@tabularmutemods}%
}%
```

Locally reenable the table data tags until finished with the final row:

```
\global\boolfalse{LWR@exitingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
\whileboolexpr{%
    test {
      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}
    } or %
    (%
        bool{LWR@intabularmetadata} and%
        not bool{LWR@tabularcelladded} and%
        test {
        \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}
        }%
    )%
}%
{%
    \LWR@tabledatasinglecolumntag%
```

The following is essentially `\LWR@tabularampersand` with `LWR@emptyatbang` added to empty the following cells:

```
    \LWR@closetabledatacell%
    \addtocounter{LWR@tableLaTeXcolindex}{1}%
    \global\boolfalse{LWR@tabularcelladded}%
    \global\booltrue{LWR@emptyatbang}%
```

Starts the next cell:

```
  \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}%
        {\LWR@getmynexttoken}%
        {}%
}%
```

Reenable the original LWR@exitingtabular to close the entire table:

```
\ifbool{LWR@tabularmutemods}{%
    \global\booltrue{LWR@exitingtabular}%
}{%
    \global\boolfalse{LWR@exitingtabular}%
}%
\global\boolfalse{LWR@tabularmutemods}%

\global\boolfalse{LWR@emptyatbang}%
}{}% ifboolexpr
}
```

71.6 Handling \\

Inside tabular, \\ is redefined to \LWR@tabularendofline

Throws away options \\[dim] or *

\LWR@tabularendofline

```
\NewDocumentCommand{\LWR@tabularendofline}{s o}{%
```

Finish the row:

```
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}%
    {\LWR@tabularfinishrow}%
    {\LWR@closetabledatacell}%
\LWR@htmltag{/tr}\LWR@orignewline%
```

xcolor row color support:

```
\@rowc@lors%
```

No longer inside a data cell:

```
\global\booltrue{LWR@intabularmetadata}%
```

Not yet started a table row:

```
\global\boolfalse{LWR@startedrow}%
```

Additional setup:

```
\setcounter{LWR@hlines}{0}%
\setcounter{LWR@hdashedlines}{0}%
\global\boolfalse{LWR@doingtbrule}%
\global\boolfalse{LWR@doingcmidrule}%
\LWR@clearmidrules%
\gdef\LWR@rowHTMLcolor{}%
```

Start at first column:

```
\setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
\global\boolfalse{LWR@tabularcelladded}%
```

Allow TEX to flush the pending paragraph. Not doing so causes a slowdown for very large tables.

```
\LWR@stoppars
\LWR@origpar
```

Look at the next token to decide between single column data tag or a special case:

```
\LWR@getmynexttoken%
}
```

71.7 Looking ahead in the column specifications

`\LWR@columnspeclookahead` {⟨*offset*⟩}

Looks `offset` tokens ahead in the column specification, setting `\LWR@strresulttwo`.

The `w` column alignment will be seen as a single unit such as `{c}`.

```
\newcommand*{\LWR@columnspeclookahead}[1]{%
\setcounter{LWR@tempcountone}{\value{LWR@tablecolspecindex}}%
\addtocounter{LWR@tempcountone}{#1}%
\fullexpandarg%
\StrChar{\LWR@origcolspec}{\arabic{LWR@tempcountone}}[\LWR@strresulttwo]%
```

Get the contents of the first group in `\LWR@strresulttwo`:

```
\exploregroups%
\StrChar{\LWR@strresulttwo}{1}[\LWR@strresulttwo]%
\noexploregroups%
}
```

71.8 Parsing @, >, <, !, bar columns

Holds the parsed argument for `@`, >, <, or `!` columns:

```
\newcommand*{\LWR@colparameter}{}
```

`\LWR@parseatcolumn` Handles `@{text}` columns.

```
\newcommand*{\LWR@parseatcolumn}{%
```

Move to the next token after the '@':

```
\LWR@traceinfo{at column}%
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
\LWR@traceinfo{about to read the next token:}%
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@traceinfo{have now read the next token}%
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \LWR@traceinfo{at the left edge}%
    \LWR@setexparray{LWR@colatspec}{leftedge}{\LWR@colparameter}%
    \LWR@traceinfo{at the left edge: %
    \LWR@getexparray{LWR@colatspec}{leftedge}}%
}%
{% not at the left edge:
    \LWR@traceinfo{not at the left edge}%
    \LWR@setexparray{LWR@colatspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
    \LWR@traceinfo{at \arabic{LWR@tabletotalLaTeXcols}: %
    \LWR@getexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcols}}}%
}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsebangcolumn Handles !{text} columns.

```
\newcommand*{\LWR@parsebangcolumn}{%
```

Move to the next token after the '!':

```
\LWR@traceinfo{bang column}%
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
\LWR@traceinfo{about to read the next token:}%
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@traceinfo{have now read the next token}%
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \LWR@traceinfo{at the left edge}%
    \LWR@setexparray{LWR@colbangspec}{leftedge}{\LWR@colparameter}%
}%
{% not at the left edge:
    \LWR@traceinfo{not at the left edge}%
    \LWR@setexparray{LWR@colbangspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
    \LWR@traceinfo{bang \arabic{LWR@tabletotalLaTeXcols}: \LWR@colparameter!}%
}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@parsebeforecolumn` Handles `>{text}` columns.

```
\newcommand*{\LWR@parsebeforecolumn}{%
```

Move to the next token after the '>':

```
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into `\LWR@colparameter`:

```
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
\fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
\LWR@setexparray{LWR@colbeforespec}%
    {\arabic{LWR@tabletotalLaTeXcolsnext}}{\LWR@colparameter}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@parseaftercolumn` Handles `<{text}` columns.

```
\newcommand*{\LWR@parseaftercolumn}{%
```

Move to the next token after the '<':

```
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into `\LWR@colparameter`:

```
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@setexparray{LWR@colafterspec}%
    {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsebarcolumn Handles vertical rules.

```
\newcommand*{\LWR@parsebarcolumn}{%
\LWR@traceinfo{LWR@parsebarcolumn}%
```

Remember the bar at this position:

```
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
    \ifdefstring{\LWR@tempone}{tvertbarl}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldouble}}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarl}}%
}%
{% not at the left edge:
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarr}%
    {%
        \LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdouble}%
    }%
    {%
        \LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarr}%
    }%
}%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsecoloncolumn Handles vertical rules.

```
\newcommand*{\LWR@parsecoloncolumn}{%
\LWR@traceinfo{LWR@parsecoloncolumn}%
```

Remember the bar at this position:

```
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
    \ifdefstring{\LWR@tempone}{tvertbarldash}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldoubledash}}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldash}}%
}%
```

```
{% not at the left edge:
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarrdash}%
    {\LWR@setexparray{LWR@colbarspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdoubledash}}%
    {\LWR@setexparray{LWR@colbarspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdash}}%
}%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsesemicoloncolumn Handles vertical rules.

```
\newcommand*{\LWR@parsesemicoloncolumn}{%
```

Treat ; as a : column:

```
\LWR@parsecoloncolumn%
```

Skip the following width token:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}
```

71.9 Parsing 'l', 'c', or 'r' columns

\LWR@parsenormalcolumn {⟨*thiscolumn*⟩}

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

```
\newcommand*{\LWR@parsenormalcolumn}[1]{%
\addtocounter{LWR@tabletotalLaTeXcols}{1}%
\addtocounter{LWR@tabletotalLaTeXcolsnext}{1}%
```

```
\LWR@setexparray{LWR@tablecolspec}{\arabic{LWR@tabletotalLaTeXcols}}{#1}%
```

```
\LWR@traceinfo{normal column \arabic{LWR@tabletotalLaTeXcols}: #1}%
\LWR@setexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbangspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbeforespec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colafterspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\global\booltrue{LWR@validtablecol}%
}
```

71.10 Parsing ‘p’, ‘m’, or ‘b’ columns

\LWR@parsepcolumn {⟨*thiscolumn*⟩} The width will be ignored.

```
\newcommand*{\LWR@parsepcolumn}[1]{%
```

Converts to the given column type:

```
\LWR@parsenormalcolumn{#1}%
```

Skips the following width token:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}
```

71.11 Parsing ‘w’ columns

\LWR@parsewcolumn The width will be ignored.

```
\newcommand*{\LWR@parsewcolumn}{%
```

```
\LWR@columnspeclookahead{1}%
\expandafter\LWR@parsenormalcolumn\expandafter{\LWR@strresulttwo}%
```

Skips the following width and alignment tokens:

```
\addtocounter{LWR@tablecolspecindex}{2}%
}
```

71.12 Parsing ’*’ columns

\LWR@parsestarcolumn

```
\newcommand*{\LWR@parsestarcolumn}{%
    \PackageError{lwarp}%
        {%
            The tabular star column specifier\MessageBreak
            *{xx}{yy}\MessageBreak
            is not yet supported by lwarp%
        }%
        {Convert *{xx}{yy} to xx copies of yy.}%
    \addtocounter{LWR@tablecolspecindex}{2}%
}
```

Table 10: Tabular baseline

l	p	m	b	r
			bot	
		mid	bot	
l	par	mid	bot	r
	par	mid		
	par			

71.13 Parsing 'D' columns

From the dcolumn package.

`\LWR@parseDcolumn` {⟨*thiscolumn*⟩} The three parameters will be ignored.

```
\newcommand*{\LWR@parseDcolumn}[1]{%
```

Converts to the given column type.

```
\LWR@parsenormalcolumn{#1}%
```

Skips the following three parameters.

```
\addtocounter{LWR@tablecolspecindex}{3}%
}
```

71.14 Parsing the column specifications

⚠ tabular baselines HTML CSS cannot exactly match the LaTeX concept of a baseline for a table row. Table 10 shows the LaTeX results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the p column specification in table 11 for details.

Table 11 describes how each kind of column is converted to HTML.

Bool `LWR@validtablecol` True if found a valid table column type.

```
\newbool{LWR@validtablecol}
```

Bool `LWR@opttablecol` True if found a table column optional argument.

```
\newbool{LWR@opttablecol}
```

`\LWR@parsetablecols` {⟨*colspecs*⟩}

Scans the column specification left to right.

Table 11: Tabular HTML column conversions

l, r, c: Converted to table cells without paragraph tags.
Uses CSS `vertical-align:middle` so that top or bottom-aligned cells may go above or below this cell.

p: Converted to table cells with paragraph tags. Ref: Table 10, LaTeX places the top line of a parbox aligned with the rest of the text line, so CSS `vertical-align:bottom` is used to have the HTML result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the HTML conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the CSS may be desired, changing `td.tdp`, `td.tdP`, `td.tdprule`, and `td.tdPrule` to `vertical-align: middle`. Another possibility is to change L,R,C, and P to `vertical-align: top` and not worry about the alignment of B and M cells or trying to approximate LaTeX baselines.

m: With paragraph tags, CSS `vertical-align:middle`.

b: With paragraph tags, CSS `vertical-align:top` so that the bottom of the text is closest to the middle of the text line.

P, M, B: Horizontally-centered versions.

S: Converted to 'r'. Ignores optional argument. From the siunitx package.

D: Converted to 'c'. From the dcolumn package.

@, !, >, <: One each, in that order.

|: Vertical rule.

Unknown: Converted to 'l'.

`\newcolumn`: Currently treated as unknown.

Builds \LWR@tablecolspec with the final specification, one LaTeX column per entry. The final number of LaTeX columns in each row is stored in LWR@tabletotalLaTeXcols, which is the number of & and \\ in each line, but which does not include @, !, <, > specifications in the count.

```
\newcommand*{\LWR@parsetablecols}[1]{%
\LWR@traceinfo{LWR@parsetablecols}%
```

Remember the original supplied column spec:

```
\renewcommand*{\LWR@origcolspec}{#1}%
```

Remove spaces:

```
\expandarg%
\StrSubstitute{\LWR@origcolspec}{ }{}[\LWR@origcolspec]%
```

The parsed column spec data array, LWR@tablecolspec, will be overwritten with new values.

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```
\setcounter{LWR@tabletotalLaTeXcols}{0}%
\setcounter{LWR@tabletotalLaTeXcolsnext}{1}%
\LWR@setexparray{LWR@colatspec}{leftedge}{}%
\LWR@setexparray{LWR@colatspec}{1}{}%
\LWR@setexparray{LWR@colatspec}{2}{}%
\LWR@setexparray{LWR@colatspec}{3}{}%
\LWR@setexparray{LWR@colbangspec}{leftedge}{}%
\LWR@setexparray{LWR@colbangspec}{1}{}%
\LWR@setexparray{LWR@colbangspec}{2}{}%
\LWR@setexparray{LWR@colbangspec}{3}{}%
\LWR@setexparray{LWR@colbeforespec}{1}{}%
\LWR@setexparray{LWR@colbeforespec}{2}{}%
\LWR@setexparray{LWR@colbeforespec}{3}{}%
\LWR@setexparray{LWR@colafterspec}{1}{}%
\LWR@setexparray{LWR@colafterspec}{2}{}%
\LWR@setexparray{LWR@colafterspec}{3}{}%
\LWR@setexparray{LWR@colbarspec}{leftedge}{}%
\LWR@setexparray{LWR@colbarspec}{1}{}%
\LWR@setexparray{LWR@colbarspec}{2}{}%
\LWR@setexparray{LWR@colbarspec}{3}{}%
```

Starting at the first column specification:

```
\setcounter{LWR@tablecolspecindex}{1}%
```

Place the colspecs string length into \LWR@strresult, and remember the number of characters in the column specification:

```
\expandarg%
\StrLen{\LWR@origcolspec}[\LWR@strresult]%
```

```
\fullexpandarg%
\LWR@traceinfo{original column spec length: \LWR@strresult}%
\setcounter{LWR@tablecolspecwidth}{\LWR@strresult}%
```

Haven't seen any optional arguments so far

```
\global\boolfalse{LWR@opttablecol}%
```

Scan through the column specifications:

```
\whileboolexpr{%
    not test{%
        \ifnumcomp{\value{LWR@tablecolspecindex}}{>}%
            {\value{LWR@tablecolspecwidth}}%
    }%
}%
{%
```

Place the next single-character column type into `\LWR@strresult`:

```
\expandarg%
\StrChar{\LWR@origcolspec}{\arabic{LWR@tablecolspecindex}}[\LWR@strresult]%
\LWR@traceinfo{position \arabic{LWR@tablecolspecindex}: \LWR@strresult}%
\fullexpandarg%
```

Not yet found a valid column type:

```
\global\boolfalse{LWR@validtablecol}%
```

Skip over any optional arguments, such as siunitx `S` column:

```
\IfStrEq{\LWR@strresult}{[}{\global\booltrue{LWR@opttablecol}}{}%
```

Throw away anything found inside the optional argument:

```
\ifbool{LWR@opttablecol}%
{}% inside an optional argument
{% not an optional tabular argument
```

Not inside an optional argument, so consider the column type:

```
\IfStrEq{\LWR@strresult}{l}{\LWR@parsenormalcolumn{l}}{}%
\IfStrEq{\LWR@strresult}{c}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{r}{\LWR@parsenormalcolumn{r}}{}%
\IfStrEq{\LWR@strresult}{L}{\LWR@parsenormalcolumn{l}}{}%
\IfStrEq{\LWR@strresult}{C}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{R}{\LWR@parsenormalcolumn{r}}{}%
\IfStrEq{\LWR@strresult}{J}{\LWR@parsenormalcolumn{l}}{}%

\IfStrEq{\LWR@strresult}{S}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{s}{\LWR@parsenormalcolumn{c}}{}%

\IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@parseatcolumn}{}%
```

```
\IfStrEq{\LWR@strresult}{!}{\LWR@parsebangcolumn}{}%
\IfStrEq{\LWR@strresult}{>}{\LWR@parsebeforecolumn}{}%
\IfStrEq{\LWR@strresult}{<}{\LWR@parseaftercolumn}{}%
\IfStrEq{\LWR@strresult}{|}{\LWR@parsebarcolumn}{}%
\IfStrEq{\LWR@strresult}{:}{\LWR@parsecoloncolumn}{}%
\IfStrEq{\LWR@strresult}{;}{\LWR@parsesemicoloncolumn}{}%
```

```
\IfStrEq{\LWR@strresult}{p}{\LWR@parsepcolumn{p}}{}%
\IfStrEq{\LWR@strresult}{m}{\LWR@parsepcolumn{m}}{}%
\IfStrEq{\LWR@strresult}{b}{\LWR@parsepcolumn{b}}{}%
```

```
\IfStrEq{\LWR@strresult}{w}{\LWR@parsewcolumn}{}%
\IfStrEq{\LWR@strresult}{W}{\LWR@parsewcolumn}{}%
```

Error if found a star column:

```
\IfStrEq{\LWR@strresult}{*}{\LWR@parsestarcolumn}{}%
```

From the dcolumn package:

```
\IfStrEq{\LWR@strresult}{D}{\LWR@parseDcolumn{c}}{}%
```

From the tabularx package. X column has no parameter, but will be given paragraph tags.

```
\IfStrEq{\LWR@strresult}{X}{\LWR@parsenormalcolumn{X}}{}%
```

Many people define centered versions “P”, “M”, and “B”:

```
\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}
```

```
\IfStrEq{\LWR@strresult}{P}{\LWR@parsepcolumn{P}}{}%
\IfStrEq{\LWR@strresult}{M}{\LWR@parsepcolumn{M}}{}%
\IfStrEq{\LWR@strresult}{B}{\LWR@parsepcolumn{B}}{}%
```

If this column was an invalid column type, convert it to an l column:

```
\ifbool{LWR@validtablecol}{}{%
    \LWR@traceinfo{invalid column type: \LWR@strresult}%
    \LWR@parsenormalcolumn{l}%
}%
}% not an optional column argument
```

If read the closing bracket, no longer inside the optional argument:

```
\IfStrEq{\LWR@strresult}{]}{\global\boolfalse{LWR@opttablecol}}{}%
```

Move to the next character:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}% whiledo
}%
```

71.15 colortbl and xparse tabular color support

These macros provide a minimal emulation of some colortbl macros which might appear between table cells. If colortbl is loaded, these macros will be replaced with functional versions.

For each of the HTML colors below, the text for the HTML color is set if requested, but the macro is empty if none has been set.

`\rownum` Reserve a counter register.

```
\@ifundefined{rownum}{\newcount\rownum}{}
```

`\@rowcolors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowcolors}{}
```

`\@rowc@lors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowc@lors}{}
```

`\LWR@xcolorrowHTMLcolor` Emulated xcolor row color.

```
\newcommand*{\LWR@xcolorrowHTMLcolor}{}
```

`\LWR@columnHTMLcolor` HTMLstyle code for the column color.

```
\def\LWR@columnHTMLcolor{}
```

`\LWR@rowHTMLcolor` HTMLstyle code for the row color.

```
\def\LWR@rowHTMLcolor{}
```

`\LWR@cellHTMLcolor` HTMLstyle code for the cell color.

```
\def\LWR@cellHTMLcolor{}
```

`\LWR@ruleHTMLcolor` HTMLstyle code for the cell color.

```
\newcommand*{\LWR@ruleHTMLcolor}{}
```

\rowcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩] Print version. The HTML version is in lwarp-colortbl. Used before starting a tabular data cell, thus \LWR@getmynexttoken.

```
\newcommand*{\rowcolor}{\LWR@getmynexttoken}%
```

\arrayrulecolor [⟨*model*⟩] {⟨*color*⟩}

\arrayrulecolornexttoken [⟨*model*⟩] {⟨*color*⟩}

Print versions for use outside and inside a tabular:

```
\newcommand{\arrayrulecolor}[2][named]{}
\newcommand{\arrayrulecolornexttoken}[2][named]{\LWR@getmynexttoken}
```

\doublerulesepcolor [⟨*model*⟩] {⟨*color*⟩}

\doublerulesepcolornexttoken [⟨*model*⟩] {⟨*color*⟩}

Print versions for use inside and outside a tabular:

```
\newcommand{\doublerulesepcolor}[2][named]{}
\newcommand{\doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}
```

71.16 Starting a new row

\LWR@maybenewtablerow If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for hline or tbrule if necessary.

```
\newcommand*{\LWR@maybenewtablerow}
{%
\ifbool{LWR@startedrow}%
{}% started the row
{% not started the row
```

Remember that now have started the row:

```
    \global\booltrue{LWR@startedrow}%
```

Create the row tag, with a class if necessary.

```
    \global\booltrue{LWR@intabularmetadata}%
    \ifboolexpr{%
        test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
        test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}}%
    }%
    {%
        \LWR@htmltag{tr class="hline" }%
        \LWR@orignewline%
    }%
```

```
    {% not doing hline
        \ifbool{LWR@doingtbrule}%
        {%
            \ifdefvoid{\LWR@ruleHTMLcolor}{%
                \LWR@htmltag{tr class="tbrule"}%
            }{%
                \LWR@htmltag{%
                    tr class="tbrule" % space
                    style="border-top: 1px solid % space
                        \LWR@origpound\LWR@ruleHTMLcolor "%
                }%
            }%
            \LWR@orignewline%
        }%
        {\LWR@htmltag{tr}\LWR@orignewline}%
    }% end of not doing hline
}% end of not started the row
}
```

71.17 Printing vertical bar tags

\LWR@printbartag {⟨*index*⟩}

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```
\newcommand*{\LWR@printbartag}[1]{%
\LWR@traceinfo{LWR@printbartag !#1!}%
\ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
{}% muting or empty
{% not muting
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{#1}}%
    \ifdefempty{\LWR@tempone}{}{ \LWR@tempone}%
}% not muting
\LWR@traceinfo{LWR@printbartag done}%
}
```

71.18 Printing at or bang tags

\LWR@printatbang {⟨*at -or- bang*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@printatbang}[2]{%
```

Fetch the column at or bang spec:

```
\xdef\LWR@atbangspec{\LWR@getexparray{LWR@col#1spec}{#2}}%
\LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}%
```

Only generate if is not empty;

```
\ifdefempty{\LWR@atbangspec}%
{}%
{% not empty
    \LWR@htmltag{%
        td class="td#1%
        \LWR@subaddcmidruletrim{}{}%
        \LWR@printbartag{#2}%
        "%
        \LWR@tdstartstyles%
        \LWR@addcmidrulewidth%
        \LWR@addcdashline%
        \LWR@addtabularrulecolors%
        \LWR@tdendstyles%
    }%
```

Create an empty cell if muting for the \bottomrule:

```
    \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
    {}%
    {\LWR@atbangspec}%
%
    \LWR@htmltag{/td}\LWR@orignewline%
    \global\booltrue{LWR@tabularcelladded}%
}% not empty
}%
```

\LWR@addleftmostbartag

```
\newcommand*{\LWR@addleftmostbartag}{%
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}{%
    \LWR@printbartag{leftedge}%
}{}%
}
```

\LWR@tabularleftedge

```
\newcommand*{\LWR@tabularleftedge}{%
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}%
{%
    \LWR@printatbang{at}{leftedge}%
    \LWR@printatbang{bang}{leftedge}%
}% left edge
{}% not left edge
}
```

71.19 Data opening tag

\LWR@thiscolspec Temporary storage.

```
\newcommand*{\LWR@thiscolspec}{}
```

\LWR@tabledatasinglecolumntag Print a table data opening tag with style for alignment and color.

```
\newcommand*{\LWR@tabledatasinglecolumntag}%
{%
\LWR@traceinfo{LWR@tabledatasinglecolumntag}%
\LWR@maybenewtablerow%
```

Don't start a new paragraph tag if have already started one:

```
\ifbool{LWR@intabularmetadata}%
{%
```

If have found the end of tabular command, do not create the next data cell:

```
    \ifbool{LWR@exitingtabular}{}%
    {% not exiting tabular
```

Print the @ and ! contents before first column:

```
        \LWR@tabularleftedge%
```

Fetch the current column's alignment character into \LWR@strresult:

```
        \xdef\LWR@strresult{%
          \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
```

print the start of a new table data cell:

```
\LWR@traceinfo{LWR@tabledatasinglecolumntag: about to print td tag}%
        \LWR@htmltag{td class="td%
```

append this column's spec:

```
        \LWR@strresult%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add vertical bar tags.

```
        \LWR@addcmidruletrim%
        \LWR@addleftmostbartag%
        \LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
        "%
```

Add styles for rules, alignment:

```
        \LWR@tdstartstyles%
        \LWR@addcmidrulewidth%
        \LWR@addcdashline%

        \xdef\LWR@thiscolspec{%
          \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
```

```
        }%
        \LWR@addformatwpalignment{\LWR@thiscolspec}%
```

Add styles for cell and rule colors:

```
        \LWR@addtabularrowcolor%
        \LWR@addtabularrulecolors%
```

```
        \LWR@tdendstyles%
        }% HTML td
        \LWR@traceinfo{LWR@tabledatasinglecolumntag: done printing td tag}%
```

If this is a p, m, b, or X column, allow paragraphs:

```
        \ifboolexpr{%
            test{ \ifdefstring{\LWR@strresult}{p} } or
            test{ \ifdefstring{\LWR@strresult}{m} } or
            test{ \ifdefstring{\LWR@strresult}{b} } or
            test{ \ifdefstring{\LWR@strresult}{P} } or
            test{ \ifdefstring{\LWR@strresult}{M} } or
            test{ \ifdefstring{\LWR@strresult}{B} } or
            test{ \ifdefstring{\LWR@strresult}{X} }
        }%
        {% allow pars
          \LWR@traceinfo{LWR@tabledatasinglecolumntag: about to LWR@startpars}%
            \global\booltrue{LWR@tableparcell}%
            \LWR@startpars%
         \LWR@traceinfo{LWR@tabledatasinglecolumntag: done with LWR@startpars}%
        }% allow pars
        {}% no pars
```

Print the > contents unless muted for the \bottomrule:

```
        \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
        {}%
        {%
         \LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
        \global\boolfalse{LWR@intabularmetadata}%
    }% not exiting tabular
}{}% in tabular metadata
\LWR@traceinfo{LWR@tabledatasinglecolumntag: done}%
}%
```

71.20 Midrules

LWR@midrules

LWR@midrules is a data array (section 42) of columns each containing a non-zero width if a midrule should be created for this column.

LWR@trimlrules

LWR@trimlrules is a data array (section 42) of columns containing l if a midrule should be left trimmed for each column.

LWR@trimrrules — LWR@trimrrules is a data array (section 42) of columns containing r if a midrule should be right trimmed for each column.

LWR@cdashlines — LWR@cdashlines is a data array (section 42) of columns each containing a Y if an arydshln package "cdashed line" should be created for this column.

Ctr LWR@midrulecounter — Indexes across the LWR@midrules and LWR@trim<l/r>rules data arrays.

```
\newcounter{LWR@midrulecounter}
```

Len \LWR@heavyrulewidth — The default width of the rule.

```
\newlength{\LWR@heavyrulewidth}
\setlength{\LWR@heavyrulewidth}{.08em}
```

Len \LWR@lightrulewidth — The default width of the rule.

```
\newlength{\LWR@lightrulewidth}
\setlength{\LWR@lightrulewidth}{.05em}
```

Len \LWR@cmidrulewidth — The default width of the rule.

```
\newlength{\LWR@cmidrulewidth}
\setlength{\LWR@cmidrulewidth}{.03em}
```

Len \LWR@thiscmidrulewidth — The width of the next rule, defaulting to \LWR@cmidrulewidth.

If not \LWR@cmidrulewidth, a style will be used to generate the custom width.

Assigned from the LWR@midrules array.

```
\newlength{\LWR@thiscmidrulewidth}
\setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}
```

\LWR@clearmidrules — Start new midrules. Called at beginning of tabular and also at \\.

Clears all LWR@midrules and LWR@trimrules markers for this line.

```
\newcommand*{\LWR@clearmidrules}
{%
\setcounter{LWR@midrulecounter}{1}%
\whileboolexpr{%
    not test{%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}%
            {\value{LWR@tabletotalLaTeXcols}}%
    }%
}%
{%
    \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{0pt}%
    \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
    \LWR@setexparray{LWR@trimlrules}{\arabic{LWR@midrulecounter}}{}%
    \LWR@setexparray{LWR@trimrrules}{\arabic{LWR@midrulecounter}}{}%
    \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{N}%
    \addtocounter{LWR@midrulecounter}{1}%
```

```
}%
}
```

\LWR@subcmidrule {⟨*width*⟩} {⟨*trim*⟩} {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks LWR@midrules data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcmidrule}[4]{%
\setcounter{LWR@midrulecounter}{#3}%
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}{#4}%
    }%
}%
{%
    \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{#1}%
    \addtocounter{LWR@midrulecounter}{1}%
}% whiledo
\IfSubStr{#2}{l}{\LWR@setexparray{LWR@trimlrules}{#3}{l}}{}%
\IfSubStr{#2}{r}{\LWR@setexparray{LWR@trimrrules}{#4}{r}}{}%
\global\booltrue{LWR@doingcmidrule}%
}
```

\LWR@docmidrule [⟨*width*⟩] (⟨*trim*⟩) {⟨*leftcolumn-rightcolumn*⟩}

Marks LWR@midrules array elements to be a non-zero width from left to right columns. Also marks trimming for the L and/or R columns.

```
\NewDocumentCommand{\LWR@docmidrule}
    {O{\LWR@cmidrulewidth} D(){} >{\SplitArgument{1}{-}}m}
    {\LWR@subcmidrule{#1}{#2}#3}
```

\LWR@subcdashline {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks LWR@cdashlines data array elements to be Y from left to right columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcdashline}[2]{%
\setcounter{LWR@midrulecounter}{#1}%
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}{#2}%
    }%
}%
{%
    \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{Y}%
    \addtocounter{LWR@midrulecounter}{1}%
```

```
}% whiledo
\global\booltrue{LWR@doingcmidrule}%
}
```

\LWR@docdashline {⟨*leftcolumn-rightcolumn*⟩}

Marks LWR@cdashlines data array elements to be Y from left to right columns.

```
\NewDocumentCommand{\LWR@docdashline}
    {>{\SplitArgument{1}{-}}m}%
    {%
        \LWR@subcdashline#1%
    }
```

Used to compute margins, tabular trims, column offsets:

```
\newlength{\LWR@templengthone}
\newlength{\LWR@templengthtwo}
\newlength{\LWR@templengththree}
\newcounter{LWR@tempcountone}
```

Used to add a style to a table data cell:

```
\newbool{LWR@tdhavecellstyle}
```

\LWR@tdstartstyles Begins possibly adding a table data cell style.

```
\newcommand*{\LWR@tdstartstyles}{\global\boolfalse{LWR@tdhavecellstyle}}
```

\LWR@tdaddstyle Starts adding a table data cell style.

```
\newcommand*{\LWR@tdaddstyle}{%
\ifbool{LWR@tdhavecellstyle}%
{; }%
{ style="}%
\booltrue{LWR@tdhavecellstyle}%
}
```

\LWR@tdendstyles Finishes possibly adding a table data cell style. Prints the closing quote.

```
\newcommand*{\LWR@tdendstyles}{%
\ifbool{LWR@tdhavecellstyle}{%
    "%
    \global\boolfalse{LWR@tdhavecellstyle}%
}{}%
}
```

\LWR@subaddcmidruletrim {⟨*lefttrim*⟩} {⟨*righttrim*⟩} Adds a \cmidrule with optional trim.

```
\newcommand*{\LWR@subaddcmidruletrim}[2]{%
```

```
\setlength{\LWR@templengthone}{%
        \LWR@getexparray{LWR@midrules}{\arabic{LWR@tableLaTeXcolindex}}%
}%
\ifdimcomp{\LWR@templengthone}{>}{0pt}%
{%
```

Print the class with left and right trim letters appended:

```
    \LWR@origtilde tdrule#1#2%
```

Remember the width of the rule:

```
    \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
}%
{%
    \setlength{\LWR@thiscmidrulewidth}{0pt}%
}%
}
```

`\LWR@addcmidruletrim` Adds left or right trim to a `\cmidrule`.

```
\newcommand*{\LWR@addcmidruletrim}{%
\LWR@subaddcmidruletrim%
{\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
{\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@tableLaTeXcolindex}}}%
}
```

`\LWR@addrulewidth` {⟨*thiswidth*⟩} {⟨*defaultwidth*⟩}

If not default width, add a custom style with width and color depending on `thiswidth`.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addrulewidth}[2]{%
```

Only add a custom width if `thiswidth` is different than the `defaultwidth`, or if a color is being used:

```
\ifboolexpr{%
    test{\ifdimcomp{#1}{=}{0pt}} or
    (
        ( test{\ifdimcomp{#1}{=}{#2}} and not bool{FormatWP} )
        and ( test {\ifdefvoid{\LWR@ruleHTMLcolor}} )
    )
}%
{}% default width and color
{% custom width and/or color
```

Ensure that the width is wide enough to display in the browser:

```
    \LWR@forceminwidth{#1}%
```

Begin adding another style:

```
    \LWR@tdaddstyle%
```

The style itself:

```
    border-top:\LWR@printlength{\LWR@atleastonept} solid %
```

If default gray, the darkness of the color depends on the thickness of the rule:

```
    \ifdefvoid{\LWR@ruleHTMLcolor}{%
        \ifdimcomp{#1}{<}{\LWR@lightrulewidth}%
        {\LWR@origpound{}A0A0A0}%
        {% lightrule or heaver
            \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}%
            {\LWR@origpound{}808080}%
            {black}%
        }% lightrule or heavier
    }{%
        \LWR@origpound\LWR@ruleHTMLcolor%
    }
}% custom width and/or color
}
```

`\LWR@addcmidrulewidth` Adds a `style` for the rule width.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addcmidrulewidth}{%
\LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
}
```

`\LWR@addcdashline` Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addcdashline}{%
\edef\LWR@tempone{%
    \LWR@getexparray{LWR@cdashlines}{\arabic{LWR@tableLaTeXcolindex}}%
}%
\ifdefstring{\LWR@tempone}{Y}{%
    \LWR@tdaddstyle%
    border-top: 1pt dashed %
    \ifdefvoid{\LWR@ruleHTMLcolor}%
        {black}%
        {\LWR@origpound\LWR@ruleHTMLcolor}%
}{}%
}
```

`\LWR@WPcell` {⟨*text-align*⟩} {⟨*vertical-align*⟩}

```
\newcommand*{\LWR@WPcell}[2]{%
\LWR@tdaddstyle%
\LWR@print@mbox{text-align:#1}; \LWR@print@mbox{vertical-align:#2}%
}
```

\LWR@addformatwpalignment If FormatWP, adds a style for the alignment.

Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
\newcommand*{\LWR@addformatwpalignment}[1]{%
\ifbool{FormatWP}{%
\IfSubStr{#1}{l}{\LWR@WPcell{left}{middle}}{}%
\IfSubStr{#1}{c}{\LWR@WPcell{center}{middle}}{}%
\IfSubStr{#1}{r}{\LWR@WPcell{right}{middle}}{}%
\IfSubStr{#1}{p}{\LWR@WPcell{left}{bottom}}{}%
\IfSubStr{#1}{m}{\LWR@WPcell{left}{middle}}{}%
\IfSubStr{#1}{b}{\LWR@WPcell{left}{top}}{}%
\IfSubStr{#1}{P}{\LWR@WPcell{center}{bottom}}{}%
\IfSubStr{#1}{M}{\LWR@WPcell{center}{middle}}{}%
\IfSubStr{#1}{B}{\LWR@WPcell{center}{top}}{}%
}{}%
}
```

71.21 Cell colors

\LWR@addtabularrowcolor Adds a cell's row color style, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```
\newcommand*{\LWR@addtabularrowcolor}{%
\ifbool{LWR@tabularmutemods}{}{%
    \ifdefvoid{\LWR@rowHTMLcolor}{%
        \ifdefvoid{\LWR@xcolorrowHTMLcolor}{}%
        {% xcolor row color
            \LWR@tdaddstyle%
            background:\LWR@origpound\LWR@xcolorrowHTMLcolor%
        }%
    }%
    {% explicit row color
        \LWR@tdaddstyle%
        background:\LWR@origpound\LWR@rowHTMLcolor%
    }%
}%
}
```

\LWR@addtabularhrulecolor Adds a cell's horizontal rule color style, if needed.

```
\newcommand*{\LWR@addtabularhrulecolor}{%
```

If either form of horizontal rule is requested:

```
\ifboolexpr{%
    test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
    test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
    bool{LWR@doingtbrule}%
}{%
```

If there is a no custom color:

```
    \ifdefvoid{\LWR@ruleHTMLcolor}%
    {%
        \ifnumcomp{\value{LWR@hlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 4px double%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 2px dashed%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 1px dashed%
        }{}}}%
```

If no color and not doubled or dashed, then add nothing, since a simpler rule is the default.

```
    }%
```

If there is a custom color:

```
    {%
        \ifnumcomp{\value{LWR@hlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 4px double \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 2px dashed \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 1px dashed \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
            \LWR@tdaddstyle%
            border-top: 1px solid \LWR@origpound\LWR@ruleHTMLcolor%
        }}}%
    }%
}{}%
}
```

`\LWR@addtabularrulecolors` Adds a cell's rule color styles, if needed.

No color is added for the final row of empty cells which finishes each `tabular`.

```
\newcommand*{\LWR@addtabularrulecolors}{%
```

Custom horizonal rule color:

```
\LWR@addtabularhrulecolor%
```

No vertical rules if finishing the `tabular` with a row of empty cells:

```
\ifbool{LWR@tabularmutemods}{}{%
```

If at the leftmost cell, possibly add a leftmost vertical rule:

```
    \ifnumequal{\value{LWR@tableLaTeXcolindex}}{1}{%
```

Fetch the left edge's vertical bar specification:

```
        \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
```

Add a custom style if a vertical bar was requested:

```
        \ifdefstring{\LWR@tempone}{tvertbarl}{%
                \LWR@tdaddstyle%
                border-left: 1px solid % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldouble}{%
                \LWR@tdaddstyle%
                border-left: 4px double % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldash}{%
                \LWR@tdaddstyle%
                border-left: 1px dashed % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldoubledash}{%
                \LWR@tdaddstyle%
                border-left: 2px dashed % space
                    \LWR@vertruleHTMLcolor%
        }{}%
    }{}%
```

Possibly add a right vertical rule for this cell:

```
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tableLaTeXcolindex}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarr}{%
```

Add a custom style if a vertical bar was requested:

```
            \LWR@tdaddstyle%
            border-right: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
```

```
    \ifdefstring{\LWR@tempone}{tvertbarrdouble}{%
            \LWR@tdaddstyle%
            border-right: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifdefstring{\LWR@tempone}{tvertbarrdash}{%
            \LWR@tdaddstyle%
            border-right: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifdefstring{\LWR@tempone}{tvertbarrdoubledash}{%
            \LWR@tdaddstyle%
            border-right: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
}%
}
```

Ctr `LWR@cellcolordepth` Counts how many cell color s were added to the current tabular data cell.

```
\newcounter{LWR@cellcolordepth}
```

`\LWR@subaddtabularcellcolor` {⟨*HTML color*⟩}

```
\newcommand*{\LWR@subaddtabularcellcolor}[1]{%
\LWR@htmltag{div class="cellcolor" style="%
    background:\LWR@origpound{}{}#1 %
" }%
\addtocounter{LWR@cellcolordepth}{1}%
}
```

`\LWR@addtabularcellcolor` Adds a cell color style, if needed.

```
\newcommand*{\LWR@addtabularcellcolor}{%
\ifdefvoid{\LWR@cellHTMLcolor}%
{%
    \ifdefvoid{\LWR@rowHTMLcolor}%
    {%
        \ifdefvoid{\LWR@xcolorrowHTMLcolor}%
        {%
            \ifdefvoid{\LWR@columnHTMLcolor}%
            {}%
            {\LWR@subaddtabularcellcolor{\LWR@columnHTMLcolor}}%
        }%
        {\LWR@subaddtabularcellcolor{\LWR@xcolorrowHTMLcolor}}%
    }%
    {\LWR@subaddtabularcellcolor{\LWR@rowHTMLcolor}}%
}%
{\LWR@subaddtabularcellcolor{\LWR@cellHTMLcolor}}%
}
```

71.22 Multicolumns

71.22.1 Parsing multicolumns

```
\newcounter{LWR@tablemulticolswidth}
```

Indexes into the multicolumn specification:

```
\newcounter{LWR@tablemulticolspos}
```

Remembers multicolumn vertical rules if found in the column spec.

```
\newcounter{LWR@mcolvertbarsl}
\newcounter{LWR@mcolvertbarsr}
\newcounter{LWR@mcolvertbarsldash}
\newcounter{LWR@mcolvertbarsrdash}
\newbool{LWR@mcolvertbaronleft}%
```

`\LWR@printmccoltype` {⟨*colspec*⟩} Print any valid column type found. Does not print `@`, `!`, `>`, or `<` columns or their associated tokens.

This is printed as part of the table data tag's `class`.

```
\newcommand*{\LWR@printmccoltype}[1]{%
\LWR@traceinfo{lwr@printmccoltype -#1-}%
```

Get one token of the column spec:

```
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Add to the HTML tag depending on which column type is found:

```
\IfStrEq{\LWR@strresult}{l}{l}{}%
\IfStrEq{\LWR@strresult}{c}{c}{}%
\IfStrEq{\LWR@strresult}{r}{r}{}%
\IfStrEq{\LWR@strresult}{p}{p}{}%
\IfStrEq{\LWR@strresult}{m}{m}{}%
\IfStrEq{\LWR@strresult}{b}{b}{}%
\IfStrEq{\LWR@strresult}{P}{P}{}%
\IfStrEq{\LWR@strresult}{M}{M}{}%
\IfStrEq{\LWR@strresult}{B}{B}{}%

\IfStrEq{\LWR@strresult}{w}{w}{}%
\IfStrEq{\LWR@strresult}{W}{W}{}%

\IfStrEq{\LWR@strresult}{S}{c}{}%
\IfStrEq{\LWR@strresult}{s}{c}{}%

\IfStrEq{\LWR@strresult}{X}{p}{}%

\IfStrEq{\LWR@strresult}{|}%
{%
```

```
    \ifbool{LWR@mcolvertbaronleft}%
        {\addtocounter{LWR@mcolvertbarsl}{1}}% left edge
        {\addtocounter{LWR@mcolvertbarsr}{1}}% not left edge
}%
{%
    \IfStrEq{\LWR@strresult}{:}%
    {%
        \ifbool{LWR@mcolvertbaronleft}%
            {\addtocounter{LWR@mcolvertbarsldash}{1}}% left edge
            {\addtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
    }%
    {%
        \IfStrEq{\LWR@strresult}{;}%
        {%
            \ifbool{LWR@mcolvertbaronleft}%
                {\addtocounter{LWR@mcolvertbarsldash}{1}}% left edge
                {\addtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
        }%
        {\boolfalse{LWR@mcolvertbaronleft}}%
    }%
}%
\LWR@traceinfo{lwr@printmccoltype done}%
}
```

`\LWR@multicolpartext` {⟨*num parameters*⟩} Print the data with paragraph tags, advance to bypass the given number of parameters.

```
\newcommand*{\LWR@multicolpartext}[1]{%
\LWR@startpars%
\LWR@multicoltext%
\addtocounter{LWR@tablemulticolspos}{#1}%
\LWR@stoppars%
}
```

`\LWR@multicolother` {⟨*colspec*⟩} For `@`, `!`, `>`, `<`, print the next token without paragraph tags:

```
\newcommand*{\LWR@multicolother}[1]{%
\addtocounter{LWR@tablemulticolspos}{1}%
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
\LWR@strresult%
```

A valid column data type was found:

```
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@multicolskip` Nothing to print for this column type.

```
\newcommand*{\LWR@multicolskip}{%
```

A valid column data type was found:

```
\global\booltrue{LWR@validtablecol}%
```

```
}
```

\LWR@printmccoldata {⟨*colspec*⟩} Print the data for any valid column type found.

```
\newcommand*{\LWR@printmccoldata}[1]{%
\LWR@traceinfo{lwr@printmccoldata -#1}%
```

Not yet found a valid column type:

```
\global\boolfalse{LWR@validtablecol}%
```

Get one token of the column spec:

```
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Print the text depending on which column type is found. Also handles @, >, < as it comes to them.

```
\IfStrEq{\LWR@strresult}{l}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{c}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{r}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{D}{%
\addtocounter{LWR@tablemulticolspos}{3}% skip parameters
\LWR@multicoltext%
}{}%
```

```
\IfStrEq{\LWR@strresult}{p}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{m}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{b}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{P}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{M}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{B}{\LWR@multicolpartext{0}}{}%
```

```
\IfStrEq{\LWR@strresult}{w}{\LWR@multicolpartext{3}}{}%
\IfStrEq{\LWR@strresult}{W}{\LWR@multicolpartext{3}}{}%
```

```
\IfStrEq{\LWR@strresult}{S}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{s}{\LWR@multicoltext}{}%
```

```
\IfStrEq{\LWR@strresult}{X}{\LWR@multicolpartext{0}}{}%
\IfStrEq{\LWR@strresult}{|}{\LWR@multicolskip}{}%
\IfStrEq{\LWR@strresult}{:}{\LWR@multicolskip}{}%
\IfStrEq{\LWR@strresult}{;}{%
    \LWR@multicolskip%
    \addtocounter{LWR@tablemulticolspos}{1}% skip parameter
}{}%
\IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{!}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{>}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{<}}{\LWR@multicolother{#1}}{}%
```

If an invalid column type:

```
\ifbool{LWR@validtablecol}{}{\LWR@multicoltext}%
```

Tracing:

```
\LWR@traceinfo{lwr@printmccoldata done}%
}
```

\parsemulticolumnalignment {⟨*1: colspec*⟩} {⟨*2: printresults*⟩}

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a p{spec} column, or @, >, <, is a token list which will NOT match l, c, r, or p.

```
\newcommand*{\LWR@parsemulticolumnalignment}[2]{%
\setcounter{LWR@tablemulticolspos}{1}%
\StrLen{#1}[\LWR@strresult]%
\setcounter{LWR@tablemulticolswidth}{\LWR@strresult}%
```

Scan across the tokens in the column spec:

```
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@tablemulticolspos}}{>}%
            {\value{LWR@tablemulticolswidth}}%
    }%
}%
{%
```

Execute the assigned print function for each token in the column spec:

```
#2{#1}%
```

Move to the next token in the column spec:

```
\addtocounter{LWR@tablemulticolspos}{1}%
}%
}
```

71.22.2 Multicolumn factored code

\LWR@addmulticolvertrulecolor

```
\newcommand*{\LWR@addmulticolvertrulecolor}{%
```

No vertical rules if finishing the tabular with a row of empty cells:

```
\ifbool{LWR@tabularmutemods}{}{%
```

Left side:

```
    \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{%
        \LWR@tdaddstyle%
        border-left: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{%
        \LWR@tdaddstyle%
        border-left: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{%
        \LWR@tdaddstyle%
        border-left: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
        \LWR@tdaddstyle%
        border-left: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
```

Right side:

```
    \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{%
        \LWR@tdaddstyle%
        border-right: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{%
        \LWR@tdaddstyle%
        border-right: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{%
        \LWR@tdaddstyle%
        border-right: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
        \LWR@tdaddstyle%
        border-right: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
}%
}
```

```
\newcommand{\LWR@multicoltext}{}
```

To find multicolumn right trim:

```
\newcounter{LWR@lastmulticolumn}
```

`\LWR@domulticolumn` [⟨*1: vpos*⟩] [⟨*2: #rows*⟩] {⟨*3: numLaTeXcols*⟩} {⟨*4: numHTMLcols*⟩} {⟨*5: colspec*⟩} {⟨*6: text*⟩}

```
\NewDocumentCommand{\LWR@domulticolumn}{o o m m m +m}{%
\LWR@traceinfo{LWR@domulticolumn -#1- -#2- -#4- -#5-}%
```

Remember the text to be inserted, and remember that a valid column type was found:

```
\renewcommand{\LWR@multicoltext}{%
#6%
\global\booltrue{LWR@validtablecol}%
}%
```

Compute the rightmost column to be included. This is used to create the right trim.

```
\setcounter{LWR@lastmulticolumn}{\value{LWR@tableLaTeXcolindex}}%
\addtocounter{LWR@lastmulticolumn}{#3}%
\addtocounter{LWR@lastmulticolumn}{-1}%
```

Row processing:

```
\LWR@maybenewtablerow%
```

Begin the opening table data tag:

```
\LWR@htmltag{td colspan="#4" %
```

```
\IfValueT{#2}{ % rows?
rowspan="#2" %
```

```
\IfValueT{#1}{% vpos?
\ifstrequal{#1}{b}{style="\LWR@print@mbox{vertical-align:bottom}" }{}%
\ifstrequal{#1}{t}{style="\LWR@print@mbox{vertical-align:top}" }{}%
}% vpos?
}% rows?
```

```
 class="td%
```

Print the column type and vertical bars:

```
\setcounter{LWR@mcolvertbarsl}{0}%
\setcounter{LWR@mcolvertbarsr}{0}%
\setcounter{LWR@mcolvertbarsldash}{0}%
\setcounter{LWR@mcolvertbarsrdash}{0}%
\booltrue{LWR@mcolvertbaronleft}%
\LWR@parsemulticolumnalignment{#5}{\LWR@printmccoltype}%
```

If this column has a cmidrule, add “rule” to the end of the HTML class tag.

If this position had a “Y” then add “rule” for a horizontal rule:

```
\LWR@subaddcmidruletrim%
{\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
{\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@lastmulticolumn}}}%
```

Also add vertical bar class.

```
\ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{ tvertbarl}{}%
\ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{ tvertbarldouble}{}%
\ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{ tvertbarr}{}%
\ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{ tvertbarrdouble}{}%
```

```
\ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{ tvertbarldash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{ tvertbarldoubledash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{ tvertbarrdash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{ tvertbarrdoubledash}{}%
```

Close the class tag's opening quote: " NOT A TYPO

```
%
\LWR@tdstartstyles%
\LWR@addtabularrowcolor%
\LWR@addcmidrulewidth%
\LWR@addcdashline%
\LWR@addtabularhrulecolor%
\LWR@addmulticolvertrulecolor%
\LWR@addformatwpalignment{#5}%
\LWR@tdendstyles%
}% end of the opening table data tag
\global\boolfalse{LWR@intabularmetadata}%
\LWR@parsemulticolumnalignment{#5}{\LWR@printmccoldata}%
}
```

71.22.3 Multicolumn

\LWR@htmlmulticolumn {⟨*numcols*⟩} {⟨*alignment*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlmulticolumn}{m m +m}%
{%
```

Figure out how many extra HTML columns to add for @ and ! columns:

```
\LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn tag:

```
\LWR@domulticolumn{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#3}%
```

Move to the next LaTeX column:

```
\addtocounter{LWR@tableLaTeXcolindex}{#1}%
\addtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}
```

71.22.4 Longtable captions

longtable captions use `\multicolumn`.

Bool LWR@starredlongtable

Per the caption pacakge, step the counter if `longtable*`.

```
\newbool{LWR@starredlongtable}
\boolfalse{LWR@starredlongtable}
```

Per the caption package. User-redefinable float type.

```
\providecommand*{\LTcaptype}{table}
```

\LWR@longtabledatacaptiontag * [⟨*toc entry*⟩] {⟨*caption*⟩}

```
\NewDocumentCommand{\LWR@longtabledatacaptiontag}{s o +m}
{%
```

Remember the latest name for `\nameref`:

```
\IfValueTF{#2}{% optional given?
    \ifblank{#2}% optional empty?
    {\LWR@setlatestname{#3}}% empty
    {\LWR@setlatestname{#2}}% given and non-empty
}% optional given
{\LWR@setlatestname{#3}}% no optional
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for `@` and `!` columns found between the first and the last column:

```
\LWR@tabularhtmlcolumns{1}{\arabic{LWR@tabletotalLaTeXcols}}
```

Create the multicolumn tag:

```
\LWR@domulticolumn{\arabic{LWR@tabletotalLaTeXcols}}%
    {\arabic{LWR@tabhtmlcoltotal}}%
    {P}%
{% \LWR@domulticolumn
\IfBooleanTF{#1}% star?
```

Star version, show a caption but do not make a LOT entry:

```
{% yes star
    \LWR@figcaption%
    \LWR@isolate{#3}%
    \endLWR@figcaption%
}%
{% No star:
```

Not the star version:

Don't step the counter if `\caption[]{A caption.}`

```
\ifbool{LWR@starredlongtable}%
{%
    \ifblank{#2}% TOC entry
    {}%
    {%
        \refstepcounter{\LTcaptype}%
        \protected@edef\@currentlabel{%
            \@nameuse{p@\LTcaptype}\@nameuse{the\LTcaptype}%
        }%
    }%
}{}%
```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```
\LWR@figcaption%
\LWR@isolate{\@nameuse{fnum@\LTcaptype}}%
\CaptionSeparator%
\LWR@isolate{#3}%
\endLWR@figcaption%
```

See if an optional caption was given:

```
\ifblank{#2}% TOC entry empty
```

if the optional caption was given, but empty, do not form a TOC entry

```
{}%
```

If the optional caption was given, but might only be `[]`:

```
{% TOC entry not empty
    \IfNoValueTF{#2}% No TOC entry?
```

The optional caption is `[]`:

```
    {% No TOC entry
        \addcontentsline%
        {\@nameuse{ext@\LTcaptype}}%
        {\LTcaptype}%
        {%
            \protect\numberline%
          {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
            {\ignorespaces \LWR@isolate{#3}\protect\relax}%
        }%
    }% end of No TOC entry
```

The optional caption has text enclosed:

```
    {% yes TOC entry
        \addcontentsline%
        {\@nameuse{ext@\LTcaptype}}%
        {\LTcaptype}%
```

```
            {%
                \protect\numberline%
              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
                {\ignorespaces \LWR@isolate{#2}\protect\relax}%
            }%
        }% end of yes TOC entry
    }% end of TOC entry not empty
}% end of no star
```

Skip any trailing @ or ! columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}% end of \LWR@domulticolumn

\addtocounter{LWR@tableLaTeXcolindex}{\arabic{LWR@tabletotalLaTeXcols}}
\addtocounter{LWR@tableLaTeXcolindex}{-1}

}
```

71.22.5 Counting HTML tabular columns

The LaTeX specification for a table includes a number of columns separated by the & character. These columns differ in content from line to line. Additional virtual columns may be specified by the special @ and ! columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, @ and ! columns are placed into their own tabular columns. Thus, a LaTeX \multicolumn command may span several additional @ and ! columns in HTML output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```
\newcounter{LWR@tabhtmlcolindex}
\newcounter{LWR@tabhtmlcolend}
\newcounter{LWR@tabhtmlcoltotal}
```

\LWR@subtabularhtmlcolumns {⟨*index*⟩}

Factored from \LWr@tabularhtmlcolumns, which follows.

```
\newcommand*{\LWR@subtabularhtmlcolumns}[1]{%
```

Temporarily define a macro equal to the @ specification for this column:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colatspec}{#1}}%
```

If the @ specification is not empty, add to the count:

```
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\addtocounter{LWR@tabhtmlcoltotal}{1}}%
```

Likewise for the ! columns:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colbangspec}{#1}}%
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\addtocounter{LWR@tabhtmlcoltotal}{1}}%
}
```

\LWR@tabularhtmlcolumns {⟨*starting LaTeX column*⟩} {⟨*number LaTeX columns*⟩}

Compute the total number of HTML columns being spanned, considering the starting LaTeX table column and the number of LaTeX tabular columns being spanned. Any @ and ! columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter LWR@tabhtmlcoltotal.

```
\newcommand*{\LWR@tabularhtmlcolumns}[2]{%
```

Count the starting index, compute ending index, and begin with the count being the LaTeX span, to which additional @ and ! columns may be added:

```
\setcounter{LWR@tabhtmlcolindex}{#1}%
\setcounter{LWR@tabhtmlcoltotal}{#2}%
\setcounter{LWR@tabhtmlcolend}{#1}%
\addtocounter{LWR@tabhtmlcolend}{#2}%
```

If at the left edge, add the at/bang columns for the left edge:

```
\ifnumcomp{\value{LWR@tabhtmlcolindex}}{=}{1}{%
    \LWR@subtabularhtmlcolumns{leftedge}%
}{}%
```

Walk across the LaTeX columns looking for @ and ! columns:

```
\whileboolexpr{%
    test {%
        \ifnumcomp{\value{LWR@tabhtmlcolindex}}{<}{\value{LWR@tabhtmlcolend}}%
    }%
}%
{%
    \LWR@subtabularhtmlcolumns{\arabic{LWR@tabhtmlcolindex}}%
    \addtocounter{LWR@tabhtmlcolindex}{1}%
}% whiledo
}
```

```
\end{warpHTML}
```

71.23 Multirow if not loaded

A default defintion in case multirow is not loaded. This is used during table parsing.

```
\begin{warpHTML}
```

```
\newcommand{\multirow}[2][c]{}
\end{warpHTML}
```

71.24 Multicolumnrow

A print-mode version is defined here, and is also used during HTML output while inside a `lateximage`.

See section 325 for the HTML versions.

for HTML & PRINT:

```
\begin{warpall}
```

`\multicolumnrow` {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

For discussion of the use of `\DeclareExpandableDocumentCommand`, see: https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex

`\AtBeginDocument` to adjust after the user may have loaded multirow, which requires several tests to determine which version is loaded and thus which options are available.

```
\AtBeginDocument{
```

`\@ifundefined{@xmultirow}` determines if multirow was never loaded.

Null action if not loaded:

```
\@ifundefined{@xmultirow}
{
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {}%
}% no version of multirow was loaded
{% \@xmultirow defined, so some version of multirow was loaded
```

`\@ifpackageloaded{multirow}` determines if v2.0 or later of multirow was used, which included the `\ProvidesPackage` macro.

The print version:

```
\@ifpackageloaded{multirow}{% v2.0 or newer
\@ifpackagelater{multirow}{2016/09/01}% 2016/09/27 for v2.0
{% v2.0+:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow[#3]{#4}[#5]{#6}[#7]{#8}}}%
}
{% loaded but older, probably not executed:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
```

```
}
}% packageloaded{multirow}
```

If not \@ifpackageloaded{multirow} but \@xmultirow is defined, then this must be v1.6 or earlier, which did not \ProvidesPackage{multirow}, and did not have the vposn option.

```
{% v1.6 or older did not \ProvidePackage
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
}

}% \@ifundefined{@xmultirow}

\providecommand*{\multicolumnrow}{\LWR@print@multicolumnrow}

}% AtBeginDocument
```

```
\end{warpall}
```

71.25 Utility macros inside a table

for HTML output:

```
\begin{warpHTML}
```

Used to prevent opening a tabular data cell if the following token is one which does not create tabular data:

```
\newcommand*{\LWR@donothing}{}
```

In case array is not loaded:

```
\let\firsthline\relax
\let\lasthline\relax
\newcommand*{\firsthline}{}
\newcommand*{\lasthline}{}
```

In case bigdelim is not loaded:

```
\newcommand*{\ldelim}{}
\newcommand*{\rdelim}{}
```

```
\end{warpHTML}
```

71.26 Special-case tabular markers

for HTML & PRINT:

```
\begin{warpall}
```

\TabularMacro Place this just before inserting a custom macro in a table data cell. Doing so tells lwarp not to automatcally start a new HTML table data cell yet. See section 9.10.1.

```
\newcommand*{\TabularMacro}{}
```

```
\end{warpall}
```

\ResumeTabular Used to resume tabular entries after resuming an environment.

⚠ tabular inside another environment When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

for HTML output:

```
\begin{warpHTML}
```

```
\newcommand*{\ResumeTabular}{%
\global\boolfalse{LWR@exitingtabular}%
\global\boolfalse{LWR@tabularmutemods}%
\LWR@getmynexttoken%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

```
\newcommand*{\ResumeTabular}{}
```

```
\end{warpprint}
```

71.27 Checking for a new table cell

for HTML output:

```
\begin{warpHTML}
```

Bool LWR@exitingtabular When \end is found, turns off the next opening data tag.

```
\newbool{LWR@exitingtabular}
```

Bool LWR@tabularmutemods

Mutes HTML output for @, !, < and >.

This is used while printing the final row to generate \bottomrules.

```
\newbool{LWR@tabularmutemods}
```

\LWR@tabledatacolumntag

Open a new HTML table cell unless the next token is for a macro which does not create data, such as \hline, \toprule, etc:

```
\newcommand*{\LWR@tabledatacolumntag}%
{%
\LWR@traceinfo{LWR@tabledatacolumntag}%
```

\show\LWR@mynexttoken to see what tokens to look for

If not any of the below, start a new table cell:

```
\global\let\LWR@mynextaction\LWR@tabledatasinglecolumntag%
```

If exiting the tabular:

```
\ifdefequal{\LWR@mynexttoken}{\end}%
    {\global\booltrue{LWR@exitingtabular}}{}%
```

longtable can have a caption in a cell

```
\ifdefequal{\LWR@mynexttoken}{\caption}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Look for other things which would not start a table cell:

```
\ifdefequal{\LWR@mynexttoken}{\multicolumn}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\multirow}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\multicolumnrow}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\noalign}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mrowcell, this is a cell to be skipped over:

```
\ifdefequal{\LWR@mynexttoken}{\mrowcell}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mcolrowcell, this is a cell to be skipped over:

```
\ifdefequal{\LWR@mynexttoken}{\mcolrowcell}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\TabularMacro}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

```
\ifdefequal{\LWR@mynexttoken}{\hline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\firsthline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\lasthline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\toprule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\midrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cmidrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\morecmidrules}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\specialrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\bottomrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\rowcolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\arrayrulecolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\doublerulesepcolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\warpprintonly}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\warpHTMLonly}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\ldelim}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\rdelim}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

For arydshln:

```
\ifdefequal{\LWR@mynexttoken}{\hdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\firsthdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\lasthdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Ignore an empty line between rows:

```
\ifdefequal{\LWR@mynexttoken}{\par}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

No action for an \end token.

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```
\LWR@traceinfo{LWR@tabledatacolumntag: about to do mynext}%
\LWR@mynextaction%
\LWR@traceinfo{LWR@tabledatacolumntag: done}%
}

\end{warpHTML}
```

71.28 \mrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mrowcell ⚠ multirow cells

The user must insert \mrowcell into any \multirow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mrowcell}{}

\end{warpall}
```

71.29 \mcolrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mcolrowcell ⚠ multirow cells

The user must insert \mcolrowcell into any \multicolumnrow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mcolrowcell}{}
```

```
\end{warpall}
```

71.30 HTML tabular environment

for HTML output:

```
\begin{warpHTML}
```

These are default defininitions in case booktabs is not loaded, and are not expected to used, but must exist as placeholders. They are pre-deleted in case memoir has already loaded booktabs.

```
\LetLtxMacro\toprule\relax
\LetLtxMacro\midrule\relax
\LetLtxMacro\cmidrule\cline
\LetLtxMacro\bottomrule\relax
\LetLtxMacro\addlinespace\relax
\LetLtxMacro\morecmidrules\relax
\LetLtxMacro\specialrule\relax

\newcommand*{\toprule}[1][]{\hline}
\newcommand*{\midrule}[1][]{\hline}
\LetLtxMacro\cmidrule\cline
\newcommand*{\bottomrule}[1][]{\hline}
\newcommand*{\addlinespace}[1][]{}
\newcommand*{\morecmidrules}{}
\newcommand*{\specialrule}[3]{\hline}
```

\noalign {⟨*text*⟩} Redefined for use inside tabular.

```
\LetLtxMacro\LWR@orignoalign\noalign

\newcommand{\LWR@tabularnoalign}[1]{%
\begingroup%
\global\advance\rownum\m@ne%
\renewcommand*{\LWR@xcolorrowHTMLcolor}{}%
\multicolumn{\value{LWR@tabletotalLaTeXcols}}{l}{#1} \\
\endgroup%
% \@rowc@lors%
\LWR@getmynexttoken%
}
```

\LWR@HTMLhline The definition of \hline depends on whether tabls has been loaded. If so, optional space below the line may be specified, but will be ignored.

```
\AtBeginDocument{
\@ifpackageloaded{lwarp-tabls}
```

```
{
\newcommand*{\LWR@HTMLhline}[1][]{%
    \ifbool{FormatWP}%
    {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
    {\addtocounter{LWR@hlines}{1}}%
    \LWR@getmynexttoken}%
}
{
\newcommand*{\LWR@HTMLhline}{%
    \ifbool{FormatWP}%
    {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
    {\addtocounter{LWR@hlines}{1}}%
    \LWR@getmynexttoken}%
}
}% AtBeginDocument
```

`\LWR@HTMLcline` {⟨*columns*⟩}

```
\NewDocumentCommand{\LWR@HTMLcline}{m}%
{\LWR@docmidrule{#1}\LWR@getmynexttoken}%
```

`\LWR@tabular@warpprintonly` {⟨*contents*⟩}

Only process the contents if producing printed output. Modified inside a `tabular` to grab the next token.

```
\newcommand{\LWR@tabular@warpprintonly}[1]{%
    \ifbool{warpingprint}{#1}{}%
    \LWR@getmynexttoken%
}
```

`\LWR@nullifyNoAutoSpacing` For babel-french, turn off auto spacing at the start of the tabular, then nullify the autospacing commands inside the tabular, since they were not compatible with the tabular column parsing code, which uses xstring.

```
\AtBeginDocument{
\@ifundefined{frenchbsetup}%
{% no babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{}
}% no babel-french
{% yes babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{%
        \NoAutoSpacing%
        \renewcommand*{\NoAutoSpacing}{}%
        \renewcommand*{\LWR@FBcancel}{}%
    }
}% yes babel-french
}% AtBeginDocument
```

Env `tabular` `<direction>` [⟨*vertposition*⟩] {⟨*colspecs*⟩}

The `<direction>` is from plext for Japanese documents, and is ignored.

```
\StartDefiningTabulars

\NewDocumentCommand{\LWR@HTML@@tabular}{d<> o m}
{%
\LWR@traceinfo{LWR@HTML@@tabular started}%
\addtocounter{LWR@tabulardepth}{1}%
```

Not yet started a table row:

```
\global\boolfalse{LWR@startedrow}%
```

Not yet doing any rules:

```
\setcounter{LWR@hlines}{0}%
\setcounter{LWR@hdashedlines}{0}%
\global\boolfalse{LWR@doingtbrule}%
\global\boolfalse{LWR@doingcmidrule}%
```

For babel-french, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the tabular parsing code.

```
\LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of tabular command. Unmute the `@` and `!` columns.

```
\global\boolfalse{LWR@exitingtabular}%
\global\boolfalse{LWR@tabularmutemods}%
```

Error if failed to use `\mrowcell` or `\mcolrowcell` when needed.

```
\boolfalse{LWR@usedmultirow}
\boolfalse{LWR@foundmrowcell}
```

Create the `table` tag:

```
\global\booltrue{LWR@intabularmetadata}%
\LWR@traceinfo{LWR@@tabular: About to LWR@forecenewpage.}%
\LWR@forcenewpage
\LWR@htmlblocktag{table}%
```

Parse the table columns:

```
\LWR@parsetablecols{#3}%
```

Table col spec is: `\LWR@tablecolspec` which is a string of `llccrr`, etc.

Do not place the table inside a paragraph:

```
\LWR@stoppars%
```

Track column #:

```
\setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
\global\boolfalse{LWR@tabularcelladded}%
```

Start looking for midrules:

```
\LWR@clearmidrules%
```

\\ becomes a macro to end the table row:

```
\LetLtxMacro{\\}{\LWR@tabularendofline}%
```

\warpprintonly inside a tabular must grab the next token.

```
\LetLtxMacro\warpprintonly\LWR@tabular@warpprintonly%
```

The following adjust for colortbl.

```
\LetLtxMacro\arrayrulecolor\arrayrulecolornexttoken%
\LetLtxMacro\doublerulesepcolor\doublerulesepcolornexttoken%
\gdef\LWR@columnHTMLcolor{}%
\gdef\LWR@rowHTMLcolor{}%
\gdef\LWR@cellHTMLcolor{}%
\@rowcolors%
```

The vertical rules are set to the color active at the start of the tabular. \arrayrulecolor will then affect horizontal rules inside the tabular, but not the vertical rules.

```
\ifdefvoid{\LWR@ruleHTMLcolor}%
    {\edef\LWR@vertruleHTMLcolor{black}}%
    {\edef\LWR@vertruleHTMLcolor{\LWR@origpound\LWR@ruleHTMLcolor}}%
```

Tracking the depth of cell color s:

```
\setcounter{LWR@cellcolordepth}{0}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with \LWR@getmynextoken to see if the next token might create a new data cell:

The optional parameter for \hline supports the tabls package.

```
\LWR@traceinfo{LWR@@HTML@tabular: redefining macros}%
\LetLtxMacro\noalign\LWR@tabularnoalign%
\LetLtxMacro\hline\LWR@HTMLhline%
\LetLtxMacro\cline\LWR@HTMLcline%

\DeclareDocumentCommand{\hdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%
```

```
\DeclareDocumentCommand{\cdashline}{m}{%
    \LWR@docdashline{##1}\LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\firsthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\lasthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%
```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use `\LWR@getmynexttoken`.

```
\renewcommand{\multicolumn}{\LWR@htmlmulticolumn}%
\renewcommand*{\mrowcell}{%
    \LWR@maybenewtablerow%
    \LWR@tabularleftedge%
    \global\booltrue{LWR@skippingmrowcell}%
    \booltrue{LWR@foundmrowcell}%
}%
\renewcommand*{\mcolrowcell}{%
    \LWR@maybenewtablerow%
    \global\booltrue{LWR@skippingmcolrowcell}%
    \booltrue{LWR@foundmrowcell}%
}%
\LetLtxMacro\caption\LWR@longtabledatacaptiontag%
```

Reset for new processing:

```
\global\boolfalse{LWR@tableparcell}%
\global\boolfalse{LWR@skippingmrowcell}%
\global\boolfalse{LWR@skippingmcolrowcell}%
\global\boolfalse{LWR@skipatbang}%
\global\boolfalse{LWR@emptyatbang}%
```

Set `&` for its special meaning inside the tabular:

```
\StartDefiningTabulars%
\protected\gdef&{\LWR@tabularampersand}%
```

Locally force any minipages to be fullwidth, until the end of the `tabular`:

```
\booltrue{LWR@forceminipagefullwidth}
```

Nest one level deeper of tabular paragraph handling:

```
\addtocounter{LWR@tabularpardepth}{1}%
```

Look ahead for a possible table data cell:

```
\LWR@traceinfo{LWR@@HTML@tabular: about to LWR@getmynexttoken}%
\LWR@getmynexttoken%
}%
```

Ending the environment:

```
\newcommand*{\LWR@HTML@endtabular}
{%
\LWR@traceinfo{LWR@HTML@endtabular}%
```

Unnest one level of tabular paragraph handling:

```
\addtocounter{LWR@tabularpardepth}{-1}%
\ifboolexpr{%
    test {%
      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}
    } or %
    (%
        bool{LWR@intabularmetadata} and%
        not bool{LWR@tabularcelladded} and%
        test {%
        \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}%
        }%
    )%
}%
{%
    \LWR@tabularfinishrow%
}%
{%
    \LWR@closetabledatacell%
}%
\LWR@htmlblocktag{/tr}%
```

xcolor row color support:

```
\@rowc@lors%
```

```
\LWR@htmlblocktag{/table}%
\global\boolfalse{LWR@intabularmetadata}%
```

Unnest one level of tabular:

```
\addtocounter{LWR@tabulardepth}{-1}%
```

Restore & to its usual meaning:

```
\protected\gdef&{\LWR@origampmacro}%
\StopDefiningTabulars%
```

Error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
\ifbool{LWR@usedmultirow}{%
    \ifbool{LWR@foundmrowcell}%
        {}%
        {%
            \PackageError{lwarp}%
            {%
            When using \protect\multirow, \protect\multicolumnrow,\MessageBreak
                or the bigdelim package,\MessageBreak
             place \protect\mrowcell\space or \protect\mcolrowcell\MessageBreak
                in empty cells which are to be skipped.\MessageBreak
                See the lwarp package documentation:\MessageBreak
                "Special cases and limitations" -> "Tabular"
            }%
            {%
                See the lwarp package documentation:\MessageBreak
                "Special cases and limitations" -> "Tabular".
            }%
        }%
}{}%
```

```
\LWR@traceinfo{LWR@HTML@endtabular finished}%
}

\csletcs{LWR@HTML@endtabular*}{LWR@HTML@endtabular}

\StopDefiningTabulars
```

siunitx may redefine tabular, so set the following later:

```
\AtBeginDocument{
    \LetLtxMacro\LWR@origendtabular\endtabular
    \csletcs{LWR@origendtabular*}{endtabular*}
    \LWR@formatted{@tabular}
    \LWR@formatted{endtabular}
    \LWR@formatted{endtabular*}
}
```

```
\end{warpHTML}
```

72 Cross-references

Sectioning commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

File *_html.aux

A new entry in *_html.aux is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

Table 12 shows the data structures related to cross-referencing.

for HTML output:

```
\begin{warpHTML}
```

72.1 Setup

`\@currentlabelname` To remember the most recently defined section name, description, or caption, for `\nameref`.

```
\providecommand*{\@currentlabelname}{}
```

`\LWR@stripperiod` {⟨*text*⟩} [⟨.⟩]

Removes a trailing period.

```
\def\LWR@stripperiod#1.\ltx@empty#2\@nil{#1}%
```

`\LWR@setlatestname` {⟨*object name*⟩}

Removes `\label`, strips any final period, and remembers the result.

```
\newcommand*{\LWR@setlatestname}[1]{%
```

Remove `\label` and other commands from the name, the strip any final period. See gettitlestring.

```
\GetTitleStringExpand{#1}%
\edef\@currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
\edef\@currentlabelname{%
    \expandafter\LWR@stripperiod\@currentlabelname%
    \ltx@empty.\ltx@empty\@nil%
}%
}
```

72.2 New lwarp labels.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

See:
http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference

Table 12: Cross-referencing data structures

Original LaTeX: (print and HTML)

\refstepcounter: Steps the couunter and sets \@currentlabel.

\@currentlabel: \p@<ctr>\the<ctr> Updated by \refstepcounter.

\label: Writes to the .aux file:
\newlabel{<label>}{{\@currentlabel}{\thepage}}

\newlabel: When the .aux file is read, sets \r@<label>.

\r@<label>: Set to: {{\@currentlabel}{\thepage}}

\ref: Returns the first part of \r@<label>.

\pageref: Returns the second part of \r@<label>.

Added by lwarp: (HTML only)

\label: Adds HTML tags (section 72.3), and another .aux entry (section 72.2).

\newlabel: Unchanged. When the .aux file is read, sets \r@<label>@lwarp.

\r@<label>@lwarp: Set to {{section_name}{file_name}{depth}{number}}:

\LWR@nameref: The section name for this label.

\LWR@htmlfileref: The filenumber or name for this label.

\LWR@lateximagedepthref: The lateximagedepth for this label.

\LWR@lateximagenumberref: The lateximagenumber for this label.

\nameref: Emualted from hyperref for lwarp. See section 72.4.

\ref and \nameref: Adds HTML tags. See section 72.4.

Added by amsmath: (print and HTML)

\label: Execution is delayed until the math environment is completed.

\ltx@label: LaTeX \label, (HTML: patched by lwarp,) later patched by cleveref.

Added by cleveref: (print and HTML)

\refstepcounter: Added: sets \cref@currentlabel.

\cref@currentlabel: (<type>=<ctr> unless an alias is used):
[<type>][\arabic{<ctr>}][<parent ctrs>]{\p@<ctr>\the<ctr>} Also see section 58.4 for use with footnotes.

\label: Writes to the .aux file:
\newlabel{<label>@cref}{{\cref@currentlabel}{\thepage}}

\newlabel: Unchanged. When the .aux file is read, sets \r@<label>@cref.

\r@<label>@cref: Set to: {{\cref@currentlabel}{\thepage}}

Utility functions: See \cref@getlabel, \cref@gettype, \cref@getcounter, \cref@getprefix.

Cross-referencing names: \crefname and \Crefname assign human-readable names for references to this counter type.

Additionally patched by lwarp: (HTML only)

\cref, etc.: Modified for lwarp. See section 86.

\label inside math: See section 78.7.1.

Footnotes: See \noteentry in section 58.4.

\LWR@setref {⟨*args list*⟩} {⟨*selector*⟩} {⟨*label*⟩}

\@setref without the \null (\hbox), and without the warning messages. Each caused problems with lwarp references. The regular reference will cause the warning.

```
\def\LWR@setref#1#2#3{%
  \ifx#1\relax%
    ??%
  \else%
   \expandafter#2#1%
  \fi}
```

\LWR@nameref {⟨*label*⟩} Returns the section name for this label:

```
\newcommand*{\LWR@nameref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@firstoffour{#1}%
}
```

\LWR@htmlfileref {⟨*label*⟩} Returns the file number or name for this label:

```
\newcommand*{\LWR@htmlfileref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@secondoffour{#1}%
}
```

\LWR@lateximagedepthref {⟨*label*⟩} Returns the lateximagedepth for this label:

```
\newcommand*{\LWR@lateximagedepthref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@thirdoffour{#1}%
}
```

\LWR@lateximagenumberref {⟨*label*⟩} Returns the lateximagenumber for this label:

```
\newcommand*{\LWR@lateximagenumberref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@fourthoffour{#1}%
}
```

\LWR@lwarplabel {⟨*label*⟩} Sanitize the name and then creates the label:

```
\newcommand*{\LWR@lwarplabel}[1]{%
\LWR@traceinfo{LWR@lwarplabel !#1!}%
\LWR@setlatestname{\@currentlabelname}%
    \@bsphack%
    \protected@write\@auxout{}%
        {\string\newlabel{#1@lwarp}{%
            {\@currentlabelname}%
        {\ifbool{FileSectionNames}{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}%
            {\arabic{LWR@lateximagedepth}}%
            {\arabic{LWR@lateximagenumber}}%
        }}%
    \@esphack%
}
```

72.3 Labels

\LWR@sublabel {⟨*label*⟩} Creates an HTML id tag.

\detokenize is used to allow underscores in the labels.

```
\newcommand*{\LWR@sublabel}[1]{%
\LWR@traceinfo{LWR@sublabel !#1!}%
```

Create an HTML id tag unless are inside a lateximage, since it would appear in the image:

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{% not lateximage
```

If not doing a lateximage, create an HTML ID tag: (To be factored…)

```
    \LWR@sanitize{#1}%
    \ifbool{LWR@doingstartpars}%
    {% pars allowed
        \ifbool{LWR@doingapar}%
        {% par started
         \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
        }% par started
        {% par not started
            \LWR@stoppars%
         \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
            \LWR@startpars%
        }% par not started
    }% pars allowed
    {% pars not allowed
        \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
    }% pars not allowed
}% not lateximage
}
```

\LWR@new@label (⟨*bookmark*⟩) {⟨*label*⟩} [⟨*type*⟩]

\label during HTML output when not in SVG math mode, removing extra spaces around the label, as done by a regular LaTeX \label.

The is also during a lateximage, including SVG math, since the special label handling is required, but \LWR@sublabel does not generate HTML tags inside a lateximage.

clevereref later encases this to add its own cross-referencing.

The optional ⟨*bookmark*⟩ is per the memoir class, and is ignored.

The optional ⟨*type*⟩ is per the ntheorem package, and is ignored.

```
\NewDocumentCommand{\LWR@new@label}{d() m o}{%
\LWR@traceinfo{LWR@new@label: starting}%
\LWR@traceinfo{LWR@new@label: !#2!}%
```

```
% \@bsphack%
```

Create a traditional LaTeX label, as modified by cleveref:

```
\LWR@orig@label{#2}%
```

Create a special label which holds the section number, LWR@htmlfilenumber, LWR@lateximagedepth, and LWR@lateximagenumber:

```
\LWR@traceinfo{LWR@new@label: filesectionnames is \ifbool{FileSectionNames}{true}{false}}%
\LWR@traceinfo{LWR@new@label: LWR@thisfilename is !\LWR@thisfilename!}%
\LWR@traceinfo{LWR@new@label: LWR@htmlfilenumber is \arabic{LWR@htmlfilenumber}}%
\LWR@lwarplabel{#2}%
\LWR@sublabel{#2}%
% \@esphack%
\LWR@traceinfo{LWR@new@label: done}%
}
```

72.4 References

\LWR@startref {⟨*label*⟩} (Common code for \ref and \nameref.)

Open an HTML tag reference to a filename, # character, and a label.

```
\newcommand*{\LWR@startref}[1]
{%
\LWR@sanitize{#1}%
\LWR@traceinfo{LWR@startref A: !#1!}%
```

Create the filename part of the link:

```
\LWR@htmltag{a href="%
\LWR@traceinfo{LWR@startref B}%
\LWR@print@mbox{\LWR@htmlrefsectionfilename{#1}}%
\LWR@traceinfo{LWR@startref C}%
\LWR@origpound%
```

Create the destination id:

See if LWR@lateximagedepth is unknown:

```
\LWR@traceinfo{LWR@startref D: !#1!}%
\ifcsundef{r@#1@lwarp}%
```

"??" if LWR@lateximagedepth is unknown, so create a link with an unknown destination:

```
{%
    \LWR@traceinfo{LWR@startref D0: ??}%
    ??%
}%
```

If LWR@lateximagedepth is known. Use a lateximage if the depth is greater than zero, or a regular link otherwise:

```
{%
    \ifthenelse{\cnttest{\LWR@lateximagedepthref{#1}}{>}{0}}%
        {%
            \LWR@ImagesName\LWR@lateximagenumberref{#1}%
        }%
        {%
            \LWR@traceinfo{LWR@startref D3}%
```

\detokenize is used to allow underscores in the labels:

```
            \LWR@print@mbox{\LWR@sanitized}%
        }%
}%
\LWR@traceinfo{LWR@startref E}%
```

Closing quote:

```
"}%
\LWR@traceinfo{LWR@startref F}%
}
```

\LWR@subnewref {⟨*label*⟩} {⟨*label or sub@label*⟩}

Factored for the subfig package. Uses the original label for the hyper-reference, but prints its own text, such as "1(b)".

```
\NewDocumentCommand{\LWR@subnewref}{m m}{%
\LWR@traceinfo{LWR@subnewref #1 #2}%
\LWR@startref{#1}%
\LWR@print@ref{#2}%
\LWR@htmltag{/a}%
}
```

\ref * {⟨*label*⟩} \ref is redefined to \LWR@HTML@ref, except inside the text part of a \hyperref, where it is redefined to \LWR@ref@ignorestar.

\LWR@HTML@ref * {⟨*label*⟩} Create an internal document reference link, or without a link if starred per hyperref.

```
\NewDocumentCommand{\LWR@HTML@ref}{s m}{%
\LWR@traceinfo{LWR@HTML@ref !#2!}%
\IfBooleanTF{#1}%
{\LWR@print@ref{#2}}%
{\LWR@subnewref{#2}{#2}}%
}

\LWR@formatted{ref}
```

\LWR@ref@ignorestar * {⟨*label*⟩} For use inside \hyperref. Ignores the star, then uses the original \ref.

```
\NewDocumentCommand{\LWR@ref@ignorestar}{s m}{%
    \LWR@print@ref{#2}%
}
```

\pagerefPageFor Text for page references.

```
\newcommand*{\pagerefPageFor}{see }
```

\pageref * {⟨*label*⟩} Create an internal document reference, or just the unlinked number if starred, per hyperref.

```
\NewDocumentCommand{\LWR@new@pageref}{s m}{%
\IfBooleanTF{#1}%
{(\pagerefPageFor\LWR@print@ref{#2})}%
{(\cpageref{#2})}%
}
```

\nameref {⟨*label*⟩}

```
\newrobustcmd*{\nameref}[1]{%
\LWR@traceinfo{nameref}%
\LWR@startref{#1}%
\LWR@traceinfo{nameref B}%
\LWR@nameref{#1}%
\LWR@traceinfo{nameref C}%
\LWR@htmltag{/a}%
\LWR@traceinfo{nameref: done}%
}
```

\Nameref {⟨*label*⟩} In print, adds the page number. In HTML, does not.

```
\LetLtxMacro\Nameref\nameref
```

72.5 Hyper-references

⚠ Note that the code currently only sanitizes the underscore character. Additional characters should be rendered inert as well. See the hyperref.sty definition of \gdef\hyper@normalise for an example.

Pkg hyperref

⚠ Do not tell other packages that hyperref is emulated. Some packages patch various commands if hyperref is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

```
% DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:
% \EmulatesPackage{hyperref}[2015/08/01]% Disabled.  Do not do this.
```

Emulates hyperref:

\@currentHref Added to support backref.

```
\AtBeginDocument{
\def\@currentHref{%
autopage-\theLWR@currentautosec%
}
}
```

\LWR@subhyperref {⟨*URL*⟩}

Starts a link for \LWR@hrefb. A group must have been opened first, with nullified catcodes. The text name is printed afterwards, after the group is closed and catcodes restored.

```
\NewDocumentCommand{\LWR@subhyperref}{m}{%
\LWR@traceinfo{LWR@subhyperref !#1!}%
\LWR@sanitize{#1}%
\LWR@htmltag{%
    a href="\LWR@sanitized" % space
    target="\_{}blank" % space
}%
}
```

\LWR@subhyperreftext {⟨*text*⟩}

Finishes the hyperref for \LWR@hrefb. Catcodes must have been restored already. To be used after \LWR@subhyperref, and after its group has been closed.

```
\newcommand{\LWR@subhyperreftext}[1]{%
#1%
\LWR@htmltag{/a}%
\LWR@ensuredoingapar%
}
```

\LWR@subhyperrefclass {⟨*URL*⟩} {⟨*text*⟩} {⟨*htmlclass*⟩}

```
\NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
\LWR@htmltag{%
    a % space
    href="\begingroup\@sanitize#1\endgroup" % space
    class="#3" % space
}\LWR@orignewline%
#2\LWR@orignewline%
\LWR@htmltag{/a}%
\LWR@ensuredoingapar%
}
```

\href [⟨*options*⟩] {⟨*URL*⟩}

Create a link with accompanying text:

```
\DeclareDocumentCommand{\LWR@hrefb}{O{} m}{%
\LWR@ensuredoingapar%
\LWR@subhyperref{#2}%
\endgroup% restore catcodes
\LWR@subhyperreftext%
}

\newrobustcmd*{\href}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hrefb%
}
```

`\nolinkurl` {⟨*URL*⟩}

Print the name of the link without creating the link:

```
\newcommand*{\LWR@nolinkurlb}[1]{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\LWR@templink%
\endgroup%
}

\newrobustcmd*{\nolinkurl}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@nolinkurlb%
}
```

`\url` {⟨*URL*⟩}

Create a link whose text name is the address of the link.

The url package may redefine `\url`, so it is `\let` to `\LWR@urla`here and also redefined by lwarp-url.

```
\DeclareDocumentCommand{\LWR@urlb}{m}{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\href{\LWR@templink}{\LWR@templink}%
\endgroup%
```

```
}

\newrobustcmd*{\url}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@urlb%
}
```

\LWR@subinlineimage [⟨*alttag*⟩] {⟨*class*⟩} {⟨*filename*⟩} {⟨*extension*⟩} {⟨*style*⟩}

```
\newcommand*{\LWR@subinlineimage}[5][]{%
\ifblank{#1}%
{%
    \LWR@htmltag{img \LWR@indentHTML
        src="#3.#4" \LWR@indentHTML
        alt="#3" \LWR@indentHTML
        style="#5" \LWR@indentHTML
        class="#2" \LWR@orignewline
    }%
}%
{%
    \LWR@htmltag{img \LWR@indentHTML
        src="#3.#4" \LWR@indentHTML
        alt="#1" \LWR@indentHTML
        style="#5" \LWR@indentHTML
        class="#2" \LWR@orignewline
    }%
}%
}
```

```
\end{warpHTML}
```

Table 13: Float data structures

For each <type> of float (figure, table, etc.) there exists the following:

counter <type>: A counter called <type>, such as figure, table.

\<type>name: Name. \figurename prints "Figure", etc.

\ext@<type>: File extension. \ext@figure prints "lof", etc.

\fps@<type>: Placement.

\the<type>: Number. \thetable prints the number of the table, etc.

\p@<type>: Parent's number. Prints the number of the [within] figure, etc.

\fnum@<type>: Prints the figure number for the caption.
\<type>name \the<type>, "Figure 123".

\<type>: Starts the float environment. \figure or \begin{figure}

\end<type>: Ends the float environment. \endfigure or \end{figure}

\tf@<ext>: The LaTeX file identifier for the output file.

LWR@have<type>: A boolean remembering whether a \listof was requested for a float of this type.

File with extension lo<f,t,a-z>: An output file containing the commands to build the \listof<type> "table-of-contents" structure.

Cross-referencing names: For cleveref's \cref and related, \crefname and \Crefname assign human-readable names for references to this float type.

73 Floats

Floats are supported, although partially through emulation.

Table 13 shows the data structure associated with each <type> of float.

\@makecaption is redefined to print the float number and caption text, separated by \CaptionSeparator, which works with the babel package to adjust the caption separator according to the language. French, for example, uses an en-dash instead of a colon: "Figure 123 – Caption text".

73.1 Float environment

for HTML output:

```
\begin{warpHTML}
```

\LWR@floatbegin {⟨*type*⟩} [⟨*placement*⟩] Begins a \newfloat environment.

```
\NewDocumentCommand{\LWR@floatbegin}{m o}{%
\ifbool{FormatWP}{\newline}{}%
\LWR@stoppars
```

There is a new float, so increment the unique float counter:

```
\addtocounter{LWR@thisautoid}{1}%
\booltrue{LWR@freezethisautoid}%
```

```
\begingroup%
```

Settings while inside the environment:

```
\LWR@print@raggedright%
```

Open an HTML `figure` tag. The figure is assigned a `class` equal to its type, and another class according to the float package style, if used. Note that `\csuse` returns an empty string if `\LWR@floatstyle@<type>` is not defined.

```
\LWR@htmltag{%
    figure id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}" % space
    class="#1 \@nameuse{LWR@floatstyle@#1}"%
}%
\ifbool{FormatWP}{%
    \LWR@orignewline%
    \LWR@BlockClassWP{}{}{wp#1}%
}{}%
```

Update the caption type:

```
\renewcommand*{\@captype}{#1}%
\caption@settype{#1}%
```

Mark the float for a word processor conversion:

```
\LWR@startpars%
\ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

=== begin #1 ===

}{}%
```

Look for `\centering`, etc:

```
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
```

For koma-script. The following does not work for tables.

```
\AtBeginDocument{
\@ifpackageloaded{tocbasic}{
\appto\figure@atbegin{%
```

```
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
}{}
}
```

\@float
\@dlbfloat

Support packages which create floats directly.

```
\let\@float\LWR@floatbegin
\let\@dblfloat\LWR@floatbegin
```

\LWR@floatend

Ends a \newfloat environment.

```
\newcommand*{\LWR@floatend}{%
```

If saw a \centering, finish the center environment:

```
\LWR@endfloatalignment%
```

Mark the float end for a word processor conversion:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

=== end ===

}{}%
\LWR@stoppars%
```

Close an HTML figure tag:

```
\ifbool{FormatWP}{\endLWR@BlockClassWP}{}%
\LWR@htmlelementend{figure}%
\endgroup%
\boolfalse{LWR@freezethisautoid}%
\LWR@startpars%
\ifbool{FormatWP}{\newline}{}%
}
```

\end@float
\end@dlbfloat

Support packages which create floats directly.

```
\let\end@float\LWR@floatend
\let\end@dblfloat\LWR@floatend
```

73.2 Float tracking

Ctr LWR@thisautoid

A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
\newcounter{LWR@thisautoid}
```

Ctr LWR@thisautoidWP A sequential counter for all word processor conversion s. This is used to convince LibreOffice to form a frame around this element.

```
\newcounter{LWR@thisautoidWP}
```

Bool LWR@freezethisautoid Prevents multiple increments of \LWR@thisautoid inside a float.

```
\newbool{LWR@freezethisautoid}
\boolfalse{LWR@freezethisautoid}
```

\LWR@newautoidanchor Adds a new <autoid> anchor.

```
\newcommand*{\LWR@newautoidanchor}{%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{
    \ifbool{LWR@freezethisautoid}{}{%
        \addtocounter{LWR@thisautoid}{1}%
        \LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}%
            \LWR@htmltag{/a}%
    }%
}
}
```

\@captype Remembers which float type is in use.

```
\newcommand*{\@captype}{}
```

\LWR@floatalignmentname Set to center, flushleft, or flushright if saw \centering, \raggedright, or \raggedleft.

```
\newcommand*{\LWR@floatalignmentname}{}
```

\LWR@floatalignment If sees a \centering, \raggedleft, or \raggedright, creates a center, flushright, or flushleft environment.

```
\newcommand*{\LWR@floatalignment}{%
\ifdefstrequal{\LWR@mynexttoken}{\centering}{%
    \center%
    \renewcommand*{\LWR@floatalignmentname}{center}%
}{}%
\ifdefstrequal{\LWR@mynexttoken}{\raggedright}{%
    \flushleft%
    \renewcommand*{\LWR@floatalignmentname}{flushleft}%
}{}%
\ifdefstrequal{\LWR@mynexttoken}{\raggedleft}{%
    \flushright%
    \renewcommand*{\LWR@floatalignmentname}{flushright}%
}{}%
}
```

\LWR@endfloatalignment Closes an environment from \LWR@floatalignment.

```
\newcommand*{\LWR@endfloatalignment}{%
\ifdefvoid{\LWR@floatalignmentname}{}{\@nameuse{end\LWR@floatalignmentname}}%
\renewcommand*{\LWR@floatalignmentname}{}%
}
```

73.3 Caption inside a float environment

\CaptionSeparator How to separate the float number and the caption text.

```
\AtBeginDocument{\providecommand*{\CaptionSeparator}{:~}}
```

\@makecaption {⟨*name and num*⟩} {⟨*text*⟩}

Prints the float type and number, the caption separator, and the caption text.

```
\AtBeginDocument{\renewcommand{\@makecaption}[2]{%
    \LWR@traceinfo{@makecaption}%
    \LWR@isolate{#1}\CaptionSeparator\LWR@isolate{#2}%
    \LWR@traceinfo{@makecaption: done}%
}%
}
```

73.4 Caption and LOF linking and tracking

When a new HTML file is marked in the LaTeX PDF file, the LaTeX page number at that point is stored in LWR@latestautopage, (and the associated filename is remembered by the special LaTeX labels). This page number is used to generate an autopage HTML <id> in the HTML output at the start of the new HTML file. Meanwhile, there is a float counter used to generate an HTML autoid <id> at the start of the float itself in the HTML file. The autopage and autoid values to use for each float are written to the .lof, etc. files just before each float's entry. These values are used by \l@figure, etc. to create the HTML links in the List of Figures, etc.

Ctr LWR@nextautoid
Ctr LWR@nextautopage

Tracks autoid for floats. Tracks autopage for floats.

These are updated per float as the .lof, .lot file is read.

```
\newcounter{LWR@nextautoid}
\newcounter{LWR@nextautopage}
```

\LWRsetnextfloat {⟨*autopage*⟩} {⟨*float autoid*⟩}

File *_html.lof
File *_html.lot

This is written to the *_html.lof or *_html.lot file just before each float's usual entry. The autopage and the float's autoid are remembered for \l@figure to use when creating the HTML links.

```
\newcommand*{\LWRsetnextfloat}[2]{%
```

```
    \setcounter{LWR@nextautopage}{#1}%
    \setcounter{LWR@nextautoid}{#2}%
}
```

Ctr LWR@latestautopage

Updated each time a new HTML file is begun. \LWRsetnextfloat is written with this and the autoid by the modified \addcontentsline just before each float's entry.

```
\newcounter{LWR@latestautopage}
\setcounter{LWR@latestautopage}{1}
```

Env LWR@figcaption

An HTML <figcaption> is not allowed in places where LaTeX does allow a figure caption, such as inside a longtable where the tabular has already started, or inside a center environment. Therefore, a of class figurecaption is used instead.

```
\newenvironment*{LWR@figcaption}
    {
        \ifbool{FormatWP}{%
            \BlockClass[font-style:italic]{figurecaption}
%             \LWR@print@vspace*{\baselineskip}
        }{
            \BlockClass{figurecaption}
        }%
    }
    {\endBlockClass}
```

\LWR@HTML@caption@begin {⟨*type*⟩}

Low-level code to create HTML tags for captions.

The print versions are from the caption package.

```
\newcommand*{\LWR@HTML@caption@begin}[1]
{
\LWR@traceinfo{LWR@HTML@caption@begin}%
```

Keep par and minipage changes local:

```
\begingroup%
```

The caption code was not allowing the closing par tag:

```
\@setpar{\LWR@closeparagraph\@@par}%
```

No need for a minipage or \parbox inside the caption:

```
\RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{}%
\RenewDocumentCommand{\parbox}{O{t} O{} O{t} m +m}{##5}%
```

Enclose the original caption code inside an HTML tag:

```
\LWR@figcaption%
\LWR@traceinfo{LWR@HTML@caption@begin: about to LWR@origcaption@begin}%
```

```
\LWR@print@caption@begin{#1}%
\LWR@traceinfo{LWR@HTML@caption@begin: done}%
}
```

\LWR@HTML@caption@end Low-level patches to create HTML tags for captions.

```
\newcommand*{\LWR@HTML@caption@end}
{%
\LWR@traceinfo{LWR@HTML@caption@end}%
\LWR@print@caption@end%
```

Closing tag:

```
\endLWR@figcaption%
\endgroup%
% \leavevmode% avoid bad space factor (0) error
\LWR@traceinfo{LWR@HTML@caption@end: done}%
}
```

\caption@begin
\caption@end
Low-level patches to create HTML tags for captions. These are assigned \AtBeginDocument so that other packages which modify captions will have already been loaded before saving the print-mode version.

```
\AtBeginDocument{
\LWR@formatted{caption@begin}
\LWR@formatted{caption@end}
}
```

\captionlistentry Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```
\let\LWR@origcaptionlistentry\captionlistentry

\renewcommand*{\captionlistentry}{%
\LWR@ensuredoingapar%
\LWR@origcaptionlistentry%
}

\def\LWR@LTcaptionlistentry{%
\LWR@ensuredoingapar%
\LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
  \bgroup
  \@ifstar{\egroup\LWR@LT@captionlistentry}% gobble *
          {\egroup\LWR@LT@captionlistentry}}%
\def\LWR@LT@captionlistentry#1{%
  \caption@listentry\@firstoftwo[\LTcaptype]{#1}}%
```

\addcontentsline Patched to write the autopage and autoid before each float's entry. No changes if writing .toc For a theorem, automatically defines \ext@<type> as needed, to mimic and reuse the float mechanism.

f

```
\let\LWR@origaddcontentsline\addcontentsline

\renewcommand*{\addcontentsline}[3]{%
\ifstrequal{#1}{toc}{}{% not TOC

\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {}%
    {\LWR@newautoidanchor}%

    \ifcsvoid{ext@#2}{\csdef{ext@#2}{#1}}{}%

    \addtocontents{\@nameuse{ext@#2}}{%
        \protect\LWRsetnextfloat%
        {\arabic{LWR@latestautopage}}%
        {\arabic{LWR@thisautoid}}%
    }%
}% not TOC
\LWR@origaddcontentsline{#1}{#2}{#3}%
}
```

Pkg capt-of
Pkg caption

Either package provides `\captionof`, which is later patched at the beginning of the document.

`\captionof` Patched to handle paragraph tags.

```
\AtBeginDocument{
\let\LWR@origcaptionof\captionof

\renewcommand*{\captionof}{%
\LWR@stoppars
\LWR@origcaptionof%
}
}

\end{warpHTML}
```

74 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The `.toc`, `.lof`, and `.lot` files are named by the source code `\jobname`.

In HTML, the printed tables are placed inside a `<div>` of class `toc`, `lof`, or `lot`.

A "sidetoc" is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular LaTeX infrastructure is used for TOC, along with some patches to generate HTML output.

for HTML output:
```
\begin{warpHTML}
```

74.1 Reading and printing the TOC

`\LWR@myshorttoc` {⟨*toc/lof/lot/sidetoc*⟩}

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the `@` character into a normal letter to allow formatting commands in the section names.

Unlike in regular LaTeX, the file is not reset after being read, since the sideTOC may be referred to again in each HTML page.

```
\newcommand*{\LWR@myshorttoc}[1]{%
\LWR@traceinfo{LWR@myshorttoc: #1}%
\LWR@ensuredoingapar%
```

Only if the file exists:

```
\IfFileExists{\jobname.#1}{%
\LWR@traceinfo{LWR@myshorttoc: loading}%
```

⚠ Many of the commands in the file will have `@` characters in them, so `@` must be made a regular letter.

```
\begingroup%
\makeatletter%
```

Read in the TOC file:

```
\@input{\jobname.#1}%
\endgroup%
}%
{}%
\LWR@traceinfo{LWR@myshorttoc: done}%
}
```

`\LWR@subtableofcontents` {⟨*toc/lof/lot*⟩} {⟨*sectionstarname*⟩}

Places a TOC/LOF/LOT at the current position.

```
\NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
\@ifundefined{chapter}
{\LWR@closeprevious{\LWR@depthsection}}
{\LWR@closeprevious{\LWR@depthchapter}}
```

Prints any pending footnotes so that they appear above the potentially large TOC:

```
\LWR@printpendingfootnotes
```

Place the list into its own chapter (if defined) or section:

```
\@ifundefined{chapter}{\section*{#2}}{\chapter*{#2}}
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
\LWR@htmlelementclass{nav}{#1}
```

Create the actual list:

```
\LWR@myshorttoc{#1}
```

Close the nav:

```
\LWR@htmlelementclassend{nav}{#1}
}
```

`\@starttoc` {⟨*ext*⟩}

Patch `\@starttoc` to encapsulate the TOC inside HTML tags:

```
\let\LWR@orig@starttoc\@starttoc

\renewcommand{\@starttoc}[1]{
\LWR@htmlelementclass{nav}{#1}
\LWR@orig@starttoc{#1}
\LWR@htmlelementclassend{nav}{#1}
}
```

Bool `LWR@copiedsidetoc` Used to only copy the TOC file to the sidetoc a single time.

(listings and perhaps other packages would re-use `\tableofcontents` for their own purposes, causing the sidetoc to be copied more than once, and thus end up empty.)

```
\newbool{LWR@copiedsidetoc}
\boolfalse{LWR@copiedsidetoc}
```

`\tableofcontents` Patch `\tableofcontents`, etc. to print footnotes first. newfloat uses `\listoffigures` for all future float types.

```
\AtBeginDocument{
\let\LWR@origtableofcontents\tableofcontents

\renewcommand*{\tableofcontents}{%
```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkTOC}}{

=== table of contents ===

```

```
}
{
```

Copy the `.toc` file to `.sidetoc` for printing the sideTOC. The original `.toc` file is renewed when `\tableofcontents` is finished.

```
    \ifbool{LWR@copiedsidetoc}{}{%
        \LWR@copyfile{\jobname.toc}{\jobname.sidetoc}%
        \booltrue{LWR@copiedsidetoc}%
    }%
    \LWR@printpendingfootnotes
    \LWR@origtableofcontents
}
}% \tableofcontents
}% AtBeginDocument
```

`\listoffigures`

```
\let\LWR@origlistoffigures\listoffigures

\renewcommand*{\listoffigures}{
\ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{

=== list of figures ===

}
{
    \LWR@printpendingfootnotes
    \LWR@origlistoffigures
}
}
```

`\listoftables`

```
\let\LWR@origlistoftables\listoftables

\renewcommand*{\listoftables}{
\ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{

=== list of tables ===

}
{
    \LWR@printpendingfootnotes
    \LWR@origlistoftables
}
}
```

74.2 High-level TOC commands

`\listof` {⟨*type*⟩} {⟨*title*⟩}

Emulate the \listof command from the float package (section 226). Used to create lists of custom float types. Also used to redefine the standard LaTeX \listoffigures and \listoftables commands.

```
\NewDocumentCommand{\listof}{m +m}{%
\@ifundefined{l@#1}{%
    \csdef{l@#1}##1##2{\hypertocfloat{1}{#1}{\@nameuse{ext@#1}}{##1}{##2}}%
}{}%
\LWR@subtableofcontents{\@nameuse{ext@#1}}{#2}
\expandafter\newwrite\csname tf@\csname ext@#1\endcsname\endcsname
\immediate\openout \csname tf@\csname ext@#1\endcsname\endcsname
    \jobname.\@nameuse{ext@#1}\relax
}
```

74.3 Side TOC

The "side TOC" is a table-of-contents positioned to the side.

It may be renamed by redefining \sidetocname, and may contain paragraphs.

CSS may be used to format the sideTOC:

CSS related to sideTOC:

div.sidetoccontainer: The entire sideTOC.
div.sidetoctitle: The title.
div.sidetoccontents: The table of contents.

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Ctr SideTOCDepth Controls how deep the side-TOC gets. Use a standard LaTeX section level similar to tocdepth.

```
\newcounter{SideTOCDepth}
\setcounter{SideTOCDepth}{1}
```

\sidetocname Holds the default name for the sideTOC.

```
\newcommand{\sidetocname}{Contents}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@sidetoc Creates the actual side-TOC.

```
\newcommand*{\LWR@sidetoc}{
\LWR@forcenewpage
\LWR@stoppars

```

The entire sideTOC is placed into a nav of class sidetoc.

```
\LWR@htmlelementclass{div}{sidetoccontainer}
\LWR@htmlelementclass{nav}{sidetoc}

\setcounter{tocdepth}{\value{SideTOCDepth}}

```

The title is placed into a of class sidetoctitle, and may contain paragraphs.

```
\begin{BlockClass}{sidetoctitle}
\ifcsvoid{thetitle}{}{\InlineClass{sidetocthetitle}{\thetitle}\par}
\sidetocname
\end{BlockClass}
```

The table of contents is placed into a of class sidetoccontents.

```
\begin{BlockClass}{sidetoccontents}
\LinkHome

\LWR@myshorttoc{sidetoc}
\end{BlockClass}
\LWR@htmlelementclassend{nav}{sidetoc}
\LWR@htmlelementclassend{div}{sidetoccontainer}
}
```

74.4 Low-level TOC line formatting

\numberline {⟨*number*⟩}

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```
\newcommand*{\LWR@numberline}[1]{%
\LWR@sectionnumber{#1}\quad%
}

\LetLtxMacro\numberline\LWR@numberline
```

\LWR@maybetocdata Replaced by tocdata. Adds author name.

```
\newcommand*{\LWR@maybetocdata}{}
```

\hypertoc {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: name*⟩} {⟨*4: page*⟩}

Called by \l@section, etc. to create a hyperlink to a section.

The autopage label is always created just after the section opens.

#1 is depth

#2 is section, subsection, etc.

#3 the text of the caption

#4 page number

```
\NewDocumentCommand{\hypertoc}{m m +m m}{%
\LWR@traceinfo{hypertoc !#1!#2!#3!#4!}%
```

Respond to tocdepth:

```
\ifthenelse{\cnttest{#1}{<=}{\value{tocdepth}}}%
    {%
        \LWR@startpars%
```

Create an HTML link to <filename>#autosec-(page), with the name, of the given HTML class.

```
        \LWR@subhyperrefclass{%
            \LWR@htmlrefsectionfilename{autopage-#4}%
                \LWR@origpound\LWR@print@mbox{autosec-#4}%
        }{#3}{toc#2}%

        \LWR@maybetocdata%

        \LWR@stoppars%
    }%
    {}%
\LWR@traceinfo{hypertoc done}%
}
```

Ctr lofdepth TOC depth for figures.

```
\@ifclassloaded{memoir}{}{
\newcounter{lofdepth}
\setcounter{lofdepth}{1}
}
```

Ctr lotdepth TOC depth for tables.

```
\@ifclassloaded{memoir}{}{
\newcounter{lotdepth}
\setcounter{lotdepth}{1}
}
```

\hypertocfloat {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: ext of parent*⟩} {⟨*4: caption*⟩} {⟨*5: page*⟩}

#1 is depth

#2 is figure, table, etc.

#3 is lof, lot, of the parent.

#4 the text of the caption

#5 page number

```
\newcommand{\hypertocfloat}[5]{%
\LWR@startpars
```

If some float-creation package has not yet defined the float type's lofdepth counter, etc, define it here:

```
\@ifundefined{c@#3depth}{%
\newcounter{#3depth}%
\setcounter{#3depth}{1}%
}{}%
```

Respond to lofdepth, etc.:

```
\LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%
\ifthenelse{\cnttest{#1}{<=}{\arabic{#3depth}}}%
    {%
        \LWR@startpars%
```

Create an HTML link to filename#autoid-(float number), with text of the caption, of the given HTML class.

```
        \LWR@subhyperrefclass{%
        \LWR@htmlrefsectionfilename{autopage-\arabic{LWR@nextautopage}}%
        \LWR@origpound\LWR@print@mbox{autoid-\arabic{LWR@nextautoid}}}%
        {#4}{toc#2}%

        \LWR@maybetocdata%

        \LWR@stoppars%
    }%
    {}%
}
```

Automatically called by \contentsline:

\l@part {⟨*name*⟩} {⟨*page*⟩}

Uses \DeclareDocumentCommand in case the class does not happen to have a \part.

```
\DeclareDocumentCommand{\l@part}{m m}{\hypertoc{-1}{part}{#1}{#2}}
```

\l@chapter {⟨*name*⟩} {⟨*page*⟩}

Uses \DeclareDocumentCommand in case the class does not happen to have a \chapter.

```
\@ifundefined{chapter}
{}
{
\DeclareDocumentCommand{\l@chapter}{m m}
    {\hypertoc{0}{chapter}{#1}{#2}}
}
```

\l@section {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
```

\l@subsection {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
```

\l@subsubsection {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsubsection}[2]{\hypertoc{3}{subsubsection}{#1}{#2}}
```

\l@paragraph {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}
```

\l@subparagraph {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}
```

\l@figure {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}
```

\l@table {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}
```

```
\end{warpHTML}
```

75 Index and glossary

See:
http://tex.stackexchange.com/questions/187038/
how-to-mention-section-number-in-index-created-by-imakeidx

Index links are tracked by the counter LWR@autoindex. This counter is used to create a label for each index entry, and a reference to this label for each entry in the index listing. This method allows each index entry to link directly to its exact position in the document.

for HTML output:

```
\begin{warpHTML}
```

```
\newcounter{LWR@autoindex}
\setcounter{LWR@autoindex}{0}

\newcounter{LWR@autoglossary}
\setcounter{LWR@autoglossary}{0}
```

Env theindex

```
\@ifundefined{chapter}
{\newcommand*{\LWR@indexsection}[1]{\section*{#1}}}
{\newcommand*{\LWR@indexsection}[1]{\chapter*{#1}}}

\AtBeginDocument{
\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

\LWR@indexitem [⟨*index key*⟩] The optional argument is added to support repeatindex.

```
\newcommand{\LWR@indexitem}[1][\@empty]{

\InlineClass{indexitem}{}#1%
}
```

\LWR@indexsubitem

```
\newcommand{\LWR@indexsubitem}{

\InlineClass{indexsubitem}{}
}
```

\LWR@indexsubsubitem

```
\newcommand{\LWR@indexsubsubitem}{

\InlineClass{indexsubsubitem}{}
}
```

\@wrindex {⟨*term*⟩} Redefined to write the LWR@autoindex counter instead of page.

```
\def\LWR@wrindex#1{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
\protected@write\@indexfile{}%
{\string\indexentry{#1}{\arabic{LWR@autoindex}}}%
\endgroup
\@esphack}

\AtBeginDocument{
\let\@wrindex\LWR@wrindex
}
```

`\@wrglossary` {⟨*term*⟩} Redefined to write the `LWR@latestautopage` counter instead of `page`.

```
\def\@wrglossary#1{%
\addtocounter{LWR@autoglossary}{1}%
\LWR@new@label{LWRglossary-\theLWR@autoglossary}%
\protected@write\@glossaryfile{}%
{\string\glossaryentry{#1}{\theLWR@autoglossary}}%
\endgroup
\@esphack}
```

`\LWR@indexnameref` {⟨*LWR@autoindex*⟩}

Creates a hyperlink based on the given entry's autoindex.

```
\newcommand*{\LWR@indexnameref}[1]{\nameref{LWRindex-#1}}
```

`\LWR@doindexentry` {⟨*LWR@autoindex, or macros.*⟩}

Creates a hyperlink, or handles `\see`, `\textbf`, etc.

```
\newrobustcmd{\LWR@doindexentry}[1]{%
\IfInteger{#1}%
    {\LWR@indexnameref{#1}}%
    {#1}%
}
```

`\LWR@hyperindexrefnullified` Handles macros commonly seen inside an `\index` entry. Each macro is redefined to create and format a link to its entry.

⚠ index formatting To handle additional macros:

```
\appto\LWR@hyperindexrefnullified{. . . }
```

```
\newcommand{\LWR@hyperindexrefnullified}{%
\renewrobustcmd{\emph}[1]{\LWR@HTML@emph{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textbf}[1]{\LWR@HTML@textbf{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textrm}[1]{\LWR@HTML@textrm{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsf}[1]{\LWR@HTML@textsf{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\texttt}[1]{\LWR@HTML@texttt{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textup}[1]{\LWR@HTML@textup{\LWR@doindexentry{##1}}}%
```

```
\renewrobustcmd{\textsc}[1]{\LWR@HTML@textsc{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsi}[1]{\LWR@HTML@textsi{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textit}[1]{\LWR@HTML@textit{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsl}[1]{\LWR@HTML@textsl{\LWR@doindexentry{##1}}}%
}
```

\hyperindexref {⟨*LWR@autoindex*⟩}

\hyperindexref{LWR@autoindex} is inserted into *.ind by the makeindex style file lwarp.ist or the xindy style file lwarp.xdy.

```
\newcommand{\hyperindexref}[1]{%
```

In long index lines with numerous entries, *makeindex* can insert a newline before the page number, resulting in an extra space before the first digit. If the first character is a space, remove it first.

```
\def\LWR@tempone{#1}%
\IfBeginWith{\LWR@tempone}{ }{%
    \StrGobbleLeft{\LWR@tempone}{1}[\LWR@tempone]%
}{}%
```

If a numeric entry, create a link. If not numeric, such as \see, use the entry as-is. \emph, \textit, etc. have been redefined above to create and format the entry.

```
\IfInteger{\LWR@tempone}%
    {\LWR@indexnameref{\LWR@tempone}}%
    {%
        \begingroup%
        \LWR@hyperindexrefnullified
        #1%
        \endgroup%
    }%
}
```

```
\end{warpHTML}
```

for PRINT output: A null command for print mode, in case hyperref was not used:

```
\begin{warpprint}
\newcommand{\hyperindexref}[1]{#1}
\end{warpprint}
```

for HTML & PRINT: For the glossaries package, try to prevent an error where \glo@name was not found:

```
\begin{warpall}
\providecommand{\glo@name}{}
\end{warpall}
```

76 Bibliography presentation

for HTML output:
```
\begin{warpHTML}
```

\bibliography {⟨*filenames*⟩}

Modified to use the base jobname instead of the _html jobname.

```
\def\bibliography#1{%
    \if@filesw
    \immediate\write\@auxout{\string\bibdata{#1}}%
    \fi
%     \@input@{\jobname.bbl}% original
    \begingroup%
    \@input@{\BaseJobname.bbl}% lwarp
    \endgroup%
}
```

\@biblabel {⟨*text-refnumber*⟩}

```
\renewcommand{\@biblabel}[1]{[#1]\quad}
```

Env thebibliography To emphasize document titles in the bibliography, the following redefines \em inside thebibliography to gather everything until the next closing brace, then display these tokens with \textit.

Adapted from embracedef.sty, *which is by* Takayuki YATO*:*
https://gist.github.com/zr-tex8r/b72555e3e7ad2f0a37f1

```
\AtBeginDocument{
\AtBeginEnvironment{thebibliography}{
\providecommand*{\LWR@newem}[1]{\textit{#1}}

\renewrobustcmd{\em}{%
  \begingroup
    \gdef\LWR@em@after{\LWR@em@finish\LWR@newem}%
    \afterassignment\LWR@em@after
    \toks@\bgroup
}

\def\LWR@em@finish#1{%
    \xdef\LWR@em@after{\noexpand#1{\the\toks@}}%
  \endgroup
  \LWR@em@after\egroup
}
}% \AtBeginEnvironment{thebibliography}
}% \AtBeginDocument

\end{warpHTML}
```

77 Restoring original formatting

\LWR@restoreorigformatting

Used to temporarily restore the print-mode meaning of a number of formatting, graphics, and symbols-related macros while generating SVG math or a `lateximage`.

Must be used inside a group.

Sets `\LWR@formatting` to `print` until the end of the group.

A number of packages will `\appto` additional actions to this macro.

Various packages add to this macro using `\appto`.

for HTML output:

```
\begin{warpHTML}
```

```
\newcommand*{\LWR@restoreorigformatting}{%
\LWR@traceinfo{LWR@restoreorigformatting}%
```

Numerous macros change their print/HTML meaning depending on `\LWR@formatting`:

```
\renewcommand*{\LWR@formatting}{print}%
\linespread{1}%
```

```
\let\par\LWR@origpar%
```

```
\LWR@select@print@hspace%
```

```
\LetLtxMacro\hfil\LWR@orighfil%
\let\hss\LWR@orighss%
\let\llap\LWR@origllap%
\let\rlap\LWR@origrlap%
\let\hfilneg\LWR@orighfilneg%
```

```
\let\,\LWR@origcomma% disable HTML short unbreakable space
\let\thinspace\LWR@origthinspace% disable HTML short unbreakable space
\let\negthinspace\LWR@orignegthinspace% disable HTML negative short unbreakable space
\let\textellipsis\LWR@origtextellipsis%
\let\textless\LWR@origtextless%
\let\textgreater\LWR@origtextgreater%
\LetLtxMacro\rmfamily\LWR@origrmfamily%
\LetLtxMacro\sffamily\LWR@origsffamily%
\LetLtxMacro\ttfamily\LWR@origttfamily%
\LetLtxMacro\bfseries\LWR@origbfseries%
\LetLtxMacro\mdseries\LWR@origmdseries%
\LetLtxMacro\upshape\LWR@origupshape%
\LetLtxMacro\slshape\LWR@origslshape%
\LetLtxMacro\scshape\LWR@origscshape%
```

```
\LetLtxMacro\sishape\LWR@origsishape%
```

```
\LetLtxMacro\itshape\LWR@origitshape%
```

```
\LetLtxMacro\em\LWR@origem%
\LetLtxMacro\normalfont\LWR@orignormalfont%
\let\sp\LWR@origsp%
\let\sb\LWR@origsb%
\LetLtxMacro\textsuperscript\LWR@origtextsuperscript%
\LetLtxMacro\@textsuperscript\LWR@orig@textsuperscript%
\LetLtxMacro\textsubscript\LWR@origtextsubscript%
\LetLtxMacro\@textsubscript\LWR@orig@textsubscript%
\LetLtxMacro\underline\LWR@origunderline%
\let~\LWR@origtilde%
\let\enskip\LWR@origenskip%
\let\quad\LWR@origquad%
\let\qquad\LWR@origqquad%
```

`\endtabular` must be restored to its original, instead of relying on lwarp's `\LWR@formatted` mechanism:

```
\LetLtxMacro\endtabular\LWR@origendtabular%
\csletcs{endtabular*}{LWR@origendtabular*}%
```

```
\LetLtxMacro\noalign\LWR@orignoalign%
\LetLtxMacro\hline\LWR@orighline%
```

```
\let\newline\LWR@orignewline%
\LetLtxMacro\includegraphics\LWR@origincludegraphics%
\let\TeX\LWR@origTeX%
\let\LaTeX\LWR@origLaTeX%
\let\LaTeXe\LWR@origLaTeXe%
\renewcommand*{\Xe}{X\textsubscript{E}}%
```

```
\LetLtxMacro\@ensuredmath\LWR@origensuredmath%
%
\LWR@restoreorigaccents%
\LWR@restoreoriglists%
%
\LWR@FBcancel%
}
```

```
\end{warpHTML}
```

78 Math

78.1 Limitations

78.1.1 Math in section names

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

78.1.2 Rendering tradeoffs

Math rendering

Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.

SVG files

Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline

The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files

Others LaTeX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML

Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 11 regarding EPUB output with MATHJAX.

78.1.3 SVG option

SVG math option

For SVG math, math is rendered as usual by LaTeX into the initial PDF file using the current font[18], then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LaTeX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the LaTeX code which generated the math, allowing copy/paste of the LaTeX math expression into other documents.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

[18] See section 499 regarding fonts and fractions.

SVG math copy/paste

For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the LaTeX code for the math expression. For $\mathcal{AMS}$ environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred $\mathcal{AMS}$ environment, although the `\tag` macro will still appear inside the LaTeX math expression.

⚠ SVG math in TeX boxes

SVG math does not work inside TeX boxes, since a `\newpage` is required before and after each image.

78.1.4 MathJax option

MathJax math option

Prog MathJax

The popular MathJax alternative (`mathjax.org`) may be used to display math.

When MathJax is enabled, math is rendered twice:

1. As regular LaTeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LaTeX, and
2. As detokenized printed LaTeX commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current LaTeX values, and the MathJax cross-referencing system is ignored in favor of the LaTeX internal system, seamlessly integrating with the rest of the LaTeX code.

78.1.5 Customizing MathJax

MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

78.1.6 MathJax limitations

MathJax limitations

Prog MathJax

Limitations when using MathJax include:

subequations

- MathJax itself does not support subequations. This may be improved by parsing the LaTeX math expression to manually insert tags, but this has not yet been done.

footnotes in math

- Footnotes inside equations are not yet supported while using MathJax.

lateximage

- Math appearing inside a lateximage, and therefore also inside a Ti*k*z or `picture` environment, is rendered as SVG math even if MathJax is used in the rest of the document.

siunitx

⚠ siunitx inside an equation

- Usage of siunitx inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

  https://github.com/burnpanck/MathJax-siunitx

  Also see section 9.7.11.

tabbing

- A `tabbing` environment is emulated using an HTML `<pre>`.While MathJax is enabled inside `tabbing`, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

⚠ other macros and packages

- Other math-related macros and packages are not supported by MathJax, including `\ensuremath` and bigdelim, along with occasionally-used macros such as `\relax`. lwarp emulates footnotes, units, and nicefrac for MathJax.

78.1.7 Catcode changes

preamble macros with math

The math shift character `$` is not set for HTML output until after the preamble. Macros defined in the preamble which contain `$` must be enclosed between `\StartDefiningMath` and `\StopDefiningMath` to temporarily change to the HTML meaning of `$`:

```
\StartDefiningMath
\newcommand{. . . }
\StopDefiningMath
```

As an alternative, use `\(` and `\)` instead of `$`, in which case `\StartDefiningMath` and `\StopDefiningMath` are not necessary.

If a package defines macros using `$`, it may be nessary to use `\StartDefiningMath` and `\StopDefiningMath` before and after loading the package.

78.1.8 Complicated inline math objects

`\inlinemathnormal`
`\inlinemathother`

changing contents

complicated `alt` tag

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as `$x+1$`, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an `alt` tag. The macro `\inlinemathother` may be used before a dynamic math expression, and `\inlinemathnormal` after. Doing so tells lwarp to use an unhashed SVG math image, even if MathJax is in use. See section 44.

78.1.9 Complicated display math objects

\displaymathnormal

By default, or when selecting \displaymathnormal, MATHJAX math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother
MathJax unsupported complicated alt tag

When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MATHJAX and will not make sense as an HTML alt tag. In this mode, MATHJAX is turned off, math display environments become SVG images, even if MATHJAX is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

78.2 HTML alt tag names

Redefinable names for the HTML alt tags, for translation according to the reader's native language.

for HTML & PRINT:

```
\begin{warpall}
```

\mathimagename
Default: ``math image''

The HTML alt tag for an SVG math image.

```
\newcommand*{\mathimagename}{math image}
```

\packagediagramname
Default: ``diagram''

Appended to the lateximage HTML alt tag for the images generated by many packages.

```
\newcommand*{\packagediagramname}{diagram}
```

```
\end{warpall}
```

78.3 Inline and display math

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@externalfilecnt

Counter for the external files which are generated and then referenced from the HTML:

```
\newcounter{LWR@externalfilecnt}
```

Bool LWR@indisplaymathimage

True if processing display math for SVG output. Inside a lateximage, display math is only set to print-mode output if LWR@indisplaymathimage is false. Used to avoid nullifying display math before it has been completed.

```
\newbool{LWR@indisplaymathimage}
```

Bool LWR@xfakebold True if xfakebold \setBold is in use.

```
\newbool{LWR@xfakebold}
\boolfalse{LWR@xfakebold}
```

\LWR@orig@setBold Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@orig@setBold}{}
```

\LWR@orig@unsetBold Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@orig@unsetBold}{}
```

\LWR@applyxfakebold Redefined by lwarp-xfakebold.

```
\newcommand*{\LWR@applyxfakebold}{}
```

\$ Plain dollar signs appearing in the HTML output may be interpreted by MathJax to be math shifts. For a plain text dollar \$, use an HTML entity to avoid it being interpreted by MathJax, unless are inside a lateximage, in which case it will not be seen by MathJax.

```
\let\LWR@origtextdollar\$

\renewcommand*{\$}{%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{\LWR@origtextdollar}%
{\HTMLentity{dollar}}%
}
```

File lwarp_baseline_marker.png File lwarp_baseline_marker.eps A marker to be used to help *pdfcrop* identify the inline math baseline and width. If either graphicx or graphics is loaded, this marker is placed at the lower left and lower right corners of the inline math. *pdfcrop* is then able to identify the width of the image, and also the height of an image such as a horizontal dash which does not otherwise touch the baseline.

A marker with alpha or opacity of 0% is not registered by *pdfcrop*, so the marker is a small square block of 1% alpha, which seems to work while still being effectively invisible in the final SVG image.

If graphicx is loaded, this marker is sized as a tiny 1 sp square. If graphics is loaded, this marker is used at its default size of around .25 pt. If neither graphics package is loaded, the marker is replaced by a 10 sp horizontal space, and there is no assistance for determining baseline or width of the inline math image. The best results are obtained when using graphicx.

\LWR@addbaselinemarker Places a small marker in an SVG inline image. If graphics or graphicx are loaded, the marker is a mostly transparent image. If neither is loaded, no marker is used.

```
\AtBeginDocument{
```

```
\ifpdf
    \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
\else
    \ifXeTeX
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
    \else
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.eps}
    \fi
\fi

\IfFileExists{\LWR@baselinename}%
{
    \@ifpackageloaded{graphicx}{
        \newcommand*{\LWR@addbaselinemarker}{%
            \LWR@origincludegraphics{\LWR@baselinename}%
        }
    }{
        \@ifpackageloaded{graphics}{
            \newcommand*{\LWR@addbaselinemarker}{%
                \LWR@origincludegraphics{\LWR@baselinename}%
            }
        }{
            \PackageWarning{lwarp}{Load graphicx or graphics
                for improved SVG math baselines,}
            \newcommand*{\LWR@addbaselinemarker}{}
        }
    }
}{% lwarp_baseline_marker.png or .eps is not present
   \PackageWarning{lwarp}{File \LWR@baselinename\space is not installed alongside
        the lwarp-*.sty files, so SVG math baselines may not be accurate,}
    \newcommand*{\LWR@addbaselinemarker}{}
}

}% AtBeginDocument
```

`\LWR@subsingledollar` * {⟨*2: alt text*⟩} {⟨*3: add'l hashing*⟩} {⟨*4: math expression*⟩}

For inline math. Uses MathJax, or for SVG math the image is measured and ajusted to the baseline of the HTML output, and placed inside a `latexi`mage.

image filename hashing

If starred, a hashed filename is used.If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing

argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

```
\newlength{\LWR@singledollarwidth}
\newlength{\LWR@singledollarheight}
\newlength{\LWR@singledollardepth}

\newsavebox{\LWR@singledollarbox}

\NewDocumentCommand{\LWR@subsingledollar}{s m m m}{%
\LWR@traceinfo{LWR@subsingledollar}%
```

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{%
\LWR@traceinfo{LWR@subsingledollar: already in a lateximage}%
    #4% contents
}%
{% not in a lateximage
\begingroup%
```

Support for xfakebold:

```
\LWR@applyxfakebold%
```

MathJax cannot parse the often complicated TEX expressions which appear in the various uses of `\ensuredmath`. `\ensuremath` forces the `alt` tag to "`(math image)`", as translated according to `\mathimagename`. If this is the case, force the use of a `lateximage` even if MathJax. Likewise for siunitx if `parse-numbers=false`.

If MathJax, or if formatting math for a word processor, and not `\ensuredmath`, and not a dynamic math expression, print the math expression:

```
\ifboolexpr{%
    (
        bool{mathjax} or
        ( bool{FormatWP} and bool{WPMarkMath} )
    ) and
    ( not test { \ifstrequal {#2} {(\mathimagename)} } ) and % from \ensuredmath
    ( not bool{LWR@dynamicmath} )
}%
```

For MATHJAX, print the math between `\(` and `\)`:

```
{%
    \LWR@traceinfo{LWR@subsingledollar: Mathjax}%
    {\textbackslash(\LWR@HTMLsanitize{#4}\textbackslash)}%
}% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the LATEX code, and a css style to control the baseline adjustment.

```
{% not mathjax
\LWR@traceinfo{LWR@subsingledollar: NOT mathjax, or is ensuremath, or is dynamic}%
```

Measure the depth, width, and height of the math image:

```
\begingroup%
```

Temporarily disable formatting while measuring the image parameters:

```
\LWR@restoreorigformatting%
\RenewDocumentEnvironment{lateximage}{s o o o}{}{}% inside group
\LWR@print@normalsize%
```

Temporarily set font for the HTML PDF output:

```
\LWR@traceinfo{Using font family \LWR@f@family}%
\@nameuse{LWR@orig\LWR@f@family family}%
\LWR@traceinfo{Using font series \LWR@f@series}%
\@nameuse{LWR@orig\LWR@f@series series}%
\LWR@traceinfo{Using font shape \LWR@f@shape}%
\@nameuse{LWR@orig\LWR@f@shape shape}%
```

`lateximagedepth` must be nested to avoid generating paragraph tags. $\mathcal{AMS}$ math modifies the `\text` macro such that `\addtocounter` does not always occur as expected. Lower-level code is used instead.

```
\global\advance\c@LWR@lateximagedepth 1\relax%
```

Typeset and save the contents, depending on how they were generated:

SVG math: `\LWR@origensuredmath` is part of argument #4.

SVG math `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

SVG dynamic math: `\LWR@origensuredmath` is part of argument #4.

Mathjax: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`. This case is handled above.

Mathjax `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

Mathjax dynamic math: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`, so `\LWR@origensuredmath` is added below.

`\ifmmode`: Included "just in case".

```
\ifmmode%
    \global\sbox{\LWR@singledollarbox}{#4}%
\else%
    \ifbool{LWR@dynamicmath}{%
        \ifbool{mathjax}{%
            \global\sbox{\LWR@singledollarbox}{\LWR@origensuredmath{#4}}%
        }{%
            \global\sbox{\LWR@singledollarbox}{#4}%
        }%
    }{%
        \global\sbox{\LWR@singledollarbox}{#4}%
```

```
        }%
    \fi%
```

Add a small and almost transparent marker at the depth of the image.

A math minus sign has the same depth as a plus, even though it does not draw anything below the baseline. This means that *pdfcrop* would crop the image without depth. The marker below the baseline is seen by *pdfcrop* and preserves the depth.

```
    \global\sbox{\LWR@singledollarbox}{%
        \usebox{\LWR@singledollarbox}%
        \raisebox{-\dp\LWR@singledollarbox}{%
            \LWR@addbaselinemarker%
        }%
    }%
```

More low-level code to undo the counter change.

```
    \global\advance\c@LWR@lateximagedepth -1\relax% Due to AmS \text macro.
```

Measure the depth:

```
    \setlength{\LWR@singledollardepth}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
```

Make the length a global change:

```
    \global\LWR@singledollardepth=\LWR@singledollardepth%
```

Likewise for width:

```
    \setlength{\LWR@singledollarwidth}{%
        \LateximageFontScale\wd\LWR@singledollarbox%
    }%
    \global\LWR@singledollarwidth=\LWR@singledollarwidth%
```

Likewise for total height:

```
    \setlength{\LWR@singledollarheight}{%
        \LateximageFontScale\ht\LWR@singledollarbox%
    }%
    \addtolength{\LWR@singledollarheight}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
    \global\LWR@singledollarheight=\LWR@singledollarheight%

    \endgroup%
```

Set a style for the the height or width. The `em` unit is used so that the math scales according to the user's selected font size.

Start with the greater of the width or the height, biased towards the width:

```
\ifdimgreater{\LWR@singledollarwidth}{.7\LWR@singledollarheight}{%
    \def\LWR@singledollarstyle{%
        width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
    }%
}{%
    \def\LWR@singledollarstyle{%
        height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
    }%
}%
```

If a very narrow width, use the height.

```
\ifdimless{\LWR@singledollarwidth}{.2em}%
{%
    \def\LWR@singledollarstyle{%
        height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
    }%
}%
{}%
```

If very wide and short, use the width:

```
\ifdimless{\LWR@singledollarheight}{.2em}%
{%
    \def\LWR@singledollarstyle{%
        width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
    }%
}%
{}%
```

If there is significant text depth, add the depth to the style.

```
\ifdimgreater{\LWR@singledollardepth}{0.05ex}{%
    \def\LWR@singledollardepthstyle{%
        \ ; % extra space
        \LWR@print@mbox{%
        vertical-align:-\LWR@convertto{em}{\the\LWR@singledollardepth} em%
        } % extra space
    }%
}{%
    \def\LWR@singledollardepthstyle{}%
}%
```

Create the `lateximage` using the alternate tag and the computed size and depth. The star causes `lateximage` to use an MD5 hash as the filename. When hashing, also include the current font and color in the hash.

```
\ifbool{LWR@dynamicmath}{%
    \LWR@traceinfo{subsingledollar: dynamic}%
    \begin{lateximage}% no hashing
        [(\mathimagename)]% alt tag
        []% no add'l hashing
        [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
}{%
```

```
        \LWR@traceinfo{subsingledollar: static}%
        \IfValueTF{#1}{%
            \LWR@findcurrenttextcolor% sets \LWR@tempcolor
```

Support for xfakebold:

```
            \ifbool{LWR@xfakebold}%
                {\def\LWR@tempone{Y}}%
                {\def\LWR@tempone{N}}%

            \begin{lateximage}*% use hashing
                [#2]% alt
                [% addl' hashing
                    #3%
                    FM\LWR@f@family%
                    SR\LWR@f@series%
                    SH\LWR@f@shape%
                    CL\LWR@tempcolor%
                    FB\LWR@tempone% xfakebold
                ]%
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
        }{%
            \begin{lateximage}% no hashing
                [#2]% alt
                []% no add'l hashing
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
        }%
    }%
```

Place small and almost transparent markers on the baseline at the left and right edges of the image. These markers are seen by *pdfcrop*, and force vertically-centered objects such as a dash to be raised off the baseline in the cropped image, and also force the total width and left / right margins to be correct. (Except that in some fonts a character may exceed the bounding box, and thus may appear wider than expected when converted to an image.)

```
    \LWR@addbaselinemarker%
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

Typeset the contents:

```
    \usebox{\LWR@singledollarbox}%
```

The closing baseline marker:

```
    \LWR@addbaselinemarker%

    \end{lateximage}%
%
}% not mathjax
```

```
\endgroup%
}% not in a lateximage
\LWR@traceinfo{LWR@subsingledollar: done}%
}
```

```
\LetLtxMacro\LWR@origdollar$
\LetLtxMacro\LWR@secondorigdollar$% balance for editor syntax highlighting
```

```
\LetLtxMacro\LWR@origopenparen\(
\LetLtxMacro\LWR@origcloseparen\)
\LetLtxMacro\LWR@origopenbracket\[
\LetLtxMacro\LWR@origclosebracket\]
```

$
$$

Redefine the dollar sign to place math inside a lateximage, or use MathJax:

```
\begingroup
\catcode`\$=\active%
\protected\gdef${\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

Used by chemformula to escape single-dollar math:

```
\protected\gdef\LWR@newsingledollar{\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

\LWR@doubledollar

Redefine the double dollar sign to place math inside a lateximage, or use MathJax:

```
\protected\gdef\LWR@doubledollar$#1$${%
```

If MathJax or formatting for a word processor, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

For MathJax, print the math between \[and \]:

```
{

    \textbackslash[%
    \LWR@HTMLsanitize{#1}%
    \textbackslash]

}% mathjax
```

For SVG, print the math inside a lateximage, with an <alt> tag of the LaTeX code:

```
{% not mathjax
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [%
        \textbackslash{[} % extra space
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash{]}%
    ]%
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

```
    \LWR@origdollar\LWR@origdollar#1\LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}% not mathjax
}%
```

\LWR@singledollar {⟨*alt text*⟩} {⟨*math expression*⟩}

```
\protected\gdef\LWR@singledollar#1${%
\ifbool{mathjax}{%
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {#1}% contents
}{% not mathjax
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {\LWR@origensuredmath{#1}}% contents
}% not mathjax
}
```

\(\[Redefine to the above dollar macros.

```
\AtBeginDocument{
\protected\gdef\(#1\){$#1$}
\protected\gdef\[#1\]{$$#1$$}
}

\endgroup
```

```
\AtBeginDocument{
\LetLtxMacro\LWR@openbracketnormal\[
\LetLtxMacro\LWR@closebracketnormal\]
}
```

\@ensuredmath {⟨*expression*⟩}

If MathJax, a `lateximage` is used, since `\ensuremath` is often used for complex TEX expressions which MathJax may not render. If SVG math, a hashed file is used with a simple `alt` tag, but additional hashing provided by the contents.

```
\LetLtxMacro\LWR@origensuredmath\@ensuredmath

\renewcommand{\@ensuredmath}[1]{%
\ifbool{mathjax}{%
    \LWR@subsingledollar*{(\mathimagename)}{%
           \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{\relax%
        \LWR@origensuredmath{#1}%
    }%
}{% SVG math
```

If already inside a `lateximage` in math mode, continue as-is.

```
\ifmmode%
    \LWR@origensuredmath{#1}%
\else%
```

Create an inline math `lateximage` with a simple `alt` tag and additional hashing according to the contents.

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {\LWR@origensuredmath{#1}}%
    {%
        \LWR@subsingledollar*{(\mathimagename)}{%
           \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
        }{%
            \LWR@origensuredmath{#1}%
        }%
    }%
\fi%
}%
}
```

Remove the old `math` and `displaymath` environments:

```
\let\math\relax
\let\endmath\relax
\let\displaymath\relax
\let\enddisplaymath\relax
```

Env `math` Set math mode then typeset the body of what was between the begin/end. See the environ package for `\BODY`.

```
\NewEnviron{math}{\expandafter\(\BODY\)}
```

Env `LWR@displaymathnormal` Set math mode then typeset the body of what was between the begin/end. See the environ package for `\BODY`.

```
\NewEnviron{LWR@displaymathnormal}{\expandafter\[\BODY\]\@ignoretrue}
```

Set the default displaymath to the normal version:

```
\LetLtxMacro\[\LWR@openbracketnormal%
\LetLtxMacro\]\LWR@closebracketnormal%
\LetLtxMacro\displaymath\LWR@displaymathnormal%
\LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
```

Env `LWR@displaymathother` A version of `displaymath` which can handle complicated objects, but does not supply MathJax or HTML `alt` tags.

```
\newenvironment{LWR@displaymathother}
{%
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [(display math)]%
    \LWR@origdollar\LWR@origdollar%
}
{%
    \LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}
```

Env `LWR@equationother` A version of `displaymath` which can handle complicated objects, but does not supply MathJax or HTML `alt` tags.

```
\newenvironment{LWR@equationother}
{%
    \begin{BlockClass}{displaymathnumbered}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [(display math)]%
    \LWR@origequation%
}
{%
    \LWR@origendequation%
    \end{lateximage}%
    \end{BlockClass}%
}
```

78.4 MathJax support

Ctr `LWR@nextequation` Used to add one to compute the next equation number.

```
\newcounter{LWR@nextequation}
```

`\LWR@syncmathjax` Sets the MathJax equation format and number for the following equations.

These MathJax commands are printed inside "\(" and "\)" characters. They are printed to HTML output, not interpreted by LaTeX.

```
\newcommand*{\LWR@syncmathjax}{%
```

If using chapters, place the chapter number in front of the equation. Otherwise, use the simple equation number.

```
\ifcsdef{thechapter}{
    \InlineClass{hidden}{
        \textbackslash(
        \textbackslash{}seteqsection \{\thechapter\}
        \textbackslash)
    }
}
{}% not using chapters
```

MathJax doesn't allow setting the equation number to 1:

```
\ifthenelse{\cnttest{\value{equation}}>0}
{
```

Tell MathJax that the next set of equations begins with the current LaTeX equation number, plus one.

```
    \setcounter{LWR@nextequation}{\value{equation}}
    \addtocounter{LWR@nextequation}{1}
```

Place the MathJax command inside "\(" and "\)" characters, to be printed to HTML, not interpreted by LaTeX.

```
    \InlineClass{hidden}{
        \textbackslash(
        \textbackslash{}seteqnumber \{\arabic{LWR@nextequation}\}
        \textbackslash)
    }
}{}% not eq > 0
}
```

`\LWR@hidelatexequation` {⟨*environment*⟩} {⟨*contents*⟩}

Creates the LaTeX version of the equation inside an HTML comment.

```
\NewDocumentCommand{\LWR@hidelatexequation}{m +m}{%
```

Stop HTML paragraph handling and open an HTML comment:

```
\LWR@stoppars
\LWR@htmlopencomment

```

Start the LaTeX math environment inside the HTML comment:

```
\begingroup
\@nameuse{LWR@orig#1}
```

While in the math environment, restore various commands to their LaTeX meanings.

```
\LWR@restoreorigformatting
```

See `\LWR@htmlmathlabel` in section 78.7.1.

Print the contents of the equation:

```
#2
```

End the LaTeX math environment inside the HTML comment:

```
\@nameuse{LWR@origend#1}
\endgroup

```

Close the HTML comment and resume HTML paragraph handling:

```
\LWR@htmlclosecomment
\LWR@startpars
}
```

`\LWR@addmathjax` {⟨*environment*⟩} {⟨*contents*⟩}

Given the name of a math environment and its contents, create a MathJax instance. The contents are printed to HTML output, not interpreted by LaTeX.

```
\NewDocumentCommand{\LWR@addmathjax}{m +m}{%
```

Enclose the MathJax environment inside printed "`\(`" and "`\)`" characters.

```
\LWR@origtilde\LWR@orignewline
\textbackslash{}begin\{#1\}
```

Print the contents, sanitizing for HTML special characters.

```
\LWR@HTMLsanitizeexpand{\detokenize\expandafter{#2}}
```

Close the MathJax environment:

```
\textbackslash{}end\{#1\}
\LWR@orignewline
}
```

78.5 Equation environment

Remember existing `equation` environment:

```
\AtBeginDocument{
\let\LWR@origequation\equation
\let\LWR@origendequation\endequation
\csletcs{LWR@origequation*}{equation*}
\csletcs{LWR@origendequation*}{endequation*}
}
```

\LWR@doequation {⟨*env contents*⟩} {⟨*env name*⟩}

For SVG math output, the contents are typeset using the original `equation` inside a `lateximage`, along with an `<alt>` tag containing a detokenized copy of the LaTeX source for the math.

For MathJax output, the contents are typeset in an original `equation` environment placed inside a HTML comment, with special processing for `\labels`. The contents are also printed to the HTML output for processing by the MathJax script.

```
\newcommand*{\LWR@doequation}[2]{%

```

If `mathjax` or `FormatWP`, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

MathJax output:

```
{
```

Print commands to syncronize MathJax's equation number and format to the current LaTeX chapter/section and equation number:

```
    \LWR@syncmathjax
```

Print the LaTeX math inside an HTML comment:

```
    \LWR@hidelatexequation{#2}{#1}
}
```

SVG output: Create the `lateximage` along with an HTML `<alt>` tag having an equation number, the LaTeX equation environment commmands, and the contents of the environment's `\BODY`.

```
{% not mathjax
```

Begin the `lateximage` with an `<alt>` tag containing the math source:

```
    \ifstrequal{#2}{equation*}{%
        \begin{BlockClass}{displaymath}%
    }{%
        \begin{BlockClass}{displaymathnumbered}%
    }%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
```

```
    \begin{lateximage}[%
        \ifstrequal{#2}{equation*}{%
            \ifdefequal{\LWR@equationtag}{\theequation}{%
%                                   no tag was given
            }{%
                (\LWR@equationtag) % tag was given
            }%
        }{%
            (\LWR@equationtag) % automatic numbering
        }%
        \textbackslash{begin\{#2\}} % extra space
        \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#1}} % extra space
        \textbackslash{end\{#2\}}%
    ]% alt tag
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

Create the actual LaTeX-formatted equation inside the `lateximage` using the contents of the environment.

```
    \@nameuse{LWR@orig#2}%
    #1% contents collected by \collect@body
    \@nameuse{LWR@origend#2}%
    \end{lateximage}%
    \end{BlockClass}%
}% not mathjax
}
```

After the environment, if MathJax, print the math to the HTML output for MathJax processing:

```
\newcommand*{\LWR@doendequation}[1]{%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {%
        \LWR@addmathjax{#1}{\BODY}%
    }{}%

}
```

Remove existing `equation` environment:

```
\AtBeginDocument{
\let\equation\relax
\let\endequation\relax
\csletcs{equation*}{relax}
\csletcs{endequation*}{relax}
}
```

Env `equation` The new `equation` environment is created with `\NewEnviron` (from the environ package), which stores the contents of its environment in a macro called `\BODY`.

```
\AtBeginDocument{
\NewEnviron{equation}%
{\LWR@doequation{\BODY}{equation}}%
[\LWR@doendequation{equation}]

\LetLtxMacro\LWR@equationnormal\equation
\LetLtxMacro\endLWR@equationnormal\endequation
}
```

Env `equation*`

```
\AtBeginDocument{
\NewEnviron{equation*}%
{\LWR@doequation{\BODY}{equation*}}%
[\LWR@doendequation{equation*}]

\csletcs{LWR@equationnormalstar}{equation*}
\csletcs{LWR@endequationnormalstar}{endequation*}
}
```

Remember the "less" version of `equation`, which uses MathJax and `alt` tags, but does not support complicated contents such as some Ti*k*z expressions.

```
\AtBeginDocument{
\LetLtxMacro\LWR@equationless\equation
\LetLtxMacro\endLWR@equationless\endequation
\csletcs{LWR@equationlessstar}{equation*}
\csletcs{LWR@endequationlessstar}{endequation*}
}
```

78.6 `\displaymathnormal` and `\displaymathother`

`\displaymathnormal` By default, or when selecting `\displaymathnormal`, MathJax math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the `alt` tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

`\displaymathother` MathJax unsupported complicated `alt` tag When selecting `\displaymathother`, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an HTML `alt` tag. In this mode, MathJax is turned off, math display environments become SVG images, even if MathJax is selected, and the HTML `alt` tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

`\displaymathnormal` simple math objects Use when display math environments have simple math which is to sent to MathJax or included in HTML `alt` tags.

```
\newcommand*{\displaymathnormal}{%
```

```
\ifbool{LWR@origmathjax}{\booltrue{mathjax}}{\boolfalse{mathjax}}%
\LetLtxMacro\[\LWR@openbracketnormal%
\LetLtxMacro\]\LWR@closebracketnormal%
\LetLtxMacro\displaymath\LWR@displaymathnormal%
\LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
\LetLtxMacro\equation\LWR@equationnormal%
\LetLtxMacro\endequation\endLWR@equationnormal%
\csletcs{equation*}{LWR@equationnormalstar}%
\csletcs{endequation*}{LWR@endequationnormalstar}%
}
```

`\displaymathother` complicated math objects

Use when display math environments have complicated objects which will not work with MathJax or should not be included in HTML `alt` tags. Complicated contents are more likely to compile correctly.

```
\newcommand*{\displaymathother}{%
\boolfalse{mathjax}%
\LetLtxMacro\displaymath\LWR@displaymathother%
\LetLtxMacro\enddisplaymath\endLWR@displaymathother%
\LetLtxMacro\[\LWR@displaymathother%
\LetLtxMacro\]\endLWR@displaymathother%
\LetLtxMacro\equation\LWR@equationother%
\LetLtxMacro\endequation\endLWR@equationother%
\csletcs{equation*}{displaymath}%
\csletcs{endequation*}{enddisplaymath}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Print-mode versions:

```
\newcommand*{\displaymathnormal}{}
\newcommand*{\displaymathother}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

78.7 AMS Math environments

78.7.1 Support macros

Bool `LWR@amsmultline` True if processing a multline environment.

To compensate for `multline`-spefific code, `LWR@amsmultline` is used to add extra horizontal space in `\LWR@htmlmathlabel` if is used in an amsmath environment which is not a `multline` environment and not an `equation`.

```
\newbool{LWR@amsmultline}
\boolfalse{LWR@amsmultline}
```

\LWR@htmlmathlabel {⟨*label*⟩}

lwarp points \ltx@label here. This is used by \label when inside a LaTeX AMS math environment's math display environment.

\LWR@origltx@label points to the LaTeX original, modified by lwarp, then by amsmath, then by cleveref.

```
\newcommand*{\LWR@htmlmathlabel}[1]{%
\LWR@traceinfo{LWR@htmlmathlabelb #1}%
```

If mathjax or FormatWP, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{%
```

The combined LaTeX & HTML label is printed in a \text field:

```
    \text{%
```

Shift the label over to the right side of the environment to avoid over-printing the math:

```
    \ifbool{LWR@amsmultline}{}{\hspace*{\totwidth@}}%
```

Temporarily end the HTML comment, insert the LaTeX & HTML label, then resume the HTML comment. \@firstofone is required to remove extra braces introduced by the amsmath package.)

```
    \LWR@htmlclosecomment%
    \LWR@origltx@label{#1}%
    \LWR@htmlopencomment%
    }% text
}% mathjax
{%
    \LWR@origltx@label{#1}%
}%
}
```

\LWR@beginhideamsmath Starts hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@beginhideamsmath}{
\LWR@stoppars
\LWR@origtilde\LWR@orignewline
\LWR@htmlopencomment

\begingroup
\LWR@restoreorigformatting
}
```

\LWR@endhideamsmath Ends hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@endhideamsmath}{
\endgroup

\LWR@htmlclosecomment
\LWR@orignewline
\LWR@startpars
}
```

78.7.2 Environment patches

The amsmath environments already collect their contents in \@envbody for further processing. eqnarray is not an $\mathcal{AMS}$ package, and thus requires special handling.

For SVG math: Each envrionment is encapsulated inside a lateximage environment, along with a special optional argument of \LWR@amsmathbody or \LWR@amsmathbodynumbered telling lateximage to use as the HTML <alt> tag the environment's contents which were automatically captured by the $\mathcal{AMS}$ environment.

For MathJax: Each environment is syched with LaTeX's equation numbers, typeset with LaTeX inside an HTML comment, then printed to HTML output for MathJax to process.

Env eqnarray This environmnet is not an $\mathcal{AMS}$ environment and thus its body is not automatically captured, so the environ package is used to capture the environment into \BODY.

```
\let\LWR@origeqnarray\eqnarray
\let\LWR@origendeqnarray\endeqnarray
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
\newbool{LWR@numbereqnarray}
\booltrue{LWR@numbereqnarray}
```

Common code used by eqnarray and Beqnarray (from fancybox):

```
\newcommand{\LWR@eqnarrayfactor}{%
```

If mathjax or FormatWP, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{%
```

If MathJax, the environment contents (the \BODY) are executed in a HTML comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for MathJax to interpret:

```
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
```

```
    \ifbool{LWR@numbereqnarray}
    {
```

If numbering the equations, execute a copy inside an HTML comment block:

```
        \LWR@beginhideamsmath
        \LWR@origeqnarray
        \BODY
        \LWR@origendeqnarray
        \LWR@endhideamsmath
```

Then print the (sanitized) contents to the output for MathJax to interpret:

```
        \LWR@addmathjax{eqnarray}{\BODY}
    }%
    {% not LWR@numbereqnarray
```

If not numbering equations, just create the contents for MathJax:

```
    \LWR@addmathjax{eqnarray*}{\BODY}
    }% LWR@numbereqnarray
}% mathjax
{% not mathjax
    \ifbool{LWR@numbereqnarray}
    {
```

For numbered SVG equations, first create a `latexmage` with an `alt` attribute containing sanitized copy of the source code:

```
        \begin{BlockClass}{displaymathnumbered}%
        \LWR@newautoidanchor%
        \booltrue{LWR@indisplaymathimage}%
        \begin{lateximage}[(\LWR@startingequationtag--\LWR@equationtag)
            \LWR@addmathjax{eqnarray}{\BODY}]
```

Support for xfakebold:

```
        \LWR@applyxfakebold%
```

Create the image contents using an actual `eqnarray`:

```
        \LWR@origeqnarray
        \BODY
        \LWR@origendeqnarray
        \end{lateximage}
        \end{BlockClass}
    }%
    {% not LWR@numbereqnarray
```

If not numbered, do the same, but an extra `\nonumber` seems to be required:

```
        \begin{BlockClass}{displaymath}
        \LWR@newautoidanchor%
        \booltrue{LWR@indisplaymathimage}%
```

```
        \begin{lateximage}[\LWR@addmathjax{eqnarray*}{\BODY}]
```

Support for xfakebold:

```
        \LWR@applyxfakebold%

        \LWR@origeqnarray
        \BODY
        \nonumber
        \LWR@origendeqnarray
        \end{lateximage}
        \end{BlockClass}
    }% LWR@numbereqnarray
}% not mathjax
```

Default to number equations in the future:

```
\booltrue{LWR@numbereqnarray}
}
```

eqnarray itself is made with a blank line before and after to force it to be on its own line:

```
\RenewEnviron{eqnarray}
{%

\LWR@eqnarrayfactor

}
```

The starred version is patched to turn off the numbering:

```
\csgpreto{eqnarray*}{\boolfalse{LWR@numbereqnarray}}

\end{warpHTML}
```

79 Lateximages

79.1 Description

Env lateximage

A lateximage is a piece of the document which is typeset in LaTeX then included in the HTML output as an image. This is used for math if SVG math is chosen, and also for the picture, tikzpicture, and other environments.

Before typesetting the lateximage a large number of formatting, graphics, and symbols-related macros are temporarily restored to their print-mode meaning by \LWR@restoreorigformatting. (See section 77.)

A lateximage is typeset on its own PDF page inside an HTML comment which starts on the preceeding page and ends on following page, and instructions are written to

lateximage.txt for *lwarpmk* to extract the lateximage from the page of the PDF file then generate an accompanying .svg file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML is created to hold both the HTML comment, which will have the *pdftotext* conversion, and also the link to the final .svg image.

A LaTeX label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

HTML alt tag

The HTML alt tag is set to the LaTeX source for SVG math, some chemistry expressions, and perhaps some other expressions which make sense for text copy/paste. In some other cases, the alt tag is set according to the package name.

When creating an SVG math image, its alt tag may be set to the math expression, which may be hashed for image reuse. In the case of \ensuremath or after \inlinemathother, where the contents require a unique image for each instance of the same expression, the alt tag is set to \mathimagename, and the image is not reused.

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "math image", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

For many packages, the output is placed inside a lateximage with an HTML alt tag set to the package name followed by \packagediagramname. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following lateximages.

SVG image font size

For the lateximage environment, the size of the math and text used in the SVG image may be adjusted by setting \LateximageFontSizeName to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by \LateximageFontScale, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

79.2 Support counters and macros

for HTML output: 9930 \begin{warpHTML}

Ctr LWR@lateximagenumber

Sequence the images.

```
\newcounter{LWR@lateximagenumber}
\setcounter{LWR@lateximagenumber}{0}
```

Ctr LWR@lateximagedepth Do not create \lateximage inside of \lateximage.

```
\newcounter{LWR@lateximagedepth}
\setcounter{LWR@lateximagedepth}{0}
```

A few utility macros to write special characters:

```
\edef\LWR@hashmark{\string#} % for use in \write
\edef\LWR@percent{\@percentchar} % for use in \write
```

Ctr LWR@LIpage Used to reference the PDF page number of a lateximage to be written into <project>-images.txt.

```
\newcounter{LWR@LIpage}
```

```
\end{warpHTML}
```

79.3 Font size

for HTML & PRINT:

```
\begin{warpall}
```

\LateximageFontSizeName Declares how large to write text in \lateximages. The .svg file text size should blend well with the surrounding HTML text size.

⚠ no backslash *Do not include the leading backslash in the name.*

```
\newcommand*{\LateximageFontSizeName}{normalsize}
```

\LateximageFontScale Declares how large to scale inline SVG math images. The .svg file text size should blend well with the surrounding HTML text size. The default is .75, but it may be redefined as needed depending on the HTML font.

```
\newcommand*{\LateximageFontScale}{.75}
```

```
\end{warpall}
```

79.4 Sanitizing math expressions for HTML

for HTML output:

```
\begin{warpHTML}
```

\LWR@HTMLsanitize {⟨*text*⟩}

Math expressions are converted to lateximages, and some math environments may contain &, <, or >, which should not be allowed inside an HTML <alt> tag, so must convert them to HTML entities.

Two versions follow, depending on expansion needs. There may be a better way…

```
\newrobustcmd{\LWR@HTMLsanitize}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
\begingroup%
\LWR@FBcancel%
\fullexpandarg%
```

The &, <, and > may be interpreted by the browser:

```
\protect\StrSubstitute{\detokenize{#1}}%
{\detokenize{&}}{\detokenize{&amp;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{<}}{\detokenize{&lt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{>}}{\detokenize{&gt;}}[\LWR@strresult]%
```

The double quote occasionally causes problems.

```
\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{"}}{\detokenize{&quot;}}[\LWR@strresult]%
```

MathJax allows expressions to be defined with \newcommand. These expressions would appear with ## for each argument, and each must be changed to a single #. This must be done after all the above changes. Attempting another conversion after this causes an error upon further expansion.

```
\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{##}}{\LWR@origpound}[\LWR@strresult]%

\LWR@strresult%
\endgroup%
}
```

\LWR@HTMLsanitizeexpand {⟨*text*⟩}

This version expands the argument before sanitizing it.

```
\newrobustcmd{\LWR@HTMLsanitizeexpand}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
\begingroup%
\LWR@FBcancel%
\fullexpandarg%
```

The difference between this and \LWR@HTMLsanitize (without "expand") is the following \expandafter:

```
\protect\StrSubstitute{\detokenize\expandafter{#1}}%
{\detokenize{&}}{\detokenize{&amp;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{<}}{\detokenize{&lt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{>}}{\detokenize{&gt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{"}}{\detokenize{&quot;}}[\LWR@strresult]%
```

\LWR@HTMLsanitizeexpand is not used for defining new MathJax macros, so the ## conversion is not needed here.

```
\LWR@strresult%
\endgroup%
}
```

79.5 Equation numbers

Ctr LWR@startingequation

For use with lateximage and multi-line numbered equations. Remembers the next equation number so that it may be printed in the alt tag.

```
\newcounter{LWR@startingequation}

\@ifundefined{chapter}
{
\renewcommand{\theLWR@startingequation}{%
\arabic{LWR@startingequation}%
}
}
{% chapter defined
\renewcommand{\theLWR@startingequation}{%
\ifnumcomp{\value{chapter}}{>}{0}{\arabic{chapter}.}{}%
\arabic{LWR@startingequation}%
}
}
```

Bool LWR@isstartingequation

True for the first equation tag, false for later tags in the same environment.

```
\newbool{LWR@isstartingequation}
```

\LWR@startingequationtag

Prints the starting equation number or tag.

```
\let\LWR@startingequationtag\theLWR@startingequation
```

\LWR@equationtag Prints the ending equation number or tag.

This is reset by lateximage, may be temporarily overwritten by \tag calling \LWR@remembertag.

```
\newcommand*{\LWR@equationtag}{}
```

Only if SVG math, patch \tag after packages have loaded, in case someone else modified \tag.

```
\AtBeginDocument{

\ifbool{mathjax}{}{% not mathjax
```

\LWR@remembertag {⟨*tag*⟩}

For use inside the math environments while using SVG math. Sets \theLWR@startingequation and \theequation to the given tag.

```
\NewDocumentCommand{\LWR@remembertag}{m}{%
\ifbool{LWR@isstartingequation}%
{%
    \global\boolfalse{LWR@isstartingequation}%
    \xdef\LWR@startingequationtag{#1}%
}{}%
\xdef\LWR@equationtag{#1}%
}%

}% not mathjax
}% AtBeginDocument
```

79.6 HTML alt tags

\LWR@amsmathbody {⟨*envname*⟩} For use inside the optional argument to a lateximage to add the contents of a AMS math environment to the <alt> tag.

```
\newcommand*{\LWR@amsmathbody}[1]
{%
\textbackslash\{begin\}\{#1\} % extra space
\LWR@HTMLsanitizeexpand{\detokenize\expandafter{\the\@envbody}}%
\textbackslash\{end\}\{#1\}%
}
```

\LWR@amsmathbodynumbered {⟨*envname*⟩} For use inside the optional argument to a lateximage to add the contents of a AMS math environment to the alt tag, prefixed by the equation numbers.

```
\newcommand*{\LWR@amsmathbodynumbered}[1]
{%
\ifnumcomp{\value{LWR@startingequation}}{=}{\value{equation}}%
{(\LWR@equationtag)}%
```

```
{(\LWR@startingequationtag--\LWR@equationtag)} % extra space
\LWR@amsmathbody{#1} % extra space
}
```

79.7 lateximage environment

Env lateximage * [⟨*2:* <alt> *tag*⟩] [⟨*3: add'l hashing*⟩] [⟨*4: css style*⟩]

Typesets the contents and then renders the result as an SVG file. Star causes the image to be hashed for reuse.

The optional <alt> tag is included in the HTML code for use with copy/paste.

image filename hashing

If starred, a hashed filename is used.If so, the hash is based on the alt tag and also the additional hashing argument.

This may be used to provide an expression with a simple alt tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple alt tag is still the same.

File *_html.aux

A new label is placed into the file *_html.aux:

```
\newlabel{LWRlateximage-<BaseJobname>-<number>}{{<x>}{<y>}}
```

This is used to find the image in the PDF file, according to its name.

File *-images.txt

A list of images to generate is created in <jobname>-images.txt. Each line has three pipe-delimited fields, containing the PDF page number from <jobname>_html.pdf, where the image is located, a boolean indicating whether the image is hashed, and the filename of the image. The last line has "end" in each field, and is used to detect an incomplete compile.

```
\catcode`\$=\active%

\NewDocumentEnvironment{lateximage}{s O{(image)} O{} O{}}
{%
\LWR@traceinfo{lateximage: starting on \jobname.pdf page \arabic{page}}%
\LWR@traceinfo{lateximage: entering depth is \arabic{LWR@lateximagedepth}}%
```

Nested lateximages remain one large lateximage:

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
```

If nesting inside an already-existing lateximage, simply record one more level. $\mathcal{AMS}$ packages redefine `\addtocounter` to do nothing if inside a `\text`, so lower-level TEX macros are used for tracking nested `lateximages`.

```
{%
%     \addtocounter{LWR@lateximagedepth}{1}%
    \global\advance\c@LWR@lateximagedepth 1\relax% Due to AmS \text macro.
}%
```

Otherwise, this is the outer-most lateximage:

```
{% start of outer-most lateximage
```

Remember the next equation number to be allocated, in case it must be printed in a multi-equation environment:

```
\LWR@traceinfo{lateximage: starting outer-most lateximage}%
    \setcounter{LWR@startingequation}{\value{equation}}%
    \addtocounter{LWR@startingequation}{1}%
    \booltrue{LWR@isstartingequation}%
    \let\LWR@startingequationtag\theLWR@startingequation%
```

The default equation tag, unless overwritten by `\tag`:

```
    \let\LWR@equationtag\theequation%
```

Starting a new lateximage:

```
    \addtocounter{LWR@lateximagenumber}{1}%
   \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{LWR@lateximagenumber}}%
```

While inside a lateximage, locally do not use mathjax:

```
    \boolfalse{mathjax}%
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Next file:

```
    \addtocounter{LWR@externalfilecnt}{1}%
   \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{LWR@externalfilecnt}}%
```

Figure out what the next page number will be. `\setcounterpageref` assigns `LWR@LIpage` to the page number for the reference `LWRlateximage-BaseJobname-XXX`:

```
    \setcounterpageref{LWR@LIpage}{%
        LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}%
    }%
    \LWR@traceinfo{lateximage: LWR@LIpage is \arabic{LWR@LIpage}}%
```

Create an HTML span which will hold the comment which contains the *pdftotext* translation of the image's page, and also will hold the link to the `.svg` file:

```
\LWR@htmltag{span\LWR@indentHTML%
 id="lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}"\LWR@indentHTML
    class="lateximagesource"\LWR@orignewline
}%
```

Write instructions to the `<ImagesDirectory>.txt` file:

```
\LWR@traceinfo{lateximage: about to write to \BaseJobname-images.txt}%
\IfBooleanTF{#1}% starred
{% hash
    \LWR@traceinfo{lateximage: hash true, adding %
        !\detokenize\expandafter{#2}!\detokenize\expandafter{#3}!}%
```

Compute and save the hashed file name for later use:

```
    \edef\LWR@hashedname{%
        \LWR@mdfive{\detokenize\expandafter{#2}-!-#3}%
    }%
    \LWR@traceinfo{lateximage: hash is \LWR@hashedname}%
```

Write the page, hashing, and hashed name:

```
    \immediate\write\LWR@lateximagesfile{%
        |\arabic{LWR@LIpage}|true|\LWR@hashedname|%
    }%
}% hash
{% no hash
```

No hash, so write the page, no hashing, and the image number:

```
    \LWR@traceinfo{lateximage: hash false}%
    \immediate\write\LWR@lateximagesfile{%
    |\arabic{LWR@LIpage}|false|\LWR@ImagesName\arabic{LWR@externalfilecnt}|%
    }%
}% no hash
```

Place an open comment tag. This will hide any traces of the lateximage PDF page which were picked up by *pdftotext*.

```
\LWR@traceinfo{lateximage: about to create open comment}%
\LWR@htmlopencomment%
```

One level deeper. At this outer-most `lateximage`, it is known that this is not being used inside an $\mathcal{AMS}$ `\text`, since the outer-most level will never be in math mode.

```
 \addtocounter{LWR@lateximagedepth}{1}%
```

Start the new PDF page:

```
\LWR@traceinfo{lateximage: about to create a new page}%
\LWR@orignewpage%
```

Typeset the image in a "standard" width page and font size:

```
    \LWR@traceinfo{lateximage: about to create minipage}%
    \LWR@print@minipage{6in}%
    \@nameuse{LWR@print@\LateximageFontSizeName}%
```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for \hspace, etc. inside a lateximage.

```
    \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
    \LWR@restoreorigformatting%
```

Use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```
    \def\@mpfn{footnote}%
    \def\thempfn{\thefootnote}%
    \LetLtxMacro\@footnotetext\LWR@footnotetext%
```

Create the LWRlateximage<number> label:

```
    \LWR@traceinfo{lateximage: about to create label}%
    \LWR@orig@label{LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}}%
    \LWR@traceinfo{lateximage: finished creating the label}%
```

Enable print-mode math functions:

```
    \LetLtxMacro$\LWR@origdollar%
    \catcode`\$=3% math shift
    \LetLtxMacro\(\LWR@origopenparen%
    \LetLtxMacro\)\LWR@origcloseparen%
```

Only enable print-mode display math if are not already inside display math:

```
    \ifbool{LWR@indisplaymathimage}{}{% not in display math
        \LetLtxMacro\[\LWR@origopenbracket%
        \LetLtxMacro\]\LWR@origclosebracket%
        \let\equation\LWR@origequation%
        \let\endequation\LWR@origendequation%
        \csletcs{equation*}{LWR@origequation*}%
        \csletcs{endequation*}{LWR@origendequation*}%
    }% not in display math
```

For chemformula:

```
    \LetLtxMacro\LWR@newsingledollar$%
    \LetLtxMacro\LWR@newsingledollar$% syntax highlighting
```

```
}% end of outer-most lateximage
\LWR@traceinfo{lateximage: finished start of environment}%
}% end of \begin{lateximage}
```

\endlateximage When the environment closes:

```
{% start of \end{lateximage}
\LWR@traceinfo{lateximage: starting end of lateximage}%
```

Nested more than one deep?

```
\LWR@traceinfo{lateximage: internal depth was \arabic{LWR@lateximagedepth}}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
```

If nesting inside an already existing lateximage, simply record one less level. Uses a lower-level TEX macro due to $\mathcal{AMS}$ `\text` change of `\addtocounter`.

```
{%
    \LWR@traceinfo{lateximage: unnesting}%
    \global\advance\c@LWR@lateximagedepth -1\relax%
}%
```

If this is the outer-most lateximage:

```
{% end of outer-most lateximage
```

Finish the lateximage minipage and start a new PDF page:

```
\LWR@traceinfo{lateximage: ending outer-most lateximage}%
    \endLWR@print@minipage%
    \LWR@orignewpage%
```

Close the HTML comment which encapsulated any traces of the lateximage picked up by *pdftotext*:

```
    \LWR@print@vspace*{.5\baselineskip}%
    \LWR@htmlclosecomment%
    \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%
```

Create a link to the lateximage, allowing its natural height:

```
    \IfBooleanTF{#1}% starred
    {% hash
        \LWR@subinlineimage[#2]{lateximage}%
        {%
            \LWR@ImagesDirectory\OSPathSymbol%
            \LWR@print@mbox{\LWR@hashedname}%
        }{svg}{#4}%
    }% hash
    {% no hash
        \LWR@subinlineimage[#2]{lateximage}%
        {%
            \LWR@ImagesDirectory\OSPathSymbol%
            \LWR@print@mbox{\LWR@ImagesName\theLWR@externalfilecnt}%
        }{svg}{#4}%
    }% no hash
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Close the HTML span which has the *pdftotext* comment and also the link to the .svg image:

```
    \LWR@htmltag{/span}%
    \ifbool{HTMLDebugComments}{%
        \LWR@htmlcomment{End of lateximage}%
    }{}%
```

Undo one lateximage level. This is not inside an $\mathcal{AMS}$ \text, so regular \addtocounter may be used here.

```
    \addtocounter{LWR@lateximagedepth}{-1}%
}% end of outer-most lateximage
\LWR@traceinfo{lateximage: exiting depth is \arabic{LWR@lateximagedepth}}%
\LWR@traceinfo{lateximage: done}%
}%
\catcode`\$=3% math shift
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Env lateximage [⟨<alt> *tag*⟩] [⟨*css style*⟩]

varwidth is used to create a box of the natural width of its contents.

```
\NewDocumentEnvironment{lateximage}{s o o o}
    {\begin{varwidth}[b]{\linewidth}}
    {\end{varwidth}}
```

```
\end{warpprint}
```

80 center, flushleft, flushright

for HTML output:

```
\begin{warpHTML}
```

Env center Replace center functionality with CSS tags:

```
\renewenvironment*{center}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:center}]{center}}
{\BlockClass{center}}
}
{\endBlockClass}
```

Env flushright

```
\renewenvironment*{flushright}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:right}]{flushright}}
{\BlockClass{flushright}}
}
{\endBlockClass}
```

Env flushleft

```
\renewenvironment*{flushleft}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:left}]{flushleft}}
{\BlockClass{flushleft}}
}
{\endBlockClass}
```

\centering, \raggedleft, and \raggedright usually have no effect on the HTML output, but they may be used to compare with the next token to identify their use at the start of a float. See \LWR@floatalignment.

\centering

```
\newcommand*{\LWR@HTML@centering}{%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{centering}%
}{}%
}
\LWR@formatted{centering}
```

\raggedleft

```
\newcommand*{\LWR@HTML@raggedleft}{%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{raggedleft}%
}{}%
}
\LWR@formatted{raggedleft}
```

\raggedright

```
\newcommand*{\LWR@HTML@raggedright}{%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{raggedright}%
}{}%
}
\LWR@formatted{raggedright}
```

\leftline {⟨*text*⟩}

```
\renewcommand{\leftline}[1]{\begin{flushleft}#1\end{flushleft}}
```

\centerline {⟨*text*⟩}

```
\renewcommand{\centerline}[1]{\begin{center}#1\end{center}}
```

\rightline {⟨*text*⟩}

```
\renewcommand{\rightline}[1]{\begin{flushright}#1\end{flushright}}
```

```
\end{warpHTML}
```

81 Preloaded packages

for HTML output:

```
\begin{warpHTML}
```

If the given package was loaded before or by lwarp, load the lwarp version as well.

\LWR@PreloadedPackage {⟨*packagename*⟩}

```
\newcommand*{\LWR@PreloadedPackage}[1]{%
    \@ifpackageloaded{#1}%
        {%
            \AtBeginDocument{
                \LWR@origRequirePackage{lwarp-#1}%
            }
        }%
        {}%
}
```

If textcomp was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{textcomp}
```

If xunicode was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{xunicode}
```

If graphics or graphicx were loaded before lwarp, perhaps by xunicode, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{graphics}
\LWR@PreloadedPackage{graphicx}
```

ulem may be preloaded by ctex, ctexart, and related classes.

```
\LWR@PreloadedPackage{ulem}
```

xetexko-vertical may be preloaded by xetexko.

```
\LWR@PreloadedPackage{xetexko-vertical}
```

geometry is preloaded by lwarp, and perhaps by various classes.

```
\LWR@PreloadedPackage{geometry}
```

plext is preloaded by some CJK classes.

```
\LWR@PreloadedPackage{plext}
```

stfloats is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{stfloats}
```

lltjext is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{lltjext}
```

```
\end{warpHTML}
```

82 siunitx

Pkg siunitx — The lwarp core passes a few options to siunitx.

fractions — Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required — Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first.

⚠ tabular — Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

for HTML output:

```
\begin{warpHTML}
```

Options for siunitx:

```
\newrobustcmd{\LWR@siunitx@textcelsius}{\HTMLentity{deg}C}
\newrobustcmd{\LWR@siunitx@textdegree}{\HTMLentity{deg}}
\newrobustcmd{\LWR@siunitx@textprime}{\HTMLunicode{2032}}
```

```
\newrobustcmd{\LWR@siunitx@textdblprime}{\HTMLunicode{2033}}
\newrobustcmd{\LWR@siunitx@textplanckbar}{\text{\textit{\HTMLunicode{0127}}}}

\appto\LWR@restoreorigformatting{%
\renewrobustcmd{\LWR@siunitx@textcelsius}{\text{\ensuremath{^\circ}C}}%
\renewrobustcmd{\LWR@siunitx@textdegree}{\text{\ensuremath{^\circ}}}%
\renewrobustcmd{\LWR@siunitx@textprime}{\text{\ensuremath{^\prime}}}%
\renewrobustcmd{\LWR@siunitx@textdblprime}{\text{\ensuremath{^{\prime\prime}}}}%
\renewrobustcmd{\LWR@siunitx@textplanckbar}{\text{\ensuremath{\hbar}}}%
}

\PassOptionsToPackage{
    detect-mode=true,
    per-mode=symbol,% fraction is not seen by pdftotext
    text-celsius = {\LWR@siunitx@textcelsius},
    text-degree = {\LWR@siunitx@textdegree},
    text-arcminute = {\LWR@siunitx@textprime} ,
    text-arcsecond = {\LWR@siunitx@textdblprime} ,
}{siunitx}

\end{warpHTML}
```

83 Graphics print-mode modifications

83.1 General limitations

⚠ scale

Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

`\includegraphics` file formats

For `\includegraphics` with `.pdf` or `.eps` files, the user must provide a `.pdf` or `.eps` image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a `.pdf` or `.eps` image is referred to with its file extension, the extension will be changed to `.svg` for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **pdftocairo -svg filename.pdf**

Prog lwarpmk pdftosvg

For a large number of images, use *lwarpmk*:

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

Prog lwarpmk epstopdf

Prog epstopdf

epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **lwarpmk pdftosvg *.PDF**

to convert to SVG images.

DVI latex

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **lwarpmk epstopdf *.eps** **(or a list of filenames)**

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

PNG and JPG

For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF

GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities

If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx

⚠ viewport

⚠ viewport units

If using the older graphics syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options

`\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys.

HTML class

With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

HTML `alt` tags

Likewise, the `\includegraphics` `alt` key adds an HTML `alt` tag to an image, and is ignored for print output. If not assigned, each image is given an `alt` tag of "`(image)`".

`\rotatebox`

`\rotatebox` accepts the optional `origin` key.

⚠ browser support

`\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

83.2 Print-mode modifications

for PRINT output: For print output, accept and then discard the new `class` key:

```
\begin{warpprint}
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
```

Print-mode additions for the overpic package. See section 345 for the HTML version.

```
\AtBeginDocument{
\@ifpackageloaded{overpic}{
\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}
}{}
}
\end{warpprint}
```

84 xcolor boxes

`Pkg xcolor` A few new definitions are provided for enhanced HTML colored boxes, and `\fcolorbox` is slightly modified. Print-mode version are also provided.

Print-mode versions of new xcolor defintions. These are defined inside `warpall` because they are also used for HTML while inside a `latexmage`. They are defined `\AtBeginDocument` so that the xcolor originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of `none`, in which case only the frame is drawn, allowing the background page color to show.

for HTML & PRINT:

```
\begin{warpall}
```

After xparse may have been loaded …

```
\AtBeginDocument{
```

… and *only* if xcolor was loaded:

```
\@ifpackageloaded{xcolor}{
\LWR@traceinfo{patching xcolor}
```

The print version:

`\colorboxBlock` `\colorboxBlock` is the same as `\colorbox`:

```
\LetLtxMacro\colorboxBlock\colorbox
```

The original definition is reused by the new versions:

```
\LetLtxMacro\LWR@orig@print@fcolorbox\fcolorbox
```

\fcolorbox [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

In print mode, \fcolorbox is modified to accept a background color of none.

(\fcolorbox is particular about its optional arguments, thus the elaborate combinations of \ifthenelse.)

```
\newsavebox{\LWR@colorminipagebox}

\NewDocumentCommand{\LWR@print@fcolorbox}{o m o m +m}{%
\LWR@traceinfo{LWR@print@fcolorbox #2 #4}%
```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
\begin{lrbox}{\LWR@colorminipagebox}%
#5%
\end{lrbox}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
\ifstrequal{#4}{none}%
{% #4 none
    \LWR@traceinfo{background is none}%
    {% scope the \colorlet
        \colorlet{LWR@currentcolor}{.}%
        \color{#2}%
        \fbox{%
            \color{LWR@currentcolor}%
            \usebox{\LWR@colorminipagebox}%
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
\LWR@traceinfo{background not none}%
\IfValueTF{#1}%
{%
    \IfValueTF{#3}%
   {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}%
{% no value #1
    \IfValueTF{#3}%
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}% no value #1
}% #4 not none
\LWR@traceinfo{LWR@print@fcolorbox done}%
}

\renewcommand*{\fcolorbox}{\LWR@print@fcolorbox}
```

\fcolorboxBlock [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

In print mode, \fcolorboxBlock is the same as \fcolorbox.

```
\newcommand*{\LWR@print@fcolorboxBlock}{\LWR@print@fcolorbox}
\newcommand*{\fcolorboxBlock}{\LWR@print@fcolorboxBlock}
```

Env fcolorminipage [⟨*1:framemodel*⟩] {⟨*2:framecolor*⟩} [⟨*3:boxmodel*⟩] {⟨*4:boxcolor*⟩} [⟨*5:align*⟩] [⟨*6:height*⟩] [⟨*7:inner-align*⟩] {⟨*8:width*⟩}

In print mode, becomes a \fcolorbox containing a minipage:

```
\NewDocumentEnvironment{LWR@print@fcolorminipage}{o m o m O{c} O{} o m}
{%
\LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%
```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
\begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```
\IfValueTF{#7}%
{\begin{minipage}[#5][#6][#7]{#8}}%
{\begin{minipage}[#5][#6][#5]{#8}}%
}%
{%
\end{minipage}%
\end{lrbox}%
\LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
\ifstrequal{#4}{none}%
{% #4 none
    {% scope the \colorlet
        \colorlet{LWR@currentcolor}{.}%
        \color{#2}%
        \fbox{%
            \color{LWR@currentcolor}%
            \usebox{\LWR@colorminipagebox}%
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
    \IfValueTF{#1}%
    {%
    \IfValueTF{#3}%
   {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
```

```
    }%
    {% no value #1
    \IfValueTF{#3}%
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
    }% no value #1
}% #4 not none
\LWR@traceinfo{*** finished end fcolorminipage}%
}

\newenvironment*{fcolorminipage}
    {\LWR@print@fcolorminipage}
    {\endLWR@print@fcolorminipage}

\LWR@traceinfo{xcolor patches done}
}{}% xcolor loaded
}% AtBeginDocument

\end{warpall}
```

85 chemmacros environments

\makepolymerdelims and redox reactions must be enclosed in a lateximage during HTML output. These environments are provided here in print mode, and in the chemmacros code in HTML mode, as a high-level semantic syntax which automatically embeds the contents in a lateximage with an appropriate alt tag.

for PRINT output:

```
\begin{warpprint}

\AtBeginDocument{
\@ifpackageloaded{chemmacros}{
```

Env polymerdelims

```
\DeclareDocumentEnvironment{polymerdelims}{}
    {}{}
```

Env redoxreaction {⟨*space above*⟩} {⟨*space below*⟩}

For print output, extra space is include above and below the image, and a lateximage is not necessary. This extra space must be enforced, even inside a float, so zero-width rules are used.

For the HTML version, see section 164.4.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
    {\rule{0pt}{#1}}{\rule[-#2]{0pt}{#2}}

}{}% chemmacros
}% AtBeginDocument

\end{warpprint}
```

86 cleveref

Pkg cleveref

cleveref package is used as-is with minor patches.

⚠ cleveref page numbers

cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for \cpageref and \cpagerefrange. This phrase includes \cpagerefFor, which defaults to "for".

Ex:

```
    \cpageref{tab:first,tab:second}
 in html becomes:
```

"pages **for** table 4.1 and **for** table 4.2"

See \cpagerefFor at page 538 to redefine the message which is printed for page number references.

loading order

cleveref and the following associated macro patches are automatically preloaded at the end of the preamble via \AtEndPreamble and \AfterEndPreamble. This is done because the HTML conversion requires cleveref. The user's document may not require cleveref, thus the user may never explicitly load it, so during HTML output lwarp loads it last. If the user's document preamble uses cleveref options, or functions such as \crefname, then cleveref may be loaded in the user's preamble near the end, and lwarp's additional loading of cleveref will have no effect.

Table 12 on page 461 shows the data structure of the label/reference system as revised by lwarp and cleveref.

A few patches allow cleveref to work as-is:

for HTML output:

```
\begin{warpHTML}
```

\AtEndPreable forces cleveref to be loaded last:

```
\AtEndPreamble{
\RequirePackage{cleveref}
}
```

The following patches are applied after cleveref has loaded, and after \AtBeginDocument. Print-mode versions are not required since they all come down to \ref eventually, and \ref has a print-mode version.

```
\AfterEndPreamble{
\LWR@traceinfo{Patching cleveref.}
```

\@@@setcref {⟨*kindofref*⟩} {⟨*label*⟩}

\@templabel becomes the section number.

```
\def\LWR@orig@@@setcref#1#2{\cref@getlabel{#2}{\@templabel}#1{\@templabel}{}{}}%

\ifdefequal{\@@setcref}{\LWR@orig@@@setcref}{% before v0.21
```

```
    \renewcommand*{\@@setcref}[2]{#1{\ref{#2}}{}{}}
}{
    \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% as of v0.21
        \renewcommand*{\@@@setcref}[2]{#1{\ref{#2}}{}{}}
    }{
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cref\space will fail.
        }%
    }
}
```

\@@@setcrefrange {⟨*text*⟩} {⟨*label*⟩} {⟨*label*⟩}

```
\def\LWR@orig@@@setcrefrange#1#2#3{%
  \cref@getlabel{#2}{\@labela}%
  \cref@getlabel{#3}{\@labelb}%
  #1{\@labela}{\@labelb}{}{}{}{}%

\ifdefequal{\@@setcrefrange}{\LWR@orig@@@setcrefrange}{
    \renewcommand{\@@setcrefrange}[3]{%
        #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
    }
}{
    \ifdefequal{\@@@setcrefrange}{\LWR@orig@@@setcrefrange}{
        \renewcommand{\@@@setcrefrange}[3]{%
            #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
        }
    }{
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\crefrange\space will fail.
        }
    }
}

```

\cpagerefFor Redefinable word between “page(s)” and the page numbers.

```
\newcommand*{\cpagerefFor}{for}
```

\@@@setcpageref {⟨*typeofref*⟩} {⟨*label*⟩}, where typeofref is “page” or “pages”

```
\def\LWR@orig@@setcpageref#1#2{% before v0.21
  \cref@getpageref{#2}{\@temppage}#1{\@temppage}{}{}}%

\def\LWR@orig@@@setcpageref#1#2{% as of v0.21
  \cpageref@getlabel{#2}{\@temppage}#1{\@temppage}{}{}}%

\ifdefequal{\@@setcpageref}{\LWR@orig@@setcpageref}{
    \renewcommand*{\@@setcpageref}[2]{%
        #1{\cpagerefFor\ \cref{#2}}{}{}%
```

```
    }
}{
    \ifdefequal{\@@@setcpageref}{\LWR@orig@@@setcpageref}{
        \renewcommand*{\@@@setcpageref}[2]{%
            #1{\cpagerefFor\ \cref{#2}}{}{}%
        }
    }
    {
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cpageref\space will fail.
        }
    }
}

\def\LWR@orig@@setcpagerefrange#1#2#3{% before v0.21
  \cref@getpageref{#2}{\@pagea}%
  \cref@getpageref{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}}%

\def\LWR@orig@@@setcpagerefrange#1#2#3{% as of v0.21
  \cpageref@getlabel{#2}{\@pagea}%
  \cpageref@getlabel{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}}%

\ifdefequal{\@@setcpagerefrange}{\LWR@orig@@setcpagerefrange}{
    \renewcommand*{\@@setcpagerefrange}[3]{%
        #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
    }
}{
    \ifdefequal{\@@@setcpagerefrange}{\LWR@orig@@@setcpagerefrange}{
        \renewcommand*{\@@@setcpagerefrange}[3]{%
            #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
        }
    }
    {
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cpagerefrange\space will fail.
        }
    }
}

}% AfterEndPreamble
```

Remember and patch some label-related defintions. These will be further encased and patched by other packages later.

`\label` and `\pageref` do NOT change their behavior according to print or HTML output, and thus do not use the `\LWR@formatted` system.

```
\LetLtxMacro\LWR@orig@label\label
\RenewDocumentCommand{\label}{}{\LWR@new@label}

\LetLtxMacro\LWR@orig@pageref\pageref
```

```
\RenewDocumentCommand{\pageref}{}{\LWR@new@pageref}
\end{warpHTML}
```

87 picture environment

Env picture The picture environment is enclosed inside a \lateximage.

for HTML output:

```
\begin{warpHTML}
```

Env picture

```
\BeforeBeginEnvironment{picture}{\begin{lateximage}[(picture)]}

\AfterEndEnvironment{picture}{\end{lateximage}}

\end{warpHTML}
```

88 Minipages and Boxes

A CSS flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

⚠ inline A line of text with an inline minipage or \parbox will have the minipage or \parbox placed onto its own line, because a paragraph is a block element and cannot be made inline-block.

placement minipages and \parboxes will be placed side-by-side in HTML unless you place a \newline between them.

side-by-side Side-by-side minipages may be separated by \quad, \qquad, \enskip, \hspace, \hfill, or a \rule. When inside a center environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side minipages and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span There is limited support for minipages inside an HTML . An HTML cannot appear inside a . While in a , minipages, and \parboxes, and any enclosed lists have limited HTML tags, resulting in an "inline" format, without markup except for HTML breaks. Use \newline or \par for an HTML break.

⚠ minipage size When using \linewidth, \textwidth, and \textheight, widths and heights in HTML are scaled proportionally to a 6×9 inch text area, and inside a multicols \linewidth is divided by the specified number of columns.

if width is \linewidth If a minipage or \parbox is assigned a width of exactly \linewidth, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if HTML A new macro \minipagefullwidth requests that, during HTML output, the next single

minipage or \parbox be generated without an HTML width attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ tabular, multicols

\UseMinipageWidths
\IgnoreMinipageWidths

Inside a tabular or multicols environment, where the width depends on the browser window, \minipagefullwidth is effectively used by default for every minipage or \parbox inside the environment. \UseMinipageWidths may be used to tell lwarp to honor the specified widths of all following minipages and \parboxes until the end of the local scope, and \IgnoreMinipageWidths may be used to tell lwarp to ignore the specified widths.

⚠ text alignment

Nested minipages adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a flushleft or similar environment in the child minipage to force a text alignment.

for HTML output:

```
\begin{warpHTML}
```

88.1 Counters and lengths

Ctr LWR@minipagedepth

Used to only reset the line width at the outermost minipage.

```
\newcounter{LWR@minipagedepth}
\setcounter{LWR@minipagedepth}{0}
```

Len \LWR@minipagewidth

Used to convert the width into printable units.

```
\newlength{\LWR@minipagewidth}
```

Len \LWR@minipageheight

Used to convert the height into printable units.

```
\newlength{\LWR@minipageheight}
```

88.2 Footnote handling

Also see section 58 for other forms of footnotes. Minipage footnotes are gathered in section 58.5, and then placed into the document in section 88.3.

88.3 Minipage handling

Bool LWR@minipagefullwidth

Should the next minipage have no HTML width?

```
\newbool{LWR@minipagefullwidth}
\boolfalse{LWR@minipagefullwidth}
```

Bool LWR@forceminipagefullwidth

Should the next minipage have no HTML width? Used to force full width for all minipages in an environment such as tabular or multicols, where the actual

width depends on the browser width. Controlled by \useminipagewidths and \ignoreminipagewidths.

```
\newbool{LWR@forceminipagefullwidth}
\boolfalse{LWR@forceminipagefullwidth}
```

\minipagefullwidth Requests that the next minipage have no width tag in HTML:

for HTML output:

```
\newcommand*{\minipagefullwidth}{\global\booltrue{LWR@minipagefullwidth}}
```

\UseMinipageWidths Locally requests that minipage widths be honored.

```
\newcommand*{\UseMinipageWidths}{\boolfalse{LWR@forceminipagefullwidth}}
```

\IgnoreMinipageWidths Locally requests that minipage widths be honored.

```
\newcommand*{\IgnoreMinipageWidths}{\booltrue{LWR@forceminipagefullwidth}}
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\minipagefullwidth}{}
\newcommand*{\UseMinipageWidths}{}
\newcommand*{\IgnoreMinipageWidths}{}
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

Bool LWR@minipagethispar Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.

```
\newbool{LWR@minipagethispar}
\boolfalse{LWR@minipagethispar}
```

Env minipage [⟨*vert position*⟩] [⟨*height*⟩] [⟨*inner vert position*⟩] {⟨*width*⟩}

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using \linewidth, \textwidth, or \textheight, these are scaled proportionally to a 6×9 inch text area.

```
\NewDocumentEnvironment{LWR@HTML@sub@minipage}{m m m m}
{%
\LWR@traceinfo{minipage}%
```

Temporarily open a group, in which width and height is computed based on a virtual page size instead of the extra-large PDF page used during HTML tag generation.

The following used to be an actual LaTeX minipage.

```
\begingroup
```

Compute width, adjusted for frames:

```
\setlength{\LWR@minipagewidth}{#4}%
\ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}{%
```

Only create a new page if not yet nested:

```
    \LWR@orignewpage%
```

Adjust virtual page size:

```
    \addtolength{\LWR@minipagewidth}{3em}% room for frames
    \setlength{\linewidth}{6in}%
    \setlength{\textwidth}{6in}%
    \setlength{\textheight}{9in}%
}{}%
\LWR@traceinfo{computed width is \LWR@printlength{\LWR@minipagewidth}}%
```

Compute height:

```
\setlength{\LWR@minipageheight}{\textheight}% default unless specified
\ifblank{#2}{}{\setlength{\LWR@minipageheight}{#2}}%
```

Track nesting depth:

```
\addtocounter{LWR@minipagedepth}{1}%
```

LaTeX wants to start a paragraph for the virtual minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

```
\ifbool{FormatWP}{\newline}{}%
\LWR@stoppars%
```

If `FormatWP`, add a text frame:

```
\ifbool{FormatWP}{%

\addtocounter{LWR@thisautoidWP}{1}%
\LWR@htmltag{%
    div id="\LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}" %
    class="wpminipage"%
}%

}{}%
```

Create the `<div>` tag with optional alignment style:

```
\LWR@traceinfo{minipage: creating div class}%
\LWR@htmltag{div class="minipage" style="%
\ifthenelse{\equal{#1}{t}}{\LWR@print@mbox{vertical-align:bottom} ; }{}%
\ifthenelse{\equal{#1}{c}}{\LWR@print@mbox{vertical-align:middle} ; }{}%
\ifthenelse{\equal{#1}{b}}{\LWR@print@mbox{vertical-align:top} ; }{}%
```

```
\ifthenelse{\equal{#3}{t}}{\LWR@print@mbox{justify-content:flex-start} ; }{}%
\ifthenelse{\equal{#3}{c}}{\LWR@print@mbox{justify-content:center} ; }{}%
\ifthenelse{\equal{#3}{b}}{\LWR@print@mbox{justify-content:flex-end} ; }{}%
\ifthenelse{\equal{#3}{s}}{\LWR@print@mbox{justify-content:space-between} ; }{}%
```

Print the width and optional height styles:

```
\LWR@traceinfo{minipage: about to print the width of \LWR@printlength{\LWR@minipagewidth}}%
\ifbool{LWR@minipagefullwidth}%
{\global\boolfalse{LWR@minipagefullwidth}}%
{%
    \ifbool{LWR@forceminipagefullwidth}%
        {}%
        {%
            \ifthenelse{\lengthtest{#4}=\linewidth}%
                {}%
                {width:\LWR@printlength{\LWR@minipagewidth} ; }%
        }%
}%
\LWR@traceinfo{minipage: about to print the height}%
\ifblank{#2}{}{height:\LWR@printlength{\LWR@minipageheight} ; }%
"}%
```

Finish with an empty line to start the contents on a new line.

```

% The preceding empty line is required.
```

Set the user-accessible line and text width and height values inside the virtual minipage. These do not affect the actual size of the PDF output, but are used by any reference to `\linewidth`, etc. inside the virtual minipage being created here.

```
\setlength{\linewidth}{#4}% the original width
\setlength{\textwidth}{6in}%
\setlength{\textheight}{9in}%
```

`\raggedright` cancels hyphenation, which will be done by HTML instead.

```
\LWR@print@raggedright%
```

Set minipage footnotes:

```
\def\@mpfn{mpfootnote}%
\def\thempfn{\thempfootnote}\c@mpfootnote\z@%
\let\@footnotetext\@mpfootnotetext%
```

Resume paragraph tag handling for the contents of the minipage:

```
\LWR@startpars%
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

=== begin minipage ===

}{}%
```

```
\LWR@traceinfo{minipage: finished starting the minipage}%
}% finished \minipage
{% \endminipage
```

Print pending minipage footnotes:

```
\LWR@printpendingmpfootnotes%
```

End the environment with closing tag:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

=== end minipage ===

}{}%
\LWR@stoppars%
```

The following used to be an actual LaTeX minipage.

```
\endgroup%

\ifbool{FormatWP}{%

\LWR@htmlelementend{div}%

}{}%
\LWR@htmldivclassend{minipage}%

\addtocounter{LWR@minipagedepth}{-1}%
\LWR@startpars%
\ifbool{FormatWP}{\newline}{}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{LWR@minipage: done}%
}

\NewDocumentEnvironment{LWR@HTML@minipage}{O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#1}{#2}{#3}{#4}}
    {\endLWR@HTML@sub@minipage}

\LWR@formattedenv{minipage}
```

88.4 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox

for HTML output:

\parbox [⟨*pos*⟩] [⟨*height*⟩] [⟨*inner-pos*⟩] {⟨*width*⟩} {⟨*text*⟩}

A parbox uses the minipage code:

```
\NewDocumentCommand{\LWR@HTML@parbox}{O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#1][#2][#3]{#4}%
#5
\end{minipage}%
}

\LWR@formatted{parbox}
```

\mbox {⟨*text*⟩} Nullified for HTML.

```
\newcommand*{\LWR@HTML@mbox}[1]{#1}

\LWR@formatted{mbox}
```

\LWR@@makebox@paren {⟨*width*⟩} , {⟨*height*⟩}

Adds to the style in \LWR@temptwo.

```
\NewDocumentCommand{\LWR@@makebox@paren}{m m}{%
\IfValueTF{#2}{%
    \setlength{\LWR@tempwidth}{#1\unitlength}%
    \setlength{\LWR@tempheight}{#2\unitlength}%
    \appto{\LWR@temptwo}{%
        \LWR@print@mbox{width:\LWR@printlength{\LWR@tempwidth}} ; % space
        \LWR@print@mbox{height:\LWR@printlength{\LWR@tempheight}} ; % space
    }%
}{%
    \PackageError{lwarp}%
        {(width,height) is missing a comma ',' character}%
        {\protect\makebox\space \protect\framebox\space accept
            a size in the format (width,height).}%
}%
}
```

\LWR@@makebox@align {⟨*alignment character*⟩}

Adds to the style in \LWR@temptwo.

```
\newcommand*{\LWR@@makebox@align}[1]{%
    \def\LWR@align{center}%
    \ifstrequal{#1}{l}{\def\LWR@align{left}}{}%
    \ifstrequal{#1}{r}{\def\LWR@align{right}}{}%
    \ifstrequal{#1}{s}{\def\LWR@align{justify}}{}%
    \appto{\LWR@temptwo}{%
        \LWR@print@mbox{text-align:\LWR@align} ; %
    }%
}
```

\makebox (⟨*width,height*⟩) [⟨*width*⟩] [⟨*pos*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@makebox}{>{\SplitArgument{1}{,}}d() o o m}{%
```

Build the style depending on arguments:

```
{% scope
    \def\LWR@temptwo{}%
    \IfValueTF{#1}%
    {% (width,height) ..
        \LWR@@makebox@paren #1%
        \IfValueT{#2}%
        {% (width,height) [posn]
            \LWR@@makebox@align{#2}%
        }%
    }%
    {% [width]
        \setlength{\LWR@tempwidth}{#2}%
        \appto{\LWR@temptwo}{%
            width:\LWR@printlength{\LWR@tempwidth} ; % space
        }%
        \IfValueT{#3}%
        {% [width] [posn]
            \LWR@@makebox@align{#3}%
        }%
    }%
    \InlineClass[%
        \LWR@print@mbox{display:inline-block} ; %
        \LWR@temptwo%
    ]%
    {makebox}%
    {#4}%
}% scope
}
\LWR@formatted{makebox}
```

`\framebox` (⟨*width,height*⟩) [⟨*width*⟩] [⟨*pos*⟩] {⟨*text*⟩}

```
\LetLtxMacro\LWR@origframebox\framebox

\NewDocumentCommand{\LWR@HTML@framebox}{d() o o m}{%
    \fbox{\makebox(#1)[#2][#3]{#4}}%
}

\LWR@formatted{framebox}
```

`\LWR@forceminwidth` {⟨*legth*⟩}

Sets `\LWR@atleastonept` to be at least 1pt.

```
\newlength{\LWR@atleastonept}

\newcommand*{\LWR@forceminwidth}[1]{%
\setlength{\LWR@atleastonept}{#1}%
\ifthenelse{%
    \lengthtest{\LWR@atleastonept>0pt}\AND%
    \lengthtest{\LWR@atleastonept<1pt}%
}%
```

```
    {\setlength{\LWR@atleastonept}{1pt}}%
    {}%
}
```

\LWR@fboxstyle Prints the HTML attributes for a black border and padding.

\LWR@forceminwidth must be used first in order to set the border width.

```
\newcommand*{\LWR@fboxstyle}{%
\LWR@findcurrenttextcolor%
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@origpound\LWR@tempcolor ; %
padding:\LWR@printlength{\fboxsep} ; %
color:\LWR@origpound\LWR@tempcolor%
}
```

\fbox {⟨*text*⟩}

Creates a framed inline span enclosing the text.

Create a new HTML version, but don't use it until after xcolor may have loaded:

```
\newcommand{\LWR@HTML@fbox}[1]{%
\LWR@traceinfo{HTML fbox}%
\LWR@forceminwidth{\fboxrule}%
\InlineClass[%
\LWR@fboxstyle%
]{fbox}{#1}%
}
```

xcolor \lets things to \fbox when it is loaded, and this must remain even for HTML output while in a lateximage, so \fbox is not modified until \AtBeginDocument:

```
\AtBeginDocument{\LWR@formatted{fbox}}
```

\fboxBlock {⟨*text*⟩} Creates a framed HTML of the text.

First, a print-mode version. This is newly defined for print mode, so it is defined inside warpall.

for HTML & PRINT:

```
\end{warpHTML}
\begin{warpall}
\let\fboxBlock\fbox
\end{warpall}

\begin{warpHTML}
```

for HTML output: Next, an HTML version:

```
\newcommand{\LWR@HTML@fboxBlock}[1]{%
\LWR@forceminwidth{\fboxrule}%
\begin{BlockClass}[%
\LWR@fboxstyle%
]{fboxBlock}
```

```
#1
\end{BlockClass}
}

\LWR@formatted{fboxBlock}

\end{warpHTML}
```

Env `fminipage` [⟨*align*⟩] [⟨*height*⟩] [⟨*align*⟩] {⟨*width*⟩}

Creates a framed HTML around its contents.

for HTML & PRINT: Print version:

```
\begin{warpall}

\newsavebox{\LWR@fminipagebox}

\NewDocumentEnvironment{LWR@print@fminipage}{O{t} o O{t} m}
{%
```

An outer minipage will be used for vertical alignment. An inner minipage will be framed with \fbox.

If the optional inner alignment is not given, use the outer instead:

```
\IfValueTF{#3}%
{\def\LWR@thisalign{#3}}
{\def\LWR@thisalign{#1}}%
```

Form the outer minipage depending on whether a height was given. Make the outer minipage larger to compensate for the frame.

```
\IfValueTF{#2}%
{\minipage[#1][#2+2\fboxsep+2\fboxrule][\LWR@thisalign]{#4+2\fboxsep+2\fboxrule}}%
{\minipage[#1]{#4+2\fboxsep+2\fboxrule}}%
```

Capture the contents of the environment:

```
\begin{lrbox}{\LWR@fminipagebox}%
```

Nest the contents inside an inner minipage of the desired size:

```
\IfValueTF{#2}%
{\minipage[#1][#2][\LWR@thisalign]{#4}}%
{\minipage[#1]{#4}}%
}
{%
```

Close the inner minipage and the LR box with the contents:

```
\endminipage%
\end{lrbox}%
```

Create a frame around the contents of the environment:

```
\fbox{\usebox{\LWR@fminipagebox}}%
```

The entire thing is placed inside the outer minipage:

```
\endminipage%
}

\LetLtxMacro\fminipage\LWR@print@fminipage
\LetLtxMacro\endfminipage\endLWR@print@fminipage
% \newenvironment{fminipage}{\LWR@print@fminipage}{\endLWR@print@fminipage}

\end{warpall}
```

HTML version:

for HTML output:

```
\begin{warpHTML}

\NewDocumentEnvironment{LWR@HTML@fminipage}{O{t} o O{t} m}
{%
\LWR@traceinfo{fminipage #1 #2 #3 #4}%
\LWR@forceminwidth{\fboxrule}%
\setlength{\LWR@tempwidth}{#4}%
\IfValueT{#2}{\setlength{\LWR@tempheight}{#2}}%

\LWR@stoppars%

\begin{BlockClass}[%
\LWR@fboxstyle ; %
\IfValueT{#2}{height:\LWR@printlength{\LWR@tempheight} ; }%
\ifbool{LWR@minipagefullwidth}%
{\global\boolfalse{LWR@minipagefullwidth}}%
{%
    \ifbool{LWR@forceminipagefullwidth}%
        {}%
        {%
            \ifthenelse{\lengthtest{\LWR@tempwidth}=\linewidth}%
                {}%
                {width:\LWR@printlength{\LWR@tempwidth} ; }%
        }%
}%
]{fminipage}%
}
{%
\end{BlockClass}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{fminipage done}%
}

```

```
\LWR@formattedenv{fminipage}
```

```
\end{warpHTML}
```

\raisebox {⟨*raiselen*⟩} [⟨*height*⟩] [⟨*depth*⟩] {⟨*text*⟩}

```
\begin{warpHTML}

\NewDocumentCommand{\LWR@HTML@raisebox}{m o o m}{%
#4%
}

\LWR@formatted{raisebox}
```

```
\end{warpHTML}
```

89 Direct formatting

⚠ \bfseries, etc. \textbf, etc. are supported, but \bfseries, etc. work only in some situations.

⚠ HTML special chars &, <, and > have special meanings in HTML. If \&, \textless, and \textgreater are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the listings package is supported, and its literate option is used to convert &, <, and > to proper HTML entities.

verbatim The various verbatim-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

For high-level block and inline custom CSS classes, see section 51.9.

for HTML output:

```
\begin{warpHTML}
```

\emph {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@emph}[1]{%
    {%
        \itshape%
        \LWR@htmlspan{em}{#1}%
    }%
}
\LWR@formatted{emph}

\DeclareRobustCommand{\LWR@null@emph}[1]{#1}
```

\textmd {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textmd}[1]{%
    {%
        \mdseries%
        \InlineClass(font-weight:normal){textmd}{#1}%
    }%
}
\LWR@formatted{textmd}

\DeclareRobustCommand{\LWR@null@textmd}[1]{#1}
```

\textbf {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textbf}[1]{%
    {%
        \bfseries%
        \LWR@htmlspan{b}{#1}%
    }%
}
\LWR@formatted{textbf}

\DeclareRobustCommand{\LWR@null@textbf}[1]{#1}
```

\textrm {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textrm}[1]{%
    {%
        \rmfamily%
        \InlineClass(font-family:serif){textrm}{#1}%
    }%
}
\LWR@formatted{textrm}

\DeclareRobustCommand{\LWR@null@textrm}[1]{#1}
```

\textsf {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsf}[1]{%
    {%
        \sffamily%
        \InlineClass(font-family:sans){textsf}{#1}%
    }%
}
\LWR@formatted{textsf}

\DeclareRobustCommand{\LWR@null@textsf}[1]{#1}
```

\texttt {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@texttt}[1]{%
    {%
        \ttfamily%
        \LWR@htmlspan{kbd}{#1}%
```

```
    }%
}
\LWR@formatted{texttt}

\DeclareRobustCommand{\LWR@null@texttt}[1]{#1}
```

\textup {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textup}[1]{%
    {%
        \upshape%
        \InlineClass(font-style:normal){textup}{#1}%
    }%
}
\LWR@formatted{textup}

\DeclareRobustCommand{\LWR@null@textup}[1]{#1}
```

\textit {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textit}[1]{%
    {%
        \itshape%
        \LWR@htmlspan{i}{#1}%
    }%
}
\LWR@formatted{textit}

\DeclareRobustCommand{\LWR@null@textit}[1]{#1}
```

\textsc {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsc}[1]{%
    {%
        \scshape%
        \InlineClass(
            font-variant: small-caps ;
            font-variant-numeric: oldstyle-nums ;
        ){textsc}{#1}%
    }%
}
\LWR@formatted{textsc}

\DeclareRobustCommand{\LWR@null@textsc}[1]{#1}
```

\textsi {⟨*text*⟩}

```
\@ifundefined{textsi}{
    \LetLtxMacro\LWR@print@textsi\LWR@print@textsc
}{}

\DeclareRobustCommand{\LWR@HTML@textsi}[1]{%
```

```
    {%
        \sishape%
        \InlineClass(
            font-style: italic;
            font-variant: small-caps ;
            font-variant-numeric: oldstyle-nums ;
        ){textsi}{#1}%
    }%
}
\LWR@formatted{textsi}

\DeclareRobustCommand{\LWR@null@textsi}[1]{#1}
```

\textsl {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsl}[1]{%
    {%
        \slshape%
        \InlineClass(font-style:oblique){textsl}{#1}%
    }%
}
\LWR@formatted{textsl}

\DeclareRobustCommand{\LWR@null@textsl}[1]{#1}
```

\textnormal {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textnormal}[1]{\textmd{\textrm{\textup{#1}}}}
\LWR@formatted{textnormal}

\DeclareRobustCommand{\LWR@null@textnormal}[1]{#1}
```

```
\DeclareRobustCommand{\LWR@null@rmfamily}{}
\DeclareRobustCommand{\LWR@null@sffamily}{}
\DeclareRobustCommand{\LWR@null@ttfamily}{}
\DeclareRobustCommand{\LWR@null@bfseries}{}
\DeclareRobustCommand{\LWR@null@mdseries}{}
\DeclareRobustCommand{\LWR@null@upshape}{}
\DeclareRobustCommand{\LWR@null@slshape}{}
\DeclareRobustCommand{\LWR@null@scshape}{}
\DeclareRobustCommand{\LWR@null@itshape}{}
\DeclareRobustCommand{\LWR@null@normalfont}{}
```

```
\DeclareRobustCommand{\LWR@null@em}{}
```

\LWR@nullfonts Removes formatting during filename operations, file references, and HTML comments.

⚠ Use only inside a group.

The following are *not* made robust, since they must be expanded to their nullified versions.

```
\catcode`\$=\active% redefining $ below
\catcode`\_=12% redefining \_ below
\newcommand*{\LWR@nullfonts}{%
\LetLtxMacro\emph\LWR@null@emph%
\LetLtxMacro\textmd\LWR@null@textmd%
\LetLtxMacro\textbf\LWR@null@textbf%
\LetLtxMacro\textrm\LWR@null@textrm%
\LetLtxMacro\textsf\LWR@null@textsf%
\LetLtxMacro\texttt\LWR@null@texttt%
\LetLtxMacro\textup\LWR@null@textup%
\LetLtxMacro\textit\LWR@null@textit%
\LetLtxMacro\textsc\LWR@null@textsc%
\LetLtxMacro\textsi\LWR@null@textsi%
\LetLtxMacro\textsl\LWR@null@textsl%
\LetLtxMacro\textnormal\LWR@null@textnormal%
\LetLtxMacro\rmfamily\LWR@null@rmfamily%
\LetLtxMacro\sffamily\LWR@null@sffamily%
\LetLtxMacro\ttfamily\LWR@null@ttfamily%
\LetLtxMacro\bfseries\LWR@null@bfseries%
\LetLtxMacro\mdseries\LWR@null@mdseries%
\LetLtxMacro\upshape\LWR@null@upshape%
\LetLtxMacro\slshape\LWR@null@slshape%
\LetLtxMacro\scshape\LWR@null@scshape%
\LetLtxMacro\sishape\LWR@null@sishape%
\LetLtxMacro\itshape\LWR@null@itshape%
\LetLtxMacro\normalfont\LWR@null@normalfont%
\LetLtxMacro\em\LWR@null@em%
```

Various built-in symbols.

```
\renewcommand*{\$}{-}%
\renewcommand*{\%}{-}%
\renewcommand*{\_}{-}%
\renewcommand*{\}}{-}%
\renewcommand*{\{}{-}%
\renewcommand*{\&}{and}%
\renewcommand*{\#}{-}%
\renewcommand*{\,}{-}%
\renewcommand*{~}{-}%
\renewcommand*{\^}[1]{-}%
\renewcommand*{\~}[1]{-}%
\renewcommand*{\newline}{-}%
\renewcommand*{\textasciicircum}{-}%
\renewcommand*{\textasciitilde}{-}%
\renewcommand*{\textasteriskcentered}{-}%
\renewcommand*{\textbackslash}{-}%
\renewcommand*{\textbar}{-}%
\renewcommand*{\textbardbl}{-}%
\renewcommand*{\textbigcircle}{-}%
\renewcommand*{\textbraceleft}{-}%
\renewcommand*{\textbraceright}{-}%
\renewcommand*{\textbullet}{-}%
```

```
\renewcommand*{\textcopyright}{-}%
\renewcommand*{\textdagger}{-}%
\renewcommand*{\textdaggerdbl}{-}%
\renewcommand*{\textdollar}{-}%
\renewcommand*{\textellipsis}{-}%
\renewcommand*{\textemdash}{-}%
\renewcommand*{\textendash}{-}%
\renewcommand*{\textexclamdown}{-}%
\renewcommand*{\textgreater}{-}%
\renewcommand*{\textless}{-}%
\renewcommand*{\textordfeminine}{-}%
\renewcommand*{\textordmasculine}{-}%
\renewcommand*{\textparagraph}{-}%
\renewcommand*{\textperiodcentered}{-}%
\renewcommand*{\textpertenthousand}{-}%
\renewcommand*{\textperthousand}{-}%
\renewcommand*{\textquestiondown}{-}%
\renewcommand*{\textquotedblleft}{-}%
\renewcommand*{\textquotedblright}{-}%
\renewcommand*{\textquoteleft}{-}%
\renewcommand*{\textquoteright}{-}%
\renewcommand*{\textregistered}{-}%
\renewcommand*{\textsection}{-}%
\renewcommand*{\textsterling}{-}%
\renewcommand*{\texttrademark}{-}%
\renewcommand*{\textunderscore}{-}%
\renewcommand*{\textvisiblespace}{-}%
\renewcommand*{\copyright}{-}%
\renewcommand*{\dag}{-}%
\renewcommand*{\ddag}{-}%
\renewcommand*{\dots}{-}%
\renewcommand*{\P}{-}%
\renewcommand*{\pounds}{-}%
\renewcommand*{\S}{-}%
\renewcommand*{\aa}{a}%
\renewcommand*{\AA}{A}%
\renewcommand*{\AE}{AE}%
\renewcommand*{\ae}{ae}%
\renewcommand*{\dh}{d}%
\renewcommand*{\DH}{D}%
\renewcommand*{\DJ}{D}%
\renewcommand*{\dj}{d}%
\renewcommand*{\IJ}{IJ}%
\renewcommand*{\ij}{ij}%
\renewcommand*{\L}{L}%
\renewcommand*{\l}{l}%
\renewcommand*{\NG}{NG}%
\renewcommand*{\ng}{ng}%
\renewcommand*{\O}{O}%
\renewcommand*{\o}{o}%
\renewcommand*{\oe}{oe}%
\renewcommand*{\OE}{OE}%
\renewcommand*{\ss}{ss}%
\renewcommand*{\SS}{SS}%
\renewcommand*{\th}{th}%
```

```
\renewcommand*{\TH}{TH}%
\renewcommand*{\guillemotleft}{}%
\renewcommand*{\guilsinglleft}{}%
\renewcommand*{\quotedblbase}{}%
\renewcommand*{\textquotedbl}{}%
\renewcommand*{\guillemotright}{}%
\renewcommand*{\guilsinglright}{}%
\renewcommand*{\quotesinglbase}{}%
```

```
\renewcommand*{\HTMLunicode}[1]{}%
\renewcommand*{\HTMLentity}[1]{}%
```

```
\renewcommand{\textsuperscript}[1]{##1}%
\renewcommand{\textsubscript}[1]{##1}%
```

```
\renewcommand{\underline}[1]{##1}%
```

```
\RenewDocumentCommand{\LWR@htmlspanclass}{o m +m}{##3}%
\DeclareExpandableDocumentCommand{\InlineClass}{D{(}{)}{} o m +m}{##4}%
```

Nullify math macros.

```
\def\(##1\){}%
\def\[##1\]{}%
\RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
\protected\def$##1${}%
```

Nullify logos:

```
\renewcommand*{\TeX}{TeX}%
\renewcommand*{\LaTeX}{LaTeX}%
\renewcommand*{\LaTeXe}{LaTeX2e}%
\renewcommand*{\LuaTeX}{LuaTeX}%
\renewcommand*{\LuaLaTeX}{LuaLaTeX}%
\renewcommand*{\XeTeX}{XeTeX}%
\renewcommand*{\XeLaTeX}{XeLaTeX}%
\renewcommand*{\ConTeXt}{ConTeXt}%
\renewcommand*{\BibTeX}{BibTeX}%
\renewcommand*{\MakeIndex}{MakeIndex}%
\renewcommand*{\AmS}{AmS}%
\renewcommand*{\MiKTeX}{MiKTeX}%
\renewcommand*{\LyX}{LyX}%
```

Use the simpler form with `\texorpdfstring`:

```
\let\texorpdfstring\relax%
\newcommand{\texorpdfstring}[2]{##2}%
}
\catcode`\$=3%
\catcode`\_=8%
```

`\FilenameNullify` {⟨*redefinitions*⟩}

Adds more nullifying definitions for filename generation.

```
\newcommand*{\FilenameNullify}[1]{%
    \appto{\LWR@nullfonts}{#1}%
}
```

Remembers the current font family, series, and shape.

```
\newcommand*{\LWR@f@family}{rm}
\newcommand*{\LWR@f@series}{md}
\newcommand*{\LWR@f@shape}{up}
```

\LWR@textcurrentfont {⟨*text*⟩}

Prints the text with the current font choices. Avoids nesting repeated font selections.

```
\newcounter{LWR@textcurrentfontdepth}
\setcounter{LWR@textcurrentfontdepth}{0}

\newcommand*{\LWR@textcurrentfont}[1]{%
    \ifnumcomp{\value{LWR@textcurrentfontdepth}}{>}{0}%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            #1%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
        }%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            \InlineClass{%
                    text\LWR@f@family\LWR@origtilde{}%
                    text\LWR@f@series\LWR@origtilde{}%
                    text\LWR@f@shape%
                }%
                {#1}%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
        }%
}
```

Env LWR@blocktextcurrentfont Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{%
\BlockClass{%
        text\LWR@f@family\LWR@origtilde{}%
        text\LWR@f@series\LWR@origtilde{}%
        text\LWR@f@shape%
    }%
}{\endBlockClass}
```

\mdseries

```
\renewrobustcmd*{\mdseries}{\renewcommand*{\LWR@f@series}{md}}
```

\bfseries

```
\renewrobustcmd*{\bfseries}{\renewcommand*{\LWR@f@series}{bf}}
```

\rmfamily

```
\renewrobustcmd*{\rmfamily}{\renewcommand*{\LWR@f@family}{rm}}
```

\sffamily

```
\renewrobustcmd*{\sffamily}{\renewcommand*{\LWR@f@family}{sf}}
```

\ttfamily

```
\renewrobustcmd*{\ttfamily}{\renewcommand*{\LWR@f@family}{tt}}
```

\upshape

```
\renewrobustcmd*{\upshape}{\renewcommand*{\LWR@f@shape}{up}}
```

\itshape

```
\renewrobustcmd*{\itshape}{\renewcommand*{\LWR@f@shape}{it}}
```

\scshape

```
\renewrobustcmd*{\scshape}{\renewcommand*{\LWR@f@shape}{sc}}
```

\sishape

```
\@ifundefined{sishape}{
    \newrobustcmd*{\sishape}{\renewcommand*{\LWR@f@shape}{si}}
}{
    \renewrobustcmd*{\sishape}{\renewcommand*{\LWR@f@shape}{si}}
}
```

\slshape

```
\renewrobustcmd*{\slshape}{\renewcommand*{\LWR@f@shape}{sl}}
```

\normalfont

```
\renewrobustcmd*{\normalfont}{\rmfamily\mdseries\upshape}
```

\sp {⟨*text*⟩}

For siunitx. Must work in math mode.

```
\renewcommand{\sp}[1]{\text{<sup>#1</sup>}{}}
```

\sb {⟨*text*⟩}

For siunitx. Must work in math mode.

```
\renewcommand{\sb}[1]{\text{<sub>#1</sub>}{}}
```

\textsuperscript {⟨*text*⟩}

```
\renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

\@textsuperscript {⟨*text*⟩}

```
\renewcommand{\@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

\textsubscript {⟨*text*⟩}

```
\AtBeginDocument{
\renewrobustcmd{\textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
}
```

\@textsubscript {⟨*text*⟩}

```
\AtBeginDocument{
\renewcommand{\@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
}
```

\up {⟨*text*⟩} Prints superscript.

This is \let at the beginning of the document in case some other package has changed the definition.

```
\AtBeginDocument{\let\up\textsuperscript}
```

\fup {⟨*text*⟩} Prints superscript.

Supports fmtcount package.

This is \let at the beginning of the document in case some other package has changed the definition.

```
\AtBeginDocument{\let\fup\textsuperscript}
```

\underline {⟨*text*⟩}

```
\renewcommand{\underline}[1]{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {underline}{#1}%
}
```

\LWR@overline {⟨*text*⟩}

```
\newcommand{\LWR@overline}[1]{%
    \InlineClass%
        (text-decoration:overline; text-decoration-skip: auto)%
        {overline}{#1}%
}
```

\LWR@currenttextcolor The color to use for text and \rule, defaulting to black:

```
\newcommand*{\LWR@currenttextcolor}{black}
```

\LWR@tempcolor
\LWR@tempcolortwo The color converted to HTML colorspace.

```
\newcommand*{\LWR@tempcolor}{}
\newcommand*{\LWR@tempcolortwo}{}
```

\LWR@findcurrenttextcolor Sets \LWR@tempcolor to the current color.

```
\newcommand*{\LWR@findcurrenttextcolor}{%
\renewcommand{\LWR@tempcolor}{000000}%
}
```

\LWR@textcurrentcolor {⟨*text*⟩} Like \textcolor but uses the current \color instead.

```
\NewDocumentCommand{\LWR@textcurrentcolor}{m}{%
    \renewcommand*{\LWR@currenttextcolor}{black}%
    #1%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\LWR@textcurrentfont {⟨*text*⟩}

Prints the text with the current font choices.

```
\newcommand*{\LWR@textcurrentfont}[1]{#1}
```

Env LWR@blocktextcurrentfont Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{}{}
```

\FilenameNullify {⟨*macros to nullify*⟩}

```
\newcommand*{\FilenameNullify}[1]{}
```

```
\end{warpprint}
```

90 Skips, spaces, font sizes

for HTML output:
```
\begin{warpHTML}
```

\, and \thinspace may be redefined by other packages, so are redefined \AtBeginDocument here.

Direct-formatting space commands become HTML entities:

```
\AtBeginDocument{
\renewrobustcmd*{\,}{\HTMLunicode{202f}} % HTML thin non-breakable space
\renewrobustcmd*{\thinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{\negthinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{~}{\HTMLentity{nbsp}}
\renewrobustcmd*{\textellipsis}{\HTMLunicode{2026}}
}
```

Direct-formatting font sizes are ignored:

```
\newrobustcmd*{\LWR@HTML@normalsize}{}
\LWR@formatted{normalsize}

\newrobustcmd*{\LWR@HTML@small}{}
\LWR@formatted{small}

\newrobustcmd*{\LWR@HTML@footnotesize}{}
\LWR@formatted{footnotesize}

\newrobustcmd*{\LWR@HTML@scriptsize}{}
\LWR@formatted{scriptsize}

\newrobustcmd*{\LWR@HTML@tiny}{}
\LWR@formatted{tiny}

\newrobustcmd*{\LWR@HTML@large}{}
\LWR@formatted{large}

\newrobustcmd*{\LWR@HTML@Large}{}
\LWR@formatted{Large}

\newrobustcmd*{\LWR@HTML@LARGE}{}
\LWR@formatted{LARGE}

\newrobustcmd*{\LWR@HTML@huge}{}
\LWR@formatted{huge}

\newrobustcmd*{\LWR@HTML@Huge}{}
\LWR@formatted{Huge}
```

```
\DeclareDocumentCommand{\onecolumn}{}{}

\DeclareDocumentCommand{\twocolumn}{O{}}{
```

```
#1

}
```

\hfill

```
\newcommand*{\LWR@HTML@hfill}{\qquad}
\LWR@formatted{hfill}
```

\hrulefill

```
\newcommand*{\LWR@HTML@hrulefill}{\rule{1in}{1pt}}
\LWR@formatted{hrulefill}
```

\dotfill

```
\newcommand*{\LWR@HTML@dotfill}{\dots}
\LWR@formatted{dotfill}
```

\newpage

```
\renewcommand*{\newpage}{

}
```

\newline Uses the HTML <br /> element.

```
\newrobustcmd*{\LWR@newlinebr}{\unskip\LWR@htmltag{br /}\LWR@orignewline}%
\LetLtxMacro\newline\LWR@newlinebr
```

\\ Redefined to \LWR@endofline or \LWR@tabularendofline.

\LWR@endofline * [⟨*len*⟩]

\\ is assigned to \LWR@endofline at \LWR@LwarpStart.

Inside tabular, \\ is temporarily changed to \LWR@tabularendofline.

```
\LetLtxMacro\LWR@origendofline\\
\NewDocumentCommand{\LWR@endofline}{s O{0pt}}
{%
\newline%

\setlength{\LWR@templengthone}{#2}%
\ifdimgreater{\LWR@templengthone}{0pt}{\newline}{}%
}
```

\LWR@minipagestartpars Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a to be inside a p, paragraphs must

be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, lwarp correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to be on its own line. Since people often place small horizontal space between minipages, it is desirable to maintain this space if possible. lwarp tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around \hspace, \enskip, \quad, and \qquad until the end of the paragraph, when the closing p tag is created.

\hspace
\enskip
\quad
\qquad

When a minipage is seen, the boolean LWR@minipagethispar is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. LWR@minipagethispar is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestartpars}{%
\ifbool{LWR@minipagethispar}{\LWR@startpars}{}%
}
```

\LWR@minipagestoppars

Placed just after \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestoppars}{%
\ifbool{LWR@minipagethispar}{\LWR@stoppars}{}%
}
```

\quad

Handles special minipage & horizontal space interactions. Uses 2003 EM SPACE to pass validation.

```
\renewrobustcmd*{\quad}{%
\LWR@minipagestoppars%
\HTMLunicode{2003}%
\LWR@minipagestartpars%
}
```

\qquad

Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\qquad}{\quad\quad}
```

\enskip

Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\enskip}{%
\LWR@minipagestoppars%
\HTMLunicode{2002}%
\LWR@minipagestartpars%
}
```

Len \LWR@tempwidth
Len \LWR@tempheight
Len \LWR@tempraise

Used to compute span width, height, raise for \hspace and \rule:

```
\newlength{\LWR@tempwidth}
```

```
\newlength{\LWR@tempheight}
\newlength{\LWR@tempraise}
```

\LWR@select@html@hspace
\hspace

* {⟨*length*⟩} * {⟨*length*⟩}

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

`\hspace{\fill}` is converted to `\hspace{2em}`, equal to `\qquad`.

```
\newcommand{\LWR@select@html@hspace}{%
\RenewDocumentCommand{\hspace}{s m}{%
\setlength{\LWR@tempwidth}{##2}%
```

If `\fill`, change to `\qquad`:

```
\ifnum\gluestretchorder\LWR@tempwidth>0%
\setlength{\LWR@tempwidth}{2em}%
\fi%
```

Only if the width is not zero:

```
\ifdimcomp{\LWR@tempwidth}{=}{0pt}{}{%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Support the HTML thin wrappable space:

```
    \ifdimcomp{\LWR@tempwidth}{=}{.16667em}%
    {%
        \HTMLunicode{2009}% thin breakable space
    }%
```

Print the span with the converted width. Not rounded.

```
    {%
        \LWR@htmltagc{%
            span style="width:\LWR@printlength{\LWR@tempwidth};  % extra space
                display:inline-block"%
        }%
```

If formatting for a word processor, approximate with a number of `\quad`s, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \quad%
                \addtolength{\LWR@templengthone}{-1em}%
```

```
            }%
        }{}%
```

Close the span:

```
        \LWR@htmltagc{/span}%
    }%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestartpars%
}% width not 0
}%
}
```

\LWR@select@html@nohspace * {⟨*length*⟩}
\hspace

Used to disable \hspace while creating description \items.

```
\newcommand{\LWR@select@html@nohspace}{%
    \RenewDocumentCommand{\hspace}{s m}{}%
}
```

\LWR@select@print@hspace

```
\newcommand*{\LWR@select@print@hspace}{%
    \renewrobustcmd\hspace{\@ifstar\@hspacer\@hspace}%
}
```

\hspace * {⟨*length*⟩}

Handles special minipage & horizontal space interactions.

```
\LWR@select@html@hspace
```

\LWR@vspace * {⟨*length*⟩} Nullified vspace.

```
\NewDocumentCommand{\LWR@HTML@vspace}{s m}{}

\LWR@formatted{vspace}
```

\linebreak [⟨*num*⟩] Inserts an HTML br tag.

```
\renewcommand*{\linebreak}[1][]{\newline}
```

\nolinebreak [⟨*num*⟩]

```
\renewcommand*{\nolinebreak}[1][]{}
```

\pagebreak [⟨*num*⟩] Starts a new paragraph.

```
\renewcommand*{\pagebreak}[1][]{

}
```

\nopagebreak [⟨*num*⟩]

```
\renewcommand*{\nopagebreak}[1][]{}
```

\enlargethispage * {⟨*len*⟩}

```
\RenewDocumentCommand{\enlargethispage}{s m}{}
```

\clearpage
\cleardoublepage

```
\renewcommand*{\clearpage}{}
\renewcommand*{\cleardoublepage}{}
```

\rule [⟨*raise*⟩] {⟨*width*⟩} {⟨*height*⟩}

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

`\fill` is zero-width, so `\hspace{\fill}` is ignored.

```
\newcommand*{\LWR@HTML@rule}[3][]{%
```

The width is copied into a temporary LaTeX length, from which comparisons and conversions may be made:

```
\setlength{\LWR@tempwidth}{#2}%
```

If it's zero-width then skip the entire rule:

```
\ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}%
{}% zero- width
{% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
    \ifthenelse{%
        \lengthtest{\LWR@tempwidth>0pt}\AND%
        \lengthtest{\LWR@tempwidth<1pt}%
    }%
        {\setlength{\LWR@tempwidth}{1pt}}%
        {}%
```

Likewise with height:

```
    \setlength{\LWR@tempheight}{#3}%
    \ifthenelse{%
        \lengthtest{\LWR@tempheight>0pt}\AND%
        \lengthtest{\LWR@tempheight<1pt}%
    }%
        {\setlength{\LWR@tempheight}{1pt}}%
        {}%
```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in LaTeX code.

```
    \LWR@findcurrenttextcolor%
    \LWR@htmltagc{%
    span\LWR@indentHTML%
    style="%
```

The background color is used to draw the filled rule. The color may be changed by `\textcolor`.

```
    \ifbool{FormatWP}{}{background:\LWR@currenttextcolor ; }%
```

The width and height are printed, converted to PT:

```
    width:\LWR@printlength{\LWR@tempwidth} ; %
    height:\LWR@printlength{\LWR@tempheight} ; %
```

The raise height is converted to a CSS transform. The `*2` raise multiplier is to approximately match HTML output's X height. Conversion to a LaTeX length allows a typical LaTeX expression to be used as an argument for the raise, whereas printing the raise argument directly to HTML output without conversion to a LaTeX length limits the allowable syntax. To do: A superior method would compute a ratio of LaTeX ex height, then print that to HTML with an ex unit.

```
    \ifblank{#1}%
    {}%
    {%
        \setlength{\LWR@tempraise}{0pt-#1}%
        \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
        \LWR@indentHTML%
        -ms-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
        -webkit-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
        transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
    }%
```

Display inline-block to place the span inline with the text:

```
    display:inline-block;"\LWR@orignewline%
    }%
```

If formatting for a word processor, approximate with a number of underscores, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \_{}%
                \addtolength{\LWR@templengthone}{-1em}%
            }%
        }{}%
```

Close the span:

```
    \LWR@htmltagc{/span}%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestartpars%
}% non-zero width
}

\LWR@formatted{rule}
```

```
\end{warpHTML}
```

91 \phantomsection

for HTML output:

```
\begin{warpHTML}
```

\phantomsection

Emulate the hyperref \phantomsection command, often used to insert the bibliography into the table of contents. Ignores \ForceHTMLTOC.

```
\DeclareDocumentCommand{\phantomsection}{}{%
\begingroup%
\boolfalse{LWR@forcinghtmltoc}%
\section*{}%
\endgroup%
}
```

```
\end{warpHTML}
```

92 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally `\let` in `\LWR@LwarpStart`.

For CSS conversions, see:
http://edward.oconnor.cx/2007/08/tex-poshlet
http://nitens.org/taraborelli/texlogo
and the spacing described in the metafont package documentation.

92.1 HTML logos

for HTML output:
```
\begin{warpHTML}
```

`\TeX` TEX

`latexlogo` is a CSS class used to properly typeset the E and A in LATEX and friends.

`latexlogofont` is a CSS class used to select the font for the rest of the logo in LATEX, LuaTEX, ConTEXt, etc.

```
\LetLtxMacro\LWR@origTeX\TeX

\newrobustcmd*{\LWR@TeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
}
```

`\LaTeX` LATEX, LATEX 2_ε
`\LaTeXe`

```
\LetLtxMacro\LWR@origLaTeX\LaTeX

\newrobustcmd*{\LWR@LaTeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            L%
            \InlineClass{latexlogosup}{a}%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
```

```
}

\LetLtxMacro\LWR@origLaTeXe\LaTeXe

\renewrobustcmd*{\LaTeXe}
{%
    \LaTeX%
    \InlineClass{latexlogofont}{%
        \InlineClass{latexlogotwoe}{%
            2%
            \InlineClass{latexlogotwoesub}{\HTMLunicode{03B5}}%
        }%
    }%
}
```

\LuaTeX \LuaLaTeX LuaTEX, LuaLATEX

```
\newrobustcmd*{\LWR@LuaTeX}{\InlineClass{latexlogofont}{Lua}\TeX}
\newrobustcmd*{\LWR@LuaLaTeX}{\InlineClass{latexlogofont}{Lua}\LaTeX}
```

\XeTeX \XeLaTeX XƎTEX, XƎLATEX

xetexlogo is a CSS class which aligns the backwards E in XƎTEX and spaces TEX appropriately.

xelatexlogo is a CSS class which aligns the backwards E in XƎLATEX and spaces LATEX appropriately.

```
\newrobustcmd*{\Xe}
    {%
        X%
        \InlineClass{xelatexlogosub}{\HTMLunicode{18e}}%
    }

\newrobustcmd*{\LWR@XeTeX}{\InlineClass{xelatexlogo}{\Xe}\TeX}

\newrobustcmd*{\LWR@XeLaTeX}{\InlineClass{xelatexlogo}{\Xe}\LaTeX}
```

\ConTeXt ConTEXt

```
\newrobustcmd*{\LWR@ConTeXt}
{\InlineClass{latexlogofont}{Con}\TeX{}%
\InlineClass{latexlogofont}{t}}
```

\BibTeX \MakeIndex BIBTEX, *MakeIndex*

```
\providerobustcmd*{\BibTeX}
{\InlineClass{latexlogofont}{B\textsc{ib}}\TeX}

\newrobustcmd*{\MakeIndex}
{\InlineClass{latexlogofont}{\textit{MakeIndex}}}
```

\AmS $\mathcal{AMS}$

amslogo is a CSS class used for the $\mathcal{AMS}$ logo.

```
\AtBeginDocument{%
\DeclareDocumentCommand{\AmS}{}
{%
    \InlineClass{amslogo}{%
        \textit{%
            A%
            \InlineClass{latexlogosub}{M}%
            S%
        }%
    }%
}%
}
```

\MiKTeX MiKTEX

```
\newrobustcmd*{\MiKTeX}{\InlineClass{latexlogofont}{MiK}\TeX}
```

\LyX LyX

lyxlogo is a CSS class used for the LyX logo.

```
\newrobustcmd*{\LyX}{\InlineClass{lyxlogo}{LyX}}
```

```
\end{warpHTML}
```

92.2 Print logos

for PRINT output:

```
\begin{warpprint}

\newrobustcmd*{\XeTeXrevE}
    {\hspace{-.1667em}\raisebox{-.5ex}{E}\hspace{-.125em}}

\AtBeginDocument{
\@ifpackageloaded{graphics}{
    \renewrobustcmd*{\XeTeXrevE}
        {\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}\hspace{-.125em}}
}{
    \PackageWarning{lwarp}{Load graphicx or graphics
        for improved XeTeX logo}
}
}

\providerobustcmd*{\XeTeX}{\mbox{X\XeTeXrevE\TeX}}
\providerobustcmd*{\XeLaTeX}{\mbox{X\XeTeXrevE\LaTeX}}
\providerobustcmd*{\AmS}{%
    \leavevmode\hbox{$\mathcal A\kern-.2em\lower.376ex%
    \hbox{$\mathcal M$}\kern-.2em\mathcal S$}%
}
```

```
\newrobustcmd*{\LyX}{\textsf{LyX}}
\providerobustcmd*{\LuaTeX}{\mbox{Lua\TeX}}
\providerobustcmd*{\LuaLaTeX}{\mbox{Lua\LaTeX}}
\providerobustcmd*{\BibTeX}{\mbox{B\textsc{ib}\TeX}}
\providerobustcmd*{\MakeIndex}{\mbox{\textit{MakeIndex}}}
\providerobustcmd*{\ConTeXt}{\mbox{Con\TeX{}t}}
\providerobustcmd*{\MiKTeX}{\mbox{MiK\TeX}}
\end{warpprint}
```

93 \AtBeginDocument, \AtEndDocument

for HTML output:

```
\begin{warpHTML}
```

\LWR@LwarpStart
\LWR@LwarpEnd

Automatically sets up the HTML-related actions for the start and end of the document.

```
\AfterEndPreamble{\LWR@LwarpStart}
\AtEndDocument{\LWR@LwarpEnd}

\end{warpHTML}
```

94 Loading Koma-script class patches

Load patches to koma-script.

for HTML output:

```
\begin{warpHTML}

\@ifclassloaded{scrbook}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrartcl}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrreprt}{\RequirePackage{lwarp-patch-komascript}}{}

\end{warpHTML}
```

95 Loading Memoir class patches

Load patches to memoir.

for HTML output:

```
\begin{warpHTML}

\@ifclassloaded{memoir}{\RequirePackage{lwarp-patch-memoir}}{}

\end{warpHTML}
```

96 ut* class patches

Load patches to uj* and ut* classes, as well as ltj* classes.

for HTML output:
```
\begin{warpHTML}
```

```
\newcommand*{\LWR@patchujtclasses}{
```

uj/t does not use \partname

```
    \def\@partnameformat{}
```

```
    \def\@partcntformat##1{%
        \prepartname%
        \csname the##1\endcsname%
        \postpartname%
        \quad%
    }
    \@ifundefined{chapter}{}{
        \def\@chapcntformat##1{%
            \prechaptername%
            \csname the##1\endcsname%
            \postchaptername%
            \quad%
        }
    }
```

Use decimal points instead of centered dots:

```
    \renewcommand{\thepart}{\@Roman\c@part}
    \@ifundefined{chapter}{
        \renewcommand{\thesection}{\@arabic\c@section}
    }{
        \renewcommand{\thechapter}{\@arabic\c@chapter}
        \renewcommand{\thesection}{\thechapter.\@arabic\c@section}
    }
    \renewcommand{\thesubsection}{\thesection.\@arabic\c@subsection}
    \renewcommand{\thesubsubsection}{%
    \thesubsection.\@arabic\c@subsubsection}
    \renewcommand{\theparagraph}{%
    \thesubsubsection.\@arabic\c@paragraph}
    \renewcommand{\thesubparagraph}{%
    \theparagraph.\@arabic\c@subparagraph}
    \@ifundefined{chapter}{
        \renewcommand{\thefigure}{\@arabic\c@figure}
        \renewcommand{\thetable}{\@arabic\c@table}
    }{
        \renewcommand{\thefigure}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@figure}
        \renewcommand{\thetable}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@table}
    }
}
```

```

\@ifclassloaded{ujarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{utarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{utbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{utreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjskiyou}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjspf}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtreport}{\LWR@patchujtclasses}{}

\end{warpHTML}
```

97 CTEX patches

Patches for ctex and related classes, which are loaded before lwarp.

All CTEX classes and the ctex package seem to load ctexpatch, so its presence is used to decide whether to have lwarp patch CTEX.

for HTML output:

```
\begin{warpHTML}
```

`\AtBeginDocument` in case the user set `FileSectionNames` in the preamble.

```
\AtBeginDocument{
    \@ifpackageloaded{ctexpatch}{%
        \def\@partcntformat#1{%
            \LWR@isolate{\CTEX@partname}~%
            \CTEX@part@aftername%
        }%

        \def\@partnameformat{}

        \def\@chapcntformat#1{%
            \LWR@isolate{\CTEX@chaptername}~%
            \CTEX@chapter@aftername%
        }%
    }{}
}

\end{warpHTML}
```

98 kotexutf patches

Patch for kotexutf, which is loaded before lwarp.

kotexutf's `\@setref` was conflicting with lwarp's cross references.

for HTML output:
```
\begin{warpHTML}
```

If kotexutf's version of `\@setref` is detected, it is reverted to the original.

```
\AtBeginDocument{
\@ifpackageloaded{kotexutf}{%
    \def\LWR@kotexutf@setref#1#2#3{%
        \@setref@dhucs@orig{#1}{#2}{#3}%
      \ifx#1\relax\else
        \bgroup
        \dhucs@make@cjkchar@null
        \edef\@temp{\expandafter#2#1}\global\josatoks\expandafter{\@temp}%
        \egroup
      \fi%
    }%

    \ifdefequal{\@setref}{\LWR@kotexutf@setref}{
        \let\@setref\@setref@dhucs@orig
    }{}
}{}
}
```

```
\end{warpHTML}
```

File 2 **lwarp-2in1.sty**

§ 99 Package

2in1

Pkg 2in1

2in1 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2in1}
```

File 3 **lwarp-2up.sty**

§ 100 Package

2up

Pkg 2up

2up is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2up}[2010/05/15]
```

```
\def\source#1#2#3{}
\def\target#1#2#3{}
\def\targetlayout#1{}
\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\def\twoupemptypage{}
\def\twoupclearpage{}
\def\twoupeject{}
\def\twouparticle{}
\def\twoupplain{}
\def\twouplegaltarget{}
\def\twouplandscape{}
\def\TwoupWrites{}
```

File 4 **lwarp-a4.sty**

§ 101 Package

a4

Pkg a4

a4 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a4}[2004/04/15]
```

```
\newcommand*{\WideMargins}{}
```

File 5 **lwarp-a4wide.sty**

§ 102 Package a4wide

Pkg a4wide

a4wide is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a4wide}[1994/08/30]
```

File 6 **lwarp-a5comb.sty**

§ 103 Package a5comb

Pkg a5comb

a5comb is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a5comb}
```

File 7 **lwarp-abstract.sty**

§ 104 Package abstract

(*Emulates or patches code by* Peter Wilson.)

Pkg abstract

abstract is supported and patched by lwarp.

⚠ missing TOC

If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

for HTML output:

memoir provides an abstract environment even though it is not an article or report class. Meanwhile, lwarp loads book to emulate memoir, but book does not have an abstract environment, so when the abstract package is loaded for emulation there is no pre-existing abstract to redefine, which would cause an error. Thus, a null abstract is provide here:

```
\ProvideDocumentEnvironment{abstract}{}{}{}
```

Accept all options for lwarp-abstract:

```
\LWR@ProvidesPackagePass{abstract}[2009/06/08]
```

```
\AtBeginDocument{
\BeforeBeginEnvironment{abstract}{
\LWR@forcenewpage
\BlockClass{abstract}
}
```

```
\AfterEndEnvironment{abstract}{\endBlockClass}
}

\renewcommand{\@bsrunintitle}{%
\hspace*{\abstitleskip}%
{\abstractnamefont%
\InlineClass{abstractrunintitle}{\abstractname}%
\@bslabeldelim}%
}

\@ifclassloaded{memoir}
{
  \renewenvironment{abstract}{%
%     \titlepage
    \null\vfil
    \@beginparpenalty\@lowpenalty
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
            \@endparpenalty\@M
          \end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
    }
}{% not memoir
\if@titlepage
  \renewenvironment{abstract}{%
%     \titlepage
    \null\vfil
    \@beginparpenalty\@lowpenalty
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
            \@endparpenalty\@M
          \end\absnamepos%
```

```
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
    }
\else
  \renewenvironment{abstract}{%
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
\begin{\absnamepos}%
\abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
\end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}}
\fi
}% not memoir
```

File 8 **lwarp-academicons.sty**

§ 105 Package

academicons

(*Emulates or patches code by* Diogo A. B. Fernandes.)

Pkg academicons

academicons is patched for use by lwarp.

If \aiicon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{academicons}[2018/06/27]

\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@academicons@orig@AI\AI

\newcommand*{\LWR@academicons@symbol}[1]{%
    \begin{lateximage}*[(academicon)][academicons#1]%
    \begingroup%
```

```
    \LWR@academicons@orig@AI%
    \LWR@orig@symbol{#1}%
    \endgroup%
    \end{lateximage}%
}

\renewcommand*{\AI}{%
    \LetLtxMacro\symbol\LWR@academicons@symbol%
}

\renewcommand*{\aiicon}[1]
{%
    \begin{lateximage}*[(#1 icon)][academicons#1]%
    \AI\csname aiicon@#1\endcsname%
    \end{lateximage}%
}
```

File 9 **lwarp-accsupp.sty**

§ 106 Package accsupp

Pkg accsupp accsupp is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{accsupp}[2018/03/28]

\newcommand*{\BeginAccSupp}[1]{}
\newcommand*{\EndAccSupp}[1]{}
```

File 10 **lwarp-acro.sty**

§ 107 Package acro

(*Emulates or patches code by* Clemens Niederberger.)

Pkg acro acro is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{acro}[2017/01/30]
```

\DeclareAcronym is used in the preamble, where lwarp has not yet made the dollar active, so temporarily enable lwarp math catcode just for this definition:

```
\ExplSyntaxOn
\NewDocumentCommand \LWR@DeclareAcronym {mm}
{
    \acro_declare_acronym:nn {#1} {#2}
    \catcode`\$=3% lwarp
}
\ExplSyntaxOff

```

```
\RenewDocumentCommand{\DeclareAcronym}{}{
    \catcode`\$=\active% lwarp
    \LWR@DeclareAcronym
}
```

Modified to activate the current font:

```
\ExplSyntaxOn
\cs_gset_protected:Npn \acro_write_short:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_short_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_alt:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_alt_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_long:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_long_format_bool
        { \l__acro_custom_long_format_tl }
        { \use:n }
      {
        \use:x
          {
            \exp_not:n {#1}
            {
              \bool_if:NTF \l__acro_first_upper_bool
                { \exp_not:N \__acro_first_upper_case:n { \exp_not:n {
                     \LWR@textcurrentfont{#2}% lwarp
                } } }
                { \exp_not:n {\LWR@textcurrentfont{#2}} }% lwarp
            }
          }
      }
    \group_end:
  }
\ExplSyntaxOff
```

File 11 **lwarp-acronym.sty**

§ 108 Package

acronym

(*Emulates or patches code by* Tobias Oetiker.)

Pkg acronym

acronym is patched for use by lwarp.

⚠ multiply-defined labels

\acresetall does not work with cleveref, causing multiply-defined labels. lwarp patches acronym for HTML, but not for print mode.

for HTML output:

```
\LWR@ProvidesPackagePass{acronym}[2015/03/21]
```

Uses \textit instead of \itshape:

```
\renewcommand{\acfia}[1]{%
  {\textit{\AC@acl{#1}}} (\ifAC@starred\acs*{#1}\else\acs{#1}\fi)}
```

Removes the mbox to allow math inside:

```
\renewcommand*\AC@acs[1]{%
%     \mbox{
 \expandafter\AC@get\csname fn@#1\endcsname\@firstoftwo{#1}}
% }
```

Fix for acronym labels in the captions of floats.

```
\renewcommand{\@starttoc}[1]{
\LWR@htmlelementclass{nav}{#1}
\LetLtxMacro\@verridelabel\@gobble
\LWR@orig@starttoc{#1}
\LWR@htmlelementclassend{nav}{#1}
}
```

Modified for cleveref and lwarp:

```
\renewcommand*\AC@und@newl@bel[3]{%
    \@ifundefined{#1@#3}%
    {%
        \global\expandafter\let\csname#2@#3\endcsname\@nnil
        \global\expandafter\let\csname#2@#3@lwarp\endcsname\@nnil% lwarp
        \global\expandafter\let\csname#2@#3@cref\endcsname\@nnil% lwarp
    }%
    {%
        \global\expandafter\let\csname#1@#3\endcsname\relax
        \global\expandafter\let\csname#1@#3@lwarp\endcsname\relax% lwarp
        \global\expandafter\let\csname#1@#3@cref\endcsname\relax% lwarp
    }%
}%
```

File 12 **lwarp-adjmulticol.sty**

§ 109 Package

adjmulticol

(*Emulates or patches code by* Boris Veytsman.)

Pkg adjmulticol

adjmulticol is emulated.

Emulation similar to multicols is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, lwarp allows a variable number of columns up to three.

for HTML output:

```
\LWR@ProvidesPackageDrop{adjmulticol}[2012/01/20]
```

```
\RequirePackage{multicol}
```

adjmulticols * {⟨*numcols*⟩} {⟨*left margi*⟩} {⟨*right margin*⟩}

```
\NewDocumentEnvironment{adjmulticols}{s m m m}
{%
```

Compute the margins, and limit to positive only:

```
\setlength{\LWR@templengthone}{#3}%
\ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{}%
\setlength{\LWR@templengthtwo}{#4}
\ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{}%
```

If one column is specified, use a of class singlecolumn, else use multicols:

```
\newcommand*{\LWR@mcolstype}{multicols}%
\ifnumcomp{#2}{=}{1}{\renewcommand*{\LWR@mcolstype}{singlecolumn}}{}%
```

Help avoid page overflow:

```
\LWR@forcenewpage%
```

Create the with the given margin and class:

```
\BlockClass[%
\LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
\LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%
]{\LWR@mcolstype}%
}
{\endBlockClass}
```

File 13 **lwarp-addlines.sty**

§ 110 Package addlines

(*Emulates or patches code by* Will Robertson.)

Pkg addlines addlines is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{addlines}[2018/12/05]
```

```
\newcommand\addlines{\@ifstar\addlines@a\addlines@a}
\newcommand\addlines@a[1][1]{}
\let\addline\addlines
\newcommand\removelines{\@ifstar\removelines@a\removelines@a}
\newcommand\removelines@a[1][1]{}
\let\removeline\removelines
\newcommand\squeezepage[1][0]{}
```

File 14 **lwarp-afterpage.sty**

§ 111 Package afterpage

(*Emulates or patches code by* David Carlisle.)

Pkg afterpage Emulated.

for HTML output: Discard all options for lwarp-afterpage:

```
\LWR@ProvidesPackageDrop{afterpage}[2014/10/28]
```

```
\newcommand{\afterpage}[1]{#1}
```

File 15 **lwarp-algorithm2e.sty**

§ 112 Package algorithm2e

(*Emulates or patches code by* Christophe Fiorio.)

Pkg algorithm2e algorithm2e is patched for use by lwarp.

For print output, captions are placed according to package options, but for HTML output captions are placed where used. Therefore, to have captions appear at the top of the algorithms for both print and HTML, place each captions at the top of each algorithm.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithm2e}[2017/07/18]
```

For the list-of entries:

```
\renewcommand{\l@algocf}[2]{\hypertocfloat{1}{algocf}{loa}{#1}{#2}}
```

Select the lwarp float style according to the algorithm2e style:

```
\newcommand*{\LWR@floatstyle@algocf}{ruled}

\ifdefstring{\algocf@style}{boxed}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxed}
}{}

\ifdefstring{\algocf@style}{boxruled}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxruled}
}{}

\ifdefstring{\algocf@style}{plain}{%
\renewcommand*{\LWR@floatstyle@algocf}{plain}
}{}
```

Paragraph handling to allow line numbers under certain conditions:

```
\newbool{LWR@algocf@dopars}
\booltrue{LWR@algocf@dopars}

\renewcommand{\algocf@everypar}{%
\ifbool{LWR@algocf@dopars}{%
    \ifbool{LWR@doingstartpars}{%
        \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
            {}%
            {%
                \algocf@everyparnl\algocf@everyparhanging%
            }%
    }{}%
}{}%
}
```

lwarp caption handling:

```
\renewcommand{\algocf@makecaption}[2]{%
\LWR@HTML@caption@begin{algocf}%
\LWR@isolate{\algocf@captiontext{#1}{#2}}%
\LWR@HTML@caption@end%
}
```

Print any caption where it is declared:

```
\renewcommand{\algocf@makecaption@plain}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@boxed}[2]{%
    \LWR@HTML@caption@begin{algocf}%
```

```
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@ruled}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}
```

Turn off line numbering while making the caption:

```
\long\def\algocf@latexcaption#1[#2]#3{% original definition of caption
\boolfalse{LWR@algocf@dopars}%  lwarp
  \par%
  \addcontentsline{\csname ext@#1\endcsname}{#1}%
 {\protect\numberline{\csname the#1\endcsname}{\ignorespaces \LWR@isolate{#2}}}%
  \begingroup%
  \@parboxrestore%
  \if@minipage%
    \@setminipage%
  \fi%
  \normalsize%
  \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par%
  \endgroup%
\booltrue{LWR@algocf@dopars}%   lwarp
}
```

Line numbers are printed in a of class `alg2elinenumber`:

```
\renewcommand{\algocf@printnl}[1]{%
    \InlineClass{alg2elinenumber}{\NlSty{#1}}~%
}%
```

While initializing an algorithm environment, locally declare the style of a regular figure to be the same as the algorithm style, in case the `figure` option was used.

```
\preto\@algocf@init{%
  \edef\LWR@floatstyle@figure{\LWR@floatstyle@algocf}%
}
```

For lwarp, the algorithm is not assembled inside a box, since `latexi`mages would not work, so the captions are printed where declared.

```
\renewcommand{\@algocf@start}{%
    \let\@mathsemicolon=\;\def\;{\ifmmode\@mathsemicolon\else\@endalgoln\fi}%
%     \raggedright%
    \AlFnt{}%
    \booltrue{LWR@algocf@dopars}% lwarp
}

\renewcommand{\@algocf@finish}{%
    \boolfalse{LWR@algocf@dopars}% lwarp
    \lineskip\normallineskip\setlength{\skiptotal}{\@defaultskiptotal}%
```

```
    \let\;=\@mathsemicolon%
    \let\]=\@emathdisplay%
}
```

Use an HTML break:

```
\renewcommand{\BlankLine}{%
\LWR@stoppars%
\LWR@htmltagc{br /}%
\LWR@startpars%
}
```

Simplified for HTML. The paragraph handling must be preserved.

```
\renewcommand{\SetKwInOut}[2]{%
  \algocf@newcommand{#1}[1]{%
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@seteveryparhanging{\relax}}%
    \ifthenelse{\boolean{algocf@inoutnumbered}}%
        {\relax}%
        {\algocf@seteveryparnl{\relax}}%
    {%
            \KwSty{#2\algocf@typo:}%
        ~##1\par%
    }%
    \algocf@linesnumbered% reset the numbering of the lines
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@reseteveryparhanging}%
  }%
}%

\renewcommand{\ResetInOut}[1]{}%
```

Each of the following creates a of a given class, and turns off line numbering while creating the tags:

```
\renewcommand{\algocf@Vline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2evline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
\booltrue{LWR@algocf@dopars}%
}
```

```
\renewcommand{\algocf@Vsline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2evsline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
```

```
\booltrue{LWR@algocf@dopars}%
}
```

```
\renewcommand{\algocf@Noline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2enoline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
\booltrue{LWR@algocf@dopars}%
}
```

The [H] environment is converted to a regular float, which in HTML is placed where declared. Reusing the regular float allows the [H] version to reuse the ruled and boxed options.

```
\LetLtxMacro\algocf@Here\algocf
\LetLtxMacro\endalgocf@Here\endalgocf
```

File 16 **lwarp-algorithmicx.sty**

§ 113 Package algorithmicx

(*Emulates or patches code by* Szász János.)

Pkg algorithmicx

algorithmicx is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithmicx}[2005/04/27]
```

Inside the algorithmic environment, level indenting is converted to a of the required length, and comments are placed inside a which is floated right.

⚠ package conflicts

If using \newfloat, trivfloat, and/or algorithmicx together, see section 468.1.

for HTML output:

```
\begin{warpHTML}
```

```
\AtBeginEnvironment{algorithmic}{%
%
\let\origALG@doentity\ALG@doentity%
%
\renewcommand*{\ALG@doentity}{%
\origALG@doentity%
\LWR@htmltagc{%
span style="width:\LWR@printlength{\ALG@thistlm}; display:inline-block;"%
}%
\ifbool{FormatWP}{%
\setlength{\LWR@templengthone}{\the\ALG@thistlm}%
\whiledo{\lengthtest{\LWR@templengthone>1em}}{%
\quad%
\addtolength{\LWR@templengthone}{-1em}%
}%
```

```
}{}%
\LWR@htmltagc{/span}%
}%

\let\LWR@origComment\Comment%

\renewcommand{\Comment}[1]{%
    \InlineClass{floatright}{\LWR@origComment{#1}}%
}%
}

\renewcommand\algorithmiccomment[1]{%
\hfill\HTMLunicode{25B7} #1% white right triangle
}%

\end{warpHTML}
```

File 17 **lwarp-alltt.sty**

§ 114 Package alltt

(*Emulates or patches code by* Johannes Braams.)

Pkg alltt alltt is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{alltt}[1997/06/16]

\AfterEndPreamble{
\LWR@traceinfo{Patching alltt.}
\AtBeginEnvironment{alltt}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{alltt}%
}
\AfterEndEnvironment{alltt}{%
    \LWR@afterendverbatim{2}%
}
}
```

File 18 **lwarp-amsmath.sty**

§ 115 Package amsmath

(*Emulates or patches code by* American Mathematical Society, LaTeX3 Project.)

Pkg amsmath amsmath is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{amsmath}[2017/09/02]
```

Patches to allow `\eqref` inside a caption:

```
\def\maketag@@@#1{\text{#1}}
\def\tagform@#1{\maketag@@@{(\ignorespaces#1\unskip)}}
```

Patches for $\mathcal{AMS}$ math \tag macro to remember the first tag:

```
\ifbool{mathjax}{}{% not mathjax

\LetLtxMacro\LWR@origmake@df@tag@@\make@df@tag@@
\LetLtxMacro\LWR@origmake@df@tag@@@\make@df@tag@@@

\renewcommand*{\make@df@tag@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@{#1}%
}

\renewcommand*{\make@df@tag@@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@@{#1}%
}

}% not mathjax
```

The following $\mathcal{AMS}$ environments are more easily patched in-place:

Env multline

```
\BeforeBeginEnvironment{multline}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \booltrue{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{multline}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{multline}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \boolfalse{LWR@amsmultline}
    \LWR@addmathjax{multline}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env multline*

```
\BeforeBeginEnvironment{multline*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \booltrue{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{multline*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{multline*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \boolfalse{LWR@amsmultline}
    \LWR@addmathjax{multline*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}

```

Env gather

```
\BeforeBeginEnvironment{gather}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{gather}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{gather}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
```

```
    \LWR@endhideamsmath
    \LWR@addmathjax{gather}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env gather*

```
\BeforeBeginEnvironment{gather*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{gather*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{gather*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{gather*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env align

```
\BeforeBeginEnvironment{align}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{align}]
    \LWR@applyxfakebold%
}
```

```
}

\AfterEndEnvironment{align}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{align}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env `align*`

```
\BeforeBeginEnvironment{align*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{align*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{align*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{align*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env `flalign`

```
\BeforeBeginEnvironment{flalign}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
```

```
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{flalign}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{flalign}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{flalign}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env flalign*

```
\BeforeBeginEnvironment{flalign*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{flalign*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{flalign*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{flalign*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env alignat

```
\BeforeBeginEnvironment{alignat}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

```
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{alignat}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{alignat}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{alignat}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

Env alignat*

```
\BeforeBeginEnvironment{alignat*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
    \LWR@beginhideamsmath
}
{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbody{alignat*}]
    \LWR@applyxfakebold%
}
}

\AfterEndEnvironment{alignat*}{

\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{
    \LWR@endhideamsmath
    \LWR@addmathjax{alignat*}{\the\@envbody}
}
{\end{lateximage}\end{BlockClass}}

}
```

File 19 **lwarp-amsthm.sty**

§ 116 Package

amsthm

(*Emulates or patches code by* Publications Technical Group — American Mathematical Society.)

The original source code is located in amsclass.dtx, and printed in amsclass.pdf.

Pkg amsthm amsthm is patched for use by lwarp.

Table 14: amsthm package — css styling of theorems and proofs

Theorem: of class amsthmbody<theoremstyle>

Theorem Name: of class amsthmname<theoremtyle>

Theorem Number: of class amsthmnumber<theoremstyle>

Theorem Note: of class amsthmnote<theoremstyle>

Proof: of class amsthmproof

Proof Name: of class amsthmproofname

where <theoremstyle> is plain, definition, etc.

for HTML output: amsthm must be loaded before mdframed:

```
\@ifpackageloaded{mdframed}{
    \PackageError{lwarp}
    {Package mdframed must be loaded after package amsthm}
    {%
        Move \detokenize{\usepackage}{amsthm} before
        \detokenize{\usepackage}{mdframed}.\MessageBreak
        Package amsthm may be loaded by something else,\MessageBreak
        which must also be moved before mdframed.%
    }
}
{}
```

```
\LWR@ProvidesPackagePass{amsthm}[2017/10/31]
```

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\renewcommand{\theoremstyle}[1]{%
  \@ifundefined{th@#1}{%
```

```
    \PackageWarning{amsthm}{Unknown theoremstyle ‘#1’}%
    \thm@style{plain}%
    \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
  }{%
    \thm@style{#1}%
    \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
  }%
}
```

Patched to remember the style for this theorem type:

```
\def\@xnthm#1#2{%
  \csedef{LWR@thmstyle#2}{\LWR@newtheoremstyle}% lwarp
  \let\@tempa\relax
  \@xp\@ifdefinable\csname #2\endcsname{%
    \global\@xp\let\csname end#2\endcsname\@endtheorem
    \ifx *#1% unnumbered, need to get one more mandatory arg
      \edef\@tempa##1{%
        \gdef\@xp\@nx\csname#2\endcsname{%
          \@nx\@thm{\@xp\@nx\csname th@\the\thm@style\endcsname}%
            {}{##1}}}%
    \else % numbered theorem, need to check for optional arg
      \def\@tempa{\@oparg{\@ynthm{#2}}[]}%
    \fi
   \AtBeginEnvironment{#2}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#2}}}% lwarp
  }%
  \@tempa
}
```

Patched to enclose with css:

```
\newcommand{\LWR@haveamsthmname}{
\renewcommand{\thmname}[1]{\InlineClass{amsthmname\LWR@thisthmstyle}{##1}}
}

\newcommand{\LWR@haveamsthmnumber}{
\renewcommand{\thmnumber}[1]{\InlineClass{amsthmnumber\LWR@thisthmstyle}{##1}}
}

\newcommand{\LWR@haveamsthmnote}{
\renewcommand{\thmnote}[1]{\InlineClass{amsthmnote\LWR@thisthmstyle}{##1}}
}

\LWR@haveamsthmname
\LWR@haveamsthmnumber
\LWR@haveamsthmnote
```

Patches for css:

```
\def\@begintheorem#1#2[#3]{%
    \item[
%   \deferred@thm@head{
%     \the\thm@headfont \thm@indent
    \@ifempty{#1}{\let\thmname\@gobble}{\LWR@haveamsthmname}% lwarp
    \@ifempty{#2}{\let\thmnumber\@gobble}{\LWR@haveamsthmnumber}% lwarp
```

```
    \@ifempty{#3}{\let\thmnote\@gobble}{\LWR@haveamsthmnote}% lwarp
    \thm@swap\swappedhead\thmhead{#1}{#2}{#3}%
    \the\thm@headpunct~
    \thmheadnl % possibly a newline.
    \hskip\thm@headsep
%   }%
    ]
  \ignorespaces}
```

Patched for css:

```
\def\@thm#1#2#3{%
  \ifhmode\unskip\unskip\par\fi
  \normalfont
  \LWR@forcenewpage% lwarp
  \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
  \trivlist
  \let\thmheadnl\relax
  \let\thm@swap\@gobble
  \thm@notefont{\fontseries\mddefault\upshape}%
  \thm@headpunct{.}% add period after heading
  \thm@headsep 5\p@ plus\p@ minus\p@\relax
  \thm@space@setup
  #1% style overrides
  \@topsep \thm@preskip               % used by thm head
  \@topsepadd \thm@postskip           % used by \@endparenv
  \def\@tempa{#2}\ifx\@empty\@tempa
    \def\@tempa{\@oparg{\@begintheorem{#3}{}}[]}%
  \else
    \refstepcounter{#2}%
    \def\@tempa{\@oparg{\@begintheorem{#3}{\csname the#2\endcsname}}[]}%
  \fi
  \@tempa
}
```

cleveref patches `\@thm` to do `\cref@thmoptarg` if an optional argument is given. lwarp then patches `\cref@thmoptarg` `\AtBeginDocument`.

```
\AtBeginDocument{%
\def\cref@thmoptarg[#1]#2#3#4{%
    \ifhmode\unskip\unskip\par\fi%
    \normalfont%
    \LWR@forcenewpage% lwarp
    \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
    \trivlist%
    \let\thmheadnl\relax%
    \let\thm@swap\@gobble%
    \thm@notefont{\fontseries\mddefault\upshape}%
    \thm@headpunct{.}% add period after heading
    \thm@headsep 5\p@ plus\p@ minus\p@\relax%
    \thm@space@setup%
    #2% style overrides
    \@topsep \thm@preskip               % used by thm head
    \@topsepadd \thm@postskip           % used by \@endparenv
    \def\@tempa{#3}\ifx\@empty\@tempa%
```

```
        \def\@tempa{\@oparg{\@begintheorem{#4}{}}[]}%
    \else%
        \refstepcounter[#1]{#3}%  <<< cleveref modification
        \def\@tempa{\@oparg{\@begintheorem{#4}{\csname the#3\endcsname}}[]}%
    \fi%
    \@tempa
}%
}% AtBeginDocument

\def\@endtheorem{\endtrivlist\endBlockClass\@endpefalse }
```

Proof QED symbol:

```
\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box

\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\openbox\LWR@orig@openbox%
\LetLtxMacro\blacksquare\LWR@orig@blacksquare%
\LetLtxMacro\Box\LWR@orig@Box%
}% appto
}{}% @ifundefined
}% AtBeginDocument
```

Patched for css:

```
\renewenvironment{proof}[1][\proofname]{\par
\LWR@forcenewpage% lwarp
    \BlockClass{amsthmproof}% lwarp
  \pushQED{\qed}%
  \normalfont \topsep6\p@\@plus6\p@\relax
  \trivlist
  \item[
        \InlineClass{amsthmproofname}{#1\@addpunct{.}}]\ignorespaces% changes
}{%
  \InlineClass{theoremendmark}{\popQED}\endtrivlist%
  \endBlockClass% lwarp
  \@endpefalse
}
```

File 20 **lwarp-anonchap.sty**

§ 117 Package anonchap

(*Emulates or patches code by* Peter Wilson.)

Pkg anonchap

anonchap is emulated.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

The code is shared by tocbibind.

for HTML output:

```
\LWR@ProvidesPackageDrop{anonchap}[2009/08/03]

\newcommand{\simplechapter}[1][\@empty]{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\newcommand{\restorechapter}{%
\let\@chapcntformat\@seccntformat%
}
```

File 21 **`lwarp-anysize.sty`**

§ 118 Package anysize

(*Emulates or patches code by* Michael Salzenberg, Thomas Esser.)

Pkg anysize

anysize is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{anysize}[1994/08/13]

\def\papersize#1#2{}
\def\marginsize#1#2#3#4{}
```

File 22 **`lwarp-appendix.sty`**

§ 119 Package appendix

(*Emulates or patches code by* Peter Wilson.)

Pkg appendix

appendix is patched for use by lwarp.

⚠ incorrect TOC link

During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

for HTML output:

```
\LWR@ProvidesPackagePass{appendix}[2009/09/02]

\renewcommand*{\@chap@pppage}{%
\part*{\appendixpagename}
```

```
\if@dotoc@pp
\addappheadtotoc
\fi
}

\renewcommand*{\@sec@pppage}{%
\part*{\appendixpagename}
\if@dotoc@pp
\addappheadtotoc
\fi
}
```

File 23 **lwarp-ar.sty**

§ 120 Package

ar

(*Emulates or patches code by* Agostino De Marco.)

Pkg ar ar is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ar}[2012/01/23]
```

Measure and print the width of the supplied glyph.

```
\newlength{\LWR@ar@width}

\newcommand*{\LWR@ar@printwidth}[1]{%
    \setlength{\LWR@ar@width}{\widthof{#1}}%
    width:%
    \LWR@convertto{em}{\the\LWR@ar@width}em%
}
```

The HTML version of \AR:

```
\newrobustcmd*{\LWR@HTML@AR}{%
```

Start a hashed lateximage, additionally hashed by the font series, with a width depending on the given glyph:

```
    \begin{lateximage}*[AR][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@AR}]%
```

For text mode, set the font series according to the HTML font series:

```
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
```

Print the original glyph using the newly set font series:

```
    \LWR@print@AR%
```

Done.

```
    \end{lateximage}%
}
```

Combine the print and HTML versions:

```
\LWR@formatted{AR}

\newrobustcmd*{\LWR@HTML@ARb}{%
    \begin{lateximage}*[AR][b][\LWR@ar@printwidth{\LWR@print@ARb}]%
    \LWR@print@ARb%
    \end{lateximage}%
}
\LWR@formatted{ARb}

\newrobustcmd*{\LWR@HTML@ARss}{%
   \begin{lateximage}*[ARss][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@ARss}]%
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
    \LWR@print@ARss%
    \end{lateximage}%
}
\LWR@formatted{ARss}

\newrobustcmd*{\LWR@HTML@ARssb}{%
    \begin{lateximage}*[AR][ssb][\LWR@ar@printwidth{\LWR@print@ARssb}]%
    \LWR@print@ARssb%
    \end{lateximage}%
}
\LWR@formatted{ARssb}

\newrobustcmd*{\LWR@HTML@ARtt}{%
    \begin{lateximage}*[AR][tt][\LWR@ar@printwidth{\LWR@print@ARtt}]%
    \LWR@print@ARtt%
    \end{lateximage}%
}
\LWR@formatted{ARtt}
```

File 24 **lwarp-arabicfront.sty**

§ 121 Package arabicfront

Pkg arabicfront

arabicfront is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{arabicfront}[2006/09/03]
```

File 25 **lwarp-array.sty**

§ 122 Package array

Pkg array

array is used as-is for print output, and emulated for HTML.

plarray and plextarray do not affect \firsthline or \lasthline, and so are not affected by the following.

for HTML output: Remove the default nullfied macros:

```
\let\firsthline\relax
\let\lasthline\relax

\LWR@ProvidesPackagePass{array}[2018/12/30]

\newcommand*{\LWR@HTML@firsthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{firsthline}

\newcommand*{\LWR@HTML@lasthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{lasthline}

\providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
\LWR@formatted{tabularnewline}
```

File 26 **lwarp-arydshln.sty**

§ 123 Package

arydshln

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg arydshln

arydshln heavily patches tabular code, so the actual package is not used. arydshln is emulated for HTML tabular, and reverts to solid rules for SVG math array and tabular in a lateximage.

CSS is not able to display a double-dashed border, so a single-dashed rule is displayed as a single-dashed border, and a double-dashed rule is displayed as a thicker single-dashed border.

for HTML output: array is required to allow \newcolumn below.

```
\RequirePackage{array}

\LWR@ProvidesPackageDrop{arydshln}[2018/09/26]
```

Ignored, but included for source compatibility:

```
\newdimen\dashlinedash \dashlinedash4pt %
\newdimen\dashlinegap \dashlinegap4pt %
\let\hdashlinewidth\dashlinedash
\let\hdashlinegap\dashlinegap

\def\ADLnullwide{}
\def\ADLsomewide{}
\def\ADLnullwidehline{}
\def\ADLsomewidehline{}

```

```
\def\ADLactivate{}
\def\ADLinactivate{}
\newcommand*{\ADLdrawingmode}[1]{}
\newcommand*{\ADLnoshorthanded}{}
\newcommand*{\dashgapcolor}[2][]{}
\newcommand*{\nodashgapcolor}{}
```

In a `lateximage`, revert to solid vertical rules:

```
\appto\LWR@restoreorigformatting{%
\newcolumntype{:}{|}%
\newcolumntype{;}[1]{|}%
\LetLtxMacro\hdashline\hline%
}
```

Some of these macros are already defined as temporary placeholders in the lwarp core, so they must be redefined here.

The emulated defaults also work for an emulated print mode inside a `lateximage`:

```
\def\hdashline{
%     \adl@hdashline\adl@ihdashline
    \adl@hdashline\adl@inactivehdl
}
\def\adl@hdashline#1{\noalign{\ifnum0=`}\fi
%         \ifadl@zwhrule \vskip-\arrayrulewidth
%         \else
%             \adl@hline\adl@connect\arrayrulewidth
                \hrule \@height \arrayrulewidth% lwarp
%         \fi
        \@ifnextchar[%]
                    {#1}%
                    {#1[%
%                         \dashlinedash/\dashlinegap
                       1pt/1pt
                    ]}}
% \def\adl@ihdashline[#1/#2]{\ifnum0=`{\fi}%
%         \multispan{\adl@columns}\unskip \adl@hcline\z@[#1/#2]%
%         \noalign{\ifnum0=`}\fi
%         \futurelet\@tempa\adl@xhline}
\def\adl@inactivehdl[#1/#2]{
%         \ifadl@zwhrule \vskip-\arrayrulewidth \fi
        \hrule\@height\arrayrulewidth
        \futurelet\@tempa\adl@xhline}
\def\adl@xhline{\ifx\@tempa\hline \adl@ixhline\fi
        \ifx\@tempa\hdashline \adl@ixhline\fi
        \ifnum0=`{\fi}}
\def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
\def\adl@hline#1#2{%
% \@tempcnta#2
%         \global\advance\adl@totalheight\@tempcnta
%         \xdef\adl@rowsL{\adl@rowsL
%                 (#1/\number\@tempcnta);}%
%         \xdef\adl@rowsR{\adl@rowsR
%                 (#1/\number\@tempcnta);}
```

```
}

\def\cdashline#1{\noalign{\ifnum0=`}\fi
        \@ifnextchar[%]
%                       {\adl@cdline[#1]}%
%                       {\adl@cdline[#1][\dashlinedash/\dashlinegap]}
                      {\adl@inactivecdl[#1]}%
                      {\adl@inactivecdl[#1][\dashlinedash/\dashlinegap]}
}

\def\adl@inactivecdl[#1-#2][#3]{\ifnum0=`{\fi}\cline{#1-#2}}
```

File 27 **lwarp-asymptote.sty**

§ 124 Package

asymptote

(*Emulates or patches code by* Andy Hammerlindl, John Bowman, Tom Prince.)

Pkg asymptote

asymptote is patched for use by lwarp.

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

for HTML output:

```
\LWR@ProvidesPackagePass{asymptote}[2016/11/26]

\BeforeBeginEnvironment{asy}{\begin{lateximage}[(-asymptote-~\packagediagramname)]}
\AfterEndEnvironment{asy}{\end{lateximage}}

\xpatchcmd{\asyinclude}
    {\begingroup}
    {\begin{lateximage}[(-asymptote-~\packagediagramname)]}
    {}
    {\LWR@patcherror{asymptote}{asyinclude-begingroup}}

\xpatchcmd{\asyinclude}
    {\endgroup}
    {\end{lateximage}}
    {}
```

```
    {\LWR@patcherror{asymptote}{asyinclude-endgroup}}
```

File 28 **lwarp-atbegshi.sty**

§ 125 Package

atbegshi

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg atbegshi Emulated.

for HTML output: Discard all options for lwarp-atbegshi:

```
\LWR@ProvidesPackageDrop{atbegshi}[2011/10/05]

\newcommand*{\AtBeginShipout}[1]{}
\newbox\AtBeginShipoutBox
\newcommand*{\AtBeginShipoutNext}[1]{}
\newcommand*{\AtBeginShipoutFirst}[1]{}
\newcommand*{\AtBeginShipoutDiscard}{}
\newcommand*{\AtBeginShipoutInit}{}
\newcommand*{\AtBeginShipoutAddToBox}[1]{}
\newcommand*{\AtBeginShipoutAddToBoxForeground}[1]{}
\newcommand*{\AtBeginShipoutUpperLeft}[1]{}
\newcommand*{\AtBeginShipoutUpperLeftForeground}[1]{}
\newcommand*{\AtBeginShipoutOriginalShipout}[1]{}
\def\AtBeginShipoutBoxWidth{0pt}
\def\AtBeginShipoutBoxHeight{0pt}
\def\AtBeginShipoutBoxDepth{0pt}

```

File 29 **lwarp-attachfile.sty**

§ 126 Package

attachfile

(*Emulates or patches code by* Scott Pakin.)

Pkg attachfile attachfile is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile}[2016/09/18]
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
```

```
            \detokenize\expandafter{\atfi@color@rgb}%
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an `\attachfile` reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \href{#1}{\LWR@attachfile@appearance}%
}
```

File 30 **`lwarp-attachfile2.sty`**

§ 127 Package attachfile2

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg `attachfile2` attachfile2 is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile2}[2016/05/16]
```

Adds memory of the selected color:

```
\def\LWR@attachfiletwo@color{}%

\define@key{AtFi}{color}{%
    \def\LWR@attachfiletwo@color{#1}%   lwarp
  \HyColor@AttachfileColor{#1}%
          \atfi@color@tex\atfi@color@inline\atfi@color@annot
          {attachfile2}{color}%
}
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
            \detokenize\expandafter{\LWR@attachfiletwo@color}%
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an `\attachfile` reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\def\atfi@set@appearance@icon{%
    \atfi@set@appearance{\csname atfi@acro\atfi@icon@icon\endcsname}%
}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \href{#1}{\LWR@attachfile@appearance}%
}
```

Modified for text color:

```
\DeclareRobustCommand{\notextattachfile}[2][]{%
  \begingroup
    \atfi@setup{#1}%
    \ifatfi@print
      \leavevmode
      \begingroup
        \HyColor@UseColor\atfi@color@tex
        \LWR@textcurrentcolor{#2}%      lwarp
% \strut
      \endgroup
%     \else
%       \sbox\ltx@zero{#2\strut}%
%       \makebox[\wd0]{}%
    \fi
  \endgroup
}
```

Modified to draw the icon:

```
\DeclareRobustCommand{\noattachfile}[1][]{%
  \begingroup
    \atfi@setup{#1}%
    \atfi@set@appearance@icon
    \ifatfi@print
        \LWR@attachfile@appearance%     lwarp
%       \expandafter
%       \atfi@refxform\csname atfi@appobj@\atfi@icon@icon\endcsname
%     \else
%       \makebox[\atfi@appearancewidth]{}%
    \fi
  \endgroup
}
```

File 31 **lwarp-authblk.sty**

§ 128 Package

authblk

(*Emulates or patches code by* Patrick W. Daly.)

Pkg authblk

authblk is patched for HTML.

package support

⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle

may be added by using \AddSubtitlePublished in the preamble. See section 65.8.

(*Emulates or patches code by* Patrick W. Daly.)

for HTML output: Require that authblk be loaded before titling:

```
\@ifpackageloaded{titling}{
\PackageError{lwarp-authblk}
{Package authblk must be loaded before titling}
{Titling appends authblk's author macro, so authblk must be loaded first.}
}
{}
```

Load authblk:

```
\LWR@ProvidesPackagePass{authblk}[2001/02/27]
```

Patch to add a class for the affiliation:

```
\LetLtxMacro\LWRAB@affil\affil

\renewcommand{\affil}[2][]{%
\LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}
}
```

Create an HTML break for an \authorcr:

```
\renewcommand*{\authorcr}{\protect\LWR@newlinebr}
```

File 32 **lwarp-axessibility.sty**

§ 129 Package axessibility

Pkg axessibility axessibility is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{axessibility}
```

```
\newcommand{\wrap}[1]{}
```

File 33 **lwarp-axodraw2.sty**

§ 130 Package axodraw2

(*Emulates or patches code by* John C. Collins, J.A.M. Vermaseren.)

Pkg axodraw2 axodraw2 is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{axodraw2}[2018/02/15]
```

```
\BeforeBeginEnvironment{axopicture}{\begin{lateximage}[(-axopicture-~\packagediagramname)]}

\AfterEndEnvironment{axopicture}{\end{lateximage}}
```

File 34 **lwarp-backref.sty**

§ 131 Package backref

(*Emulates or patches code by* David Carlisle and Sebastian Rahtz.)

Pkg backref backref is patched for use by lwarp.

⚠ loading Note that backref must be explicitly loaded, and is not automatically loaded by hyperref when generating HTML output.

for HTML output:

```
\LWR@ProvidesPackagePass{backref}[2016/05/21]
```

Force the hyperref option:

```
\def\backref{}\let\backrefxxx\hyper@section@backref
```

File 35 **lwarp-balance.sty**

§ 132 Package balance

(*Emulates or patches code by* Patrick W. Daly.)

Pkg balance Emulated.

for HTML output: Discard all options for lwarp-balance:

```
\LWR@ProvidesPackageDrop{balance}[1999/02/23]
```

```
\newcommand*{\balance}{}
\newcommand*{\nobalance}{}
```

File 36 **lwarp-bbding.sty**

§ 133 Package bbding

(*Emulates or patches code by* Karel Horak, Peter Møller Neergaard.)

Pkg bbding bbding is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bbding}[1999/04/15]
```

```
\newcommand*{\LWR@bbdingsymbol}[2]{\HTMLunicode{#2}}

\newcommand{\LWR@HTML@ScissorRightBrokenBottom}{\LWR@bbdingsymbol{000}  {2701}}
\newcommand{\LWR@HTML@ScissorRight}{\LWR@bbdingsymbol{001}              {2702}}
\newcommand{\LWR@HTML@ScissorRightBrokenTop}{\LWR@bbdingsymbol{002}     {2703}}
\newcommand{\LWR@HTML@ScissorLeftBrokenBottom}{\LWR@bbdingsymbol{003}   {2701}}
\newcommand{\LWR@HTML@ScissorLeft}{\LWR@bbdingsymbol{004}               {2702}}
\newcommand{\LWR@HTML@ScissorLeftBrokenTop}{\LWR@bbdingsymbol{005}      {2703}}
\newcommand{\LWR@HTML@ScissorHollowRight}{\LWR@bbdingsymbol{006}        {2704}}
\newcommand{\LWR@HTML@ScissorHollowLeft}{\LWR@bbdingsymbol{007}         {2704}}
\newcommand{\LWR@HTML@Phone}{\LWR@bbdingsymbol{010}                     {260E}}
\newcommand{\LWR@HTML@PhoneHandset}{\LWR@bbdingsymbol{011}              {2706}}
\newcommand{\LWR@HTML@Tape}{\LWR@bbdingsymbol{012}                      {2707}}
\newcommand{\LWR@HTML@Plane}{\LWR@bbdingsymbol{013}                     {2708}}
\newcommand{\LWR@HTML@Envelope}{\LWR@bbdingsymbol{014}                  {2709}}
\newcommand{\LWR@HTML@HandCuffRight}{\LWR@bbdingsymbol{015}             {261B}}
\newcommand{\LWR@HTML@HandCuffLeft}{\LWR@bbdingsymbol{016}              {261A}}
\newcommand{\LWR@HTML@HandCuffRightUp}{\LWR@bbdingsymbol{017}           {261D}}
\newcommand{\LWR@HTML@HandCuffLeftUp}{\LWR@bbdingsymbol{020}            {261F}}
\newcommand{\LWR@HTML@HandRight}{\LWR@bbdingsymbol{021}                 {261E}}
\newcommand{\LWR@HTML@HandLeft}{\LWR@bbdingsymbol{022}                  {261C}}
\newcommand{\LWR@HTML@HandRightUp}{\LWR@bbdingsymbol{023}               {261D}}
\newcommand{\LWR@HTML@HandLeftUp}{\LWR@bbdingsymbol{024}                {261F}}
\newcommand{\LWR@HTML@Peace}{\LWR@bbdingsymbol{025}                     {270C}}
\newcommand{\LWR@HTML@HandPencilLeft}{\LWR@bbdingsymbol{026}            {270D}}
\newcommand{\LWR@HTML@PencilRight}{\LWR@bbdingsymbol{027}               {270F}}
\newcommand{\LWR@HTML@PencilLeft}{\LWR@bbdingsymbol{030}                {270F}}
\newcommand{\LWR@HTML@PencilRightUp}{\LWR@bbdingsymbol{031}             {2710}}
\newcommand{\LWR@HTML@PencilLeftUp}{\LWR@bbdingsymbol{032}              {2710}}
\newcommand{\LWR@HTML@PencilRightDown}{\LWR@bbdingsymbol{033}           {270E}}
\newcommand{\LWR@HTML@PencilLeftDown}{\LWR@bbdingsymbol{034}            {270E}}
\newcommand{\LWR@HTML@NibRight}{\LWR@bbdingsymbol{035}                  {2711}}
\newcommand{\LWR@HTML@NibLeft}{\LWR@bbdingsymbol{036}                   {2711}}
\newcommand{\LWR@HTML@NibSolidRight}{\LWR@bbdingsymbol{037}             {2712}}
\newcommand{\LWR@HTML@NibSolidLeft}{\LWR@bbdingsymbol{040}              {2712}}
\newcommand{\LWR@HTML@Checkmark}{\LWR@bbdingsymbol{041}                 {2713}}
\newcommand{\LWR@HTML@CheckmarkBold}{\LWR@bbdingsymbol{042}             {2714}}
\newcommand{\LWR@HTML@XSolid}{\LWR@bbdingsymbol{043}                    {2715}}
\newcommand{\LWR@HTML@XSolidBold}{\LWR@bbdingsymbol{044}                {2716}}
\newcommand{\LWR@HTML@XSolidBrush}{\LWR@bbdingsymbol{045}               {2717}}
\newcommand{\LWR@HTML@PlusOutline}{\LWR@bbdingsymbol{046}               {2719}}
\newcommand{\LWR@HTML@Plus}{\LWR@bbdingsymbol{047}                      {271A}}
\newcommand{\LWR@HTML@PlusCenterOpen}{\LWR@bbdingsymbol{050}            {271C}}
\newcommand{\LWR@HTML@PlusThinCenterOpen}{\LWR@bbdingsymbol{051}        {271B}}
\newcommand{\LWR@HTML@Cross}{\LWR@bbdingsymbol{052}                     {271D}}
\newcommand{\LWR@HTML@CrossOpenShadow}{\LWR@bbdingsymbol{053}           {271E}}
\newcommand{\LWR@HTML@CrossOutline}{\LWR@bbdingsymbol{054}              {271F}}
\newcommand{\LWR@HTML@CrossBoldOutline}{\LWR@bbdingsymbol{055}          {271F}}
\newcommand{\LWR@HTML@CrossMaltese}{\LWR@bbdingsymbol{056}              {2720}}
\newcommand{\LWR@HTML@DavidStarSolid}{\LWR@bbdingsymbol{057}            {2721}}
\newcommand{\LWR@HTML@DavidStar}{\LWR@bbdingsymbol{060}                 {2721}}
\newcommand{\LWR@HTML@FourAsterisk}{\LWR@bbdingsymbol{061}              {2722}}
\newcommand{\LWR@HTML@JackStar}{\LWR@bbdingsymbol{062}                  {2723}}
\newcommand{\LWR@HTML@JackStarBold}{\LWR@bbdingsymbol{063}              {2724}}
\newcommand{\LWR@HTML@CrossClowerTips}{\LWR@bbdingsymbol{064}           {2725}}
```

```
\newcommand{\LWR@HTML@FourStar}{\LWR@bbdingsymbol{065}                  {2726}}
\newcommand{\LWR@HTML@FourStarOpen}{\LWR@bbdingsymbol{066}              {2727}}
\newcommand{\LWR@HTML@FiveStarLines}{\LWR@bbdingsymbol{067}             {2729}}
\newcommand{\LWR@HTML@FiveStar}{\LWR@bbdingsymbol{070}                  {2605}}
\newcommand{\LWR@HTML@FiveStarOpen}{\LWR@bbdingsymbol{071}              {2729}}
\newcommand{\LWR@HTML@FiveStarOpenCircled}{\LWR@bbdingsymbol{072}       {272A}}
\newcommand{\LWR@HTML@FiveStarCenterOpen}{\LWR@bbdingsymbol{073}        {272B}}
\newcommand{\LWR@HTML@FiveStarOpenDotted}{\LWR@bbdingsymbol{074}        {272C}}
\newcommand{\LWR@HTML@FiveStarOutline}{\LWR@bbdingsymbol{075}           {272D}}
\newcommand{\LWR@HTML@FiveStarOutlineHeavy}{\LWR@bbdingsymbol{076}      {272E}}
\newcommand{\LWR@HTML@FiveStarConvex}{\LWR@bbdingsymbol{077}            {272F}}
\newcommand{\LWR@HTML@FiveStarShadow}{\LWR@bbdingsymbol{100}            {2730}}
\newcommand{\LWR@HTML@AsteriskBold}{\LWR@bbdingsymbol{101}              {2731}}
\newcommand{\LWR@HTML@AsteriskCenterOpen}{\LWR@bbdingsymbol{102}        {2732}}
\newcommand{\LWR@HTML@AsteriskThin}{\LWR@bbdingsymbol{103}              {273B}}
\newcommand{\LWR@HTML@AsteriskThinCenterOpen}{\LWR@bbdingsymbol{104}    {273C}}
\newcommand{\LWR@HTML@EightStarTaper}{\LWR@bbdingsymbol{105}            {2733}}
\newcommand{\LWR@HTML@EightStarConvex}{\LWR@bbdingsymbol{106}           {2735}}
\newcommand{\LWR@HTML@SixStar}{\LWR@bbdingsymbol{107}                   {2736}}
\newcommand{\LWR@HTML@EightStar}{\LWR@bbdingsymbol{110}                 {2737}}
\newcommand{\LWR@HTML@EightStarBold}{\LWR@bbdingsymbol{111}             {2738}}
\newcommand{\LWR@HTML@TwelweStar}{\LWR@bbdingsymbol{112}                {2739}}
\newcommand{\LWR@HTML@SixteenStarLight}{\LWR@bbdingsymbol{113}          {273A}}
\newcommand{\LWR@HTML@SixFlowerPetalRemoved}{\LWR@bbdingsymbol{114}     {273B}}
\newcommand{\LWR@HTML@SixFlowerOpenCenter}{\LWR@bbdingsymbol{115}       {273C}}
\newcommand{\LWR@HTML@Asterisk}{\LWR@bbdingsymbol{116}                  {273D}}
\newcommand{\LWR@HTML@SixFlowerAlternate}{\LWR@bbdingsymbol{117}        {273E}}
\newcommand{\LWR@HTML@FiveFlowerPetal}{\LWR@bbdingsymbol{120}           {273F}}
\newcommand{\LWR@HTML@SixFlowerPetalDotted}{\LWR@bbdingsymbol{121}      {2740}}
\newcommand{\LWR@HTML@FiveFlowerOpen}{\LWR@bbdingsymbol{122}            {2740}}
\newcommand{\LWR@HTML@EightFlowerPetal}{\LWR@bbdingsymbol{123}          {2741}}
\newcommand{\LWR@HTML@SunshineOpenCircled}{\LWR@bbdingsymbol{124}       {2742}}
\newcommand{\LWR@HTML@SixFlowerAltPetal}{\LWR@bbdingsymbol{125}         {2743}}
\newcommand{\LWR@HTML@FourClowerOpen}{\LWR@bbdingsymbol{126}            {273F}}
\newcommand{\LWR@HTML@FourClowerSolid}{\LWR@bbdingsymbol{127}           {273F}}
\newcommand{\LWR@HTML@AsteriskRoundedEnds}{\LWR@bbdingsymbol{130}       {2749}}
\newcommand{\LWR@HTML@EightFlowerPetalRemoved}{\LWR@bbdingsymbol{131}   {274A}}
\newcommand{\LWR@HTML@EightAsterisk}{\LWR@bbdingsymbol{132}             {274B}}
\newcommand{\LWR@HTML@SixFlowerRemovedOpenPetal}{\LWR@bbdingsymbol{133}  {2740}}
\newcommand{\LWR@HTML@SparkleBold}{\LWR@bbdingsymbol{134}               {2748}}
\newcommand{\LWR@HTML@Sparkle}{\LWR@bbdingsymbol{135}                   {2747}}
\newcommand{\LWR@HTML@SnowflakeChevron}{\LWR@bbdingsymbol{136}          {2744}}
\newcommand{\LWR@HTML@SnowflakeChevronBold}{\LWR@bbdingsymbol{137}      {2746}}
\newcommand{\LWR@HTML@Snowflake}{\LWR@bbdingsymbol{140}                 {2744}}
\newcommand{\LWR@HTML@CircleSolid}{\LWR@bbdingsymbol{141}               {25CF}}
\newcommand{\LWR@HTML@Ellipse}{\LWR@bbdingsymbol{142}                   {274D}}
\newcommand{\LWR@HTML@EllipseSolid}{\LWR@bbdingsymbol{143}              {25CF}}
\newcommand{\LWR@HTML@CircleShadow}{\LWR@bbdingsymbol{144}              {274D}}
\newcommand{\LWR@HTML@EllipseShadow}{\LWR@bbdingsymbol{145}             {274D}}
\newcommand{\LWR@HTML@Square}{\LWR@bbdingsymbol{146}                    {25A1}}
\newcommand{\LWR@HTML@SquareSolid}{\LWR@bbdingsymbol{147}               {25A0}}
\newcommand{\LWR@HTML@SquareShadowBottomRight}{\LWR@bbdingsymbol{150}   {2751}}
\newcommand{\LWR@HTML@SquareShadowTopRight}{\LWR@bbdingsymbol{151}      {2752}}
\newcommand{\LWR@HTML@SquareShadowTopLeft}{\LWR@bbdingsymbol{152}       {2752}}
\newcommand{\LWR@HTML@SquareCastShadowBottomRight}{\LWR@bbdingsymbol{153} {2751}}
```

```
\newcommand{\LWR@HTML@SquareCastShadowTopRight}{\LWR@bbdingsymbol{154}   {2752}}
\newcommand{\LWR@HTML@SquareCastShadowTopLeft}{\LWR@bbdingsymbol{155}   {2752}}
\newcommand{\LWR@HTML@TriangleUp}{\LWR@bbdingsymbol{156}                {25B2}}
\newcommand{\LWR@HTML@TriangleDown}{\LWR@bbdingsymbol{157}              {25BC}}
\newcommand{\LWR@HTML@DiamondSolid}{\LWR@bbdingsymbol{160}              {25C6}}
\newcommand{\LWR@HTML@OrnamentDiamondSolid}{\LWR@bbdingsymbol{161}     {2756}}
\newcommand{\LWR@HTML@HalfCircleRight}{\LWR@bbdingsymbol{162}           {25D7}}
\newcommand{\LWR@HTML@HalfCircleLeft}{\LWR@bbdingsymbol{163}            {25D6}}
\newcommand{\LWR@HTML@RectangleThin}{\LWR@bbdingsymbol{164}             {2758}}
\newcommand{\LWR@HTML@Rectangle}{\LWR@bbdingsymbol{165}                 {2759}}
\newcommand{\LWR@HTML@RectangleBold}{\LWR@bbdingsymbol{166}             {275A}}
\newcommand{\LWR@HTML@ArrowBoldRightStrobe}{\LWR@bbdingsymbol{167}     {27A0}}
\newcommand{\LWR@HTML@ArrowBoldUpRight}{\LWR@bbdingsymbol{170}         {27A6}}
\newcommand{\LWR@HTML@ArrowBoldDownRight}{\LWR@bbdingsymbol{171}       {27A5}}
\newcommand{\LWR@HTML@ArrowBoldRightShort}{\LWR@bbdingsymbol{172}      {27A7}}
\newcommand{\LWR@HTML@ArrowBoldRightCircled}{\LWR@bbdingsymbol{173}    {27B2}}


\LWR@formatted{ScissorRightBrokenBottom}
\LWR@formatted{ScissorRight}
\LWR@formatted{ScissorRightBrokenTop}
\LWR@formatted{ScissorLeftBrokenBottom}
\LWR@formatted{ScissorLeft}
\LWR@formatted{ScissorLeftBrokenTop}
\LWR@formatted{ScissorHollowRight}
\LWR@formatted{ScissorHollowLeft}
\LWR@formatted{Phone}
\LWR@formatted{PhoneHandset}
\LWR@formatted{Tape}
\LWR@formatted{Plane}
\LWR@formatted{Envelope}
\LWR@formatted{HandCuffRight}
\LWR@formatted{HandCuffLeft}
\LWR@formatted{HandCuffRightUp}
\LWR@formatted{HandCuffLeftUp}
\LWR@formatted{HandRight}
\LWR@formatted{HandLeft}
\LWR@formatted{HandRightUp}
\LWR@formatted{HandLeftUp}
\LWR@formatted{Peace}
\LWR@formatted{HandPencilLeft}
\LWR@formatted{PencilRight}
\LWR@formatted{PencilLeft}
\LWR@formatted{PencilRightUp}
\LWR@formatted{PencilLeftUp}
\LWR@formatted{PencilRightDown}
\LWR@formatted{PencilLeftDown}
\LWR@formatted{NibRight}
\LWR@formatted{NibLeft}
\LWR@formatted{NibSolidRight}
\LWR@formatted{NibSolidLeft}
\LWR@formatted{Checkmark}
\LWR@formatted{CheckmarkBold}
\LWR@formatted{XSolid}
\LWR@formatted{XSolidBold}
```

```
\LWR@formatted{XSolidBrush}
\LWR@formatted{PlusOutline}
\LWR@formatted{Plus}
\LWR@formatted{PlusCenterOpen}
\LWR@formatted{PlusThinCenterOpen}
\LWR@formatted{Cross}
\LWR@formatted{CrossOpenShadow}
\LWR@formatted{CrossOutline}
\LWR@formatted{CrossBoldOutline}
\LWR@formatted{CrossMaltese}
\LWR@formatted{DavidStarSolid}
\LWR@formatted{DavidStar}
\LWR@formatted{FourAsterisk}
\LWR@formatted{JackStar}
\LWR@formatted{JackStarBold}
\LWR@formatted{CrossClowerTips}
\LWR@formatted{FourStar}
\LWR@formatted{FourStarOpen}
\LWR@formatted{FiveStarLines}
\LWR@formatted{FiveStar}
\LWR@formatted{FiveStarOpen}
\LWR@formatted{FiveStarOpenCircled}
\LWR@formatted{FiveStarCenterOpen}
\LWR@formatted{FiveStarOpenDotted}
\LWR@formatted{FiveStarOutline}
\LWR@formatted{FiveStarOutlineHeavy}
\LWR@formatted{FiveStarConvex}
\LWR@formatted{FiveStarShadow}
\LWR@formatted{AsteriskBold}
\LWR@formatted{AsteriskCenterOpen}
\LWR@formatted{AsteriskThin}
\LWR@formatted{AsteriskThinCenterOpen}
\LWR@formatted{EightStarTaper}
\LWR@formatted{EightStarConvex}
\LWR@formatted{SixStar}
\LWR@formatted{EightStar}
\LWR@formatted{EightStarBold}
\LWR@formatted{TwelweStar}
\LWR@formatted{SixteenStarLight}
\LWR@formatted{SixFlowerPetalRemoved}
\LWR@formatted{SixFlowerOpenCenter}
\LWR@formatted{Asterisk}
\LWR@formatted{SixFlowerAlternate}
\LWR@formatted{FiveFlowerPetal}
\LWR@formatted{SixFlowerPetalDotted}
\LWR@formatted{FiveFlowerOpen}
\LWR@formatted{EightFlowerPetal}
\LWR@formatted{SunshineOpenCircled}
\LWR@formatted{SixFlowerAltPetal}
\LWR@formatted{FourClowerOpen}
\LWR@formatted{FourClowerSolid}
\LWR@formatted{AsteriskRoundedEnds}
\LWR@formatted{EightFlowerPetalRemoved}
\LWR@formatted{EightAsterisk}
\LWR@formatted{SixFlowerRemovedOpenPetal}
```

```
\LWR@formatted{SparkleBold}
\LWR@formatted{Sparkle}
\LWR@formatted{SnowflakeChevron}
\LWR@formatted{SnowflakeChevronBold}
\LWR@formatted{Snowflake}
\LWR@formatted{CircleSolid}
\LWR@formatted{Ellipse}
\LWR@formatted{EllipseSolid}
\LWR@formatted{CircleShadow}
\LWR@formatted{EllipseShadow}
\LWR@formatted{Square}
\LWR@formatted{SquareSolid}
\LWR@formatted{SquareShadowBottomRight}
\LWR@formatted{SquareShadowTopRight}
\LWR@formatted{SquareShadowTopLeft}
\LWR@formatted{SquareCastShadowBottomRight}
\LWR@formatted{SquareCastShadowTopRight}
\LWR@formatted{SquareCastShadowTopLeft}
\LWR@formatted{TriangleUp}
\LWR@formatted{TriangleDown}
\LWR@formatted{DiamondSolid}
\LWR@formatted{OrnamentDiamondSolid}
\LWR@formatted{HalfCircleRight}
\LWR@formatted{HalfCircleLeft}
\LWR@formatted{RectangleThin}
\LWR@formatted{Rectangle}
\LWR@formatted{RectangleBold}
\LWR@formatted{ArrowBoldRightStrobe}
\LWR@formatted{ArrowBoldUpRight}
\LWR@formatted{ArrowBoldDownRight}
\LWR@formatted{ArrowBoldRightShort}
\LWR@formatted{ArrowBoldRightCircled}
```

File 37 **lwarp-biblatex.sty**

§ 134 Package biblatex

(*Emulates or patches code by* Philipp Lehman.)

Pkg biblatex When biblatex is used, modifications from newfloat may have to be undone.

for HTML output:

1. lwarp uses newfloat.
2. For classes with chapters which newfloat does not know about, such as CTEX-related classes, newfloat may modify `\addtocontents`.
3. biblatex, though, wants to patch `\addtocontents`, which causes an error if `\addtocontents` has been changed.
4. Therefore, `\addtocontents` is restored to its original here, since biblatex is about to be loaded.
5. This means that the newfloat's `chapterlistsgaps` option may no longer work.

```
\ifdef{\newfloat@addtocontents@ORI}{
    \let\addtocontents\newfloat@addtocontents@ORI
}{}

\LWR@ProvidesPackagePass{biblatex}[2018/03/04]
```

File 38 **lwarp-bibunits.sty**

§ 135 Package

bibunits

(*Emulates or patches code by* Thorsten Hansen.)

Pkg bibunits

bibunits is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bibunits}[2004/05/12]

\def\bu@bibdata{\BaseJobname}
```

File 39 **lwarp-bigdelim.sty**

§ 136 Package

bigdelim

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigdelim

bigdelim is used as-is for print or `lateximage`, and patched for HTML.

The delimiters are displayed in HTML by printing the delimiter, the text, and a thick border across the side of the `\multirow` which indicates the actual height of the delimiter. The delimiter character is given a `<span>` class of `ldelim` or `rdelim`, and the default CSS sets this to `font-size:200%`

⚠ use `\mrowcell`

`\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

<->	a	b
left {	c	d
	e	f
	g	h
<->	i	j

for HTML output: First, remove the temporary definitions of `\ldelim` and `\rdelim`, which were previously defined for tabular scanning in case bigdelim was not loaded:

```
\let\ldelim\relax
\let\rdelim\relax
```

Next, load the package's new definitions:

```
\LWR@ProvidesPackagePass{bigdelim}[2018/08/03]
```

`\ldelim` `\rdelim` {⟨*1:delimiter*⟩} {⟨*2:#rows*⟩} {⟨*3:width*⟩} [⟨*4:text*⟩]

```
\NewDocumentCommand{\LWR@HTML@ldelim}{m m m O{}}{%
\renewcommand{\LWR@multirowborder}{right}%
\multirow{#2}{#3}{#4 \InlineClass{ldelim}{#1}}%
}

\LWR@formatted{ldelim}

\NewDocumentCommand{\LWR@HTML@rdelim}{m m m O{}}{%
\renewcommand{\LWR@multirowborder}{left}%
\multirow{#2}{#3}{\InlineClass{rdelim}{#1} #4}%
}

\LWR@formatted{rdelim}
```

File 40 **lwarp-bigfoot.sty**

§ 137 Package

bigfoot

`Pkg` `bigfoot` bigfoot is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{bigfoot}[2015/08/30]
```

```
\RequirePackage{manyfoot}
```

```
\RequirePackage{perpage}

\def\RestyleFootnote#1#2{}
\def\FootnoteSpecific#1{}
\def\DefineFootnoteStack#1{}
\def\PushFootnoteMark#1{}
\def\PopFootnoteMark#1{}
\def\hfootfraction{0.9}
\def\vtypefraction{0.7}
\def\FootnoteMinimum{1sp}
\def\FootnoteMainMinimum{0pt}
\newcount\bigfoottolerance
\bigfoottolerance=100
\providecommand\footnotecarryratio{2}
```

File 41 **lwarp-bigstrut.sty**

§ 138 Package bigstrut

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigstrut

bigstrut is used as-is for print or lateximage, and patched for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{bigstrut}[2018/08/03]

\LetLtxMacro\LWR@origbigstrut\bigstrut

\renewcommand\bigstrut[1][x]{}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bigstrut\LWR@origbigstrut%
}
```

File 42 **lwarp-bitpattern.sty**

§ 139 Package bitpattern

(*Emulates or patches code by* Jean-Marc Bourguet.)

Pkg bitpattern

bitpattern is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bitpattern}[2015/12/11]

\xpatchcmd{\bitpattern}
    {\begingroup}
    {\begin{lateximage}[(-bitpattern-~\packagediagramname)]}
    {}
    {\LWR@patcherror{bitpattern}{bitpattern}}

\xpatchcmd{\bp@Done}
```

```
{\endgroup}
{\end{lateximage}}
{}
{\LWR@patcherror{bitpattern}{bp@Done}}
```

File 43 **lwarp-blowup.sty**

§ 140 Package

blowup

Pkg blowup blowup is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{blowup}[2018/01/02]
```

```
\newcommand*\blowUp[1]{}
```

File 44 **lwarp-booklet.sty**

§ 141 Package

booklet

(*Emulates or patches code by* Peter Wilson.)

Pkg booklet booklet is nullified.

for HTML output:

```
\LWR@ProvidesPackageDrop{booklet}[2009/09/02]
```

```
\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\newif\ifsidebyside     \sidebysidetrue
\newif\ifuselandscape   \uselandscapefalse
\newif\ifprintoption    \printoptionfalse
\newcommand*{\pagespersignature}[1]{}
\def\magstepminus#1{}
\newcommand*{\target}[3]{}
\newcommand*{\source}[3]{}
\newcommand*{\setpdftargetpages}{}
\newcommand*{\setdvipstargetpages}{}
\newcommand*{\targettopbottom}{}
\newcommand*{\twoupemptypage}{}
\newcommand*{\twoupclearpage}{}
\newcommand*{\checkforlandscape}{}
```

File 45 **lwarp-bookmark.sty**

§ 142 Package

bookmark

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg bookmark

bookmark is emulated.

for HTML output: Discard all options for lwarp-bookmark:

```
\LWR@ProvidesPackageDrop{bookmark}[2016/05/17]
```

```
\newcommand*{\bookmarksetup}[1]{}
\newcommand*{\bookmarksetupnext}[1]{}
\newcommand*{\bookmark}[2][]{}
\newcommand*{\bookmarkdefinestyle}[2]{}
\newcommand*{\bookmarkget}[1]{}
\newcommand{\BookmarkAtEnd}[1]{}
```

File 46 **lwarp-booktabs.sty**

§ 143 Package

booktabs

(*Emulates or patches code by* Simon Fear.)

Pkg booktabs

booktabs is emulated during HTML output, and used as-is during print output and inside an HTML `lateximage`.

for HTML output: First, forget the placeholder macros:

```
\LetLtxMacro\toprule\relax
\LetLtxMacro\midrule\relax
\LetLtxMacro\cmidrule\cline
\LetLtxMacro\bottomrule\relax
\LetLtxMacro\addlinespace\relax
\LetLtxMacro\morecmidrules\relax
\LetLtxMacro\specialrule\relax

\LWR@ProvidesPackagePass{booktabs}[2016/04/27]
```

```
\DeclareDocumentCommand{\LWR@HTML@toprule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1]({1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
                {\LWR@docmidrule[#1]({1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\global\booltrue{LWR@doingtbrule}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{toprule}

\DeclareDocumentCommand{\LWR@HTML@midrule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1]({1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
```

```
                {\LWR@docmidrule[#1]({1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\addtocounter{LWR@hlines}{1}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{midrule}

\DeclareDocumentCommand{\LWR@HTML@cmidrule}{O{\LWR@cmidrulewidth} d() m}{%
    \LWR@docmidrule[#1](#2){#3}%
    \LWR@getmynexttoken%
}%

\LWR@expandableformatted{cmidrule}

\DeclareDocumentCommand{\LWR@HTML@bottomrule}{o d()}{%
    \IfValueTF{#1}%
        {\LWR@docmidrule[#1]({1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {%
            \ifbool{FormatWP}%
            {\LWR@docmidrule[#1]({1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {\global\booltrue{LWR@doingtbrule}}%
        }%
    \LWR@getmynexttoken%
}%

\LWR@expandableformatted{bottomrule}

\DeclareDocumentCommand{\LWR@HTML@addlinespace}{o}{}%

\LWR@expandableformatted{addlinespace}

\DeclareDocumentCommand{\LWR@HTML@morecmidrules}{}{}%

\LWR@expandableformatted{morecmidrules}

\DeclareDocumentCommand{\LWR@HTML@specialrule}{m m m d()}%
  {\LWR@docmidrule[#1]({1-\arabic{LWR@tabletotalLaTeXcols}}\LWR@getmynexttoken}%

\LWR@expandableformatted{specialrule}
```

File 47 **lwarp-bophook.sty**

§ 144 Package

bophook

Pkg bophook bophook is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bophook}[2001/03/29]
```

```
\newcommand*{\AtBeginPage}[1]{}
\newcommand*{\PageLayout}[1]{}
```

File 48 **lwarp-bounddvi.sty**

§ 145 Package

bounddvi

Pkg bounddvi

bounddvi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bounddvi}[2016/12/28]
```

File 49 **lwarp-boxedminipage2e.sty**

§ 146 Package

boxedminipage2e

(*Emulates or patches code by* Scott Pakin.)

Pkg boxedminipage2e

boxedminipage2e is emulated.

for HTML output:

Discard all options for lwarp-boxedminipage2e:

```
\LWR@ProvidesPackageDrop{boxedminipage2e}[2015/03/09]
```

```
\newenvironment{boxedminipage}{%
\begin{BlockClass}{framebox}%
\minipage%
}
{
\endminipage%
\end{BlockClass}
}
```

File 50 **lwarp-breakurl.sty**

§ 147 Package

breakurl

(*Emulates or patches code by* Vilar Camara Neto.)

Pkg breakurl

breakurl is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{breakurl}[2013/04/10]
```

```
\LetLtxMacro\burl\url

\NewDocumentCommand{\LWR@burlaltb}{O{} +m m}{%
\LWR@ensuredoingapar%
\LWR@subhyperref{#2}%
\LWR@subhyperreftext{#3}%
```

```
\endgroup% restore catcodes
}

\newrobustcmd*{\burlalt}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@burlaltb%
}

\LetLtxMacro\urlalt\burlalt
```

File 51 **lwarp-breqn.sty**

§ 148 Package

breqn

(*Emulates or patches code by* Michael J. Downes, Morten Høgholm.)

Pkg breqn breqn is patched for use by lwarp.

⚠ darray darray is not supported.

⚠ MathJax MathJax does not support breqn.

for HTML output:

```
\LWR@ProvidesPackagePass{breqn}[2017/01/27]

\setkeys{breqn}{spread={5pt}}

\def\eqnumside{R}
% \def\eqnumplace{T}

\BeforeBeginEnvironment{dmath}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath- \mathimagename]
}

\AfterEndEnvironment{dmath}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dmath*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath*- \mathimagename]
}

\AfterEndEnvironment{dmath*}{
```

```
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dseries}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dseries- \mathimagename]
}

\AfterEndEnvironment{dseries}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dseries*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dseries*- \mathimagename]
}

\AfterEndEnvironment{dseries*}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dgroup}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dgroup- \mathimagename]
}

\AfterEndEnvironment{dgroup}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dgroup*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dgroup*- \mathimagename]
}

\AfterEndEnvironment{dgroup*}{
    \end{lateximage}\end{BlockClass}
}
```

File 52 **lwarp-bsheaders.sty**

§ 149 Package

bsheaders

Pkg bsheaders

bsheaders is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bsheaders}[1997/10/06]
```

File 53 **lwarp-bxpapersize.sty**

§ 150 Package bxpapersize

Pkg bxpapersize

bxpapersize is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bxpapersize}[2017/10/08]

\providecommand*\papersizesetup{\bxpapersizesetup}
\newcommand*\bxpapersizesetup[1]{}
```

File 54 **lwarp-bytefield.sty**

§ 151 Package bytefield

(*Emulates or patches code by* Scott Pakin.)

Pkg bytefield

bytefield is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bytefield}[2017/09/15]

\BeforeBeginEnvironment{bytefield}{\begin{lateximage}[(-bytefield-~\packagediagramname)]}

\AfterEndEnvironment{bytefield}{\end{lateximage}}
```

File 55 **lwarp-cancel.sty**

§ 152 Package cancel

Pkg cancel

cancel is used as-is for SVG math, and emulated for HTML text output.

for HTML output:

```
\LWR@origRequirePackage{lwarp-xcolor}% for \convertcolorspec
\LWR@ProvidesPackagePass{cancel}[2013/04/12]
```

`\cancel`to is math-only, so is used as-is.

```
\LetLtxMacro\LWR@origcancel\cancel
\LetLtxMacro\LWR@origbcancel\bcancel
\LetLtxMacro\LWR@origxcancel\xcancel

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\cancel\LWR@origcancel%
\LetLtxMacro\bcancel\LWR@origbcancel%
\LetLtxMacro\xcancel\LWR@origxcancel%
}
```

\LWR@cancelcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@cancelcolor}[5]{%
\ifcsempty{#2}%
{\InlineClass(#5){#3}{#1}}%
{\LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}%
}
```

\cancel {⟨*text*⟩}

```
\DeclareRobustCommand{\cancel}[1]{%
\begingroup%
\CancelColor%
\LWR@findcurrenttextcolor%
\color{black}%
\LWR@cancelcolor{#1}{LWR@tempcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
\endgroup%
}

\LetLtxMacro\bcancel\cancel
\LetLtxMacro\xcancel\cancel
```

File 56 **lwarp-canoniclayout.sty**

§ 153 Package canoniclayout

Pkg canoniclayout canoniclayout is ignored.

for HTML output: S

```
\LWR@ProvidesPackageDrop{canoniclayout}[2011/11/05]

\newcommand*{\currentfontletters}{}
\newcommand*{\charactersperpage}{}
```

File 57 **lwarp-caption.sty**

§ 154 Package caption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg caption caption is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{caption}[2018/10/05]

\renewcommand\caption@ibox[3]{%
  \@testopt{\caption@iibox{#1}{#2}{#3}}{%
%         \wd\@tempboxa%
```

```
        \linewidth% lwarp
  }%
% \LWR@traceinfo{caption@ibox: done}%
}

\long\def\caption@iibox#1#2#3[#4]{%
  \@testopt{\caption@iiibox{#1}{#2}{#3}{#4}}\captionbox@hj@default
}

\long\def\caption@iiibox#1#2#3#4[#5]#6{%
%   \setbox\@tempboxa\hbox{#6}%
  \begingroup
  #1*% set \caption@position
  \caption@iftop{%
    \LWR@traceinfo{caption@iiibox top}%
    \endgroup
    \parbox[t]{#4}{%
      #1\relax
      \caption@setposition t%
%       \vbox{\caption#2{#3}}%
      {\caption#2{#3}}% lwarp
%       \captionbox@hrule
%       \csname caption@hj@#5\endcsname
%       \unhbox\@tempboxa
       #6% lwarp
    }%
  }{%
    \LWR@traceinfo{caption@iiibox bottom}%
    \endgroup
    \parbox[b]{#4}{%
      #1\relax
      \caption@setposition b%
%       \csname caption@hj@#5\endcsname
%       \unhbox\@tempboxa
        #6% lwarp
%       \captionbox@hrule
%       \vtop{\caption#2{#3}}}%
      {\caption#2{#3}}% lwarp
     }%
  }%
\LWR@traceinfo{caption@iiibox: done}%
}

\def\caption@caption{%
  \caption@iftype
    {%
     \caption@checkgrouplevel\@empty\caption
     \caption@star
       {\caption@refstepcounter\@captype}%
       {\caption@dblarg{\@caption\@captype}}}%
    {\caption@Error{\noexpand\caption outside float}%
     \caption@gobble}%
}

\long\def\caption@@caption#1[#2]#3{%
```

```
  \ifcaption@star \else
    \caption@prepareanchor{#1}{#2}%
    \memcaptioninfo{#1}{\csname the#1\endcsname}{#2}{#3}%
    \@nameuse{nag@hascaptiontrue}%
  \fi

  \par
  \caption@beginex{#1}{#2}{#3}%
    \caption@setfloatcapt{%
      \caption@boxrestore
      \if@minipage
        \@setminipage
      \fi
      \caption@normalsize
      \ifcaption@star
        \let\caption@makeanchor\@firstofone
      \fi
      \@makecaption{\csname fnum@#1\endcsname}%
                   {\ignorespaces\caption@makeanchor{#3}}\par
      \caption@if@minipage\@minipagetrue\@minipagefalse}%
  \caption@end%
}
```

\caption@@@make {⟨*caption label*⟩} {⟨*caption text*⟩}

```
\renewcommand\caption@@@make[2]{%
\LWR@startpars% lwarp
%   \sbox\@tempboxa{#1}%
%   \ifdim\wd\@tempboxa=\z@
%     \let\caption@lsep\relax
%   \fi
  \caption@ifempty{#2}{%
    \let\caption@lsep\@empty
    \let\caption@tfmt\@firstofone
  }%
  \@setpar{\LWR@closeparagraph\@@par}% lwarp
  \caption@applyfont
  \caption@fmt
    {\ifcaption@star\else
       \begingroup
         \captionlabelfont
         #1%
       \endgroup
     \fi}%
    {\ifcaption@star\else
       \begingroup
         \caption@iflf\captionlabelfont
         \relax\caption@lsep
       \endgroup
     \fi}%
    {{\captiontextfont
      \caption@ifstrut
        {\vrule\@height\ht\strutbox\@width\z@}%
        {}%
      \nobreak\hskip\z@skip % enable hyphenation
```

```
      \caption@tfmt{#2}
    \LWR@ensuredoingapar% lwarp
      \caption@ifstrut
        {\ifhmode\@finalstrut\strutbox\fi}%
        {}%
      \par}}
\LWR@stoppars% lwarp
}
```

\caption@@make@ {⟨⟩} {⟨⟩}

```
\renewcommand{\caption@@make@}[2]{%
  \caption@stepthecounter
  \caption@beginhook
      \caption@@@make{#1}{#2}%
  \caption@endhook
}
```

```
% \DeclareCaptionBox{none}{#2}
\DeclareCaptionBox{parbox}{%
#2%
}
\DeclareCaptionBox{colorbox}{%
#2%
}
```

File 58 **lwarp-cases.sty**

§ 155 Package

cases

(*Emulates or patches code by* Donald Arseneau.)

Pkg cases cases is patched for use by lwarp.

⚠ MathJax MathJax does not support cases.

for HTML output:

```
\LWR@ProvidesPackagePass{cases}[2002/05/02]
```

```
\BeforeBeginEnvironment{numcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \mathimagename]
}

\AfterEndEnvironment{numcases}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{subnumcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
```

```
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \mathimagename]
}

\AfterEndEnvironment{subnumcases}{
    \end{lateximage}\end{BlockClass}
}
```

File 59 **lwarp-changebar.sty**

§ 156 Package changebar

Pkg changebar

changebar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{changebar}[2018/03/09]
```

```
\newcommand*{\cbstart}{}
\newcommand*{\cbend}{}
\newenvironment*{\changebar}{}{}
\newcommand*{\cbdelete}{}
\newcommand*{\nochnagebars}{}
\newcommand*{\cbcolor}[1]{}
\newlength{\changebarwidth}
\newlength{\deletebarwidth}
\newlength{\changebarsep}
\newcounter{changebargrey}
```

File 60 **lwarp-changepage.sty**

§ 157 Package changepage

(*Emulates or patches code by* Peter Wilson.)

Pkg changepage

changepage is emulated.

for HTML output:

Discard all options for lwarp-changepage:

```
\LWR@ProvidesPackageDrop{changepage}[2009/10/20]
```

```
\newif\ifoddpage
\DeclareRobustCommand{\checkoddpage}{\oddpagetrue}
\DeclareRobustCommand{\changetext}[5]{}
\DeclareRobustCommand{\changepage}[9]{}

\@ifundefined{adjustwidth}{
\newenvironment{adjustwidth}[2]{}{}
\newenvironment{adjustwidth*}[2]{}{}
}{
\renewenvironment{adjustwidth}[2]{}{}
\renewenvironment{adjustwidth*}[2]{}{}
```

```
}

\DeclareDocumentCommand{\strictpagecheck}{}{}
\DeclareDocumentCommand{\easypagecheck}{}{}
```

File 61 **lwarp-changes.sty**

§ 158 Package

changes

(*Emulates or patches code by* Ekkart Kleinod.)

Pkg changes changes is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{changes}[2015/04/27]

\xpatchcmd{\Changes@output}
    {#1}
    {\LWR@textcurrentcolor{#1}}
    {}
    {\LWR@patcherror{changes}{Changes@output}}

\xpatchcmd{\listofchanges}
    {
        \ifthenelse{\equal{\Changes@InID}{\@empty}}
        {\changesauthorname: \changesanonymousname}
        {%
        \changesauthorname: \Changes@InID
        \ifthenelse{\equal{\Changes@InName}{\@empty}}
        {}
        { (\Changes@InName)}
        }
    }
    {
        \LWR@textcurrentcolor{% lwarp
            \ifthenelse{\equal{\Changes@InID}{\@empty}}
            {\changesauthorname: \changesanonymousname}
            {%
            \changesauthorname: \Changes@InID
            \ifthenelse{\equal{\Changes@InName}{\@empty}}
            {}
            { (\Changes@InName)}
            }
        }
    }
    {}
    {\LWR@patcherror{changes}{listofchanges}}

\xpatchcmd{\listofchanges}
    {\parbox{\Changes@Len@summ}}
    {}
    {}
    {\LWR@patcherror{changes}{listofchanges}}
```

```

\xpatchcmd{\listofchanges}
    {\parbox{\Changes@Len@summ}}
    {}
    {}
    {\LWR@patcherror{changes}{listofchanges}}

\xpatchcmd{\listofchanges}
    {\parbox{\Changes@Len@summ}}
    {}
    {}
    {\LWR@patcherror{changes}{listofchanges}}
```

File 62 **lwarp-chappg.sty**

§ 159 Package chappg

(*Emulates or patches code by* Robin Fairbairns.)

Pkg chappg chappg is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{chappg}[2006/05/09]

\renewcommand{\pagenumbering}[2][]{}
\providecommand{\chappgsep}{--}
```

File 63 **lwarp-chapterbib.sty**

§ 160 Package chapterbib

(*Emulates or patches code by* Donald Arseneau.)

Pkg chapterbib chapterbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chapterbib}[2010/09/18]

\xdef\@savedjobname{\BaseJobname}
\let\@currentipfile\@savedjobname
```

File 64 **lwarp-chemfig.sty**

§ 161 Package chemfig

(*Emulates or patches code by* Christian Tellechea.)

Pkg chemfig chemfig is patched for use by lwarp.

If using \polymerdelim to add delimiters to a \chemfig, wrap both inside a single lateximage:

```
\begin{lateximage}[(-chemfig-~\packagediagramname)]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

The images are not hashed because they depend on external settings which may be changed at any time, and are unlikely to be reused inline anyhow.

for HTML output:

```
\LWR@ProvidesPackagePass{chemfig}

\LetLtxMacro\LWR@chemfig@origchemfig\chemfig

\DeclareDocumentCommand\chemfig{s O{} O{} m}{%
    \begin{lateximage}[(-chemfig-~\packagediagramname)]%
    \IfBooleanTF{#1}{%
        \LWR@chemfig@origchemfig*[#2][#3]{#4}%
    }{%
        \LWR@chemfig@origchemfig[#2][#3]{#4}%
    }
    \end{lateximage}%
}

\LetLtxMacro\LWR@chemfig@origCF@lewis@b\CF@lewis@b

\def\CF@lewis@b#1#2{%
\begin{lateximage}[(-chemfig-~\packagediagramname)]%
\LWR@chemfig@origCF@lewis@b{#1}{#2}%
\end{lateximage}%
}

\preto{\schemestart}{\begin{lateximage}[(-chemfig-~\packagediagramname)]}
\appto{\CF@schemestop}{\end{lateximage}}

\LetLtxMacro\LWR@chemfig@origchemleft\chemleft

\def\chemleft#1#2\chemright#3{%
\begin{lateximage}[(-chemfig-~\packagediagramname)]%
\LWR@chemfig@origchemleft#1#2\chemright#3%
\end{lateximage}%
}

\LetLtxMacro\LWR@chemfig@origchemup\chemup

\def\chemup#1#2\chemdown#3{%
\begin{lateximage}[(-chemfig-~\packagediagramname)]%
\LWR@chemfig@origchemup#1#2\chemdown#3%
\end{lateximage}%
}
```

File 65 **lwarp-chemformula.sty**

§ 162 Package

chemformula

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemformula

chemformula is patched for use by lwarp.

The svg images are hashed according to contents and local options. Global options are assumed to be constant document-wide.

⚠ chemformula with MathJax

chemformula works best without MathJax. If MathJax is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The chemformula package adapts to `array`, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, `\displaymathother` may also be used for other forms of display and inline math which contain chemformula expressions.

for HTML output:

```
\LWR@ProvidesPackagePass{chemformula}[2017/03/23]
```

```
\ExplSyntaxOn
```

`\ch`

Enclose in an inline svg image or MathJax. The `alt` tag is is the contents of the `\ch` expression. The filename is hashed, and also has additional hashing information based on the local options.

```
\RenewDocumentCommand \ch { O{}m }
 {%
```

To work inside `align` with `\displaymathother`, a simple version must be used to work with chemformula's adaptation to `align`.

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%  lwarp
    {
        \chemformula_ch:nn {#1} {#2}%   original
    }
```

If used as the outer level, must temporarily ensure MathJax is disabled:

```
    {
        \begingroup%
        \boolfalse{mathjax}%
```

An inline image is used, adjusted for the baseline:

```
        \LWR@subsingledollar*{% lwarp
            \textbackslash{}ch\{\LWR@HTMLsanitize{#2}\}% alt text
        }{%
         \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}% add'l hashing
        }%
        {%
```

```
            \chemformula_ch:nn {#1} {#2}%   original
        }%
        \endgroup%
    }
  }
```

\chcpd Similar to \ch.

```
\cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
  {
    \begingroup%
    \boolfalse{mathjax}%
    \LWR@subsingledollar*{% lwarp
        \textbackslash{}chcpd\{\LWR@HTMLsanitize{#2}\}%
    }{%
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{% original
    \group_begin:
      \tl_if_blank:nF {#2}
        {
          \keys_set:nn {chemformula} {#1}
          \__chemformula_save_catcodes:
          \__chemformula_sanitize:Nn
            \l__chemformula_chemformula_tmpa_tl
            {#2}
          \__chemformula_input_compound_no_check:NV
            \l__chemformula_compound_tl
            \l__chemformula_chemformula_tmpa_tl
          \__chemformula_prepare_output:N \l__chemformula_compound_tl
          \chemformula_write:V \l__chemformula_compound_tl
        }
    \group_end:
    }
    \endgroup
  }
```

\charrow If standalone, appears in a regular lateximage.

```
\RenewDocumentCommand \charrow { mO{}O{} }
{
    \begin{lateximage}[(-chemformula- charrow)]
    \group_begin:
      \__chemformula_draw_arrow:nnn {#1} {#2} {#3}
    \group_end:
    \end{lateximage}
}
```

\chname If standalone, appears in a regular lateximage, hashed according to contents.

```
\RenewDocumentCommand \chname { R(){}R(){} }
  {
    \begin{lateximage}*[%
        \textbackslash{}chname(\LWR@HTMLsanitize{#1})(\LWR@HTMLsanitize{#2})
    ]%
        \chemformula_chwritebelow:nn {#1} {#2}
```

```
    \end{lateximage}
  }
```

\chlewis Placed inline, hashed according to contents and options.

```
\RenewDocumentCommand \chlewis { O{}mm }
  {
    \begingroup%
    \boolfalse{mathjax}%
    \LWR@subsingledollar*{\textbackslash{}chlewis\{#2\}\{#3\}}%
    {
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{
        \chemformula_lewis:nnn {#1} {#2} {#3}
    }
    \endgroup%
  }
```

lwarp redefines the $ character, so special handling is required to escape math expressions inside \ch.

This boolean tracks a new kind of escaped math:

```
\bool_new:N      \l__chemformula_first_last_LWRdollar_bool
```

\chemformula_input_escape_math

Adds additional escaping for the new dollar definition:

```
\cs_gset_protected:Npn \__chemformula_input_escape_math:n #1
  {
    \__chemformula_first_last_math:n {#1}
    \bool_if:NT \l__chemformula_first_last_dollar_bool
      {
        \bool_set_true:N \l__chemformula_first_last_math_bool
        \__chemformula_read_escape_dollar:w #1 \q_nil
      }
    \bool_if:NT \l__chemformula_first_last_mathbraces_bool
      {
        \bool_set_true:N \l__chemformula_first_last_math_bool
        \__chemformula_read_escape_mathbraces:w #1 \q_nil
      }
```

Added by lwarp:

```
    \bool_if:NT \l__chemformula_first_last_LWRdollar_bool%      lwarp
      {
        \bool_set_true:N \l__chemformula_first_last_math_bool%  lwarp
        \__chemformula_read_escape_LWRdollar:w #1 \q_nil%       lwarp
      }
  }
```

\chemformula_read_escape_LWRdollar

The following parses the contents inside the new dollars.

lwarp keeps the dollar as its original math shift until the document starts. While chemmacros is being patched, the dollar must temporarily be set to its new meaning during the following definition.

```
\begingroup
\catcode`\$=\active

\cs_new_protected:Npn \__chemformula_read_escape_LWRdollar:w $#1$ \q_nil
{
    \__chemformula_read_escape_math:n {#1}
}

\endgroup
```

\chemformula_bool_set_if_first_last

The following looks at the first and last tokens for delimiters to escape math inside \ch. The original definition is modified to look for the control sequences which are used by the new meaning of $.

```
\cs_new_protected:Npn \__chemformula_bool_cs_set_if_first_last:NnNN #1#2#3#4
  {
    \int_zero:N \l__chemformula_tmpa_int
    \int_zero:N \l__chemformula_tmpb_int
    \int_set:Nn \l__chemformula_tmpa_int { \tl_count:n {#2} }
    \tl_map_inline:nn {#2}
      {
        \int_incr:N \l__chemformula_tmpb_int
        \int_compare:nT { \l__chemformula_tmpb_int = 1 }
          {
```

At the start, the cs_ version compares control sequences:

```
            \ifdefstrequal{##1}{#3}% lwarp
                {
                    \bool_set_true:N #1
                }% lwarp
                {}
          }
```

At the end, compare more control sequences:

```
        \int_compare:nT { \l__chemformula_tmpb_int = \l__chemformula_tmpa_int }
          {
            \ifdefstrequal{##1}{#4}
                {}
                {
                    \bool_set_false:N #1
                }
          }
      }
  }
```

\chemformula_first_last_math

Modified to check for the new meaning of $ at first/last:

```
\cs_gset_protected:Npn \__chemformula_first_last_math:n #1
 {
   \bool_set_false:N \l__chemformula_first_last_math_bool
   \bool_set_false:N \l__chemformula_first_last_dollar_bool
   \bool_set_false:N \l__chemformula_first_last_LWRdollar_bool%    lwarp
   \bool_set_false:N \l__chemformula_first_last_mathbraces_bool
   \__chemformula_bool_set_if_first_last:Nnnn
     \l__chemformula_first_last_dollar_bool
     {#1}
     { $ } { $ }
   \bool_if:NF \l__chemformula_first_last_dollar_bool
     {
       \__chemformula_bool_set_if_first_last:Nnnn
         \l__chemformula_first_last_mathbraces_bool
         {#1}
         { \( } { \) }
```

Added by lwarp:

```
         \bool_if:NF \l__chemformula_first_last_mathbraces_bool%   lwarp
           {
               \__chemformula_bool_cs_set_if_first_last:NnNN
               \l__chemformula_first_last_LWRdollar_bool
               {#1}
               { \LWR@newsingledollar } { \LWR@newsingledollar }
           }%  lwarp
     }
 }

\ExplSyntaxOff
```

File 66 **lwarp-chemgreek.sty**

§ 163 Package

chemgreek

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemgreek

chemgreek is patched for use by lwarp.

Greek symbols

⚠ package selection

To use text-mode symbols, use packages textalpha or textgreek. Using the other packages supported by chemgreek will result in math-mode greek characters, which will result in svg images being used. These images will be hashed.

⚠ XeLaTeX, LuaLaTeX

If using XeLaTeX or LuaLaTeX, select the fontspec mapping:

```
\selectchemgreekmapping{fontspec}
```

for HTML output:

```
\LWR@ProvidesPackagePass{chemgreek}[2016/02/10]

\ExplSyntaxOn
```

```

\cs_gset_protected:Npn \chemgreek_text:n #1
  { { \text {#1} } }

\appto\LWR@restoreorigformatting{%
\cs_set_protected:Npn \chemgreek_text:n #1%
  { \ensuremath { \text {#1} } }%
}

\ExplSyntaxOff
```

File 67 **lwarp-chemmacros.sty**

§ 164 Package chemmacros

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemmacros chemmacros is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chemmacros}[2017/08/28]
```

SVG file hashing assumes that the relevent options are constant for the entire document.

§ 164.1 Changes to the user's document

⚠ \makepolymerdelims When using \makepolymerdelims, enclose the entire expression inside a polymerdelims environment, such as (from the chemmacros manual):

```
\begin{polymerdelims}
\chemfig{-[@{op,.75}]CH_2-CH(-[6]Cl)-[@{cl,0.25}]}
\makepolymerdelims{5pt}[27pt]{op}{cl}
\end{polymerdelims}
```

⚠ redox reactions Redox reactions must be enclosed inside a redoxreaction environment. For print output, extra space must be included above and/or below the result, so they are declared as arguments to the environment, instead of being manually entered as per the chemmacros manual. For HTML output, the extra space is ignored and a lateximage is used instead.

```
\begin{redoxreaction}{7mm}{7mm}
\OX{a,Na} $\rightarrow$ \OX{b,Na}\pch\redox(a,b){oxidation}
\end{redoxreaction}
```

§ 164.2 Code

§ 164.3 Loading modules

Patching chemmacros modules must be done `\AtBeginDocument`, since modules are invoked by the user in the preamble, and each patch is only done if the module is loaded.

```
\ExplSyntaxOn

\newcommand{\@ifchemmacrosmoduleloaded}[1]{%
\@ifl@aded{\c__chemmacros_module_extension_tl}{\c__chemmacros_module_prefix_tl.#1}%
}

\ExplSyntaxOff
```

§ 164.4 New environments

`\makepolymerdelims` and redox reactions must be enclosed in a `lateximage` during HTML output. These environments are provided here in HTML mode, and in the lwarp core in print mode, as a high-level semantic syntax which automatically embeds the contents in a `lateximage` with an appropriate `alt` tag.

Env `polymerdelims`

```
\DeclareDocumentEnvironment{polymerdelims}{}
{\begin{lateximage}[(-chemmacros- polymer)]}
{\end{lateximage}}
```

Env `redoxreaction` {⟨*space above*⟩} {⟨*space below*⟩}

For HTML output, the above and below space is ignored, and a `lateximage` is used instead. For the print output version, see section 85.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
{\begin{lateximage}[(-chemmacros- redoxreaction)]}
{\end{lateximage}}
```

```
\ExplSyntaxOn
```

§ 164.5 Acid-base

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{acid-base}{
\PackageInfo{lwarp}{Patching~chemmacros~module~acid-base}

\cs_gset_protected:Npn \chemmacros_p:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{
        \textbackslash{}p\{\LWR@HTMLsanitize{#1}\}
    }{
        chemmacrosp\protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
```

```
    }{
    \group_begin:
      \mbox
        {
          \chemmacros_p_style:n {p}
          \ensuremath {#1}
        }
    \group_end:
    }
    \endgroup
  }

\RenewDocumentCommand \pH  {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {H} }
    }
    \endgroup
}

\RenewDocumentCommand \pOH {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pOH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {OH} }
    }
    \endgroup
}

\RenewDocumentCommand \pKa {O{}}
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKa{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Ka \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
    \endgroup
  }

\RenewDocumentCommand \pKb {O{}}
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKb{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Kb \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
```

```
    \endgroup
  }

\LetLtxMacro\LWR@chemmacros@origKa\Ka
\renewcommand*{\Ka}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Ka}{chemmacros}{%
        \LWR@chemmacros@origKa%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKb\Kb
\renewcommand*{\Kb}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Kb}{chemmacros}{%
        \LWR@chemmacros@origKb%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKw\Kw
\renewcommand*{\Kw}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Kw}{chemmacros}{
        \LWR@chemmacros@origKw
    }
    \endgroup
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.6 Charges

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{charges}{
\PackageInfo{lwarp}{Patching~chemmacros~module~charges}

\cs_gset_protected:Npn \fplus  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fplus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fplus:}  }
    \endgroup
}
\cs_gset_protected:Npn \fminus {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fminus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fminus:} }
    \endgroup
```

```
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.7 Nomenclature

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{nomenclature}{
\PackageInfo{lwarp}{Patching~chemmacros~module~nomenclature}

\cs_gset_protected:Npn \chemmacros_charge:n #1
  {
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}
    {\chemmacros_chemformula:n { {}^{#1} }}
    {
        \ifmmode
            {\chemmacros_chemformula:n { {}^{#1} }}
        \else
            { \textsuperscript{\ensuremath{#1}} }
        \fi
    }
  }


\LetLtxMacro\LWR@chemmacros@origchemprime\chemprime

\protected\def\chemprime { \HTMLunicode{2032} }

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\chemprime\LWR@chemmacros@origchemprime%
}
```

```
\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_cip:n #1
  {
    \tl_set:Nn \l__chemmacros_tmpa_tl {#1}
    \int_step_inline:nnnn {0} {1} {9}
      {
        \tl_replace_all:Nnn \l__chemmacros_tmpa_tl
          {##1}
          { { \l__chemmacros_cip_number_tl ##1} }
      }
    {
        \l__chemmacros_cip_inner_tl
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \l__chemmacros_tmpa_tl
        }}% lwarp
    }
  }
\EndChemCompatibility
```

```
\RenewDocumentCommand \Sconf { O{S} } {
\begin{lateximage}[\textbackslash{}Sconf{[}#1{]}]
    \chemmacros_sconf:n {#1}
\end{lateximage}
```

```
}

\RenewDocumentCommand \Rconf { O{R} } {
\begin{lateximage}[\textbackslash{}Rconf{[}#1{]}]
    \chemmacros_rconf:n {#1}
\end{lateximage}
}

\cs_gset_protected:Npn \chemmacros_hapto:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}hapto\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemeta }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_dento:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}dento\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemkappa }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_bridge:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}bridge\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        { \l__chemmacros_bridge_super_bool }
        { \chemmu }
        {#1}
    }
    \endgroup
```

```
  }
}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.8 Particles

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{particles}{
\PackageInfo{lwarp}{Patching~chemmacros~module~particles}

\cs_gset_protected:Npn \chemmacros_declare_nucleophile:Nn #1#2
  {
    \cs_set_protected:cpn {__chemmacros_ \chemmacros_remove_backslash:N #1:}
      {
        \bool_if:NTF \l__chemmacros_nucleophile_elpair_bool
          {
            \chemmacros_elpair:n { #2 }
            \chemmacros_if_compatibility:nnT {>=} {5.3}
              { \skip_horizontal:N \l__chemmacros_nucleophile_dim }
            \chemmacros_chemformula:n { {}^{-} }
          }
          { \chemmacros_chemformula:n { #2^{-} } }
      }
    \DeclareDocumentCommand #1 {o}
      {%
        \begin{lateximage}%
        \group_begin:%
          \IfNoValueF {##1}%
            { \chemmacros_set_keys:nn {particles} {##1} }%
          \use:c {__chemmacros_ \chemmacros_remove_backslash:N #1:}%
        \group_end:%
        \end{lateximage}%
      }
  }

\RenewChemNucleophile \Nuc {Nu}
\RenewChemNucleophile \ba  {ba}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.9 Phases

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{phases}{
\PackageInfo{lwarp}{Patching~chemmacros~module~phases}

\cs_undefine:N \chemmacros_phase:n
\cs_new_protected:Npn \chemmacros_phase:n #1
  {
    \chemmacros_leave_vmode:
    \bool_if:NTF \l__chemmacros_phases_sub_bool
      {
        \ifnumequal{\value{LWR@lateximagedepth}}{0}
        {
```

```
            \textsubscript{ (#1) }
        }
        {
            \chemformula_subscript:n { (#1) }
        }
      }
      {
        \skip_horizontal:N \l__chemmacros_phases_space_dim
        \chemmacros_text:n { (#1) }
      }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.10 Mechanisms

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{mechanisms}{
\PackageInfo{lwarp}{Patching~chemmacros~module~mechanisms}

\chemmacros_define_keys:nn {textmechanisms}
  {
    type      .choice: ,
    type /    .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{N}
          }
          { }
      } ,
    type / 1  .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{N}
            1
          }
          { }
      } ,
    type / 2  .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{N}
            2
          }
          { }
      } ,
    type / se .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{E}
```

```
          }
          { }
      } ,
    type / 1e .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{E}
            1
          }
          { }
      } ,
    type / 2e .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{E}
            2
          }
          { }
      } ,
    type / ar .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{E}
          }
          { Ar - }
      } ,
    type / e  .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { } { } } ,
    type / e1 .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { 1 } { } } ,
    type / e2 .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { 2 } { } } ,
    type / cb .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { E }
          {
            1
              \textsubscript{cb}
          }
          { }
      } ,
    type      .default:n =
  }

\cs_gset_protected:Npn \chemmacros_mechanisms:n #1
  {
    \tl_if_blank:nTF {#1}
      { \chemmacros_set_keys:nn {textmechanisms} { type } }
      { \chemmacros_set_keys:nn {textmechanisms} { type = #1 } }
    \mbox
      {
        \tl_use:N \l__chemmacros_mechanisms_ar_tl
```

```
        \tl_use:N \l__chemmacros_mechanisms_type_tl
        \tl_use:N \l__chemmacros_mechanisms_mol_tl
      }
  }

\appto\LWR@restoreorigformatting{%
\cs_set_protected:Npn \chemmacros_mechanisms:n #1%
  {%
    \tl_if_blank:nTF {#1}%
      { \chemmacros_set_keys:nn {mechanisms} { type } }%
      { \chemmacros_set_keys:nn {mechanisms} { type = #1 } }%
    \mbox%
      {%
        \tl_use:N \l__chemmacros_mechanisms_ar_tl%
        \tl_use:N \l__chemmacros_mechanisms_type_tl%
        \tl_use:N \l__chemmacros_mechanisms_mol_tl%
      }%
  }%
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.11 Newman

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{newman}{
\PackageInfo{lwarp}{Patching~chemmacros~module~newman}

\RenewDocumentCommand \newman {od()m}%
  {
    \IfValueTF{#2}
    {\begin{lateximage}[\textbackslash{}newman(#2)\{#3\}]}
    {\begin{lateximage}[\textbackslash{}newman\{#3\}]}
    \group_begin:
      \IfNoValueF  {#1} { \chemmacros_set_keys:nn {newman} {#1} }
      \IfNoValueTF {#2}
        { \chemmacros_newman:nn {  } {#3} }
        { \chemmacros_newman:nn {#2} {#3} }
    \group_end:
    \end{lateximage}
  }%

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.12 Orbital

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{orbital}{
\PackageInfo{lwarp}{Patching~chemmacros~module~orbital}

\RenewDocumentCommand \orbital {om}
  {
    \IfValueTF{#1}
```

```
    {
        \begin{lateximage}[%
            \textbackslash{}orbital{[}\LWR@HTMLsanitize{#1}{]}\{#2\}%
        ][][margin-left: 1em ; margin-right: 1em]
    }
    {
        \begin{lateximage}[%
            \textbackslash{}orbital\{#2\}%
        ][][margin-left: 1em ; margin-right: 1em]
    }
    \group_begin:
      \chemmacros_set_keys:nn {orbital/type} {#2}
      \IfNoValueTF {#1}
        { \chemmacros_orbital:n {  } }
        { \chemmacros_orbital:n {#1} }
    \group_end:
    \end{lateximage}
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.13 Reactions

\chemmacros_declare_reaction_env {⟨*chem*⟩} {⟨*math*⟩} {⟨*args number*⟩} {⟨*argument list ({#2}{#3}...)*⟩}

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{reactions}{
\PackageInfo{lwarp}{Patching~chemmacros~module~reactions}

\cs_gset_protected:Npn \chemmacros_declare_reaction_env:nnnn #1#2#3#4
  {
   \exp_args:Nnx \DeclareDocumentEnvironment {#1} { O{} \prg_replicate:nn {#3+0} {m} }
      {
        \boolfalse{mathjax}%    lwarp
        \chemmacros_add_reaction_description:n {##1}
        \__chemmacros_begin_reaction:
        \chemmacros_reaction_read:nnw {#2} {#4}
      }
      {
        \__chemmacros_end_reaction:
      }
  }
\cs_generate_variant:Nn \chemmacros_declare_reaction_env:nnnn {nnnV}

\RenewChemReaction {reaction}   {equation}
\RenewChemReaction {reaction*}  {equation*}
\RenewChemReaction {reactions}  {align}
\RenewChemReaction {reactions*} {align*}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.14 Redox

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{redox}{
\PackageInfo{lwarp}{Patching~chemmacros~module~redox}

\NewDocumentCommand \LWR@chemmacros@ox { s m >{\SplitArgument{1}{,}}m }
  {
    \IfBooleanTF {#1}
      { \chemmacros_ox:nnnn {#1} {#2} #3 }
      { \chemmacros_ox:nnnn {  } {#2} #3 }
  }

\RenewDocumentCommand \ox { s O{} m }
  {
    \begingroup
    \boolfalse{mathjax}
    \IfBooleanTF {#1}
      {
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            star \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
        }{%
            \LWR@chemmacros@ox* {#2} {#3}% contents
        }%
      }
      {
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
        }{%
            \LWR@chemmacros@ox {#2} {#3}% contents
        }%
      }
    \endgroup
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.15 Scheme

Fix for chemmacros as of v5.8b, when using newfloat and babel:

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{scheme}{
\PackageInfo{lwarp}{Patching~chemmacros~module~scheme}

\ifdefstring{\schemename}{los}{
\SetupFloatingEnvironment{scheme}{
name = \chemmacros_translate:n {scheme-name}
}
}{}
```

```

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.16 Spectroscopy

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{spectroscopy}{
\PackageInfo{lwarp}{Patching~chemmacros~module~spectroscopy}

\ChemCompatibilityTo{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
      {
        \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
        \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
      }
    \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%     \chemmacros_chemformula:n { ^{#1} }
    \textsuperscript{#1}
    \bool_if:NTF \l__chemmacros_nmr_parse_bool
      { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
      { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
    \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
    \tl_use:N \l__chemmacros_nmr_method_tl
  }
\EndChemCompatibility
\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \group_begin:
      \tl_use:N \l__chemmacros_nmr_base_format_tl
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
          \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
        }
      \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%       \chemmacros_chemformula:n { ^{#1} }
      \textsuperscript{#1}
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \bool_if:NTF \l__chemmacros_nmr_parse_bool
            { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
            { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
        }
      \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
      \tl_use:N \l__chemmacros_nmr_method_tl
    \group_end:
  }
\EndChemCompatibility


\cs_gset_protected:Npn \chemmacros_nmr_position:n #1
```

```
  {
    \chemmacros_chemformula:x
      {
        \exp_not:V \g__chemmacros_nmr_element_tl
        \bool_if:NF \l__chemmacros_nmr_position_side_bool
          {
            \tl_if_eq:NnTF \l__chemmacros_nmr_position_tl {^}% lwarp
            { \textsuperscript{\exp_not:n { {#1} }} }% lwarp
            { \textsubscript{\exp_not:n { {#1} }} }% lwarp
%             \exp_not:V \l__chemmacros_nmr_position_tl
%             \exp_not:n { {#1} }
          }
      }
    \bool_if:NT \l__chemmacros_nmr_position_side_bool
      {
        \tl_use:N \l__chemmacros_nmr_position_tl
        \__chemmacros_nmr_position:n {#1}
      }
  }

\cs_gset_protected:Npn \__chemmacros_nmr_coupling:w (#1;#2)
  {
    \tl_set:Nn \l__chemmacros_nmr_coupling_bonds_tl
      {
        \l__chemmacros_nmr_coupling_bonds_pre_tl
        #1
        \l__chemmacros_nmr_coupling_bonds_post_tl
      }
    \bool_if:NTF \l__chemmacros_nmr_coupling_nuclei_sub_bool
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
%             \c_math_subscript_token
            \textsubscript% lwarp
              {
                \l__chemmacros_nmr_coupling_nuclei_pre_tl
                \chemmacros_chemformula:n {#2}
                \l__chemmacros_nmr_coupling_nuclei_post_tl
              }
          }
      }
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
            \l__chemmacros_nmr_coupling_nuclei_pre_tl
            \chemmacros_chemformula:n {#2}
            \l__chemmacros_nmr_coupling_nuclei_post_tl
          }
      }
    \__chemmacros_nmr_coupling_aux_i:w
  }

\AfterEndPreamble{% After \AtBeginDocument
% \NMR{<num>,<elem>}(<num>,<unit>)[<solvent>] ALL arguments are optional
% \NMR* same but without ": $\delta$" at end
```

```
\cs_gset_protected:Npn \chemmacros_nmr:nnnn #1#2#3#4
    {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item \scan_stop: }
    \group_begin:
        \chemmacros_leave_vmode:
        \bool_set_false:N \l__chemmacros_nmr_frequency_bool
        \bool_set_false:N \l__chemmacros_nmr_solvent_bool
        \tl_if_empty:nF {#3}
        { \bool_set_true:N \l__chemmacros_nmr_frequency_bool }
        \tl_if_empty:nF {#4}
        { \bool_set_true:N \l__chemmacros_nmr_solvent_bool }
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            ||
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_delimiters_bool }
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            &&
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_comma_bool }
        \tl_if_empty:nTF {#2}
        {
            \__chemmacros_nmr_nucleus:VV
            \l__chemmacros_nmr_isotope_default_tl
            \l__chemmacros_nmr_element_default_tl
        }
        { \__chemmacros_nmr_nucleus:w #2 \q_stop }
        \mode_if_math:TF
        {
            \text
            {
                \group_begin:
                \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
                \__chemmacros_nmr_base:VV
                    \g__chemmacros_nmr_isotope_tl
                    \g__chemmacros_nmr_element_tl
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ~ ( }
                \bool_if:NT \l__chemmacros_nmr_frequency_bool
                    { \__chemmacros_nmr_frequency:n {#3} }
                \bool_if:NT \l__chemmacros_nmr_comma_bool
                    { , ~ }
                \bool_if:NT \l__chemmacros_nmr_solvent_bool
                    { \chemmacros_chemformula:n {#4} }
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ) }
                \tl_if_blank:nT {#1} {:~}
}}% lwarp
                \group_end:
```

```
            }
            \tl_if_blank:nT {#1}
            {
                \delta
                \text { \l__chemmacros_nmr_delta_tl }
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {=}
            }
        }
        {
            \group_begin:
            \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \__chemmacros_nmr_base:VV
                \g__chemmacros_nmr_isotope_tl
                \g__chemmacros_nmr_element_tl
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {~(}
            \bool_if:NT \l__chemmacros_nmr_frequency_bool
                { \__chemmacros_nmr_frequency:n {#3} }
            \bool_if:NT \l__chemmacros_nmr_comma_bool
                {,~}
            \bool_if:NT \l__chemmacros_nmr_solvent_bool
                {
                \bool_if:NTF \l__chemmacros_nmr_parse_bool

%                     { \chemformula_ch:nn { } {#4} }%  original
                    {\ch{#4}}%  lwarp
                    {#4}
                }
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {)}
}}% lwarp
            \tl_if_blank:nT {#1} {:}
            \group_end:
            \tl_if_blank:nT {#1}
            {
                \tl_use:N \c_space_tl
                \c_math_toggle_token
                \delta
                \c_math_toggle_token
                \l__chemmacros_nmr_delta_tl
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {~=}
            }
        }
    \group_end:
    }
}% AfterEndPremble


\RenewDocumentCommand \chemmacros_data:w { smo }
  {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item }
      {
%         \tl_use:N \l__chemmacros_nmr_format_tl #2
        \tl_use:N \l__chemmacros_nmr_format_tl
```

```
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            #2
            \IfNoValueF {#3} { ~ ( #3 ) }
         \IfBooleanT {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { : } }
        }}% lwarp
      }
    \IfBooleanF {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { ~ = } }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 164.17 Thermodynamics

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{thermodynamics}{
\PackageInfo{lwarp}{Patching~chemmacros~module~thermodynamics}

\cs_gset_protected:Npn \chemmacros_state:nn #1#2
  {
    \group_begin:
      \boolfalse{mathjax}
      \chemmacros_set_keys:nn {thermodynamics} {#1}
        \LWR@subsingledollar*{% yes hashing
            \textbackslash{}state\{\LWR@HTMLsanitize{#2}\}% alt
        }{%
            chemmacros_state% add'l hashing
            #1% options
            LSP \tl_use:N \l__chemmacros_state_sp_left_tl% super/subscripts
            LSB \tl_use:N \l__chemmacros_state_sb_left_tl
            RSP \tl_use:N \l__chemmacros_state_sp_right_tl
            RSB \tl_use:N \l__chemmacros_state_sb_right_tl
        }
        {
         \LWR@origensuredmath{
          \chemmacros_text:V \l__chemmacros_state_pre_tl
          \c_math_superscript_token
            { \chemmacros_text:V \l__chemmacros_state_sp_left_tl }
```

Only add the subscripts if they are being used. This avoids causing an incorrect depth, as the empty subscript will be measured by TEX but cropped out by *pdfcrop*.

```
          \tl_if_empty:NTF \l__chemmacros_state_sb_left_tl
          {}
          {
            \c_math_subscript_token
            { \chemmacros_text:V \l__chemmacros_state_sb_left_tl }
          }
          #2
          \c_math_superscript_token
            { \chemmacros_text:V \l__chemmacros_state_sp_right_tl }
          \tl_if_empty:NTF \l__chemmacros_state_sb_right_tl
          {}
          {
            \c_math_subscript_token
```

```
            { \chemmacros_text:V \l__chemmacros_state_sb_right_tl }
          }
          \chemmacros_text:V \l__chemmacros_state_post_tl
         }
        }
    \group_end:
  }
\cs_generate_variant:Nn \chemmacros_state:nn { nV }

\cs_gset_protected:Npn \chemmacros_declare_state:Nn #1#2
  {
    \chemmacros_define_keys:xn
      {thermodynamics/\chemmacros_remove_backslash:N #1}
      {
        pre               .meta:nn = {chemmacros/thermodynamics} { pre = ##1 } ,
        post             .meta:nn = {chemmacros/thermodynamics} { post = ##1 } ,
     superscript-left  .meta:nn = {chemmacros/thermodynamics} { superscript-left = ##1 } ,
     superscript-right .meta:nn = {chemmacros/thermodynamics} { superscript-right = ##1 } ,
        superscript       .meta:n  = { superscript-right = ##1 } ,
     subscript-left   .meta:nn = {chemmacros/thermodynamics} { subscript-left = ##1 } ,
     subscript-right  .meta:nn = {chemmacros/thermodynamics} { subscript-right = ##1 } ,
        subscript         .meta:n     = { subscript-left = ##1 } ,
        subscript-pos     .choices:nn =
          { left , right }
          { \tl_set_eq:NN \l__chemmacros_state_sb_pos_tl \l_keys_choice_tl } ,
        symbol            .tl_set:N = \l__chemmacros_state_symbol_tl ,
        unit              .tl_set:N = \l__chemmacros_state_unit_tl
      }
    \DeclareDocumentCommand #1 { sO{}D(){}m }
      {
        \group_begin:
          \chemmacros_set_keys:xn
            {thermodynamics/\chemmacros_remove_backslash:N #1}
            {#2}
          \tl_if_blank:nF {##3}
            {
              \chemmacros_set_keys:nx {thermodynamics}
               { subscript-\l__chemmacros_state_sb_pos_tl = \exp_not:n {##3} }
            }
              \chemmacros_state:nV {##2} \l__chemmacros_state_symbol_tl
             \chemmacros_set_keys_groups:nnn {thermodynamics} {variables} {##2}
           \IfBooleanF {##1} {  = ~ \SI {##4} { \l__chemmacros_state_unit_tl } }
        \group_end:
      }
  }
```

The pre-existing macros are redefined with the new definition:

```
\RenewChemState \enthalpy { symbol = H , unit = \kilo\joule\per\mole }
\RenewChemState \entropy  { symbol = S , unit = \joule\per\kelvin\per\mole , pre = }
\RenewChemState \gibbs    { symbol = G , unit = \kilo\joule\per\mole }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

```
\ExplSyntaxOff
```

File 68 **lwarp-chemnum.sty**

§ 165 Package

chemnum

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemnum chemnum is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chemnum}[2016/04/14]

\ExplSyntaxOn

\cs_gset_protected:Npn \chemnum_compound_write:n #1
  {
    \chemnum_get_compound_property:nn {#1} {pre-main-label-code}
    \group_begin:
      \bool_if:NTF \l__chemnum_compound_local_bool
        { \l__chemnum_local_label_format_tl }
        { \chemnum_get_compound_property:nn {#1} {label-format} }
      {
        \LWR@textcurrentfont{
            \chemnum_get_compound_property:nn {#1} {counter-representation}
        }
      }
    \group_end:
    \chemnum_get_compound_property:nn {#1} {post-main-label-code}
  }

\cs_gset_protected:Npn \chemnum_subcompound_write:nn #1#2
  {
    \group_begin:
      \bool_if:NTF \l__chemnum_compound_local_bool
        { \l__chemnum_local_label_format_tl }
        { \chemnum_get_compound_property:nn {#1} {label-format} }
      {
        \LWR@textcurrentfont{
            \chemnum_get_subcompound_property:nnn {#1} {#2}
            {counter-representation}
        }
      }
    \group_end:
  }

\ExplSyntaxOff
```

File 69 **lwarp-chkfloat.sty**

§ 166 Package

chkfloat

Pkg chkfloat chkfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{chkfloat}[2012/08/19]
```

File 70 **lwarp-chngpage.sty**

§ 167 Package

chngpage

(*Emulates or patches code by* Peter Wilson.)

Pkg chngpage chngpage is emulated.

for HTML output: Discard all options for lwarp-chngpage:

```
\LWR@ProvidesPackageDrop{chngpage}[2009/10/20]
\LWR@origRequirePackage{lwarp-changepage}
```

File 71 **lwarp-cite.sty**

§ 168 Package

cite

(*Emulates or patches code by* Donald Arseneau.)

Pkg cite cite is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{cite}[2015/02/27]
```

For the [super] option, the `\kern` must be removed:

```
\def\LWRCT@biblabel#1{\@citess{#1}\kern-\labelsep\,}

\ifdefstrequal{\@biblabel}{\LWRCT@biblabel}
{
    \def\@biblabel#1{\@citess{#1}}
}{}
```

For the [super] option, `\textsuperscript` is used instead of math superscript:

```
\def\@citess#1{\textsuperscript{#1}}

\DeclareDocumentCommand\citepunct{}{,\,\relax}
```

File 72 **lwarp-CJK.sty**

§ 169 Package

CJK

Pkg CJK CJK does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJK}{ctex, xeCJK}
}

\LWR@ProvidesPackagePass{CJK}[2015/04/18]
```

File 73 **lwarp-CJKutf8.sty**

§ 170 Package

CJKutf8

Pkg CJKutf8 CJKutf8 does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJKutf8}{ctex, xeCJK}
}

\LWR@ProvidesPackagePass{CJKutf8}[2015/04/18]
```

File 74 **lwarp-clrdblpg.sty**

§ 171 Package

clrdblpg

Pkg clrdblpg clrdblpg is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{clrdblpg}[2018/04/21]
```

File 75 **lwarp-cmdtrack.sty**

§ 172 Package

cmdtrack

Pkg cmdtrack cmdtrack is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{cmdtrack}[2012/12/18]

\newcommand{\untrack}[1]{}
```

File 76 **lwarp-color.sty**

§ 173 Package

color

Pkg color

Allowed but ignored. xcolor is then required as well.

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

for HTML output:

```
\LWR@ProvidesPackageDrop{color}[2016/07/10]
\RequirePackage{xcolor}
```

File 77 **lwarp-colortbl.sty**

§ 174 Package

colortbl

Pkg colortbl

colortbl is used as-is for print output, and emulated for HTML.

⚠ row/cell color

Only use \rowcolor and \cellcolor at the start of a row, in that order.

colortbl ignores the overhang arguments.

for HTML output:

A placeholder definition is forgotten first:

```
\let\rowcolor\relax

\LWR@ProvidesPackagePass{colortbl}[2018/12/12]
```

The following \LWR@HTML versions are used inside an HTML tabular.

\columncolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

\LWR@getmynexttoken is not used here because \columncolor is not used inside the data area of the tabular.

```
\NewDocumentCommand{\LWR@HTML@columncolor}{O{named} m o o}{%
\convertcolorspec{#1}{#2}{HTML}\LWR@columnHTMLcolor%
\LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{columncolor}}
```

\LWR@getmynexttoken is used for \rowcolor because it is used inside the data area of the tabular.

\rowcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

```
\NewDocumentCommand{\LWR@HTML@rowcolor}{O{named} m o o}{%
```

```
\convertcolorspec{#1}{#2}{HTML}\LWR@rowHTMLcolor%
\LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{rowcolor}}
```

\cellcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

```
\NewDocumentCommand{\LWR@HTML@cellcolor}{O{named} m o o}{%
\convertcolorspec{#1}{#2}{HTML}\LWR@cellHTMLcolor%
\LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{cellcolor}}
```

\arrayrulecolor [⟨*model*⟩] {⟨*color*⟩}

The HTML version for use outside a tabular. Inside a tabular, \LWR@HTML@arrayrulecolornexttoken is used instead.

```
\newcommand{\LWR@HTML@arrayrulecolor}[2][named]{%
\convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolor}}
```

\LWR@arrayrulecolornexttoken [⟨*model*⟩] {⟨*color*⟩}

The HTML version for use inside a tabular.

```
\newcommand{\LWR@HTML@arrayrulecolornexttoken}[2][named]{%
\convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
\LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolornexttoken}}
```

\doublerulesepcolor [⟨*model*⟩] {⟨*color*⟩}

The version for use outside a tabular.

```
\newcommand{\LWR@HTML@doublerulesepcolor}[2][named]{}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolor}}
```

\LWR@doublerulesepcolornexttoken [⟨*model*⟩] {⟨*color*⟩}

The version for use inside a tabular.

```
\newcommand{\LWR@HTML@doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolornexttoken}}
```

File 78 **lwarp-continue.sty**

§ 175 Package

continue

Pkg continue

continue is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{continue}}[2018/12/09]

\newcommand*{\flagcont}{}
\newcommand*{\flagend}{}
\newcommand*{\flagword}{}
\newcommand*{\preflagword}{}
\newcommand*{\postflagword}{}
\newlength\contsep
\newlength\contdrop
```

File 79 **lwarp-copyrightbox.sty**

§ 176 Package

copyrightbox

(*Emulates or patches code by* Thomas Fischer, Ives van der Flaas.)

Pkg copyrightbox

copyrightbox is emulated for use by lwarp.

The entire copyright box is placed inside a of class copyrightbox.

The contents are placed inside a of class copyrightboxcontents.

The copyright notice is placed inside a of class copyrightboxnote.

for HTML output:

```
\LWR@ProvidesPackageDrop{copyrightbox}[2011/11/27]

\newcommand{\copyrightbox}[3][r]{%
\begin{BlockClass}[
    display: inline-flex;
    flex-direction: column ;
]{copyrightbox}
\begin{BlockClass}{copyrightboxcontents}
#2
\end{BlockClass}
\begin{BlockClass}{copyrightboxnote}
#3
\end{BlockClass}
\end{BlockClass}
}

\newcommand{\CRB@setcopyrightfont}{}
\newcommand{\CRB@setcopyrightparagraphstyle}{}
```

File 80 **lwarp-crop.sty**

§ 177 Package

crop

(*Emulates or patches code by* Melchior FRANZ.)

Pkg crop Emulated.

for HTML output: Discard all options for lwarp-crop:

```
\LWR@ProvidesPackageDrop{crop}[2003/05/20]
```

```
\newcommand*{\crop}[1][]{}
\newcommand*{\cropdef}[6][]{}
```

File 81 **lwarp-ctable.sty**

§ 178 Package

ctable

(*Emulates or patches code by* Wybo Dekker.)

Pkg ctable ctable is patched for use by lwarp.

⚠ Misplaced alignment tab character & Use `\StartDefiningTabulars` before one or more `\ctables`, and `\StopDefiningTabulars` after. These change the meaning of the ampersand & character.

for HTML output:

```
\LWR@ProvidesPackagePass{ctable}[2015/10/17]
```

The following is in the original:

```
\newcommand{\LWR@HTML@ctable}[4][]{%
   \let\@CTtaborfig  \@dfltCTtaborfig
   \let\@CTalign     \@dfltCTalign
   \let\@CTsideways  \@dfltCTsideways
   \let\@CTcontinued \empty
   \let\@CTpos       \@dfltCTpos
   \let\@CTcaption   \empty
   \let\@CTcap       \undefined
   \let\@CTlabel     \empty
   \let\@CTbotcap    \@dfltCTbotcap
   \let\@CTstarred   \@dfltCTstarred
   \let\@CTsuper     \@dfltCTsuper
   \let\@CTnotespar  \@dfltCTnotespar
   \let\@CTdoinside  \@dfltCTdoinside
   \let\@CTbgopacity \@dfltCTbgopacity
   \@CTframerule     \@dfltCTframerule
   \@CTcaptionskip   \@dfltCTcaptionskip
   \@CTframesep      \@dfltCTframesep
```

```
\@CTwidth         \@dfltCTwidth
\@CTmaxwidth      \@dfltCTmaxwidth
\@CTmincapwidth   \@dfltCTmincapwidth
\@CTfooterwidth   \@dfltCTfooterwidth
\def\@CTfgactual {@dfltCTframefg}%
\def\@CTbgactual {@dfltCTframebg}%
\def\@CTbeg      {\begin{\@CTsideways\@CTtaborfig\@CTstarred}}%
\def\@CTbegin    {\@CTbeg}%
\def\@CTend      {\end{\@CTsideways\@CTtaborfig\@CTstarred}}%
\setkeys{CT}{#1}%
\ifx\@CTcap\undefined\let\@CTcap\@CTcaption\fi
\ifx\@CTcap\empty
  \if@CTcaptionloaded\else
    \PackageWarningNoLine{ctable}{\MessageBreak
       An empty cap= option prevents lot/loc entry only\MessageBreak
       if the caption package is loaded!}
  \fi
\fi
\if@CTinmemoir\else
   \ifx\@CTbotcap\undefined
      \PackageError{ctable}{\MessageBreak
         You can, currently, use the sidecap option only with\MessageBreak
         memoir documents. Use topcap or botcap only}
   \fi
\fi
\ifdim\@CTwidth=0pt\else
   \ifdim\@CTmaxwidth=0pt\else
      \PackageError{ctable}{\MessageBreak
        You may not use the width and maxwidth options together\MessageBreak
         Use either width or maxwidth}
   \fi
\fi
\ifx\@CTpos\empty
   \ifx\@CTsideways\empty\else
   \PackageError{ctable}{\MessageBreak
      You may not use the pos and sideways options together\MessageBreak
      Rotated tables and figures are always typeset on a separate page}
   \fi
\fi
\ifx\@CTcaption\empty
   \ifx\@CTlabel\empty\else
      \PackageError{ctable}{\MessageBreak
         You may not label a captionless table\MessageBreak
         Such a label can't be referenced}
   \fi
\fi
```

Some of the original, regarding computing the width of `\CT@t`, is removed here.

```
\@CTbegin
   \ifx\@CTcontinued\empty\else\addtocounter{\@CTtaborfig}{-1}\fi
   \@CTalign
```

lwarp's patches begin here:

```
    \begin{center}
        \setlength{\fboxrule}{\@CTframerule}
        \setlength{\fboxsep}{\@CTframesep}
        \LWR@forceminwidth{\fboxrule}%  lwarp
        \convertcolorspec{named}{\@CTbgactual}{HTML}\LWR@tempcolor% lwarp
        \begin{BlockClass}[%                            lwarp
            border:
                \LWR@printlength{\LWR@atleastonept}
                solid
                \LWR@colorstyle{named}{\@CTfgactual} ; %
            padding:\LWR@printlength{\fboxsep} ; %
            \ifdefstring{\LWR@tempcolor}{FFFFFF}{}{%
                background: \LWR@colorstyle{named}{\@CTbgactual} ; %
            }%
        ]{fminipage}%       lwarp
         \ifx\@CTbotcap\@CTfalse\@CTCaption\vskip\@CTcaptionskip\fi
         \ifx\@CTbotcap\undefined%
             \begin{sidecaption}[\@CTcap]{\@CTcaption}[\@CTlabel]
         \fi
         \@CTdoinside
         \begin{tabularx}{\linewidth}{#2}%      lwarp
            #4%
         \end{tabularx}%                    lwarp
         \def\@CTfootnotes{#3}%
         \ifx#3\empty\else{% append footnotes, if any
            \begin{BlockClass}{tnotes}%     lwarp
            #3
            \end{BlockClass}%               lwarp
         }
         \fi
         \ifx\@CTbotcap\undefined\end{sidecaption}\fi
         \ifx\@CTbotcap\@CTtrue\vskip\@CTcaptionskip\@CTCaption\fi
        \end{BlockClass}
     \end{center}
    \@CTend
}
\LWR@formatted{ctable}
```

Required to properly detect the toprule:

```
\LetLtxMacro\FL\toprule
```

Table notes are redefined for HTML:

```
\newcommand{\LWR@HTML@tmark}[1][a]{%
   \textsuperscript{\textrm{\textit{#1}}}
}
\LWR@formatted{tmark}

\newcommand{\LWR@HTML@tnote}[2][a]{%
    \tmark[#1]\,#2\par
}
\LWR@formatted{tnote}
```

File 82 **lwarp-cuted.sty**

§ 179 Package

cuted

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg cuted cuted is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{cuted}[2012/10/04]

\newenvironment{strip}{}{}
\newskip\stripsep
\def\oldcolsbreak#1{}
```

File 83 **lwarp-cutwin.sty**

§ 180 Package

cutwin

(*Emulates or patches code by* Peter Wilson and Alan Hoenig.)

Pkg cutwin Emulated.

for HTML output: Discard all options for lwarp-cutwin:

```
\LWR@ProvidesPackageDrop{cutwin}[2010/09/29]

\newcommand*{\opencutleft}{}
\newcommand*{\opencutright}{}
\newcommand*{\opencutcenter}{}
\newcommand*{\cutfuzz}{}

\newenvironment{cutout}[4]
{\marginpar{\windowpagestuff}}
{}

\newcommand*{\windowpagestuff}{}

\newcommand*{\pageinwindow}{%
% \begin{minipage}{.3\linewidth}
\windowpagestuff
% \end{minipage}
}

\newenvironment{shapedcutout}[3]
{\marginpar{\picinwindow}}
{}

\newcommand*{\putstuffinpic}{}
```

```

\newcommand*{\picinwindow}{%
\begin{picture}(0,0)
\putstuffinpic
\end{picture}}
```

File 84 **lwarp-dblfloatfix.sty**

§ 181 Package dblfloatfix

Pkg dblfloatfix dblfloatfix is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{dblfloatfix}[2012/12/31]
```

File 85 **lwarp-dblfnote.sty**

§ 182 Package dblfnote

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg dblfnote dblfnote is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{dblfnote}[1999/07/14]

\newcounter{DFNsloppiness}
\newdimen\DFNcolumnsep
\newdimen\DFNcolumnwidth
\def\DFNallowcbreak{}
\def\DFNinhibitcbreak{}
\def\DFNtrysingle{}
\def\DFNalwaysdouble{}
\def\DFNruleboth{}
\def\DFNruleleft{}
```

File 86 **lwarp-dcolumn.sty**

§ 183 Package dcolumn

Pkg dcolumn dcolumn is emulated by the lwarp core.

```
\LWR@ProvidesPackageDrop{dcolumn}[2014/10/28]
```

File 87 **lwarp-diagbox.sty**

§ 184 Package

diagbox

(*Emulates or patches code by* Leo Liu.)

Pkg diagbox

diagbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{diagbox}[2016/12/28]
```

To restore print-mode inside a `lateximage`:

```
\LetLtxMacro\LWR@origdiagbox@double\diagbox@double
\LetLtxMacro\LWR@origdiagbox@triple\diagbox@triple

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\diagbox@double\LWR@origdiagbox@double%
\LetLtxMacro\diagbox@triple\LWR@origdiagbox@triple%
}
```

`\LWR@diagbox@AB` {⟨*E/W*⟩} {⟨*A*⟩} {⟨*E/W*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagbox@AB}[4]{
\begingroup%
\LetLtxMacro\\\newline%
\BlockClassSingle{diagbox#1}{#2}%
\BlockClassSingle{diagbox#3}{#4}%
\endgroup%
\LWR@stoppars%
}
```

`\LWR@diagboxNW` {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxNW}[2]{%
\LWR@diagbox@AB{E}{#2}{W}{#1}%
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxNE}[2]{%
\LWR@diagbox@AB{W}{#1}{E}{#2}%
}

\let\LWR@diagboxSW\LWR@diagboxNE
\let\LWR@diagboxSE\LWR@diagboxNW
```

`\diagbox@double` {⟨*keys*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\def\diagbox@double#1#2#3{%
\setkeys{diagbox}{dir=NW,#1}%
```

```
\@nameuse{LWR@diagbox\diagbox@dir}{#2}{#3}%
}
```

\LWR@diagboxTNW {⟨*title*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxTNW}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNW{#2}{#3}
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxTNE}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNE{#2}{#3}
}

\newcommand{\LWR@diagboxTSW}[3]{%
\LWR@diagboxSW{#2}{#3}
\BlockClassSingle{diagboxtitleS}{#1}
\LWR@stoppars%
}

\newcommand{\LWR@diagboxTSE}[3]{%
\LWR@diagboxSE{#2}{#3}
\BlockClassSingle{diagboxtitleS}{#1}
\LWR@stoppars%
}
```

\diagbox@triple {⟨*keys*⟩} {⟨*A*⟩} {⟨*T*⟩} {⟨*B*⟩}

```
\def\diagbox@triple#1#2#3#4{%
\setkeys{diagbox}{dir=NW,#1}%
\@nameuse{LWR@diagboxT\diagbox@dir}{#3}{#2}{#4}%
}
```

File 88 **lwarp-dingbat.sty**

§ 185 Package dingbat

(*Emulates or patches code by* Scott Pakin.)

Pkg dingbat dingbat is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{dingbat}[2001/04/27]
```

```
\newcommand*{\LWR@dingbatsymbol}[1]{\HTMLunicode{#1}}

\newcommand{\LWR@HTML@rightpointright}{\LWR@dingbatsymbol{261E}}
\newcommand{\LWR@HTML@leftpointright}{\LWR@dingbatsymbol{261E}}
\newcommand{\LWR@HTML@leftthumbsdown}{\LWR@dingbatsymbol{1F44E}}
\newcommand{\LWR@HTML@leftthumbsup}{\LWR@dingbatsymbol{1F44D}}
```

```
\newcommand{\LWR@HTML@rightpointleft}{\LWR@dingbatsymbol{261C}}
\newcommand{\LWR@HTML@rightthumbsdown}{\LWR@dingbatsymbol{1F44E}}
\newcommand{\LWR@HTML@rightthumbsup}{\LWR@dingbatsymbol{1F44D}}
\newcommand{\LWR@HTML@squarewithdots}{\LWR@dingbatsymbol{25C7}}
\newcommand{\LWR@HTML@filledsquarewithdots}{\LWR@dingbatsymbol{25C6}}
\newcommand{\LWR@HTML@Sborder}{\LWR@dingbatsymbol{271A}}
\newcommand{\LWR@HTML@Zborder}{\LWR@dingbatsymbol{274B}}
\newcommand{\LWR@HTML@largepencil}{\LWR@dingbatsymbol{270E}}
\newcommand{\LWR@HTML@anchor}{\LWR@dingbatsymbol{2693}}
\newcommand{\LWR@HTML@carriagereturn}{\LWR@dingbatsymbol{23CE}}
\newcommand{\LWR@HTML@checkmark}{\LWR@dingbatsymbol{2713}}
\newcommand{\LWR@HTML@eye}{\LWR@dingbatsymbol{1F441}}
\newcommand{\LWR@HTML@satellitedish}{\LWR@dingbatsymbol{1F4E1}}
\newcommand{\LWR@HTML@smallpencil}{\LWR@dingbatsymbol{270E}}

\LWR@formatted{rightpointright}
\LWR@formatted{leftpointright}
\LWR@formatted{leftthumbsdown}
\LWR@formatted{leftthumbsup}
\LWR@formatted{rightpointleft}
\LWR@formatted{rightthumbsdown}
\LWR@formatted{rightthumbsup}
\LWR@formatted{squarewithdots}
\LWR@formatted{filledsquarewithdots}
\LWR@formatted{Sborder}
\LWR@formatted{Zborder}
\LWR@formatted{largepencil}
\LWR@formatted{anchor}
\LWR@formatted{carriagereturn}
\LWR@formatted{checkmark}
\LWR@formatted{eye}
\LWR@formatted{satellitedish}
\LWR@formatted{smallpencil}
```

File 89 **lwarp-dprogress.sty**

§ 186 Package dprogress

Pkg dprogress dprogress is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{dprogress}[2008/02/21]
```

File 90 **lwarp-draftcopy.sty**

§ 187 Package draftcopy

Pkg draftcopy draftcopy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftcopy}[2002/02/25]
```

```
\newcommand{\draftcopyVersion}[1]{}
\newcommand{\draftcopySetGrey}[1]{}
\newcommand{\draftcopySetScale}[1]{}
\newcommand{\draftcopySetScaleFactor}[1]{}
\newcommand{\draftcopyFirstPage}[1]{}
\newcommand{\draftcopyLastPage}[1]{}
\newcommand{\draftcopyName}[2]{}
\newcommand{\draftcopyPageTransform}[1]{}
\newcommand{\draftcopyBottomTransform}[1]{}
\newcommand{\draftcopyPageX}[1]{}
\newcommand{\draftcopyPageY}[1]{}
\newcommand{\draftcopyBottomX}[1]{}
\newcommand{\draftcopyBottomY}[1]{}
```

File 91 **lwarp-draftfigure.sty**

§ 188 Package draftfigure

Pkg draftfigure draftfigure is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftfigure}[2017/07/19]
\RequirePackage{xkeyval}

\define@key{draftfigure}{code}{}
\define@key{draftfigure}{noframe}[true]{}
\define@key{draftfigure}{filename}[true]{}
\define@key{draftfigure}{content}[]{}
\define@key{draftfigure}{style}[normal]{}
\define@key{draftfigure}{position}[left]{}
\define@key{draftfigure}{size}[normal]{}
\newcommand\setdf[1]{\setkeys{draftfigure}{#1}}
```

File 92 **lwarp-draftwatermark.sty**

§ 189 Package draftwatermark

(*Emulates or patches code by* Sergio Callegari.)

Pkg draftwatermark draftwatermark is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftwatermark}[2015/02/19]

\newcommand{\SetWatermarkAngle}[1]{}
\newcommand{\SetWatermarkColor}[1]{}
\newcommand{\SetWatermarkLightness}[1]{}
\newcommand{\SetWatermarkFontSize}[1]{}
\newcommand{\SetWatermarkScale}[1]{}
\newcommand{\SetWatermarkHorCenter}[1]{}
\newcommand{\SetWatermarkVertCenter}[1]{}
\newcommand{\SetWatermarkText}[1]{}
```

File 93 **lwarp-easy-todo.sty**

§ 190 Package

easy-todo

(*Emulates or patches code by* Juan Rada-Vilela.)

Pkg easy-todo easy-todo is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{easy-todo}[2014/01/01]
```

\listoftodos Modified to correct buggy use of \flushright.

```
\let\LWR@origlistoftodos\listoftodos

\renewcommand{\listoftodos}{%
\begingroup
\renewcommand{\flushright}{}
\LWR@origlistoftodos
\endgroup
}
```

\todoii Modified to use \textcolor instead of \color.

```
\renewcommand{\todoii}[2]{%
\ifthenelse{\equal{\@todoobeyfinal}{true}}%
    {%
        \ifoptionfinal{\todoenable{false}}{\todoenable{true}}%
    }%
    {}%
\ifthenelse{\equal{\@todoenable}{true}}%
    {%
        \refstepcounter{todos}%
        \noindent{%
            \todocolor%
            \LWR@textcurrentcolor{%
                \normalfont\scriptsize{\bfseries{\thetodos.#1}}%
            }%
        }%
        \addcontentsline{lod}{todos}{\protect{\thetodos. }\LWR@isolate{#2}}%
    }%
    {}%
}
```

File 94 **lwarp-ebook.sty**

§ 191 Package

ebook

(*Emulates or patches code by* Jørgen Steensgaard.)

Pkg ebook ebook is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{ebook}

\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}

\providecommand{\pagefill}[1][0.001mm]{\noindent}

\providecommand{\ebook}{
\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}
}
```

File 95 **lwarp-ed.sty**

§ 192 Package

ed

(*Emulates or patches code by* Michael Kohlhase.)

Pkg ed ed is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ed}[2012/01/29]
```

Bugs:

1. `todolist` fails with the `hide` option, as does `\edexplanation`.
2. `\edstubURI` is actually `\edstuURI`.

```
\RequirePackage{xcolor}

\renewenvironment{edstub}[2][The following blue text]
{%
    \def\@test{#1}%
    \begin{center}%
        \huge%
        \textcolor{red}{%
            #1 is only a provisional stub\\\Large
            the Office document
            \ifx\ed@stubURI\@empty{#2}\else\href{\ed@stubURI}{#2}\fi\
            contains more text\\which will be merged for the final document%
        }%
    \end{center}%
    \BlockClass[color:blue]{edstub}%
}
{\endBlockClass}
```

File 96 **lwarp-ellipsis.sty**

§ 193 Package ellipsis

(*Emulates or patches code by* Peter J. Heslin.)

Pkg ellipsis ellipsis is emulated.

```
\LWR@ProvidesPackageDrop{ellipsis}[2004/09/28]

\newcommand{\ellipsisgap}{0.1em}

\newcommand*{\midwordellipsis}{\,\textellipsis\,}
```

File 97 **lwarp-embrac.sty**

§ 194 Package embrac

(*Emulates or patches code by* Clemens Niederberger.)

Pkg embrac embrac is nullfied for HTML and used as-is for print.

for HTML output:

```
\LWR@ProvidesPackagePass{embrac}[2017/07/04]

\LetLtxMacro\LWR@orig@HTML@emph\LWR@HTML@emph
\RenewDocumentCommand{\LWR@HTML@emph}{s m}{\LWR@orig@HTML@emph{#2}}

\LetLtxMacro\LWR@orig@HTML@textit\LWR@HTML@textit
\RenewDocumentCommand{\LWR@HTML@textit}{s m}{\LWR@orig@HTML@textit{#2}}

\LetLtxMacro\LWR@orig@HTML@textsl\LWR@HTML@textsl
\RenewDocumentCommand{\LWR@HTML@textsl}{s m}{\LWR@orig@HTML@textsl{#2}}

\ifxetexorluatex
    \LetLtxMacro\LWR@orig@HTML@textsi\LWR@HTML@textsi
    \RenewDocumentCommand{\LWR@HTML@textsi}{s m}{%
    \LWR@orig@HTML@textsi{#2}}
\fi

\AtBeginDocument{
    \LWR@formatted{emph}
    \LWR@formatted{textit}
    \LWR@formatted{textsl}
    \ifxetexorluatex
        \LWR@formatted{textsi}
    \fi
}

```

```
\newcommand{\LWR@HTML@EmbracOff}{}
\LWR@formatted{EmbracOff}

\newcommand{\LWR@HTML@EmbracOn}{}
\LWR@formatted{EmbracOn}
```

File 98 **lwarp-emptypage.sty**

§ 195 Package

emptypage

Pkg emptypage

emptypage is ignored.

for HTML output: Discard all options for lwarp-emptypage:

```
\LWR@ProvidesPackageDrop{emptypage}[2010/05/30]
```

File 99 **lwarp-endfloat.sty**

§ 196 Package

endfloat

Pkg endfloat

endfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endfloat}[2018/03/24]

\newcommand\figureplace{}
\newcommand\tableplace{}
\newcommand\floatplace[1]{}
\newcounter{posttable}
\newcounter{postfigure}
\newcommand*{\theposttbl}{}
\newcommand*{\thepostfig}{}
\newcommand{\AtBeginFigures}[1]{}
\newcommand{\AtBeginTables}[1]{}
\newcommand{\AtBeginDelayedFloats}[1]{}
\newcommand*{\processdelayedfloats}{}
\newcommand*{\efloatseparator}{}
\def\efloattype{}
\providecommand\efloatheading[1]{}
\providecommand\efloatpreamble{}
\providecommand\efloatpostamble{}
```

File 100 **lwarp-endheads.sty**

§ 197 Package

endheads

Pkg endheads

endheads is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endheads}[2017/04/06]
```

```
\newcommand{\changesinglepageabbrev}[1]{}
\newcommand{\changemultiplepageabbrev}[1]{}
\newcommand{\changenotesname}[1]{}
\newcommand{\changenotesheader}[1]{}
\newcommand{\changenotescontentsname}[1]{}
\newcommand{\changechapternotesline}[1]{}
\newcommand{\checknoteheaders}{}
\newif\ifnotesincontentson \notesincontentsonfalse
\newcommand{\notesincontents}{\notesincontentsontrue}
\newif\ifendnoteheaderson \endnoteheadersonfalse
\newcommand{\setupendnoteheaders}{%
    \endnoteheadersontrue%
}
\newif\iftitleinnotes \titleinnotestrue
\newcommand{\styleforchapternotebegin}{}
\newcommand{\styleforchapternoteend}{}
\newcommand{\setstyleforchapternotebegin}[1]{%
    \renewcommand{\styleforchapternotebegin}{#1}%
}
\newcommand{\setstyleforchapternoteend}[1]{%
    \renewcommand{\styleforchapternoteend}{#1}%
}
\newcommand{\resetendnotes}{}
\newif\ifnotesbychapteron \notesbychapteronfalse
\newcommand{\notesbychapter}{\notesbychapterontrue}
```

File 101 **lwarp-endnotes.sty**

§ 198 Package

endnotes

(*Emulates or patches code by* John Lavagnino.)

Pkg endnotes

Used as-is.

table of contents

To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

HTML page

To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

for HTML output:

```
\LWR@ProvidesPackagePass{endnotes}
```

```
\def\enoteformat{%
% \rightskip\z@ \leftskip\z@ \parindent=1.8em
\leavevmode
% \llap{
\makeenmark
```

```
% }
}

\def\@makeenmark{\hbox{\LWR@htmlspan{sup}{\normalfont\theenmark}}}
\def\makeenmark{\@makeenmark}
```

File 102 **lwarp-enumerate.sty**

§ 199 Package enumerate

Pkg enumerate

enumerate is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by lwarp and thus must no longer be dropped.

for HTML output:

```
\LWR@ProvidesPackagePass{enumerate}[2015/07/23]
```

File 103 **lwarp-enumitem.sty**

§ 200 Package enumitem

(*Emulates or patches code by* Javier Bezos.)

Pkg enumitem

enumitem is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{enumitem}[2018/11/30]
```

for HTML output:

```
\begin{warpHTML}
```

\newlist {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}
\renewlist {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}

For enumitem lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

```
\let\LWR@enumitem@orignewlist\newlist

\renewcommand*{\newlist}[3]{%
\LWR@enumitem@orignewlist{#1}{#2}{#3}%
\AtBeginEnvironment{#1}{\@nameuse{LWR@#2start}}%
\AtEndEnvironment{#1}{\@nameuse{LWR@#2end}}%
}

\def\DrawEnumitemLabel{}
```

```
\end{warpHTML}
```

File 104 **lwarp-epigraph.sty**

§ 201 Package

epigraph

(*Emulates or patches code by* Peter Wilson.)

Pkg epigraph epigraph is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{epigraph}[2009/09/02]
```

```
\DeclareDocumentCommand{\qitem}{m m}
{
\begin{BlockClass}{qitem}
#1
\ifbool{FormatWP}
{\begin{BlockClass}[border-top:1px solid gray]{epigraphsource}}
{\begin{BlockClass}{epigraphsource}}
#2
\end{BlockClass}
\end{BlockClass}
}
```

```
\DeclareDocumentCommand{\epigraph}{m m}
{
\begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{epigraph}
\qitem{#1}{#2}
\end{LWR@BlockClassWP}
}

\DeclareDocumentEnvironment{epigraphs}{}
{\LWR@BlockClassWP{\LWR@print@mbox{text-align:right}}{}{epigraph}}
{\endLWR@BlockClassWP}
```

Use css to format epigraphs.

The following are null commands for source compatibility:

```
\newenvironment*{flushepinormal}{}{}
```

```
\@ifclassloaded{memoir}{
\setlength{\epigraphwidth}{.5\linewidth}
\renewcommand{\textflush}{flushepinormal}
\renewcommand{\epigraphhead}[2][0]{#2}
\renewcommand{\dropchapter}[1]{}
\renewcommand*{\undodrop}{}
}{% not memoir
\newlength{\epigraphwidth}
\setlength{\epigraphwidth}{.5\linewidth}
\newcommand{\textflush}{flushepinormal}
\newcommand{\epigraphflush}{flushright}
```

```
\newcommand{\sourceflush}{flushright}
\newcommand*{\epigraphsize}{\small}
\newlength{\epigraphrule}
\newlength{\beforeepigraphskip}
\newlength{\afterepigraphskip}
\newcommand{\epigraphhead}[2][0]{#2}
\newcommand{\dropchapter}[1]{}
\newcommand*{\undodrop}{}
}% not memoir

\let\cleartoevenpage\relax% also in nextpage
\newcommand{\cleartoevenpage}[1][]{}
```

File 105 **lwarp-epsfig.sty**

§ 202 Package

epsfig

Pkg epsfig epsfig is emulated for use by lwarp.

⚠ Only the LaTeX2e syntax is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{epsfig}[2017/06/25]
```

A few additional keys to capture the filename:

```
\RequirePackage{graphics}

\define@key{igraph}{file}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{figure}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{prolog}{}

\define@key{igraph}{silent}[]{}
```

The captured filename is used as the argument to `\includegraphics`:

```
\newcommand{\epsfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}

\newcommand{\psfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
```

File 106 **lwarp-epstopdf.sty**

§ 203 Package

epstopdf

Pkg epstopdf Previous versions of lwarp had a nullfied version, but now epstopdf-base is supported.

lwarp-epstopdf becomes a placeholder to overwrite previous versions.

See package epstopdf-base for details.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf}[2016/05/15]
```

File 107 **lwarp-epstopdf-base.sty**

§ 204 Package

epstopdf-base

Pkg epstopdf-base

⚠ convert to .svg

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf-base}[2016/05/15]
```

Redefine to remember the image filename, replacing .pdf with .svg. Use the epstopdf print version inside a lateximage.

```
\newcommand*{\LWR@HTML@ETE@OrgGin@setfile}[3]{%
    \edef\LWR@tempone{#3}%
    \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
    \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
    \xdef\LWR@parsedfilename{\LWR@tempone}%
}

\LWR@formatted{ETE@OrgGin@setfile}
```

\includegraphics in HTML mode redefines \Gin@setfile to be \LWR@HTML@Gin@setfile, which is now redirected to epstopdf's version:

```
\renewcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \ETE@Gin@setfile{#1}{#2}{#3}%
}
```

Allow .eps images to be found if a suffix is not provided:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{%
    .eps,.EPS,.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Likewise when inside a lateximage:

```
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{%
    .eps,.EPS,.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}%
}
```

File 108 **lwarp-eqlist.sty**

§ 205 Package

eqlist

Pkg eqlist eqlist is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{eqlist}[2002/08/15]
```

```
\newenvironment{eqlist}[1][]{\description}{\enddescription}
\newenvironment{eqlist*}[1][]{\description}{\enddescription}
\newenvironment{Eqlist}[2][]{\description}{\enddescription}
\newenvironment{Eqlist*}[2][]{\description}{\enddescription}
\newcommand*{\longitem}[1][]{\item[#1]}
\newcommand*{\eqlistinit}{}
\newcommand*{\eqliststarinit}{}
\newcommand*{\eqlistinitpar}{}
\def\eqlistlabel#1{#1}
\newcommand{\eqlistauto}[1]{}
\newcommand{\eqlistnoauto}{}
```

File 109 **lwarp-eqparbox.sty**

§ 206 Package

eqparbox

(*Emulates or patches code by* Scott Pakin.)

Pkg eqparbox eqparbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{eqparbox}[2017/09/03]
```

```
\NewDocumentCommand{\LWR@HTML@eqparbox}{O{t} O{} O{t} m +m}{%
    {%
        \minipagefullwidth%
        \parbox[#1][#2][#3]{\linewidth}{#5}%
    }%
}
\LWR@formatted{eqparbox}

\NewDocumentCommand{\LWR@HTML@eqmakebox}{o o m}{%
    \makebox[#2]{#3}%
}
\LWR@formatted{eqmakebox}

\NewDocumentCommand{\LWR@HTML@eqframebox}{o o m}{%
```

```
    \framebox[#2]{#3}%
}
\LWR@formatted{eqframebox}

\NewDocumentEnvironment{LWR@HTML@eqminipage}{O{t} O{} O{t} m}
{%
    \begingroup%
    \minipagefullwidth%
    \minipage[#1][#2][#3]{\linewidth}%
}%
{%
    \endminipage%
    \endgroup%
}

\newcommand*{\LWR@HTML@eqboxwidth}[1]{.25\linewidth}
\LWR@formatted{eqboxwidth}

\newcommand*{\LWR@HTML@eqsetminwidth}[2]{}
\newcommand*{\LWR@HTML@eqsetmaxwidth}[2]{}

\newcommand*{\LWR@HTML@eqsetminwidthto}[2]{}
\newcommand*{\LWR@HTML@eqsetmaxwidthto}[2]{}
```

File 110 **lwarp-errata.sty**

§ 207 Package

errata

(*Emulates or patches code by* Michael Kohlhase.)

Pkg errata

errata is patched for use by lwarp.

This is for v0.3 of errata. A newer version of errata with more features is under development, at which time the lwarp version will have to be updated.

for HTML output:

Macros are being defined with the math dollar, so enable the HTML version during package loading:

```
\StartDefiningMath
```

Now load the package:

```
\LWR@ProvidesPackagePass{errata}[2006/11/12]
```

Patches for dynamic inline math:

```
\xpatchcmd{\erratumAdd}
    {$_a^{\arabic{erratum}}$}
%     {\inlinemathother$_a^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{a}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumAdd}}

```

```
\xpatchcmd{\erratumDelete}
    {$_d^{\arabic{erratum}}$}
%     {\inlinemathother$_d^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratumReplace}
    {$_r^{\arabic{erratum}}$}
%     {\inlinemathother$_r^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumReplace}}

\xpatchcmd{\erratum}
    {$_a$}
%     {\inlinemathother$_a$\inlinemathnormal}
    {\textsubscript{a}}
    {}
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratum}
    {$_d^{\@thefnmark}$}
%     {\inlinemathother$_d^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eDelete}}

\xpatchcmd{\erratum}
    {$_r^{\@thefnmark}$}
%     {\inlinemathother$_r^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eReplace}}
```

Finish the current page's errata before closing and reloading the list:

```
\preto\PrintErrata{\LWR@orignewpage}
```

No longer defining math macros with the HTML $:

```
\StopDefiningMath
```

File 111 **lwarp-eso-pic.sty**

§ 208 Package

eso-pic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg eso-pic eso-pic is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{eso-pic}[2018/04/12]
```

```
\newcommand*{\LenToUnit}{}
\newcommand{\AtPageUpperLeft}[1]{}
\newcommand{\AtPageLowerLeft}[1]{}
\newcommand{\AtPageCenter}[1]{}
\newcommand{\AtStockLowerLeft}[1]{}
\newcommand{\AtStockUpperLeft}[1]{}
\newcommand{\AtStockCenter}[1]{}
\newcommand{\AtTextUpperLeft}[1]{}
\newcommand{\AtTextLowerLeft}[1]{}
\newcommand{\AtTextCenter}[1]{}
\NewDocumentCommand{\AddToShipoutPictureBG}{s +m}{}
```

```
\newcommand{\AddToShipoutPicture}{\AddToShipoutPictureBG}
\NewDocumentCommand{\AddToShipoutPictureFG}{s +m}{}
\newcommand*{\ClearShipoutPictureBG}{}
\newcommand*{\ClearShipoutPicture}{}
\newcommand*{\ClearShipoutPictureFG}{}
\newcommand{\gridSetup}[6][]{}
```

File 112 **lwarp-eurosym.sty**

§ 209 Package eurosym

(*Emulates or patches code by* Henrik Theiling.)

Pkg eurosym eurosym is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{eurosym}[1998/08/06]
```

```
\renewrobustcmd\officialeuro{\HTMLentity{euro}}
\let\geneuro\officialeuro
\let\geneuronarrow\officialeuro
\let\geneurowide\officialeuro
\let\euro\officialeuro
\renewrobustcmd\eurobars{}
\renewrobustcmd\eurobarsnarrow{}
\renewrobustcmd\eurobarswide{}
```

File 113 **lwarp-everypage.sty**

§ 210 Package everypage

(*Emulates or patches code by* Sergio Callegari.)

Pkg everypage everypage is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{everypage}[2007/06/20]
```

```
\newcommand*{\AddEverypageHook}[1]{}
\newcommand*{\AddThispageHook}[1]{}
```

File 114 **lwarp-everyshi.sty**

§ 211 Package everyshi

(*Emulates or patches code by* Martin Schröder.)

Pkg everyshi Emulated.

for HTML output: Discard all options for lwarp-everyshi:

```
\LWR@ProvidesPackageDrop{everyshi}[2001/05/15]

\newcommand*{\EveryShipout}[1]{}
\newcommand*{\AtNextShipout}[1]{}
```

File 115 **lwarp-extramarks.sty**

§ 212 Package extramarks

(*Emulates or patches code by* Piet van Oostrum.)

Pkg extramarks extramarks is emulated.

for HTML output: Discard all options for lwarp-extramarks:

```
\LWR@ProvidesPackageDrop{extramarks}[2019/01/31]

\newcommand*{\extramarks}[2]{}
\newcommand*{\firstleftxmark}{}
\newcommand*{\lastleftxmark}{}
\newcommand*{\firstrightxmark}{}
\newcommand*{\lastrightxmark}{}
\newcommand*{\firstxmark}{}
\newcommand*{\lastxmark}{}
\newcommand*{\topxmark}{}
\newcommand*{\topleftxmark}{}
\newcommand*{\toprightxmark}{}
\newcommand*{\firstleftmark}{}
\newcommand*{\lastrightmark}{}
\newcommand*{\firstrightmark}{}
\newcommand*{\lastleftmark}{}
```

File 116 **lwarp-fancybox.sty**

§ 213 Package fancybox

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancybox

fancybox is supported with some patches.

framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives

\fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example

The fancybox documentation's example framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method loses HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim

lwarp does not support the verbatim environment inside a span, box, or fancybox's \Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \beginVerbatim
}{
  \endVerbatim
  \endfminipage
}
```

framed \VerbBox

fancybox's \VerbBox may be used inside \fbox.

indented alignment

LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

fancybox, fancyvrb
⚠ \VerbatimFootnotes
⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\LWR@ProvidesPackagePass{fancybox}[2010/05/15]
```

After the preamble is loaded, after any patches to Verbatim:

```
\AfterEndPreamble{
\LWR@traceinfo{Patching fancybox.}
```

\VerbatimFootnotes

Patched to use the new version.

```
\def\VerbatimFootnotes{%
\let\@footnotetext\V@footnotetext%
\let\LWR@footnotetext\V@footnotetext% lwarp
}
```

\V@@footnotetext

Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@@footnotetext.

```
\def\V@@footnotetext{%
\LWR@traceinfo{V@footnotetext}%
\global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
    \unvbox\LWR@footnotebox%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Use HTML superscripts in the footnote even inside a lateximage:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{}%
  \bgroup%
  \aftergroup{\V@@@footnotetext}%
  \ignorespaces%
}%

}% AfterEndPreamble

\renewcommand*{\@shadowbox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black]{shadowbox}{#1}}%
{\InlineClass{shadowbox}{#1}}%
}

\renewcommand*{\@doublebox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px double black]{doublebox}{#1}}%
{\InlineClass{doublebox}{#1}}%
}

\renewcommand*{\@ovalbox}[2]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black; border-radius:1ex]{ovalbox}{#2}}%
{%
    \ifthenelse{\isequivalentto{#1}{\thinlines}}%
        {\InlineClass{ovalbox}{#2}}%
        {\InlineClass{Ovalbox}{#2}}%
}%
}
```

Convert minipages, parboxes, and lists into linear text using the `LWR@nestspan` environment:

```
\let\LWR@origSbox\Sbox

\def\Sbox{\LWR@origSbox\LWR@nestspan}


\let\LWR@origendSbox\endSbox

\def\endSbox{\endLWR@nestspan\LWR@origendSbox}
```

`Beqnarray` is adapted for MathJax or enclosed inside a `latexiimage`:

```
\RenewEnviron{Beqnarray}
{\LWR@eqnarrayfactor}

\csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}
```

`\GenericCaption` is enclosed in an HTML block:

```
\renewcommand{\GenericCaption}[1]{%
\LWR@figcaption%
```

```
\LWR@isolate{#1}%
\endLWR@figcaption%
}
```

`Btrivlist` is enclosed in an HTML block. This is a tabular, and does not use `\item`.

`\trivlist` {⟨*l/c/r*⟩} [⟨*t/c/b*⟩]

```
\RenewDocumentEnvironment{Btrivlist}{m o}
{%
    \begin{BlockClass}{Btrivlist}%
    \tabular{#1}%
}
{%
    \endtabular%
    \end{BlockClass}%
}
```

`Btrivlist` is also neutralized when used inside a span:

```
\AtBeginEnvironment{LWR@nestspan}{%
\RenewDocumentEnvironment{Btrivlist}{m o}{}{}%
}
```

lwarp's handling of `\item` is patched to accept fancybox's optional arguments:

```
\let\LWRFB@origitemizeitem\LWR@itemizeitem
\let\LWRFB@origdescitem\LWR@descitem

\RenewDocumentCommand{\LWR@itemizeitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origitemizeitem[#2]%
    }{%
        \LWRFB@origitemizeitem%
    }%
}

\RenewDocumentCommand{\LWR@descitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origdescitem[#2]~%
    }{%
        \LWRFB@origdescitem%
    }%
}
```

```
\RenewDocumentCommand{\LWR@nestspanitem}{d()}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
\LWR@origitem%
}
```

The various boxed lists become regular lists:

```
\renewenvironment{Bitemize}[1][]{\begin{itemize}}{\end{itemize}}
```

```
\renewenvironment{Benumerate}[1][]{\begin{enumerate}}{\end{enumerate}}
\renewenvironment{Bdescription}[1][]{\begin{description}}{\end{description}}
```

`\boxput` simply prints one then the other argument, side-by-side instead of above and behind:

```
\RenewDocumentCommand{\boxput}{s d() m m}{%
\IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
}
```

Neutralized commands:

```
\RenewDocumentCommand{\fancyput}{s d() m}{}
\RenewDocumentCommand{\thisfancyput}{s d() m}{}

\RenewDocumentCommand{\fancypage}{m m}{}
\RenewDocumentCommand{\thisfancypage}{m m}{}

\def\LandScape#1{}
\def\endLandScape{}
\def\@Landscape#1#2#3{}
\def\endLandscape{}
```

Low-level patches for `UseVerbatim` and friends:

```
\let\LWRFB@UseVerbatim\UseVerbatim
\renewcommand*{\UseVerbatim}[1]{%
\LWR@atbeginverbatim{3}{Verbatim}%
\LWRFB@UseVerbatim{#1}%
\LWR@afterendverbatim{.5}%
}

\let\LWRFB@LUseVerbatim\LUseVerbatim

\renewcommand*{\LUseVerbatim}[1]{%
\LWR@atbeginverbatim{3}{LVerbatim}%
\noindent%
\LWRFB@LUseVerbatim{#1}%
\LWR@afterendverbatim{.5}%
}

\def\@BUseVerbatim[#1]#2{%
\LWR@atbeginverbatim{3}{BVerbatim}%
\LWRFB@UseVerbatim{#2}%
\LWR@afterendverbatim{.5}%
}
```

File 117 **lwarp-fancyhdr.sty**

§ 214 Package fancyhdr

(*Emulates or patches code by* Piet van Oostrum.)

Pkg fancyhdr

fancyhdr is nullified.

for HTML output: Discard all options for lwarp-fancyhdr:

```
\LWR@ProvidesPackageDrop{fancyhdr}[2019/01/31]
```

```
\newcommand*{\fancyhead}[2][]{}
\newcommand*{\fancyfoot}[2][]{}
\newcommand*{\fancyhf}[2][]{}
\newcommand*{\fancypagestyle}[2]{}
\newcommand*{\lhead}[2][]{}
\newcommand*{\chead}[2][]{}
\newcommand*{\rhead}[2][]{}
\newcommand*{\lfoot}[2][]{}
\newcommand*{\cfoot}[2][]{}
\newcommand*{\rfoot}[2][]{}
\newcommand*{\headrulewidth}{}
\newcommand*{\footrulewidth}{}
\newcommand*{\headrule}{}
\newcommand*{\footrule}{}
\newlength{\headwidth}
\newcommand*{\fancyheadoffset}[2][]{}
\newcommand*{\fancyfootoffset}[2][]{}
\newcommand*{\fancyhfoffset}[2][]{}
\newcommand*{\iffloatpage}[2]{#2}
\newcommand*{\ifftopfloat}[2]{#2}
\newcommand*{\iffbotfloat}[2]{#2}
\newcommand*{\iffootnote}[2]{#2}
```

File 118 **lwarp-fancyref.sty**

§ 215 Package fancyref

Pkg fancyref

fancyref is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{fancyref}[1999/02/03]
```

To remove the margin option, if \fancyrefhook is anything other than the paren option, then force it to the default instead. (Comparing to the margin option was not possible since lwarp has revised the meaning of \mbox so the comparison failed.)

```
\newcommand*{\LWRfref@parenfancyrefhook}[1]{(#1)}

\ifdefstrequal{\fancyrefhook}{\LWRfref@parenfancyrefhook}
{}{
    \renewcommand*{\fancyrefhook}[1]{#1}%
}
```

Modified to ignore the page number and varioref.

```
\renewcommand*{\@f@ref}[4]{%
  \@ifundefined{#1r@#2@#3}{%
```

```
    \PackageError{fancyref}{%
      \backslashchar#1ref\space format ‘‘#2’’
      undefined\MessageBreak
      for label type ‘‘#3’’%
    }{%
      The format ‘‘#2’’ was not defined for the label type
      ‘‘#3’’\MessageBreak
      and the \backslashchar#1ref\space command.  Perhaps
      you have only misspelled its name.\MessageBreak
      Otherwise you will have to define it with
      \protect\new#1refformat\MessageBreak
      prior to using it.%
    }%
  }{%
    \fancyrefhook{%
      \@nameuse{#1r@#2@#3}%
        {\ref{#3\fancyrefargdelim#4}}%
%         {\pageref{#3\fancyrefargdelim#4}}% original
%         {\@fancyref@page@ref{#3\fancyrefargdelim#4}}% original
        {}% lwarp
        {}% lwarp
    }%
  }%
}%
```

File 119 **lwarp-fancytabs.sty**

§ 216 Package

fancytabs

Pkg fancytabs

fancytabs is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fancytabs}[2016/03/29]
```

```
\newcommand{\fancytab}[3][RIGHT]{}
\newcommand{\fancytabsStyle}[1]{}
\newcommand{\fancytabsHeight}[1]{}
\newcommand{\fancytabsWidth}[1]{}
\newcommand{\fancytabsCount}[1]{}
\newcommand{\fancytabsLeftColor}[1]{}
\newcommand{\fancytabsRightColor}[1]{}
\newcommand{\fancytabsTop}[1]{}
\newcommand{\fancytabsTextVPos}[1]{}
\newcommand{\fancytabsTextHPos}[1]{}
\newcommand{\fancytabsGap}[1]{}
\newcommand{\fancytabsFloor}[1]{}
\newcommand{\fancytabsRotate}[1]{}
```

File 120 **lwarp-fancyvrb.sty**

§ 217 Package

fancyvrb

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancyvrb

fancyvrb is supported with some patches.

fancybox, fancyvrb
⚠ \VerbatimFootnotes
⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackagePass{fancyvrb}[2008/02/07]
```

Initial default patch for fancyvrb:

```
\fvset{frame=none}%
```

After the preamble is loaded, after any patches to Verbatim:

```
\AfterEndPreamble{
\LWR@traceinfo{Patching fancyvrb.}
```

\VerbatimFootnotes

Patched to use the new version.

```
\def\VerbatimFootnotes{%
\let\@footnotetext\V@footnotetext%
\let\footnote\V@footnote%
\let\LWR@footnotetext\V@footnotetext% lwarp
}
```

\V@@footnotetext

Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@@footnotetext.

```
\def\V@@footnotetext{%
\LWR@traceinfo{V@footnotetext}%
\global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
    \unvbox\LWR@footnotebox%
```

Remember the footnote number for `\ref`:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Use HTML superscripts in the footnote even inside a `lateximage`:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{}%
```

```
  \bgroup%
  \aftergroup{\V@@@footnotetext}%
  \ignorespaces%
}%
```

```
\preto\FVB@Verbatim{\LWR@forcenewpage}
\preto\FVB@LVerbatim{\LWR@forcenewpage}
% \preto\FVB@BVerbatim{\LWR@forcenewpage}% Fails, so done below.
```

Simplified to remove PDF formatting:

```
\def\FV@BeginListFrame@Single{%
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Single{%
  \FV@SingleFrameLine{\@ne}%
}

\def\FV@BeginListFrame@Lines{%
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Lines{%
    \FV@SingleFrameLine{\@ne}%
}

\renewcommand*{\FV@SingleFrameSep}{}
```

Adds HTML formatting:

```
\def\FV@BUseVerbatim#1{%
    \LWR@atbeginverbatim[\LWR@FVstyle]{0}{verbatim}%
```

```
    \FV@BVerbatimBegin#1\FV@BVerbatimEnd%
    \LWR@afterendverbatim{0}%
}
```

\LWR@FVstyle Holds the style of the verbatim.

```
\newcommand*{\LWR@FVstyle}{}
```

The following patches to Verbatim are executed at the start and end of the environment, depending on the choice of frame. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@fvstartnone}{%
\LWR@traceinfo{fvstartnone}%
% \hbox to\z@{
\LWR@atbeginverbatim[\LWR@FVstyle]{0}{verbatim}%
% }%
}

\newcommand*{\LWR@fvendnone}{%
\LWR@traceinfo{fvendnone}%
% \hbox to\z@{
\LWR@afterendverbatim{0}%
% }%
}

\newcommand*{\LWR@fvstartsingle}{%
\LWR@traceinfo{fvstartsingle}%
\LWR@fvstartnone%
\FV@BeginListFrame@Single%
}

\newcommand*{\LWR@fvendsingle}{%
\LWR@traceinfo{fvendsingle}%
\FV@EndListFrame@Single%
\LWR@fvendnone%
}

\newcommand*{\LWR@fvstartline}{%
\LWR@traceinfo{fvstartline}%
\LWR@fvstartnone%
% \setlength{\LWR@templengthone}{\baselineskip}%
\FV@BeginListFrame@Lines%
% \setlength{\baselineskip}{\LWR@templengthone}%
% \setlength{\baselineskip}{5pt}%
}

\newcommand*{\LWR@fvendline}{%
\LWR@traceinfo{fvendline}%
\FV@EndListFrame@Lines%
\LWR@fvendnone%
}
```

The following patches select the start/left/right/end behaviors depending on `frame`. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@FVfindbordercolor}{%
\FancyVerbRuleColor%
\LWR@findcurrenttextcolor%
\color{black}%
}

% border width of \FV@FrameRule
\newcommand*{\LWR@FVborderstyle}[1]{%
padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ; %
\LWR@FVfindbordercolor %
border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt %
solid \LWR@origpound\LWR@tempcolor ; %
}

\def\FV@Frame@none{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle}%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}

\FV@Frame@none% default values

\def\FV@Frame@single{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{}}%
\let\FV@BeginListFrame\LWR@fvstartsingle%
\let\FV@LeftListFrame\FV@LeftListFrame@Single%
\let\FV@RightListFrame\FV@RightListFrame@Single%
\let\FV@EndListFrame\LWR@fvendsingle}

\def\FV@Frame@lines{%
\renewcommand*{\LWR@FVstyle}{%
  \LWR@currenttextcolorstyle\LWR@FVborderstyle{-top}\LWR@FVborderstyle{-bottom}%
}%
\let\FV@BeginListFrame\LWR@fvstartline%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendline}

\def\FV@Frame@topline{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-top}}%
\let\FV@BeginListFrame\LWR@fvstartline%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}

\def\FV@Frame@bottomline{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-bottom}}%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendline}
```

```

\def\FV@Frame@leftline{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-left}}%
% To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)
\ifx\FancyVerbFillColor\relax%
\let\FV@FrameFillLine\relax%
\else%
\@tempdima\FV@FrameRule\relax%
\multiply\@tempdima-\tw@%
\edef\FV@FrameFillLine{%
{\noexpand\FancyVerbFillColor{\vrule\@width\number\@tempdima sp}%
\kern-\number\@tempdima sp}}%
\fi%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\FV@LeftListFrame@Single%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}
```

Adds the optional label to the top and bottom edges. Original code is from the fancyvrb package.

```
\def\FV@SingleFrameLine#1{%
%   \hbox to\z@{%
%     \kern\leftmargin
    \ifnum#1=\z@\relax
      \let\FV@Label\FV@LabelBegin
    \else
      \let\FV@Label\FV@LabelEnd
    \fi
    \ifx\FV@Label\relax
%       \FancyVerbRuleColor{\vrule \@width\linewidth \@height\FV@FrameRule}%
    \else
      \ifnum#1=\z@
%         \setbox\z@\hbox{\strut\enspace\FV@LabelBegin\enspace\strut}%
        \ifx\FV@LabelPositionTopLine\relax
        \else
        \LWR@FVfindbordercolor
        \LWR@htmltagc{%
            div class="fancyvrblabel" % extra space
                style="color: \LWR@origpound\LWR@tempcolor"%
        }
        \LWR@print@textrm{\FV@LabelBegin}% \textrm preserves emdash
        \LWR@htmltagc{/div}
        \fi
      \else
%         \setbox\z@\hbox{\strut\enspace\FV@LabelEnd\enspace\strut}%
        \ifx\FV@LabelPositionBottomLine\relax
        \else
        \LWR@FVfindbordercolor

        \LWR@htmltagc{%
            div class="fancyvrblabel" % extra space
                style="color: \LWR@origpound\LWR@tempcolor"%
        }
        \LWR@print@textrm{\FV@LabelEnd}
```

```
        \LWR@htmltagc{/div}
        \fi
      \fi
    \fi
%     \hss
%     }
}
```

Processes each line, adding optional line numbers. Original code is from the fancyvrb package.

```
\def\FV@ListProcessLine#1{%
   \hbox to \hsize{%
%      \kern\leftmargin
      \hbox to \VerbatimHTMLWidth {%
       \ifcsvoid{FV@LeftListNumber}{}{\kern 2.5em}%
        \FV@LeftListNumber%
%       \FV@LeftListFrame
      \FancyVerbFormatLine{#1}%
      \hss%
%       \FV@RightListFrame
      \FV@RightListNumber%
    }%
      \hss% required to avoid underfull hboxes
}
}
```

Env `BVerbatim`

```
\AtBeginEnvironment{BVerbatim}
{%
\LWR@forcenewpage% instead of \preto
\LWR@atbeginverbatim{0}{bverbatim}%
}

\AfterEndEnvironment{BVerbatim}
{%
\LWR@afterendverbatim{0}%
}
```

End of the modifications to make at the end of the preamble:

```
} % \AfterEndPreamble
```

File 121 **`lwarp-figcaps.sty`**

§ 218 Package

figcaps

(*Emulates or patches code by* Patrick W. Daly.)

Pkg `figcaps` Emulated.

for HTML output: Discard all options for lwarp-figcaps:

```
\LWR@ProvidesPackageDrop{figcaps}[1999/02/23]
```

```
\newcommand*{\figcapson}{}
\newcommand*{\figcapsoff}{}
\newcommand*{\printfigures}{}
\newcommand*{\figmarkon}{}
\newcommand*{\figmarkoff}{}
\def\figurecapname{Figure Captions}
\def\tablepagename{Tables}
\def\figurepagename{Figures}
```

File 122 **lwarp-figsize.sty**

§ 219 Package figsize

(*Emulates or patches code by* Anthony A. Tanbakuchi.)

Pkg figsize figsize is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{figsize}[2002/03/18]
```

Emulates a virtual 6×9 inch textsize.

```
\newlength{\figwidth}
\newlength{\figheight}

\newcommand{\SetFigLayout}[3][0]{%
\setlength{\figheight}{8in}%
\setlength{\figheight}{\figheight / #2}%
%
\setlength{\figwidth}{5.5in}%
\setlength{\figwidth}{\figwidth / #3}%
}
```

File 123 **lwarp-fitbox.sty**

§ 220 Package fitbox

Pkg fitbox fitbox is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fitbox}[2019/02/20]
```

```
\NewDocumentCommand{\fitbox}{s o m}{%
    \begin{BlockClass}{fitbox}
    #3
    \end{BlockClass}
}
```

```

\newcommand*{\fitboxset}[1]{}

\newdimen\fitboxnatheight
\newdimen\fitboxnatwidth

\newcommand\SetFitboxLayout[3][]{}
```

File 124 **lwarp-fix2col.sty**

§ 221 Package fix2col

Pkg fix2col fix2col is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fix2col}[2015/11/13]
```

File 125 **lwarp-fixme.sty**

§ 222 Package fixme

(*Emulates or patches code by* Didier Verna.)

Pkg fixme fixme is patched for use by lwarp.

⚠ external layouts External layouts (`\fxloadlayouts`) are not supported.

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

for HTML output:

```
\LWR@ProvidesPackagePass{fixme}[2017/03/05]
```

Restore lwarp's version of `\@wrindex`, ignoring the fixme package's `target` option:

```
\let\@wrindex\LWR@wrindex
```

Float-related macros required by lwarp:

```
\newcommand{\ext@fixme}{lox}

\renewcommand{\l@fixme}[2]{\hypertocfloat{1}{fixme}{lox}{#1}{#2}}
```

Other modifications:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
```

```

\renewcommand*\FXLayoutInline[3]{ %
\InlineClass[\FXFaceInlineHTMLStyle]{fixmeinline}%
    {\@fxtextstd{#1}{#2}{#3}}%
}

\def\FXFaceEnvHTMLStyle{font-weight:bold}

\renewcommand*\FXEnvLayoutPlainBegin[2]{%
\BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
\ignorespaces#2 \fxnotename{#1}: \ignorespaces}

\renewcommand*\FXEnvLayoutPlainEnd[2]{\endBlockClass}

\renewcommand*\FXEnvLayoutSignatureBegin[2]{%
\BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
\fxnotename{#1}: \ignorespaces}

\renewcommand*\FXEnvLayoutSignatureEnd[2]{\@fxsignature{#2}\endBlockClass}

\def\FXFaceSignatureHTMLStyle{font-style:italic}

\DeclareRobustCommand*\@fxsignature[1]{%
\ifthenelse{\equal{#1}{}}%
    {}%
    { -- {\InlineClass[\FXFaceSignatureHTMLStyle]{fixmesignature}{#1}}}%
}


\def\FXFaceTargetHTMLStyle{font-style:italic}

\renewcommand\FXTargetLayoutPlain[2]{%
    \InlineClass[\FXFaceTargetHTMLStyle]{fixmetarget}{#2}%
}
```

File 126 **lwarp-fixmetodonotes.sty**

§ 223 Package

fixmetodonotes

(*Emulates or patches code by* Gioele Barabucci.)

Pkg fixmetodonotes fixmetodonotes is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{fixmetodonotes}[2013/04/28]

\renewcommand{\NOTES@addtolist}[2]{%
    \refstepcounter{NOTES@note}%
%   \phantomsection% REMOVED
    \addcontentsline{notes}{NOTES@note}{%
        \protect\numberline{\theNOTES@note}{{#1}: {#2}}%
    }%
}

```

```
\renewcommand{\NOTES@marker}[2]{\fbox{%
    \textcolor{#2}{% WAS \color
        \textbf{#1}}%
    }}

\renewcommand{\NOTES@colorline}[2]{%
  \bgroup%
    \ULon{\LWR@backgroundcolor{#1}{#2}}%
}
```

File 127 **lwarp-flafter.sty**

§ 224 Package

flafter

Pkg flafter flafter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flafter}[2018/01/08]
\providecommand\fl@trace[1]{}
```

File 128 **lwarp-flippdf.sty**

§ 225 Package

flippdf

Pkg flippdf flippdf is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flippdf}[2006/06/30]

\newcommand\FlipPDF{}
\newcommand\UnFlipPDF{}
```

File 129 **lwarp-float.sty**

§ 226 Package

float

(*Emulates or patches code by* Anselm Lingnau.)

Pkg float float is emulated.

Float styles boxed and ruled are emulated by CSS and a float class according to style.

The HTML <figure> class is set to the float type, so CSS may also be used to format the float and its caption, according to float type. Furthermore, an additional class is set to the float style: plain, plaintop, boxed, or ruled, so CSS may be used to format by float style as well. Default formatting by CSS is provided for ruled and boxed styles.

for HTML output:

```
\LWR@ProvidesPackageDrop{float}[2001/11/08]
```

`\listof` See section 74.2 for the `\listof` command.

`\LWR@floatstyle` The default float style:

```
\newcommand*{\LWR@floatstyle}{plain}
```

`\newfloat` {⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the `\newfloat` command from the float package.

"placement" is ignored.

```
\NewDocumentCommand{\newfloat}{m m m o}{%
\IfValueTF{#4}%
{\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}%
{\DeclareFloatingEnvironment[fileext=#3]{#1}}%
```

Remember the float style:

```
\csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the `\listof` command for new floats, but float does not, so remove `\listof` here in case it is manually created later.

```
\cslet{listof#1s}\relax%
\cslet{listof#1es}\relax%
```

Likesize, newfloat also creates `\l@<type>`, but float does not, so remove it here:

```
\cslet{l@#1}\relax%
}
```

`\floatname` {⟨*type*⟩} {⟨*name*⟩}

Sets the text name of the float, such as "Figure".

```
\NewDocumentCommand{\floatname}{m +m}{%
    \SetupFloatingEnvironment{#1}{name=#2}%
}
```

`\floatplacement` {⟨*type*⟩} {⟨*placement*⟩}

Float placement is ignored.

```
\newcommand*{\floatplacement}[2]{%
    \SetupFloatingEnvironment{#1}{placement=#2}%
}
```

`\floatstyle` {⟨*style*⟩}

Remember the style for future floats:

```
\newcommand{\floatstyle}[1]{%
    \def\LWR@floatstyle{#1}%
}
```

\restylefloat * {⟨*type*⟩}

Remember the style for this float:

```
\NewDocumentCommand{\restylefloat}{s m}{%
    \csedef{LWR@floatstyle@#2}{\LWR@floatstyle}%
}
```

File 130 **lwarp-floatflt.sty**

§ 227 Package

floatflt

(*Emulates or patches code by* Mats Dahlgren.)

Pkg floatflt Emulated.

for HTML output: Discard all options for lwarp-floatflt:

```
\LWR@ProvidesPackageDrop{floatflt}[1997/07/16]
```

Env [⟨⟩] offset {⟨*type*⟩} {⟨*width*⟩} Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTfloatflt@marginfloat}{O{-1.2ex} m m}
{%
\setlength{\LWR@templengthone}{#3}%
\LWR@BlockClassWP{%
    float:right; %
    width:\LWR@printlength{\LWR@templengthone};  % extra space
    margin:10pt%
}{%
    width:\LWR@printlength{\LWR@templengthone}%
}%
{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}
```

Env floatingfigure [⟨*placement*⟩] {⟨*width*⟩}

```
\DeclareDocumentEnvironment{floatingfigure}{o m}
  {\begin{KFLTfloatflt@marginfloat}{figure}{#2}}
  {\end{KFLTfloatflt@marginfloat}}
```

Env floatingtable [⟨*placement*⟩]

```
\DeclareDocumentEnvironment{floatingtable}{o}
  {\begin{KFLTfloatflt@marginfloat}{table}{1.5in}}
  {\end{KFLTfloatflt@marginfloat}}
```

File 131 **lwarp-floatpag.sty**

§ 228 Package floatpag

(*Emulates or patches code by* Vytas Statulevičius and Sigitas Tolušis.)

Pkg floatpag Emulated.

for HTML output: Discard all options for lwarp-floatpag:

```
\LWR@ProvidesPackageDrop{floatpag}[2012/05/29]
```

```
\newcommand*{\floatpagestyle}[1]{}
\newcommand*{\rotfloatpagestyle}[1]{}
\newcommand*{\thisfloatpagestyle}[1]{}
```

File 132 **lwarp-floatrow.sty**

§ 229 Package floatrow

(*Emulates or patches code by* Olga Lapko.)

Pkg floatrow floatrow is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{floatrow}[2008/08/02]
```

⚠ Misplaced alignment tab character &

Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 9.10.1.

⚠ subfig package

When combined with the subfig package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ `\FBwidth`, `\FBheight`

The emulation of floatrow does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether subcaption was loaded. If not, it is assumed that subfig is used instead:

```
\newbool{LWR@subcaptionloaded}

\AtBeginDocument{
\@ifpackageloaded{subcaption}
{\booltrue{LWR@subcaptionloaded}}
{\boolfalse{LWR@subcaptionloaded}}
}
```

\floatbox [⟨*1 preamble*⟩] {⟨*2 captype*⟩} [⟨*3 width*⟩] [⟨*4 height*⟩] [⟨*5 vert pos*⟩] {⟨*6 caption*⟩} {⟨*7 object*⟩}

Only parameters for captype, width, caption, and object are used.

LWR@insubfloatrow is true if inside a subfloatrow environment.

There are two actions, depending on the use of subcaption or subfig.

```
\NewDocumentCommand{\floatbox}{o m o o o +m +m}{%
\ifbool{LWR@subcaptionloaded}%
{% subcaption
```

For subcaption:

```
    \ifbool{LWR@insubfloatrow}%
    {% subcaption in a subfloatrow
```

subfigure and subtable environments take width as an argument.

```
        \IfValueTF{#3}%
        {\@nameuse{sub#2}{#3}}%
        {\@nameuse{sub#2}{\linewidth}}%
    }% subcaption in a subfloatrow
    {% subcaption not in subfloatrow
```

figure and table environments do not take a width argument.

```
        \@nameuse{#2}%
    }% subcaption not in subfloatrow
    #6

    #7
```

End the environments:

```
    \ifbool{LWR@insubfloatrow}%
    {\@nameuse{endsub#2}}%
    {\@nameuse{end#2}}%
}% subcaption
{% assume subfig
```

For subfig:

```
\ifbool{LWR@insubfloatrow}%
{% subfig in a subfloatrow
```

\subfloat is a macro, not an environment.

Package subfig's \subfloat command takes an optional argument which is the caption, but \floatbox argument #6 contains commands to create the caption and label,

not the caption itself. Thus, \caption is temporarily disabled to return its own argument without braces.

```
    \begingroup
    \let\caption\@firstofone
    \subfloat[#6]{#7}
    \endgroup
}% subfig in a subfloatrow
{% subfig package, but not a subfig
```

figure and table are environments:

```
\@nameuse{#2}
#6

#7
\@nameuse{end#2}
}% subfig package, but not a subfig
}% assume subfig
}
```

Not used:

```
\newcommand*{\nocapbeside}{}
\newcommand*{\capbeside}{}
\newcommand*{\captop}{}
\newlength{\FBwidth}
\setlength{\FBwidth}{.3\linewidth}
\newlength{\FBheight}
\setlength{\FBheight}{2in}
\newcommand*{\useFCwidth}{}
\newcommand{\floatsetup}[2][]{}
\newcommand{\thisfloatsetup}[1]{}
\newcommand{\clearfloatsetup}[1]{}
\newcommand*{\killfloatstyle}{}
```

\newfloatcommand {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\newfloatcommand}{m m o o}{%
\@namedef{#1}{
\floatbox{#2}
}
}
```

\renewfloatcommand {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\renewfloatcommand}{m m o o}{%
\@namedef{#1}{%
\floatbox{#2}
}
}
```

\ffigbox [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ffigbox}{figure}[\nocapbeside][]
```

\ttabbox [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ttabbox}{table}[\captop][\FBwidth]
```

\fcapside [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{fcapside}{figure}[\capbeside][]
```

Env floatrow [⟨*numfloats*⟩]

The row of floats is placed into a of class floatrow.

```
\newenvironment*{floatrow}[1][2]
{
\LWR@forcenewpage
\BlockClass{floatrow}
```

While inside the floatrow, divide the \linewidth by the number of floats.

```
\booltrue{LWR@infloatrow}
\setlength{\linewidth}{6in/#1}
}
{
\boolfalse{LWR@infloatrow}
\endBlockClass
}
```

Keys for \DeclareNewFloatType:

```
\newcommand*{\LWR@frowkeyplacement}{}
\newcommand*{\LWR@frowkeyname}{}
\newcommand*{\LWR@frowkeyfileext}{}
\newcommand*{\LWR@frowkeywithin}{}
\newcommand*{\LWR@frowkeycapstyle}{}

\define@key{frowkeys}{placement}{}%
\define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}%
\define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}%
\define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}%
\define@key{frowkeys}{relatedcapstyle}{}%
```

\DeclareNewFloatType {⟨*type*⟩} {⟨*options*⟩}

Use \listof{type}{Title} to print a list of the floats.

```
\newcommand*{\DeclareNewFloatType}[2]{%
```

Reset key values:

```
\renewcommand*{\LWR@frowkeyplacement}{}%
\renewcommand*{\LWR@frowkeyname}{}%
\renewcommand*{\LWR@frowkeyfileext}{}%
\renewcommand*{\LWR@frowkeywithin}{}%
\renewcommand*{\LWR@frowkeycapstyle}{}%
```

Read new key values:

```
\LWR@traceinfo{about to setkeys frowkeys}%
\setkeys{frowkeys}{#2}%
\LWR@traceinfo{finished setkeys frowkeys}%
```

Create a new float with optional [within]:

```
\ifthenelse{\equal{\LWR@frowkeywithin}{}}%
{%
    \LWR@traceinfo{about to newfloat #1 \LWR@frowkeyplacement\ %
        \LWR@frowkeyfileext}%
    \newfloat{#1}{\LWR@frowkeyplacement}{\LWR@frowkeyfileext}%
}%
{%
    \LWR@traceinfo{about to newfloat #1\ \LWR@frowkeyplacement\ %
        \LWR@frowkeyfileext\ \LWR@frowkeywithin}%
    \newfloat{#1}{\LWR@frowkeyplacement}%
    {\LWR@frowkeyfileext}[\LWR@frowkeywithin]%
    \LWR@traceinfo{finished newfloat #1}%
}%
```

Rename the float if a name was given:

```
\ifthenelse{\equal{\LWR@frowkeyname}{}}%
    {}%
    {\floatname{#1}{\LWR@frowkeyname}}%
}
```

Not used:

```
\newcommand{\buildFBBOX}[2]{}
\newcommand*{\CenterFloatBoxes}{}
\newcommand*{\TopFloatBoxes}{}
\newcommand*{\BottomFloatBoxes}{}
\newcommand*{\PlainFloatBoxes}{}

\newcommand{\capsubrowsettings}{}

\NewDocumentCommand{\RawFloats}{o o}{}
```

`\RawCaption` {⟨*text*⟩}

To be used inside a minipage or parbox.

```
\newcommand{\RawCaption}[1]{#1}
```

`\floatfoot` {⟨*text*⟩}

Places additional text inside a float, inside a CSS `<div>` of class `floatfoot`.

```
\NewDocumentCommand{\floatfoot}{s +m}{%
\begin{BlockClass}{floatfoot}
#2
\end{BlockClass}
}
```

Used to compute \linewidth.

```
\newbool{LWR@insubfloatrow}
\boolfalse{LWR@insubfloatrow}
```

Env subfloatrow [⟨*num_floats*⟩]

```
\newenvironment*{subfloatrow}[1][2]
{
```

The row of floats is placed into a of class floatrow:

```
\LWR@forcenewpage
\BlockClass{floatrow}
```

While inside the floatrow, LWR@insubfloatrow is set true, which tells \floatbox to use \subfigure or \subtable.

```
\begingroup
\booltrue{LWR@insubfloatrow}
}
{
\endgroup
\endBlockClass
\boolfalse{LWR@insubfloatrow}
}
```

File 133 **lwarp-fltrace.sty**

§ 230 Package fltrace

Pkg fltrace fltrace is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fltrace}[2018/01/08]
```

```
\def\tracefloats{}
\def\tracefloatsoff{}
\def\tracefloatvals{}
```

File 134 **lwarp-flushend.sty**

§ 231 Package flushend

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg flushend Emulated.

for HTML output: Discard all options for lwarp-flushend:

```
\LWR@ProvidesPackageDrop{flushend}[2017/03/27]
```

```
\newcommand*{\flushend}{}
\newcommand*{\raggedend}{}
\newcommand*{\flushcolsend}{}
\newcommand*{\raggedcolsend}{}
\newcommand*{\atColsBreak}[1]{}
\newcommand*{\atColsEnd}[1]{}
\newcommand*{\showcolsendrule}{}
```

File 135 **lwarp-fnbreak.sty**

§ 232 Package fnbreak

Pkg fnbreak

fnbreak is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnbreak}[2012/01/01]
```

```
\newcommand*{\fnbreakverbose}{}
\newcommand*{\fnbreaknonverbose}{}
\newcommand*{\fnbreaklabel}{}
\newcommand*{\fnbreaknolabel}{}
```

File 136 **lwarp-fncychap.sty**

§ 233 Package fncychap

(*Emulates or patches code by* Ulf A. Lindgren.)

Pkg fncychap

fncychap is emulated.

for HTML output:

Discard all options for lwarp-fncychap:

```
\LWR@ProvidesPackageDrop{fncychap}[2007/07/30]
```

```
\def\mghrulefill#1{}
\def\ChNameLowerCase{}
\def\ChNameUpperCase{}
\def\ChNameAsIs{}
\def\ChTitleLowerCase{}
\def\ChTitleUpperCase{}
\def\ChTitleAsIs{}
\newcommand{\ChRuleWidth}[1]{}
\newcommand{\ChNameVar}[1]{}
\newcommand{\ChNumVar}[1]{}
\newcommand{\ChTitleVar}[1]{}
\newcommand{\TheAlphaChapter}{}
\newcommand{\DOCH}{}
\newcommand{\DOTI}[1]{}
\newcommand{\DOTIS}[1]{}
\newlength{\mylen}
\newlength{\myhi}
```

```
\newlength{\px}
\newlength{\py}
\newlength{\pyy}
\newlength{\pxx}
\newlength{\RW}
\newcommand{\FmN}[1]{#1}
\newcommand{\FmTi}[1]{#1}
```

File 137 **lwarp-fnlineno.sty**

§ 234 Package fnlineno

Pkg fnlineno fnlineno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnlineno}[2011/01/07]
```

File 138 **lwarp-fnpara.sty**

§ 235 Package fnpara

Pkg fnpara fnpara is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpara}
```

File 139 **lwarp-fnpos.sty**

§ 236 Package fnpos

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg fnpos fnpos is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpos}[1999/07/14]
```

```
\newcommand*{\makeFNbottom}{}
\newcommand*{\makeFNmid}{}
\newcommand*{\makeFNbelow}{}
\newcommand*{\makeFNabove}{}
```

File 140 **lwarp-fontawesome.sty**

§ 237 Package fontawesome

(*Emulates or patches code by* Xavier Danaux.)

Pkg fontawesome

fontawesome is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

⚠ *poppler* syntax warning

If using pdfLaTeX, *poppler* may issue a syntax warning regarding parsing a ligature component. XeLaTeX or LuaLaTeX may be used to avoid this warning.

In the following, the general strategy is to intercept `\symbol` and embed it inside a `lateximage`. These changes are done inside a local group.

For pdfLaTeX, the `alt` tag includes the icon (symbol) number. For XeLaTeX and LuaLaTeX, the `alt` tag is generic.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome}[2016/05/15]

\LetLtxMacro\LWR@orig@symbol\symbol

\ifxetexorluatex

\newfontfamily{\LWR@orig@FA}{FontAwesome}

\newcommand*{\LWR@fontawesome@xelatex@symbol}[1]{%
\begin{lateximage}*[(icon)][fontawesomexetex#1]%
\begingroup%
\LWR@orig@FA%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\RenewDocumentCommand{\FA}{}{%
    \LetLtxMacro\symbol\LWR@fontawesome@xelatex@symbol%
}

\else

\newcommand*{\LWR@fontawesome@symbolone}[1]{%
\begin{lateximage}*[(icon #1)][fontawesomeone#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesomeone}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\newcommand*{\LWR@fontawesome@symboltwo}[1]{%
\begin{lateximage}*[(icon #1)][fontawesometwo#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesometwo}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\newcommand*{\LWR@fontawesome@symbolthree}[1]{%
```

```
\begin{lateximage}*[(icon #1)][fontawesomethree#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesomeonethree}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\renewrobustcmd\FAone{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolone%
}

\renewrobustcmd\FAtwo{%
    \LetLtxMacro\symbol\LWR@fontawesome@symboltwo%
}

\renewrobustcmd\FAthree{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolthree%
}
\fi
```

File 141 **lwarp-fontawesome5.sty**

§ 238 Package

fontawesome5

(*Emulates or patches code by* Marcel Krüger.)

Pkg fontawesome5

fontawesome5 is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

The `alt` tag has the name of the icon.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome5}[2018/07/27]

\ExplSyntaxOn
\cs_set:Nn\fontawesome_use_icon:nn{
  \cs_if_exist:cTF{c__fontawesome_slot_#2_tl}{
    \begin{lateximage}*[(#2)][#1]
    \exp_last_unbraced:Nv
      \__fontawesome_icon_at:nnnn
      {c__fontawesome_slot_#2_tl}
        {#1}{#2}
    \end{lateximage}
  }{
    \msg_error:nnxx{fontawesome5}{icon-not-found}{#2}{#1}
  }
}
\ExplSyntaxOff
```

File 142 **lwarp-fontenc.sty**

§ 239 Package

fontenc

Pkg fontenc

If using pdfLaTeX, lwarp used to require fontenc be loaded before lwarp, but now lwarp itself loads \fontenc with T1 encoding, which lwarp requires. fontenc is now allowed to be loaded with another encoding after lwarp.

lwarp-fontenc is no longer necessary, but is still provided to overwrite older versions.

for HTML output:

```
\LWR@ProvidesPackagePass{fontenc}[2017/04/05]
```

File 143 **lwarp-footmisc.sty**

§ 240 Package

footmisc

(*Emulates or patches code by* Robin Fairbairns.)

Pkg footmisc

footmisc is emulated.

lwarp incidentally happens to emulate the stable option.

```
\LWR@ProvidesPackageDrop{footmisc}[2011/06/06]
```

Some nullified commands:

```
\newcommand{\footnotelayout}{}
\newcommand{\setfnsymbol}[1]{}
\NewDocumentCommand{\DefineFNsymbols}{s m o m}{}

\newdimen\footnotemargin
\footnotemargin1.8em\relax

\newcommand*\hangfootparskip{0.5\baselineskip}
\newcommand*\hangfootparindent{0em}%

\let\pagefootnoterule\footnoterule
\let\mpfootnoterule\footnoterule
\def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}

\providecommand*{\multiplefootnotemarker}{3sp}
\providecommand*{\multfootsep}{,}
```

Using cleveref:

```
\providecommand*{\footref}[1]{\labelcref{#1}}
```

The following work as-is:

```
\newcommand\mpfootnotemark{%
  \@ifnextchar[%
    \@xmpfootnotemark%
    {%
      \stepcounter\@mpfn%
      \protected@xdef\@thefnmark{\thempfn}%
      \@footnotemark%
    }%
}
\def\@xmpfootnotemark[#1]{%
  \begingroup%
    \csname c@\@mpfn\endcsname #1\relax%
    \unrestored@protected@xdef\@thefnmark{\thempfn}%
  \endgroup%
  \@footnotemark%
}
```

File 144 **lwarp-footnote.sty**

§ 241 Package

footnote

(*Emulates or patches code by* Mark Wooding.)

Pkg footnote

footnote is used with minor patches.

for HTML output:

```
\LWR@ProvidesPackagePass{footnote}[1997/01/28]
```

Removed print-version formatting:

```
\def\fn@startnote{%
%   \@parboxrestore%
  \protected@edef\@currentlabel{\csname p@\@mpfn\endcsname\@thefnmark}%
%   \color@begingroup% *** conflicts with lwarp
}

% \let\fn@endnote\color@endgroup% *** conflicts with lwarp
\def\fn@endnote{%
\LWR@htmltagc{/\LWR@tagregularparagraph}%
\LWR@orignewline%
}
```

Removed print-version formatting:

```
\def\fn@startfntext{%
  \setbox\z@\vbox\bgroup%
    \fn@startnote%
    \fn@prefntext%
    \ignorespaces%
}
```

Removed print-version formatting, added closing paragraph tag:

```
\def\fn@endfntext{%
    \LWR@htmltagc{/\LWR@tagregularparagraph}%
    \LWR@orignewline%
    \fn@postfntext%
  \egroup%
  \begingroup%
    \let\@makefntext\@empty%
    \let\@finalstrut\@gobble%
    \LetLtxMacro\rule\@gobbletwo% *8* also the optional argument?
    \@footnotetext{\unvbox\z@}%
  \endgroup%
}
```

These have been redefined, so re-`\let` them again:

```
\let\endfootnote\fn@endfntext
\let\endfootnotetext\endfootnote
```

File 145 **lwarp-footnotebackref.sty**

§ 242 Package

footnotebackref

Pkg `footnotebackref` footnotebackref is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnotebackref}[2012/07/01]
```

File 146 **lwarp-footnotehyper.sty**

§ 243 Package

footnotehyper

Pkg `footnotehyper` footnotehyper is a hyperref-safe version of footnote. For lwarp, footnotehyper is emulated.

for HTML output: Discard all options for lwarp-footnotehyper:

```
\RequirePackage{footnote}
\LWR@ProvidesPackageDrop{footnotehyper}[2018/01/23]
```

File 147 **lwarp-footnoterange.sty**

§ 244 Package

footnoterange

(*Emulates or patches code by* H.-Martin Münch.)

Pkg `footnoterange` footnoterange is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{footnoterange}[2012/02/17]

\csletcs{footnoterange}{footnoterange*}
\csletcs{endfootnoterange}{endfootnoterange*}
```

File 148 **lwarp-footnpag.sty**

§ 245 Package footnpag

Pkg footnpag

footnpag is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnpag}
```

File 149 **lwarp-foreign.sty**

§ 246 Package foreign

(*Emulates or patches code by* Philip G. Ratcliffe.)

Pkg foreign

foreign is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{foreign}[2012/09/25]

\renewcommand\foreignabbrfont{\emph}
```

File 150 **lwarp-forest.sty**

§ 247 Package forest

(*Emulates or patches code by* Sašo Živanović.)

Pkg forest

forest is patched for use by lwarp.

⚠ `\Forest*` The starred version of the macro `\Forest*` is not supported. lwarp encases each `lateximage` in an environment, so the global results of the starred `\Forest*` are lost.

for HTML output:

```
\LWR@ProvidesPackagePass{forest}[2017/07/14]

\BeforeBeginEnvironment{forest}{\begin{lateximage}[forest]}

\AfterEndEnvironment{forest}{\end{lateximage}}

\RenewDocumentCommand{\Forest}{s D(){} m}{%
  \forest@config{#2}%
  \IfBooleanTF{#1}{%
        \PackageError{lwarp-forest}%
```

```
        {Starred \Forest is not supported}%
     {Lwarp uses an environment for images, but \Forest* cannot work in an environment.}%
        \let\forest@next\forest@env%
    }{\let\forest@next\forest@group@env}%
    \begin{lateximage}[forest]%     lwarp
  \forest@next{#3}%
    \end{lateximage}%               lwarp
}
```

File 151 **lwarp-framed.sty**

§ 248 Package

framed

(*Emulates or patches code by* Donald Arseneau.)

Pkg framed framed is supported and patched by lwarp.

for HTML output: Accept all options for lwarp-framed:

```
\LWR@ProvidesPackagePass{framed}[2011/10/22]
\RequirePackage{xcolor}% for \convertcolorspec


\renewenvironment{framed}{%
\LWR@forcenewpage
\BlockClass{framed}%
}
{\endBlockClass}

\renewenvironment{oframed}{%
\LWR@forcenewpage
\BlockClass{framed}%
}
{\endBlockClass}


\renewenvironment{shaded}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
}
{\endBlockClass}

\renewenvironment{shaded*}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
}
{\endBlockClass}


\renewenvironment{leftbar}{%
\LWR@forcenewpage
```

```
    \BlockClass{framedleftbar}
  \def\FrameCommand{}%
  \MakeFramed {}
}%
 {\endMakeFramed\endBlockClass}


\renewenvironment{snugshade}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\renewenvironment{snugshade*}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\let\oframed\framed
\let\endoframed\endframed


\RenewEnviron{titled-frame}[1]{%
\CustomFBox{#1}{}{0pt}{0pt}{0pt}{0pt}{\BODY}
}
```

\CustomFBox {⟨*toptitle*⟩} {⟨*bottitle*⟩} {⟨*thicknesstop*⟩} {⟨*bottom*⟩} {⟨*left*⟩} {⟨*right*⟩} {⟨*text contents*⟩}

```
\renewcommand{\CustomFBox}[7]{%
\convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\begin{BlockClass}[border: 3px solid \LWR@origpound\LWR@tempcolor]{framed}%
\ifthenelse{\isempty{#1}}{}{% not empty
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#1}}%
    \end{BlockClass}
}% not empty

#7

\ifthenelse{\isempty{#2}}{}{% not empty
    \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#2}}%
    \end{BlockClass}
}% not empty
\end{BlockClass}
}
```

\TitleBarFrame [⟨*marker*⟩] {⟨*title*⟩} {⟨*contents*⟩}

```
\renewcommand\TitleBarFrame[3][]{
\CustomFBox
    {#2}{}%
    \fboxrule\fboxrule\fboxrule\fboxrule
    {#3}%
}
```

```
\renewcommand{\TF@Title}[1]{#1}
```

MakeFramed {⟨*settings*⟩}

```
\let\MakeFramed\relax
\let\endMakeFramed\relax

\NewEnviron{MakeFramed}[1]{%
\FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
}
```

\fb@put@frame {⟨*frame cmd no split*⟩} {⟨*frame cmd split*⟩}

```
\renewcommand*{\fb@put@frame}[2]{%
\relax%
\@tempboxa%
}
```

File 152 **lwarp-ftcap.sty**

§ 249 Package

ftcap

Pkg ftcap

ftcap is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ftcap}
```

File 153 **lwarp-ftnright.sty**

§ 250 Package

ftnright

Pkg ftnright

ftnright is ignored.

for HTML output: Discard all options for lwarp-ftnright:

```
\LWR@ProvidesPackageDrop{ftnright}[2014/10/28]
```

File 154 **lwarp-fullminipage.sty**

§ 251 Package fullminipage

Pkg fullminipage

fullminipage is nullified.

for HTML output:

```
\LWR@ProvidesPackageDrop{fullminipage}[2014/07/06]
\newenvironment{fullminipage}[1][]{}{}
```

File 155 **lwarp-fullpage.sty**

§ 252 Package fullpage

Pkg fullpage

fullpage is ignored.

for HTML output:

Discard all options for lwarp-fullpage:

```
\LWR@ProvidesPackageDrop{fullpage}[1994/06/01]
```

File 156 **lwarp-fullwidth.sty**

§ 253 Package fullwidth

(*Emulates or patches code by* Marco Daniel.)

Pkg fullwidth

fullwidth is emulated.

A minipage is used, of no HTML width.

for HTML output:

```
\LWR@ProvidesPackageDrop{fullwidth}[2011/11/18]
\newenvironment*{fullwidth}[1][]{%
\minipagefullwidth%
\minipage{\linewidth}%
}
{%
\endminipage%
}
```

File 157 **lwarp-fwlw.sty**

§ 254 Package fwlw

Pkg fwlw fwlw is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fwlw}

\newbox\FirstWordBox      \global\setbox\FirstWordBox\hbox{}
\newbox\NextWordBox       \global\setbox\NextWordBox\hbox{}
\newbox\LastWordBox       \global\setbox\LastWordBox\hbox{}
\def\ps@fwlwhead{}
\def\ps@NextWordFoot{}
```

File 158 **lwarp-gentombow.sty**

§ 255 Package gentombow

Pkg gentombow gentombow is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gentombow}[2018/05/17]

\newcommand{\settombowbanner}[1]{}
\newcommand{\settombowbannerfont}[1]{}
\newcommand{\settombowwidth}[1]{}
\newcommand{\settombowbleed}[1]{}
\newcommand{\settombowcolor}[1]{}
```

File 159 **lwarp-geometry.sty**

§ 256 Package geometry

(*Emulates or patches code by* Hideo Umeki.)

Pkg geometry geometry is preloaded by lwarp, but must be nullified as seen by the user's source code.

for HTML output: Discard all options for lwarp-geometry:

```
\LWR@ProvidesPackageDrop{geometry}[2018/04/16]

\renewcommand*{\geometry}[1]{}
\renewcommand*{\newgeometry}[1]{}
\renewcommand*{\restoregeometry}{}
\renewcommand*{\savegeometry}[1]{}
\renewcommand*{\loadgeometry}[1]{}
```

File 160 **lwarp-gloss.sty**

§ 257 Package

gloss

(*Emulates or patches code by* Jose Luis Díiaz, Javier Bezos.)

Pkg gloss

gloss is patched for use by lwarp.

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

for HTML output:

```
\LWR@ProvidesPackagePass{gloss}[2002/07/26]

\xpatchcmd{\gls@gloss@iii}
   {\thepage}
   {\theLWR@previousautopagelabel}
   {}
   {\LWR@patcherror{gloss}{gls@gloss@iii}}

\def\gls@page@i#1#2{%
  \endgroup
  \global\@namedef{glsp@#1}{\nameref{autopage-#2}}}
```

File 161 **lwarp-glossaries.sty**

§ 258 Package

glossaries

(*Emulates or patches code by* Nicola L.C. Talbot.)

Pkg glossaries

processing glossaries

Opt GlossaryCmd

Default: makeglossaries

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

lwarpmk has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

The shell command to execute is set by the lwarp option `GlossaryCmd`, which defaults to **makeglossaries**. The print or HTML glossary filename is appended to this command.

⚠ *makeglossaries* not found

In some situations it may be required to modify the default command, such as to add the **perl** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and TOC options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style

The default `style=item` option for glossaries conflicts with lwarp, so the style is forced to `index` instead.

⚠ number list

The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/HTML versions

The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

for HTML output:

```
\PassOptionsToPackage{xindy}{glossaries}

\LWR@ProvidesPackagePass{glossaries}[2018/07/23]

\setupglossaries{nonumberlist}
\setglossarystyle{index}
```

Patched to fix TOC pointing to the previous page:

```
\renewcommand*{\@p@glossarysection}[2]{%
  \glsclearpage
  \phantomsection
  \ifdefempty\@@glossarysecstar
  {%
    \csname\@@glossarysec\endcsname{#2}%
  }%
  {%
```

In the original, the TOC entry was made before the section, thus linking to the phantomsection in the printed version, but for HTML, this caused the link to point to the page before the glossaries, which could be a different HTML file. Here, the TOC entry is made after the section is created:

```
      \csname\@@glossarysec\endcsname*{#2}%
    \@gls@toc{#1}{\@@glossarysec}% Moved after the previous line.
  }%
  \@@glossaryseclabel
}
```

lwarp's sectioning commands cannot handle robust macros when splitting HTML into named filenames. glossaries uses `\translate` in sectioning names, and `\translate` is robust and cannot be expanded. The following pre-expands the translations at this moment, making use of `\translatelet`.

```
\newcommand*{\LWR@comp@glossaryname}{\translate{Glossary}}

\ifdefstrequal{\glossaryname}{\LWR@comp@glossaryname}{
    \translatelet\LWR@translatetemp{Glossary}
    \edef\glossaryname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@acronymname}{\translate{Acronym}}

\ifdefstrequal{\acronymname}{\LWR@comp@acronymname}{
    \translatelet\LWR@translatetemp{Acronym}
    \edef\acronymname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glssymbolsgroupname}{\translate{Symbols (glossaries)}}

\ifdefstrequal{\glssymbolsgroupname}{\LWR@comp@glssymbolsgroupname}{
    \translatelet\LWR@translatetemp{Symbols (glossaries)}
    \edef\glssymbolsgroupname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glsnumbersgroupname}{\translate{Numbers (glossaries)}}

\ifdefstrequal{\glsnumbersgroupname}{\LWR@comp@glsnumbersgroupname}{
    \translatelet\LWR@translatetemp{Numbers (glossaries)}
    \edef\glsnumbersgroupname{\LWR@translatetemp}
}{}
```

File 162 **lwarp-gmeometric.sty**

§ 259 Package

gmeometric

Pkg gmeometric

gmeometric is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gmeometric}[2008/11/22]
```

File 163 **lwarp-graphics.sty**

§ 260 Package

graphics

(*Emulates or patches code by* D. P. Carlisle.)

Pkg graphics graphics is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{graphics}[2017/06/25]
```

§ 260.1 Graphics extensions

\DeclareGraphicsExtensions {⟨*list*⟩}

\AtBeginDocument allow svg files instead of pdf:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Inside a lateximage, allow pdf instead of svg:

```
\ifpdf
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
\else% \ifpdf
        \ifXeTeX
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \else
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \fi
\fi
```

§ 260.2 Length conversions and graphics options

⚠ whitespace

A scaled image in LaTeX by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

Used to store the user's selected dimensions and HTML class.

The class defaults to "inlineimage" unless changed by a `class=xyx` option.

```
\newlength{\LWR@igwidth}
\newlength{\LWR@igheight}
\newcommand*{\LWR@igwidthstyle}{}
\newcommand*{\LWR@igheightstyle}{}
\newcommand*{\LWR@igorigin}{}
\newcommand*{\LWR@igangle}{}
\newcommand*{\LWR@igxscale}{1}
\newcommand*{\LWR@igyscale}{1}
\newcommand*{\LWR@igclass}{inlineimage}
```

```
\newcommand*{\LWR@igalt}{(image)}
```

Set the actions of each of the key/value combinations for `\includegraphics`. Many are ignored.

If an optional width was given, set an HTML style:

```
\define@key{igraph}{width}{%
\setlength{\LWR@igwidth}{#1}%
\ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes px
    {}% not px
}{}% end of length > 0pt
}
```

If an optional height was given, set an HTML style:

```
\define@key{igraph}{height}{%
\setlength{\LWR@igheight}{#1}%
\ifthenelse{\lengthtest{\LWR@igheight > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igheightstyle}{%
    height:\LWR@printlength{\LWR@igheight} % extra space
    }%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes px
    {}% not px
}{}% end of length > 0pt
}
```

Handle origin key:

```
\define@key{igraph}{origin}[c]{%
    \renewcommand*{\LWR@igorigin}{#1}%
}
```

Handle angle key:

```
\define@key{igraph}{angle}{\renewcommand*{\LWR@igangle}{#1}}
```

Handle class key:

```
\define@key{igraph}{class}{\renewcommand*{\LWR@igclass}{#1}}
```

Handle alt key:

```
\define@key{igraph}{alt}{\renewcommand*{\LWR@igalt}{#1}}
```

It appears that graphicx does not have separate keys for `xscale` and `yscale`. `scale` adjusts both at the same time.

```
\define@key{igraph}{scale}{%
    \ifthenelse{\equal{#1}{1}}{}{%  must expand #1
        \PackageWarning{lwarp}{%
```

```
            It is recommended to use\MessageBreak
            [width=xx\protect\linewidth]\MessageBreak
            instead of [scale=yy],%
        }%
    }%
    \renewcommand*{\LWR@igxscale}{#1}%
    \renewcommand*{\LWR@igyscale}{#1}%
}
```

Numerous ignored keys:

```
\define@key{igraph}{bb}{}
\define@key{igraph}{bbllx}{}
\define@key{igraph}{bblly}{}
\define@key{igraph}{bburx}{}
\define@key{igraph}{bbury}{}
\define@key{igraph}{natwidth}{}
\define@key{igraph}{natheight}{}
\define@key{igraph}{hiresbb}[true]{}
\define@key{igraph}{viewport}{}
\define@key{igraph}{trim}{}
\define@key{igraph}{totalheight}{}
\define@key{igraph}{keepaspectratio}[true]{}
\define@key{igraph}{clip}[true]{}
\define@key{igraph}{draft}[true]{}
\define@key{igraph}{type}{}
\define@key{igraph}{ext}{}
\define@key{igraph}{read}{}
\define@key{igraph}{command}{}
```

New in v1.1a:

```
\define@key{igraph}{quite}{}
\define@key{igraph}{page}{}
\define@key{igraph}{pagebox}{}
\define@key{igraph}{interpolate}[true]{}
```

New in v1.1b:

```
\define@key{igraph}{decodearray}{}
```

§ 260.3 Printing HTML styles

`\LWR@rotstyle` {⟨*prefix*⟩} {⟨*degrees*⟩}

Prints the rotate style with the given prefix.

`prefix` is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:rotate` style.

```
\newcommand*{\LWR@rotstyle}[2]{%
 #1transform:rotate(-#2deg);
}
```

\LWR@scalestyle {⟨*prefix*⟩} {⟨*xscale*⟩} {⟨*yscale*⟩}

Prints the scale style with the given prefix.

prefix is -ms- or -webkit- or nothing, and is used to generate three versions of the transform:scale style.

```
\newcommand*{\LWR@scalestyle}[3]{%
 #1transform:scale(#2,#3);
}
```

§ 260.4 \includegraphics

Bool LWR@infloatrow Used to compute \linewidth.

```
\newbool{LWR@infloatrow}
\boolfalse{LWR@infloatrow}
```

\LWR@opacity For HTML, used only for \includegraphics.

\LWR@opacity may be set by the transparent package.

```
\def\LWR@opacity{1}
```

\LWR@imagesizebox Used to determine the actual image size if needed.

```
\newsavebox{\LWR@imagesizebox}
```

\LWR@HTML@Gin@setfile {⟨*w*⟩} {⟨*h*⟩} {⟨*filename*⟩} Sets the parsed filename for HTML output.

```
\newcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \xdef\LWR@parsedfilename{#3}%
}
```

Key [Gin] class CSS class for the image.

Define the new class key for the print-mode version of \includegraphics, which is enabled inside a lateximage.

```
\AtBeginDocument{
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
}
```

\LWR@replaceEPSSVG Usually, references to EPS files become SVG files, but if the epstopdf package is being used, it automatically converts EPS to PDF, and the following must NOT be done.

```
\AtBeginDocument{
\@ifpackageloaded{epstopdf}
{
    \newcommand*{\LWR@replaceEPSSVG}{}
```

```
}{%
    \newcommand*{\LWR@replaceEPSSVG}{%
        \StrSubstitute{\LWR@tempone}{.eps}{.svg}[\LWR@tempone]%
        \StrSubstitute{\LWR@tempone}{.EPS}{.SVG}[\LWR@tempone]%
    }
}%
}
```

\LWR@includegraphicsb * [⟨*2: options*⟩] [⟨*3: options*⟩] {⟨*4: filename*⟩}

graphics syntax is \includegraphics * [⟨*llx,lly*⟩] [⟨*urx,ury*⟩] {⟨*file*⟩}

graphicx syntax is \includegraphics [⟨*key values*⟩] {⟨*file*⟩}

If #3 is empty, only one optional argument was given, thus graphicx syntax.

If using \epsfig or \psfig from the epsfig package, #4 will be \LWR@epsfig@filename, which will have been set by the file or figure keys. Therefore, #4 must not be used until after the keys have been processed.

```
\NewDocumentCommand{\LWR@includegraphicsb}{s o o m}
{%
```

Start the image tag on a new line, allow PDF output word wrap:

```
\LWR@origtilde \LWR@orignewline%
```

Temporarily compute \linewidth, \textwidth, \textheight arguments with a 6x9 inch size until the next \endgroup.

```
\begingroup%
\ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}%
{%
    \ifbool{LWR@infloatrow}%
    {}
    {% not in a minipage or a floatrow:
        \setlength{\linewidth}{6in}%
        \setlength{\textwidth}{6in}%
        \setlength{\textheight}{9in}%
    }%
}{}%
```

For correct em sizing during the width and height conversions:

```
\large%
```

Reset some defaults, possibly will be changed below if options were given:

```
\setlength{\LWR@igwidth}{0pt}%
\setlength{\LWR@igheight}{0pt}%
\renewcommand*{\LWR@igwidthstyle}{}%
\renewcommand*{\LWR@igheightstyle}{}%
\renewcommand*{\LWR@igorigin}{}%
```

```
\renewcommand*{\LWR@igangle}{}%
\renewcommand*{\LWR@igxscale}{1}%
\renewcommand*{\LWR@igyscale}{1}%
\renewcommand*{\LWR@igclass}{inlineimage}%
```

```
\renewcommand*{\LWR@igalt}{(image)}%
```

If #3 is empty, only one optional argument was given, thus graphicx syntax:

```
\IfValueF{#3}{%
    \IfValueTF{#2}%
        {\setkeys{igraph}{#2}}%
        {\setkeys{igraph}{}}%
}%
```

Fully expand and detokenize the filename, changing the file extension to .svg if necessary.

```
\begingroup%
\LetLtxMacro\Gin@setfile\LWR@HTML@Gin@setfile%
\edef\LWR@tempone{#4}%
\StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
\StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
\LWR@replaceEPSSVG%
\xdef\LWR@parsedfilename{\LWR@tempone}%
\Ginclude@graphics{\detokenize\expandafter{\LWR@tempone}}%
\endgroup%
\filename@parse{\LWR@parsedfilename}%
\LWR@traceinfo{LWR@parsedfilename is \LWR@parsedfilename}%
% \LWR@sanitize{\LWR@parsedfilename}%
```

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```
\ifbool{FormatWP}{%
    \begingroup%
    \LWR@restoreorigformatting%
    \ifpdf%
    \appto\LWR@restoreorigformatting{%
   \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
    }%
    \else% \ifpdf
            \ifXeTeX%
    \appto\LWR@restoreorigformatting{%
   \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
    }%
            \else%
    \appto\LWR@restoreorigformatting{%
   \DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
    }%
            \fi%
    \fi% \ifpdf
    \define@key{Gin}{angle}{}%
    \IfBooleanTF{#1}%
```

```
    {% starred
        \IfValueTF{#3}%
        {%
        \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics*[#2][#3]{#4}}%
        }%
        {%
            \IfValueTF{#2}%
            {%
           \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics*[#2]{#4}}%
            }{%
               \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics*{#4}}%
            }%
        }%
    }% starred
    {% not starred
        \IfValueTF{#3}%
        {%
        \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics[#2][#3]{#4}}%
        }%
        {%
            \IfValueTF{#2}%
            {%
            \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics[#2]{#4}}%
            }{%
                \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics{#4}}%
            }%
        }%
    }% not starred
    \endgroup%
    \settowidth{\LWR@igwidth}{\usebox{\LWR@imagesizebox}}%
   \global\renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
    \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
   \global\renewcommand*{\LWR@igheightstyle}{height:\LWR@printlength{\LWR@igheight}}%
}{}% FormatWP
```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class.

The `\LWR@origtilde` adds space between tags in case this is being done inside a `\savebox` where `\newline` has no effect.

```
\LWR@traceinfo{LWR@includegraphicsb: about to create href}%
\href{\LWR@parsedfilename}%
{% start of href
\LWR@traceinfo{LWR@includegraphicsb: about to LWR@htmltag}%
\LWR@htmltag{% start of image tags
img\LWR@indentHTML%
src="%
```

```
\detokenize\expandafter{\LWR@parsedfilename}%
```

```
"\LWR@indentHTML%
```

Only include a style tag if a width, height, angle, or scale was given:

```
\ifthenelse{
    \NOT\equal{\LWR@igwidthstyle}{} \OR
    \NOT\equal{\LWR@igheightstyle}{} \OR
    \NOT\equal{\LWR@igorigin}{} \OR
    \NOT\equal{\LWR@igangle}{} \OR
    \NOT\equal{\LWR@igxscale}{1} \OR
    \NOT\equal{\LWR@igyscale}{1}
}%
{%
    style="\LWR@indentHTML
    \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{}}%
        {\LWR@igwidthstyle;\LWR@indentHTML}{}%
    \ifthenelse{\NOT\equal{\LWR@igheightstyle}{}}%
        {\LWR@igheightstyle;\LWR@indentHTML}{}%
    \ifthenelse{\NOT\equal{\LWR@igorigin}{}}%
        {%
            transform-origin: \LWR@originnames{\LWR@igorigin};\LWR@indentHTML%
        }{}%
    \ifthenelse{\NOT\equal{\LWR@igangle}{}}%
    {%
        \LWR@rotstyle{-ms-}{\LWR@igangle}\LWR@indentHTML
        \LWR@rotstyle{-webkit-}{\LWR@igangle}\LWR@indentHTML
        \LWR@rotstyle{}{\LWR@igangle }\LWR@indentHTML
    }{}%
    \ifthenelse{%
        \NOT\equal{\LWR@igxscale}{1}\OR%
        \NOT\equal{\LWR@igyscale}{1}%
    }%
    {%
        \LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
        \LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
        \LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
    }{}%
    %
    \ifthenelse{\NOT\equal{\LWR@opacity}{1}}%
        {opacity:\LWR@opacity;\LWR@indentHTML}{}%
    %
    "\LWR@indentHTML%
}{}%
```

Set the class and alt tag:

```
class="\LWR@igclass"\LWR@indentHTML%
alt="\LWR@igalt" \LWR@orignewline%
}% end of image tags
}% end of href
```

Return to original page size and font size:

```
\endgroup
\LWR@traceinfo{LWR@includegraphicsb done}%
}
```

\includegraphics [⟨*key=val*⟩] {⟨*filename*⟩}

Handles width and height, converted to fixed width and heights.

The user should always use no file suffix in the document source.

```
\AtBeginDocument{

\LWR@traceinfo{Patching includegraphics.}

\LetLtxMacro\LWR@origincludegraphics\includegraphics

\renewcommand*{\includegraphics}
{%
```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```
\LWR@traceinfo{includegraphics}%
\LWR@ensuredoingapar%
\LWR@includegraphicsb%
}% includegraphics
}% AtBeginDocument
```

§ 260.5 Boxes

\LWR@rotboxorigin Holds the origin key letters.

```
\newcommand*{\LWR@rotboxorigin}{}
```

\LWR@originname {⟨*letter*⟩}

Given one LaTeX origin key value, translate into an HTML origin word:

```
\newcommand*{\LWR@originname}[1]{%
    \ifthenelse{\equal{#1}{t}}{top}{}%
    \ifthenelse{\equal{#1}{b}}{bottom}{}%
    \ifthenelse{\equal{#1}{c}}{center}{}%
    \ifthenelse{\equal{#1}{l}}{left}{}%
    \ifthenelse{\equal{#1}{r}}{right}{}%
}
```

\LWR@originnames {⟨*letters*⟩}

Given one- or two-letter LaTeX origin key values, translate into HTML origin words:

```
\newcommand*{\LWR@originnames}[1]{%
\StrChar{#1}{1}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
\StrChar{#1}{2}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
}
```

Handle the origin key for \rotatebox:

```
\define@key{krotbox}{origin}{%
\renewcommand*{\LWR@rotboxorigin}{#1}%
}
```

These keys are ignored:

```
\define@key{krotbox}{x}{}
\define@key{krotbox}{y}{}
\define@key{krotbox}{units}{}
```

\rotatebox [⟨*keyval list*⟩] {⟨*angle*⟩} {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@rotatebox}{O{} m +m}{%
```

Reset the origin to "none-given":

```
\renewcommand*{\LWR@rotboxorigin}{}
```

Process the optional keys, which may set \LWR@rotateboxorigin:

```
\setkeys{krotbox}{#1}%
```

Select inline-block so that HTML will transform this span:

```
\LWR@htmltagc{%
    span\LWR@indentHTML
    style="\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

If an origin was given, translate and print the origin information:

```
    \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{}}%
      {transform-origin: \LWR@originnames{\LWR@rotboxorigin};\LWR@indentHTML}%
        {}%
```

Print the rotation information:

```
    \LWR@rotstyle{-ms-}{#2}\LWR@indentHTML
    \LWR@rotstyle{-webkit-}{#2}\LWR@indentHTML
    \LWR@rotstyle{}{#2}"\LWR@orignewline%
}\LWR@orignewline%
```

Print the text to be rotated:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{rotatebox}

}% AtBeginDocument
```

\scalebox {⟨*h-scale*⟩} [⟨*v-scale*⟩] {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@scalebox}{m o m}{%
```

Select `inline-block` so that HTML will transform this span:

```
\LWR@htmltagc{%
    span\LWR@indentHTML
    style="\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

Print the scaling information:

```
    \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{}{#1}{\IfNoValueTF{#2}{#1}{#2}}
    "\LWR@orignewline
}\LWR@orignewline%
```

Print the text to be scaled:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{scalebox}

}% AtBeginDocument
```

\reflectbox {⟨*text*⟩}

```
\AtBeginDocument{

\newcommand{\LWR@HTML@reflectbox}[1]{%
\scalebox{-1}[1]{#1}%
}% \reflectbox

\LWR@formatted{reflectbox}

}% AtBeginDocument
```

\resizebox {⟨*h-length*⟩} {⟨*v-length*⟩} {⟨*text*⟩}

Simply prints its text argument.

```
\AtBeginDocument{

\NewDocumentCommand{\LWR@HTML@resizebox}{s m m m}{%
#4%
}

\LWR@formatted{resizebox}

}% AtBeginDocument
```

File 164 **lwarp-graphicx.sty**

§ 261 Package graphicx

Pkg graphicx

graphicx is emulated.

graphicx loads graphics, which also loads lwarp-graphics, which remembers the original graphics definitions for use inside a lateximage, and then patches them \AtBeginDocument for HTML output.

lwarp-graphics handles the syntax of either graphics or graphicx.

for HTML output:

```
\LWR@ProvidesPackagePass{graphicx}[2017/06/01]
```

File 165 **lwarp-grffile.sty**

§ 262 Package grffile

Pkg grffile

⚠ matching PDF and SVG

grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

lwarp-grffile now exists as a placeholder since grffile used to be emulated by lwarp, and thus older versions of lwarp-grffile may exist and should be overwritten by this newer version.

for HTML output:

```
\LWR@ProvidesPackagePass{grffile}[2017/06/30]
```

File 166 **lwarp-grid.sty**

§ 263 Package grid

Pkg grid

grid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{grid}[2009/06/16]
```

```
\newenvironment*{gridenv}{}{}
```

File 167 **lwarp-grid-system.sty**

§ 264 Package grid-system

(*Emulates or patches code by* Marcus Bitzl.)

Pkg grid-system

grid-system is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{grid-system}[2014/02/16]
```

(`\ifdef` is in case the older syntax is removed.)

```
\AtBeginEnvironment{Row}{\setlength{\linewidth}{6in}}

\ifdef{\endrow}{
    \AtBeginEnvironment{row}{\setlength{\linewidth}{6in}}
}{}

\renewcommand{\gridsystem@finishcell}{\hspace{\gridsystem@cellsep}}
```

File 168 **lwarp-gridset.sty**

§ 265 Package gridset

Pkg gridset

gridset is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gridset}
```

```
\newcommand*{\gridbase}{}
```

```
\newcommand*{\gridinterval}{}
\newcommand*{\savepos}[1]{}
\newcounter{gridcnt}
\newcommand*{\vskipnextgrid}{}
\newcommand*{\thegridinfo}[1]{}
\newcommand*{\theposinfo}[1]{}
\newcommand*{\theypos}[1]{}
```

File 169 **lwarp-hang.sty**

§ 266 Package

hang

(*Emulates or patches code by* Andreas Nolda.)

Pkg hang hang is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hang}[2017/02/18]

\newlength{\hangingindent}
\setlength{\hangingindent}{1em}
\newlength{\hangingleftmargin}
\setlength{\hangingleftmargin}{0em}

\newcommand*{\LWR@findhangingleftmargin}{%
\setlength{\LWR@templengthone}{\hangingleftmargin}%
\addtolength{\LWR@templengthone}{\hangingindent}%
}

\newenvironment{hangingpar}
{
    \LWR@findhangingleftmargin%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}

\newenvironment{hanginglist}
{%
    \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}%
    \renewcommand*{\LWR@printopenlist}{%
        \LWR@findhangingleftmargin%
        ul style="%
            \LWR@print@mbox{list-style-type:none;} % extra space
            \LWR@print@mbox{%
                margin-left:\LWR@printlength{\LWR@templengthone}%
            } ; % extra space
            \LWR@print@mbox{%
                text-indent:-\LWR@printlength{\hangingindent}%
            }%
        "%
```

```
    }%
    \let\item\LWR@itemizeitem%
    \list{}{}%
}
{\endlist}

\newenvironment{compacthang}
{\hanginglist}
{\endhanginglist}

\newlength{\labeledleftmargin}
\setlength{\labeledleftmargin}{0em}

\newenvironment{labeledpar}[2]
{%
    \BlockClass[%
        \LWR@findhangingleftmargin%
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]{labeledpar}#2%
}
{\endBlockClass}

\newenvironment{labeledlist}[1]
{\hanginglist}
{\endhanginglist}

\newenvironment{compactlabel}[1]
{\hanginglist}
{\endhanginglist}
```

File 170 **lwarp-hanging.sty**

§ 267 Package

hanging

Pkg hanging

hanging is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hanging}[2009/09/02]
```

```
\@ifclassloaded{memoir}{
\let\hangpara\relax
\let\hangparas\relax
\let\endhangparas\relax
\let\hangpunct\relax
\let\endhangpunct\relax
}{}
```

\hangpara {⟨*indent*⟩} {⟨*afternum*⟩}

Use hangparas instead.

```
\newcommand*{\hangpara}[2]{}
```

Env hangparas {⟨*indent*⟩} {⟨*afternum*⟩}

```
\newenvironment*{hangparas}[2]
{%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{#1}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{#1}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}
```

Env hangpunct

```
\newenvironment*{hangpunct}
{\BlockClass{hangpunct}}
{\endBlockClass}
```

```
\newcommand{\nhpt}{.}
\newcommand{\nhlq}{‘}
\newcommand{\nhrq}{’}
```

File 171 **lwarp-hypcap.sty**

§ 268 Package hypcap

Pkg hypcap hypcap is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypcap}[2016/05/16]
```

```
\newcommand*{\capstart}{}
\newcommand*{\hypcapspace}{}
\newcommand*{\hypcapredef}[1]{}
\newcommand*{\capstartfalse}{}
\newcommand*{\capstarttrue}{}
```

File 172 **lwarp-hypdestopt.sty**

§ 269 Package hypdestopt

Pkg hypdestopt hypdestopt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypdestopt}[2016/05/21]
```

File 173 **lwarp-hypernat.sty**

§ 270 Package

hypernat

Pkg hypernat hypernat is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{hypernat}[2001/07/09]
```

File 174 **lwarp-hyperref.sty**

§ 271 Package

hyperref

(*Emulates or patches code by* Sebastian Rahtz, Heiko Oberdiek.)

Pkg hyperref hyperref is emulated.

for HTML output:

```
1 % \LWR@ProvidesPackageDrop{hyperref}
2 \typeout{Using the lwarp html version of package ‘hyperref’, discarding options.}
3 \typeout{    Are not using ProvidesPackage, so that other packages}
4 \typeout{    do not attempt to patch lwarp’s version of ‘hyperref’.}
5 % \ProvidesPackage{lwarp-#1-#2}
6 \DeclareOption*{}
```

```
7 % \ProcessOptions\relax
8 \let\ds@\@empty%         from the original \ProcessOptions
9 \edef\@curroptions{}%    lwarp modification to \ProcessOptions
10 \@process@ptions\relax%  from the original \ProcessOptions
```

```
11 \newcommand*{\hypersetup}[1]{}
12 \newcommand*{\hyperbaseurl}[1]{}
```

\hyperimage {⟨*URL*⟩} {⟨*alt text*⟩}

Insert an image with alt text:

```
13 \NewDocumentCommand{\LWR@hyperimageb}{m +m}{%
14 \LWR@ensuredoingapar%
15 \def\LWR@templink{#1}%
16 \@onelevel@sanitize\LWR@templink%
17 \LWR@htmltag{img src="\LWR@templink" alt="#2" class="hyperimage"}%
18 \LWR@ensuredoingapar%
19 \endgroup%
20 }
21
22 \newrobustcmd*{\hyperimage}{%
23 \begingroup%
24 \catcode‘\#=12%
25 \catcode‘\%=12%
```

```
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperimageb%
}

```

\hyperdef {⟨*1: category*⟩} {⟨*2: name*⟩} {⟨*3: text*⟩}

Creates an HTML anchor to `category.name` with the given text.

```
\NewDocumentCommand{\LWR@hyperdefb}{m m +m}{%
\LWR@ensuredoingapar%
\LWR@sublabel{#1.#2}%
#3%
\endgroup%
}

\newcommand*{\hyperdef}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperdefb%
}

```

\LWR@hyperrefb {⟨*1: URL*⟩} {⟨*2: category*⟩} {⟨*3: name*⟩} {⟨*4: text*⟩}

Creates an HTML link to `URL#category.name` with the given text.

```
\newcommand{\LWR@hyperreffinish}[1]{%
\begingroup%
\RenewDocumentCommand{\ref}{}{\LWR@ref@ignorestar}%
#1%
\endgroup%
\LWR@htmltag{/a}%
}

\newcommand*{\LWR@hyperrefbb}[3]{%
\LWR@htmltag{%
    a href="%
        \detokenize\expandafter{#1}\LWR@hashmark%
        \detokenize\expandafter{#2}.\detokenize\expandafter{#3}%
    "%
}%
\endgroup%
\LWR@hyperreffinish%
}

\newrobustcmd*{\LWR@hyperrefb}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
```

```
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperrefbb%
}
```

\LWR@hyperrefc [⟨*label*⟩] {⟨*text*⟩}

Creates text as an HTML link to the LaTeX label.

```

\NewDocumentCommand{\LWR@hyperrefcb}{O{label}}{%
\LWR@startref{#1}%
\endgroup%
\LWR@hyperreffinish%
}

\newcommand*{\LWR@hyperrefc}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperrefcb%
}
```

\hyperref {⟨*1: URL*⟩} {⟨*2: category*⟩} {⟨*3: name*⟩} {⟨*4: text*⟩} — or — [⟨*1: label*⟩] {⟨*2: text*⟩}

```
\DeclareRobustCommand*{\hyperref}{%
\LWR@ensuredoingapar%
\@ifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
}
```

\hypertarget {⟨*name*⟩} {⟨*text*⟩}

Creates an anchor to name with the given text.

```
\NewDocumentCommand{\LWR@hypertargetb}{m +m}{%
\label{LWR-ht-#1}%
#2%
\endgroup%
}

\newcommand*{\hypertarget}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hypertargetb%
}
```

\hyperlink {⟨*name*⟩} {⟨*text*⟩}

Creates a link to the anchor created by hypertarget, with the given link text.

Declared because also defined by memoir.

```
\DeclareDocumentCommand{\LWR@hyperlinkb}{m}{%
\LWR@hyperrefcb[LWR-ht-#1]%
}

\DeclareDocumentCommand{\hyperlink}{}{%
\LWR@ensuredoingapar%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperlinkb%
}
```

\autoref * {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autoref}{s m}{%
    \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
}
```

\autopageref {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autopageref}{s m}{%
    \IfBooleanTF{#1}{\cpageref{#2}}{\cref{#2}}%
}
```

\pdfstringdef {⟨*macroname*⟩} {⟨*TEXstring*⟩}

```
\newcommand{\pdfstringdef}[2]{}
```

\pdfbookmark [⟨*level*⟩] {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\pdfbookmark}[3][]{}
```

\currentpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\currentpdfbookmark}[2]{}
```

\subpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\subpdfbookmark}[2]{}
```

\belowpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
\newcommand{\belowpdfbookmark}[2]{}
```

\texorpdfstring {⟨*TEXstring*⟩} {⟨*PDFstring*⟩}

```
\newcommand{\texorpdfstring}[2]{#1}
```

\hypercalcbp {⟨*dimen*⟩} From hyperref.

```
\def\hypercalcbp#1{%
\strip@pt\dimexpr 0.99626401\dimexpr(#1)\relax\relax
}%
```

\Acrobatmenu {⟨*menuoption*⟩} {⟨*text*⟩}

```
\newcommand{\Acrobatmenu}[2]{}
```

\TextField [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\TextField}[2][]{}
```

\CheckBox [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\CheckBox}[2][]{}
```

\ChoiceMenu [⟨*parameters*⟩] {⟨*label*⟩} {⟨*choices*⟩}

```
\DeclareRobustCommand{\ChoiceMenu}[3][]{}
```

\PushButton [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\PushButton}[2][]{}
```

\Submit [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\Submit}[2][]{}
```

\Reset [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\Reset}[2][]{}
```

\Gauge [⟨*parameters*⟩] {⟨*label*⟩}

```
\DeclareRobustCommand{\Gauge}[2][]{}
```

\LayoutTextField {⟨*label*⟩} {⟨*field*⟩}

```
\newcommand*{\LayoutTextField}[2]{}
```

\LayoutChoiceField {⟨*label*⟩} {⟨*field*⟩}

```
\newcommand*{\LayoutChoiceField}[2]{}
```

\LayoutCheckField {⟨*label*⟩} {⟨*field*⟩}

```
\newcommand*{\LayoutCheckField}[2]{}
```

\MakeRadioField {⟨*width*⟩} {⟨*height*⟩}

```
\newcommand*{\MakeRadioField}[2]{}
```

\MakeCheckField {⟨*width*⟩} {⟨*height*⟩}

```
\newcommand*{\MakeCheckField}[2]{}
```

\MakeTextField {⟨*width*⟩} {⟨*height*⟩}

```
\newcommand*{\MakeTextField}[2]{}
```

\MakeChoiceField {⟨*width*⟩} {⟨*height*⟩}

```
\newcommand*{\MakeChoiceField}[2]{}
```

\MakeFieldButton {⟨*text*⟩}

```
\newcommand{\MakeFieldButton}[1]{}
```

File 175 **lwarp-hyperxmp.sty**

§ 272 Package hyperxmp

Pkg hyperxmp Emulated.

for HTML output: Discard all options for lwarp-hyperxmp:

```
\LWR@ProvidesPackageDrop{hyperxmp}[2018/11/27]
```

File 176 **lwarp-hyphenat.sty**

§ 273 Package hyphenat

Pkg hyphenat hyphenat is emulated during HTML output, while the print-mode version is used inside a lateximage.

for HTML output:

```
\LWR@ProvidesPackagePass{hyphenat}[2009/09/02]
```

```
\LetLtxMacro\LWRHYNAT@origtextnhtt\textnhtt
\LetLtxMacro\LWRHYNAT@orignhttfamily\nhttfamily
\LetLtxMacro\LWRHYNAT@orignohyphens\nohyphens
\LetLtxMacro\LWRHYNAT@origbshyp\bshyp
```

```
\LetLtxMacro\LWRHYNAT@origfshyp\fshyp
\LetLtxMacro\LWRHYNAT@origdothyp\dothyp
\LetLtxMacro\LWRHYNAT@origcolonhyp\colonhyp
\LetLtxMacro\LWRHYNAT@orighyp\hyp

\LetLtxMacro\textnhtt\texttt
\LetLtxMacro\nhttfamily\ttfamily

\renewcommand{\nohyphens}[1]{#1}
\renewrobustcmd{\bshyp}{%
    \ifmmode\backslash\else\textbackslash\fi%
}
\renewrobustcmd{\fshyp}{/}
\renewrobustcmd{\dothyp}{.}
\renewrobustcmd{\colonhyp}{:}
\renewrobustcmd{\hyp}{-}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\textnhtt\LWRHYNAT@origtextnhtt%
\LetLtxMacro\nhttfamily\LWRHYNAT@orignhttfamily%
\LetLtxMacro\nohyphens\LWRHYNAT@orignohyphens%
\LetLtxMacro\bshyp\LWRHYNAT@origbshyp%
\LetLtxMacro\fshyp\LWRHYNAT@origfshyp%
\LetLtxMacro\dothyp\LWRHYNAT@origdothyp%
\LetLtxMacro\colonhyp\LWRHYNAT@origcolonhyp%
\LetLtxMacro\hyp\LWRHYNAT@orighyp%
}
```

File 177 **lwarp-idxlayout.sty**

§ 274 Package

idxlayout

(*Emulates or patches code by* Thomas Titz.)

Pkg idxlayout Emulated.

for HTML output: Discard all options for lwarp-idxlayout:

```
\LWR@ProvidesPackageDrop{idxlayout}[2012/03/30]
```

```
\newcommand{\LWR@indexprenote}{}

\preto\printindex{

\LWR@orignewpage
\LWR@startpars

\LWR@indexprenote

}

\newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
\newcommand*{\noindexprenote}{\renewcommand{\LWR@indexprenote}{}}
```

```

\newcommand{\idxlayout}[1]{}
\newcommand*{\indexfont}{}
\newcommand*{\indexjustific}{}
\newcommand*{\indexsubsdelim}{}
\newcommand*{\indexstheadcase}{}
```

File 178 **lwarp-ifoddpage.sty**

§ 275 Package ifoddpage

(*Emulates or patches code by* Martin Scharrer.)

Pkg ifoddpage ifoddpage is emulated.

for HTML output: Discard all options for lwarp-ifoddpage:

```
\LWR@ProvidesPackageDrop{ifoddpage}[2016/04/23]
```

```
\newif\ifoddpage

\newif\ifoddpageoroneside

\DeclareRobustCommand{\checkoddpage}{\oddpagetrue\oddpageoronesidetrue}

\def\oddpage@page{1}

\def\@ifoddpage{%
        \expandafter\@firstoftwo
}

\def\@ifoddpageoroneside{%
        \expandafter\@firstoftwo
}
```

File 179 **lwarp-imakeidx.sty**

§ 276 Package imakeidx

(*Emulates or patches code by* Enrico Gregorio.)

Pkg imakeidx imakeidx is patched for use by lwarp.

letter headings When using *makeindex*, to match the print and HTML output's display of index letter headings, specify the `lwarp.ist` style:

```
\makeindex[options={-s lwarp.ist}]
```

(For HTML the `lwarp.ist` style is used automatically, which displays letter headings. When using *xindy* the default style also displays letter headings.)

index setup

See section 9.6.17 for how to setup *lwarpmk* to process the indexes with imakeidx, both with and without shell escape.

for HTML output:

```
\LWR@ProvidesPackagePass{imakeidx}[2016/10/15]
```

Use the new HTML suffix:

```
\catcode`\_=12%
\define@key{imki}{name}{\def\imki@name{#1_html}}
\catcode`\_=8%
```

\printindex

The HTML version of \printindex:

```
\catcode`\_=12%

\renewcommand*{\printindex}[1][\imki@jobname]{%
\LWR@orignewpage%
\LWR@startpars%
\ifstrequal{#1}{\imki@jobname}{%
  \@ifundefined{#1@idxfile}{%
        \imki@error{#1}%
    }{%
        \imki@putindex{#1}%
    }%
}{%
 \@ifundefined{#1_html@idxfile}{\imki@error{#1_html}}{\imki@putindex{#1_html}}%
}%
}

\catcode`\_=8%
```

\@index

The HTML version of \index:

```
\catcode`\_=12%

\def\@index[#1]{%
    \ifstrequal{#1}{\imki@jobname}%
    {%
        \@ifundefined{#1@idxfile}%
        {%
            \PackageWarning{imakeidx}{Undefined index file `#1'}%
            \begingroup
            \@sanitize
            \imki@nowrindex%
        }%
        {%
            \edef\@idxfile{#1}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
    {%
        \@ifundefined{#1_html@idxfile}%
```

```
        {%
            \PackageWarning{imakeidx}{Undefined index file ‘#1_html’}%
            \begingroup
            \@sanitize
            \imki@nowrindex%
        }%
        {%
            \edef\@idxfile{#1_html}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
}

\catcode‘\_=8%
```

\item
\subitem
\subsubitem

HTML versions of \item, etc.:

```
\appto\theindex{%
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}
```

\imki@wrindexentrysplit {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}
\imki@wrindexentryunique {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}

While writing index entries, adds an HTML label, and writes the label's index instead of the page number:

```
\renewcommand\imki@wrindexentrysplit[3]{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
  \expandafter\protected@write\csname#1@idxfile\endcsname{}%
    {\string\indexentry{#2}{\arabic{LWR@autoindex}}}%
}

\renewcommand\imki@wrindexentryunique[3]{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
  \protected@write\@indexfile{}%
    {\string\indexentry[#1]{#2}{\arabic{LWR@autoindex}}}%
}

\def\imki@wrindexsplit#1#2{%
\imki@wrindexentrysplit{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
}

\def\imki@wrindexunique#1#2{%
```

```
\imki@wrindexentryunique{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
  }

```

\LWR@imki@setxdydefopts

Sets the xindy HTML options, ignoring the user's settings.

```
\newcommand*{\LWR@imki@setxdydefopts}{%
    \edef\imki@options{ \space %
        -M \space \LWR@xindyStyle\space %
        -L \space \LWR@xindyLanguage\space %
        -C \space \LWR@xindyCodepage\space %
    }%
}
```

\LWR@imki@setdefopts {⟨*user options*⟩}

Sets the HTML options, added to the user's settings, depending on whether makeindex or xindy are used.

For *makeindex*, the user's choice is ignored, and only the lwarp version is used. (Only one style at a time is possible.)

For *xindy*, multiple modules may be specified, and the lwarp version is appended.

```
\newcommand*{\LWR@imki@setdefopts}[1]{%
\ifblank{#1}{%
    \edef\imki@options{\space -s \space \LWR@makeindexStyle \space}%
    \ifdefstring{\imki@progdefault}{xindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{texindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{truexindy}{\LWR@imki@setxdydefopts}{}%
}{%
    \edef\imki@options{\space #1 \space}%
}%
}
```

\imki@makeindex

Use the new HTML options:

```
\xpatchcmd{\imki@makeindex}
    {\let\imki@options\space}
    {\LWR@imki@setdefopts{}}%
    {}
    {\LWR@patcherror{imakeidx}{makeindex}}
```

Use the new HTML options.

```
\define@key{imki}{options}{\LWR@imki@setdefopts{#1}}
```

\imki@resetdefaults

Use the new HTML options:

```
\xpatchcmd{\imki@resetdefaults}
    {\def\imki@options{ }}
    {\LWR@imki@setdefopts{}}
    {}
```

```
    {\LWR@patcherror{imakeidx}{resetdefaults}}
```

theindex was already defined \AtBeginDocument by the lwarp core, so it must be redefined here similarly, but patched for imakeidx:

Env theindex

```
\AtBeginDocument{
\renewenvironment*{theindex}{%
    \imki@maybeaddtotoc
     \imki@indexlevel{\indexname}
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

Update to the new defaults:

```
\imki@resetdefaults
```

Update to the new patches:

\AtBeginDocument is because \@wrindex is previously defined as \AtBeginDocument in the lwarp core.

```
\ifimki@splitindex
  \let\imki@startidx\imki@startidxunique
  \AtBeginDocument{\let\@wrindex\imki@wrindexunique}
  \let\imki@putindex\imki@putindexunique
  \let\imki@wrindexentry\imki@wrindexentryunique
  \let\imki@startidxsplit\@undefined
  \let\imki@wrindexsplit\@undefined
  \let\imki@putindexsplit\@undefined
\else
  \let\imki@startidx\imki@startidxsplit
  \AtBeginDocument{\let\@wrindex\imki@wrindexsplit}
  \let\imki@putindex\imki@putindexsplit
  \let\imki@wrindexentry\imki@wrindexentrysplit
  \let\imki@startidxunique\@undefined
  \let\imki@wrindexunique\@undefined
  \let\imki@putindexunique\@undefined
\fi
```

File 180 **lwarp-index.sty**

§ 277 Package index

(*Emulates or patches code by* David M. Jones.)

Pkg index

index is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{index}[2004/01/20]
```

Use \theLWR@autoindex instead of \thepage. \@tempswatrue is used to force an immediate write to the index file instead of waiting until the end of the page.

```
\xpatchcmd{\newindex}
    {\x@newindex[thepage]}
    {%
        \@tempswatrue%
        \x@newindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{newindex}}

\xpatchcmd{\renewindex}
    {\x@renewindex[thepage]}
    {%
        \@tempswatrue%
        \x@renewindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{renewindex}}
```

Patched to set a new autoindex:

```
\xpatchcmd{\@wrindex}
    {\begingroup}
    {%
        \addtocounter{LWR@autoindex}{1}%                    lwarp
        \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
        \begingroup%
    }
    {}
    {\LWR@patcherror{index}{@wrindex}}
```

\AtBeginDocument lwarp core \lets \@wrindex to \LWR@wrindex. Since the index package has been loaded, \let to its version instead:

```
\let\LWR@index@wrindex\@wrindex

\AtBeginDocument{
\let\@wrindex\LWR@index@wrindex
}
```

Modified to add \index@prologue:

```
\AtBeginDocument{
\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \ifx\index@prologue\@empty\else
        \index@prologue
        \bigskip
    \fi
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
```

```
}% AtBeginDocument
```

Disabled:

```
\def\@showidx#1{}
\let\@texttop\relax
\renewcommand*{\raggedbottom}{}
\renewcommand*{\flushbottom}{}
\renewcommand*{\markboth}[2]{}
\renewcommand*{\markright}[1]{}
```

File 181 **lwarp-intopdf.sty**

§ 278 Package intopdf

Pkg intopdf intopdf is emulated.

The MIME type and description are ignored for now.

for HTML output:

```
\LWR@ProvidesPackageDrop{intopdf}[2018/03/15]
```

```
\NewDocumentCommand{\attachandlink}{m o m m}{%
    \href{#1}{#4}%
}
```

File 182 **lwarp-karnaugh-map.sty**

§ 279 Package karnaugh-map

(*Emulates or patches code by* Mattias Jacobsson.)

Pkg karnaugh-map karnaugh-map is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{karnaugh-map}[2017/02/20]
```

(It is hard to patch this macro, so the entire thing is redefined here, with the lwarp modificaitions identified in comments.)

```
\RenewDocumentEnvironment{karnaugh-map}{s O{4} O{4} O{1} O{$X_1X_0$} O{$X_3X_2$} O{$X_5X_4$}} {%
  \begingroup
    % store map size {[START]
      \renewcommand{\@karnaughmap@var@mapsizex@}{#2}%
      \renewcommand{\@karnaughmap@var@mapsizey@}{#3}%
      \renewcommand{\@karnaughmap@var@mapsizez@}{#4}%
    % [END]}
    % determinate if markings should be color or black and white
    \IfBooleanTF{#1}{%
      % should be black and white
      \renewcommand{\@karnaughmap@var@bw@}{1}%
```

```
}{%
  % should be color
  \renewcommand{\@karnaughmap@var@bw@}{0}%
}%
%
% find matching matrix template and alignment parameters {[START]
\newcommand{\@karnaughmap@local@matrixtemplate@}{0}% '0' is considered as missing matrix template
  \newcommand{\@karnaughmap@local@maprealignmentx@}{0}%
  \newcommand{\@karnaughmap@local@maprealignmenty@}{0}%
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=221
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
              \&                  0 \&                  1 \& \phantom{0} \\
          0 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&         \\
          1 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&         \\
    \phantom{0}  \&                    \&                    \&          \\
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=241
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
              \&                  0 \&                  1 \& \phantom{00} \\
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&         \\
         01 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&         \\
         11 \& |(000110)| \phantom{0} \& |(000111)| \phantom{0} \&         \\
         10 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \&         \\
    \phantom{00} \&                    \&                    \&          \\
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=421
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&              00 \&              01 \&              11 \&              10 \& \phanto
         0  \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
         1  \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
   \phantom{00} \&                \&                \&                \&                \&
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=441
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&              00 \&              01 \&              11 \&              10 \& \phanto
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(0000
         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(0001
         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(0011
         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(0010
   \phantom{00} \&                \&                \&                \&                \&
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=442
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
             \&              00 \&              01 \&              11 \&              10 \& \phanto
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(0000
         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(0001
         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(0011
         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(0010
   \phantom{00} \&                \&                \&                \&                \&
    }%
    \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
```

```
      \fi
    \ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=444
        \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
                \&               00 \&               01 \&               11 \&               10 \& \phanto
             00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(0000
             01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(0001
             11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(0011
             10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(0010
      \phantom{00} \&                 \&                 \&                 \&                 \&
             00 \& |(100000)| \phantom{0} \& |(100001)| \phantom{0} \& |(100011)| \phantom{0} \& |(1000
             01 \& |(100100)| \phantom{0} \& |(100101)| \phantom{0} \& |(100111)| \phantom{0} \& |(1001
             11 \& |(101100)| \phantom{0} \& |(101101)| \phantom{0} \& |(101111)| \phantom{0} \& |(1011
             10 \& |(101000)| \phantom{0} \& |(101001)| \phantom{0} \& |(101011)| \phantom{0} \& |(1010
      \phantom{00} \&                 \&                 \&                 \&                 \&
        }%
        \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
        \renewcommand{\@karnaughmap@local@maprealignmenty@}{-2.5}%
      \fi
    % [END]}
  % test if a matrix template is found or not(aka "\@karnaughmap@local@matrixtemplate@" equals to '0')
    \ifdefstring{\@karnaughmap@local@matrixtemplate@}{0}{%  lwarp
%     \ifnum0=\@karnaughmap@local@matrixtemplate@%  original
      % print error if no template could be found
      \PackageError{karnaugh-map}{%
     Can not find a template fitting your specification (\@karnaughmap@var@mapsizex@\space x \@karnaughma
      }{%
     Existing templates have the following dimensions: 2x2x1, 2x4x1, 4x2x1, 4x4x1, 4x4x2, and 4x4x4.
      }%
%     \fi   original
    }{}%    lwarp
    \begin{tikzpicture}
      % grid
      % for all dimensions
    \draw[color=black, ultra thin] (0,0) grid (\@karnaughmap@var@mapsizex@,\@karnaughmap@var@mapsizey@);
      % when there are 2 sub maps
      \ifnum\@karnaughmap@var@mapsizez@=2
        \draw[color=black, ultra thin] (5,0) grid (9,4);
      \fi
      % when there are 4 sub maps
      \ifnum\@karnaughmap@var@mapsizez@=4
        \draw[color=black, ultra thin] (5,0) grid (9,4);
        \draw[color=black, ultra thin] (0,-5) grid (4,-1);
        \draw[color=black, ultra thin] (5,-5) grid (9,-1);
      \fi
      % labels
      % for all dimensions
    \node[above] at (\@karnaughmap@var@mapsizex@*0.5,\@karnaughmap@var@mapsizey@+0.9) {\small{#5}};
      \node[left] at (-0.9,\@karnaughmap@var@mapsizey@*0.5) {\small{#6}};
      % when there are 2 sub maps
      \ifnum\@karnaughmap@var@mapsizez@=2
        \node[above] at (7,4.9) {\small{#5}};
        % extra sub maps labels
        \node[below] at (2,-0.1) {\small{#7$=0$}};
        \node[below] at (7,-0.1) {\small{#7$=1$}};
      \fi
```

```
      % when there are 4 sub maps
      \ifnum\@karnaughmap@var@mapsizez@=4
        \node[above] at (7,4.9) {\small{#5}};
        \node[left] at (-0.9,-3) {\small{#6}};
        % extra sub maps labels
        \node[below] at (2,-0.1) {\small{#7$=00$}};
        \node[below] at (7,-0.1) {\small{#7$=01$}};
        \node[below] at (2,-5.1) {\small{#7$=10$}};
        \node[below] at (7,-5.1) {\small{#7$=11$}};
      \fi
      % data
      \matrix[
        matrix of nodes,
        ampersand replacement=\&,
        column sep={1cm,between origins},
        row sep={1cm,between origins},
    ] at (\@karnaughmap@var@mapsizex@*0.5+\@karnaughmap@local@maprealignmentx@,\@karnaughmap@var@mapsiz
        \@karnaughmap@local@matrixtemplate@%
      };
}{
    \end{tikzpicture}
  \endgroup
}
```

File 183 **lwarp-keyfloat.sty**

§ 280 Package

keyfloat

(*Emulates or patches code by* Brian Dunn.)

Pkg keyfloat

keyfloat is supported with a considerable amount of hacking. (It's a mashup of lwarp, keyfloat, and tocdata.)

⚠ keywrap

If placing a `\keyfig[H]` inside a keywrap, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the `lw` option.)

for HTML output:

```
\LWR@ProvidesPackagePass{keyfloat}[2019/03/21]

\@ifpackagelater{keyfloat}{2019/03/21}{}{
    \PackageError{lwarp-keyfloat}
    {%
        The keyfloat package is out of date.\MessageBreak
        Update to keyfloat v2.00 2019/03/21 or later%
    }
    {%
        Please update the keyfloat package.  It's worth it!%
    }
}
```

After keyfloat has loaded:

```
\AtBeginDocument{
```

```
\providecommand*{\KFLT@LWR@hook@boxouter}{}
\renewcommand*{\KFLT@LWR@hook@boxouter}{%
    \ifbool{KFLT@keywrap}{}{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
            \setlength{\textheight}{9in}%
        }{}%
    }%
}

\let\KFLT@LWR@hook@boxouter@minipage\relax
\let\endKFLT@LWR@hook@boxouter@minipage\relax
\newenvironment*{KFLT@LWR@hook@boxouter@minipage}[2][]{}{}

\providecommand*{\KFLT@LWR@hook@keysubfloats}{}
\renewcommand*{\KFLT@LWR@hook@keysubfloats}{%
    \ifbool{KFLT@keywrap}{}{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
            \setlength{\textheight}{9in}%
        }{}%
    }%
}

\let\KFLT@LWR@hook@keyfloatsminipage\relax
\let\endKFLT@LWR@hook@keyfloatsminipage\relax
\newenvironment*{KFLT@LWR@hook@keyfloatsminipage}[1]{}{}

\providecommand*{\KFLT@LWR@hook@keyfloats}{}
\renewcommand*{\KFLT@LWR@hook@keyfloats}{%
    \ifbool{KFLT@keywrap}{}{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
            \setlength{\textheight}{9in}%
        }{}%
    }%
}

\renewcommand*{\KFLT@maybeendfloatrow}{%
    \ifnumless{\value{KFLT@thiscol}}{\value{KFLT@numcols}}%
    {}% thiscol < numcols
    {% >=
        \defcounter{KFLT@thiscol}{0}%
    }%
}%

\renewcommand{\KFLT@trackrows}%
{%
```

If are nested inside a keyfloats or a subfloat:

```
    \ifboolexpr{%
```

```
        test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or%
        bool{KFLT@inkeysubfloats}%
    }%
    {% nested
```

Tracks row start and end:

```
        \KFLT@maybestartfloatrow%
```

Possibly fill space between columns:

```
        \ifnumgreater{\value{KFLT@thiscol}}{1}%
            {%
%                   \hfill%
            }%
            {}%
    }% nested
    {}% not nested
}
```

```
\RenewDocumentCommand{\KFLT@onefigureimage}{m}
{%
\LWR@traceinfo{KFLT@onefigureimage}%
% \begin{lrbox}{\KFLT@envbox}%
\ifthenelse{\NOT\equal{\KFLT@lw}{}}%
    {%
        \KFLT@frame{\includegraphics%
        [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
    }%
    {% not linewidth
        \ifthenelse{\dimtest{\KFLT@w}{>}{0pt}}%
        {% width is given
            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
            {% w and h
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,%
                width=\KFLT@imagewidth,height=\KFLT@h]{#1}}%
            }% w and h
            {% only w
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
            }% only w
        }% width is given
        {% width is not given
            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
            {%
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,height=\KFLT@h]{#1}}%
            }%
            {%
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s]{#1}}%
            }%
        }% width is not given
    }% not linewidth
```

```
% \end{lrbox}%
% \unskip%
% \KFLT@findenvboxwidth%
% \begin{turn}{\KFLT@r}%
% \KFLT@frame{\usebox{\KFLT@envbox}}%
% \unskip%
% \end{turn}%
\LWR@traceinfo{KFLT@onefigureimage: done}%
}

\RenewDocumentEnvironment{KFLT@boxinner}{}
{%
    \LWR@traceinfo{KFLT@boxinner}%
    \LWR@stoppars%
    \minipagefullwidth%
    \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{
        \fminipage{\KFLT@imagewidth}%
    }{%
        \minipage{\KFLT@imagewidth}%
    }%
}
{%
    \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{
        \endfminipage%
    }{%
        \endminipage%
    }%
    \LWR@startpars%
    \LWR@traceinfo{KFLT@boxinner: done}%
}

\newcommand*{\LWR@KFLT@settextalign}[1]{%
    \def\LWR@KFLT@textalign{justify}%
    \ifcsstring{KFLT@#1textalign}{\centering}%
        {\def\LWR@KFLT@textalign{center}}%
        {}%
    \ifcsstring{KFLT@#1textalign}{\raggedleft}%
        {\def\LWR@KFLT@textalign{right}}%
        {}%
    \ifcsstring{KFLT@#1textalign}{\raggedright}%
        {\def\LWR@KFLT@textalign{left}}%
        {}%
}

\renewcommand{\KFLT@addtext}[1]
{%
```

Is there text to add?

```
    \ifcsempty{KFLT@#1t}%
    {}% no text
    {% text to add
        {% local
```

Add some space, then create a full-width minipage to contain the text:

```
        \addvspace{\smallskipamount}%
        \LWR@KFLT@settextalign{#1}%
        \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%
```

Set the alignment and some text parameters:

```
%         \csuse{KFLT@#1textalign}%
%         \footnotesize%
        \setlength{\parskip}{1.5ex}%
        \setlength{\parindent}{0em}%
```

Typeset the actual text:

```
        \csuse{KFLT@#1t}%
```

Close it all out with a little more space:

```
        \end{BlockClass}%
%         \par\addvspace{2ex}%
        }% local
    }% text to add
}

\@ifpackageloaded{tocdata}
{}
{% tocdata not loaded

    \newcommand*{\LWR@KFLT@setnamealign}[1]{%
        \def\LWR@KFLT@textalign{justify}%
        \ifstrequal{#1}{\centering}%
            {\def\LWR@KFLT@textalign{center}}%
            {}%
        \ifstrequal{#1}{\raggedleft}%
            {\def\LWR@KFLT@textalign{right}}%
            {}%
        \ifstrequal{#1}{\raggedright}%
            {\def\LWR@KFLT@textalign{left}}%
            {}%
    }

    \renewcommand*{\KFLT@@addartisttext}[3]{%

```

Add space and create the name inside a full-width minipage:

```
%         \addvspace{\medskipamount}%
    %     \begin{minipage}{\linewidth}%
        \LWR@KFLT@setnamealign{#3}%
        \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%

```

Text alignment is #3, and depends on artist or author:

```
    %     #3%

```

#1 is empty or 'subgrp'
#2 is empty for artist, 'u' for author:

```
        \footnotesize\textsc{%
            \KFLT@optionalname{\csuse{KFLT@#1a#2p}}%
            \KFLT@optionalname{\csuse{KFLT@#1a#2f}}%
            \csuse{KFLT@#1a#2l}%
            \csuse{KFLT@#1a#2s}%
        }%
    %     \end{minipage}%
        \end{BlockClass}
%         \par\addvspace{2ex}%
    }

}% tocdata not loaded
```

```
\DeclareDocumentEnvironment{KFLT@marginfloat}{O{-1.2ex} m}
{%
    \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
    \captionsetup{type=#2}%
    \minipage{2in}%
}
{%
    \endminipage%
    \endLWR@BlockClassWP%
}
```

```
\DeclareDocumentEnvironment{marginfigure}{o}
    {\begin{KFLT@marginfloat}{figure}}
    {\end{KFLT@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
    {\begin{KFLT@marginfloat}{table}}
    {\end{KFLT@marginfloat}}
```

```
\DeclareDocumentEnvironment{keywrap}{m +m}
{%
    \LWR@ensuredoingapar%
    \setlength{\linewidth}{6in}%
    \setlength{\LWR@templengthone}{#1}%
    \begin{LWR@BlockClassWP}%
        {%
         float:right; width:\LWR@printlength{\LWR@templengthone};  % extra space
            margin:10pt%
        }%
        {%
            width:\LWR@printlength{\LWR@templengthone}%
        }%
        {marginblock}%
    \setlength{\linewidth}{.95\LWR@templengthone}%
    \booltrue{KFLT@keywrap}%
```

```
    #2%
    \end{LWR@BlockClassWP}%
}
{}

}% AtBeginDocument
```

File 184 **lwarp-layaureo.sty**

§ 281 Package

layaureo

Pkg layaureo

layaureo is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{layaureo}[2004/09/16]
```

File 185 **lwarp-layout.sty**

§ 282 Package

layout

Pkg layout

layout is ignored.

for HTML output:

Discard all options for lwarp-layout:

```
\LWR@ProvidesPackageDrop{layout}[2014/10/28]

\NewDocumentCommand{\layout}{s}{}
```

File 186 **lwarp-layouts.sty**

§ 283 Package

layouts

Pkg layouts

layouts is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{layouts}[2009/09/02]

\newif\ifoddpagelayout
  \oddpagelayouttrue
\newif\iftwocolumnlayout
  \twocolumnlayoutfalse
\newif\ifdrawmarginpars
  \drawmarginparstrue
\newif\ifdrawparameters
  \drawparameterstrue
\newif\iflistaspara
  \listasparatrue
\newif\ifruninhead
```

```
  \runinheadfalse
\newif\ifprintparameters
  \printparameterstrue
\newif\ifdrawdimensions
  \drawdimensionsfalse
\newif\ifprintheadings
  \printheadingstrue
\newcommand{\testdrawdimensions}{}
\newcommand{\testprintparameters}{}
\newcommand{\setlabelfont}[1]{}
\newcommand{\setparametertextfont}[1]{}
\newcommand{\setvaluestextsize}[1]{}
\newcommand{\setlayoutscale}[1]{}
\newcommand{\setuplayouts}{}
\newcommand{\printinunitsof}[1]{}
\newcommand{\prntlen}[1]{}
\newcommand{\trypaperwidth}[1]{}
\newcommand{\trypaperheight}[1]{}
\newcommand{\tryhoffset}[1]{}
\newcommand{\tryvoffset}[1]{}
\newcommand{\trytopmargin}[1]{}
\newcommand{\tryheadheight}[1]{}
\newcommand{\tryheadsep}[1]{}
\newcommand{\trytextheight}[1]{}
\newcommand{\tryfootskip}[1]{}
\newcommand{\tryoddsidemargin}[1]{}
\newcommand{\tryevensidemargin}[1]{}
\newcommand{\trytextwidth}[1]{}
\newcommand{\trymarginparsep}[1]{}
\newcommand{\trymarginparwidth}[1]{}
\newcommand{\trymarginparpush}[1]{}
\newcommand{\trycolumnsep}[1]{}
\newcommand{\trycolumnseprule}[1]{}
\newcommand{\setfootbox}[2]{}
\newcommand{\currentpage}{}
\newcommand{\drawpage}{(draw page)}
\newcommand{\pagediagram}{(page diagram)}
\newcommand{\pagedesign}{(page design)}
\newcommand{\pagevalues}{(page values)}
\newcommand{\trystockwidth}[1]{}
\newcommand{\trystockheight}[1]{}
\newcommand{\trytrimedge}[1]{}
\newcommand{\trytrimtop}[1]{}
\newcommand{\tryuppermargin}[1]{}
\newcommand{\tryspinemargin}[1]{}
\newcommand{\currentstock}{}
\newcommand{\drawstock}{(draw stock)}
\newcommand{\stockdiagram}{(stock diagram)}
\newcommand{\stockdesign}{(stock design)}
\newcommand{\stockvalues}{(stock values)}
\newcommand{\tryitemindent}[1]{}
\newcommand{\trylabelwidth}[1]{}
\newcommand{\trylabelsep}[1]{}
\newcommand{\tryleftmargin}[1]{}
\newcommand{\tryrightmargin}[1]{}
```

```
\newcommand{\trylistparindent}[1]{}
\newcommand{\trytopsep}[1]{}
\newcommand{\tryparskip}[1]{}
\newcommand{\trypartopsep}[1]{}
\newcommand{\tryparsep}[1]{}
\newcommand{\tryitemsep}[1]{}
\newcommand{\currentlist}{}
\newcommand{\drawlist}{(draw list)}
\newcommand{\listdiagram}{(list diagram)}
\newcommand{\listdesign}{(list design)}
\newcommand{\listvalues}{(list values)}
\newcommand{\tryfootins}[1]{}
\newcommand{\tryfootnotesep}[1]{}
\newcommand{\tryfootnotebaseline}[1]{}
\newcommand{\tryfootruleheight}[1]{}
\newcommand{\tryfootrulefrac}[1]{}
\newcommand{\currentfootnote}{}
\newcommand{\drawfootnote}{(draw footnote)}
\newcommand{\footnotediagram}{(footnote diagram)}
\newcommand{\footnotedesign}{(footnote design)}
\newcommand{\footnotevalues}{(footnote values)}
\newcommand{\tryparindent}[1]{}
\newcommand{\tryparlinewidth}[1]{}
\newcommand{\tryparbaselineskip}[1]{}
\newcommand{\currentparagraph}{}
\newcommand{\drawparagraph}{(draw paragraph)}
\newcommand{\paragraphdiagram}{(paragraph diagram)}
\newcommand{\paragraphdesign}{(paragraph design)}
\newcommand{\paragraphvalues}{(paragraph values)}
\newcommand{\trybeforeskip}[1]{}
\newcommand{\tryafterskip}[1]{}
\newcommand{\tryindent}[1]{}
\newcommand{\currentheading}{}
\newcommand{\drawheading}[1]{(draw heading)}
\newcommand{\headingdiagram}[1]{(heading diagram)}
\newcommand{\headingdesign}[1]{(heading design)}
\newcommand{\headingvalues}{(heading values)}
\newcommand{\trytextfloatsep}[1]{}
\newcommand{\tryfloatsep}[1]{}
\newcommand{\tryintextsep}[1]{}
\newcommand{\trytopfigrule}[1]{}
\newcommand{\trybotfigrule}[1]{}
\newcommand{\currentfloat}{}
\newcommand{\drawfloat}{(draw float)}
\newcommand{\floatdiagram}{(float diagram)}
\newcommand{\floatdesign}{(float design)}
\newcommand{\floatvalues}{(float values)}
\newcommand{\trytotalnumber}[1]{}
\newcommand{\trytopnumber}[1]{}
\newcommand{\trybottomnumber}[1]{}
\newcommand{\trytopfraction}[1]{}
\newcommand{\trytextfraction}[1]{}
\newcommand{\trybottomfraction}[1]{}
\newcommand{\currentfloatpage}{}
\newcommand{\drawfloatpage}{(draw floatpage)}
```

```
\newcommand{\floatpagediagram}{(floatpage diagram)}
\newcommand{\floatpagedesign}{(floatpage design)}
\newcommand{\floatpagevalues}{(floatpage values)}
\newcommand{\trytocindent}[1]{}
\newcommand{\trytocnumwidth}[1]{}
\newcommand{\trytoclinewidth}[1]{}
\newcommand{\trytocrmarg}[1]{}
\newcommand{\trytocpnumwidth}[1]{}
\newcommand{\trytocdotsep}[1]{}
\newcommand{\currenttoc}{}
\newcommand{\drawtoc}{(draw toc)}
\newcommand{\tocdiagram}{(toc diagram)}
\newcommand{\tocdesign}{(toc design)}
\newcommand{\tocvalues}{(toc values)}
\newcommand{\drawaspread}[8][0]{(a spread)}
\newcommand{\drawfontframe}[1]{(font frame)}
\newcommand{\drawfontframelabel}[1]{}
```

File 187 **lwarp-leading.sty**

§ 284 Package leading

Pkg leading

leading is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{leading}[2008/12/11]
```

```
\newcommand\leading[1]{}
```

File 188 **lwarp-letterspace.sty**

§ 285 Package letterspace

(*Emulates or patches code by* R Schlicht.)

Pkg letterspace

letterspace is a subset of microtype, which is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output: Discard all options for lwarp-letterspace:

```
\LWR@ProvidesPackageDrop{letterspace}[2018/01/14]
```

```
\newcommand*\lsstyle{}
\newcommand\textls[2][]{}
\def\textls#1#{}
\newcommand*\lslig[1]{#1}
```

File 189 **lwarp-lettrine.sty**

§ 286 Package

lettrine

(*Emulates or patches code by* Daniel Flipo.)

Pkg lettrine Emulated.

for HTML output: Discard all options for lwarp-lettrine:

```
\LWR@ProvidesPackageDrop{lettrine}[2018-08-28]
```

The initial letter is in a of class `lettrine`, and the following text is in a of class `lettrinetext`. `\lettrine` [⟨*keys*⟩] {⟨*letter*⟩} {⟨*additional text*⟩}

```
\DeclareDocumentCommand{\lettrine}{o m m}{%
\InlineClass{lettrine}{#2}\InlineClass{lettrinetext}{#3} % extra space
}

\newcounter{DefaultLines}
\setcounter{DefaultLines}{2}
\newcounter{DefaultDepth}
\newcommand*{\DefaultOptionsFile}{\relax}
\newcommand*{\DefaultLoversize}{0}
\newcommand*{\DefaultLraise}{0}
\newcommand*{\DefaultLhang}{0}
\newdimen\DefaultFindent
\setlength{\DefaultFindent}{\z@}
\newdimen\DefaultNindent
\setlength{\DefaultNindent}{0.5em}
\newdimen\DefaultSlope
\setlength{\DefaultSlope}{\z@}
\newdimen\DiscardVskip
\setlength{\DiscardVskip}{0.2\p@}
\newif\ifLettrineImage
\newif\ifLettrineOnGrid
\newif\ifLettrineRealHeight

\newcommand*{\LettrineTextFont}{\scshape}
\newcommand*{\LettrineFontHook}{}
\newcommand*{\LettrineFont}[1]{\InlineClass{lettrine}{#1}}
\newcommand*{\LettrineFontEPS}[1]{\includegraphics[height=1.5ex]{#1}}
```

File 190 **lwarp-lineno.sty**

§ 287 Package

lineno

(*Emulates or patches code by* Stephan I. Böttcher.)

Pkg lineno lineno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lineno}[2005/11/02]

\newcommand*\resetlinenumber[1][\@ne]{}

\def\linenumbers{%
     \@ifnextchar[{\resetlinenumber}%]
                  {\@ifstar{\resetlinenumber}{}}%
     }

\newcommand*{\nolinenumbers}{}

\@namedef{linenumbers*}{\par\linenumbers*}
\@namedef{runninglinenumbers*}{\par\runninglinenumbers*}

\def\endlinenumbers{\par}
\let\endrunninglinenumbers\endlinenumbers
\let\endpagewiselinenumbers\endlinenumbers
\expandafter\let\csname endlinenumbers*\endcsname\endlinenumbers
\expandafter\let\csname endrunninglinenumbers*\endcsname\endlinenumbers
\let\endnolinenumbers\endlinenumbers

\def\pagewiselinenumbers{\linenumbers\setpagewiselinenumbers}

\def\runninglinenumbers{\setrunninglinenumbers\linenumbers}

\def\setpagewiselinenumbers{}

\def\setrunninglinenumbers{}

\def\linenomath{}%
\@namedef{linenomath*}{}%
\def\endlinenomath{}
\expandafter\let\csname endlinenomath*\endcsname\endlinenomath

\let\linelabel\label

\def\switchlinenumbers{\@ifstar{}{}}
\def\setmakelinenumbers#1{\@ifstar{}{}}

\def\leftlinenumbers{\@ifstar{}{}}
\def\rightlinenumbers{\@ifstar{}{}}

\newcounter{linenumber}
\newcount\c@pagewiselinenumber
\let\c@runninglinenumber\c@linenumber

\def\runningpagewiselinenumbers{}
\def\realpagewiselinenumbers{}


\NewDocumentCommand\modulolinenumbers{s o}{}

\chardef\c@linenumbermodulo=5
```

```
\modulolinenumbers[1]

\newcommand*\firstlinenumber[1]{}

\newcommand\internallinenumbers{}
\let\endinternallinenumbers\endlinenumbers
\@namedef{internallinenumbers*}{\internallinenumbers*}
\expandafter\let\csname endinternallinenumbers*\endcsname\endlinenumbers

\newcommand*{\linenoplaceholder}[1]{% redefine per language
    (line number reference for \detokenize\expandafter{#1})
}

\newcommand*{\lineref}[2][]{\linenoplaceholder{#2}}
\newcommand*{\linerefp}[2][]{\linenoplaceholder{#2}}
\newcommand*{\linerefr}[2][]{\linenoplaceholder{#2}}

\newcommand\quotelinenumbers
   {\@ifstar\linenumbers{\@ifnextchar[\linenumbers{\linenumbers*}}}

\newdimen\linenumbersep
\newdimen\linenumberwidth
\newdimen\quotelinenumbersep

\quotelinenumbersep=\linenumbersep
\let\quotelinenumberfont\linenumberfont

\def\linenumberfont{\normalfont\tiny\sffamily}


\linenumberwidth=10pt
\linenumbersep=10pt

\def\thelinenumber{}

\def\LineNumber{}
\def\makeLineNumber{}
\def\makeLineNumberLeft{}
\def\makeLineNumberRight{}
\def\makeLineNumberOdd{}
\def\makeLineNumberEven{}
\def\makeLineNumberRunning{}


\newenvironment{numquote}     {\quote}{\endquote}
\newenvironment{numquotation} {\quotation}{\endquotation}
\newenvironment{numquote*}    {\quote}{\endquote}
\newenvironment{numquotation*}{\quotation}{\endquotation}

\newdimen\bframerule
\bframerule=\fboxrule

\newdimen\bframesep
\bframesep=\fboxsep

```

```
\newenvironment{bframe}
{%
    \LWR@forceminwidth{\bframerule}%
    \BlockClass[
        border:\LWR@printlength{\LWR@atleastonept} solid black ; %
        padding:\LWR@printlength{\bframesep}%
    ]{bframe}
}
{\endBlockClass}
```

File 191 **lwarp-lips.sty**

§ 288 Package

lips

(*Emulates or patches code by* Matt Swift.)

Pkg lips lips is emulated.

```
% \LWR@ProvidesPackageDrop{lips}
\PackageInfo{lwarp}{Using the lwarp version of package ‘lips’.}%
\ProvidesPackage{lwarp-lips}[2001/08/31]

\NewDocumentCommand{\Lips}{}{\textellipsis}

\NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}

\let\lips\Lips
\let\olips\lips

\DeclareOption*{}
\DeclareOption{mla}{
\let\lips\BracketedLips
}
\ProcessOptions\relax

\newcommand \LPNobreakList {}
```

File 192 **lwarp-listings.sty**

§ 289 Package

listings

(*Emulates or patches code by* Carsten Heinz, Brooks Moses, Jobst Hoffmann.)

Pkg listings listings is supported with some limitations. Text formatting is not yet supported.

for HTML output:

```
\begin{warpHTML}
```

```
\LWR@ProvidesPackagePass{listings}[2018/09/02]
```

Force flexible columns. Fixed columns inserts spaces in the PDF output.

```
\lst@column@flexible
```

Patches to embed listings inside pre tags:

```
\let\LWR@origlst@Init\lst@Init
\let\LWR@origlst@DeInit\lst@DeInit

\let\LWR@origlsthkEveryPar\lsthk@EveryPar

\renewcommand{\l@lstlisting}[2]{\hypertocfloat{1}{lstlisting}{lol}{#1}{#2}}
```

\lstset {⟨*options*⟩}

Use the listings `literate` option to replace HTML entities:

```
\def\lstset@#1{\endgroup%
%  \ifx\@empty#1%
%         \@empty%
%     \else%
        \setkeys{lst}{%
            #1%
            ,literate=%
            {<}{\HTMLentity{lt}}{4}%
            {>}{\HTMLentity{gt}}{4}%
            {\&}{\HTMLentity{amp}}{5}%
        }%
%     \fi%
}
```

\lst@Init {⟨*backslash-processing*⟩} Done at the start of a listing.

```
\renewcommand{\lst@Init}[1]{%
```

Perform the listings initialization:

```
\LWR@traceinfo{lst@Init}%
\renewcommand*{\@captype}{lstlisting}%
\let\lst@aboveskip\z@\let\lst@belowskip\z@%
\gdef\lst@boxpos{t}%
\let\lst@frame\@empty
    \let\lst@frametshape\@empty
    \let\lst@framershape\@empty
    \let\lst@framebshape\@empty
    \let\lst@framelshape\@empty
\lstframe@\lst@frameround ffff\relax%
\lst@multicols\@empty%
\LWR@origlst@Init{#1}\relax%
```

Avoids extra horizontal space:

```
\def\lst@framelr{}%
```

```
\LWR@traceinfo{finished origlst@Init}%
\lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the <pre>, then reenable line numbers.

```
\LWR@traceinfo{About to create verbatim.}%
\let\lsthk@EveryPar\relax%
\LWR@forcenewpage
\LWR@atbeginverbatim{2}{programlisting}%

\let\lsthk@EveryPar\LWR@origlsthkEveryPar%
\else%
```

Inline, so open a :

```
\ifbool{LWR@verbtags}{\LWR@htmltag{span class="inlineprogramlisting"}}{}%
\fi%
}

```

\lst@DeInit Done at the end of a listing.

```
\renewcommand*{\lst@DeInit}{%
\lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```
\let\lsthk@EveryPar\relax%
\LWR@afterendverbatim{0}%
\let\lsthk@EveryPar\LWR@origlsthkEveryPar%
\else%
```

Inline, so create the closing :

```
\ifbool{LWR@verbtags}{\noindent\LWR@htmltag{/span}}{}%
\fi%
```

Final listings deinit:

```
\LWR@origlst@DeInit%
}
```

\lst@MakeCaption {⟨*t/b*⟩}

This is called BOTH at the top and at the bottom of each listing.

Patched for lwarp.

```
\def\lst@MakeCaption#1{%
\LWR@traceinfo{MAKING CAPTION at #1}%
  \lst@ifdisplaystyle
\LWR@traceinfo{making a listings display caption}%
    \ifx #1t%
         \ifx\lst@@caption\@empty\expandafter\lst@HRefStepCounter \else
                                  \expandafter\refstepcounter
         \fi {lstlisting}%
\LWR@traceinfo{About to assign label: !\lst@label!}%
%         \ifx\lst@label\@empty\else
% \label{\lst@label}\fi
\LWR@traceinfo{Finished assigning the label.}%
```

```
        \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
        \global\let\lst@name\lst@arg \global\let\lstname\lst@name
        \lst@ifnolol\else
            \ifx\lst@@caption\@empty
                \ifx\lst@caption\@empty
                    \ifx\lst@intname\@empty \else \def\lst@temp{ }%
                    \ifx\lst@intname\lst@temp \else
```

This code places a contents entry for a non-float. This would have to be modified for lwarp:

```
\LWR@traceinfo{addcontents lst@name: -\lst@name-}%
%                           \addcontentsline{lol}{lstlisting}{\lst@name}
                    \fi\fi
                \fi
            \else
```

This would have to be modified for lwarp:

```
\LWR@traceinfo{addcontents lst@@caption: -\lst@@caption-}%
                 \addcontentsline{lol}{lstlisting}%
{\protect\numberline{\thelstlisting}%
{\protect\ignorespaces \LWR@isolate{\lst@@caption} \protect\relax}}%
            \fi
         \fi
     \fi
    \ifx\lst@caption\@empty\else
\LWR@traceinfo{lst@caption not empty-}%
        \lst@IfSubstring #1\lst@captionpos
            {\begingroup
\LWR@traceinfo{at the selected position}%
```

These space and box commands are not needed for HTML output:

```
%              \let\@@vskip\vskip
%              \def\vskip{\afterassignment\lst@vskip \@tempskipa}%
%              \def\lst@vskip{\nobreak\@@vskip\@tempskipa\nobreak}%
%              \par\@parboxrestore\normalsize\normalfont % \noindent (AS)
%              \ifx #1t\allowbreak \fi
             \ifx\lst@title\@empty
```

New lwarp code to create a caption:

```
                  \lst@makecaption\fnum@lstlisting{\ignorespaces \lst@caption}
             \else
```

New lwarp code to create a title:

```
%                  \lst@maketitle\lst@title % (AS)
\LWR@traceinfo{Making title: \lst@title}%
\begin{BlockClass}{lstlistingtitle}% lwarp
\lst@maketitle\lst@title% lwarp
\end{BlockClass}% lwarp
             \fi
\LWR@traceinfo{About to assign label: !\lst@label!}%
        \ifx\lst@label\@empty\else
\leavevmode% gets rid of bad space factor error
\GetTitleStringExpand{\lst@caption}%
\edef\LWR@lntemp{\GetTitleStringResult}%
\edef\@currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
```

```
\label{\lst@label}\fi
\LWR@traceinfo{Finished assigning the label.}%
```

Not needed for lwarp:

```
%              \ifx #1b\allowbreak \fi
             \endgroup}{}%
    \fi
\LWR@traceinfo{end of making a listings display caption}%
  \else
\LWR@traceinfo{INLINE}%
  \fi
\LWR@traceinfo{DONE WITH CAPTION at #1}%
}
```

line numbers Patched to keep left line numbers outside of the left margin, and place right line numbers in a field `\VerbatimHTMLWidth` wide.

```
\lst@Key{numbers}{none}{%
    \let\lst@PlaceNumber\@empty
    \lstKV@SwitchCases{#1}%
    {none:\\%
     left:\def\lst@PlaceNumber{%
```

For now, lwarp places left line numbers inline. Ideally the entire line would be moved to the right, but conflicts with list indenting occurs.

```
%         \LWR@origllap{
            \LWR@orignormalfont%
            \lst@numberstyle{\thelstnumber}\kern\lst@numbersep%
%         }
    }\\%
     right:\def\lst@PlaceNumber{\LWR@origrlap{\LWR@orignormalfont
                \kern 6in \kern\lst@numbersep
                \lst@numberstyle{\thelstnumber}}}%
    }{\PackageError{Listings}{Numbers #1 unknown}\@ehc}}

\end{warpHTML}
```

File 193 **`lwarp-listliketab.sty`**

§ 290 Package listliketab

Pkg `listliketab` listliketab is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{listliketab}[2005/01/09]

\newcommand*{\storestyleof}[1]{}
\newcommand*{\storeliststyle}{}
\newenvironment{listliketab}{}{}
```

File 194 **lwarp-lltjext.sty**

§ 291 Package

lltjext

(*Emulates or patches code by* The LuaTEX-ja project team.)

Pkg lltjext lltjext is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{lltjext}[2018/10/07]

\protected\def\yoko{%
  \directlua{luatexja.direction.set_list_direction(4, 'yoko')}%
}
\protected\def\tate{\yoko}
\protected\def\dtou{\yoko}
\protected\def\utod{\yoko}

\define@key[ltj]{japaram}{direction}{}

\yoko

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

File 195 **lwarp-longtable.sty**

§ 292 Package

longtable

(*Emulates or patches code by* David Carlisle.)

Pkg longtable longtable is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{longtable}[2014/10/28]
```

Use one of either \endhead or \endfirsthead for both print and HTML, and use a \warpprintonly macro to disable the other head phrase, and also the \endfoot and \endfirstfoot phrases. (See section 9.10.4 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{         % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced \noalign Use the \warpprintonly macro instead of the warpprint environment. Doing so helps avoid "Misplaced \noalign." when using \begin{warpprint}.

⚠ \kill \kill is ignored, place a \kill line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside \warpprintonly.

⚠ latexmage longtable is not supported inside a latexmage.

See:
http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable

Used to detect more than one of \endhead and \endfirsthead in use for HTML at the same time.

```
\newbool{LWR@longtable@havehead}
\boolfalse{LWR@longtable@havehead}
```

Env longtable * [⟨*horizalignment*⟩] {⟨*colspec*⟩} Emulates the longtable environment.

Per the caption package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options [c], [l], and [r] are ignored.

```
\newenvironment{longtable*}[2][]{%
\LWR@floatbegin{table}%
\setcaptiontype{\LTcaptype}%
\caption@setoptions{longtable}%
\caption@setoptions{@longtable}%
\caption@LT@setup%
\booltrue{LWR@starredlongtable}%
\boolfalse{LWR@longtable@havehead}%
\let\captionlistentry\LWR@LTcaptionlistentry%
\tabular{#2}
}
{\endtabular\LWR@floatend}

\newenvironment{longtable}[2][]{%
\LWR@floatbegin{table}%
\setcaptiontype{\LTcaptype}%
\caption@setoptions{longtable}%
\caption@setoptions{@longtable}%
\caption@LT@setup%
\refstepcounter{\LTcaptype}%
\boolfalse{LWR@longtable@havehead}%
\let\captionlistentry\LWR@LTcaptionlistentry%
\tabular{#2}
}
{\endtabular\LWR@floatend}
```

Provided for compatibility, but ignored:

```
\newcounter{LTchunksize}
```

Error for heads which should have been in `\warpprintonly`:

```
\newcommand*{\LWR@longtable@headerror}{%
    \PackageError{lwarp}
    {For longtable:\MessageBreak
    1: Keep either one of an \protect\endhead\space or
        \protect\endfirsthead\space\MessageBreak
        \space phrase as-is, to be used by both print and HTML.\MessageBreak
    2: Place any other \protect\end... phrases inside a\MessageBreak
        \space\protect\warpprintonly\space macro,
            to be ignored by HTML.\MessageBreak
    3: Add a final footer for HTML at the end of the table\MessageBreak
        \space inside a \protect\warpHTMLonly\space macro.
            This can be\MessageBreak
        \space a copy of an \protect\endfoot\space or
            \protect\endfirstfoot\space phrase,\MessageBreak
        \space but without the actual \protect\endfoot\space
            or \protect\endfirstfoot\MessageBreak
        \space macros.  If using threeparttablex, add\MessageBreak
        \space \protect\insertTableNotes\space here,
```

```
            optionally with\MessageBreak
        \space \protect\UseMinipageWidths\space in front.\MessageBreak
    See the lwarp documentation regarding longtables\MessageBreak
    and threeparttablex}
    {See the lwarp documentation regading longtables and threeparttablex.}
}
```

Error if more than one of `\endhead` or `\endfirsthead` is outside of `warpprintonly`.

```
\newcommand*{\LWR@longtable@maybeheaderror}{%
\ifbool{LWR@longtable@havehead}%
    {\LWR@longtable@headerror}%
    {%
        \booltrue{LWR@longtable@havehead}
        \LWR@tabularendofline% throws away options //[dim] and //*
    }%
}
```

Error if more than one of these is outside of `warpprint`.

```
\def\endhead{\LWR@longtable@maybeheaderror}
\def\endfirsthead{\LWR@longtable@maybeheaderror}
```

Error if ANY of these is outside of `warpprint`.

```
\def\endfoot{\LWR@longtable@headerror}
\def\endlastfoot{\LWR@longtable@headerror}
```

```
\providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
\LWR@formatted{tabularnewline}
```

```
\newcommand{\setlongtables}{}% Obsolete command, does nothing.
\newlength{\LTleft}
\newlength{\LTright}
\newlength{\LTpre}
\newlength{\LTpost}
\newlength{\LTcapwidth}
```

```
\LetLtxMacro\LWR@origkill\kill
\renewcommand*{\kill}{\LWR@tabularendofline}
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\kill\LWR@origkill%
}
```

File 196 **lwarp-lscape.sty**

§ 293 Package

lscape

(*Emulates or patches code by* D. P. Carlisle.)

Pkg `lscape` lscape is emulated.

for HTML output: Discard all options for lwarp-lscape.

```
\LWR@ProvidesPackageDrop{lscape}[2000/10/22]

\newenvironment*{landscape}{}{}
```

File 197 **lwarp-ltablex.sty**

§ 294 Package ltablex

(*Emulates or patches code by* Anil K. Goel.)

Pkg `ltablex` ltablex is emulated by lwarp.

for HTML output: Relies on tabularx.

```
\RequirePackage{tabularx}

\LWR@ProvidesPackageDrop{ltablex}[2014/08/13]

\DeclareDocumentEnvironment{tabularx}{m o m}
{\longtable{#3}}
{\endlongtable}

\DeclareDocumentEnvironment{tabularx*}{m o m}
{\longtable{#3}}
{\endlongtable}

\newcommand*{\keepXColumns}{}
\newcommand*{\convertXColumns}{}
```

File 198 **lwarp-ltcaption.sty**

§ 295 Package ltcaption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg `ltcaption` ltcaption is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltcaption}[2018/08/26]
```

`\LTcaptype` is already defined by lwarp.

`longtable*` is already defined by lwarp-longtable.

```
\newlength{\LTcapskip}
\newlength{\LTcapleft}
\newlength{\LTcapright}
\newcommand*{\LTcapmarginsfalse}{}
```

File 199 **lwarp-ltxgrid.sty**

§ 296 Package

ltxgrid

Pkg ltxgrid

ltxgrid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltxgrid}[2010/07/25]
```

```
\newcommand*{\onecolumngrid}{}
\newcommand*{\twocolumngrid}{}
\newcommand*{\removestuff}{}
\newcommand*{\addstuff}[2]{}
\newcommand*{\replacestuff}[2]{}
```

File 200 **lwarp-ltxtable.sty**

§ 297 Package

ltxtable

Pkg ltxtable

ltxtable is emulated.

⚠ table numbering

The print version does not seem to honor `longtable*` from the caption package, while lwarp does.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltxtable}[1995/12/11]
```

\LTXtable {⟨*width*⟩} {⟨*file*⟩}

```
\newcommand*{\LTXtable}[2]{%
\input{#2}%
}
```

File 201 **lua-check-hyphen.sty**

§ 298 Package

lua-check-hyphen

Pkg lua-check-hyphen

lua-check-hyphen is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-check-hyphen}[2018/04/19]
```

```
\newcommand*{\LuaCheckHyphen}[1]{}
```

File 202 **lwarp-lua-visual-debug.sty**

§ 299 Package

lua-visual-debug

Pkg lua-visual-debug lua-visual-debug is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-visual-debug}[2016/05/30]
```

File 203 **lwarp-luacolor.sty**

§ 300 Package

luacolor

Pkg luacolor luacolor is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{luacolor}[2016/05/16]
```

```
\newcommand{\luacolorProcessBox}[1]{}
```

File 204 **lwarp-luatodonotes.sty**

§ 301 Package

luatodonotes

(*Emulates or patches code by* Fabian Lipp.)

Pkg luatodonotes luatodonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{luatodonotes}[2017/09/30]
```

Nullify options:

```
\@todonotes@additionalMarginEnabledfalse
```

```
\if@todonotes@disabled
\else

\newcommand{\ext@todo}{tdo}

\renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}
```

```
\let\LWRTODONOTES@orig@todototoc\todototoc

\renewcommand*{\todototoc}{%
\phantomsection%
\LWRTODONOTES@orig@todototoc%
}


\renewcommand{\@todonotes@drawMarginNoteWithLine}{%
\fcolorbox
    {\@todonotes@currentbordercolor}
    {\@todonotes@currentbackgroundcolor}
    {\arabic{@todonotes@numberoftodonotes}}
\marginpar{\@todonotes@drawMarginNote}
}

\renewcommand{\@todonotes@drawInlineNote}{%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \if@todonotes@authorgiven%
        {\@todonotes@author:\,}%
        \fi%
        \@todonotes@text%
    }%
}

\newcommand{\@todonotes@drawMarginNote}{%
    \if@todonotes@authorgiven%
        \@todonotes@author\par%
    \fi%
    \arabic{@todonotes@numberoftodonotes}: %
    \fcolorbox%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \@todonotes@sizecommand%
        \@todonotes@text %
    }%
}%

\renewcommand{\missingfigure}[2][]{%
\setkeys{todonotes}{#1}%
\addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todocommon\@todocommon
```

```

\RenewDocumentCommand{\@todocommon}{m m}{%
\begingroup%
\renewcommand*{\phantomsection}{}%
\LWRTODONOTES@orig@todocommon{#1}{#2}%
\endgroup%
}

\renewcommand{\@todoarea}[3][]{%
    \@todonotes@areaselectedtrue%
    \@todocommon{#1}{#2}%
    \todonotes@textmark@highlight{#3}%
    \zref@label{@todonotes@\arabic{@todonotes@numberoftodonotes}@end}%
}%


\DeclareDocumentCommand{\todonotes@textmark@highlight}{m}{%
\InlineClass[background:\LWR@origpound{}B3FFB3]{highlight}{#1}%
}

\fi% \if@todonotes@disabled
```

File 205 **lwarp-magaz.sty**

§ 302 Package magaz

Pkg magaz magaz is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{magaz}[2011/11/24]

\newcommand\FirstLine[1]{%
    \begingroup%
    \FirstLineFont{%
        \LWR@textcurrentcolor{%
            \LWR@textcurrentfont{%
                #1%
            }%
        }%
    }%
    \endgroup%
}

\providecommand\FirstLineFont{\scshape}
```

File 206 **lwarp-makeidx.sty**

§ 303 Package makeidx

(*Emulates or patches code by* LaTeX Project Team.)

Pkg makeidx

makeidx is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{makeidx}[2014/09/29]
```

\@wrindex is redefined \AtBeginDocument by the lwarp core.

\printindex

```
\preto\printindex{%
    \LWR@orignewpage%
    \LWR@startpars%
}
```

File 207 **lwarp-manyfoot.sty**

§ 304 Package

manyfoot

Pkg manyfoot

manyfoot is emulated.

bigfoot, manyfoot

⚠ verbatim

Verbatim footnotes are not yet supported.

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XeLaTeX or LuaLaTeX instead of pdfLaTeX.

lwarp's emulation of bigfoot uses manyfoot, so some of the bigfoot enhancements are included here.

The bigfoot "default" footnote is ignored, using the lwarp version instead.

for HTML output:

```
\LWR@ProvidesPackageDrop{manyfoot}[2005/09/11]
```

```
\RequirePackage{nccfoots}

\newcommand{\extrafootnoterule}{}

\let\defaultfootnoterule\footnoterule

\newcommand*{\SelectFootnoteRule}[2][0]{}

\newcommand{\footnoterulepriority}{1}

\newcommand{\SetFootnoteHook}[1]{}
\@onlypreamble\SetFootnoteHook
```

```

\newcommand{\SplitNote}{}

\newcommand*\ExtraParaSkip[1]{}

\newcommand*{\newfootnote}[2][plain]{%
    \ifstrequal{#2}{default}{}{% not "default"
        \expandafter\newbox\csname LWR@footnote#2box\endcsname%
        \appto{\LWR@printpendingfootnotes}{%
            \LWR@@printpendingfootnotes{footnote#2}%
        }
        \long\csdef{Footnotetext#2}##1##2{%
            \NCC@makefnmark{##1}%
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
        \long\csdef{Footnotetext#2+}##1##2{%
            \NCC@makefnmark{##1}%
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
    }% not "default"
}
\@onlypreamble\newfootnote

\newcommand*{\DeclareNewFootnote}[2][plain]{%
  \@ifnextchar[%
        {\LWR@manyfoot@declare{#1}{#2}}%
        {\LWR@manyfoot@declare{#1}{#2}[arabic]}%
}

\def\LWR@manyfoot@declare#1#2[#3]{%
\ifstrequal{#2}{default}{}{% not "default"
  \newfootnote[#1]{#2}%
  \newcounter{footnote#2}%
    \newcounter{footnote#2Reset}%
    \setcounter{footnote#2Reset}{0}%
    \csdef{thefootnote#2}{%
      \expandafter\noexpand\csname @#3\endcsname%
      \expandafter\noexpand\csname c@footnote#2\endcsname%
    }%
```

For bigfoot, the footnote commands may be appended with one or two plusses or one or two minuses, which are ignored in HTML.

```
  \expandafter\NewDocumentCommand\csname footnote#2\endcsname{t{+}t{+}t{-}t{-}}{%
        \stepcounter{footnote#2}%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \@footnotemark%
        \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
    }%
    \csdef{footnotemark#2}{%
        \stepcounter{footnote#2}%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \@footnotemark%
    }%
  \expandafter\NewDocumentCommand\csname footnotetext#2\endcsname{t{+}t{+}t{-}t{-}}{%
```

```
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
    }%
    \csdef{Footnotemark#2}{%
      \Footnotemark%
    }%
    \csdef{Footnote#2}##1{%
      \Footnotemark{##1}%
      \csuse{Footnotetext#2}{##1}%
    }%
}% not "default"
}
\@onlypreamble\DeclareNewFootnote
```

File 208 **lwarp-marginal.sty**

§ 305 Package

marginal

Pkg marginal

marginal is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{marginal}
```

```
\newcommand*{\showlostmarginals}{}
\newcommand*{\enlargefreelist}{}
\newcommand*{\onesidemarginals}{}
```

File 209 **lwarp-marginfit.sty**

§ 306 Package

marginfit

Pkg marginfit

marginfit is ignored.

for HTML output: Discard all options for lwarp-marginfit:

```
\LWR@ProvidesPackageDrop{marginfit}[2018/06/08]
```

File 210 **lwarp-marginfix.sty**

§ 307 Package

marginfix

(*Emulates or patches code by* Stephen Hicks.)

Pkg marginfix

Emulated.

for HTML output: Discard all options for lwarp-marginfix:

```
\LWR@ProvidesPackageDrop{marginfix}[2013/09/08]
```

```
\newcommand*{\marginskip}[1]{}
\newcommand*{\clearmargin}{}
\newcommand*{\softclearmargin}{}
\newcommand*{\extendmargin}[1]{}
\newcommand*{\mparshift}[1]{}
\newdimen\marginheightadjustment
\newdimen\marginposadjustment
\newcommand*{\blockmargin}[1][]{}
\newcommand*{\unblockmargin}[1][]{}
\newcommand*{\marginphantom}[2][]{}
```

File 211 **lwarp-marginnote.sty**

§ 308 Package marginnote

(*Emulates or patches code by* Markus Kohm.)

Pkg marginnote Emulated.

for HTML output: Discard all options for lwarp-marginnote:

```
\LWR@ProvidesPackageDrop{marginnote}[2018/08/09]
```

```
\NewDocumentCommand{\marginnote}{+o +m o}{\marginpar{#2}}
```

```
\newcommand*{\marginnoteleftadjust}{}
\newcommand*{\marginnoterightadjust}{}
\newcommand*{\marginnotetextwidth}{}
\let\marginnotetextwidth\textwidth
\newcommand*{\marginnotevadjust}{}
\newcommand*{\marginfont}{}
\newcommand*{\raggedleftmarginnote}{}
\newcommand*{\raggedrightmarginnote}{}
```

File 212 **lwarp-marvosym.sty**

§ 309 Package marvosym

(*Emulates or patches code by* Thomas Henlich, Mojca Miklavec.)

Pkg marvosym marvosym is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```
\LWR@ProvidesPackagePass{marvosym}[2011/07/20]
```

```
\renewcommand{\mvchr}[1]{%
    \begin{lateximage}*[(symbol #1)][marvosym #1]%
    \mvs\char#1%
```

```
    \end{lateximage}%
}

\renewcommand{\textmvs}[1]{%
    \begin{lateximage}%
    \mvs #1%
    \end{lateximage}%
}
```

File 213 **lwarp-mcaption.sty**

§ 310 Package mcaption

(*Emulates or patches code by* Stephan Hennig.)

Pkg mcaption mcaption is nullified.

for HTML output: Discard all options for lwarp-mcaption:

```
\LWR@ProvidesPackageDrop{mcaption}[2009/03/13]
```

```
\newenvironment{margincap}{}{}
\newcommand*{\margincapalign}{}
\newlength{\margincapsep}
```

File 214 **lwarp-mdframed.sty**

§ 311 Package mdframed

(*Emulates or patches code by* Marco Daniel, Elke Schubert.)

Pkg mdframed mdframed is loaded with options forced to `framemethod=none`.

§ 311.1 Limitations

support Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading When used, lwarp loads mdframed in HTML with `framemethod=none`.

font For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where \textbf must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support \bfseries and friends, only one font selection may be made at a time.

theoremtitlefont theoremtitlefont is not supported, since the following text is not in braces in the mdframed source.

ignored options userdefinedwidth and align are currently ignored.

css classes Environments created or encapsulated by mdframed are enclosed in a of class mdframed, and also class md<environmentname> for new environments.

Frame titles are placed in a of class |mdframedtitle|. Subtitles are in a of class |mdframedsubtitle|, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

§ 311.2 Package loading

for HTML output:

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackageDrop{mdframed}[2013/07/01]
```

Do not require Ti*k*z or pstricks:

```
\LWR@origRequirePackage[framemethod=none]{mdframed}
```

§ 311.3 Patches

Patch to remove PDF formatting and add HTML tags:

```
\AtBeginDocument{
\def\mdf@trivlist#1{%
  \edef\mdf@temp{%
%     \topsep=\the\topsep\relax%
%     \partopsep=\the\partopsep\relax%
%     \parsep=\the\parsep\relax%
  }%
%   \setlength{\topsep}{#1}%
%   \topskip\z@%
%   \partopsep\z@%
%   \parsep\z@%
%   \@nmbrlistfalse%
%   \@trivlist%
%   \labelwidth\z@%
%   \leftmargin\z@%
%   \itemindent\z@%
  \let\@itemlabel\@empty%
  \def\makelabel##1{##1}%
%   \item\relax\mdf@temp\relax%
}

\renewcommand*{\endmdf@trivlist}{%
\LWR@traceinfo{endmdf@trivlist}%
```

```
% \endtrivlist%
\LWR@listend%
}
}% AtBeginDocument
```

§ 311.4 Initial setup

To handle css and paragraphs, patch code at start and end of environment and contents. `\LWR@print@raggedright` helps avoid hyphenation.

```
\mdfsetup{
startcode={\LWR@mdframedstart\LWR@print@raggedright},
endcode={\LWR@mdframedend},
startinnercode={\LWR@startpars\LWR@print@raggedright},
endinnercode={\LWR@stoppars},
}
```

§ 311.5 Color and length HTML conversion

`\LWR@mdfprintcolor` {⟨*mdfcolorkey*⟩}

Given the mdframed key, print the color.

```
\newcommand*{\LWR@mdfprintcolor}[1]{%
\convertcolorspec{named}{\@nameuse{mdf@#1}}{HTML}\LWR@tempcolor%
\LWR@origpound\LWR@tempcolor
}
```

`\LWR@mdfprintlength` {⟨*mdflengthkey*⟩}

Given the mdframed key, print the length.

```
\newcommand*{\LWR@mdfprintlength}[1]{%
\LWR@forceminwidth{\@nameuse{mdf@#1@length}}%
\LWR@printlength{\LWR@atleastonept}%
}
```

§ 311.6 Environment encapsulation

`\LWR@mdframedstart` Actions before an mdframe starts.

Encapsulate a frame inside a `<div>` of the desired `class`.

```
\newcommand*{\LWR@mdframedstart}{%
\LWR@traceinfo{LWR@mdframedstart start}%
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
\LWR@stoppars%
```

Open a `<div>` and with custom `class` and custom `style`. A `BlockClass` environment is not used because this `<div>` is created by the mdframed `startcode` and `endcode` settings, which do not properly nest the `<div>` inside the `mdframed` environment.

```
\LWR@htmltagc{div class="%
mdframed%
\ifdefstring{\LWR@mdthisenv}{mdframed}{}{ \LWR@mdthisenv}%
" \LWR@orignewline
style=" \LWR@orignewline
```

Convert and print the background color:

```
background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
border: \LWR@mdfprintlength{linewidth} solid
\LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
\ifbool{mdf@shadow}{%
    box-shadow:
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintcolor{shadowcolor} ;
}
{box-shadow: none ;}
\LWR@orignewline

"}
% \LWR@htmldivclass{\LWR@mdthisenv}
```

mdframed environment may not work with the HTML versions of the following, so restore them to their originals while inside mdframed:

```
\LWR@select@print@hspace%
\renewcommand*{\rule}{\LWR@print@rule}
\LetLtxMacro\makebox\LWR@print@makebox%

\LWR@startpars%
\LWR@traceinfo{LWR@mdframedstart done}%
}
```

\LWR@mdframedend Actions after an mdframe ends.

After closing the , globally restore to the default environment type:

```
\newcommand*{\LWR@mdframedend}{
\LWR@traceinfo{LWR@mdframedend start}%
```

Close the custom :

```
\LWR@htmldivclassend{\LWR@mdthisenv}
```

Reset future custom class to the default:

```
\gdef\LWR@mdthisenv{mdframed}
```

Resume paragraph handling:

```
\LWR@startpars%
\LWR@traceinfo{LWR@mdframedend done}%
}
```

§ 311.7 Mdframed environment

```
\renewenvironment{mdframed}[1][]{%
\color@begingroup%
  \mdfsetup{userdefinedwidth=\linewidth,#1}%
  \mdf@startcode%
  \mdf@preenvsetting%
  \ifdefempty{\mdf@firstframetitle}{}%
          {\let\mdf@frametitlesave\mdf@frametitle%
           \let\mdf@frametitle\mdf@firstframetitle%
          }%
  \ifvmode\nointerlineskip\fi%
       \ifdefempty{\mdf@frametitle}{}%
           {\mdfframedtitleenv{\mdf@frametitle}%
%            \mdf@@frametitle@use%
           }%
  \mdf@trivlist{\mdf@skipabove@length}%%
  \mdf@settings%
%    \mdf@lrbox{\mdf@splitbox@one}%
%    \mdf@startinnercode%
 }%
 {%
%    \mdf@@ignorelastdescenders%
  \par%
%     \unskip\ifvmode\nointerlineskip\hrule \@height\z@ \@width\hsize\fi%%
  \ifmdf@footnoteinside%
     \def\mdf@reserveda{%
       \mdf@footnoteoutput%
%        \mdf@endinnercode%
%        \endmdf@lrbox%
%        \ifdefempty{\mdf@frametitle}{}%
%            {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%        \detected@mdf@put@frame
     }%
  \else%
     \def\mdf@reserveda{%
%        \mdf@endinnercode%
%        \endmdf@lrbox%
%        \ifdefempty{\mdf@frametitle}{}%
%            {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%        \detected@mdf@put@frame%
       \mdf@footnoteoutput%
       }%
  \fi%
  \mdf@reserveda%
 \aftergroup\endmdf@trivlist%
\color@endgroup%
\mdf@endcode%
}
```

\mdf@footnoteoutput

```
\renewrobustcmd*\mdf@footnoteoutput{%
    \LWR@printpendingmpfootnotes%
}
```

§ 311.8 Titles and subtitles

\mdframedtitleenv {⟨*title*⟩}

Place the title inside a of class mdframedtitle:

```
\newlength{\LWR@titleroundcorner}

\renewrobustcmd\mdframedtitleenv[1]{%
\LWR@traceinfo{LWR@mdframedtitleenv start}%
```

Open a with a custom class and custom style:

```
\begin{BlockClass}[%
```

Convert and print the title background color:

```
background:
\LWR@mdfprintcolor{frametitlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the title rule:

```
\ifbool{mdf@frametitlerule}{%
    border-bottom:
    \LWR@mdfprintlength{frametitlerulewidth}
    solid
    \LWR@mdfprintcolor{frametitlerulecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening tag:

```
]{mdframedtitle}%
```

Print the title inside the :

```
\mdf@frametitlefont{\LWR@textcurrentfont{#1}}%
```

Close the :

```
\end{BlockClass}%
\LWR@traceinfo{LWR@mdframedtitleenv end}%
}
```

\LWR@mdfsubtitlecommon {⟨*sub -or- subsub*⟩} [⟨*options*⟩] {⟨*title*⟩}

Common code for \LWR@mdfsubtitle and \LWR@mdfsubsubtitle.

Encapsulate the subtitle inside a of class mdframedsubtitle:

```
\NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}
{% the following empty line is required

\LWR@traceinfo{LWR@mdframedsubtitlecommon start}%
```

Open a with a custom class and custom style:

```
\begin{BlockClass}[%
```

Convert and print the background color:

```
background:
\LWR@mdfprintcolor{#1titlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the above line:

```
\ifbool{mdf@#1titleaboveline}{%
    border-top:
    \LWR@mdfprintlength{#1titleabovelinewidth}
    solid
    \LWR@mdfprintcolor{#1titleabovelinecolor}
    ; \LWR@orignewline
}{}%
```

Convert and print the below line:

```
\ifbool{mdf@#1titlebelowline}{%
    border-bottom:
    \LWR@mdfprintlength{#1titlebelowlinewidth}
    solid
    \LWR@mdfprintcolor{#1titlebelowlinecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening tag:

```
]{mdframed#1title}%
```

Perform the original subtitle action:

```
\IfNoValueTF{#2}
{\@nameuse{LWR@origmdf#1title}{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
{\@nameuse{LWR@origmdf#1title}[#2]{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
```

Close the :

```
\end{BlockClass}%
\LWR@traceinfo{LWR@mdframedsubtitlecommon end}%
}
```

`\LWR@mdfsubtitle` [⟨*options*⟩] {⟨*title*⟩}

```
\newcommand*{\LWR@mdfsubtitle}{%
\LWR@mdfsubtitlecommon{sub}%
}
\let\mdfsubtitle\LWR@mdfsubtitle
```

`\LWR@mdfsubsubtitle` [⟨*options*⟩] {⟨*title*⟩}

```
\newcommand*{\LWR@mdfsubsubtitle}{%
\LWR@mdfsubtitlecommon{subsub}%
}
\let\mdfsubsubtitle\LWR@mdfsubsubtitle
```

§ 311.9 New environments

\LWR@mdthisenv Stores the environment of the frame about to be created:

```
\newcommand*{\LWR@mdthisenv}{mdframed}
```

\newmdenv [⟨*options*⟩] {⟨*env-name*⟩}

Modified from the original to remember the environment.

```
\renewrobustcmd*\newmdenv[2][]{%
\newenvironment{#2}%
{%
\mdfsetup{#1}%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}%
}
{\end{mdframed}}%
}
```

\surroundwithmdframed [⟨*options*⟩] {⟨*environment*⟩}

Modified from the original to remember the environment.

```
\renewrobustcmd*{\surroundwithmdframed}[2][]{%
\BeforeBeginEnvironment{#2}{%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}[#1]}%
\AfterEndEnvironment{#2}{\end{mdframed}}%
}
```

\mdtheorem [⟨*mdframed-options*⟩] {⟨*envname*⟩} [⟨*numberedlike*⟩] {⟨*caption*⟩} [⟨*within*⟩]

Modified from the original to remember the environment.

```
\DeclareDocumentCommand{\mdtheorem}{ O{} m o m o }%
 {\ifcsdef{#2}%
   {\mdf@PackageWarning{Environment #2 already exits\MessageBreak}}%
   {%
    \IfNoValueTF {#3}%
     {%#3 not given -- number relationship
      \IfNoValueTF {#5}%
        {%#3+#5 not given
        \@definecounter{#2}%
        \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
        \newenvironment{#2}[1][]{%
          \refstepcounter{#2}%
          \ifstrempty{##1}%
            {\let\@temptitle\relax}%
            {%
             \def\@temptitle{\mdf@theoremseparator%
                             \mdf@theoremspace%
                             \mdf@theoremtitlefont%
                             \LWR@textcurrentfont{##1}}% lwarp
             \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
             }%
          \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
```

```
                                        \@temptitle}]}%
        {\end{mdframed}}%
      \newenvironment{#2*}[1][]{%
        \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
        \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
        {\end{mdframed}}%
      }%
      {%#5 given -- reset counter
      \@definecounter{#2}\@newctr{#2}[#5]%
      \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
      \expandafter\xdef\csname the#2\endcsname{%
             \expandafter\noexpand\csname the#5\endcsname \@thmcountersep%
                \@thmcounter{#2}}%
      \newenvironment{#2}[1][]{%
        \refstepcounter{#2}%
        \ifstrempty{##1}%
          {\let\@temptitle\relax}%
          {%
           \def\@temptitle{\mdf@theoremseparator%
                           \mdf@theoremspace%
                           \mdf@theoremtitlefont%
                           \LWR@textcurrentfont{##1}}% lwarp
           \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
           }
        \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                        \@temptitle}]}%
        {\end{mdframed}}%
      \newenvironment{#2*}[1][]{%
        \ifstrempty{##1}%
          {\let\@temptitle\relax}%
          {%
           \def\@temptitle{\mdf@theoremseparator%
                           \mdf@theoremspace%
                           \mdf@theoremtitlefont%
                           \LWR@textcurrentfont{##1}}% lwarp
           \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
           }%
        \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
        {\end{mdframed}}%
      }%
    }%
    {%#3 given -- number relationship
      \global\@namedef{the#2}{\@nameuse{the#3}}%
      \newenvironment{#2}[1][]{%
        \refstepcounter{#3}%
        \ifstrempty{##1}%
          {\let\@temptitle\relax}%
          {%
           \def\@temptitle{\mdf@theoremseparator%
                           \mdf@theoremspace%
                           \mdf@theoremtitlefont%
                           \LWR@textcurrentfont{##1}}% lwarp
           \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
           }
        \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
```

```
                                          \@temptitle}]}%
          {\end{mdframed}}%
        \newenvironment{#2*}[1][]{%
          \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
          {\end{mdframed}}%
     }%
    \BeforeBeginEnvironment{#2}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
    \BeforeBeginEnvironment{#2*}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
   }%
}
```

\newmdtheoremenv [⟨*1: mdframed-options*⟩] {⟨*2: envname*⟩} [⟨*3: numberedlike*⟩] {⟨*4: caption*⟩} [⟨*5: within*⟩]

Modified from the original to remember the environment.

```
\DeclareDocumentCommand\newmdtheoremenv{O{} m o m o }{%
 \ifboolexpr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }%
    {\newtheorem{#2}{#4}}%
    {%
     \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}%
     \IfValueT{#5}{\newtheorem{#2}{#4}[#5]}%
    }%
\BeforeBeginEnvironment{#2}{%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}[#1]}%
\AfterEndEnvironment{#2}{%
\end{mdframed}}%
}
```

File 215 **lwarp-memhfixc.sty**

§ 312 Package memhfixc

Pkg memhfixc memhfixc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{memhfixc}[2013/05/30]
```

File 216 **lwarp-metalogo.sty**

§ 313 Package metalogo

(*Emulates or patches code by* Andrew Gilbert Moschou.)

Pkg metalogo metalogo is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{metalogo}[2010/05/29]
```

```
\newcommand\setlogokern[2]{}
```

```
\newcommand\setlogodrop[2][XeTeX]{}
\newcommand\setLaTeXa[1]{}
\newcommand\setLaTeXee[1]{}
\newcommand\seteverylogo[1]{}
\newcommand\everylogo[1]{}
```

File 217 **lwarp-mhchem.sty**

§ 314 Package

mhchem

(*Emulates or patches code by* Martin Hensel.)

Pkg mhchem

mhchem is patched for use by lwarp.

mhchem expressions are converted to svg math. Inline expressions use hashed filenames to allow reuse, and assume that any mhchem options are global.

⚠ MathJax and mhchem

The MathJax mhchem extension is not yet used. If MathJax is used for math in the rest of the document, lwarp converts standalone mhchem expressions into svg math images, but expressions inside math must be placed between `\displaymathother` and `\displaymathnormal`:

```
\displaymathother
\[ \ce{ . . . } \]     . . .     $ \ce { . . . } $
\displaymathnormal
```

⚠ nested math

When producing html output, lwarp does not support the use of nested dollar signs in mhchem expressions.

For some examples from the mhchem manual, change as follows:

```
$\ce{NaOH(aq,$\infty$)}$            % old
$\ce{NaOH(aq,\infty)}$              % new

$\ce{Fe(CN)_{$\frac{6}{2}}$}$       % old
$\ce{Fe(CN)_{\frac{6}{2}}}$         % new

$\ce{NO_$x$}$                       % old
$\ce{NO_x}$                         % new

$\ce{NO_${x}$}$                     % old
$\ce{NO_{x}}$                       % new

$\ce{$cis${-}[PtCl2(NH3)2]}$        % old
$\ce{\mathit{cis}{-}[PtCl2(NH3)2]}$ % new
```

for HTML output:

```
\LWR@ProvidesPackagePass{mhchem}[2018/06/22]
```

The original definition of `\ce`:

```
\LetLtxMacro\LWR@mhchem@origce\ce
```

The new definition, called from the new \ce after math shift is set. The starred lateximage uses a hashed filename for the SVG image. The alt tag is set to the mhchem expression.

```
\newcommand{\LWR@mhchem@HTML@ce}[1]{%
\begin{lateximage}*[\textbackslash{}ce\{\LWR@HTMLsanitize{#1}\}]%
\LWR@mhchem@origce{#1}%
\end{lateximage}%
\endgroup%
\addtocounter{LWR@mhchem@cedepth}{-1}%
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cedepth}
\setcounter{LWR@mhchem@cedepth}{0}
```

The new \ce. Sets math shift then continues.

```
\renewcommand{\ce}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cedepth}}{0}{%
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cedepth}{1}%
\LWR@mhchem@HTML@ce%
}
```

The original definition of \cesplit:

```
\LetLtxMacro\LWR@mhchem@origcesplit\cesplit
```

The new definition, called from the new \cesplit after math shift is set. The starred lateximage uses a hashed filename for the SVG image. The alt tag is set to the mhchem expression.

```
\newcommand*{\LWR@mhchem@HTML@cesplit}[2]
{%
\begin{lateximage}*[\textbackslash{}cesplit\{\LWR@HTMLsanitize{#2}\}]%
\LWR@mhchem@origcesplit{#1}{#2}%
\end{lateximage}%
\endgroup%
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cesplitdepth}
\setcounter{LWR@mhchem@cesplitdepth}{0}
```

The new \cesplit. Sets math shift then continues.

```
\renewcommand{\cesplit}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cesplitdepth}}{0}{%
```

```
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cesplitdepth}{1}%
\LWR@mhchem@HTML@cesplit%
}
```

Resore originals inside a `lateximage`:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\ce\LWR@mhchem@origce%
\LetLtxMacro\cesplit\LWR@mhchem@origcesplit%
}
```

File 218 **`lwarp-microtype.sty`**

§ 315 Package

microtype

(*Emulates or patches code by* R Schlicht.)

Pkg `microtype` microtype is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output: Discard all options for lwarp-microtype:

```
\LWR@ProvidesPackageDrop{microtype}[2018/01/14]
```

```
\DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m}{}
\DeclareDocumentCommand{\UseMicrotypeSet}{o m}{}
\DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m}{}
\DeclareDocumentCommand{\SetProtrusion}{o m m}{}
\DeclareDocumentCommand{\SetExpansion}{o m m}{}
\DeclareDocumentCommand{\SetTracking}{o m m}{}
\DeclareDocumentCommand{\SetExtraKerning}{o m m}{}
\DeclareDocumentCommand{\SetExtraSpacing}{o m m}{}
\DeclareDocumentCommand{\DisableLigatures}{o m}{}
\DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m}{}
\DeclareDocumentCommand{\DeclareMicrotypeVariants}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m}{}
\DeclareDocumentCommand{\LoadMicrotypeFile}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m}{}
\DeclareDocumentCommand{\microtypesetup}{m}{}
\DeclareDocumentCommand{\microtypecontext}{m}{}
\DeclareDocumentCommand{\textmicrotypecontext}{m m}{#2}
\@ifpackageloaded{letterspace}{\let\MT@textls\relax}{%
\DeclareDocumentCommand{\lsstyle}{}{}
\DeclareDocumentCommand{\textls}{o +m}{}
\DeclareDocumentCommand{\lslig}{m}{#1}
}
\def\DeclareMicrotypeSet#1#{\@gobbletwo}
\def\DeclareMicrotypeVariants#1#{\@gobble}
\@onlypreamble\DeclareMicrotypeSet
\@onlypreamble\UseMicrotypeSet
\@onlypreamble\DeclareMicrotypeSetDefault
```

```
\@onlypreamble\DisableLigatures
\@onlypreamble\DeclareMicrotypeVariants
\@onlypreamble\DeclareMicrotypeBabelHook
```

File 219 **lwarp-midfloat.sty**

§ 316 Package midfloat

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg midfloat midfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{midfloat}[2012/05/29]
```

```
\newenvironment{strip}[1][]{}{}
\newskip\stripsep
```

File 220 **lwarp-midpage.sty**

§ 317 Package midpage

Pkg midpage midpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{midpage}[2009/09/03]
```

```
\newenvironment{midpage}
{\begin{BlockClass}[%
    \LWR@print@mbox{margin-top:6ex} ; \LWR@print@mbox{margin-bottom:6ex}%
]{midpage}}
{\end{BlockClass}}
```

File 221 **lwarp-minitoc.sty**

§ 318 Package minitoc

Pkg minitoc minitoc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{minitoc}[2018/07/12]
```

mtcoff disables minitoc.

```
\usepackage{mtcoff}
```

File 222 **lwarp-morefloats.sty**

§ 319 Package

morefloats

Pkg morefloats morefloats is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{morefloats}[2015/07/22]
```

File 223 **lwarp-moreverb.sty**

§ 320 Package

moreverb

(*Emulates or patches code by* Robin Fairbairns.)

Pkg moreverb moreverb is supported with some patches.

for HTML output:

```
\begin{warpHTML}

\LWR@ProvidesPackagePass{moreverb}[2008/06/03]

\BeforeBeginEnvironment{verbatimtab}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{Verbatim}%
}
\AfterEndEnvironment{verbatimtab}{%
\LWR@afterendverbatim{1}%
}


\LetLtxMacro\LWRMV@orig@verbatimtabinput\@verbatimtabinput

\renewcommand{\@verbatimtabinput}[2][]{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{Verbatim}%
\LWRMV@orig@verbatimtabinput[#1]{#2}%
\LWR@afterendverbatim{1}%
}

\BeforeBeginEnvironment{listing}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
}

\AfterEndEnvironment{listing}{%
\LWR@afterendverbatim{1}%
}

\BeforeBeginEnvironment{listingcont}{%
```

```
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
}

\AfterEndEnvironment{listingcont}{%
\LWR@afterendverbatim{1}%
}

\LetLtxMacro\LWRMV@@listinginput\@listinginput

\renewcommand{\@listinginput}[3][]{
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
\LWRMV@@listinginput[#1]{#2}{#3}%
\LWR@afterendverbatim{1}%
}


\renewenvironment*{boxedverbatim}
{
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{boxedverbatim}%
\verbatim%
}
{
\endverbatim%
\LWR@afterendverbatim{1}%
}

\end{warpHTML}
```

File 224 **lwarp-mparhack.sty**

§ 321 Package mparhack

Pkg mparhack Ignored.

for HTML output: Discard all options for lwarp-mparhack:

```
\LWR@ProvidesPackageDrop{mparhack}[2005/04/17]
```

File 225 **lwarp-multicap.sty**

§ 322 Package multicap

Pkg multicap multicap is emualted.

for HTML output:

```
\LWR@ProvidesPackageDrop{multicap}[2002/05/04]
```

```
\newcommand*{\mfcaption}{\captionof{figure}}
\newcommand*{\mtcaption}{\captionof{table}}
\newcounter{mcapsize}
\newcounter{mcapskip}
\newlength{\abvmcapskip}
\newlength{\blwmcapskip}
```

File 226 **lwarp-multicol.sty**

§ 323 Package

multicol

(*Emulates or patches code by* Frank Mittelbach.)

Pkg multicol

multicol is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{multicol}[2018/12/27]
```

Multicols are converted into a 1–3 column display, browser-supported.

The optional multicols heading is placed inside a of class multicolsheading.

The content is placed inside a of class multicols.

```
\begin{warpHTML}
```

Env multicols

* {⟨*numcols*⟩} [⟨*heading*⟩]

```
\NewDocumentEnvironment{multicols}{s m o}
```

HTML class to contain everything:

```
{
    \LWR@forcenewpage
    \BlockClass{multicols}
```

Optional HTML class for the heading:

```
    \IfValueT{#3}{\begin{BlockClass}{multicolsheading}#3\end{BlockClass}}%
```

Change \linewidth to compensate for expected size:

```
    \setlength{\linewidth}{\linewidth/#2}
```

Locally force any minipages to be fullwidth:

```
    \booltrue{LWR@forceminipagefullwidth}
}
```

When done with the environment, close the :

```
{\endBlockClass}
```

Emulated null functions which are not used in HTML:

```
\newcommand*{\columnbreak}{}
\newcommand*{\RLmulticolcolumns}{}
```

```
\newcommand*{\LRmulticolcolumns}{}

\newlength{\premulticols}
\newlength{\postmulticols}
\newlength{\multicolsep}
\newlength{\multicolbaselineskip}
\newlength{\multicoltolerance}
\newlength{\multicolpretolerance}
\newcommand*{\columnseprulecolor}{\normalcolor}
\newcounter{columnbadness}
\newcounter{finalcolumnbadness}
\newcounter{collectmore}
\newcounter{unbalance}
\newlength{\multicolovershoot}
\newlength{\multicolundershoot}

\NewDocumentCommand{\docolaction}{s o m m m}{%
    \IfValueTF{#2}{#2}{#3}%
}

\end{warpHTML}
```

File 227 **lwarp-multicolrule.sty**

§ 324 Package multicolrule

Pkg multicolrule

multicolrule is ignored.

for HTML output:

```
\RequirePackage{multicol}

\LWR@ProvidesPackageDrop{multicolrule}[2019/01/01]

\newcommand*{\SetMCRule}[1]{}
\NewDocumentCommand{\DeclareMCRulePattern}{m m}{}
```

File 228 **lwarp-multirow.sty**

§ 325 Package multirow

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg multirow

multirow is emulated during HTML output, and used as-is while inside a `lateximage`.

vposn

- Note that recent versions of multirow include a new optional `vposn` argument.

multirow cells

- For multirow, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
. . . &   \multirow{2}{.5in}{text}   & . . .
. . . &   \mrowcell                  & . . .
```

colored cells

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so `\warpprintonly` and `\warpHTMLonly` must be used to make versions for print and HTML.

with `\multicolumn`

- See section 325.2 for `\multicolumrow`.

⚠ `\multicolumn` & `\multirow`

lwarp does not support directly combining `\multicolumn` and `\multirow`. Use `\multicolumnrow` instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for `\multicolumn` come first, followed by the five arguments for `\multirow`, many of which are optional, followed by the contents.

⚠ skipped cells

⚠ empty cells

As per `\multirow`, skipped cells to the right of the `\multicolumnrow` statement are not included in the source code on the same line. On the following lines, `\mcolrowcell` must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```
. . . &   \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}   & . . .
. . . &   \mcolrowcell          &          \mcolrowcell   & . . .
. . . &   \mcolrowcell          &          \mcolrowcell   & . . .
```

In a `lateximage`, `\LWR@restoreorigformatting` restores the original print-mode versions.

See section 71.24 for the print-mode versions.

for HTML output: Remove the placeholder macro which was used if multirow was not loaded:

```
\LetLtxMacro\multirow\relax
```

```
\LWR@ProvidesPackagePass{multirow}[2018/08/03]
```

`\LWR@multirowborder` Set to `left` or `right` to create a thick border for the cell, for use by bigdelim:

```
\newcommand{\LWR@multirowborder}{}
```

§ 325.1 Multirow

`\multirow` [⟨*vpos*⟩] {⟨*numrows*⟩} [⟨*bigstruts*⟩] {⟨*width*⟩} [⟨*fixup*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@multirow}{O{c} m o m o +m}%
{%
\LWR@traceinfo{*** LWR@HTML@multirow #1 #2 #4}%
\booltrue{LWR@usedmultirow}%
\LWR@maybenewtablerow%
\LWR@tabularleftedge%
```

Print the start of a new table data cell:

```
\LWR@htmltag{td rowspan="#2" %
```

The vertical alignment, if given:

```
\IfValueT{#1}{%
\ifstrequal{#1}{b}{style="\LWR@print@mbox{vertical-align:bottom}" }{}%
\ifstrequal{#1}{t}{style="\LWR@print@mbox{vertical-align:top}" }{}%
}%
```

The left/right border, if given:

```
\ifdefvoid{\LWR@multirowborder}{}{%
style="\LWR@print@mbox{border-\LWR@multirowborder:} 2px dotted black ; %
\LWR@print@mbox{padding-\LWR@multirowborder:} 2px" %
}%
```

A class adds the column spec and the rule:

```
class="td%
```

Append this column's spec:

```
\LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add the vertical bar class.

```
\LWR@addcmidruletrim%
\LWR@addleftmostbartag%
\LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
"%
```

```
\LWR@tdstartstyles%
\LWR@addcmidrulewidth%
\LWR@addcdashline%
\LWR@addtabularrulecolors%
\LWR@tdendstyles%
}%
```

The column's < spec:

```
\LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
```

While printing the text, redefine \\ to generate a new line

```
\begingroup\LetLtxMacro{\\}{\LWR@endofline}#6\endgroup%
\LWR@stoppars%
\global\boolfalse{LWR@intabularmetadata}%
\renewcommand{\LWR@multirowborder}{}%
\LWR@traceinfo{*** LWR@HTML@multirow done}%
}%
```

```
\LWR@formatted{multirow}
```

§ 325.2 Combined multicolumn and multirow

\multicolumnrow {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

\@ifpackageloaded{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The HTML version follows.

\AtBeginDocument because the print version had to see if multirow was loaded before determining how to define \LWR@print@multicolumnrow.

```
\AtBeginDocument{

\NewExpandableDocumentCommand{\LWR@HTML@multicolumnrow}{m m O{} m O{} m O{} +m}{%

\booltrue{LWR@usedmultirow}%
```

Figure out how many extra HTML columns to add for @ and ! columns:

```
\LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn/multirow tag:

```
\begingroup%
\LetLtxMacro{\\}{\LWR@endofline}%
\LWR@domulticolumn[#3][#4]{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#8}%
\endgroup%
```

Move to the next LaTeX column:

```
\addtocounter{LWR@tableLaTeXcolindex}{#1}%
\addtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}

\LWR@expandableformatted{multicolumnrow}

}% \AtBeginDocument
```

File 229 **lwarp-multitoc.sty**

§ 326 Package multitoc

Pkg multitoc

multitoc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{multitoc}[1999/06/08]

\newcommand{\multicolumntoc}{2}
\newcommand{\multicolumnlot}{2}
\newcommand{\multicolumnlof}{2}
\newcommand*{\immediateaddtocontents}[2]{}
```

File 230 **lwarp-musicography.sty**

§ 327 Package musicography

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg musicography

musicography is patched for use by lwarp.

Images are used for the meter symbols, since the HTML fonts tend not to be the correct size. The HTML `alt` tag copies `C` and `3/2`, etc. Hashes are used for the meter images, which are then reused as necessary.

⚠ Note that browser support for musical symbols may be buggy. Copy/paste into a text editor works well.

for HTML output:

```
\LWR@ProvidesPackagePass{musicography}[2018/05/21]

\RenewDocumentCommand{\musSymbol}{ O{\musFont} m m m m }{%
\begin{lateximage}%
{#1\kern#2\raisebox{#3}{#5}\kern#4}%
\end{lateximage}%
}

\RenewDocumentCommand{\musStemmedNote}{ m }{%
\begin{lateximage}%
\musSymbol{0.05em}{0.5ex}{0.2em}{#1\musStem}%
\end{lateximage}%
}

\RenewDocumentCommand{\musFlaggedNote}{ m m }{%
\begin{lateximage}%
\musSymbol{0.05em}{0.5ex}{0pt}{#1\musStem}%
\musSymbol{0pt}{0pt}{0.9em}{#2}%
\end{lateximage}%
}
```

```

\RenewDocumentCommand{\musDottedNote}{ m }{%
\begin{lateximage}%
#1\musDot%
\end{lateximage}%
}

\RenewDocumentCommand{\musMeter}{ m m }{%
\begin{lateximage}*[#1/#2][#1#2]%
\musStack{#1}{#2}\kern0.05em%
\end{lateximage}%
}

\RenewDocumentCommand{\meterCplus}{ m }{%
\begin{lateximage}*[C#1]%
    \meterC{}\kern-0.7pt#1%
\end{lateximage}%
}

\RenewDocumentCommand{\meterC}{}{%
\begin{lateximage}*[C]%
\musSymbolMeter{\symbol{83}}%
\end{lateximage}%
}

\RenewDocumentCommand{\meterCutC}{}{%
\begin{lateximage}*[C|]%
\musSymbolMeter{\symbol{82}}%
\end{lateximage}%
}

\RenewDocumentCommand{\meterCThreeTwo}{}{%
\begin{lateximage}*[C3/2]%
\meterCplus{\musStack{3}{2}}%
\end{lateximage}%
}

\RenewDocumentCommand{\musFlat}       {}{\HTMLunicode{266D}}
\RenewDocumentCommand{\musDoubleFlat} {}{\HTMLunicode{1D12B}}
\RenewDocumentCommand{\musSharp}      {}{\HTMLunicode{266F}}
\RenewDocumentCommand{\musDoubleSharp}{}{\HTMLunicode{1D12A}}
\RenewDocumentCommand{\musNatural}    {}{\HTMLunicode{266E}}

\RenewDocumentCommand{\musWhole}{}{\HTMLunicode{1D15D}}
\RenewDocumentCommand{\musHalf}{}{\HTMLunicode{1D15E}}
\RenewDocumentCommand{\musQuarter}{}{\HTMLunicode{1D15F}}
\RenewDocumentCommand{\musEighth}{}{\HTMLunicode{1D160}}
\RenewDocumentCommand{\musSixteenth}{}{\HTMLunicode{1D161}}

\RenewDocumentCommand{\musWholeDotted}{}{\HTMLunicode{1D15D}\HTMLunicode{1D16D}}
\RenewDocumentCommand{\musHalfDotted}{}{\HTMLunicode{1D15E}\HTMLunicode{1D16D}}
\RenewDocumentCommand{\musQuarterDotted}{}{\HTMLunicode{1D15F}\HTMLunicode{1D16D}}
\RenewDocumentCommand{\musEighthDotted}{}{\HTMLunicode{1D160}\HTMLunicode{1D16D}}
\RenewDocumentCommand{\musSixteenthDotted}{}{\HTMLunicode{1D161}\HTMLunicode{1D16D}}
```

File 231 **lwarp-nameauth.sty**

§ 328 Package

nameauth

(*Emulates or patches code by* Charles P. Schaum.)

Pkg nameauth nameauth is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nameauth}[2017/03/22]
```

lwarp formatting is inserted in the following.

```
\renewcommand*\@nameauth@Hook[1]
{%
  \if@nameauth@Lock
    \@nameauth@InHooktrue%
    \protected@edef\test{#1}%
    \expandafter\@nameauth@TestDot\expandafter{\test}%
    \if@nameauth@InAKA
      \if@nameauth@AlwaysFormat
        \@nameauth@FirstFormattrue%
      \else
        \unless\if@nameauth@AKAFormat
        \@nameauth@FirstFormatfalse\fi
      \fi
      \if@nameauth@MainFormat
        \if@nameauth@FirstFormat
          \bgroup\NamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\MainNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \else
        \if@nameauth@FirstFormat
          \bgroup\FrontNamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\FrontNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \fi
    \else
      \if@nameauth@AlwaysFormat
        \@nameauth@FirstFormattrue%
      \fi
      \if@nameauth@MainFormat
```

```
      \if@nameauth@FirstFormat
        \bgroup\NamesFormat{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \else
        \bgroup\MainNameHook{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \fi
    \else
      \if@nameauth@FirstFormat
        \bgroup\FrontNamesFormat{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \else
        \bgroup\FrontNameHook{%
          \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
        }\egroup%
      \fi
    \fi
  \fi
  \@nameauth@FirstFormatfalse%
  \@nameauth@InHookfalse%
 \fi
}
```

File 232 **lwarp-nameref.sty**

§ 329 Package nameref

Pkg nameref nameref is emulated by lwarp.

for HTML output: Discard all options for lwarp-nameref:

```
\typeout{Using the lwarp html version of package ‘nameref’, discarding options.}
\typeout{    Are not using ProvidesPackage, so that other packages}
\typeout{    do not attempt to patch lwarp’s version of ‘nameref’.}
\DeclareOption*{}
\ProcessOptions\relax
```

File 233 **lwarp-natbib.sty**

§ 330 Package natbib

(*Emulates or patches code by* Patrick W. Daly.)

Pkg natbib natbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{natbib}[2010/09/13]
```

Replace math < and > with `\textless` and `\textgreater`:

A macro to compare:

```
\newcommand{\LWRNB@NAT@open}{$<$}
```

To patch \NAT@open and \NAT@close

```
\newcommand{\LWRNB@patchnatbibopenclose}{
\ifdefstrequal{\NAT@open}{\LWRNB@NAT@open}
{
    \renewcommand{\NAT@open}{\textless}
    \renewcommand{\NAT@close}{\textgreater}
}{}
}
```

Do it now in case angle was selected as an option:

```
\LWRNB@patchnatbibopenclose
```

Also patch \setcitestyle to patch after settings are made:

```
\let\LWRNB@origsetcitestyle\setcitestyle

\renewcommand{\setcitestyle}[1]{%
\LWRNB@origsetcitestyle{#1}%
\LWRNB@patchnatbibopenclose%
}
```

File 234 **lwarp-nccfancyhdr.sty**

§ 331 Package

nccfancyhdr

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg nccfancyhdr

nccfancyhdr is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nccfancyhdr}[2004/12/07]
```

```
\newcommand*{\headrulewidth}{}
\newcommand*{\footrulewidth}{}
\newcommand{\headstrutheight}{}
\newcommand{\footstrutheight}{}
\newcommand*{\headrule}{}
\newcommand*{\footrule}{}

\newdimen\headwidth
\newcommand*{\extendedheaders}{}
\newcommand*{\normalheaders}{}

\newcommand*{\fancyhead}[2][]{}
\newcommand*{\fancyfoot}[2][]{}
\newcommand*{\fancyhf}[2][]{}
\newcommand*{\fancypagestyle}[2]{}
```

```
\newcommand*{\lhead}[2][]{}
\newcommand*{\chead}[2][]{}
\newcommand*{\rhead}[2][]{}
\newcommand*{\lfoot}[2][]{}
\newcommand*{\cfoot}[2][]{}
\newcommand*{\rfoot}[2][]{}

\newcommand{\nouppercase}[1]{#1}

\NewDocumentCommand{\fancycenter}{o o m m m}{}

\NewDocumentCommand{\newpagestyle}{m o m}{}

\newcommand*{\iffloatpage}[2]{#2}
\newcommand*{\ifftopfloat}[2]{#2}
\newcommand*{\iffbotfloat}[2]{#2}
```

File 235 **lwarp-needspace.sty**

§ 332 Package needspace

(*Emulates or patches code by* Peter Wilson.)

Pkg needspace needspace is not used during HTML conversion.

for HTML output: Discard all options for lwarp-needspace:

```
\LWR@ProvidesPackageDrop{needspace}[2010/09/12]

\DeclareDocumentCommand{\needspace}{m}{}
\DeclareDocumentCommand{\Needspace}{s m}{}
```

File 236 **lwarp-nextpage.sty**

§ 333 Package nextpage

(*Emulates or patches code by* Peter Wilson.)

Pkg nextpage nextpage is nullified.

for HTML output: Discard all options for lwarp-nextpage.

```
\LWR@ProvidesPackageDrop{nextpage}[2009/09/03]

\DeclareDocumentCommand{\cleartoevenpage}{o}{}
\DeclareDocumentCommand{\movetoevenpage}{o}{}
\DeclareDocumentCommand{\cleartooddpage}{o}{}
\DeclareDocumentCommand{\movetooddpage}{o}{}
```

File 237 **lwarp-nicefrac.sty**

§ 334 Package

nicefrac

(*Emulates or patches code by* Axel Reichert.)

Pkg nicefrac nicefrac is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nicefrac}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@@UnitsNiceFrac}[3][]{%
    {% localize font selection
        #1{%
            \LWR@textcurrentfont{%
                \InlineClass{numerator}{#2}%
                /%
                \InlineClass{denominator}{#3}%
            }%
        }%
    }%
}

\LWR@formatted{@UnitsNiceFrac}

\DeclareRobustCommand*{\LWR@HTML@@UnitsUglyFrac}[3][]{%
    {% localize font selection
        #1{\LWR@textcurrentfont{#2/#3}}%
    }%
}

\LWR@formatted{@UnitsUglyFrac}
```

For Mathjax:

```
\CustomizeMathJax{\newcommand{\nicefrac}[3][]{#2/#3}}
```

File 238 **lwarp-niceframe.sty**

§ 335 Package

niceframe

Pkg niceframe niceframe is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{niceframe}% the original date is in yyyy/dd/mm format

\newcommand{\LWR@niceframe}[3]{
    \setlength{\LWR@templengthone}{#1}
    \begin{BlockClass}[max-width:\LWR@printlength{\LWR@templengthone}]{#3}
    #2
```

```
    \end{BlockClass}
}

\newcommand{\niceframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{niceframe}}
\newcommand{\curlyframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{curlyframe}}
\newcommand{\artdecoframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{artdecoframe}}

\newcommand{\generalframe}[9]{\LWR@niceframe{\textwidth}{#9}{generalframe}}
```

File 239 **lwarp-nomencl.sty**

§ 336 Package nomencl

(*Emulates or patches code by* Boris Veytsman, Bernd Schandl, Lee Netherton, CV Radhakrishnan.)

Pkg nomencl nomencl is patched for use by lwarp.

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

for HTML output:

```
\LWR@ProvidesPackagePass{nomencl}[2005/09/22]

\def\@@@nomenclature[#1]#2#3{%
 \def\@tempa{#2}\def\@tempb{#3}%
 \protected@write\@nomenclaturefile{}%
  {\string\nomenclatureentry{#1\nom@verb\@tempa @[{\nom@verb\@tempa}]%
      \begingroup\nom@verb\@tempb\protect\nomeqref{\theequation}%
        |nompageref}{\theLWR@previousautopagelabel}}%   lwarp
 \endgroup
 \@esphack}

\renewcommand*{\pagedeclaration}[1]{, \nameref{autopage-#1}}
```

File 240 **lwarp-nonfloat.sty**

§ 337 Package nonfloat

(*Emulates or patches code by* Kai Rascher.)

Pkg nonfloat nonfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonfloat}[1999/07/05]

\LetLtxMacro\topcaption\caption
\newcommand{\figcaption}{\def\@captype{figure}\caption}
\newcommand{\tabcaption}{\def\@captype{table}\topcaption}
\newenvironment{narrow}[2]{}{}
```

File 241 **lwarp-nonumonpart.sty**

§ 338 Package

nonumonpart

Pkg nonumonpart nonumonpart is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonumonpart}[2011/04/15]
```

File 242 **lwarp-nopageno.sty**

§ 339 Package

nopageno

Pkg nopageno nopageno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nopageno}[1989/01/01]
```

File 243 **lwarp-notes.sty**

§ 340 Package

notes

Pkg notes notes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{notes}[2002/10/29]

\newcommand*{\LWR@notes@onenote}[2]{%
\newenvironment{#1}
    {
        \BlockClass{notes#1}
        \begin{BlockClass}{notesicon}\textcircled{~#2~}\end{BlockClass}
        \BlockClass{notescontents}
    }
    {\endBlockClass\endBlockClass}
}

\LWR@notes@onenote{importantnote}{!}

\LWR@notes@onenote{warningnote}{--}

\LWR@notes@onenote{informationnote}{i}
```

File 244 **lwarp-notespages.sty**

§ 341 Package notespages

Pkg notespages notespages is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{notespages}[2016/08/21]
```

```
\newcommand*{\npnotesname}{}
\newcommand*{\npnotestext}{}
\newcommand*{\remainingtextheight}{}
\newdimen\remainingtextheight
\newcommand*{\notestitletext}{}
\newcommand*{\notesareatext}{}
\newcommand*{\npnpinfo}[1]{}
\newcommand*{\tracingnpmarks}{}
\newcommand*{\notespage}[1][]{}
\newcommand*{\notespages}[1][]{}
\newcommand*{\notesfill}[1][]{}
\newcommand*{\setnotespages}[1]{}
\newcommand*{\definenotesoption}[2]{}
\newcommand{\definenotesstyle}[2]{}
\newcommand{\definetitlestyle}[2]{}
\newcommand{\nppatchchapter}[1]{}
\newcommand{\npunpatchchapter}{}
```

File 245 **lwarp-nowidow.sty**

§ 342 Package nowidow

(*Emulates or patches code by* Raphaël Pinson.)

Pkg nowidow nowidow is not used during HTML conversion.

Discard all options for lwarp-nowidow:

for HTML output:

```
\LWR@ProvidesPackageDrop{nowidow}[2011/09/20]
```

\nowidow [⟨*lines*⟩]

\setnowidow [⟨*lines*⟩]

```
\newcommand*{\nowidow}[1][]{}
\newcommand*{\setnowidow}[1][]{}
```

\noclub [⟨*lines*⟩]

\setnoclub [⟨*lines*⟩]

```
\newcommand*{\noclub}[1][]{}
\newcommand*{\setnoclub}[1][]{}
```

File 246 **lwarp-ntheorem.sty**

§ 343 Package ntheorem

(*Emulates or patches code by* Wolfgang May, Andreas Schedler.)

Pkg ntheorem ntheorem is patched for use by lwarp.

Table 15: Ntheorem package — CSS styling of theorems and proofs

Theorem: `<div>` of class `theorembody<theoremstyle>`

Theorem Header: `<span>` of class `theoremheader<style>`

where `<theoremstyle>` is `plain`, `break`, etc.

§ 343.1 Limitations

⚠ Font control This conversion is not total. Font control is via CSS, and the custom LaTeX font settings are ignored.

⚠ Equation numbering ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environmentswhen the option `thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's `thref` option.

§ 343.2 Options

Options `amsthm` or `standard` choose which set of theorems and proofs to initialize.

⚠ Disabled options The options `thmmarks` and `amsmath` are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option `thref` is disabled because cleveref functions are used instead. `\thref` is emulated.

Option `hyperref` is disabled because lwarp emulated hyperref.

for HTML output: Some disabled options:

```
\DeclareOption{thref}{}


\newbool{LWR@ntheoremmarks}
\boolfalse{LWR@ntheoremmarks}

\DeclareOption{thmmarks}{
\booltrue{LWR@ntheoremmarks}
```

```
\newif\ifsetendmark\setendmarktrue
}


\newbool{LWR@ntheoremamsthm}
\boolfalse{LWR@ntheoremamsthm}

\DeclareOption{amsthm}{\booltrue{LWR@ntheoremamsthm}}


\DeclareOption{amsmath}{}
\DeclareOption{hyperref}{}

\LWR@ProvidesPackagePass{ntheorem}[2011/08/15]
```

§ 343.3 Remembering the theorem style

Storage for the style being used for new theorems.

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

```
\AtBeginDocument{
\@ifpackageloaded{cleveref}{
\gdef\@thm#1#2#3{%
   \if@thmmarks
     \stepcounter{end\InTheoType ctr}%
   \fi
   \renewcommand{\InTheoType}{#1}%
   \if@thmmarks
     \stepcounter{curr#1ctr}%
     \setcounter{end#1ctr}{0}%
   \fi
   \refstepcounter[#1]{#2}%  <<< cleveref modification
   \theorem@prework
    \LWR@forcenewpage% lwarp
    \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
   \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
     \ifthm@inframe
       \thm@topsep\theoreminframepreskipamount
       \thm@topsepadd\theoreminframepostskipamount
      \else
       \thm@topsep\theorempreskipamount
       \thm@topsepadd\theorempostskipamount
      \fi
    \else% oldframeskips
      \thm@topsep\theorempreskipamount
      \thm@topsepadd \theorempostskipamount
      \ifvmode\advance\thm@topsepadd\partopsep\fi
   \fi
   \@topsep\thm@topsep
   \@topsepadd\thm@topsepadd
   \advance\linewidth -\theorem@indent
   \advance\linewidth -\theorem@rightindent
   \advance\@totalleftmargin \theorem@indent
```

```
   \parshape \@ne \@totalleftmargin \linewidth
   \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
}
}{% not @ifpackageloaded{cleveref}
\gdef\@thm#1#2#3{%
   \if@thmmarks
     \stepcounter{end\InTheoType ctr}%
   \fi
   \renewcommand{\InTheoType}{#1}%
   \if@thmmarks
     \stepcounter{curr#1ctr}%
     \setcounter{end#1ctr}{0}%
   \fi
   \refstepcounter{#2}%
   \theorem@prework
    \LWR@forcenewpage% lwarp
    \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
   \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
     \ifthm@inframe
       \thm@topsep\theoreminframepreskipamount
       \thm@topsepadd\theoreminframepostskipamount
      \else
       \thm@topsep\theorempreskipamount
       \thm@topsepadd\theorempostskipamount
      \fi
    \else% oldframeskips
      \thm@topsep\theorempreskipamount
      \thm@topsepadd \theorempostskipamount
      \ifvmode\advance\thm@topsepadd\partopsep\fi
   \fi
   \@topsep\thm@topsep
   \@topsepadd\thm@topsepadd
   \advance\linewidth -\theorem@indent
   \advance\linewidth -\theorem@rightindent
   \advance\@totalleftmargin \theorem@indent
   \parshape \@ne \@totalleftmargin \linewidth
   \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
}
}
}% AtBeginDocument
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
   \@ifundefined{th@#1}{\@warning
          {Unknown theoremstyle ‘#1’. Using ‘plain’}%
          \theorem@style{plain}
            \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
            }%
      {
        \theorem@style{#1}
        \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
        }
}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

\gdef\@xnthm#1#2[#3]{%
  \ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \expandafter\@ifundefined{c@#1}%
        {\@definecounter{#1}}{}%
     \@newctr{#1}[#3]%
     \expandafter\xdef\csname the#1\endcsname{%
       \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
          {\noexpand\csname\the\theoremnumbering\endcsname{#1}}}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@ynthm#1#2{%
  \ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \expandafter\@ifundefined{c@#1}%
        {\@definecounter{#1}}{}%
     \expandafter\xdef\csname the#1\endcsname
        {\noexpand\csname\the\theoremnumbering\endcsname{#1}}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@othm#1[#2]#3{%
  \@ifundefined{c@#2}{\@nocounterr{#2}}%
   {\ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \global\@namedef{the#1}{\@nameuse{the#2}}%
     \expandafter\protected@xdef\csname num@addtheoremline#1\endcsname{%
              \noexpand\@num@addtheoremline{#1}{#3}}%
     \expandafter\protected@xdef\csname nonum@addtheoremline#1\endcsname{%
              \noexpand\@nonum@addtheoremline{#1}{#3}}%
    \theoremkeyword{#3}%
    \expandafter\protected@xdef\csname #1Keyword\endcsname
             {\the\theoremkeyword}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
                \@thm{#1}{#2}{#3}
        }%
     \global\@namedef{end#1}{\@endtheorem}
```

```
    \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi}
}
```

§ 343.4 HTML cross-referencing

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```
\newcommand{\LWR@inctheorem}{%
\addtocounter{LWR@thisautoid}{1}%
\LWR@stoppars%
\LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
\LWR@startpars%
}
```

§ 343.5 \newtheoremstyle

The following are patched for CSS.

These were in individual files thp.sty for plain, thmb.sty for margin break, etc. They are gathered together here.

Each theorem is encased in a BlockClass environment of class theorembody<style>.

Each header is encased in an \InlineClass of class theoremheader<style>.

```
\gdef\newtheoremstyle#1#2#3{%
  \expandafter\@ifundefined{th@#1}%
   {\expandafter\gdef\csname th@#1\endcsname{%
    \def\@begintheorem####1####2{%
    \LWR@inctheorem% lwarp
    #2}%
    \def\@opargbegintheorem####1####2####3{%
    \LWR@inctheorem% lwarp
    #3}%
}%
}%
{\PackageError{\basename}{Theorem style #1 already defined}\@eha}
}
```

§ 343.6 Standard styles

```
\renewtheoremstyle{plain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}

\renewtheoremstyle{break}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheaderbreak}%
```

```
        {##1\ ##2\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{change}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]}

\renewtheoremstyle{changebreak}%
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\theorem@separator}\newline
    ]}%
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{margin}%
  {\item[
        \InlineClass{theoremheadermargin}{##2 \qquad ##1\theorem@separator}
    ]}%
  {\item[
      \InlineClass{theoremheadermargin}{##2 \qquad ##1\ (##3)\theorem@separator}
    ]}

\renewtheoremstyle{marginbreak}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{nonumberplain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ (##3)\theorem@separator}]}

\renewtheoremstyle{nonumberbreak}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{empty}%
  {\item[]}%
  {\item[
    \InlineClass{theoremheaderplain}{##3}]}
```

```

\renewtheoremstyle{emptybreak}%
  {\item[]}%
  {\item[
    \InlineClass{theoremheaderplain}{##3}] \ \newline}
```

§ 343.7 Additional objects

The following manually adjust the CSS for the standard configuration objects which are not a purely plain style:

```
\ifbool{LWR@ntheoremamsthm}{}{%
```

Upright text via CSS:

```
    \newtheoremstyle{plainupright}%
    {\item[
        \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
    {\item[
        \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}
```

Upright text and small caps header via CSS:

```
    \newtheoremstyle{nonumberplainuprightsc}%
    {\item[
        \InlineClass{theoremheadersc}{##1\theorem@separator}]}%
    {\item[
        \InlineClass{theoremheadersc}{##1\ (##3)\theorem@separator}]}
}% not amsthm
```

§ 343.8 Renewed standard configuration

The following standard configuration is renewed using the new CSS:

```
\ifbool{LWR@ntheoremamsthm}{}{%
```

```
\ifx\thm@usestd\@undefined
\else
    \theoremnumbering{arabic}
    \theoremstyle{plain}
    \RequirePackage{latexsym}
    \theoremsymbol{\Box}
    \theorembodyfont{\itshape}
    \theoremheaderfont{\normalfont\bfseries}
    \theoremseparator{}
    \renewtheorem{Theorem}{Theorem}
    \renewtheorem{theorem}{Theorem}
    \renewtheorem{Satz}{Satz}
    \renewtheorem{satz}{Satz}
    \renewtheorem{Proposition}{Proposition}
    \renewtheorem{proposition}{Proposition}
    \renewtheorem{Lemma}{Lemma}
    \renewtheorem{lemma}{Lemma}
    \renewtheorem{Korollar}{Korollar}
```

```
    \renewtheorem{korollar}{Korollar}
    \renewtheorem{Corollary}{Corollary}
    \renewtheorem{corollary}{Corollary}

    \theoremstyle{plainupright}
    \theorembodyfont{\upshape}
    \theoremsymbol{\HTMLunicode{25A1}}% UTF-8 white box
    \renewtheorem{Example}{Example}
    \renewtheorem{example}{Example}
    \renewtheorem{Beispiel}{Beispiel}
    \renewtheorem{beispiel}{Beispiel}
    \renewtheorem{Bemerkung}{Bemerkung}
    \renewtheorem{bemerkung}{Bemerkung}
    \renewtheorem{Anmerkung}{Anmerkung}
    \renewtheorem{anmerkung}{Anmerkung}
    \renewtheorem{Remark}{Remark}
    \renewtheorem{remark}{Remark}
    \renewtheorem{Definition}{Definition}
    \renewtheorem{definition}{Definition}

    \theoremstyle{nonumberplainuprightsc}
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \renewtheorem{Proof}{Proof}
    \renewtheorem{proof}{Proof}
    \renewtheorem{Beweis}{Beweis}
    \renewtheorem{beweis}{Beweis}
    \qedsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof

    \theoremsymbol{}
\fi
}% not amsthm
```

§ 343.9 amsthm option

Only if the amsthm option was given:

```
\ifbool{LWR@ntheoremamsthm}{

\gdef\th@plain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderplain}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberplain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
```

```
      \item[
  \InlineClass{theoremheaderplain}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ (##3).}
        ]}}

\gdef\th@definition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberdefinition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderdefinition}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ (##3).}
        ]}}

\gdef\th@remark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderremark}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberremark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1.}
        ]}%
```

```
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderremark}{##1\ (##3).}
        ]}}

\gdef\th@proof{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderproof}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderproof}{##1\ (##3).}
        ]}}



\newcounter{proof}%
\if@thmmarks
    \newcounter{currproofctr}%
    \newcounter{endproofctr}%
\fi

\gdef\proofSymbol{\openbox}

\newcommand{\proofname}{Proof}

\newenvironment{proof}[1][\proofname]{
    \th@proof
    \def\theorem@headerfont{\itshape}%
    \normalfont
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \@thm{proof}{proof}{#1}
}%
{\@endtheorem}

}{}% amsthm option
```

§ 343.10 Ending a theorem

Patched for CSS:

```
\let\LWR@origendtheorem\@endtheorem
\renewcommand{\@endtheorem}{%
\ifbool{LWR@ntheoremmarks}{%
    \ifsetendmark%
    \InlineClass{theoremendmark}{\csname\InTheoType Symbol\endcsname}%
    \setendmarkfalse%
    \fi%
}{}%
\LWR@origendtheorem% also does \@endtrivlist
```

```
\ifbool{LWR@ntheoremmarks}{\global\setendmarktrue}{}%
\endBlockClass%
}
```

§ 343.11 \NoEndMark

```
\gdef\NoEndMark{\global\setendmarkfalse}
```

§ 343.12 List-of

Redefined to reuse the float mechanism to add list-of-theorem links:

\thm@thmline {⟨*1: printed type*⟩} {⟨*2: #*⟩} {⟨*3: optional*⟩} {⟨*4: page*⟩}

```
\renewcommand{\thm@@thmline@noname}[4]{%
\hypertocfloat{1}{theorem}{thm}{#2 #3}{}%
}

\renewcommand{\thm@@thmline@name}[4]{%
\hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}%
}
```

This was redefined by ntheorem when loaded, so it is now redefined for lwarp:

```
\def\thm@@thmline{\thm@@thmline@name}
```

Patch for css:

```
\def\listtheorems#1{
\LWR@htmlelementclass{nav}{lothm}%
\begingroup
\c@tocdepth=-2%
\def\thm@list{#1}\thm@processlist
\endgroup
\LWR@htmlelementclassend{nav}{lothm}%
}
```

§ 343.13 Symbols

Proof QED symbol:

```
\newcommand{\qed}{\qquad\the\qedsymbol}

\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box

\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

\appto\LWR@restoreorigformatting{%
```

```
\LetLtxMacro\openbox\LWR@orig@openbox%
\LetLtxMacro\blacksquare\LWR@orig@blacksquare%
\LetLtxMacro\Box\LWR@orig@Box%
}% appto
}{}% @ifundefined
}% AtBeginDocument
```

§ 343.14 Cross-referencing

\thref {⟨*label*⟩}

```
\newcommand*{\thref}[1]{\cref{#1}}%
```

File 247 **lwarp-octave.sty**

§ 344 Package octave

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg octave octave is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{octave}[2017/10/31]
```

Remove the leading 1pt kern:

```
\RenewDocumentCommand{\@PrintTicks}{ m }{%
\kern-1pt%  lwarp
\@TickNum = #1%
\loop
\@Tick{}%
\advance\@TickNum by -1
\ifnum\@TickNum > 0
\repeat
}
```

Use unicode for the prime character:

```
\RenewDocumentCommand{\@Tick}{}{\HTMLunicode{2032}}
```

Catch the inline font:

```
\RenewDocumentCommand{\pitch}{ m o m }{%
\if@OctaveNumber%
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \MakeUppercase{#1}%
            \IfValueTF{#2}{#2}{}\textsubscript{#3}%
        }%
    }%
}%
\else%
```

```
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \@GetOctaveTick{#1}[#2]{#3}%
        }%
    }%
}%
\fi%
}
```

The original was hard to adapt to lwarp's handling of &.

```
\StartDeferingTabulars
\renewcommand{\octavetable}{%
\begin{tabular}{ll}
\octaveprimes \pitch{C}{0} & \octavenumbers \pitch{C}{0} \\
\octaveprimes \pitch{C}{1} & \octavenumbers \pitch{C}{1} \\
\octaveprimes \pitch{C}{2} & \octavenumbers \pitch{C}{2} \\
\octaveprimes \pitch{C}{3} & \octavenumbers \pitch{C}{3} \\
\octaveprimes \pitch{C}{4} & \octavenumbers \pitch{C}{4} \\
\octaveprimes \pitch{C}{5} & \octavenumbers \pitch{C}{5} \\
\octaveprimes \pitch{C}{6} & \octavenumbers \pitch{C}{6} \\
\octaveprimes \pitch{C}{7} & \octavenumbers \pitch{C}{7} \\
\end{tabular}
}
\StopDeferingTabulars
```

File 248 **lwarp-overpic.sty**

§ 345 Package

overpic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg `overpic` overpic is patched for use by lwarp.

⚠ scaling The macros `\overpicfontsize` and `\overpicfontskip` are used during HTML generation. These are sent to `\fontsize` to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the `overpic` and `Overpic` environments.

See section 83.2 for the print-mode version of `\overpicfontsize` and `\overpicfontskip`.

for HTML output:

```
\LWR@ProvidesPackagePass{overpic}[2017/10/06]
```

```
\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}

\BeforeBeginEnvironment{overpic}{%
    \begin{lateximage}%
    \fontsize{\overpicfontsize}{\overpicfontskip}%
    \selectfont%
}
```

```

\AfterEndEnvironment{overpic}{\end{lateximage}}

\BeforeBeginEnvironment{Overpic}{%
    \begin{lateximage}%
    \fontsize{\overpicfontsize}{\overpicfontskip}%
    \selectfont%
}

\AfterEndEnvironment{Overpic}{\end{lateximage}}
```

File 249 **lwarp-pagegrid.sty**

§ 346 Package pagegrid

Pkg pagegrid pagegrid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pagegrid}[2016/05/16]

\newcommand*{\pagegridsetup}[1]{}
```

File 250 **lwarp-pagenote.sty**

§ 347 Package pagenote

Pkg pagenote pagenote works as-is, but the page option is disabled.

for HTML output:

```
\DeclareOption{page}{}
\LWR@ProvidesPackagePass{pagenote}[2009/09/03]
```

File 251 **lwarp-pagesel.sty**

§ 348 Package pagesel

Pkg pagesel pagesel is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pagesel}[2016/05/16]
```

File 252 **lwarp-paralist.sty**

§ 349 Package paralist

(*Emulates or patches code by* Bernd Schandl.)

Pkg paralist

paralist is supported with minor changes.

for HTML output:

```
\LWR@ProvidesPackagePass{paralist}[2017/01/22]
```

The compact environments are identical to the regular ones:

```
\LetLtxMacro\compactitem\itemize
\LetLtxMacro\compactenum\enumerate
\LetLtxMacro\compactdesc\description
\LetLtxMacro\endcompactitem\enditemize
\LetLtxMacro\endcompactenum\endenumerate
\LetLtxMacro\endcompactdesc\enddescription
```

For the inline environments, revert `\item` to its original print-mode version:

```
\AtBeginEnvironment{inparaitem}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparaenum}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparadesc}{\LetLtxMacro\item\LWR@origitem}
```

Manual formatting of the description labels:

```
\def\paradescriptionlabel#1{{\normalfont\textbf{#1}}}
```

File 253 **lwarp-parnotes.sty**

§ 350 Package

parnotes

(*Emulates or patches code by* Chelsea Hughes.)

Pkg parnotes

parnotes is supported with some patches.

for HTML output:

```
\LWR@ProvidesPackagePass{parnotes}[2016/08/15]
```

```
\long\def\PN@parnote@real#1#2{%
    \parnotemark{#1}%
    % Unless this is the first parnote in \PN@text, add a separator first
    \unless\ifx\PN@text\@empty\g@addto@macro\PN@text{\parnoteintercmd}\fi
    % Redefine \@currentlabel to the parnote label, so \label works
    \g@addto@macro\PN@text{%
%         \phantomsection%
        \def\@currentlabel{#1}%
        \def\cref@currentlabel{%        lwarp
            [parnotemark][\arabic{parnotemark}][]\theparnotemark%
        }%
    }%
    \g@addto@macro\PN@text{%
        \LWR@textcurrentfont{%          lwarp
            \parnotemark{#1}\nolinebreak\thinspace#2%
        }%
    }%
}

```

```
\def\PN@parnotes@real{%
    % We call \par later, so this avoids recursion with \PN@parnotes@auto
    \PN@inparnotestrue
    \unless\ifvmode\par\fi
    % Avoid page breaks between a paragraph and its parnotes
    \nopagebreak\addvspace{\parnotevskip}%
    \LWR@forcenewpage%                  lwarp
    \begin{BlockClass}{footnotes}%      lwarp
    {\parnotefmt{\PN@text}\par}%
    \end{BlockClass}%                   lwarp
    \global\def\PN@text{}%
    \addvspace{\parnotevskip}%
    %
    % These can be enabled or disabled by package options
    %
    \PN@disable@indent
    \PN@reset@optional
    \PN@inparnotesfalse
}

\AtBeginDocument{
\crefname{parnotemark}{paragraph note}{paragraph notes}%
\Crefname{parnotemark}{Paragraph note}{Paragraph notes}
}
```

File 254 **lwarp-parskip.sty**

§ 351 Package parskip

Pkg parskip parskip is ignored.

for HTML output: Discard all options for lwarp-parskip.

```
\LWR@ProvidesPackageDrop{parskip}[2001/04/09]
```

File 255 **lwarp-pbox.sty**

§ 352 Package pbox

(*Emulates or patches code by* Simon Law.)

Pkg pbox pbox is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{pbox}[2011/12/07]
```

```
\NewDocumentCommand{\pbox}{O{t} O{} O{t} m +m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox[#1][#2][#3]{#4}{#5}%
}
```

```
\newcommand{\settominwidth}[3][\columnwidth]{%
\settowidth{#2}{#3}%
}

\newcommand{\widthofpbox}[1]{%
\widthof{#1}%
}
```

File 256 **lwarp-pdfcomment.sty**

§ 353 Package pdfcomment

Pkg pdfcomment

pdfcomment is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcomment}[2016/06/13]
```

```
\newenvironment{pdfsidelinecomment}[2][]{}{}
\newcommand{\pdfcomment}[2][]{}
\newcommand{\pdfmargincomment}[2][]{}
\newcommand{\pdfmarkupcomment}[3][]{#2}
\newcommand{\pdffreetextcomment}[2][]{}
\newcommand{\pdfsquarecomment}[2][]{}
\newcommand{\pdfcirclecomment}[2][]{}
\newcommand{\pdflinecomment}[2][]{}
\newcommand{\pdftooltip}[3][]{#2}
\newcommand{\pdfcommentsetup}[2][]{}
\newcommand{\listofpdfcomments}[1][]{}
\newcommand{\setliststyle}[1]{}
\newcommand{\defineliststyle}[2]{}
\newcommand{\defineavatar}[2]{}
\newcommand{\definestyle}[2]{}
```

File 257 **lwarp-pdflscape.sty**

§ 354 Package pdflscape

Pkg pdflscape

pdflscape is ignored.

for HTML output: Discard all options for lwarp-pdflscape:

```
\LWR@ProvidesPackageDrop{pdflscape}[2016/05/14]
```

File 258 **lwarp-pdfmarginpar.sty**

§ 355 Package pdfmarginpar

Pkg pdfmarginpar

pdfmarginpar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfmarginpar}[2011/08/05]
```

```
\newcommand{\pdfmarginpar}[2][]{}
\newcommand{\pdfmarginparset}[1]{}
```

File 259 **lwarp-pdfpages.sty**

§ 356 Package

pdfpages

(*Emulates or patches code by* Andreas Matthias.)

Pkg pdfpages

pdfpages is patched for use by lwarp.

Option `link` and `linkname` work:

```
\hyperlink{<filename>.pdf.<pagenubmer}}{some text}
\hyperlink{<linkname>.<pagenubmer}}{some text}
```

Options which make no sense in HTML are disabled.

for HTML output:

```
\LWR@ProvidesPackagePass{pdfpages}[2017-10-31]
```

Disable option which have no meaning for HTML output:

```
\define@key{pdfpages}{fitpaper}[false]{}
\define@key{pdfpages}{landscape}[false]{}
\define@key{pdfpages}{openright}[false]{}
\define@key{pdfpages}{signature}{}
\define@key{pdfpages}{signature*}{}
\define@key{pdfpages}{booklet}[false]{}
\define@key{pdfpages}{rotateoversize}[false]{}
\define@key{pdfpages}{doublepages}[false]{}
\define@key{pdfpages}{doublepagestwist}[false]{}
\define@key{pdfpages}{doublepagestwistodd}[false]{}
\define@key{pdfpages}{doublepagestwist*}[false]{}
\define@key{pdfpages}{doublepagestwistodd*}[false]{}
\define@key{pdfpages}{duplicatepages}[2]{}
\define@key{pdfpages}{thread}[false]{}
\define@key{pdfpages}{threadname}{}
\define@key{pdfpages}{linkfit}{}
\define@key{pdfpages}{linktodoc}[false]{}
\define@key{pdfpages}{linktodocfit}{}
\define@key{pdfpages}{linkfilename}{}
\define@key{pdfpages}{survey}[false]{}
\define@key{pdfpages}{survey-nolink}[false]{}
\define@key{pdfpages}{newwindow}[false]{}
```

Use print mode while measuring the page numbers:

```
\xpretocmd{\AM@getpagecount}{\LWR@restoreorigformatting}{}{}
```

Emulate a bit of eso-pic:

```
\newif\ifESO@texcoord

\newcommand{\ESO@HookIIBG}{}

\renewcommand{\AM@AddToShipoutPicture}{\g@addto@macro\ESO@HookIIBG}

\renewcommand{\ClearShipoutPicture}{}
```

\LWR@esopic@newpage At each \newpage.

```
\newcommand*{\LWR@esopic@newpage}{%
```

Is there something to draw?

```
\ifdefvoid{\ESO@HookIIBG}%
{}%
{%
```

If the link option was specified, add a hyper taraget:

```
    \ifAM@link%
        \hypertarget{\AM@linkname.\AM@page}{}%
    \fi%
```

Draw inside a picture environment of the size of a virtual page:

```
    \begingroup%
    \setlength{\unitlength}{1in}%
    \begin{picture}(8,10.5)%
    \ESO@HookIIBG%
    \end{picture}%
    \endgroup%
    \global\let\ESO@HookIIBG\@empty%
}
}
```

\AM@output Patched to use \LWR@esopic@newpage.

```
\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-1}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-2}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-3}}
```

\includepdf Patched to set a reasonable paper size.

```
\xpretocmd{\includepdf}{%
    \begingroup%
    \setlength{\paperwidth}{8in}%
    \setlength{\paperheight}{10.5in}%
}{}{}

\xapptocmd{\includepdf}{%
    \endgroup%
}{}{}
```

\includepdfmerge Patched to set a reasonable paper size.

```
\xpretocmd{\includepdfmerge}{%
    \begingroup%
    \setlength{\paperwidth}{8in}%
    \setlength{\paperheight}{10.5in}%
}{}{}

\xapptocmd{\includepdfmerge}{%
    \endgroup%
}{}{}
```

\AM@hyper@begin@i Hyper links are created by \LWR@esopic@newpage, so don't create them here:

```
\renewcommand{\AM@hyper@begin@i}{}
```

File 260 **lwarp-pdfprivacy.sty**

§ 357 Package pdfprivacy

Pkg pdfprivacy pdfprivacy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfprivacy}[2017/12/03]
```

File 261 **lwarp-pdfrender.sty**

§ 358 Package pdfrender

Pkg pdfrender pdfrender is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfrender}[2016/05/17]
```

```
\newcommand*{\pdfrender}[1]{}
\newcommand{\textpdfrender}[2]{#2}
```

File 262 **lwarp-pdfsync.sty**

§ 359 Package

pdfsync

(*Emulates or patches code by* J. Laurens.)

Pkg pdfsync Emulated.

for HTML output: Discard all options for lwarp-pdfsync:

```
\LWR@ProvidesPackageDrop{pdfsync}[2008/01/26]
```

```
\newcommand*{\pdfsync}{}
\newcommand*{\pdfsyncstart}{}
\newcommand*{\pdfsyncstop}{}
```

File 263 **lwarp-pdftricks.sty**

§ 360 Package

pdftricks

(*Emulates or patches code by* C. V. Radhakrishnan, C. V. Rajagopal, Antoine Chambert-Loir.)

Pkg pdftricks pdftricks is patched for use by lwarp.

⚠ convert image files The pdftricks image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **`lwarpmk pdftosvg <jobname>-fig*.pdf`**

for HTML output:

```
\LWR@ProvidesPackagePass{pdftricks}[2003/08/10]
```

Reuse the print-mode images:

```
\def\PDFTfigname{\BaseJobname-fig\thepsfig}
```

If the `.pdf` images have not yet been converted to `.svg` then an error about a missing file will occur. Warn the user to convert the images.

```
\PackageWarning{lwarp-pdftricks}{
When the pdftricks images change,
remember to convert PDF images to SVG using 'lwarpmk pdftosvg *-fig.pdf',
}

\AfterEndDocument{\typeout{***}}
\AfterEndDocument{\typeout{*** Note: If pdftricks images are not found, new, or updated,}}
\AfterEndDocument{\typeout{*** \space use 'lwarpmk pdftosvg \BaseJobname-fig*.pdf'}}
\AfterEndDocument{\typeout{***}}
```

File 264 **lwarp-pdfx.sty**

§ 361 Package

pdfx

Pkg pdfx pdfx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfx}[2017/05/18]
```

File 265 **lwarp-perpage.sty**

§ 362 Package

perpage

(*Emulates or patches code by* David Kastrup.)

Pkg perpage perpage is mostly ignored, but support is added for footnote counters.

There is no page number in HTML, so most counters are not reset. If the document redefines `\the<countername>` to include `\theperpage`, it is necessary to place that redefininition inside a `warpprint` environment to avoid modifying the HTML defintions.

`\AddAbsoluteCounter` must not be inside `warpprint`, as the counter must be added for HTML also, although it is not incremented.

footnote numbering To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by `FootnoteDepth`, which is not necessarily by HTML page. This is recommended for `\alph`, `\Alph`, or `\fnsymbol` footnotes, due to the limited number of symbols which are available.

for HTML output:

```
\LWR@ProvidesPackageDrop{perpage}[2014/10/25]

\newcommand\AddAbsoluteCounter[1]
{
    \@ifundefined{c@abs#1}{%
        \expandafter\newcount\csname c@abs#1\endcsname
        \global\value{abs#1}\@ne
%         \global\expandafter\let\csname cl@abs#1\endcsname\@empty
        \expandafter\xdef\csname theabs#1\endcsname{%
%             \noexpand\number \csname c@abs#1\endcsname
```

```
        }%
%         \global\@namedef{c@pabs@#1}{\pp@cl@begin
%         \stepcounter{abs#1}%
%         \pp@cl@end}%
%         \@addtoreset{pabs@#1}{#1}
    }
    {}
}

\AddAbsoluteCounter{page}
\def\theabspage{1}

\newcommand*\MakePerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
    }{

}%
}

\newcommand*\MakeSorted[1]{}

\newcommand*\MakeSortedPerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
    }{
}%
}

\newcommand*{\theperpage}{1}
```

File 266 **lwarp-pfnote.sty**

§ 363 Package

pfnote

Pkg pfnote

pfnote is emulated.

pfnote

⚠ pfnote numbers

While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

for HTML output:

```
\LWR@ProvidesPackageDrop{pfnote}[1999/07/14]
```

File 267 **lwarp-phfqit.sty**

§ 364 Package

phfqit

(*Emulates or patches code by* Philippe Faist.)

Pkg phfqit

phfqit is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{phfqit}[2017/08/16]

\LetLtxMacro\LWR@origbitstring\bitstring

\renewcommand\bitstring[1]{%
\InlineClass[%
    text-decoration: overline underline ;
]{bitstring}{#1}%
% \phfqit@bitstring{#1}%
}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bitstring\LWR@origbitstring%
}
```

File 268 **lwarp-pifont.sty**

§ 365 Package pifont

(*Emulates or patches code by* Walter Schmidt.)

Pkg pifont pifont is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```
\LWR@ProvidesPackagePass{pifont}[2005/04/12]

\renewcommand{\Pisymbol}[2]{%
    \begin{lateximage}*[(Pisymbol)][pisymbol#1#2]%
    {\Pifont{#1}\char#2}%
    \end{lateximage}%
}

\newcommand{\LWR@HTML@Pifill}[2]{
    \Pisymbol{#1}{#2} \Pisymbol{#1}{#2} \Pisymbol{#1}{#2}
}
\LWR@formatted{Pifill}

\newcommand{\LWR@HTML@Piline}[2]{%
    \par\noindent\hspace*{0.5in}
    \Pifill{#1}{#2} \Pifill{#1}{#2} \Pifill{#1}{#2}
}
\LWR@formatted{Piline}
```

File 269 **lwarp-placeins.sty**

§ 366 Package placeins

(*Emulates or patches code by* Donald Arseneau.)

Pkg placeins

placeins is not used during HTML conversion.

Discard all options for lwarp-placeins:

for HTML output:

```
\LWR@ProvidesPackageDrop{placeins}[2005/04/18]

\newcommand*{\FloatBarrier}{}
```

File 270 **lwarp-plarydshln.sty**

§ 367 Package plarydshln

Pkg plarydshln

plarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plarydshln}[2018/10/20]

\LWR@origRequirePackage{lwarp-arydshln}
```

File 271 **lwarp-plext.sty**

§ 368 Package plext

Pkg plext

plext is preloaded by jtarticle and related classes.

for HTML output:

```
\LWR@loadbefore{plext}

\LWR@ProvidesPackagePass{plext}[2017/07/21]

\let\tate\relax

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

% \layoutfloat(width,height)[pos]#4
\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

% \DeclareLayoutCaption{type} <dir>(width)[pos1pos2]
\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

% \layoutcaption<dir>(width)[pos]
\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
```

Add the optional <t/y> direction:

```
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
```

```
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

% \pbox <t/y> [width] [l/r] {contents}
\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

picture, as modified by pext, is encapsulated by the lwarp core.

File 272 **lwarp-plextarydshln.sty**

§ 369 Package plextarydshln

Pkg plextarydshln plextarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextarydshln}[2018/10/20]

\LWR@origRequirePackage{lwarp-arydshln}
```

File 273 **lwarp-plextcolortbl.sty**

§ 370 Package plextcolortbl

Pkg plextcolortbl plextcolortbl is emulated by lwarp-colortbl.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextcolortbl}[2018/09/19]

\LWR@origRequirePackage{lwarp-colortbl}
```

File 274 **lwarp-prelim2e.sty**

§ 371 Package prelim2e

(*Emulates or patches code by* Martin Schröder.)

Pkg prelim2e Emulated.

for HTML output:

Discard all options for lwarp-prelim2e:

```
\LWR@ProvidesPackageDrop{prelim2e}[2009/05/29]

\newcommand{\PrelimText}{}
\newcommand{\PrelimTextStyle}{}
\newcommand{\PrelimWords}{}
```

File 275 **lwarp-prettyref.sty**

§ 372 Package prettyref

(*Emulates or patches code by* Kevin S. Ruland.)

Pkg prettyref prettyref is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{prettyref}[1998/07/09]

\newrefformat{fig}{Figure \ref{#1}}
\newrefformat{tab}{Table \ref{#1}}
```

File 276 **lwarp-preview.sty**

§ 373 Package preview

Pkg preview preview is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{preview}[2017/04/24]

\newenvironment{preview}{}{}
\newenvironment{nopreview}{}{}
\NewDocumentCommand{\PreviewMacro}{s o o +m}{}
\NewDocumentCommand{\PreviewEnvironment}{s o o +m}{}
\newcommand{\PreviewSnarfEnvironment}[2][]{}
\NewDocumentCommand{\PreviewOpen}{s o}{}
\NewDocumentCommand{\PreviewClose}{s o}{}
\let\ifPreview\iffalse% \fi for syntax highlighting
```

File 277 **lwarp-psfrag.sty**

§ 374 Package psfrag

(*Emulates or patches code by* Michael C. Grant, David Carlisle.)

Pkg psfrag psfrag is patched for use by lwarp.

⚠ use psfrags The psfrags environment is modified to use lateximage to encapsulate the image.

Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

for HTML output:

```
\LWR@ProvidesPackagePass{psfrag}[1998/04/11]
```

A lateximage captures the modified image from the document.

```
\BeforeBeginEnvironment{psfrags}{%
    \begin{lateximage}[(-psfrags-~\packagediagramname)]%
}

\AfterEndEnvironment{psfrags}{\end{lateximage}}
```

File 278 **lwarp-psfragx.sty**

§ 375 Package psfragx

(*Emulates or patches code by* PASCAL KOCKAERT.)

Pkg psfragx psfragx is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{psfragx}[2012/05/02]
```

A lateximage captures the modified image from the document.

```
\def\pfx@includegraphicx#1#2{%
    \begin{lateximage}[(-psfragx-~\packagediagramname)]%
    \mbox{\pfx@overpix{#1}{#2}\endpfx@overpix}%
    \end{lateximage}%
}

\def\@@@overpix[#1]<#2>[#3]#4{%
    \begin{lateximage}[(-psfragx-~\packagediagramname)]%
    \pfx@overpix{#1,ovpfgd={#2},ovpbgd={#3}}{#4}%
}

\def\endoverpix{%
    \endpfx@overpix%
    \end{lateximage}%
}
```

File 279 **lwarp-pst-eps.sty**

§ 376 Package pst-eps

(*Emulates or patches code by* HERBERT VOSS.)

Pkg pst-eps pst-eps is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{pst-eps}[2005/05/20]

\renewenvironment{TeXtoEPS}{}{}
\renewcommand{\PSTtoEPS}[3][]{}
```

File 280 **lwarp-pstool.sty**

§ 377 Package

pstool

(*Emulates or patches code by* Zebb Prime, Will Robertson.)

Pkg pstool pstool is patched for use by lwarp.

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

for HTML output:

```
\LWR@ProvidesPackagePass{pstool}[2018/01/20]
```

Each image is placed inside a lateximage to capture the results of psfrag.

```
\renewcommand\pstool@alwaysprocess[3][]{%
    \begin{lateximage}[(-pstool-~\packagediagramname)]%
    \includegraphics{#2.pdf}%
    \end{lateximage}%
}
\LetLtxMacro\pstool@neverprocess\pstool@alwaysprocess
\LetLtxMacro\pstool@maybeprocess\pstool@alwaysprocess

\renewcommand\pstool@@psfragfig[4]{%
    \begin{lateximage}[(-pstool-~\packagediagramname)]%
    \includegraphics{#2.pdf}%
    \end{lateximage}%
}
```

File 281 **lwarp-pstricks.sty**

§ 378 Package

pstricks

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg pstricks pstricks is patched for use by lwarp.

⚠ use pspicture All pstricks content should be contained inside a pspicture environment.

for HTML output:

```
\LWR@ProvidesPackagePass{pstricks}[2018/01/06]

\BeforeBeginEnvironment{pspicture}{\begin{lateximage}[(pspicture)]}
\AfterEndEnvironment{pspicture}{\end{lateximage}}
```

File 282 **lwarp-pxatbegshi.sty**

§ 379 Package

pxatbegshi

Pkg pxatbegshi pxatbegshi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxatbegshi}[2017/11/04]

\LWR@origRequirePackage{lwarp-atbegshi}
```

File 283 **lwarp-pxeveryshi.sty**

§ 380 Package

pxeveryshi

Pkg pxeveryshi pxeveryshi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxeveryshi}[2012/05/19]

\LWR@origRequirePackage{lwarp-everyshi}
```

File 284 **lwarp-pxftnright.sty**

§ 381 Package

pxftnright

Pkg pxftnright pxftnright is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxftnright}[2017/02/28]
```

```
\LWR@origRequirePackage{lwarp-ftnright}
```

File 285 **lwarp-pxjahyper.sty**

§ 382 Package

pxjahyper

Pkg pxjahyper

pxjahyper is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxjahyper}[2018/07/15]
```

File 286 **lwarp-quotchap.sty**

§ 383 Package

quotchap

(*Emulates or patches code by* Karsten Tinnefeld, Jan Klever.)

Pkg quotchap

quotchap is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{quotchap}[2012/10/20]

\newcommand{\@quotchap}{}
\newlength{\LWR@quotchapwidth}

\let\@printcites\relax

\newcommand*{\@iprintcites}{%
```

Place the quotes inside a of class quotchap, of the maximum selected width:

```
\begin{BlockClass}[max-width: \LWR@printlength{\LWR@quotchapwidth}]{quotchap}
%\begin{minipage}{\LWR@quotchapwidth}
\@quotchap
%\end{minipage}
\end{BlockClass}
```

Deactivate the quote printing:

```
\global\let\@printcites\relax
}

\NewEnviron{savequote}[1][\linewidth]{%
```

Remember the width, adjusted for HTML, and make the length assignment global, per: https://tex.stackexchange.com/questions/300823/why-is-setlength-ineffective-inside-a-tabular-environment

```
\setlength{\LWR@quotchapwidth}{#1*2}%
\global\LWR@quotchapwidth=\LWR@quotchapwidth%
```

Remember the body, and activate the quote printing:

```
\global\let\@quotchap\BODY
\global\let\@printcites\@iprintcites%
}
```

The quotation author is placed inside a of class qauthor:

```
\newcommand{\qauthor}[1]{\begin{BlockClass}{qauthor}{#1}\end{BlockClass}}
```

\qsetcnfont is ignored:

```
\newcommand{\qsetcnfont}[1]{}
```

File 287 **lwarp-quoting.sty**

§ 384 Package quoting

(*Emulates or patches code by* Thomas Titz.)

Pkg quoting quoting is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{quoting}[2014/01/28]
```

```
\xpatchcmd{\quoting}{\quo@begintext}
    {\begin{LWR@blocktextcurrentfont}\quo@begintext}
    {}
    {\LWR@patcherror{quoting}{quoting}}

\xpatchcmd{\endquoting}{\quo@endtext}
    {\quo@endtext\end{LWR@blocktextcurrentfont}}
    {}
    {\LWR@patcherror{imakeidx}{endquoting}}
```

File 288 **lwarp-ragged2e.sty**

§ 385 Package ragged2e

(*Emulates or patches code by* Martin Schröder.)

Pkg ragged2e ragged2e is not used during HTML conversion.

Discard all options for lwarp-ragged2e:

for HTML output:

```
\LWR@ProvidesPackageDrop{ragged2e}[2009/05/21]
```

```
\LetLtxMacro\Centering\centering
\LetLtxMacro\RaggedLeft\raggedleft
\LetLtxMacro\RaggedRight\raggedright
```

```
\newcommand*{\justifying}{}
\newlength{\CenteringLeftskip}
\newlength{\RaggedLeftLeftskip}
\newlength{\RaggedRightLeftskip}
\newlength{\CenteringRightskip}
\newlength{\RaggedLeftRightskip}
\newlength{\RaggedRightRightskip}
\newlength{\CenteringParfillskip}
\newlength{\RaggedLeftParfillskip}
\newlength{\RaggedRightParfillskip}
\newlength{\JustifyingParfillskip}
\newlength{\CenteringParindent}
\newlength{\RaggedLeftParindent}
\newlength{\RaggedRightParindent}
\newlength{\JustifyingParindent}
\newenvironment*{Center}{\center}{\endcenter}
\newenvironment*{FlushLeft}{\flushleft}{\endflushleft}
\newenvironment*{FlushRight}{\flushright}{\endflushright}
\newenvironment*{justify}{\justifying}{\endjustifying}
```

File 289 **lwarp-realscripts.sty**

§ 386 Package

realscripts

(*Emulates or patches code by* Will Robertson.)

Pkg realscripts realscripts is emulated. See `lwarp.css` for the `<span>` of class `supsubscript`.

for HTML output:

```
\LWR@ProvidesPackageDrop{realscripts}[2016/02/13]

\let\realsuperscript\textsuperscript
\let\realsubscript\textsubscript

\let\fakesuperscript\textsuperscript
\let\fakesubscript\textsubscript

\newlength{\subsupersep}

\newcommand*{\LWR@realscriptsalign}{}

\newcommand*{\LWR@setrealscriptsalign}[1]{%
    \renewcommand*{\LWR@realscriptsalign}{}%
    \ifthenelse{\equal{#1}{c}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:center} ; %
        }%
    }{}%
    \ifthenelse{\equal{#1}{r}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:right} ; %
        }%
    }{}%
}
```

```

\DeclareDocumentCommand \textsubsuperscript {s O{l} mm} {%
    \LWR@setrealscriptsalign{#2}%
    \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
        \textsuperscript{#4}\textsubscript{#3}%
    }%
}

\DeclareDocumentCommand \textsupersubscript {s O{l} mm} {%
    \LWR@setrealscriptsalign{#2}%
    \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
        \textsubscript{#4}\textsuperscript{#3}%
    }%
}
```

File 290 **lwarp-refcheck.sty**

§ 387 Package refcheck

Pkg refcheck refcheck is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{refcheck}[2013/02/14]

\def\showrefnames{}
\def\norefnames{}
\def\showcitenames{}
\def\nocitenames{}
\def\setonmsgs{}
\def\setoffmsgs{}
\def\checkunlbld{}
\def\ignoreunlbld{}
\newcommand*{\refcheckxrdoc}[2][]{}
```

File 291 **lwarp-register.sty**

§ 388 Package register

(*Emulates or patches code by* Matthew Lovell.)

Pkg register register is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{register}[2019/01/01]

\xpatchcmd{\register}
    {\centering}
    {\begin{center}\begin{lateximage}[(-register-~\packagediagramname)]}
    {}
    {\LWR@patcherror{register}{register}}

```

```
\xpatchcmd{\endregister}
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister}}

\expandafter\xapptocmd\csname register*\endcsname
    {\begin{center}\begin{lateximage}[(-register-~\packagediagramname)]}
    {}
    {\LWR@patcherror{register}{register*}}

\expandafter\xpatchcmd\csname endregister*\endcsname
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister*}}

\setlength{\regWidth}{5in}
```

File 292 **lwarp-relsize.sty**

§ 389 Package

relsize

(*Emulates or patches code by* Donald Arseneau, Bernie Cosell, Matt Swift.)

Pkg relsize

relsize is patched for use by lwarp.

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small

The HTML browser's setting for minumum font size may limit how small the output will be displayed.

for HTML output:

```
\LWR@ProvidesPackagePass{relsize}[2013/03/29]
```

```
\let\LWR@origrelsize\relsize
\LetLtxMacro\LWR@origlarger\larger
\LetLtxMacro\LWR@origsmaller\smaller
\let\LWR@relscale\relscale
\LetLtxMacro\LWR@origtextlarger\textlarger
\LetLtxMacro\LWR@origtextsmaller\textsmaller
\let\LWR@textscale\textscale
```

```

\appto\LWR@restoreorigformatting{%
\let\relsize\LWR@origrelsize%
\LetLtxMacro\larger\LWR@origlarger%
\LetLtxMacro\smaller\LWR@origsmaller%
\let\relscale\LWR@relscale%
\LetLtxMacro\textlarger\LWR@origtextlarger%
\LetLtxMacro\textsmaller\LWR@origtextsmaller%
\let\textscale\LWR@textscale%
}

\newcounter{LWR@relsizetemp}

\renewcommand*{\relsize}[1]{}
\renewcommand*{\larger}[1][]{}
\renewcommand*{\smaller}[1][]{}
\renewcommand*{\relscale}[1]{}

\renewcommand*{\textlarger}[2][1]{%
\setcounter{LWR@relsizetemp}{100+(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textlarger}{#2}%
}

\renewcommand*{\textsmaller}[2][1]{%
\setcounter{LWR@relsizetemp}{100-(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textsmaller}{#2}%
}

\renewcommand*{\textscale}[2]{%
\setcounter{LWR@relsizetemp}{100*\real{#1}}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textscale}{#2}%
}
```

File 293 **lwarp-repeatindex.sty**

§ 390 Package

repeatindex

Pkg repeatindex

repeatindex is emulated for lwarp.

⚠ style file

lwarp must be used with a special style file:

```
\usepackage[makeindex,makeindexStyle={lwarp_repeatindex}]{lwarp}
```

where lwarp_repeatindex.ist may be copied from the following modified version of lwarp.ist:

```
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
      \\par\\textbf{#1}\\par
      \\nopagebreak
```

```
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 "], \\hyperindexref{"
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"

item_0 "\n  \\item ["
```

(The modifications are the `delim_0` and `item_0` entries.)

for HTML output:

```
\LWR@ProvidesPackageDrop{repeatindex}[2001/10/13]
```

In the lwarp core, `\LWR@indexitem` is modified to accept the optional `\item` argument.

```
\RequirePackage{makeidx}
\def\entryprefix{\itshape}
\def\entrypostfix{\dots}
```

File 294 **lwarp-resizegather.sty**

§ 391 Package resizegather

Pkg resizegather

resizegather is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{resizegather}[2016/05/16]
```

```
\newcommand*{\resizegathersetup}[1]{}
```

File 295 **lwarp-rmpage.sty**

§ 392 Package rmpage

Pkg rmpage

rmpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{rmpage}[1997/09/29]
```

File 296 **lwarp-romanbar.sty**

§ 393 Package romanbar

(*Emulates or patches code by* H.-Martin Münch.)

Pkg romanbar romanbar is patched for use by lwarp.

An inline class with an overline and underline is used.

for HTML output:

```
\LWR@ProvidesPackagePass{romanbar}[2012/01/01]

\DeclareRobustCommand{\Roman@bar}[1]{% #1 is in Roman, i.e. MMXII
\InlineClass[%
    text-decoration: overline underline ;
]{romanbar}{#1}%
}
```

File 297 **lwarp-romanbarpagenumber.sty**

§ 394 Package romanbarpagenumber

Pkg romanbarpagenumber romanbarpagenumber is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{romanbarpagenumber}[2015/02/06]
```

File 298 **lwarp-rotating.sty**

§ 395 Package rotating

(*Emulates or patches code by* Robin Fairbairns, Sebastian Rahtz, Leonor Barroca.)

Pkg rotating rotating is emulated.

All rotations are ignored in HTML output.

for HTML output:

```
\LWR@ProvidesPackageDrop{rotating}[2016/08/11]
\RequirePackage{graphicx}

\LetLtxMacro\sidewaystable\table
\let\endsidewaystable\endtable

\LetLtxMacro\sidewaysfigure\figure
\let\endsidewaysfigure\endfigure

```

```
\newenvironment*{sideways}{}{}
\newenvironment*{turn}[1]{}{}
\newenvironment*{rotate}[1]{}{}
\NewDocumentCommand{\turnbox}{m +m}{#2}
\let\rotcaption\caption
\let\@makerotcaption\@makecaption
```

File 299 **lwarp-rotfloat.sty**

§ 396 Package

rotfloat

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg rotfloat

rotfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{rotfloat}[2004/01/04]

\RequirePackage{float}
```

\newfloat {⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the \newfloat command from the float package. Sideways floats are \let to the same as regular floats.

"placement" is ignored.

```
\RenewDocumentCommand{\newfloat}{m m m o}{%
\IfValueTF{#4}%
{%
    \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}%
}%
{%
    \DeclareFloatingEnvironment[fileext=#3]{#1}%
}%
\csletcs{sideways#1}{#1}%
\csletcs{endsideways#1}{end#1}%
```

Remember the float style:

```
\csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
\csedef{LWR@floatstyle@sideways#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later:

```
\cslet{listof#1s}\relax%
\cslet{listof#1es}\relax%
\cslet{listofsideways#1s}\relax%
\cslet{listofsideways#1es}\relax%
}
```

File 300 **lwarp-rviewport.sty**

§ 397 Package

rviewport

Pkg rviewport

rviewport is honored inside a lateximage, and otherwise ignored for HTML output.

If rviewport is important for an image, enclose the image inside a lateximage environment.

for HTML output:

```
\LWR@ProvidesPackagePass{rviewport}[2011/08/27]
\define@key{igraph}{rviewport}{}
```

File 301 **lwarp-savetrees.sty**

§ 398 Package

savetrees

Pkg savetrees

Emulated.

for HTML output:

Discard all options for lwarp-savetrees:

```
\LWR@ProvidesPackageDrop{savetrees}[2016/04/13]
```

File 302 **lwarp-scalefnt.sty**

§ 399 Package

scalefnt

(*Emulates or patches code by* D. Carlisle.)

Pkg scalefnt

scalefnt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{scalefnt}
\DeclareRobustCommand\scalefont[1]{}
```

File 303 **lwarp-schemata.sty**

§ 400 Package

schemata

(*Emulates or patches code by* Charles P. Schaum.)

Pkg schemata

schemata is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{schemata}[2016/01/25]
```

```
\LetLtxMacro\LWR@schemata@origschema\schema
\LetLtxMacro\LWR@schemata@origSchema\Schema

\renewcommand{\schema}[3][open]{%
\begin{lateximage}%
\LWR@print@normalsize
\LWR@schemata@origschema[#1]{#2}{#3}%
\end{lateximage}%
}

\renewcommand{\Schema}[5][open]{%
\begin{lateximage}%
\LWR@print@normalsize
\LWR@schemata@origSchema[#1]{#2}{#3}{#4}{#5}%
\end{lateximage}%
}
```

File 304 **lwarp-scrextend.sty**

§ 401 Package

scrextend

Pkg scrextend

scrextend is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. `\DeclareDocumentCommand` is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{scrextend}[2018/03/30]

\DeclareDocumentCommand{\setkomafont}{m m}{}
\DeclareDocumentCommand{\addkomafont}{m m}{}
\DeclareDocumentCommand{\usekomafont}{m}{}

\DeclareDocumentCommand{\usefontofkomafont}{m}{}
\DeclareDocumentCommand{\useencodingofkomafont}{m}{}
\DeclareDocumentCommand{\usesizeofkomafont}{m}{}
\DeclareDocumentCommand{\usefamilyofkomafont}{m}{}
\DeclareDocumentCommand{\useseriesofkomafont}{m}{}
\DeclareDocumentCommand{\useshapeofkomafont}{m}{}

\AtBeginDocument{
\let\LWR@maketitle\maketitle
\DeclareDocumentCommand{\maketitle}{o}{\LWR@maketitle}
}

\DeclareDocumentCommand{\extratitle}{m}{}
\DeclareDocumentCommand{\titlehead}{m}{}
\DeclareDocumentCommand{\subject}{m}{}
\DeclareDocumentCommand{\publishers}{m}{\published{#1}}
\DeclareDocumentCommand{\uppertitleback}{m}{}
\DeclareDocumentCommand{\lowertitleback}{m}{}
\DeclareDocumentCommand{\dedication}{m}{}
```

```

\DeclareDocumentCommand{\ifthispageodd}{m m}{#1}

\DeclareDocumentCommand{\titlepagestyle}{}{}

\DeclareDocumentCommand{\cleardoublepageusingstyle}{m}{}
\DeclareDocumentCommand{\cleardoubleemptypage}{}{}
\DeclareDocumentCommand{\cleardoubleplainpage}{}{}
\DeclareDocumentCommand{\cleardoublestandardpage}{}{}
\DeclareDocumentCommand{\cleardoubleoddpage}{}{}
\DeclareDocumentCommand{\cleardoubleoddpageusingstyle}{m}{}
\DeclareDocumentCommand{\cleardoubleoddemptypage}{}{}
\DeclareDocumentCommand{\cleardoubleoddplainpage}{}{}
\DeclareDocumentCommand{\cleardoubleoddstandardpage}{}{}
\DeclareDocumentCommand{\cleardoubleevenpage}{}{}
\DeclareDocumentCommand{\cleardoubleevenpageusingstyle}{m}{}
\DeclareDocumentCommand{\cleardoubleevenemptypage}{}{}
\DeclareDocumentCommand{\cleardoubleevenplainpage}{}{}
\DeclareDocumentCommand{\cleardoubleevenstandardpage}{}{}

\DeclareDocumentCommand{\multiplefootnoteseparator}{}{%
  \begingroup\let\thefootnotemark\multfootsep\@makefnmark\endgroup
}

\DeclareDocumentCommand{\multfootsep}{}{,}

\DeclareDocumentCommand{\footref}{m}{%
  \begingroup
    \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
  \endgroup
  \@footnotemark
}

\DeclareDocumentCommand{\deffootnote}{o m m m}{}
\DeclareDocumentCommand{\deffootnotemark}{m}{}
\DeclareDocumentCommand{\setfootnoterule}{o m}{}
\DeclareDocumentCommand{\raggedfootnote}{}{}

\DeclareDocumentCommand{\dictum}{o m}{
\begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{dictum}
    #2
    \IfValueT{#1}
    {
        \ifbool{FormatWP}
      {\begin{BlockClass}[\LWR@print@mbox{border-top:} 1px solid gray]{dictumauthor}}
        {\begin{BlockClass}{dictumauthor}}
        \dictumauthorformat{#1}
        \end{BlockClass}
    }
\end{LWR@BlockClassWP}
}

\DeclareDocumentCommand{\dictumwidth}{}{}
\DeclareDocumentCommand{\dictumauthorformat}{m}{(#1)}
\DeclareDocumentCommand{\dictumrule}{}{}
```

```
\DeclareDocumentCommand{\raggeddictum}{}{}
\DeclareDocumentCommand{\raggeddictumtext}{}{}
\DeclareDocumentCommand{\raggeddictumauthor}{}{}

\DeclareDocumentEnvironment{labeling}{o m}
{%
\def\sc@septext{#1}%
\list{}{}%
\let\makelabel\labelinglabel%
}
{
\endlist
}

\DeclareDocumentCommand{\labelinglabel}{m}{%
#1 \qquad \sc@septext%
}

\let\addmargin\relax
\let\endaddmargin\relax
\cslet{addmargin*}{\relax}
\cslet{endaddmargin*}{\relax}

\NewDocumentEnvironment{addmargin}{s O{} m}
{
\setlength{\LWR@templengthtwo}{#3}
\ifblank{#2}
{
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthtwo}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
{
    \setlength{\LWR@templengthone}{#2}
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
}
{\end{BlockClass}}
```

Ref to create a starred environment:
https://tex.stackexchange.com/questions/45401/
use-the-s-star-argument-with-newdocumentenvironment

```

\ExplSyntaxOn
\cs_new:cpn {addmargin*} {\addmargin*}
\cs_new_eq:cN {endaddmargin*} \endaddmargin
\ExplSyntaxOff

\DeclareDocumentCommand{\marginline}{m}{\marginpar{#1}}
```

File 305 **lwarp-scrhack.sty**

§ 402 Package

scrhack

Pkg scrhack scrhack is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{scrhack}[2018/03/30]
```

File 306 **lwarp-scrlayer.sty**

§ 403 Package

scrlayer

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer scrlayer is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer}[2018/03/30]

\newcommand*{\DeclareSectionNumberDepth}[2]{}
\newcommand*{\DeclareLayer}[2][]{}
\newcommand*{\DeclareNewLayer}[2][]{}
\newcommand*{\ProvideLayer}[2][]{}
\newcommand*{\RedeclareLayer}[2][]{}
\newcommand*{\ModifyLayer}[2][]{}
\newcommand*{\layerhalign}{}
\newcommand*{\layervalign}{}
\newcommand*{\layerxoffset}{}
\newcommand*{\layeryoffset}{}
\newcommand*{\layerwidth}{}
\newcommand*{\layerheight}{}
\providecommand*{\LenToUnit}[1]{\strip@pt\dimexpr#1*\p@/\unitlength}
\newcommand*{\putUL}[1]{}
\newcommand*{\putUR}[1]{}
\newcommand*{\putLL}[1]{}
\newcommand*{\putLR}[1]{}
\newcommand*{\putC}[1]{}
\newcommand*{\GetLayerContents}[1]{}
\newcommand{\IfLayerExists}[3]{#3}
\newcommand*{\DestroyLayer}[1]{}
\newcommand*{\layercontentsmeasure}{}
\newcommand*{\currentpagestyle}{}
\newcommand*{\BeforeSelectAnyPageStyle}[1]{}
\newcommand*{\AfterSelectAnyPageStyle}[1]{}
\newcommand*{\DeclarePageStyleAlias}[2]{}
\newcommand*{\DeclareNewPageStyleAlias}[2]{}
\newcommand*{\ProvidePageStyleAlias}[2]{}
```

```
\newcommand*{\RedeclarePageStyleAlias}[2]{}
\newcommand*{\DestroyPageStyleAlias}[1]{}
\newcommand*{\GetRealPageStyle}[1]{}
\newcommand*{\DeclarePageStyleByLayers}[3][]{}
\newcommand*{\DeclareNewPageStyleByLayers}[3][]{}
\newcommand*{\ProvidePageStyleByLayers}[3][]{}
\newcommand*{\RedeclarePageStyleByLayers}[3][]{}
\NewDocumentCommand{\ForEachLayerOfPageStyle}{s m m}{}
\newcommand*{\AddLayersToPageStyle}[2]{}
\newcommand*{\AddLayersAtBeginOfPageStyle}[2]{}
\newcommand*{\AddLayersAtEndOfPageStyle}[2]{}
\newcommand*{\RemoveLayersFromPageStyle}[2]{}
\newcommand*{\AddLayersToPageStyleBeforeLayer}[3]{}
\newcommand*{\AddLayersToPageStyleAfterLayer}[3]{}
\newcommand*{\UnifyLayersAtPageStyle}[1]{}
\newcommand*{\ModifyLayerPageStyleOptions}[2]{}
\newcommand*{\AddToLayerPageStyleOptions}[2]{}
\newcommand{\IfLayerPageStyleExists}[3]{#3}
\newcommand{\IfRealLayerPageStyleExists}[3]{#3}
\newcommand{\IfLayerAtPageStyle}[4]{#4}
\newcommand{\IfSomeLayerAtPageStyle}[4]{#4}
\newcommand{\IfLayersAtPageStyle}[4]{#4}
\newcommand*{\DestroyRealLayerPageStyle}[1]{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\automark}{s o m}{}
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
```

```
\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\DeclareDocumentCommand{\GenericMarkFormat}{m}{}
```

```
\newcommand*{\@mkleft}[1]{}
\newcommand*{\@mkright}[1]{}
\newcommand*{\@mkdouble}[1]{}
\newcommand*{\@mkboth}[2]{}
\newcommand*{\scrlayerInitInterface}[1][]{}
\newcommand{\scrlayerAddToInterface}[3][]{}
\newcommand{\scrlayerAddCsToInterface}[3][]{}
\newcommand{\scrlayerOnAutoRemoveInterface}[2][]{}
```

File 307 **lwarp-scrlayer-notecolumn.sty**

§ 404 Package scrlayer-notecolumn

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-notecolumn scrlayer-notecolumn is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-notecolumn}[2018/02/02]

\newcommand*{\DeclareNoteColumn}[2][]{}
\newcommand*{\DeclareNewNoteColumn}[2][]{}
\newcommand*{\ProvideNoteColumn}[2][]{}
\newcommand*{\RedeclareNoteColumn}[2][]{}
\NewDocumentCommand{\makenote}{s o m}{\marginpar{#3}}
\newcommand*{\syncwithnotecolumn}[1][]{}
\newcommand*{\syncwithnotecolumns}[1][]{}
\newcommand*{\clearnotecolumn}[1][]{}
\newcommand*{\clearnotecolumns}[1][]{}
```

File 308 **lwarp-scrlayer-scrpage.sty**

§ 405 Package scrlayer-scrpage

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-scrpage scrlayer-scrpage is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-scrpage}[2018/03/30]

\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{s o m}{}
\NewDocumentCommand{\cehead}{s o m}{}
\NewDocumentCommand{\rehead}{s o m}{}
\NewDocumentCommand{\lohead}{s o m}{}
\NewDocumentCommand{\cohead}{s o m}{}
\NewDocumentCommand{\rohead}{s o m}{}
\NewDocumentCommand{\lefoot}{s o m}{}
\NewDocumentCommand{\cefoot}{s o m}{}
\NewDocumentCommand{\refoot}{s o m}{}
\NewDocumentCommand{\lofoot}{s o m}{}
\NewDocumentCommand{\cofoot}{s o m}{}
\NewDocumentCommand{\rofoot}{s o m}{}
\NewDocumentCommand{\ohead}{s o m}{}
\NewDocumentCommand{\chead}{s o m}{}
\NewDocumentCommand{\ihead}{s o m}{}
\NewDocumentCommand{\ofoot}{s o m}{}
\NewDocumentCommand{\cfoot}{s o m}{}
\NewDocumentCommand{\ifoot}{s o m}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
\newcommand*{\defpairofpagestyles}[3][]{}
\newcommand*{\newpairofpagestyles}[3][]{}
\newcommand*{\renewpairofpagestyles}[3][]{}
\newcommand*{\providepairofpagestyles}[3][]{}

\newcommand*{\clearmainofpairofpagestyles}{}
```

```
\newcommand*{\clearplainofpairofpagestyles}{}
\newcommand*{\clearpairofpagestyles}{}
\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}
```

```
\NewDocumentCommand{\deftriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\newtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\renewtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\providetriplepagestyle}{m o o m m m m m m}{}
\newcommand*{\defpagestyle}[3]{}
\newcommand*{\newpagestyle}[3]{}
\newcommand*{\providepagestyle}[3]{}
\newcommand*{\renewpagestyle}[3]{}
```

File 309 **lwarp-scrpage2.sty**

§ 406 Package

scrpage2

(*Emulates or patches code by* Markus Kohm.)

Pkg scrpage2 scrpage2 is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrpage2}[2018/03/30]
```

```
\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{o m}{}
\NewDocumentCommand{\cehead}{o m}{}
\NewDocumentCommand{\rehead}{o m}{}
\NewDocumentCommand{\lohead}{o m}{}
\NewDocumentCommand{\cohead}{o m}{}
\NewDocumentCommand{\rohead}{o m}{}
\NewDocumentCommand{\lefoot}{o m}{}
\NewDocumentCommand{\cefoot}{o m}{}
\NewDocumentCommand{\refoot}{o m}{}
\NewDocumentCommand{\lofoot}{o m}{}
\NewDocumentCommand{\cofoot}{o m}{}
\NewDocumentCommand{\rofoot}{o m}{}
\NewDocumentCommand{\ohead}{o m}{}
\NewDocumentCommand{\chead}{o m}{}
\NewDocumentCommand{\ihead}{o m}{}
\NewDocumentCommand{\ofoot}{o m}{}
\NewDocumentCommand{\cfoot}{o m}{}
\NewDocumentCommand{\ifoot}{o m}{}
\DeclareDocumentCommand{\automark}{o m}{}
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
\NewDocumentCommand{\deftripstyle}{m o o m m m m m m}{}
\NewDocumentCommand{\defpagestyle}{s m m m}{}
\NewDocumentCommand{\newpagestyle}{s m m m}{}
```

```
\NewDocumentCommand{\renewpagestyle}{s m m m}{}
\NewDocumentCommand{\providepagestyle}{s m m m}{}
\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\newcommand{\subsectionmarkformat}{}
\newcommand{\subsubsectionmarkformat}{}
\newcommand{\paragraphmarkformat}{}
\newcommand{\subparagraphmarkformat}{}

\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}
```

File 310 **lwarp-section.sty**

§ 407 Package

section

Pkg section

section is ignored.

(*Emulates or patches code by* Oliver Pretzel.)

for HTML output:

```
\LWR@ProvidesPackageDrop{section}
```

```
\ifx\chapter\undefined
 \def\chsize{\Large}\def\hdsize{\huge}\else
 \def\chsize{\huge}\def\hdsize{\Huge}
\fi
\let\ttsize\LARGE
\let\ausize\large
\let\dasize\large
\let\secsize\Large
\let\subsize\large
\let\hdpos\raggedright
\newcounter{hddepth}
\let\fpind\relax
\def\ttfnt{}
\def\hdfnt{}
\def\fefnt{}
\def\thfnt{}
\def\pgfnt{}
\def\hmkfnt{}
\let\mkcse\uppercase
\def\hddot{}
\def\cpdot{:}
\def\nmdot{}
\ifx\secindent\undefined
 \newdimen\secindent
 \newskip\secpreskp
 \newskip\secpstskp
 \newdimen\subindent
```

```
\newskip\subpreskp
\newskip\subpstskp
\newskip\parpstskp
\newcount\c@hddepth
\fi
```

File 311 **lwarp-sectionbreak.sty**

§ 408 Package sectionbreak

(*Emulates or patches code by* Michal Hoftich.)

Pkg sectionbreak sectionbreak is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{sectionbreak}[2018-01-03]

\renewcommand\asterism{\HTMLunicode{2042}}

\renewcommand\pre@sectionbreak{}
\renewcommand\post@sectionbreak{}

\renewcommand\print@sectionbreak[1]{%
\begin{center}
#1
\end{center}
}

```

File 312 **lwarp-sectsty.sty**

§ 409 Package sectsty

(*Emulates or patches code by* Rowland McDonnell.)

Pkg sectsty sectsty is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{sectsty}[2002/02/25]

\newcommand*{\partfont}          [1] {}
\newcommand*{\partnumberfont}    [1] {}
\newcommand*{\parttitlefont}     [1] {}
\newcommand*{\chapterfont}       [1] {}
\newcommand*{\chapternumberfont} [1] {}
\newcommand*{\chaptertitlefont}  [1] {}
\newcommand*{\sectionfont}       [1] {}
\newcommand*{\subsectionfont}    [1] {}
\newcommand*{\subsubsectionfont} [1] {}
\newcommand*{\paragraphfont}     [1] {}
\newcommand*{\subparagraphfont}  [1] {}
\newcommand*{\minisecfont}  [1] {}
```

```
\newcommand*{\allsectionsfont}[1] {}
\newcommand{\nohang}{}
```

\sectionrule is only to be used in *font commands, thus it is ignored.

```
\newcommand*{\sectionrule}[5]{}

\def\ulemheading#1#2{}
```

File 313 **lwarp-semantic-markup.sty**

§ 410 Package

semantic-markup

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg semantic-markup semantic-markup is patched for use by lwarp.

⚠ If using the endnotes option, add \theendnotes where desired.

for HTML output:

```
\LWR@ProvidesPackagePass{semantic-markup}[2018/05/21]
```

The endnotes must be printed by the user before the end of the document, since the end is after the HTML footer, etc.

```
\ifendnotes
\RenewDocumentCommand{\SetupEndnotes}{}{%
    \let\footnote=\endnote
%     \AtEndDocument{\DoBeforeEndnotes{\EndnoteFont\theendnotes}}%
}
\fi
```

HTML unicode characters from musicography are used.

```
\RequirePackage{musicography}

\let\fl\musFlat
\let\sh\musSharp
\let\na\musNatural
```

The \musfig is placed inside a hashed image, with a simple alt tag.

```
\RequirePackage{amsmath}

\RenewDocumentCommand{\musfig}{ m m }{%
    \LWR@subsingledollar*%
        {#1/#2}% alt tag
        {musfig}% addl' hashing
        {% contents
            \LWR@origensuredmath{%
                \genfrac{}{}{0pt}{1}{\text{#1}}{\text{#2}}%
            }%
        }%
```

```
}
```

The \meter is taken from musicography, and becomes a hashed image with a simple alt tag.

```
\RenewDocumentCommand{\meter}{ m m }{%
    \musMeter{#1}{#2}%
}
```

File 314 **lwarp-setspace.sty**

§ 411 Package

setspace

(*Emulates or patches code by* Robin Fairbairns.)

Pkg setspace

setspace is not used during HTML conversion.

Discard all options for lwarp-setspace:

for HTML output:

```
\LWR@ProvidesPackageDrop{setspace}[2011/12/19]

\newcommand*{\setstretch}[1]{}
\newcommand*{\SetSinglespace}[1]{}
\newcommand*{\singlespacing}{}
\newcommand*{\onehalfspacing}{}
\newcommand*{\doublespacing}{}

\newenvironment*{singlespace}
{
\LWR@forcenewpage
\BlockClass{singlespace}
}
{\endBlockClass}

\newenvironment*{singlespace*}
{
\LWR@forcenewpage
\BlockClass{singlespace}
}
{\endBlockClass}

\newenvironment*{spacing}[1]{

}{

}

\newenvironment*{onehalfspace}
{
\LWR@forcenewpage
\BlockClass{onehalfspace}
}
{\endBlockClass}
```

```

\newenvironment*{doublespace}
{
\LWR@forcenewpage
\BlockClass{doublespace}
}
{\endBlockClass}
```

File 315 **lwarp-shadow.sty**

§ 412 Package shadow

(*Emulates or patches code by* Mauro Orlandini.)

Pkg shadow shadow is emulated.

for HTML output: Discard all options for lwarp-shadow:

```
\LWR@ProvidesPackageDrop{shadow}[2003/02/19]
```

```
\newdimen\sboxsep
\newdimen\sboxrule
\newdimen\sdim

\newcommand{\shabox}[1]{%
\InlineClass{shabox}{#1}%
}
```

File 316 **lwarp-showidx.sty**

§ 413 Package showidx

Pkg showidx showidx is ignored.

for HTML output: Discard all options for lwarp-showidx:

```
\LWR@ProvidesPackageDrop{showidx}[2014/09/29]
```

`\@wrindex` is redefined `\AtBeginDocument` by the lwarp core.

File 317 **lwarp-showkeys.sty**

§ 414 Package showkeys

(*Emulates or patches code by* David Carlisle, Morten Høgholm.)

Pkg showkeys showkeys is ignored.

for HTML output: Discard all options for lwarp-showkeys:

```
\LWR@ProvidesPackageDrop{showkeys}[2014/10/28]
\NewDocumentCommand{\showkeys}{s}{}
```

File 318 **lwarp-showtags.sty**

§ 415 Package showtags

Pkg showtags showtags is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{showtags}% no version is given
\newcommand{\thecitetag}[1]{}
```

File 319 **lwarp-sidecap.sty**

§ 416 Package sidecap

(*Emulates or patches code by* Rolf Niepraschk, Hubert Gässlein.)

Pkg sidecap sidecap is emulated.

for HTML output: Discard all options for lwarp-sidecap.

```
\LWR@ProvidesPackageDrop{sidecap}[2003/06/06]
```

See:
http://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment
regarding the creation of starred environments with xparse.

```
\NewDocumentEnvironment{SCtable}{soo}
{\IfValueTF{#3}{\table[#3]}{\table}}
{\endtable}

\ExplSyntaxOn
\cs_new:cpn {SCtable*} {\SCtable*}
\cs_new_eq:cN {endSCtable*} \endSCtable
\ExplSyntaxOff


\NewDocumentEnvironment{SCfigure}{soo}
{\IfValueTF{#3}{\figure[#3]}{\figure}}
{\endfigure}

\ExplSyntaxOn
\cs_new:cpn {SCfigure*} {\SCfigure*}
```

```
\cs_new_eq:cN {endSCfigure*} \endSCfigure
\ExplSyntaxOff


\newenvironment*{wide}{}{}
```

File 320 **lwarp-sidenotes.sty**

§ 417 Package

sidenotes

(*Emulates or patches code by* Andy Thomas, Oliver Schebaum.)

Pkg sidenotes Patched for lwarp.

for HTML output: Load the original package:

```
\LWR@ProvidesPackagePass{sidenotes}
```

The following patch sidenotes for use with lwarp:

\sidecaption * [⟨*entry*⟩] [⟨*offset*⟩] {⟨*text*⟩}

```
\RenewDocumentCommand \sidecaption {s o o +m}
{
   \LWR@stoppars
   \begingroup
 \captionsetup{style=sidecaption}
 \IfBooleanTF{#1}
 { % starred
   \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
   \caption*{#4}
   \end{BlockClass}
 }
 { % unstarred
 \IfNoValueOrEmptyTF{#2}
   {\def\@sidenotes@sidecaption@tof{#4}}
   {\def\@sidenotes@sidecaption@tof{#2}}
   \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
   \caption[\@sidenotes@sidecaption@tof]{#4}
   \end{BlockClass}
 }
   \endgroup
   \LWR@startpars
}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTsidenotes@marginfloat}{O{-1.2ex} m}
{% start
\LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
\captionsetup{type=#2}%
}
{%
```

```
\endLWR@BlockClassWP%
}

\RenewDocumentEnvironment{marginfigure}{o}
  {\begin{KFLTsidenotes@marginfloat}{figure}}
  {\end{KFLTsidenotes@marginfloat}}

\RenewDocumentEnvironment{margintable}{o}
  {\begin{KFLTsidenotes@marginfloat}{table}}
  {\end{KFLTsidenotes@marginfloat}}
```

The following were changed by sidenotes, and now are reset back to their lwarp-supported originals:

Restoring the definition from the LaTeX 2_ε `article.cls` source:

```
\renewenvironment{figure*}
               {\@dblfloat{figure}}
               {\end@dblfloat}

\renewenvironment{table*}
               {\@dblfloat{table}}
               {\end@dblfloat}
```

File 321 **lwarp-SIunits.sty**

§ 418 Package

SIunits

(*Emulates or patches code by* Marcel Heldoorn.)

Pkg SIunits

SIunits is patched for use by lwarp.

It is recommended to use `\unit` where possible, which combines the entire expression into a single `lateximage`, and adds the `alt` tag containing the LaTeX code, allowing for copy/paste. When units are used outside of the `\unit` macro, each unit macro will have its own `lateximage`, and each will have the `alt` tag set to "`(<\mathimagename>)`", which defaults to "`(math image)`".

for HTML output:

```
\LWR@ProvidesPackagePass{SIunits}[2007/12/02]
```

Patched for copy/paste with the HTML `alt` tag:

```
\DeclareRobustCommand{\unit}[2]{%
\@inunitcommandtrue%    original
\LWR@subsingledollar*%  lwarp
{% alt tag
    \textbackslash{}unit\{\LWR@HTMLsanitize{#1}\}%
        \{ \LWR@HTMLsanitize{#2}\}% extra space
}%
{SIunits}% add'l hashing
{%
    \LWR@origensuredmath{%  lwarp modification
```

```
        \SI@fstyle{#1\@qsk\period@active{#2}}%  original
    }%
}% contents
\@inunitcommandfalse%   original
}
```

File 322 **lwarp-siunitx.sty**

§ 419 Package

siunitx

(*Emulates or patches code by* Joseph Wright.)

Pkg siunitx

siunitx is patched for use by lwarp.

fractions

Due to *pdftotext* limitations, fraction output is replaced by symbol output for per-mode and quotient-mode.

⚠ math mode required

Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first.

⚠ tabular

Tabular S columns are rendered as simple c columns, and tabular s columns are not supported. These may be replaced by c columns with each cell contained in \num or \si.

for HTML output:

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackagePass{siunitx}[2018/05/17]
```

```
\AtBeginDocument{% in case textcomp was not loaded
\DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
\DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
\DeclareSIUnit\elementarycharge{\textit{e}}
\DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
\DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
\DeclareSIUnit\planckbar{\LWR@siunitx@textplanckbar}
}% AtBeginDocument
```

\@ensuredmath is not supported inside an \hbox, so it must temporarily be restored to its original. Similar for \mbox. SVG math is created explicitly when necessary, using \LWR@subsingledollar.

```

\ExplSyntaxOn
%
```

Modified to set set HTML \textcolor if not black:

```
\cs_undefine:N \__siunitx_print_aux:
```

```
\cs_new_protected:Npn \__siunitx_print_aux:
  {
    \text
      {
        \__siunitx_ensure_ltr:n
          {
            \color@begingroup
            \__siunitx_print_color:
            \__siunitx_font_shape:
            \__siunitx_font_weight:
            \use:c
              {
                @@_ \l__siunitx_print_type_tl _
                text \l__siunitx_font_family_tl :
              }
            \bool_if:NTF \l__siunitx_font_math_mode_bool
              { \__siunitx_print_math: }
              {
                \LWR@findcurrenttextcolor% lwarp
                \ifdefstring{\LWR@tempcolor}{000000}% lwarp
                {\__siunitx_print_text:}% lwarp
                {% lwarp
                    \LWR@textcurrentcolor{% lwarp
                        \__siunitx_print_text:
                    }% lwarp
                }% lwarp
              }
            \color@endgroup
          }
      }
  }


\cs_undefine:N \__siunitx_set_math_fam:n
\cs_new_protected:Npn \__siunitx_set_math_fam:n #1 {
  \int_new:c { c__siunitx_math #1 _int }
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \hbox_set:Nn \l__siunitx_tmp_box
      {
        \ensuremath
          {
            \use:c { math #1 }
              {
                \int_gset:cn { c__siunitx_math #1 _int } { \fam }
              }
          }
      }
  \group_end:% lwarp
}

\cs_undefine:N \__siunitx_combined_output:n
\cs_new_protected:Npn \__siunitx_combined_output:n #1 {
    \group_begin:% lwarp
```

```
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
  \bool_if:NTF \l__siunitx_number_parse_bool
    {
      \tl_clear:N \l__siunitx_number_out_tl
      \bool_set_false:N \l__siunitx_number_compound_bool
      \__siunitx_number_output_parse:n {#1}
    }
    {
      \__siunitx_unit_output_pre_print:
```

For parse-numbers=false:

```
%       \__siunitx_print:nn { number } { \ensuremath {#1} }
        \LWR@subsingledollar{% lwarp
            \textbackslash( \LWR@HTMLsanitize{#1} \textbackslash)% lwarp
        }{siunitx}{%
            \__siunitx_print:nn { number } {%
                \LWR@origensuredmath{#1}%
            }%
        }% lwarp

      \__siunitx_unit_output_print:
    }
    \group_end:% lwarp
}
%
```

For quotients, the fraction code is replaced by the symbol code:

```
\cs_undefine:N \__siunitx_number_output_quotient_fraction:
\cs_new_protected:Npn \__siunitx_number_output_quotient_fraction: {
  \bool_set_true:N \l__siunitx_number_compound_bool
  \__siunitx_number_output_quotient_aux_i:
  \tl_set_eq:NN \l__siunitx_number_out_tl
    \l__siunitx_number_numerator_tl
  \tl_put_right:NV \l__siunitx_number_out_tl \l__siunitx_output_quotient_tl
  \tl_put_right:NV \l__siunitx_number_out_tl
    \l__siunitx_number_denominator_tl
  \__siunitx_number_output_single_aux:
}
```

For units, the fraction code is replaced by the symbol code:

```
\cs_undefine:N \__siunitx_unit_format_fraction_fraction:
\cs_new_protected:Npn \__siunitx_unit_format_fraction_fraction: {
  \__siunitx_unit_format_fraction_symbol_aux:
  \int_compare:nNnT { \l__siunitx_unit_denominator_int } > { 1 }
    {
      \bool_if:NT \l__siunitx_unit_denominator_bracket_bool
        {
       \tl_put_left:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_open_tl
       \tl_put_right:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_close_tl
        }
```

```
    }
  \tl_set_eq:NN \l__siunitx_unit_tl \l__siunitx_unit_numerator_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_per_symbol_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_unit_denominator_tl
}

\cs_undefine:N \__siunitx_angle_print_astronomy_aux:
\cs_new_protected:Npn \__siunitx_angle_print_astronomy_aux: {
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-integer }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
 {% lateximage
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
    }
  \hbox_set:Nn \l__siunitx_angle_unit_box
    {
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \skip_horizontal:n { -\scriptspace }
    }
  \__siunitx_angle_print_astronomy_aux:n { marker }
  \__siunitx_angle_print_astronomy_aux:n { unit }
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \box_use:N \l__siunitx_angle_marker_box
      \box_use:N \l__siunitx_angle_unit_box
    }
  \dim_compare:nNnTF
    { \l__siunitx_angle_marker_dim } > { \l__siunitx_angle_unit_dim }
    { \__siunitx_angle_print_astronomy_marker: }
    { \__siunitx_angle_print_astronomy_unit: }
 }% lateximage
 {% not a lateximage
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
 }% not a lateximage
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-decimal }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
}

\RenewDocumentCommand \num { o m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_number_output:n {#2}
  \group_end:% lwarp
}

```

```
\RenewDocumentCommand \numrange { o m m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_range_numbers:nn {#2} {#3}
  \group_end:% lwarp
}

\RenewDocumentCommand \ang { o > { \SplitArgument { 2 } { ; } } m } {
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_angle_output:nnn #2
  \group_end:% lwarp
}

\RenewDocumentCommand \si { o m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_unit_output:nn {#2} { } }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_unit_output:nn {#2} {#1}
      }
  \group_end:% lwarp
}


\RenewDocumentCommand{\SIrange}{o m m m}
{%
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_range_unit:nnnn {#4} { } {#2} {#3} }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_range_unit:nnnn {#4} {#1} {#2} {#3}
      }
  \group_end:% lwarp
}

\ExplSyntaxOff
```

File 323 **lwarp-soul.sty**

§ 420 Package

soul

(*Emulates or patches code by* Melchior FRANZ.)

Pkg soul Emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{soul}[2003/11/17]
\RequirePackage{xcolor}% for \convertcolorspec
```

Storage for the colors to use:

```
\newcommand*{\LWR@soululcolor}{}

\newcommand*{\LWR@soulstcolor}{}

% \definecolor{LWR@soulhlcolordefault}{HTML}{F8E800}
% \newcommand*{\LWR@soulhlcolor}{LWR@soulhlcolordefault}
\newcommand*{\LWR@soulhlcolor}{}
```

\so {⟨*text*⟩}

Basic markup with css:

```
\newcommand{\so}[1]{%
\InlineClass(letter-spacing:.2ex){letterspacing}{#1}%
}
```

\caps {⟨*text*⟩}

```
\newcommand{\caps}[1]{%
    \InlineClass%
        (font-variant:small-caps;letter-spacing:.1ex)%
        {capsspacing}{#1}%
}
```

\LWR@soulcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@soulcolor}[5]{%
\ifcsempty{#2}%
{%
    \InlineClass(#5){#3}{#1}%
}%
{%
    \convertcolorspec{named}{\@nameuse{#2}}{HTML}\LWR@tempcolor%
    \LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}%
}%
}
```

```
\newcommand{\ul}[1]{%
\LWR@soulcolor{#1}{LWR@soululcolor}{uline}{text-decoration-color}%
    {text-decoration:underline; text-decoration-skip: auto;}%
}

\newcommand{\st}[1]{
\LWR@soulcolor{#1}{LWR@soulstcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
}

\newcommand{\hl}[1]{
\LWR@soulcolor{#1}{LWR@soulhlcolor}{highlight}{background-color}%
    {background:\LWR@origpound{}F8E800}
}
```

Nullified:

```
\newcommand*{\soulaccent}[1]{}
\newcommand*{\soulregister}[2]{}
\newcommand{\sloppyword}[1]{#1}
\newcommand*{\sodef}[5]{\DeclareRobustCommand*#1[1]{\so{##1}}}
\newcommand*{\resetso}{}
\newcommand*{\capsdef}[5]{}
\newcommand*{\capsreset}{}
\newcommand*{\capssave}[1]{}
\newcommand*{\capsselect}[1]{}
\newcommand*{\setul}[2]{}
\newcommand*{\resetul}{}
\newcommand*{\setuldepth}[1]{}
\newcommand*{\setuloverlap}[1]{}
```

Set colors:

```
\newcommand*{\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}
\newcommand*{\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}
\newcommand*{\sethlcolor}[1]{\renewcommand{\LWR@soulhlcolor}{#1}}
```

Long versions of the user-level macros:

```
\let\textso\so
\let\textul\ul
\let\texthl\hl
\let\textcaps\caps
```

File 324 **lwarp-soulpos.sty**

§ 421 Package

soulpos

(*Emulates or patches code by* Javier Bezos.)

Pkg soulpos soulpos is emulated.

for HTML output:

```
\RequirePackage{soul}
\RequirePackage{soulutf8}
\LWR@ProvidesPackageDrop{soulpos}[2012/02/25]

\NewDocumentCommand{\ulposdef}{m o m}{}

\newdimen\ulwidth

\newcommand\ifulstarttype[1]{%
\expandafter\@secondoftwo%
}

\newcommand\ifulendtype[1]{%
\expandafter\@secondoftwo%
}

\newcommand{\ulstarttype}{0}
\newcommand{\ulendtype}{0}
\newcommand\ulpostolerance{0}%
```

File 325 **lwarp-soulutf8.sty**

§ 422 Package soulutf8

Pkg soulutf8 soulutf8 is emulated.

lwarp's HTML output naturally supports UTF-8 encoding.

for HTML output:

```
\LWR@ProvidesPackageDrop{soulutf8}[2016/05/16]
```

File 326 **lwarp-splitidx.sty**

§ 423 Package splitidx

(*Emulates or patches code by* Markus Kohm.)

Pkg splitidx splitidx is patched for use by lwarp.

If the latexmk option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

⚠ \thepage When using \AtWriteToIndex or \AtNextWriteToIndex, the user must not refer to \thepage during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 512.17 in the lwarp-patch-memoir package for the \@@wrspindexhyp macro as an example.

for HTML output:

```
\LWR@ProvidesPackagePass{splitidx}[2016/02/18]

\catcode`\_=12%
\xpatchcmd{\newindex}
    {\jobname-#2.idx}
    {\jobname-#2_html.idx}
    {}
    {\LWR@patcherror{splitidx}{@newindex}}
\catcode`\_=8%
```

Patched to use lwarp's automatic indexing counter instead of \thepage:

```
\renewcommand*{\@wrsindex}[2][]{%
  \ifx\relax#1\relax
    \if@splitidx
      \@wrsindex[idx]{#2}%
    \else
      \def\@tempa{#2}%
      \if@verbindex\@onelevel@sanitize\@tempa\fi
      \@wrindex{\@tempa}%
    \fi
  \else
    \def\@tempa{#2}%
    \csname index@#1@hook\endcsname
%     \expandafter\ifx\csname @@wrsindex\endcsname\relax
    \addtocounter{LWR@autoindex}{1}%                    lwarp
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
%       \@@@wrsindex{#1}{{\@tempa}{\thepage}}%
      \@@@wrsindex{#1}{{\@tempa}{\arabic{LWR@autoindex}}}%
%     \else
%       \def\@tempb{\@@wrsindex{#1}}%
%       \expandafter\@tempb\@tempa||\\%
%     \fi
    \endgroup
    \@esphack
  \fi
}
```

lwarp defines sectioning commands with xparse, so the below patches are done as temporary redefinitions instead of being \let.

```
\xpatchcmd{\printsubindex}
    {\let\section\subsection}
    {\renewcommand*{\section}{\subsection}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-section}}

\xpatchcmd{\printsubindex}
    {\let\chapter\section}
```

```
    {\renewcommand*{\chapter}{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}

\xpatchcmd{\printsubindex}
    {\let\@makechapterhead\section}
    {\def\@makechapterhead{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}
```

File 327 **lwarp-srcltx.sty**

§ 424 Package srcltx

Pkg srcltx srcltx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{srcltx}[2006/11/12]
```

```
\newif\ifSRCOK \SRCOKfalse
\newcommand*\srcIncludeHook[1]{}
\newcommand*\srcInputHook[1]{}
\newcommand*\MainFile{}
\def\MainFile{\jobname.tex}
\newcommand*\CurrentInput{}
\gdef\CurrentInput{\MainFile}
\newcommand\Input{}
\let\Input\input
```

File 328 **lwarp-srctex.sty**

§ 425 Package srctex

Pkg srctex srctex is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{srctex}[2006/11/12]
\LWR@origRequirePackage{lwarp-srcltx}
```

File 329 **lwarp-stabular.sty**

§ 426 Package stabular

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg stabular stabular is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{stabular}[2014/03/20]
```

Env `stabular` [⟨*vpos*⟩] {⟨*colspec*⟩}

```
\newenvironment{stabular}[2][c]
{
\begin{tabular}[#1]{#2}
\renewcommand{\noalign}[1]{}
}
{\end{tabular}}
```

Env `stabular` {⟨*width*⟩} [⟨*vpos*⟩] {⟨*colspec*⟩}

```
\NewDocumentEnvironment{stabular*}{m o m}
{
\begin{tabular}[#2]{#3}
\renewcommand{\noalign}[1]{}
}
{\end{tabular}}
```

File 330 **lwarp-stfloats.sty**

§ 427 Package stfloats

Pkg `stfloats` stfloats is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{stfloats}[2017/03/27]
```

stfloats may have been preloaded by a ltj* class.

The following are provided in case they have not yet been defined:

```
\providecommand*{\fnbelowfloat}{}
\providecommand*{\fnunderfloat}{}
\providecommand*{\setbaselinefloat}{}
\providecommand*{\setbaselinefixed}{}
```

Nullified for HTML:

```
\renewcommand*{\fnbelowfloat}{}
\renewcommand*{\fnunderfloat}{}
\renewcommand*{\setbaselinefloat}{}
\renewcommand*{\setbaselinefixed}{}
```

File 331 **lwarp-struktex.sty**

§ 428 Package struktex

(*Emulates or patches code by* Jobst Hoffmann.)

Pkg `struktex` struktex is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{struktex}[2018/06/04]

\BeforeBeginEnvironment{struktogramm}{\begin{lateximage}[(struktogramm)]}
\AfterEndEnvironment{struktogramm}{\end{lateximage}}

\newenvironment{LWR@HTML@centernss}{\begin{center}}{\end{center}}
\LWR@formattedenv{centernss}

\newcommand{\LWR@HTML@CenterNssFile}[1]{%
    \begin{center}
    \input{#1.nss}
    \end{center}
}
\LWR@formatted{CenterNssFile}

\newcommand{\LWR@HTML@centernssfile}{\LWR@HTML@CenterNssFile}
\LWR@formatted{centernssfile}
```

File 332 **lwarp-subcaption.sty**

§ 429 Package subcaption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg subcaption subcaption is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{subcaption}[2018/05/01]
```

Tells lwarp to ignore minipage widths inside a subfigure or subtable. In print mode the minipages are used to place the items next to each other. In HTML they are placed side-by-side automatically.

```
\ifdef{\subcaption@minipage}{
    \xpatchcmd{\subcaption@minipage}
        {\minipage}
        {\minipagefullwidth\minipage}
        {}
        {\LWR@patcherror{subcaption}{subcaption@minipage}}
}{}
```

Likewise for a \subcaptionbox:

```
\ifdef{\subcaptionbox}{
    \xpretocmd{\subcaptionbox}
        {\minipagefullwidth}
        {}
        {\LWR@patcherror{subcaption}{subcaptionbox}}
}{}
```

File 333 **lwarp-subfig.sty**

§ 430 Package

subfig

(*Emulates or patches code by* Steven Douglas Cochran.)

Pkg subfig

subfig is supported and patched by lwarp.

⚠ lof/lotdepth

At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

In the document source, use `\hfill` and `\hspace*` subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

for HTML output:

Accept all options for lwarp-subfig:

```
\LWR@ProvidesPackagePass{subfig}[2005/06/28]
```

`\sf@@@subfloat` {⟨*1 type*⟩} [⟨*2 LOF entry*⟩] [⟨*3 caption*⟩] {⟨*4 contents*⟩}

The outer minipage allows side-by-side subfloats with `\hfill` between.

```
\long\def\sf@@@subfloat#1[#2][#3]#4{%
\begin{minipage}{\linewidth}% lwarp

\IfValueTF{#2}{%
    \LWR@setlatestname{#2}%
}{%
    \IfValueTF{#3}{%
        \LWR@setlatestname{#3}%
    }{}%
}%
\LWR@stoppars% lwarp
    \@ifundefined{FBsc@max}{}%
        {\FB@readaux{\let\FBsuboheight\relax}}%
    \@tempcnta=\@ne
    \if@minipage
      \@tempcnta=\z@
    \else\ifdim \lastskip=\z@ \else
      \@tempcnta=\tw@
    \fi\fi
    \ifmaincaptiontop
      \sf@top=\sf@nearskip
      \sf@bottom=\sf@farskip
    \else
      \sf@top=\sf@farskip
      \sf@bottom=\sf@nearskip
    \fi
    \leavevmode
```

```
%     \setbox\@tempboxa \hbox{#4}%
%     \@tempdima=\wd\@tempboxa
%     \@ifundefined{FBsc@max}{}%
%         {\global\advance\Xhsize-\wd\@tempboxa
%          \dimen@=\ht\@tempboxa
%          \advance\dimen@\dp\@tempboxa
%          \ifdim\dimen@>\FBso@max
%            \global\FBso@max\dimen@
%          \fi}%
```

Do not use boxes, which interfere with `lateximages`:

```
%     \vtop%
    \bgroup
%       \vbox%
      \bgroup
        \ifcase\@tempcnta
          \@minipagefalse
        \or
%           \vskip\sf@top
        \or
          \ifdim \lastskip=\z@ \else
%             \@tempskipb\sf@top\relax\@xaddvskip
          \fi
        \fi
        \sf@ifpositiontop{%
          \ifx \@empty#3\relax \else
            \sf@subcaption{#1}{#2}{#3}%
%             \vskip\sf@capskip
%             \vskip\sf@captopadj
          \fi\egroup
%           \hrule width0pt height0pt depth0pt
            \LWR@startpars% lwarp
%  \box\@tempboxa
            #4
            \LWR@stoppars% lwarp
        }{%
        \LWR@startpars% lwarp
        \@ifundefined{FBsc@max}%
            {
%  \box\@tempboxa
                #4
            }%
            {\ifx\FBsuboheight\relax
%                \box\@tempboxa
                #4
             \else
%                \vbox to \FBsuboheight{\FBafil\box\@tempboxa\FBbfil}%
                #4
             \fi}%
        \LWR@stoppars% lwarp
          \egroup
          \ifx \@empty#3\relax \else
%             \vskip\sf@capskip
%             \hrule width0pt height0pt depth0pt
            \sf@subcaption{#1}{#2}{#3}%
```

```
         \fi
        }%
%       \vskip\sf@bottom
    \egroup
    \@ifundefined{FBsc@max}{}%
        {\addtocounter{FRobj}{-1}%
         \ifnum\c@FRobj=0\else
           \subfloatrowsep
         \fi}%
    \ifmaincaptiontop\else
      \global\advance\@nameuse{c@\@captype}\m@ne
    \fi
\end{minipage}% lwarp
\LWR@startpars% lwarp
  \endgroup\ignorespaces%
}%
```

\sf@subcaption {⟨*1 type*⟩} {⟨*2 LOF entry*⟩} {⟨*3 caption*⟩}

```
\long\def\sf@subcaption#1#2#3{%
\LWR@stoppars% lwarp
  \ifx \relax#2\relax \else
    \bgroup
      \let\label=\@gobble
      \let\protect=\string
      \def\@subcaplabel{%
        \caption@lstfmt{\@nameuse{p@#1}}{\@nameuse{the#1}}}%
      \sf@updatecaptionlist{#1}{#2}{\the\value{\@captype}}{\the\value{#1}}%
    \egroup
  \fi
  \bgroup
    \ifx \relax#3\relax
      \let\captionlabelsep=\relax
    \fi
%     \setbox0\vbox{%
%        \hb@xt@\the\@tempdima{%
%
% %          \hss
% %         \parbox[t]{\the\@tempdima}{%
%           \caption@make
%               {\@nameuse{sub\@captype name}}%
%               {\@nameuse{thesub\@captype}}%
%               {#3}
% %  }%
% %            \hss
%   }
%  }%
    \@ifundefined{FBsc@max}%
%         {\box0}%
        {
%  \parbox[t]{\the\@tempdima}{%
\LWR@traceinfo{sfsubcap B1}% lwarp
            \LWR@figcaption% lwarp
            \caption@make
                {\@nameuse{sub\@captype name}}%
```

```
                {\@nameuse{thesub\@captype}}%
                {\LWR@isolate{#3}}%

            \endLWR@figcaption% lwarp
\LWR@traceinfo{sfsubcap B2}% lwarp
%  }%
        }%
        {\dimen@\ht0%
         \advance\dimen@\dp0%
         \ifdim\dimen@>\FBsc@max
           \global\FBsc@max\dimen@
         \fi
         \FB@readaux{\let\FBsubcheight\relax}%
         \ifx\FBsubcheight\relax
           \def\next{
%  \parbox[t]{\the\@tempdima}
            }%
         \else
           \def\next{
%  \parbox[t][\FBsubcheight][t]{\the\@tempdima}
            }%
         \fi
%          \vbox{%
%            \hb@xt@\the\@tempdima{%

%              \hss
%              \next{%
\LWR@traceinfo{sfsubcap C1}% lwarp
               \caption@make
                   {\@nameuse{sub\@captype name}}%
                   {\@nameuse{thesub\@captype}}%
                   {#3}
\LWR@traceinfo{sfsubcap C1}% lwarp
%  }%
%              \hss

%  }
%           }
        }%
  \egroup
\LWR@startpars% lwarp
}
```

\subfloat@label Patches for \sf@sub@label:

```
\def\subfloat@label{%
\LWR@ensuredoingapar% lwarp
  \@ifnextchar(%   %) match left parenthesis
    {\sf@sub@label}
    {\sf@sub@label(Sub\@captype\space
                   \@ifundefined{thechapter}{}{\@nameuse{thechapter}\space}%
                   \@nameuse{p@sub\@captype}%
                   \@nameuse{thesub\@captype}.)}}
```

Patches for \subref.

\sf@subref {⟨*label*⟩}

The unstarred version uses a \ref link whose printed text comes from the sub@<label>:

```
\renewcommand{\sf@subref}[1]{%
\LWR@subnewref{#1}{sub@#1}%
}
```

\sf@@subref {⟨*label*⟩}

The starred version uses the printed sub@<label> which is stored as if it were a page number:

```
\renewcommand{\sf@@subref}[1]{\LWR@orig@pageref{sub@#1}}
```

Defining new subfloats. The l@sub<type> for each is redefined.

\@newsubfloat [⟨*keys/values*⟩] {⟨*float name*⟩}

```
\LetLtxMacro\LWR@orig@newsubfloat\@newsubfloat

\def\@newsubfloat[#1]#2{%
\LWR@orig@newsubfloat[#1]{#2}%
\renewcommand{\l@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
}
```

Pre-defined for figures and tables:

\l@subfigure {⟨*text*⟩} {⟨*pagenum*⟩}

```
\renewcommand{\l@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}
```

\l@subtable {⟨*text*⟩} {⟨*pagenum*⟩}

```
\renewcommand{\l@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
```

File 334 **lwarp-subfigure.sty**

§ 431 Package

subfigure

Pkg subfigure

subfigure is emulated by subfig.

for HTML output:

```
\LWR@ProvidesPackageDrop{subfigure}[2002/03/15]
\RequirePackage{subfig}

\LetLtxMacro\subfigure\subfloat
\LetLtxMacro\subtable\subfloat
\LetLtxMacro\Subref\subref
\@ifundefined{figuretopcaptrue}{\newif\iffiguretopcap}{}
\newif\ifsubfiguretopcap
\newif\ifsubcaphang
\newif\ifsubcapcenter
```

```
\newif\ifsubcapcenterlast
\newif\ifsubcapnooneline
\newif\ifsubcapraggedright
\newskip\subfigtopskip
\newskip\subfigcapskip
\newdimen\subfigcaptopadj
\newskip\subfigbottomskip
\newdimen\subfigcapmargin
\newskip\subfiglabelskip
\newcommand*{\subcapsize}{}
\newcommand*{\subcaplabelfont}{}
\newcommand*{\subcapfont}{}
```

File 335 **lwarp-supertabular.sty**

§ 432 Package

supertabular

(*Emulates or patches code by* Johannes Braams, Theo Jurriens.)

Pkg supertabular

supertabular is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{supertabular}[2004/02/20]
```

⚠ Misplaced alignment tab character &

For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 9.10.1.

⚠ lateximage

supertabular and xtab are not supported inside a lateximage.

```
\newcommand{\LWRST@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRST@firsthead{#1}%
}

\newcommand{\tablehead}[1]{}
\newcommand{\tabletail}[1]{}

\newcommand{\LWRST@lasttail}{}

\newcommand{\tablelasttail}[1]{%
    \long\gdef\LWRST@lasttail{#1}%
}
```

```
\newcommand{\tablecaption}[2][]{%
    \long\gdef\LWRST@caption{%
        \ifblank{#1}%
```

```
            {\caption{#2}}%
            {\caption[#1]{#2}}%
    }%
}

\let\topcaption\tablecaption
\let\bottomcaption\tablecaption
```

```
\newcommand*{\LWRST@caption}{}

\newcommand*{\shrinkheight}[1]{}

\NewDocumentEnvironment{supertabular}{s o m}
{%
\LWR@traceinfo{supertabular}%
\begin{table}%
\LWRST@caption%
\begin{tabular}{#3}%
\TabularMacro\ifdefvoid{\LWRST@firsthead}%
{\LWR@getmynexttoken}%
{\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
}%
{%
\ifdefvoid{\LWRST@lasttail}%
{}%
{%
\TabularMacro\ResumeTabular%
\LWRST@lasttail%
}%
\end{tabular}%
\end{table}%
```

```
\gdef\LWRST@caption{}%
```

```
\LWR@traceinfo{supertabular done}%
}

\NewDocumentEnvironment{mpsupertabular}{s o m}
{\minipage{\linewidth}\supertabular{#3}}
{\endsupertabular\endminipage}
```

File 336 **lwarp-syntonly.sty**

§ 433 Package

syntonly

(*Emulates or patches code by* Frank Mittelbach, Rainer Schöpf.)

Pkg syntonly Emulated.

for HTML output: Discard all options for lwarp-syntonly:

```
\LWR@ProvidesPackageDrop{syntonly}[2017/06/30]
```

```
\newif\ifsyntax@
\syntax@false

\newcommand*{\syntaxonly}{}

\@onlypreamble\syntaxonly
```

File 337 **lwarp-tablefootnote.sty**

§ 434 Package

tablefootnote

Pkg tablefootnote

tablefootnote is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tablefootnote}[2014/01/26]
```

This works because in HTML tables are no longer floats.

```
\LetLtxMacro\tablefootnote\footnote
```

File 338 **lwarp-tabls.sty**

§ 435 Package

tabls

(*Emulates or patches code by* Donald Arseneau.)

Pkg tabls

tabls is emulated. `\LWR@hline` is used to handle the optional argument when tabls is loaded.

for HTML output:

```
\LWR@ProvidesPackageDrop{tabls}
```

```
\newdimen\tablinesep
\newdimen\arraylinesep
\newdimen\extrarulesep
```

File 339 **lwarp-tabularx.sty**

§ 436 Package

tabularx

(*Emulates or patches code by* David Carlisle.)

Pkg tabularx

tabularx is emulated by lwarp.

for HTML output:

Discard all options for lwarp-tabularx:

```
\LWR@ProvidesPackageDrop{tabularx}[2016/02/03]
\RequirePackage{array}
```

```
\DeclareDocumentEnvironment{tabularx}{m o m}
{\tabular{#3}}
{\endtabular}

\DeclareDocumentEnvironment{tabularx*}{m o m}
{\tabular{#3}}
{\endtabular}
```

File 340 **lwarp-tabulary.sty**

§ 437 Package tabulary

(*Emulates or patches code by* David Carlisle.)

Pkg tabulary

tabulary is emulated by lwarp.

for HTML output: Discard all options for lwarp-tabulary.

Column types L, C, R, and J are emulated by lwarp core code.

```
\LWR@ProvidesPackageDrop{tabulary}[2014/06/11]
\RequirePackage{array}

\NewDocumentEnvironment{tabulary}{m o m}
{\tabular{#3}}
{\endtabular}

\NewDocumentEnvironment{tabulary*}{m o m}
{\tabular{#3}}
{\endtabular}

\newdimen\tymin
\newdimen\tymax
\def\tyformat{}
```

File 341 **lwarp-tascmac.sty**

§ 438 Package tascmac

Pkg tascmac

tascmac is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tascmac}[2018/03/09]

\newenvironment*{boxnote}
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid black ;
            border-top: 1px dashed black ;
        ]{boxnote}
```

```
    }
    {\endBlockClass}

\newenvironment*{screen}[1][]
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
            border-radius: 8pt
        ]{boxnote}
    }
    {\endBlockClass}

\newenvironment*{itembox}[2][]
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
            border-radius: 8pt
        ]{boxnote}
        \InlineClass{itemboxtitle}{#2}\par
    }
    {\endBlockClass}

\newenvironment*{shadebox}
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid black ;
            box-shadow: 3px 3px 3px \#808080 ;
        ]{boxnote}
    }
    {\endBlockClass}

\newcommand*{\mask}[2]{%
    \InlineClass[background: lightgray]{mask}{#1}%
}

\newcommand*{\maskbox}[5]{%
    \InlineClass[background: lightgray]{mask}{#5}%
}

\newcommand*{\Maskbox}[6]{%
    \InlineClass[
        background: lightgray ;
        border: #5 solid black
    ]{mask}{#6}%
}

\newcommand*{\keytop}[2][]{%
    \InlineClass[%
        padding: .2ex ;
        border: 1px solid black ;
        border-radius: .7ex ;
    ]{keytop}{#2}%
```

```
}

\def\yen{\HTMLunicode{00A5}}

\def\return{\HTMLunicode{23CE}}

\def\Return{\HTMLunicode{23CE}}

\def\ascii{ASCII Corporation}

\def\Ascii{ASCII Corporation}

\def\ASCII{ASCII Corporation}
```

File 342 **lwarp-textarea.sty**

§ 439 Package textarea

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg textarea textarea is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{textarea}[2005/12/26]
```

```
\newcommand\StartFromTextArea{}
\newcommand\StartFromHeaderArea{}
\newcommand*\RestoreTextArea{}
\newcommand*\ExpandTextArea[1][*]{}
\let\NCC@restoretextarea\@empty
```

File 343 **lwarp-textcomp.sty**

§ 440 Package textcomp

(*Emulates or patches code by* Frank Mittelbach, Robin Fairbairns, Werner Lemberg.)

Pkg textcomp textcomp is patched for use by lwarp.

§ 440.1 Limitations

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols Many textcomp symbols are not supported by many system / browser fonts. In the css try referencing fonts which are more complete, but expect to see gaps in coverage.

§ 440.2 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{textcomp}[2017/04/05]
```

§ 440.3 HTML symbols

For HTML, use HTML entities or direct Unicode, depending on the engine.

\AtBeginDocument improves support for LuaLaTeX and XeLaTeX.

§ 440.3.1 pdfLaTeX symbols

```
\AtBeginDocument{
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@HTML@textdegree}{\HTMLentity{deg}}
\newcommand*{\LWR@HTML@textcelsius}{\HTMLunicode{2103}}
\newcommand*{\LWR@HTML@textohm}{\HTMLunicode{2126}}
\newcommand*{\LWR@HTML@textmu}{\HTMLunicode{00B5}}
\newcommand*{\LWR@HTML@textlquill}{\HTMLunicode{2045}}
\newcommand*{\LWR@HTML@textrquill}{\HTMLunicode{2046}}
\newcommand*{\LWR@HTML@textcircledP}{\HTMLunicode{2117}}
\newcommand*{\LWR@HTML@texttwelveudash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textmho}{\HTMLunicode{2127}}
\newcommand*{\LWR@HTML@textnaira}{\HTMLunicode{20A6}}
\newcommand*{\LWR@HTML@textpeso}{\HTMLunicode{20B1}}
\newcommand*{\LWR@HTML@textrecipe}{\HTMLunicode{211E}}
\newcommand*{\LWR@HTML@textinterrobangdown}{\HTMLunicode{2E18}}
\newcommand*{\LWR@HTML@textperthousand}{\HTMLunicode{2030}}
\newcommand*{\LWR@HTML@textpertenthousand}{\HTMLunicode{2031}}
\newcommand*{\LWR@HTML@textbaht}{\HTMLunicode{0E3F}}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{\HTMLunicode{2120}}
\else
```

§ 440.3.2 XeLaTeX and LuaLaTeX symbols

NOTE: Some of the following do not print well in the listing. Consult the .dtx or .sty file for the actual characters.

```
\newcommand*{\LWR@HTML@textdegree}{°}
\newcommand*{\LWR@HTML@textcelsius}{}
\newcommand*{\LWR@HTML@textohm}{}
\newcommand*{\LWR@HTML@textmu}{µ}
\newcommand*{\LWR@HTML@textlquill}{}
\newcommand*{\LWR@HTML@textrquill}{}
\newcommand*{\LWR@HTML@textcircledP}{}
\newcommand*{\LWR@HTML@texttwelveudash}{---}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{---}% emdash
\newcommand*{\LWR@HTML@textmho}{}
\newcommand*{\LWR@HTML@textnaira}{}
\newcommand*{\LWR@HTML@textpeso}{}
\newcommand*{\LWR@HTML@textrecipe}{}
```

```
\newcommand*{\LWR@HTML@textinterrobangdown}{}
\newcommand*{\LWR@HTML@textperthousand}{%}
\newcommand*{\LWR@HTML@textpertenthousand}{%}
\newcommand*{\LWR@HTML@textbaht}{}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{}
\fi

\LWR@formatted{textdegree}
\LWR@formatted{textcelsius}
\LWR@formatted{textohm}
\LWR@formatted{textmu}
\LWR@formatted{textlquill}
\LWR@formatted{textrquill}
\LWR@formatted{textcircledP}
\LWR@formatted{texttwelveudash}
\LWR@formatted{textthreequartersemdash}
\LWR@formatted{textmho}
\LWR@formatted{textnaira}
\LWR@formatted{textpeso}
\LWR@formatted{textrecipe}
\LWR@formatted{textinterrobangdown}
\LWR@formatted{textperthousand}
\LWR@formatted{textpertenthousand}
\LWR@formatted{textbaht}
\LWR@formatted{textdiscount}
\LWR@formatted{textservicemark}
```

§ 440.4 HTML diacritics

For HTML, Unicode diacritical marks are used:

```
\newcommand*{\LWR@HTML@capitalcedilla}[1]{#1\HTMLunicode{0327}}
\newcommand*{\LWR@HTML@capitalogonek}[1]{#1\HTMLunicode{0328}}
\newcommand*{\LWR@HTML@capitalgrave}[1]{#1\HTMLunicode{0300}}
\newcommand*{\LWR@HTML@capitalacute}[1]{#1\HTMLunicode{0301}}
\newcommand*{\LWR@HTML@capitalcircumflex}[1]{#1\HTMLunicode{0302}}
\newcommand*{\LWR@HTML@capitaltilde}[1]{#1\HTMLunicode{0303}}
\newcommand*{\LWR@HTML@capitaldieresis}[1]{#1\HTMLunicode{0308}}
\newcommand*{\LWR@HTML@capitalhungarumlaut}[1]{#1\HTMLunicode{30B}}
\newcommand*{\LWR@HTML@capitalring}[1]{#1\HTMLunicode{30A}}
\newcommand*{\LWR@HTML@capitalcaron}[1]{#1\HTMLunicode{30C}}
\newcommand*{\LWR@HTML@capitalbreve}[1]{#1\HTMLunicode{306}}
\newcommand*{\LWR@HTML@capitalmacron}[1]{#1\HTMLunicode{304}}
\newcommand*{\LWR@HTML@capitaldotaccent}[1]{#1\HTMLunicode{307}}
```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with xunicode.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
\InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{capitalcedilla}
\LWR@formatted{capitalogonek}
```

```
\LWR@formatted{capitalgrave}
\LWR@formatted{capitalacute}
\LWR@formatted{capitalcircumflex}
\LWR@formatted{capitaltilde}
\LWR@formatted{capitaldieresis}
\LWR@formatted{capitalhungarumlaut}
\LWR@formatted{capitalring}
\LWR@formatted{capitalcaron}
\LWR@formatted{capitalbreve}
\LWR@formatted{capitalmacron}
\LWR@formatted{capitaldotaccent}
\LWR@formatted{textcircled}
```

Nullify textcomp macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify

}% AtBeginDocument
```

File 344 **lwarp-textfit.sty**

§ 441 Package textfit

Pkg textfit textfit is emulated.

Text is placed into a of class `textfit`. Sizes are approximated, and also limited by browser min/max font-size settings.

for HTML output:

```
\LWR@ProvidesPackageDrop{textfit}[1994/04/15]

\newsavebox{\LWR@textfitbox}

\newcommand*{\LWR@textfitscale}[2]{%
\setlength{\LWR@templengthone}{#1}%
\setlength{\LWR@templengthone}{%
    1em*\ratio{\LWR@templengthone}{\LWR@templengthtwo}%
}%
\InlineClass[font-size:\LWR@printlength{\LWR@templengthone}]{textfit}{#2}%
}

\newcommand*{\scaletowidth}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settowidth{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}

\newcommand*{\scaletoheight}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}
```

File 345 **lwarp-textpos.sty**

§ 442 Package textpos

(*Emulates or patches code by* Norman Gray.)

Pkg textpos textpos is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{textpos}[2016/06/07]

\NewDocumentEnvironment{textblock}{m r()}{}{}
\NewDocumentEnvironment{textblock*}{m o r()}{}{}
\newcommand*{\TPGrid}[3][]{}
\NewDocumentCommand{\TPMargin}{s o}{}
\newcommand*{\textblockcolour}[1]{}
```

```
\newcommand*{\textblockrulecolour}[1]{}
\newcommand*{\textblockcolor}[1]{}
\newcommand*{\textblockrulecolor}[1]{}
\newcommand*{\tekstblokkulur}[1]{}
\newcommand*{\tekstblokrulekulur}[1]{}
\newlength{\TPHorizModule}
\newlength{\TPVertModule}
\newlength{\TPboxrulesize}
\newcommand{\textblocklabel}[1]{}
\newcommand*{\showtextsize}{}
\newcommand{\textblockorigin}[2]{}
```

File 346 **lwarp-theorem.sty**

§ 443 Package theorem

(*Emulates or patches code by* Frank Mittelbach.)

Pkg theorem theorem is patched for use by lwarp.

Table 16: Theorem package — css styling of theorems and proofs

Theorem: of class theorembody<theoremstyle>

Theorem Header: of class theoremheader

where <theoremstyle> is plain, break, etc.

for HTML output:

```
\LWR@ProvidesPackagePass{theorem}[2014/10/28]
```

§ 443.1 Remembering the theorem style

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
   \@ifundefined{th@#1}{\@warning
          {Unknown theoremstyle ‘#1’. Using ‘plain’}%
          \theorem@style{plain}%
           \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
          }%
      {%
          \theorem@style{#1}%
          \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
      }%
      \begingroup
        \csname th@\the\theorem@style \endcsname
      \endgroup}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
\gdef\@xnthm#1#2[#3]{%
   \expandafter\@ifdefinable\csname #1\endcsname
   {%
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \@definecounter{#1}\@newctr{#1}[#3]%
    \expandafter\xdef\csname the#1\endcsname
      {\expandafter \noexpand \csname the#3\endcsname
       \@thmcountersep \@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}%
    \expandafter \@tempa \expandafter{%
      \csname th@\the \theorem@style
            \expandafter \endcsname \the \theorem@bodyfont
     \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@ynthm#1#2{%
    \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \@definecounter{#1}%
    \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@othm#1[#2]#3{%
  \expandafter\ifx\csname c@#2\endcsname\relax
   \@nocounterr{#2}%
  \else
   \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \expandafter \xdef \csname the#1\endcsname
     {\expandafter \noexpand \csname the#2\endcsname}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#2}{#3}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
    }%
  \fi}
```

§ 443.2 css patches

The following are patched for CSS.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader`.

```
\gdef\th@plain{%
  \def\@begintheorem##1##2{%
        \item[
            \InlineClass{theoremheader}{##1\ ##2}
        ]
    }%
\def\@opargbegintheorem##1##2##3{%
   \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}
    ]
    }
}

\gdef\th@break{%
  \def\@begintheorem##1##2{%
    \item[
        \InlineClass{theoremheader}{##1\ ##2}\newline%
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
  \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}\newline
    ]
    }
}

\gdef\th@marginbreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}\newline
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1\ %
        (##3)}\newline
    ]
    }
}

\gdef\th@changebreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2\ ##1}\newline
    ]
```

```
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{ ##2\ ##1\ %
        (##3)}\newline
    ]
    }
}

\gdef\th@change{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2\ ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2\ ##1\ (##3)}
    ]
    }
}

\gdef\th@margin{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
            \InlineClass{theoremheader}{##2 \qquad ##1\ (##3)}
    ]
    }
}
```

Patched for css:

```
\gdef\@thm#1#2{\refstepcounter{#1}%
\LWR@forcenewpage% lwarp
    \BlockClass{theorembody\LWR@thisthmstyle}% lwarp
   \trivlist
   \@topsep \theorempreskipamount               % used by first \item
   \@topsepadd \theorempostskipamount           % used by \@endparenv
   \@ifnextchar [%
   {\@ythm{#1}{#2}}%
   {\@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}}

\gdef\@endtheorem{%
\endtrivlist
\endBlockClass
}
```

File 347 **lwarp-thinsp.sty**

§ 444 Package

thinsp

Pkg thinsp thinsp is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{thinsp}[2016/10/02]
```

```
\AtBeginDocument{
\let\thinthinspace\relax% defined by some packages
\newcommand*{\thinthinspace}{\thinspace}
}

\newcommand*{\stretchthinspace}{\thinspace}
\newcommand*{\stretchthinthinspace}{\thinthinspace}
\newcommand*{\stretchnegthinspace}{\negthinspace}
```

File 348 **lwarp-threadcol.sty**

§ 445 Package

threadcol

Pkg threadcol threadcol is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{threadcol}[2013/01/06]
```

```
\newcommand{\setthreadname}[1]{}
```

File 349 **lwarp-threeparttable.sty**

§ 446 Package

threeparttable

(*Emulates or patches code by* Donald Arseneau.)

Pkg threeparttable threeparttable is emulated.

Table note are contained inside a CSS `<div>` of class `tnotes`. If enumitem is used, the note item labels are also individually highlighted with an additional CSS `<span>` of class `tnoteitemheader`, otherwise they are plain text.

for HTML output:

```
\LWR@ProvidesPackageDrop{threeparttable}[2003/06/13]
```

Env threeparttable [⟨*alignment*⟩] To emulate threeparttable:

```
\newenvironment*{threeparttable}[1][b]
```

```
    {\def\@captype{table}}
    {}
```

Env tablenotes [⟨*options*⟩]

```
\newenvironment*{tablenotes}[1][]
{%
\LWR@forcenewpage
\BlockClass{tnotes}%
\description%
}
{%
\enddescription%
\endBlockClass%
}
```

\tnote {⟨*text*⟩}

```
\newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}
```

File 350 **lwarp-threeparttablex.sty**

§ 447 Package threeparttablex

Pkg threeparttablex threeparttablex is patched for use by lwarp.

threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{         % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width The table notes are created using a \multicolumn. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use \UseMinipageWidths before \insertTableNotes. The width is then specified, and in many cases the result is an improvement in overall table layout.

for HTML output:

```
\LWR@ProvidesPackagePass{threeparttablex}[2013/07/23]
```

The width is guessed depending on the number of columns, then limited to a min/max.

```
\renewcommand\insertTableNotes{%
    \setlength{\LWR@templengthone}{.375in*\value{LWR@tabletotalLaTeXcols}}%
    \setlength{\LWR@templengthone}{\minof{\textwidth}{\LWR@templengthone}}%
    \setlength{\LWR@templengthone}{\maxof{2.5in}{\LWR@templengthone}}%
  \multicolumn{\value{LWR@tabletotalLaTeXcols}}{c}{%
      \parbox{\LWR@templengthone}{%
        \begin{tablenotes}[\TPTL@optarg]%
          \TPTL@font%
          \TPTL@body%
        \end{tablenotes}%
      }%
  }%
}

\renewcommand\TPTL@tnotex[2]{\tnote{\nameref{#2}}}
```

File 351 **lwarp-thumb.sty**

§ 448 Package thumb

Pkg thumb

thumb is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{thumb}[1997/12/24]
```

```
\newcommand*{\Overviewpage}{}
\newlength{\thumbheight}
\newlength{\thumbwidth}
```

File 352 **lwarp-thumbs.sty**

§ 449 Package thumbs

Pkg thumbs

thumbs is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{thumbs}[2014/03/09]
```

```
\newcommand{\addthumb}[4]{}
\newcommand{\addtitlethumb}[5]{}
\newcommand{\stopthumb}{}
\newcommand{\continuethumb}{}
\newcommand{\thumbsoverview}[1]{}
\newcommand{\thumbsoverviewback}[1]{}
\newcommand{\thumbsoverviewverso}[1]{}
\newcommand{\thumbsoverviewdouble}[1]{}
\newcommand{\thumbnewcolumn}{}
```

```
\newcommand{\addthumbsoverviewtocontents}[2]{}
\newcommand{\thumbsnophantom}{}
```

File 353 **lwarp-tikz.sty**

§ 450 Package

tikz

(*Emulates or patches code by* Till Tantau.)

Pkg tikz

tikz is supported.

⚠ displaymath and matrices

If using display math with tikzpicture or \tikz, along with matrices with the & character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of & in the tikz expression must be replaced with \&.

Accept all options for lwarp-tikz:

```
\LWR@ProvidesPackagePass{tikz}[2015/08/07]
```

catcodes

lwarp changes the catcode of $ for its own use. The Ti*k*z babel library temporarily changes catcodes back to normal for Ti*k*z's use. tikz v3.0.0 introduced the babel library which handles catcode changes. For older versions, lwarp must change $'s catcode itself.

Also see:
https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded

```
\newbool{LWR@tikzbabel}

\@ifpackagelater{tikz}{2013/12/20}% Test for Tikz version v3.0.0
{\usetikzlibrary{babel}\booltrue{LWR@tikzbabel}}
{\boolfalse{LWR@tikzbabel}}
```

Env pgfpicture

The \pgfpicture environment is enclosed inside a \lateximage. Enclose the low-level \pgfpicture in a lateximage. This is also used by the higher-level \tikz and tikzpicture.

```
\preto\pgfpicture{%
    \begin{lateximage}%
    \ifbool{LWR@tikzbabel}% Test for Tikz version v3.0.0
    {}%
    {\catcode`\$=3}% dollar sign is math shift
}

\appto\endpgfpicture{\end{lateximage}}
```

Ti*k*z is placed inside an SVG image, so use the original meanings of the following:

```
\LetLtxMacro\pgfutil@minipage\LWR@print@minipage
\let\pgfutil@endminipage\endLWR@print@minipage

\let\pgfutil@raggedleft\LWR@print@raggedleft
\let\pgfutil@raggedright\LWR@print@raggedright

\def\pgfutil@font@tiny{\LWR@printtiny}
\def\pgfutil@font@scriptsize{\LWR@printscriptsize}
\def\pgfutil@font@footnotesize{\LWR@printfootnotesize}
\def\pgfutil@font@small{\LWR@print@small}
\def\pgfutil@font@normalsize{\LWR@print@normalsize}
\def\pgfutil@font@large{\LWR@printlarge}
\def\pgfutil@font@Large{\LWR@printLarge}
\def\pgfutil@font@huge{\LWR@printhuge}
\def\pgfutil@font@Huge{\LWR@printHuge}

\def\pgfutil@font@itshape{\LWR@origitshape}
\def\pgfutil@font@bfseries{\LWR@origbfseries}

\def\pgfutil@font@normalfont{\LWR@orignormalfont}
```

File 354 **lwarp-titleps.sty**

§ 451 Package

titleps

(*Emulates or patches code by* Javier Bezos.)

Pkg titleps

titleps is loaded and used by lwarp during HTML output. All user options and macros are ignored and disabled.

Discard all options for lwarp-titleps:

for HTML output:

```
\LWR@ProvidesPackageDrop{titleps}[2016/03/15]
```

\pagestyle and \thispagestyle are already disabled in the lwarp code.

\newpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\newpagestyle}{m o m}{}
```

\renewpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\renewpagestyle}{m o m}{}
```

\sethead [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\sethead}{o o o m m m}{}
```

\setfoot [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\setfoot}{o o o m m m}{}
```

\settitlemarks * {⟨*names*⟩}

```
\NewDocumentCommand{\settitlemarks}{s m}{}
```

\headrule

```
\newcommand*{\headrule}{}
```

\footrule

```
\newcommand*{\footrule}{}
```

\setheadrule {⟨*length*⟩}

```
\newcommand*{\setheadrule}[1]{}
```

\setfootrule {⟨*length*⟩}

```
\newcommand*{\setfootrule}[1]{}
```

\makeheadrule

```
\newcommand*{\makeheadrule}{}
```

\makefootrule

```
\newcommand*{\makefootrule}{}
```

\setmarkboth {⟨*code*⟩}

```
\newcommand{\setmarkboth}[1]{}
```

\widenhead

```
\NewDocumentCommand{\widenhead}{s o o m m}{}
```

\bottitlemarks

```
\newcommand*{\bottitlemarks}{}
```

\toptitlemarks

```
\newcommand*{\toptitlemarks}{}
```

\firsttitlemarks

```
\newcommand*{\firsttitlemarks}{}
```

\nexttitlemarks

```
\newcommand*{\nexttoptitlemarks}{}
```

\outertitlemarks

```
\newcommand*{\outertitlemarks}{}
```

\innertitlemarks

```
\newcommand*{\innertitlemarks}{}
```

\newtitlemark * {⟨*name*⟩}

```
\NewDocumentCommand{\newtitlemark}{s m}{}
```

\pretitlemark * {⟨*section*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\pretitlemark}{s m m}{}
```

\ifsamemark {⟨*group*⟩} {⟨*command*⟩} {⟨*true*⟩} {⟨*false*⟩}

```
\newcommand{\ifsamemark}[4]{}
```

\setfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\setfloathead}{s o o o m m m m m}{}
```

\setfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\setfloatfoot}{s o o o m m m m m}{}
```

\nextfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\nextfloathead}{s o o o m m m m m}{}
```

\nextfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
\NewDocumentCommand{\nextfloatfoot}{s o o o m m m m m}{}
```

\newmarkset {⟨*markset*⟩}

```
\newcommand{\newmarkset}[1]{}
```

\newextramark * {⟨*markset*⟩} {⟨*macro-name*⟩}

```
\NewDocumentCommand{\newextramarkset}{s m m}{}
```

\botextramarks {⟨*markset*⟩}

```
\newcommand{\botextramarks}[1]{}
```

\topextramarks {⟨*markset*⟩}

```
\newcommand{\topextramarks}[1]{}
```

\firstextramarks {⟨*markset*⟩}

```
\newcommand{\firstextramarks}[1]{}
```

\nextextramarks {⟨*markset*⟩}

```
\newcommand{\nexttopextramarks}[1]{}
```

\outerextramarks {⟨*markset*⟩}

```
\newcommand{\outerextramarks}[1]{}
```

\innerextramarks {⟨*markset*⟩}

```
\newcommand{\innerextramarks}[1]{}
```

File 355 **lwarp-titleref.sty**

§ 452 Package titleref

Pkg titleref titleref is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{titleref}[2001/04/05]

\LetLtxMacro\titleref\nameref

\providecounter{LWR@currenttitle}

\newcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}

\newcommand*{\theTitleReference}[2]{}
```

File 356 **lwarp-titlesec.sty**

§ 453 Package titlesec

(*Emulates or patches code by* Javier Bezos.)

Pkg titlesec titlesec is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titlesec:

for HTML output:

```
\LWR@ProvidesPackageDrop{titlesec}[2016/03/21]
```

\titlelabel {⟨*label-format*⟩}

```
\newcommand*{\titlelabel}[1]{}
```

\titleformat* {⟨*command*⟩} {⟨*format*⟩}

\titleformat {⟨*command*⟩} [⟨*shape*⟩] {⟨*format*⟩} {⟨*label*⟩} {⟨*sep*⟩} {⟨*begfore*⟩} [⟨*after*⟩]

```
\newcommand\titleformat{%
  \@ifstar{\ttl@format@s}%
          {\ttl@format@i}}
\newcommand{\ttl@format@s}[1]{}
\NewDocumentCommand{\ttl@format@i}{m o m m m m o}{}
```

\chaptertitlename

```
\@ifundefined{@chapapp}{\let\@chapapp\chaptername}{}
\newcommand\chaptertitlename{\@chapapp}
```

\titlespacing * {⟨*command*⟩} {⟨*left*⟩} {⟨*before*⟩} {⟨*after*⟩} [⟨*right*⟩]

```
\NewDocumentCommand{\titlespacing}{s m m m m o}{}
```

\filright

```
\newcommand*{\filright}{}
```

\filcenter

```
\newcommand*{\filcenter}{}
```

\filleft

```
\newcommand*{\filleft}{}
```

\fillast

```
\newcommand*{\fillast}{}
```

\filinner

```
\newcommand*{\filinner}{}
```

\filouter

```
\newcommand*{\filouter}{}
```

\wordsep

```
\newcommand\wordsep{\fontdimen\tw@\font \@plus
  \fontdimen\thr@@\font \@minus \fontdimen4\font}
```

\titleline * [⟨*align*⟩] {⟨*material*⟩}

```
\NewDocumentCommand{\titleline}{s o m}{}
```

\titlerule [⟨*height*⟩]

```
\providecommand*\titlerule{\@ifstar{\ttl@row}{\ttl@rule}}
\newcommand*{\ttl@rule}[1][]{}
\newcommand*{\ttl@row}[2][]{}
```

\iftitlemeasuring {⟨*true*⟩} {⟨*false*⟩}

```
\newcommand{\iftitlemeasuring}[2]{#2}
```

\assignpagestyle {⟨*command*⟩} {⟨*pagestyle*⟩}

```
\newcommand{\assignpagestyle}[2]{#2}
```

\titleclass {⟨*name*⟩} [⟨*startlevel*⟩] {⟨*class*⟩} [⟨*cmd*⟩]

```
\NewDocumentCommand{\titleclass}{m o m o}
```

File 357 **lwarp-titletoc.sty**

§ 454 Package

titletoc

(*Emulates or patches code by* Javier Bezos.)

Pkg titletoc titletoc is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titletoc:

for HTML output:

```
\LWR@ProvidesPackageDrop{titletoc}[2011/12/15]
```

\dottedcontents {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*label*⟩} {⟨*leader*⟩}

```
\NewDocumentCommand{\dottedcontents}{m o m m m}{}
```

\titlecontents * {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*numbered*⟩} {⟨*numberless*⟩} {⟨*filler*⟩} [⟨*below or begin*⟩] [⟨*separator*⟩] [⟨*end*⟩]

```
\newcommand{\titlecontents}{\@ifstar{\ttl@tcstar}{\ttl@tcnostar}}
\NewDocumentCommand{\ttl@tcstar}{m o m m m m o o o}{}
\NewDocumentCommand{\ttl@tcnostar}{m o m m m m o}{}
```

\contentsmargin [⟨*correction*⟩] {⟨*right*⟩}

```
\newcommand{\contentsmargin}[2][]{}
```

\thecontentslabel

```
\newcommand*{\thecontentslabel}{thecontentslabel}
```

\thecontentspage

```
\newcommand*{\thecontentspage}{thecontentspage}
```

\contentslabel [⟨*format*⟩] {⟨*space*⟩}

```
\newcommand{\contentslabel}[2][]{\thecontentslabel}
```

\contentspage [⟨*format*⟩]

```
\newcommand{\contentspage}[1][]{\thecontentspage}
```

\contentspush {⟨*text*⟩}

```
\newcommand{\contentspush}[1]{}
```

\contentsuse {⟨*name*⟩} {⟨*text*⟩}

```
\newcommand{\contentsuse}[2]{}
```

\startcontents [⟨*name*⟩]

```
\newcommand*{\startcontents}[1][]{}
```

\stopcontents [⟨*name*⟩]

```
\newcommand*{\stopcontents}[1][]{}
```

\resumecontents [⟨*name*⟩]

```
\newcommand*{\resumecontents}[1][]{}
```

\printcontents [⟨*name*⟩] {⟨*prefix*⟩} {⟨*start*⟩} {⟨*code*⟩}

```
\newcommand{\printcontents}[4][]{}
```

\startlist [⟨*name*⟩] {⟨*list*⟩}

```
\newcommand{\startlist}[2][]{}
```

\stoplist [⟨*name*⟩] {⟨*list*⟩}

```
\newcommand{\stoplist}[2][]{}
```

\resumelist [⟨*name*⟩] {⟨*list*⟩}

```
\newcommand{\resumelist}[2][]{}
```

\printlist [⟨*name*⟩] {⟨*list*⟩} {⟨*prefix*⟩} {⟨*code*⟩}

```
\newcommand{\printlist}[4][]{}
```

File 358 **lwarp-titling.sty**

§ 455 Package

titling

(*Emulates or patches code by* Peter Wilson.)

Pkg titling

package support
⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 65.8.

The various titling footnote restyling commands have no effect.

Pass all options to lwarp-titling:

for HTML output:

```
\LWR@ProvidesPackagePass{titling}[2009/09/04]
```

\@bsmtitlempty

Patch \@bsmtitlempty:

```
\let\LWR@orig@bsmtitlempty\@bsmtitlempty
\renewcommand*{\@bsmtitlempty}{%
\LWR@orig@bsmtitlempty%
}
```

\keepthetitle

Patch \keepthetitle:

```
\let\LWR@origkeepthetitle\keepthetitle
\renewcommand*{\keepthetitle}{%
\LWR@orig@keepthetitle%
}
```

\killtitle

Patch \killtitle:

```
\let\LWR@origkilltitle\killtitle
\renewcommand*{\killtitle}{%
\LWR@orig@killtitle%
}
```

Env titlingpage

```
\renewenvironment*{titlingpage}
{%
```

Start an HTML titlepage div:

```
\LWR@printpendingfootnotes
\begin{titlepage}
```

Prepare for a custom version of \maketitle inside the titlingpage:

```
\LWR@maketitlesetup
\let\maketitle\LWR@titlingmaketitle
}
{
```

At the end of the environment, end the HTML titlepage div:

```
\end{titlepage}
}
```

Patch the pre/post title/author/date to add HTML tags, then initilize:

```

\pretitle{}
\posttitle{}

\preauthor{}
\postauthor{}

\predate{}
\postdate{}
```

\LWR@maketitlesetup Patches \thanks macros.

```
\renewcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
\def\@makefnmark{\textsuperscript{\@thefnmark}}
```

\thefootnote ⇒ \nameuse{arabic}{footnote}, or
\thefootnote ⇒ \nameuse{fnsymbol}{footnote}

Redefine the footnote text:

```
\long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
\makethanksmark~%
```

\makethanksmark ⇒ \thanksfootmark ⇒ \tamark ⇒
\@thefnmark ⇒ \itshape a (or similar)

Print the text:

```
##1%
}% \@makefntext
}
```

\thanksfootmark

```
\renewcommand{\thanksfootmark}{%
%   \hb@xt@\thanksmarkwidth{\hfil\normalfont%
        \thanksscript{%
            \thanksfootpre \tamark \thanksfootpost%
        }%
%   }%
}
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage is used for all classes.

```
\begin{titlepage}
```

Select which kind of footnote marks to use:

```
\@bsmarkseries
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\@thanks
```

Close the HTML titlepage div:

```
\end{titlepage}
```

Reset the footnote counter:

```
\@bscontmark
}
```

\@maketitle Typesets the title, etc. Patched for HTML.

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \maketitlehooka
    {
        \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
```

```
        \@bspretitle \@title \@bsposttitle%
        \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
    }
    \maketitlehookb
    {
        \begin{BlockClass}{author}
        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }
        \begin{BlockClass}{oneauthor}%
        \@bspreauthor \@author  \@bspostauthor%
        \end{BlockClass}%
        \end{BlockClass}%
    }
    \maketitlehookc
    {
        \begin{BlockClass}{titledate}%
        \@bspredate \@date \@bspostdate%
        \end{BlockClass}%
    }
    \maketitlehookd
}
```

`\LWR@titlingmaketitle` `\maketitle` for use inside an HTML `titlingpage` environment.

```
\renewcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\@thanks
```

Select which kind of footnote marks to use:

```
\@bsmarkseries
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any `\thanks` footnotes:

```
\@thanks
```

Reset the footnote counter:

```
\@bscontmark
}
```

\thanksmarkseries {⟨*series*⟩}

Sets the type of footnote marks used by \thanks, where type is 'arabic', 'roman', 'fnsymbol', etc.

```
\renewcommand{\thanksmarkseries}[1]{%
\def\@bsmarkseries{\renewcommand{\thefootnote}{\@nameuse{#1}{footnote}}}%
}
```

Set default titlepage thanks footnote marks. See section 65.7.

```
\@ifclassloaded{memoir}{
   \thanksmarkseries{arabic}
}{% not memoir
\if@titlepage
   \thanksmarkseries{arabic}
\else
   \thanksmarkseries{fnsymbol}
\fi
}% not memoir
```

File 359 **lwarp-tocbasic.sty**

§ 456 Package

tocbasic

(*Emulates or patches code by* Markus Kohm.)

Pkg tocbasic

tocbasic is nullified for lwarp.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackagePass{tocbasic}[2018/12/30]
```

```
\DeclareDocumentCommand{\usetocbasicnumberline}{o}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntry}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntries}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCEntryStyle}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryOption}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryBooleanOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryCommandOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryIfOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryLengthOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryNumberOption}{m o m m m}{}
\DeclareDocumentCommand{\CloneTOCEntryStyle}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleInitCode}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleStartInitCode}{m m}{}
```

File 360 **lwarp-tocbibind.sty**

§ 457 Package

tocbibind

(*Emulates or patches code by* Peter Wilson.)

Pkg tocbibind tocbibind is patched for use by lwarp.

placement and TOC options An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex

numbered index section

Use the tocbibind numindex option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

for HTML output:

```
\let\simplechapterdelim\relax

\LWR@ProvidesPackagePass{tocbibind}[2010/10/13]

\renewenvironment{theindex}%
{%
     \if@bibchapter
        \if@donumindex
            \chapter{\indexname}
        \else
          \if@dotocind
            \chapter*{\indexname}
            \addcontentsline{toc}{chapter}{\LWR@isolate{\indexname}}
          \else
            \chapter*{\indexname}
          \fi
        \fi
     \else
        \if@donumindex
            \section{\indexname}
        \else
          \if@dotocind
            \section*{\indexname}
            \addcontentsline{toc}{\@tocextra}{\LWR@isolate{\indexname}}
          \else
            \section*{\indexname}
          \fi
        \fi
     \fi
\let\item\LWR@indexitem%
\let\subitem\LWR@indexsubitem%
\let\subsubitem\LWR@indexsubsubitem%
}{}
```

The following code is shared by anonchap.

```
\DeclareDocumentCommand{\simplechapter}{O{\@empty}}{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\DeclareDocumentCommand{\restorechapter}{}{%
\let\@chapcntformat\@seccntformat%
}
```

File 361 **lwarp-tocdata.sty**

§ 458 Package tocdata

(*Emulates or patches code by* Brian Dunn.)

Pkg tocdata

tocdata is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{tocdata}[2019/03/21]

\renewcommand*{\LWR@maybetocdata}{%
    \ifdefempty{\TD@thistocdata}{}{%
        \qquad --- \InlineClass{authorartist}{\TD@thistocdata}%
        \def\TD@thistocdata{}
    }
}

\renewrobustcmd{\tocdatapartprint}[4]
{%
    \LWR@htmltagc{br /}%
    \InlineClass{authorartist}{%
        \qquad --- %
        \TD@optionalname{#1}\TD@optionalname{#2}#3#4%
    }%
}

\@ifundefined{chapter}{}{
    \let\tocdatachapterprint\tocdatapartprint
}
\let\tocdatasectionprint\tocdatapartprint
\let\tocdatasubsectionprint\tocdatapartprint

\newcommand*{\LWR@TD@settextalign}[1]{%
    \def\LWR@TD@textalign{justify}%
    \ifcsstring{TD@#1align}{\centering}%
        {\def\LWR@TD@textalign{center}}%
        {}%
    \ifcsstring{TD@#1align}{\raggedleft}%
        {\def\LWR@TD@textalign{right}}%
        {}%
    \ifcsstring{TD@#1align}{\raggedright}%
        {\def\LWR@TD@textalign{left}}%
        {}%
}

\renewcommand{\TD@artistauthorprint}[5]{%
    \LWR@TD@settextalign{#1}%
    \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
    \InlineClass{authorartist}{\TD@optionalname{#2}\TD@optionalname{#3}#4#5}%
    \end{BlockClass}%
}

\newcommand*{\LWR@TD@setnamealign}[1]{%
    \def\LWR@TD@textalign{justify}%
    \ifcsstring{TD@#1textalign}{\centering}%
        {\def\LWR@TD@textalign{center}}%
        {}%
    \ifcsstring{TD@#1textalign}{\raggedleft}%
        {\def\LWR@TD@textalign{right}}%
        {}%
    \ifcsstring{TD@#1textalign}{\raggedright}%
```

```
        {\def\LWR@TD@textalign{left}}%
        {}%
}

\renewcommand{\TD@artistauthortextprint}[2]{%
    \LWR@TD@setnamealign{#1}%
    \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
    #2%
    \end{BlockClass}%
}
```

File 362 **lwarp-tocenter.sty**

§ 459 Package

tocenter

Pkg tocenter

tocenter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tocenter}[2004/12/09]
```

```
\NewDocumentCommand{\ToCenter}{s o m m}{}
\NewDocumentCommand{\FromMargins}{s o m m m m}{}
```

File 363 **lwarp-tocloft.sty**

§ 460 Package

tocloft

(*Emulates or patches code by* Peter Wilson.)

Pkg tocloft

tocloft is emulated. Most user options and macros are ignored and disabled. `\newlistof` and `\cftchapterprecis` are supported.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

Discard all options for lwarp-tocloft:

for HTML output:

```
\LWR@ProvidesPackageDrop{tocloft}[2017/08/31]
```

`\tocloftpagestyle` {⟨*style*⟩}

```
\newcommand{\tocloftpagestyle}[1]{}
```

`\cftmarktoc`

```
\newcommand*{\cftmarktoc}{}
```

`\cfttoctitlefont`

```
\newcommand*{\cfttoctitlefont}{}
```

\cftaftertoctitle

```
\newcommand*{\cftaftertoctitle}{}

\newlength{\cftbeforetoctitleskip}
\newlength{\cftaftertoctitleskip}
```

\cftmarklof

```
\newcommand*{\cftmarklof}{}
```

\cftloftitlefont

```
\newcommand*{\cftloftitlefont}{}
```

\cftafterloftitle

```
\newcommand*{\cftafterloftitle}{}

\newlength{\cftbeforeloftitleskip}
\newlength{\cftafterloftitleskip}
```

\cftmarklot

```
\newcommand*{\cftmarklot}{}
```

\cftlottitlefont

```
\newcommand*{\cftlottitlefont}{}
```

\cftafterlottitle

```
\newcommand*{\cftafterlottitle}{}

\newlength{\cftbeforelottitleskip}
\newlength{\cftafterlottitleskip}
```

\cftdot

```
\providecommand*{\cftdot}{.}
```

\cftdotsep

```
\providecommand*{\cftdotsep}{1}
```

\cftnodots

```
\providecommand*{\cftnodots}{5000}
```

\cftdotfill {⟨*sep*⟩}

```
\providecommand{\cftdotfill}[1]{}
```

\cftsetpnumwidth {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetpnumwidth}{m}{}
```

\cftsetrmarg {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetrmarg}{m}{}
```

\cftpnumalign {⟨*alignment*⟩}

```
\DeclareDocumentCommand{\cftpnumalign}{m}{}
```

```
\LWR@providelength{\cftparskip}
```

The part-related items are also provided by memoir:

```
\LWR@providelength{\cftbeforepartskip}
\LWR@providelength{\cftpartindent}
\LWR@providelength{\cftpartnumwidth}
\providecommand*{\cftpartfont}{}
\providecommand*{\cftpartpresnum}{}
\providecommand*{\cftpartaftersnum}{}
\providecommand*{\cftpartaftersnumb}{}
\providecommand*{\cftpartleader}{}
\providecommand*{\cftpartdotsep}{1}
\providecommand*{\cftpartpagefont}{}
\providecommand*{\cftpartafterpnum}{}
```

memoir uses the full name “chapter” instead of “chap”:

```
\LWR@providelength{\cftbeforechapskip}
\LWR@providelength{\cftchapindent}
\LWR@providelength{\cftchapnumwidth}
\newcommand*{\cftchapfont}{}
\newcommand*{\cftchappresnum}{}
\newcommand*{\cftchapaftersnum}{}
\newcommand*{\cftchapaftersnumb}{}
\newcommand*{\cftchapleader}{}
\newcommand*{\cftchapdotsep}{1}
\newcommand*{\cftchappagefont}{}
\newcommand*{\cftchapafterpnum}{}
```

The following do not appear in memoir:

```
\LWR@providelength{\cftbeforesecskip}
\LWR@providelength{\cftsecindent}
\LWR@providelength{\cftsecnumwidth}
\newcommand*{\cftsecfont}{}
\newcommand*{\cftsecpresnum}{}
```

```
\newcommand*{\cftsecaftersnum}{}
\newcommand*{\cftsecaftersnumb}{}
\newcommand*{\cftsecleader}{}
\newcommand*{\cftsecdotsep}{1}
\newcommand*{\cftsecpagefont}{}
\newcommand*{\cftsecafterpnum}{}

\LWR@providelength{\cftbeforesubsecskip}
\LWR@providelength{\cftsubsecindent}
\LWR@providelength{\cftsubsecnumwidth}
\newcommand*{\cftsubsecfont}{}
\newcommand*{\cftsubsecpresnum}{}
\newcommand*{\cftsubsecaftersnum}{}
\newcommand*{\cftsubsecaftersnumb}{}
\newcommand*{\cftsubsecleader}{}
\newcommand*{\cftsubsecdotsep}{1}
\newcommand*{\cftsubsecpagefont}{}
\newcommand*{\cftsubsecafterpnum}{}

\LWR@providelength{\cftbeforesubsubsecskip}
\LWR@providelength{\cftsubsubsecindent}
\LWR@providelength{\cftsubsubsecnumwidth}
\newcommand*{\cftsubsubsecfont}{}
\newcommand*{\cftsubsubsecpresnum}{}
\newcommand*{\cftsubsubsecaftersnum}{}
\newcommand*{\cftsubsubsecaftersnumb}{}
\newcommand*{\cftsubsubsecleader}{}
\newcommand*{\cftsubsubsecdotsep}{1}
\newcommand*{\cftsubsubsecpagefont}{}
\newcommand*{\cftsubsubsecafterpnum}{}

\LWR@providelength{\cftbeforeparaskip}
\LWR@providelength{\cftparaindent}
\LWR@providelength{\cftparanumwidth}
\newcommand*{\cftparafont}{}
\newcommand*{\cftparapresnum}{}
\newcommand*{\cftparaaftersnum}{}
\newcommand*{\cftparaaftersnumb}{}
\newcommand*{\cftparaleader}{}
\newcommand*{\cftparadotsep}{1}
\newcommand*{\cftparapagefont}{}
\newcommand*{\cftparaafterpnum}{}

\LWR@providelength{\cftbeforesubparaskip}
\LWR@providelength{\cftsubparaindent}
\LWR@providelength{\cftsubparanumwidth}
\newcommand*{\cftsubparafont}{}
\newcommand*{\cftsubparapresnum}{}
\newcommand*{\cftsubparaaftersnum}{}
\newcommand*{\cftsubparaaftersnumb}{}
\newcommand*{\cftsubparaleader}{}
\newcommand*{\cftsubparadotsep}{1}
\newcommand*{\cftsubparapagefont}{}
\newcommand*{\cftsubparaafterpnum}{}
```

```
\LWR@providelength{\cftbeforefigskip}
\LWR@providelength{\cftfigindent}
\LWR@providelength{\cftfignumwidth}
\newcommand*{\cftfigfont}{}
\newcommand*{\cftfigpresnum}{}
\newcommand*{\cftfigaftersnum}{}
\newcommand*{\cftfigaftersnumb}{}
\newcommand*{\cftfigleader}{}
\newcommand*{\cftfigdotsep}{1}
\newcommand*{\cftfigpagefont}{}
\newcommand*{\cftfigafterpnum}{}
```

```
\LWR@providelength{\cftbeforesubfigskip}
\LWR@providelength{\cftsubfigindent}
\LWR@providelength{\cftsubfignumwidth}
\newcommand*{\cftsubfigfont}{}
\newcommand*{\cftsubfigpresnum}{}
\newcommand*{\cftsubfigaftersnum}{}
\newcommand*{\cftsubfigaftersnumb}{}
\newcommand*{\cftsubfigleader}{}
\newcommand*{\cftsubfigdotsep}{1}
\newcommand*{\cftsubfigpagefont}{}
\newcommand*{\cftsubfigafterpnum}{}
```

```
\LWR@providelength{\cftbeforetabskip}
\LWR@providelength{\cfttabindent}
\LWR@providelength{\cfttabnumwidth}
\newcommand*{\cfttabfont}{}
\newcommand*{\cfttabpresnum}{}
\newcommand*{\cfttabaftersnum}{}
\newcommand*{\cfttabaftersnumb}{}
\newcommand*{\cfttableader}{}
\newcommand*{\cfttabdotsep}{1}
\newcommand*{\cfttabpagefont}{}
\newcommand*{\cfttabafterpnum}{}
```

```
\LWR@providelength{\cftbeforesubtabskip}
\LWR@providelength{\cftsubtabindent}
\LWR@providelength{\cftsubtabnumwidth}
\newcommand*{\cftsubtabfont}{}
\newcommand*{\cftsubtabpresnum}{}
\newcommand*{\cftsubtabaftersnum}{}
\newcommand*{\cftsubtabaftersnumb}{}
\newcommand*{\cftsubtableader}{}
\newcommand*{\cftsubtabdotsep}{1}
\newcommand*{\cftsubtabpagefont}{}
\newcommand*{\cftsubtabafterpnum}{}
```

```
\DeclareDocumentCommand{\cftsetindents}{m m m}{}
```

```
\newcommand{\pagenumbersoff}[1]{}
\newcommand{\pagenumberson}[1]{}
```

\newlistentry [⟨*within*⟩] {⟨*counter*⟩} {⟨*ext*⟩} {⟨*level-1*⟩}

```
\DeclareDocumentCommand{\newlistentry}{o m m m}
{%
\LWR@traceinfo{newlistentry #2 #3 #4}%
\IfValueTF{#1}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}[#1]%
        \expandafter\edef\csname the#2\endcsname{%
            \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}%
        }%
    }{}%
}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}%
    }{}%
}%
\@namedef{l@#2}##1##2{%
    \hypertocfloat{1}{#2}{#3}{##1}{##2}%
    \def\cftwhatismyname{#2}% from memoir
}%
\expandafter\newlength\csname cftbefore#2skip\endcsname%
\expandafter\newlength\csname cft#2indent\endcsname%
\expandafter\newlength\csname cft#2numwidth\endcsname%
\@namedef{cft#2font}{}%
\@namedef{cft#2presnum}{}%
\@namedef{cft#2aftersnum}{}%
\@namedef{cft#2aftersnumb}{}%
\@namedef{cft#2leader}{}%
\@namedef{cft#2dotsep}{1}%
\@namedef{cft#2pagefont}{}%
\@namedef{cft#2afterpnum}{}%
\@namedef{toclevel@#2}{#4}%
\@namedef{cft#2fillnum}##1{}%
\LWR@traceinfo{newlistentry done}%
}
```

\newlistof [⟨*within*⟩] {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the `\newfloat` mechanism.

```
\DeclareDocumentCommand{\newlistof}{o m m m}
{%
\IfValueTF{#1}
{\newlistentry[#1]{#2}{#3}{0}}
{\newlistentry{#2}{#3}{0}}
\@namedef{ext@#2}{#3}
\@ifundefined{c@#3depth}{\newcounter{#3depth}}{}
\setcounter{#3depth}{1}
\@namedef{cftmark#3}{}
\@namedef{listof#2}{\listof{#2}{#4}}
\@namedef{@cftmake#3title}{}
\expandafter\newlength\csname cftbefore#3titleskip\endcsname
\expandafter\newlength\csname cftafter#3titleskip\endcsname
```

```
\@namedef{cft#3titlefont}{}
\@namedef{cftafter#3title}{}
\@namedef{cft#3prehook}{}
\@namedef{cft#3posthook}{}
}
```

\cftchapterprecis {⟨*text*⟩}

```
\newcommand{\cftchapterprecis}[1]{%
  \cftchapterprecishere{#1}
  \cftchapterprecistoc{#1}}
\newcommand{\cftchapterprecishere}[1]{%
  \begin{quote}\textit{#1}\end{quote}}
\newcommand{\cftchapterprecistoc}[1]{
  \addtocontents{toc}{%
  {
     \protect\begin{quote}#1\protect\end{quote}}
  }
}
```

File 364 **lwarp-tocstyle.sty**

§ 461 Package tocstyle

Pkg tocstyle tocstyle is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{tocstyle}[2017/02/23]
```

```
\newcommand*{\usetocstyle}[2][]{}
\newcommand*{\deactivatetocstyle}[1][]{}
\newcommand*{\reactivatetocstyle}[1][]{}
\NewDocumentCommand{\settocfeature}{o o m m}{}
\NewDocumentCommand{\settocstylefeature}{o m m}{}
\NewDocumentCommand{\newtocstyle}{o o m m}{}
\newcommand*{\aliastoc}[2]{}
\newcommand*{\showtoc}[2][]{}
\newcommand{\iftochasdepth}[4]{}
```

File 365 **lwarp-todo.sty**

§ 462 Package todo

(*Emulates or patches code by* Federico Garcia.)

Pkg todo todo is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{todo}[2010/03/31]
```

```
\renewcommand\todoitem[2]{%
    \refstepcounter{todo}%
    \item[%
        \HTMLunicode{2610} \quad
        \ref{todopage:\thetodo}
     ] : {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
    \label{todolbl:\thetodo}%
}%

\renewcommand\doneitem[2]{%
    \stepcounter{todo}%
    \item[%
        \HTMLunicode{2611} \quad
        \ref{todopage:\thetodo}
    ] \@nameuse{@done\the\c@todo}:
        {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
}

\xpatchcmd{\@displaytodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displaytodo.}}

\xpatchcmd{\@displayfulltodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displayfulltodo.}}

\patchcmd{\todoenv}{\itshape see text.}{\textit{see text.}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch todoenv.}}

\patchcmd{\astodos}{\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch astodos.}}

\AtBeginDocument{
    \crefname{todo}{todo}{todos}
    \Crefname{todo}{Todo}{Todos}
}
```

File 366 **lwarp-todonotes.sty**

§ 463 Package

todonotes

(*Emulates or patches code by* Henrik Skov Midtiby.)

Pkg todonotes todonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{todonotes}[2012/07/25]
```

```
\if@todonotes@disabled
\else
```

```

\newcommand{\ext@todo}{tdo}

\renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}


\let\LWRTODONOTES@orig@todototoc\todototoc

\renewcommand*{\todototoc}{%
\phantomsection%
\LWRTODONOTES@orig@todototoc%
}

\renewcommand{\@todonotes@drawMarginNoteWithLine}{
\fcolorbox
    {\@todonotes@currentbordercolor}
    {\@todonotes@currentbackgroundcolor}
    {\arabic{@todonotes@numberoftodonotes}}
\marginpar{\@todonotes@drawMarginNote}
}

\renewcommand{\@todonotes@drawInlineNote}{%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \if@todonotes@authorgiven%
        {\@todonotes@author:\,}%
        \fi%
        \@todonotes@text%
    }%
}

\renewcommand{\@todonotes@drawMarginNote}{%
    \if@todonotes@authorgiven%
        \@todonotes@author\par%
    \fi%
    \arabic{@todonotes@numberoftodonotes}: %
    \fcolorbox%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \@todonotes@sizecommand%
        \@todonotes@text %
    }%
}%

\renewcommand{\@todonotes@drawLineToRightMargin}{}

\renewcommand{\@todonotes@drawLineToLeftMargin}{}

\renewcommand{\missingfigure}[2][]{%
\setkeys{todonotes}{#1}%
\addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
```

```
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todo\@todo

\RenewDocumentCommand{\@todo}{o m}{%
\begingroup%
\renewcommand*{\phantomsection}{}%
\IfValueTF{#1}{%
    \LWRTODONOTES@orig@todo[#1]{#2}%
}{%
    \LWRTODONOTES@orig@todo{#2}%
}
\endgroup%
}

\fi% \if@todonotes@disabled
```

File 367 **lwarp-topcapt.sty**

§ 464 Package topcapt

Pkg topcapt

topcapt is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{topcapt}[2004/12/11]
```

```
\LetLtxMacro\topcaption\caption
```

File 368 **lwarp-tram.sty**

§ 465 Package tram

Pkg tram

tram is emulated.

⚠ block only

The HTML emulation uses a , which must not appear inside an HTML or an HTML paragraph. For this reason, the tram environment should only be used to contain paragraphs inside a \parbox or minipage. tram should not be used to mark up inline text.

To disable tram, allowing source compatibility with inline uses:

```
\begin{warpHTML}
\renewenvironment{tram}[1][]{}{}
\end{warpHTML}
```

for HTML output:

```
\LWR@ProvidesPackageDrop{tram}[2013/04/04]
```

```
\newenvironment{tram}[1][]%
    {\BlockClass[background:lightgray]{tram}}
    {\endBlockClass}
```

File 369 **lwarp-transparent.sty**

§ 466 Package

transparent

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg transparent

Emulated. \texttransparent works for inline objects. \transparent only works for \includegraphics.

⚠ Not XƎLaTeX!

Note that transparent does not work with XƎLaTeX.

for HTML output:

Discard all options for lwarp-transparent:

```
\LWR@ProvidesPackageDrop{transparent}[2016/05/16]
```

```
\newcommand*{\transparent}[1]{\edef\LWR@opacity{#1}}

\newcommand*{\texttransparent}[2]{%
\begingroup%
\transparent{#1}%
\InlineClass[opacity: #1]{transparent}{#2}%
\endgroup%
}
```

File 370 **lwarp-trimclip.sty**

§ 467 Package

trimclip

Pkg trimclip

trimclip is nullified.

for HTML output:

```
\LWR@ProvidesPackageDrop{trimclip}[2018/04/08]
```

The third argument, the text, is not touched. This allows \bgroup / \egroup, and verbatim content.

```
\csdef{trimbox}{\@ifstar\@gobble\@gobble}
\csletcs{trimbox*}{trimbox}
\def\endtrimbox{}
\csletcs{endtrimbox*}{endtrimbox}

\csletcs{clipbox}{trimbox}
\csletcs{clipbox*}{trimbox}
\csletcs{endclipbox}{endtrimbox}
\csletcs{endclipbox*}{endtrimbox}

```

```
\csletcs{marginbox}{trimbox}
\csletcs{marginbox*}{trimbox}
\csletcs{endmarginbox}{endtrimbox}
\csletcs{endmarginbox*}{endtrimbox}
```

File 371 **lwarp-trivfloat.sty**

§ 468 Package

trivfloat

(*Emulates or patches code by* Joseph Wright.)

Pkg `trivfloat` trivfloat is forced to use the built-in lwarp emulation for floats.

To create a new float type and change its name:

```
\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}
```

Discard all options for lwarp-trivfloat. This tells trivfloat not to use floatrow or memoir.

```
\LWR@ProvidesPackageDrop{trivfloat}[2009/04/23]
\LWR@origRequirePackage{trivfloat}
```

`\tfl@chapter@fix` Nullified at the beginning of the document. Is used by trivfloat to correct float chapter numbers, but is not needed for lwarp.

for HTML output:

```
\begin{warpHTML}
```

```
\AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{}}
```

```
\end{warpHTML}
```

§ 468.1 Combining `\newfloat`, `\trivfloat`, and algorithmicx

for HTML & PRINT:

```
\begin{warpall}
```

For both print and HTML output:

⚠ When using float, trivfloat, or algorithmicx at the same time, be aware of conflicting file usage. algorithmicx uses `.loa`. trivfloat by default starts with `.loa` and goes up for additional floats, skipping `.lof` and `.lot`.

⚠ When using `\newfloat`, be sure to manually assign higher letters to the `\newfloat` files to avoid `.loa` used by algorithmicx, and any files used by trivfloat. Also avoid using `.lof` and `.lot`.

⚠ When using `\trivfloat`, you may force it to avoid conflicting with algorithmicx by starting trivfloat's file extensions with `.lob`:

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
```

```
\end{warpall}
```

File 372 **lwarp-truncate.sty**

§ 469 Package truncate

Pkg truncate truncate is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{truncate}[2001/08/20]
```

```
\providecommand{\TruncateMarker}{}
\newcommand{\truncate}[3][\TruncateMarker]{#3}
```

File 373 **lwarp-turnthepage.sty**

§ 470 Package turnthepage

Pkg turnthepage turnthepage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{turnthepage}[2011/03/24]
```

```
\newcommand{\turnthepage}{}
```

File 374 **lwarp-twoup.sty**

§ 471 Package twoup

Pkg twoup twoup is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{twoup}[2007/02/26]
```

```
\newcommand{\cleartolastpage}{}
```

File 375 **lwarp-typearea.sty**

§ 472 Package typearea

(*Emulates or patches code by* Markus Kohm.)

Pkg typearea typearea is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{typearea}[2018/03/30]
```

```
\DeclareDocumentCommand{\typearea}{o m}{}
\DeclareDocumentCommand{\recalctypearea}{}{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\areaset}{o m m}{}
\DeclareDocumentCommand{\activateareas}{}{}
\DeclareDocumentCommand{\storeareas}{m}{}
\DeclareDocumentCommand{\BeforeRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterCalculatingTypearea}{s m}{}
\DeclareDocumentCommand{\AfterSettingArea}{s m}{}
```

File 376 **lwarp-typicons.sty**

§ 473 Package typicons

(*Emulates or patches code by* Arthur Vigil, Xavier Danaux.)

Pkg typicons typicons is patched for use by lwarp.

If \ticon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{typicons}[2015/05/20]
```

```
\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@orig@typicon@TI\TI

\newcommand*{\LWR@typicon@symbol}[1]{%
    \begin{lateximage}*[(typicon)][typicon#1]%
    \begingroup%
    \LWR@orig@typicon@TI%
    \LWR@orig@symbol{#1}%
    \endgroup%
```

```
    \end{lateximage}%
}

\renewcommand*{\TI}{%
    \LetLtxMacro\symbol\LWR@typicon@symbol%
}

\renewcommand*{\ticon}[1]
{%
    \begin{lateximage}*[(#1 icon)][typicon#1]%
    \TI\csname ticon@#1\endcsname%
    \end{lateximage}%
}
```

File 377 **lwarp-ulem.sty**

§ 474 Package

ulem

(*Emulates or patches code by* Donald Arseneau.)

Pkg ulem Patched for use by lwarp.

for HTML output: Use the original package:

```
\LWR@ProvidesPackagePass{ulem}[2012/05/18]
```

Basic markup commands, using css:

```
\NewDocumentCommand{\LWR@HTML@uline}{+m}{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {uline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uline}

\NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:double%
        )%
        {uuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uuline}

\NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:wavy%
        )%
        {uwave}{\LWR@isolate{#1}}%
}
```

```
\LWR@formatted{uwave}

\NewDocumentCommand{\LWR@HTML@sout}{+m}{%
    \InlineClass%
        (text-decoration:line-through)%
        {sout}{\LWR@isolate{#1}}%
}
\LWR@formatted{sout}

\NewDocumentCommand{\LWR@HTML@xout}{+m}{%
    \InlineClass%
        (text-decoration:line-through)%
        {xout}{\LWR@isolate{#1}}%
}

\NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style:dashed%
        )%
        {dashuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{xout}

\NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style: dotted%
        )%
        {dotuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{dotuline}
```

Nullified/emulated macros:

```
\NewDocumentCommand{\LWR@HTML@markoverwith}{m}{}
\LWR@formatted{markoverwith}

\NewDocumentCommand{\LWR@HTML@ULon}{+m}{\uline{#1}\egroup}
\LWR@formatted{ULon}
```

File 378 **lwarp-umoline.sty**

§ 475 Package umoline

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg umoline umoline is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{umoline}[2000/07/11]

\newcommand*{\LWR@HTML@Underline}[1]{%
    \InlineClass{uline}{#1}%
}
\LWR@formatted{Underline}

\newcommand*{\LWR@HTML@Midline}[1]{%
    \InlineClass{sout}{#1}%
}
\LWR@formatted{Midline}

\newcommand*{\LWR@HTML@Overline}[1]{%
    \InlineClass{oline}{#1}%
}
\LWR@formatted{Overline}

\newcommand*{\LWR@HTML@UMOline}[2]{%
    \InlineClass{uline}{#2}%
}
\LWR@formatted{UMOline}

\NewDocumentCommand{\LWR@HTML@UMOspace}{s m o}{\hspace*{#2}}
\LWR@formatted{UMOspace}

\NewDocumentCommand{\LWR@HTML@UMOnewline}{s}{\newline}
\LWR@formatted{UMOnewline}
```

File 379 **lwarp-underscore.sty**

§ 476 Package underscore

Pkg underscore underscore is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{underscore}[2006/09/13]
```

File 380 **lwarp-units.sty**

§ 477 Package units

(*Emulates or patches code by* Axel Reichert.)

Pkg units units is patched for use by lwarp.

Values are not styled by CSS, and take the style of the surrounding HTML text.

Units are styled according to the print version, so they will be forced to upright roman in HTML if the print version does so. It may be necessary to adjust the document's body CSS to match the print version.

for HTML output:

```
\LWR@ProvidesPackagePass{units}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@unit}[2][]{%
\ifblank{#1}%
    {\LWR@textcurrentfont{#2}}%
    {%
        #1%
        \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
        \LWR@textcurrentfont{#2}%
    }%
}
\LWR@formatted{unit}

\DeclareRobustCommand*{\LWR@HTML@unitfrac}[3][]{%
\ifblank{#1}%
    {%
            \nicefrac{#2}{#3}%
    }%
    {%
            #1%
            \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
            \nicefrac{#2}{#3}%
    }%
}

\LWR@formatted{unitfrac}
```

For Mathjax:

```
\CustomizeMathJax{\newcommand{\unit}[2][]{#1 #2}}
\CustomizeMathJax{\newcommand{\unitfrac}[3][]{#1 #2/#3}}
```

File 381 **lwarp-unitsdef.sty**

§ 478 Package unitsdef

(*Emulates or patches code by* Patrick Happel.)

Pkg unitsdef unitsdef is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{unitsdef}[2005/01/04]

\renewcommand{\unitvaluesep}{\,}

\renewcommand{\unittimes}{\@@setunitsepfalse\HTMLunicode{22c5}}% \cdot

\renewunit{\arcmin}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^\prime}}%
        {\HTMLunicode{2032}}% prime
}

```

```
\renewunit{\arcsec}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^{\prime\prime}}}%
        {\HTMLunicode{2033}}% dbl prime
}

\renewrobustcmd{\SI}[2]{%
  \begingroup%
    \let\unit@@xspace\relax%
    \unitSIdef\selectfont%
      \LWR@textcurrentfont{#1#2}% lwarp
  \endgroup%
}
```

File 382 **lwarp-upref.sty**

§ 479 Package upref

Pkg upref Ignored.

for HTML output: Discard all options for lwarp-upref:

```
\LWR@ProvidesPackageDrop{upref}[2007/03/14]
```

File 383 **lwarp-url.sty**

§ 480 Package url

(*Emulates or patches code by* Donald Arseneau.)

Pkg url url is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{url}[2013/09/16]
```

url uses math mode to print its string inside a group, so the original meaning of math is restored first.

```
\LetLtxMacro\LWR@url@origUrl@FormatString\Url@FormatString

\renewcommand*{\Url@FormatString}{%
    \InlineClass{verbatim}{%
        \LWR@restoreorigformatting%
        \LWR@url@origUrl@FormatString%
    }%
}
```

File 384 **lwarp-uspace.sty**

§ 481 Package

uspace

Pkg uspace

uspace is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{uspace}[2016/11/06]
```

File 385 **lwarp-verse.sty**

§ 482 Package

verse

(*Emulates or patches code by* Peter Wilson.)

Pkg verse

verse is supported and patched by lwarp.

for HTML output:

Pass all options for lwarp-verse:

```
1 \LWR@ProvidesPackagePass{verse}[2009/09/04]
```

When using verse or memoir, always place a \\ after each line.

\attrib

The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

Env verse

The verse environment will be placed inside a HTML <pre>.

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verse.}
```

At the beginning of the verse environment:

```
\AtBeginEnvironment{verse}
{%
```

Use the original list environment inside a <pre> to attempt to preserve formatting.

```
\LWR@restoreoriglists%
```

Pkg verse
Cls memoir
\flagverse
Len \vleftskip

The verse or memoir packages can place stanza numbers to the left with their \flagverse command. Do not allow them to go into the left margin, which would cause *pdfcrop* to crop the entire page further to the left:

```
\ifdef{\vleftskip}{%
\setlength{\vleftskip}{\HTMLvleftskip}
\setlength{\leftmargini}{\HTMLleftmargini}
}{}
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{verse}%
}
```

After the end of the verse environment, which places the <pre> tag at the regular left margin:

```
\AtEndEnvironment{verse}{%
\leavevmode%
\LWR@afterendverbatim{1}%
}
```

Patch to place poemtitle inside an HTML of class poemtitle:

```
\ifdef{\poemtitle}{
\DeclareDocumentCommand{\@vstypeptitle}{m}{%
   \vspace{\beforepoemtitleskip}%
   {\InlineClass{poemtitle}{\poemtitlefont #1}\par}%
   \vspace{\afterpoemtitleskip}%
 }
}{}

\LWR@traceinfo{Finished patching verse.}
}% AfterEndPreamble
```

File 386 **lwarp-versonotes.sty**

§ 483 Package

versonotes

(*Emulates or patches code by* Norman Gray.)

Pkg versonotes versonotes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{versonotes}[2015/12/08]
```

```
\newcommand{\versonote}[1]{\marginpar{#1}}
\newdimen\versotextwidth
\newdimen\versoleftmargin
\newcommand*{\versolayout}{}
```

File 387 **lwarp-vertbars.sty**

§ 484 Package vertbars

(*Emulates or patches code by* Peter Wilson.)

Pkg vertbars vertbars is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{vertbars}[2010/11/27]
```

```
\newlength{\barwidth}
\setlength{\barwidth}{0.4pt}
\newlength{\barspace}
\setlength{\barspace}{1em}

\newenvironment{vertbar}{
    \LWR@forcenewpage
    \LWR@forceminwidth{\barwidth}
    \begin{BlockClass}[%
        border-left: \LWR@printlength{\LWR@atleastonept} solid black ; %
        padding-left: \LWR@printlength{\barspace}%
    ]{vertbar}
}{
    \end{BlockClass}
}
```

File 388 **lwarp-vmargin.sty**

§ 485 Package vmargin

Pkg vmargin vmargin is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vmargin}[2004/07/15]
```

```
\newcommand*{\LWRVM@customsize}[2]{}
\newcommand*{\setpapersize}[2][]{\ifstrequal{#2}{custom}{\LWRVM@customsize}{}}
\newcommand*{\setmargins}[8]{}
\newcommand*{\setmarginsrb}[8]{}
\newcommand*{\setmargnohf}[4]{}
\newcommand*{\setmargnohfrb}[4]{}
```

```
\newcommand*{\setmarg}[4]{}
\newcommand*{\setmargrb}[4]{}
\newlength{\PaperWidth}
\setlength{\PaperWidth}{8.5in}
\newlength{\PaperHeight}
\setlength{\PaperHeight}{11in}
\newif\ifLandscape
```

File 389 **lwarp-vowel.sty**

§ 486 Package vowel

(*Emulates or patches code by* FUKUI REI.)

Pkg vowel vowel is patched for use by lwarp.

This package has been tested with *pdflatex* and the Type 1 TIPA fonts using the following package load sequence:

```
\usepackage[T3,T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[noenc]{tipa}
\usepackage{vowel}
```

for HTML output:

```
\LWR@ProvidesPackagePass{vowel}[2002/08/08]
```

```
\renewenvironment{vowel}[1][]
    {%
        \begin{lateximage}[(-vowel-~\packagediagramname)]%
        \@vowel[#1]%
    }
    {%
        \@@vowel%
        \end{lateximage}%
    }
```

File 390 **lwarp-vpe.sty**

§ 487 Package vpe

Pkg vpe vpe is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vpe}[2012/04/18]
```

File 391 **lwarp-vwcol.sty**

§ 488 Package

vwcol

(*Emulates or patches code by* Will Robertson.)

Pkg vwcol vwcol is patched for use with lwarp.

The width option is ignored. All vwcol environments adjust to 1–3 equal-width columns, depening on the width of the browser window.

The remaining options are supported, except for lines and maxrecursion.

for HTML output:

```
\LWR@ProvidesPackagePass{vwcol}[2015/02/10]
```

Factored from \vwcol. Each is given a style tag to append to the final style.

\LWR@vwcol@addrule {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addrule}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
      \LWR@printlength{\vwcol@rule} solid \LWR@origpound\LWR@vwcol@rulecolor ; %
    }%
}
```

\LWR@vwcol@addrule {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addgap}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
        \LWR@printlength{\vwcol@sep} ; %
    }%
}
```

Env vwcol {⟨*key/values*⟩}

Redefine the environment to add a HTML style. The style is built depending on the required options.

```
\renewenvironment*{vwcol}[1][]{%
```

New paragraph, and process the options:

```
\par\noindent%
\vwcolsetup{#1}%
```

Begin with no style:

```
\newcommand*{\LWR@vwcolstyle}{}
```

presep and postsep are created with HTML margins:

```
\if@vwcol@presep
```

```
    \appto{\LWR@vwcolstyle}{margin-left: 1em ; padding-left: .5em ; }
\fi
\if@vwcol@postsep
    \appto{\LWR@vwcolstyle}{margin-right: 1em ; padding-right: .5em ; }
\fi
```

sep becomes column-gap:

```
\ifdimgreater{\vwcol@sep}{1sp}{
    \LWR@vwcol@addgap{column-gap}
    \LWR@vwcol@addgap{-moz-column-gap}
    \LWR@vwcol@addgap{-webkit-column-gap}
}{}
```

rule become column-rule, while prerule and postrule become HTML borders:

```
\convertcolorspec{named}{\vwcol@rulecol}{HTML}\LWR@vwcol@rulecolor%
\ifdimgreater{\vwcol@rule}{0pt}{
    \ifdimless{\vwcol@rule}{1pt}{
        \setlength{\vwcol@rule}{1pt}
    }{}
    \LWR@vwcol@addrule{column-rule}
    \LWR@vwcol@addrule{-moz-column-rule}
    \LWR@vwcol@addrule{-webkit-column-rule}
    \if@vwcol@prerule\LWR@vwcol@addrule{border-left}\fi
    \if@vwcol@postrule\LWR@vwcol@addrule{border-right}\fi
}{}
```

Each of the justify options becomes a text-align. Indentation is added where appropriate.

```
\ifdefequal{\vwcol@justify}{\RaggedRight}{
    \appto{\LWR@vwcolstyle}{text-align: left ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
}{}
```

```
\ifdefequal{\vwcol@justify}{\RaggedLeft}{
    \appto{\LWR@vwcolstyle}{text-align: right ; }
}{}
```

```
\ifdefequal{\vwcol@justify}{\Centering}{
    \appto{\LWR@vwcolstyle}{text-align: center ; }
}{}
```

```
\ifdefequal{\vwcol@justify}{\justifying}{
    \appto{\LWR@vwcolstyle}{text-align: justify ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
}{}
```

Create the with the assembled style:

```
\BlockClass[\LWR@vwcolstyle]{multicols}
```

```
}
```

When the environment ends:

```
{
\endBlockClass
}
```

File 392 **lwarp-wallpaper.sty**

§ 489 Package

wallpaper

(*Emulates or patches code by* Michael H.F. Wilkinson.)

Pkg wallpaper wallpaper is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{wallpaper}[2005/01/18]
```

```
\newcommand*{\CenterWallPaper}[2]{}
\newcommand*{\ThisCenterWallPaper}[2]{}
\newcommand*{\TileWallPaper}[3]{}
\newcommand*{\ThisTileWallPaper}[3]{}
\newcommand*{\TileSquareWallPaper}[2]{}
\newcommand*{\ThisTileSquareWallPaper}[2]{}
\newcommand*{\ULCornerWallPaper}[2]{}
\newcommand*{\ThisULCornerWallPaper}[2]{}
\newcommand*{\LLCornerWallPaper}[2]{}
\newcommand*{\ThisLLCornerWallPaper}[2]{}
\newcommand*{\URCornerWallPaper}[2]{}
\newcommand*{\ThisURCornerWallPaper}[2]{}
\newcommand*{\LRCornerWallPaper}[2]{}
\newcommand*{\ThisLRCornerWallPaper}[2]{}
\newcommand*{\ClearWallPaper}{}
\newlength{\wpXoffset}
\newlength{\wpYoffset}
```

File 393 **lwarp-watermark.sty**

§ 490 Package

watermark

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg watermark watermark is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{watermark}[2004/12/09]
```

```
\newcommand{\watermark}[1]{}
\newcommand{\leftwatermark}[1]{}
\newcommand{\rightwatermark}[1]{}
\newcommand{\thiswatermark}[1]{}
\newcommand{\thispageheading}[1]{}
```

File 394 **lwarp-widows-and-orphans.sty**

§ 491 Package widows-and-orphans

Pkg widows-and-orphans widows-and-orphans is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{widows-and-orphans}[2018/09/01]

\NewDocumentCommand\WaOsetup{m}{}
\NewDocumentCommand\WaOparameters{}{}
\NewDocumentCommand\WaOignorenext{}{}
```

File 395 **lwarp-wrapfig.sty**

§ 492 Package wrapfig

(*Emulates or patches code by* Donald Arseneau.)

Pkg wrapfig wrapfig is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{wrapfig}[2003/01/31]

\newcommand*{\LWR@wrapposition}{}

\newcommand*{\LWR@subwrapfigure}[2]{%
\renewcommand*{\LWR@wrapposition}{}%
\ifthenelse{%
    \equal{#1}{r}\OR\equal{#1}{R}\OR%
    \equal{#1}{o}\OR\equal{#1}{O}%
}%
    {\renewcommand*{\LWR@wrapposition}{float:right}}%
    {\renewcommand*{\LWR@wrapposition}{float:left}}%
\setlength{\LWR@templengthone}{#2}%
\LWR@BlockClassWP{%
    width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
    margin:10pt%
}%
{%
    width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition%
}%
{marginblock}%
}


\NewDocumentEnvironment{wrapfigure}{o m o m}
{%
\LWR@subwrapfigure{#2}{#4}%
\captionsetup{type=figure}%
```

```
}
{%
\endLWR@BlockClassWP%
}


\NewDocumentEnvironment{wraptable}{o m o m}
{%
\LWR@subwrapfigure{#2}{#4}%
\captionsetup{type=table}%
}
{%
\endLWR@BlockClassWP%
}


\NewDocumentEnvironment{wrapfloat}{m o m o m}
{%
\LWR@subwrapfigure{#3}{#5}%
\captionsetup{type=#1}%
}
{%
\endLWR@BlockClassWP%
}

\newlength{\wrapoverhang}
```

File 396 **lwarp-xbmks.sty**

§ 493 Package xbmks

Pkg xbmks xbmks is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xbmks}[2018/07/04]

\newcommand{\xbmksetup}[1]{}
\NewDocumentCommand{\pdfbookmarkx}{o m o m}{}
\NewDocumentCommand{\currentpdfbookmarkx}{m o m}{}
\NewDocumentCommand{\subpdfbookmarkx}{m o m}{}
\NewDocumentCommand{\belowpdfbookmarkx}{m o m}{}
```

File 397 **lwarp-xcolor.sty**

§ 494 Package xcolor

(*Emulates or patches code by* Dr. Uwe Kern.)

Pkg xcolor xcolor is supported by lwarp.

§ 494.1 Limitations

\colorboxBlock and \fcolorboxBlock

\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a instead of a . These s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none

\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes required.

colored tables

\rowcolors is supported, except that the optional argument is ignored so far.

colored text and boxes

\textcolor, \colorbox, and \fcolorbox are supported.

\color and \pagecolor

\color and \pagecolor are ignored. Use CSS or \textcolor where possible.

§ 494.2 xcolor definitions: location and timing

The lwarp core and its lwarp-xcolor package are tightly integrated to allow comparable results for print, HTML, and print inside an HTML lateximage. This requires a number of definitions and redefintions depending on whether each of xcolor and lateximage is being used, and whether print or HTML is being generated. Some of these actions are one-time when xcolor is loaded, and others are temporary as lateximage is used.

When xcolor is loaded in print mode: No special actions are taken at the time that xcolor is loaded in print mode, but see \AtBeginDocument below.

When lwarp-xcolor is loaded in HTML mode: xcolor's original definitions are saved for later restoration. \LWR@restoreorigformatting is appended to restore these definitions for use inside a lateximage. New HTML-mode definitions are created for \textcolor, \pagecolor, \nopagecolor, \colorbox, \colorboxBlock, \fcolorbox, \fcolorboxBlock, and fcolorminipage.

\AtBeginDocument in print or HTML mode: See Section 84. If xcolor has been loaded, the print-mode \fcolorbox is modified to accept a background color of none, and additional definitions are created for lwarp's new macros print-mode macros \colorboxBlock, \fcolorboxBlock, and fcolorminipage. The HTML versions of these macros will already have been created by lwarp-xcolor if it has been loaded.

For use inside an HTML lateximage, \LWR@restoreorigformatting is appended to temporarily set these functions to their print-mode versions.

In a lateximage in HTML mode: \LWR@restoreorigformatting temporarily restores the print-mode definitions of xcolor's functions. See \LWR@restoreorigformatting on page 490.

\color:

Print: Used as-is.

HTML: Ignored by *pdftotext*, and will not appear.

HTML lateximage: Colors will appear in a `lateximage`.

`\textcolor`:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 961.

HTML lateximage: Remembers and reuses the print version.

`\pagecolor`:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a `lateximage`.

`\nopagecolor`:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a `lateximage`.

`\colorbox`:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 961.

HTML lateximage: Remembers and reuses the print version.

`\colorboxBlock`:

Print: Becomes `\colorbox`.

HTML: Newly defined by lwarp-xcolor to use a `<div>`, page 962.

HTML lateximage: Remembers and reuses the print version `\colorbox`.

`\fcolorbox`:

Print: Modified to allow a background of `none`.
`\LWR@print@fcolorbox` at section 84

HTML: Redefined by lwarp-xcolor, page 962.

HTML lateximage: Remembers and reuses the print version.

`\fcolorboxBlock`:

Print: Becomes `\fcolorbox`. Section 84

HTML: Newly defined by lwarp-xcolor to use a `<div>`, page 963.

HTML lateximage: Remembers and reuses the print version `\fcolorbox`.

`fcolorminipage`:

Print: Newly defined in the lwarp core.
`LWR@print@fcolorminipage` at section 84

HTML: Newly defined by lwarp-xcolor, page 964.

HTML lateximage: Uses the print version.

\boxframe:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 965.

HTML lateximage: Remembers and reuses the print version.

§ 494.3 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{xcolor}[2016/05/11]
```

```
\begin{warpHTML}
```

§ 494.4 Remembering and restoring original definitions

Remember the following print-mode actions to be restored when inside a lateximage environment:

```
\LetLtxMacro\LWR@print@pagecolor\pagecolor
\LetLtxMacro\LWR@print@nopagecolor\nopagecolor
```

\LWR@restoreorigformatting

Inside a lateximage the following gets restored to their print-mode actions:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\pagecolor\LWR@print@pagecolor%
\LetLtxMacro\nopagecolor\LWR@print@nopagecolor%
}
```

§ 494.5 HTML color style

\LWR@findcurrenttextcolor

Sets \LWR@tempcolor to the current color.

```
\renewcommand*{\LWR@findcurrenttextcolor}{%
\protect\colorlet{LWR@current@color}{.}%
\protect\convertcolorspec{named}{LWR@current@color}{HTML}\LWR@tempcolor%
}
```

\LWR@currenttextcolorstyle

Prints a color style for the current color.

```
\newcommand*{\LWR@currenttextcolorstyle}{%
\LWR@findcurrenttextcolor%
\ifdefstring{\LWR@tempcolor}{000000}%
{}%
{color: \LWR@origpound\LWR@tempcolor ; }%
}
```

\LWR@textcurrentcolor

{⟨*text*⟩} Like \textcolor but uses the current \color instead.

```
\DeclareDocumentCommand{\LWR@textcurrentcolor}{m}{%
\begingroup%
```

```
\LWR@FBcancel%
\LWR@findcurrenttextcolor%
\InlineClass[color:\LWR@origpound\LWR@tempcolor]{textcolor}{%
    \renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
    #1%
}%
\endgroup%
}
```

\LWR@colorstyle {⟨*2: model*⟩} {⟨*3: color*⟩}

For a color style, prints the color converted to HTML colors.

```
\NewDocumentCommand{\LWR@colorstyle}{m m}{%
\begingroup%
\LWR@FBcancel%
```

Use the xcolor package to convert to an HTML color space:

```
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```
\LWR@origpound\LWR@tempcolor%
\endgroup%
}
```

\LWR@backgroundcolor [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Similar to \textcolor, but prints black text against a color background.

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@backgroundcolor}{O{named} m m}{%
\begingroup%
\LWR@FBcancel%
\InlineClass[background:\LWR@colorstyle{#1}{#2}]{backgroundcolor}{%
#3%
}%
\endgroup%
}
```

§ 494.6 HTML border

\LWR@borderpadding {⟨*colorstyle*⟩} {⟨*color*⟩} Prints the HTML attributes for a black border and padding. \LWR@forceminwidth must be used first in order to set the border width.

```
\newcommand*{\LWR@borderpadding}[2]{%
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
}
```

§ 494.7 High-level macros

\textcolor [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@HTML@textcolor}{o m m}{%
\begingroup%
```

Set the PDF color, to be picked up by SVG math if possible.

The print-mode \color command cannot accept the named option with color mixing, but it works with no option at all.

```
\IfValueTF{#1}{%
    \color[#1]{#2}%
}{%
    \color{#2}%
}%

\LWR@FBcancel%
\IfValueTF{#1}{%
\InlineClass[color:\LWR@colorstyle{#1}{#2}]{textcolor}{%
\renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
#3%
}%
}{%
\InlineClass[color:\LWR@colorstyle{named}{#2}]{textcolor}{%
\renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
#3%
}%
}%
\endgroup%
}

\LWR@formatted{textcolor}
```

\pagecolor [⟨*model*⟩] {⟨*color*⟩}

Ignored. Use CSS instead.

```
\renewcommand*{\pagecolor}[2][named]{}
```

\nopagecolor Ignored.

```
\renewcommand*{\nopagecolor}{}
```

\colorbox [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex background color .

```
\NewDocumentCommand{\LWR@HTML@colorbox}{O{named} m +m}{%
\begingroup%
\LWR@FBcancel%
\InlineClass[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorbox}{#3}%
\endgroup%
}

\AtBeginDocument{
\LWR@formatted{colorbox}
}
```

\colorboxBlock [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex background color `<div>`.

```
\NewDocumentCommand{\LWR@HTML@colorboxBlock}{O{named} m +m}{%
\begingroup%
\LWR@FBcancel%

\LWR@stoppars%

\begin{BlockClass}[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorboxBlock}
#3
\end{BlockClass}%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
\LWR@formatted{colorboxBlock}
}
```

\fcolorbox [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

Converted into a framed HTML hex background color span.

A background color of `none` creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorbox}{O{named} m O{named} m +m}{%
\LWR@traceinfo{HTML fcolorbox #2 #4}%
\begingroup%
```

```
\LWR@FBcancel%
\LWR@forceminwidth{\fboxrule}%
\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2}%
        ]{fcolorbox}{#5}%
    }%
    {% yes background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2} ; %
        background:\LWR@colorstyle{#3}{#4}%
        ]{fcolorbox}{#5}%
    }%
\endgroup%
}

\AtBeginDocument{
\LWR@formatted{fcolorbox}
}
```

\fcolorboxBlock [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorboxBlock}{O{named} m O{named} m +m}{%
\LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
\begingroup%
\LWR@FBcancel%
\LWR@forceminwidth{\fboxrule}%
```

```
\LWR@stoppars%
```

```
\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \begin{BlockClass}[%
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
        \end{BlockClass}%
    }%
    {% yes background color
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \begin{BlockClass}[%
            background:\LWR@origpound\LWR@tempcolortwo\ ; %
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
        \end{BlockClass}%
    }%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{HTML fcolorboxBlock done}%
}

\AtBeginDocument{
\LWR@formatted{fcolorboxBlock}
}
```

Creates a framed HTML around its contents.

A print-output version is defined in the lwarp core: section 84

\LWR@subfcolorminipage {⟨*framemodel*⟩} {⟨*framecolor*⟩} {⟨*background tag*⟩} {⟨*height*⟩}

```
\NewDocumentCommand{\LWR@subfcolorminipage}{m m m m}{%
\LWR@stoppars%
\begin{BlockClass}[%
#3%
\LWR@borderpadding{#1}{#2} ; %
\IfValueT{#4}{height:\LWR@printlength{\LWR@tempheight} ; }%
width:\LWR@printlength{\LWR@tempwidth}%
]{fcolorminipage}%
}
```

Env fcolorminipage [⟨*1:framemodel*⟩] {⟨*2:framecolor*⟩} [⟨*3:boxmodel*⟩] {⟨*4:boxcolor*⟩} [⟨*5:align*⟩] [⟨*6:height*⟩] [⟨*7:inner-align*⟩] {⟨*8:width*⟩}

```
\NewDocumentEnvironment{LWR@HTML@fcolorminipage}{O{named} m O{named} m O{c} o o m}
{%
\LWR@FBcancel%
\setlength{\LWR@tempwidth}{#8}%
\IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
\LWR@forceminwidth{\fboxrule}%
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
\ifthenelse{\equal{#4}{none}}%
    {\LWR@subfcolorminipage{#1}{#2}{}{#6}}%
    {%
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \LWR@subfcolorminipage{#1}{#2}%
            {background:\LWR@origpound\LWR@tempcolortwo\ ; }%
            {#6}%
    }%
}%
{%
    \end{BlockClass}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
    \global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
\LWR@formattedenv{fcolorminipage}
}
```

\boxframe {⟨*width*⟩} {⟨*height*⟩} {⟨*depth*⟩}

The depth is added to the height, but the box is not decended below by the depth. \textcolor is honored.

```
\newcommand*{\LWR@HTML@boxframe}[3]{%
{%
\setlength{\LWR@tempwidth}{#1}%
\setlength{\LWR@tempheight}{#2}%
\addtolength{\LWR@tempheight}{#3}%
\LWR@forceminwidth{\fboxrule}%
\LWR@findcurrenttextcolor%
\InlineClass[%
display:inline-block ; %
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@currenttextcolor{} ; %
width:\LWR@printlength{\LWR@tempwidth} ; %
height:\LWR@printlength{\LWR@tempheight}%
]{boxframe}{}%
}%
}

\LWR@formatted{boxframe}
```

§ 494.8 Row colors

\rowc@l@rs [⟨*cmds*⟩] {⟨*startrow*⟩} {⟨*odd color*⟩} {⟨*even color*⟩}

```
\newcommand*{\LWR@xcolortempcolor}{}

\def\rowc@l@rs[#1]#2#3#4%
{
\global\rownum=1
   \global\@rowcolorstrue
   \@ifxempty{#3}%
     {\def\@oddrowcolor{\@norowcolor}}%
     {%
        \convertcolorspec{named}{#3}{HTML}\LWR@xcolortempcolor%
        \edef\@oddrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
        }%
     }%
   \@ifxempty{#4}%
     {\def\@evenrowcolor{\@norowcolor}}%
     {%
        \convertcolorspec{named}{#4}{HTML}\LWR@xcolortempcolor%
        \edef\@evenrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
```

```
        }%
      }%
    \if@rowcmd
      \def\@rowcolors
      {%
%         #1%
        \if@rowcolors
%         \noalign{%
            \relax\ifnum\rownum<#2\@norowcolor\else
            \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi\fi%
%          }%
        \fi%
      }%
    \else
      \def\@rowcolors
      {%
        \if@rowcolors
            \ifnum\rownum<#2%
%            \noalign{%
                \@norowcolor
%             }
            \else
%            #1%
%            \noalign{%
                \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi%
%             }%
            \fi
        \fi%
      }%
    \fi
    \ignorespaces%
}
```

`\@norowcolor` Turns off color for this row.

```
\def\@norowcolor{%
\renewcommand{\LWR@xcolorrowHTMLcolor}{}%
}
```

`\@rowc@lors` Executed at the end of each row.

```
\def\@rowc@lors{%
%   \noalign{%
        \global\advance\rownum\@ne%
%   }%
    \@rowcolors%
}
```

```
\end{warpHTML}
```

File 398 **lwarp-xechangebar.sty**

§ 495 Package xechangebar

Pkg xechangebar xechangebar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xechangebar}[2017/08/03]
\LWR@origRequirePackage{lwarp-changebar}
```

File 399 **lwarp-xellipsis.sty**

§ 496 Package xellipsis

(*Emulates or patches code by* Donald P. Goodman III.)

Pkg xellipsis xellipsis is patched for use by lwarp.

When non-zero, each of the spaces is converted to an HTML thin unbreakable space.

for HTML output:

```
\LWR@ProvidesPackagePass{xellipsis}[2015/11/01]
```

```
\newcommand*{\LWR@xellipsespace}[1]{%
\ifdim#1=0pt\else%
    \ifdim#1<\fontdimen2\font%
        \,%
    \else%
        ~%
    \fi%
\fi%
}

\def\xelip{%
\mbox{%
    \LWR@xellipsespace{\xelipprebef}%
    \xelipprechar%
    \LWR@xellipsespace{\xelippreaft}%
    \LWR@xellipsespace{\xelipbef}%
    \xelipchar%
    \xel@loopi = 1%
    \loop\ifnum\xelipnum>\xel@loopi%
        \advance\xel@loopi by1%
        \LWR@xellipsespace{\xelipgap}%
        \xelipchar%
    \repeat%
    \LWR@xellipsespace{\xelipaft}%
    \LWR@xellipsespace{\xelippostbef}%
    \xelippostchar%
    \LWR@xellipsespace{\xelippostaft}%
```

```
}%
}%
```

File 400 **lwarp-xetexko-vertical.sty**

§ 497 Package

xetexko-vertical

(*Emulates or patches code by* Dohyun Kim.)

Pkg xetexko-vertical xetexko-vertical is patched for use by lwarp.

for HTML output:

```
\LWR@loadbefore{xetexko-vertical}

\LWR@ProvidesPackagePass{xetexko-vertical}[2018/04/06]

\renewcommand{\verticaltypesetting}{}
\renewenvironment{vertical}[1]{\BlockClass{verticalrl}}{\endBlockClass}
\renewenvironment{horizontal}[1]{\BlockClass{horizontaltb}}{\endBlockClass}
\renewcommand{\vertlatin}[1]{#1}
```

File 401 **lwarp-xfakebold.sty**

§ 498 Package

xfakebold

(*Emulates or patches code by* Herbert Voss.)

Pkg xfakebold xfakebold is patched for use by lwarp, and additional underlying support is found in the lwarp core.

⚠ page breaks Note that the print version resets to unbold at each page break, whereas the HTML version maintains the bold state until it is undone.

for HTML output:

```
\LWR@ProvidesPackagePass{xfakebold}[2018/07/25]

\let\LWR@orig@setBold\setBold
\let\LWR@orig@unsetBold\unsetBold
\renewcommand*{\setBold}{\booltrue{LWR@xfakebold}}
\renewcommand*{\unsetBold}{\boolfalse{LWR@xfakebold}}

\renewcommand*{\LWR@applyxfakebold}{%
    \ifbool{LWR@xfakebold}{\LWR@orig@setBold}{\LWR@orig@unsetBold}%
}
```

File 402 **lwarp-xfrac.sty**

§ 499 Package

xfrac

(*Emulates or patches code by* The LaTeX3 Project.)

Pkg xfrac Supported by adding xfrac instances.

for HTML output:

```
\LWR@ProvidesPackagePass{xfrac}[2018-08-23]
```

⚠ font size In the user's document preamble, lwarp should be loaded after font-related setup. During HTML conversion, this font is used by lwarp to generate its initial PDF output containing HTML tags, later to be converted by *pdftotext* to a plain text file. While the text may be in any font which *pdftotext* can read, the math is directly converted into SVG images using this same user-selected font. `xfrac` below is set for the Latin Modern (lmr) font. If another font is used, it may be desirable to redefine `\xfracHTMLfontsize` with a different em size.

`\sfrac` [⟨*instance*⟩] {⟨*num*⟩} [⟨*sep*⟩] {⟨*denom*⟩}

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in HTML tags. `\scalebox` is made null inside the numerator and denominator, since the HTML tags should not be scaled, and we do not want to introduce additional HTML tags for scaling.

In math mode, which will appear inside a `lateximage`, no adjustments are necessary.

for HTML & PRINT:

```
\begin{warpall}
```

`\xfracHTMLfontsize` User-redefinable macro which controls the font size of the fraction.

```
\newcommand*{\xfracHTMLfontsize}{.6em}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

instances Instances of xfrac for various font choices:

Produce CSS for a small raised numerator and a small denominator.

Scaling is turned off so that *pdftotext* correctly reads the result.

```
\DeclareInstance{xfrac}{default}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmr}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmss}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmtt}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}
```

```
\end{warpHTML}
```

File 403 **lwarp-xltabular.sty**

§ 500 Package xltabular

(*Emulates or patches code by* Rolf Niepraschk, Herbert Voss.)

Pkg xltabular xltabular is emulated by lwarp.

for HTML output: Relies on tabularx.

⚠ table numbering At present, an `xltabular` without a caption or with only a `\caption*` may be misnumbered in HTML, so it may be necessary to place at the end of the table:

```
\warpHTMLonly{\addtocounter{table}{-1}}
```

```
\RequirePackage{tabularx}

\LWR@ProvidesPackageDrop{xltabular}[2018/05/23]

\DeclareDocumentEnvironment{xltabular}{o m m}
{\longtable{#3}}
{\endlongtable}
```

File 404 **lwarp-xltxtra.sty**

§ 501 Package xltxtra

(*Emulates or patches code by* Will Robertson, Jonathan Kew.)

Pkg xltxtra xltxtra is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xltxtra}[2016/01/21]
```

```
\RequirePackage{realscripts}
\RequirePackage{metalogo}
\newcommand*\TeX@logo@spacing[6]{}

\newcommand*{\vfrac}[2]{%
\textsuperscript{#1}/\textsubscript{#2}%
}

```

```
\newcommand\namedglyph[1]{%
  \@tempcnta=\XeTeXglyphindex "#1"\relax
  \ifnum\@tempcnta>0
    \XeTeXglyph\@tempcnta
  \else
    \xxt@namedglyph@fallback{#1}%
  \fi}

\newcommand\xxt@namedglyph@fallback[1]{[#1]}

\DeclareDocumentCommand{\showhyphens}{m}{}
```

File 405 **lwarp-xmpincl.sty**

§ 502 Package xmpincl

(*Emulates or patches code by* Maarten Sneep.)

Pkg xmpincl Emulated.

for HTML output: Discard all options for lwarp-xmpincl:

```
\LWR@ProvidesPackageDrop{xmpincl}[2008/05/10]
```

```
\newcommand*{\includexmp}[1]{}
```

File 406 **lwarp-xpiano.sty**

§ 503 Package xpiano

(*Emulates or patches code by* Enrico Gregorio.)

Pkg xpiano xpiano is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{xpiano}
```

```
\ExplSyntaxOn
\NewDocumentCommand{\LWR@print@keyboard}{ O{}m }
{
\xpiano_keyboard:nn { #1 } { #2 }
}

\NewDocumentCommand{\LWR@HTML@keyboard}{ O{}m }
{
\begin{lateximage}*
    [(-xpiano-~\packagediagramname{}: \detokenize\expandafter{#2})]
    [\detokenize\expandafter{#1}]
\xpiano_keyboard:nn { #1 } { #2 }
\end{lateximage}
}
```

```
\ExplSyntaxOff

\LWR@formatted{keyboard}
```

File 407 **lwarp-xpinyin.sty**

§ 504 Package

xpinyin

(*Emulates or patches code by* Soben Lee.)

Pkg xpinyin

xpinyin is partly supported. \xpinyin and pinyinscope are nullified, but \pinyin works.

for HTML output:

```
\LWR@ProvidesPackagePass{xpinyin}[2018/01/28]
```

```
\RenewDocumentEnvironment{pinyinscope}{O{}}{}{}

\RenewDocumentCommand{\xpinyin}{s O{} m}{%
    \IfBooleanTF{#1}{#3}{\@firstoftwo#3}%
}

\RenewDocumentCommand{\enablepinyin}{}{}
```

File 408 **lwarp-xtab.sty**

§ 505 Package

xtab

(*Emulates or patches code by* Peter Wilson.)

Pkg xtab

xtab is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xtab}[2011/07/31]
```

⚠ Misplaced alignment tab character &

For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 9.10.1.

⚠ lateximage

supertabular and xtab are not supported inside a lateximage.

```
\newcommand{\LWRXT@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRXT@firsthead{#1}%
}

```

```
\newcommand{\tablehead}[1]{}

\newcommand{\tablelasthead}[1]{}

\newcommand{\notablelasthead}{}

\newcommand{\tabletail}[1]{}

\newcommand{\LWRXT@lasttail}{}

\newcommand{\tablelasttail}[1]{%
    \long\gdef\LWRXT@lasttail{#1}%
}
```

```
\newcommand{\tablecaption}[2][]{%
    \long\gdef\LWRXT@caption{%
        \ifblank{#1}%
            {\caption{#2}}%
            {\caption[#1]{#2}}%
    }%
}

\let\topcaption\tablecaption
\let\bottomcaption\tablecaption
```

```
\newcommand*{\LWRXT@caption}{}

\newcommand*{\shrinkheight}[1]{}

\newcommand*{\xentrystretch}[1]{}

\NewDocumentEnvironment{xtabular}{s o m}
{%
\LWR@traceinfo{xtabular}%
\table%
\LWRXT@caption%
\begin{tabular}{#3}%
\TabularMacro\ifdefvoid{\LWRXT@firsthead}%
{\LWR@getmynexttoken}%
{\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
}%
{%
\ifdefvoid{\LWRXT@lasttail}%
{}%
{%
\TabularMacro\ResumeTabular%
\LWRXT@lasttail%
}%
\end{tabular}%
\endtable%
```

```
\gdef\LWRXT@caption{}%
```

```
\LWR@traceinfo{xtabular done}%
}

\NewDocumentEnvironment{mpxtabular}{s o m}
{\minipage{\linewidth}\xtabular{#3}}
{\endxtabular\endminipage}
```

File 409 **lwarp-xunicode.sty**

§ 506 Package

xunicode

Pkg xunicode

Error if xunicode is loaded after lwarp.

Patch lwarp-xunicode, but also verify that is was loaded before lwarp:

for HTML output:

```
\LWR@loadbefore{xunicode}%

\LWR@ProvidesPackagePass{xunicode}[2011/09/09]
```

\textcircled becomes a span with a rounded border. \providecommand is used to avoid conflict with textcomp.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
    \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{textcircled}
```

Nullify textcomp macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
```

```
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify
```

File 410 **lwarp-xurl.sty**

§ 507 Package xurl

Pkg xurl xurl is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xurl}[2018/06/02]
```

File 411 **lwarp-xy.sty**

§ 508 Package xy

(*Emulates or patches code by* Kristoffer H. Rose, Ross Moore.)

Pkg xy xy is patched for use by lwarp.

⚠ \xypolygon \xypolygon must be used inside the xy environment, or inside \xy ... \endxy.

for HTML output:

```
\LWR@ProvidesPackagePass{xy}[2013/10/06]

\AtBeginDocument{

\preto{\xy}{\begin{lateximage}[(-xy-~\packagediagramname)]}
\appto{\endxy}{\end{lateximage}}

\@ifundefined{xymatrix}{}{
\LetLtxMacro\LWR@origxymatrix\xymatrix

\renewcommand{\xymatrix}[1]{%
\begin{lateximage}[(-xy- xymatrix \packagediagramname)]
\LWR@origxymatrix{#1}
\end{lateximage}
}
}

\@ifundefined{xygraph}{}{
```

```
\LetLtxMacro\LWR@origxygraph\xygraph

\renewcommand{\xygraph}[1]{%
\begin{lateximage}[(-xy- xygraph \packagediagramname)]
\LWR@origxygraph{#1}
\end{lateximage}
}
}

}
```

File 412 **lwarp-zhlineskip.sty**

§ 509 Package

zhlineskip

Pkg zhlineskip

zhlineskip is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{zhlineskip}[2018/11/30]

\newcommand*\SetTextEnvironmentSinglespace[1]{}
\newcommand*\RestoreTextEnvironmentLeading{}
\newcommand*\SetMathEnvironmentSinglespace[1]{}
\newcommand*\RestoreMathEnvironmentLeading{}
```

File 413 **lwarp-zwpagelayout.sty**

§ 510 Package

zwpagelayout

(*Emulates or patches code by* Zdeněk Wagner.)

Pkg zwpagelayout

zwpagelayout is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{zwpagelayout}[2013/01/13]

\def\noBboxes{}
\@onlypreamble\noBboxes

\expandafter\ifx\csname definecolor\endcsname\relax \else
  \definecolor{cmykblack}{cmyk}{0,0,0,1}
  \definecolor{grblack}{gray}{0}
%   \ifzwpl@redefineblack
%     \definecolor{black}{cmyk}{0,0,0,1}\color{black}
%   \fi
  \definecolor{cmykred}{cmyk}{0,1,1,0}
  \definecolor{cmykgreen}{cmyk}{1,0,1,0}
  \definecolor{cmykblue}{cmyk}{1,1,0,0}
  \definecolor{rgbred}{rgb}{1,0,0}
  \definecolor{rgbgreen}{rgb}{0,1,0}
  \definecolor{rgbblue}{rgb}{0,0,1}
```

```
%   \ifzwpl@redefinetocmyk
%     \definecolor{red}{cmyk}{0,1,1,0}
%     \definecolor{green}{cmyk}{1,0,1,0}
%     \definecolor{blue}{cmyk}{1,1,0,0}
%   \fi
\fi

\let\OverprintXeTeXExtGState\relax

\DeclareRobustCommand\SetOverprint{\ignorespaces}
\DeclareRobustCommand\SetKnockout{\ignorespaces}
\DeclareRobustCommand\textoverprint[1]{{\SetOverprint#1}}
\DeclareRobustCommand\textknockout[1]{{\SetKnockout#1}}

\def\SetPDFminorversion#1{}
\@onlypreamble\SetPDFminorversion

\newcommand*\Vcorr{}

\DeclareRobustCommand\vb[1][]{}
\NewDocumentCommand{\NewOddPage}{* o}{}
\NewDocumentCommand{\NewEvenPage}{* o}{}
\def\SetOddPageMessage#{\gdef\ZW@oddwarning}
\def\SetEvenPageMessage#{\gdef\Z@@evenwarning}
\def\ZW@oddwarning{Empty page inserted}\let\ZW@evenwarning\ZW@oddwarning

\def\clap#1{#1}

\def\CropFlap{2in}
\def\CropSpine{1in}
\def\CropXSpine{1in}
\def\CropXtrim{.25in}
\def\CropYtrim{.25in}
\def\UserWidth{5in}
\def\UserLeftMargin{1in}
\def\UserRightMargin{1in}
\def\UserTopMargin{1in}
\def\UserBotMargin{1in}
\def\thePageNumber{\LWR@origpound\,\arabic{page}}
\ifXeTeX
\def\ifcaseZWdriver{\ifcase2}
\else
\def\ifcaseZWdriver{\ifcase1}
\fi
\DeclareRobustCommand\ZWifdriver[2]{}
```

File 414 **lwarp-patch-komascript.sty**

§ 511 Package

patch-komascript

Pkg lwarp-patch-komascript

Patches for komascript classes.

lwarp loads this package when scrbook, scrartcl, or scrreprt classes are detected.

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

`\titlehead`, `\subject`, `\captionformat`, `\figureformat`, and `\tableformat` are not yet emulated.

⚠ Not fully tested! Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

for HTML output:

```
\ProvidesPackage{lwarp-patch-komascript}
```

typearea is emulated.

```
\RequirePackage{lwarp-typearea}
```

tocbasic is emulated.

```
\RequirePackage{lwarp-tocbasic}
```

scrextend patches most of the new macros.

```
\RequirePackage{lwarp-scrextend}
```

Indexing macros, simplified for lwarp:

```
\AtBeginDocument{

\renewcommand*{\idx@heading}{%
  \idx@@heading{\indexname}%
}

\renewenvironment{theindex}{%
  \idx@heading%
  \index@preamble\par\nobreak
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}
{}

\renewcommand*\indexspace{}

}% AtBeginDocument
```

The `\minisec` is placed inside a `<div>` of class `minisec`.

```
\renewcommand*{\minisec}[1]{
\begin{BlockClass}{minisec}
#1
\end{BlockClass}
}
```

The part and chapter preambles are placed as plain text just after each heading.

```
\@ifundefined{setpartpreamble}{}{
\RenewDocumentCommand{\setpartpreamble}{o o +m}{%
\renewcommand{\part@preamble}{#3}%
}
}

\@ifundefined{setchapterpreamble}{}{
\RenewDocumentCommand{\setchapterpreamble}{o o +m}{%
\renewcommand{\chapter@preamble}{#3}%
}
}
```

Simple captions are used in all cases.

```
\LetLtxMacro\captionbelow\caption
\LetLtxMacro\captionabove\caption

\LetLtxMacro\captionofbelow\captionof
\LetLtxMacro\captionofabove\captionof

\RenewDocumentEnvironment{captionbeside}{o m o o o s}
{}
{%
\IfValueTF{#1}%
{\caption[#1]{#2}}%
{\caption{#2}}%
}

\RenewDocumentEnvironment{captionofbeside}{m o m o o o s}
{}
{%
\IfValueTF{#2}%
{\captionof{#1}[#2]{#3}}%
{\captionof{#1}{#3}}%
}

\RenewDocumentCommand{\setcapindent}{s m}{}
\renewcommand*{\setcaphanging}{}
\renewcommand*{\setcapwidth}[2][]{}
\renewcommand*{\setcapdynwidth}[2][]{}
\RenewDocumentCommand{\setcapmargin}{s o m}{}
```

File 415 **lwarp-patch-memoir.sty**

§ 512 Package

patch-memoir

(*Emulates or patches code by* Peter Wilson.)

Pkg `lwarp-patch-memoir` Patches for memoir class.

⚠ Not fully tested! Please send bug reports!

lwarp loads this package when the memoir class is detected.

⚠ options clash

While emulating memoir, lwarp pre-loads a number of packages (section 512.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

`\verbfootnote` is not supported.

`\newfootnoteseries`, etc. are not supported.

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in `\pagenotesubhead` and related macros.

Poem numbering is not supported.

The `verbatim` environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

for HTML output:

```
\ProvidesPackage{lwarp-patch-memoir}
```

§ 512.1 Packages

These are pre-loaded to provide emulation for many of memoir's functions. memoir pretends that abstract, etc. are already loaded, via its "emulated" package mechanism, but lwarp is directly loading the "`lwarp-`" version of each, which happens to avoid memoir's emulation system.

```
\RequirePackage{lwarp-abstract}% req'd
\RequirePackage{lwarp-array}% req'd
\RequirePackage{lwarp-booktabs}% req'd
% \RequirePackage{lwarp-ccaption}% emualated below
\RequirePackage{lwarp-changepage}% req'd
\RequirePackage{lwarp-crop}
\RequirePackage{lwarp-dcolumn}% req'd
\RequirePackage{lwarp-enumerate}% req'd
\RequirePackage{lwarp-epigraph}% req'd
\RequirePackage{lwarp-fancyvrb}% req'd
\RequirePackage{lwarp-footmisc}% req'd
```

```
\RequirePackage{lwarp-framed}% req'd
\RequirePackage{lwarp-hanging}% req'd
\RequirePackage{lwarp-makeidx}% req'd
\DisemulatePackage{moreverb}
\RequirePackage{lwarp-moreverb}
\RequirePackage{lwarp-mparhack}
\RequirePackage{lwarp-needspace}% req'd
\RequirePackage{lwarp-nextpage}% req'd
\RequirePackage{lwarp-pagenote}% req'd
\RequirePackage{lwarp-parskip}
\RequirePackage{lwarp-setspace}% req'd
\RequirePackage{lwarp-showidx}
\RequirePackage{lwarp-subfigure}% red'q
\makeindex
```

subfigure is emulated via subfig, which pre-defines `subfigure` and `subtable`, but memoir does not, so they must be tested for here:

```
\LetLtxMacro\LWR@memorignewsubfloat\newsubfloat
\RenewDocumentCommand{\newsubfloat}{O{} m}{%
    \@ifundefined{c@sub#2}{%
        \LWR@memorignewsubfloat[#1]{#2}%
    }{}%
}

\RequirePackage{lwarp-tabularx}% req'd
\RequirePackage{lwarp-titling}% req'd
% \RequirePackage{lwarp-tocbibind}% not emulated by memoir
\RequirePackage{lwarp-tocloft}% req'd
\RequirePackage{lwarp-verse}% req'd
```

§ 512.2 Preliminary setup

Bypass the memoir package mechanism:

```
\LetLtxMacro\LWR@orig@label\@mem@old@label
```

memoir already set the page size to a default, so it must be forced large for lwarp's use, to avoid tag overflows off the page.

```
\setstocksize{190in}{20in}
\setlrmarginsandblock{2in}{2in}{*}
\setulmarginsandblock{1in}{1in}{*}
```

§ 512.3 Laying out the page

```
\renewcommand*{\stockavi}{}
\renewcommand*{\stockav}{}
\renewcommand*{\stockaiv}{}
\renewcommand*{\stockaiii}{}
\renewcommand*{\stockbvi}{}
\renewcommand*{\stockbv}{}
\renewcommand*{\stockbiv}{}
\renewcommand*{\stockbiii}{}
% \renewcommand*{\stockmetriccrownvo}{}% in docs but not in the package
\renewcommand*{\stockmlargecrownvo}{}
\renewcommand*{\stockmdemyvo}{}
\renewcommand*{\stockmsmallroyalvo}{}
\renewcommand*{\pageavi}{}
\renewcommand*{\pageav}{}
\renewcommand*{\pageaiv}{}
\renewcommand*{\pageaiii}{}
\renewcommand*{\pagebvi}{}
\renewcommand*{\pagebv}{}
\renewcommand*{\pagebiv}{}
\renewcommand*{\pagebiii}{}
% \renewcommand*{\pagemetriccrownvo}{}% in docs but not in the package
\renewcommand*{\pagemlargecrownvo}{}
\renewcommand*{\pagemdemyvo}{}
\renewcommand*{\pagemsmallroyalvo}{}

\renewcommand*{\stockdbill}{}
\renewcommand*{\stockstatement}{}
\renewcommand*{\stockexecutive}{}
\renewcommand*{\stockletter}{}
\renewcommand*{\stockold}{}
\renewcommand*{\stocklegal}{}
\renewcommand*{\stockledger}{}
\renewcommand*{\stockbroadsheet}{}
\renewcommand*{\pagedbill}{}
\renewcommand*{\pagestatement}{}
\renewcommand*{\pageexecutive}{}
\renewcommand*{\pageletter}{}
\renewcommand*{\pageold}{}
\renewcommand*{\pagelegal}{}
\renewcommand*{\pageledger}{}
\renewcommand*{\pagebroadsheet}{}

\renewcommand*{\stockpottvo}{}
\renewcommand*{\stockfoolscapvo}{}
\renewcommand*{\stockcrownvo}{}
\renewcommand*{\stockpostvo}{}
\renewcommand*{\stocklargecrownvo}{}
\renewcommand*{\stocklargepostvo}{}
\renewcommand*{\stocksmalldemyvo}{}
\renewcommand*{\stockdemyvo}{}
\renewcommand*{\stockmediumvo}{}
\renewcommand*{\stocksmallroyalvo}{}
\renewcommand*{\stockroyalvo}{}
\renewcommand*{\stocksuperroyalvo}{}
```

```
\renewcommand*{\stockimperialvo}{}
\renewcommand*{\pagepottvo}{}
\renewcommand*{\pagefoolscapvo}{}
\renewcommand*{\pagecrownvo}{}
\renewcommand*{\pagepostvo}{}
\renewcommand*{\pagelargecrownvo}{}
\renewcommand*{\pagelargepostvo}{}
\renewcommand*{\pagesmalldemyvo}{}
\renewcommand*{\pagedemyvo}{}
\renewcommand*{\pagemediumvo}{}
\renewcommand*{\pagesmallroyalvo}{}
\renewcommand*{\pageroyalvo}{}
\renewcommand*{\pagesuperroyalvo}{}
\renewcommand*{\pageimperialvo}{}

\renewcommand*{\memfontfamily}{}
\renewcommand*{\memfontenc}{}
\renewcommand*{\memfontpack}{}

\renewcommand*{\anyptfilebase}{}
\renewcommand*{\anyptsize}{10}

\renewcommand*{\setstocksize}[2]{}
\renewcommand*{\settrimmedsize}[3]{}
\renewcommand*{\settrims}[2]{}

% \newlength{\lxvchars}
% \setlength{\lxvchars}{305pt}
% \newlength{\xlvchars}
% \setlength{\xlvchars}{190pt}
\renewcommand*{\setxlvchars}[1]{}
\renewcommand*{\setlxvchars}[1]{}

\renewcommand*{\settypeblocksize}[3]{}
\renewcommand*{\setlrmargins}[3]{}
\renewcommand*{\setlrmarginsandblock}[3]{}
\renewcommand*{\setbinding}[1]{}
\renewcommand*{\setulmargins}[3]{}
\renewcommand*{\setulmarginsandblock}[3]{}
\renewcommand*{\setcolsepandrule}[2]{}

\renewcommand*{\setheadfoot}[2]{}
\renewcommand*{\setheaderspaces}[3]{}
\renewcommand*{\setmarginnotes}[3]{}
\renewcommand*{\setfootins}[2]{}
\renewcommand*{\checkandfixthelayout}[1][]{}
\renewcommand*{\checkthelayout}[1]{}
\renewcommand*{\fixthelayout}{}
%
% \newlength{\stockheight}
% \newlength{\trimtop}
% \newlength{\trimedge}
% \newlength{\stockwidth}
% \newlength{\spinemargin}
% \newlength{\foremargin}
```

```
% \newlength{\uppermargin}
% \newlength{\headmargin}
%
\renewcommand*{\typeoutlayout}{}
\renewcommand*{\typeoutstandardlayout}{}
\renewcommand*{\settypeoutlayoutunit}[1]{}
\renewcommand*{\fixpdflayout}{}
\renewcommand*{\fixdvipslayout}{}

\renewcommand*{\medievalpage}[1][]{}
\renewcommand*{\isopage}[1][]{}
\renewcommand*{\semiisopage}[1][]{}

\renewcommand{\setpagebl}[3]{}
\renewcommand{\setpageml}[3]{}
\renewcommand{\setpagetl}[3]{}
\renewcommand{\setpagetm}[3]{}
\renewcommand{\setpagetr}[3]{}
\renewcommand{\setpagemr}[3]{}
\renewcommand{\setpagebr}[3]{}
\renewcommand{\setpagebm}[3]{}
\renewcommand{\setpagecc}[3]{}
```

§ 512.4 Text and fonts

```
\let\miniscule\tiny
\let\HUGE\Huge

\renewcommand*{\abnormalparskip}[1]{}
\renewcommand*{\nonzeroparskip}{}
\renewcommand*{\traditionalparskip}{}

\let\onelineskip\baselineskip

\let\OnehalfSpacing\onehalfspacing
\let\DoubleSpacing\doublespacing
\renewcommand*{\setPagenoteSpacing}[1]{}
\renewcommand*{\setFloatSpacing}[1]{}
\let\SingleSpacing\singlespacing
\let\setSingleSpace\SetSinglespace
\let\SingleSpace\singlespace
\let\endSingleSpace\endsinglespace
\let\Spacing\spacing
\let\endSpacing\endspacing
\let\OnehalfSpace\onehalfspace
\let\endOnehalfSpace\endonehalfspace
\csletcs{OnehalfSpace*}{onehalfspace}
\csletcs{endOnehalfSpace*}{endonehalfspace}
\let\DoubleSpace\doublespace
\let\endDoubleSpace\enddoublespace
\csletcs{DoubleSpace*}{doublespace}
\csletcs{endDoubleSpace*}{enddoublespace}
\renewcommand*{\setDisplayskipStretch}[1]{}
\renewcommand*{\memdskipstretch}{}
\renewcommand*{\noDisplayskipStretch}{}
```

```
\renewcommand*{\memdskips}{}

\renewcommand*{\midsloppy}{}
\renewenvironment*{midsloppypar}{}{}

\renewcommand*{\sloppybottom}{}
```

§ 512.5 Titles

```
\csletcs{titlingpage*}{titlingpage}
\csletcs{endtitlingpage*}{endtitlingpage}
\let\titlingpageend\relax
\newcommand{\titlingpageend}[2]{}
\let\andnext\and
\renewcommand*{\thanksmarkstyle}[1]{}
\renewcommand{\thanksfootmark}{%
\thanksscript{\tamark}%
}

% \newlength{\thanksmarksep}
```

§ 512.6 Abstracts

```
\renewcommand*{\abstractcol}{}
\renewcommand*{\abstractintoc}{}
\renewcommand*{\abstractnum}{}
\renewcommand*{\abstractrunin}{}
```

§ 512.7 Docment divisions

```

\def\@apppage{%
    \part*{\appendixpagename}
}
\renewcommand\mempreaddapppagetotochook{}
\renewcommand\mempostaddapppagetotochook{}

\def\@sapppage{%
    \part*{\appendixpagename}
}

\csletcs{frontmatter*}{frontmatter}
\csletcs{mainmatter*}{mainmatter}
\renewcommand*{\raggedbottomsection}{}
\renewcommand*{\normalbottomsection}{}
\renewcommand*{\bottomsectionskip}{}
\renewcommand*{\bottomsectionpenalty}{}
\csletcs{appendixpage*}{appendixpage}
\renewcommand*{\namedsubappendices}{}
\renewcommand*{\unnamedsubappendices}{}
\renewcommand*{\setsecnumdepth}[1]{}% todo tocvsec2
\renewcommand*{\maxsecnumdepth}[1]{}% todo tocvsec2
\renewcommand*{\beforebookskip}{}
\renewcommand*{\afterbookskip}{}
\renewcommand*{\beforepartskip}{}
```

```
\renewcommand*{\afterpartskip}{}
\renewcommand*{\midbookskip}{}
\renewcommand*{\midpartskip}{}
\renewcommand*{\printbookname}{}
\renewcommand*{\booknamefont}{}
\renewcommand*{\booknamenum}{}
\renewcommand*{\printbooknum}{}
\renewcommand*{\booknumfont}{}
\renewcommand*{\printpartname}{}
\renewcommand*{\partnamefont}{}
\renewcommand*{\partnamenum}{}
\renewcommand*{\printpartnum}{}
\renewcommand*{\partnumfont}{}
\renewcommand*{\printbooktitle}[1]{}
\renewcommand*{\booktitlefont}{}
\renewcommand{\printparttitle}[1]{}
\renewcommand*{\parttitlefont}{}
\renewcommand*{\bookpageend}{}
\renewcommand*{\bookblankpage}{}
\renewcommand*{\nobookblankpage}{}
\renewcommand*{\partpageend}{}
\renewcommand*{\partblankpage}{}
\renewcommand*{\nopartblankpage}{}
\RenewDocumentCommand{\newleadpage}{s o m m}{}% todo
\RenewDocumentCommand{\renewleadpage}{s o m m}{}% todo
\renewcommand*{\leadpagetoclevel}{chapter}

\renewcommand*{\openright}{}
\renewcommand*{\openleft}{}
\renewcommand*{\openany}{}
\renewcommand*{\clearforchapter}{}
\renewcommand*{\memendofchapterhook}{}
\renewcommand*{\chapterheadstart}{}
% \newlength{\beforechapskip}
\renewcommand*{\afterchapternum}{}
% \newlength{\midchapskip}
\renewcommand*{\afterchaptertitle}{}
% \newlength{\afterchapskip}
\renewcommand*{\printchaptername}{}
\renewcommand*{\chapnamefont}{}
\renewcommand*{\chapternamenum}{}
\renewcommand*{\printchapternum}{}
\renewcommand*{\chapnumfont}{}
\renewcommand{\printchaptertitle}[1]{}
\renewcommand*{\chaptitlefont}{}
\renewcommand*{\printchapternonum}{}
\renewcommand*{\indentafterchapter}{}
\renewcommand*{\noindentafterchapter}{}
\renewcommand*{\insertchapterspace}{}

\renewcommand*{\chapterstyle}[1]{}
\renewcommand{\makechapterstyle}[2]{}
\renewcommand*{\chapindent}{}
\let\chapterprecis\cftchapterprecis
\let\chapterprecishere\cftchapterprecishere
```

```
\let\chapterprecistoc\cftchapterprecistoc
\renewcommand*{\precisfont}{}
\renewcommand*{\prechapterprecis}{}
\renewcommand*{\postchapterprecis}{}
\renewcommand{\precistoctext}[1]{}
\renewcommand*{\precistocfont}{}
\renewcommand*{\precistocformat}{}
% \newlength{\prechapterprecisshift}

\renewcommand*{\setbeforesecskip}[1]{}
\renewcommand*{\setaftersecskip}[1]{}
\renewcommand*{\setsecindent}[1]{}
\renewcommand*{\setsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsecskip}[1]{}
\renewcommand*{\setaftersubsecskip}[1]{}
\renewcommand*{\setsubsecindent}[1]{}
\renewcommand*{\setsubsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsubsecskip}[1]{}
\renewcommand*{\setaftersubsubsecskip}[1]{}
\renewcommand*{\setsubsubsecindent}[1]{}
\renewcommand*{\setsubsubsecheadstyle}[1]{}
\renewcommand*{\setbeforeparaskip}[1]{}
\renewcommand*{\setafterparaskip}[1]{}
\renewcommand*{\setparaindent}[1]{}
\renewcommand*{\setparaheadstyle}[1]{}
\renewcommand*{\setbeforesubparaskip}[1]{}
\renewcommand*{\setaftersubparaskip}[1]{}
\renewcommand*{\setsubparaindent}[1]{}
\renewcommand*{\setsubparaheadstyle}[1]{}
\renewcommand{\@hangfrom}[1]{#1}
\renewcommand{\sethangfrom}[1]{}
\renewcommand{\setsecnumformat}[1]{}

\renewcommand*{\hangsecnum}{}
\renewcommand*{\defaultsecnum}{}

\renewcommand*{\sechook}{}
\renewcommand{\setsechook}[1]{}
\renewcommand*{\subsechook}{}
\renewcommand{\setsubsechook}[1]{}
\renewcommand*{\subsubsechook}{}
\renewcommand{\setsubsubsechook}[1]{}
\renewcommand*{\parahook}{}
\renewcommand{\setparahook}[1]{}
\renewcommand*{\subparahook}{}
\renewcommand{\setsubparahook}[1]{}

\RenewDocumentCommand{\plainbreak}{s m}{\begin{center}~\end{center}}

\RenewDocumentCommand{\fancybreak}{s +m}{%
\begin{center}#2\end{center}%
}

\RenewDocumentCommand{\plainfancybreak}{s m m +m}{%
\begin{center}#4\end{center}%
```

```
}

\RenewDocumentCommand{\pfbreak}{s}{%
\begin{center}
\pfbreakdisplay
\end{center}
}

% \newlength{\pfbreakskip}
\renewcommand{\pfbreakdisplay}{*\quad*\quad*}

\renewcommand{\makeheadstyles}[2]{}
\renewcommand*{\headstyles}[1]{}
```

§ 512.8 Pagination and headers

```
\renewcommand*{\savepagenumber}{}
\renewcommand*{\restorepagenumber}{}
\renewcommand*{\uppercaseheads}{}
\renewcommand*{\nouppercaseheads}{}

\renewcommand*{\bookpagemark}[1]{}
\renewcommand*{\partmark}[1]{}
\renewcommand*{\bibmark}{}
\renewcommand*{\indexmark}{}
\renewcommand*{\glossarymark}{}

\LWR@origpagestyle{empty}
\renewcommand*{\ps@empty}{}
\renewcommand*{\makepagestyle}[1]{}
\renewcommand*{\emptypshook}{}%
% \renewcommand*{\empty@oddhead}{}
% \renewcommand*{\empty@oddfoot}{}
% \renewcommand*{\empty@evenhead}{}
% \renewcommand*{\empty@evenfoot}{}
\renewcommand*{\@oddhead}{}
\renewcommand*{\@oddfoot}{}
\renewcommand*{\@evenhead}{}
\renewcommand*{\@evenfoot}{}
\renewcommand*{\aliaspagestyle}[2]{}
\renewcommand*{\copypagestyle}[2]{}

\renewcommand*{\makeevenhead}[4]{}
\renewcommand*{\makeoddhead}[4]{}
\renewcommand*{\makeevenfoot}[4]{}
\renewcommand*{\makeoddfoot}[4]{}
\renewcommand*{\makerunningwidth}[3]{}
% \newlength{\headwidth}
\renewcommand*{\makeheadrule}[3]{}
\renewcommand*{\makefootrule}[3]{}
\renewcommand*{\makeheadfootruleprefix}[3]{}
% \newlength{\normalrulethickness}
% \setlength{\normalrulethickness}{.4pt}
% \newlength{\footruleheight}
% \newlength{\footruleskip}
```

```
\renewcommand*{\makeheadposition}[5]{}
\renewcommand{\makepsmarks}[2]{}
\renewcommand*{\makeheadfootstrut}[3]{}

\renewcommand{\createplainmark}[3]{}
\renewcommand{\memUChead}[1]{}
\renewcommand{\createmark}[5]{}
\renewcommand*{\clearplainmark}[1]{}
\renewcommand*{\clearmark}[1]{}
\renewcommand{\addtopsmarks}[3]{}
\renewcommand{\ifonlyfloats}[2]{#2}
\renewcommand*{\mergepagefloatstyle}[3]{}

\renewcommand*{\framepichead}{}
\renewcommand*{\framepictextfoot}{}
\renewcommand*{\framepichook}{}
\renewcommand*{\showheadfootlocoff}{}
\renewcommand*{\showtextblocklocoff}{}
```

§ 512.9 Paragraphs and lists

```
\renewcommand{\hangfrom}[1]{#1}
\let\centerfloat\centering
\renewcommand*{\raggedyright}[1][]{}
% \newlength{\ragrparindent}
\renewcommand{\sourceatright}[2][]{\attribution{#2}}
\let\memorigdbs\LWR@endofline
\let\memorigpar\par
\let\atcentercr\LWR@endofline

\renewcommand*{\linenottooshort}[1][]{}
\renewcommand*{\russianpar}{}
\renewcommand*{\lastlinerulefill}{}
\renewcommand*{\lastlineparrule}{}
\renewcommand*{\justlastraggedleft}{}
\renewcommand*{\raggedrightthenleft}{}
\renewcommand*{\leftcenterright}{}

\renewcommand{\leftspringright}[4]{%
\begin{minipage}{#1\linewidth}#3\end{minipage}\qquad%
\begin{minipage}{#2\linewidth}\begin{flushright}#4\end{flushright}\end{minipage}%
}

\renewenvironment*{blockdescription}
{\LWR@descriptionstart\LWR@origdescription}
{\enddescription}
\renewcommand*{\blockdescriptionlabel}[1]{\textbf{#1}}
\renewenvironment*{labelled}[1]{\begin{description}}{\end{description}}
\renewenvironment*{flexlabelled}[6]{\begin{description}}{\end{description}}
\renewcommand*{\tightlists}{}
\renewcommand*{\defaultlists}{}
\RenewDocumentCommand{\firmlists}{s}{}
\renewcommand*{\firmlist}{}
\renewcommand*{\tightlist}{}
\renewcommand*{\zerotrivseps}{}
```

```
\renewcommand*{\savetrivseps}{}
\renewcommand*{\restoretrivseps}{}
```

§ 512.10 Contents lists

```
\csletcs{tableofcontents*}{tableofcontents}
\csletcs{listoffigures*}{listoffigures}
\csletcs{listoftables*}{listoftables}
\renewenvironment{KeepFromToc}{}{}
\renewcommand*{\onecoltocetc}{}
\renewcommand*{\twocoltocetc}{}
\renewcommand*{\ensureonecol}{}
\renewcommand*{\restorefromonecol}{}
\renewcommand*{\doccoltocetc}{}
\renewcommand*{\maxtocdepth}[1]{}% tocvsec2
\renewcommand*{\settocdepth}[1]{}% tocvsec2

\renewcommand{\tocheadstart}{}
\renewcommand{\printtoctitle}[1]{}
\renewcommand{\tocmark}{}
\renewcommand{\aftertoctitle}{}
\renewcommand{\lofheadstart}{}
\renewcommand{\printloftitle}[1]{}
\renewcommand{\lofmark}{}
\renewcommand{\afterloftitle}{}
\renewcommand{\lotheadstart}{}
\renewcommand{\printlottitle}[1]{}
\renewcommand{\lotmark}{}
\renewcommand{\afterlottitle}{}

\renewcommand*{\setpnumwidth}[1]{}
\renewcommand*{\setrmarg}[1]{}
\renewcommand*{\cftbookbreak}{}
\renewcommand*{\cftpartbreak}{}
\renewcommand*{\cftchapterbreak}{}
```

```
% \newlength{\cftbeforebookskip}
% \newlength{\cftbookindent}
% \newlength{\cftbooknumwidth}
\renewcommand*{\cftbookfont}{}
\renewcommand*{\cftbookname}{}
\renewcommand*{\cftbookpresnum}{}
\renewcommand*{\cftbookaftersnum}{}
\renewcommand*{\cftbookaftersnumb}{}
\renewcommand*{\cftbookleader}{}
\renewcommand*{\cftbookdotsep}{1}
\renewcommand*{\cftbookpagefont}{}
\renewcommand*{\cftbookafterpnum}{}
\renewcommand*{\cftbookformatpnum}[1]{}
\renewcommand*{\cftbookformatpnumhook}[1]{}
```

Part is already defined by tocloft.

```
% \newlength{\cftbeforechapterskip}
% \newlength{\cftchapterindent}
```

```
% \newlength{\cftchapternumwidth}
\renewcommand*{\cftchapterfont}{}
\renewcommand*{\cftchaptername}{}
\renewcommand*{\cftchapterpresnum}{}
\renewcommand*{\cftchapteraftersnum}{}
\renewcommand*{\cftchapteraftersnumb}{}
\renewcommand*{\cftchapterleader}{}
\renewcommand*{\cftchapterdotsep}{1}
\renewcommand*{\cftchapterpagefont}{}
\renewcommand*{\cftchapterafterpnum}{}
\renewcommand*{\cftchapterformatpnum}[1]{}
\renewcommand*{\cftchapterformatpnumhook}[1]{}
```

```
% \newlength{\cftbeforesectionskip}
% \newlength{\cftsectionindent}
% \newlength{\cftsectionnumwidth}
\renewcommand*{\cftsectionfont}{}
\renewcommand*{\cftsectionname}{}
\renewcommand*{\cftsectionpresnum}{}
\renewcommand*{\cftsectionaftersnum}{}
\renewcommand*{\cftsectionaftersnumb}{}
\renewcommand*{\cftsectionleader}{}
\renewcommand*{\cftsectiondotsep}{1}
\renewcommand*{\cftsectionpagefont}{}
\renewcommand*{\cftsectionafterpnum}{}
\renewcommand*{\cftsectionformatpnum}[1]{}
\renewcommand*{\cftsectionformatpnumhook}[1]{}
```

```
% \newlength{\cftbeforesubsectionskip}
% \newlength{\cftsubsectionindent}
% \newlength{\cftsubsectionnumwidth}
\renewcommand*{\cftsubsectionfont}{}
\renewcommand*{\cftsubsectionname}{}
\renewcommand*{\cftsubsectionpresnum}{}
\renewcommand*{\cftsubsectionaftersnum}{}
\renewcommand*{\cftsubsectionaftersnumb}{}
\renewcommand*{\cftsubsectionleader}{}
\renewcommand*{\cftsubsectiondotsep}{1}
\renewcommand*{\cftsubsectionpagefont}{}
\renewcommand*{\cftsubsectionafterpnum}{}
\renewcommand*{\cftsubsectionformatpnum}[1]{}
\renewcommand*{\cftsubsectionformatpnumhook}[1]{}
```

```
% \newlength{\cftbeforesubsubsectionskip}
% \newlength{\cftsubsubsectionindent}
% \newlength{\cftsubsubsectionnumwidth}
\renewcommand*{\cftsubsubsectionfont}{}
\renewcommand*{\cftsubsubsectionname}{}
\renewcommand*{\cftsubsubsectionpresnum}{}
\renewcommand*{\cftsubsubsectionaftersnum}{}
\renewcommand*{\cftsubsubsectionaftersnumb}{}
\renewcommand*{\cftsubsubsectionleader}{}
\renewcommand*{\cftsubsubsectiondotsep}{1}
\renewcommand*{\cftsubsubsectionpagefont}{}
\renewcommand*{\cftsubsubsectionafterpnum}{}
\renewcommand*{\cftsubsubsectionformatpnum}[1]{}
```

```
\renewcommand*{\cftsubsubsectionformatpnumhook}[1]{}

% \newlength{\cftbeforeparagraphskip}
% \newlength{\cftparagraphindent}
% \newlength{\cftparagraphnumwidth}
\renewcommand*{\cftparagraphfont}{}
\renewcommand*{\cftparagraphname}{}
\renewcommand*{\cftparagraphpresnum}{}
\renewcommand*{\cftparagraphaftersnum}{}
\renewcommand*{\cftparagraphaftersnumb}{}
\renewcommand*{\cftparagraphleader}{}
\renewcommand*{\cftparagraphdotsep}{1}
\renewcommand*{\cftparagraphpagefont}{}
\renewcommand*{\cftparagraphafterpnum}{}
\renewcommand*{\cftparagraphformatpnum}[1]{}
\renewcommand*{\cftparagraphformatpnumhook}[1]{}

% \newlength{\cftbeforesubparagraphskip}
% \newlength{\cftsubparagraphindent}
% \newlength{\cftsubparagraphnumwidth}
\renewcommand*{\cftsubparagraphfont}{}
\renewcommand*{\cftsubparagraphname}{}
\renewcommand*{\cftsubparagraphpresnum}{}
\renewcommand*{\cftsubparagraphaftersnum}{}
\renewcommand*{\cftsubparagraphaftersnumb}{}
\renewcommand*{\cftsubparagraphleader}{}
\renewcommand*{\cftsubparagraphdotsep}{1}
\renewcommand*{\cftsubparagraphpagefont}{}
\renewcommand*{\cftsubparagraphafterpnum}{}
\renewcommand*{\cftsubparagraphformatpnum}[1]{}
\renewcommand*{\cftsubparagraphformatpnumhook}[1]{}

% \newlength{\cftbeforefigureskip}
% \newlength{\cftfigureindent}
% \newlength{\cftfigurenumwidth}
\renewcommand*{\cftfigurefont}{}
\renewcommand*{\cftfigurename}{}
\renewcommand*{\cftfigurepresnum}{}
\renewcommand*{\cftfigureaftersnum}{}
\renewcommand*{\cftfigureaftersnumb}{}
\renewcommand*{\cftfigureleader}{}
\renewcommand*{\cftfiguredotsep}{1}
\renewcommand*{\cftfigurepagefont}{}
\renewcommand*{\cftfigureafterpnum}{}
\renewcommand*{\cftfigureformatpnum}[1]{}
\renewcommand*{\cftfigureformatpnumhook}[1]{}

% \newlength{\cftbeforesubfigureskip}
% \newlength{\cftsubfigureindent}
% \newlength{\cftsubfigurenumwidth}
\newcommand*{\cftsubfigurefont}{}
\newcommand*{\cftsubfigurename}{}
\newcommand*{\cftsubfigurepresnum}{}
\newcommand*{\cftsubfigureaftersnum}{}
\newcommand*{\cftsubfigureaftersnumb}{}
\newcommand*{\cftsubfigureleader}{}
```

```
\newcommand*{\cftsubfiguredotsep}{1}
\newcommand*{\cftsubfigurepagefont}{}
\newcommand*{\cftsubfigureafterpnum}{}
\newcommand*{\cftsubfigureformatpnum}[1]{}
\newcommand*{\cftsubfigureformatpnumhook}[1]{}

% \newlength{\cftbeforetableskip}
% \newlength{\cfttableindent}
% \newlength{\cfttablenumwidth}
\renewcommand*{\cfttablefont}{}
\renewcommand*{\cfttablename}{}
\renewcommand*{\cfttablepresnum}{}
\renewcommand*{\cfttableaftersnum}{}
\renewcommand*{\cfttableaftersnumb}{}
\renewcommand*{\cfttableleader}{}
\renewcommand*{\cfttabledotsep}{1}
\renewcommand*{\cfttablepagefont}{}
\renewcommand*{\cfttableafterpnum}{}
\renewcommand*{\cfttableformatpnum}[1]{}
\renewcommand*{\cfttableformatpnumhook}[1]{}

% \newlength{\cftbeforesubtableskip}
% \newlength{\cftsubtableindent}
% \newlength{\cftsubtablenumwidth}
\newcommand*{\cftsubtablefont}{}
\newcommand*{\cftsubtablename}{}
\newcommand*{\cftsubtablepresnum}{}
\newcommand*{\cftsubtableaftersnum}{}
\newcommand*{\cftsubtableaftersnumb}{}
\newcommand*{\cftsubtableleader}{}
\newcommand*{\cftsubtabledotsep}{1}
\newcommand*{\cftsubtablepagefont}{}
\newcommand*{\cftsubtableafterpnum}{}
\newcommand*{\cftsubtableformatpnum}[1]{}
\newcommand*{\cftsubtableformatpnumhook}[1]{}

\renewcommand*{\booknumberline}[1]{}
\renewcommand*{\partnumberline}[1]{}
\renewcommand*{\chapternumberline}[1]{}
\renewcommand*{\numberlinehook}[1]{}
% \renewcommand*{\cftwhatismyname}{}%
\renewcommand*{\booknumberlinehook}[1]{}
\renewcommand*{\partnumberlinehook}[1]{}
\renewcommand*{\chapternumberlinehook}[1]{}
\renewcommand{\numberlinebox}[2]{}
\renewcommand{\booknumberlinebox}[2]{}
\renewcommand{\partnumberlinebox}[2]{}
\renewcommand{\chapternumberlinebox}[2]{}
%
% \newlength{\cftparfillskip}
\renewcommand*{\cftpagenumbersoff}[1]{}
\renewcommand*{\cftpagenumberson}[1]{}
\renewcommand*{\cftlocalchange}[3]{}
\renewcommand*{\cftaddtitleline}[4]{}
\renewcommand*{\cftaddnumtitleline}[4]{}
\renewcommand{\cftinsertcode}[2]{}
```

```
\renewcommand{\cftinserthook}[2]{}
\renewcommand{\settocpreprocessor}[2]{}
\DeclareRobustCommand{\cftpagenumbersoff}[1]{}
\DeclareRobustCommand{\cftpagenumberson}[1]{}
```

§ 512.11 Floats and captions

\newfloat [⟨*1: within*⟩] {⟨*2: type*⟩} {⟨*3: ext*⟩} {⟨*4: capname*⟩}

```
\RenewDocumentCommand{\newfloat}{o m m m}{%
\IfValueTF{#1}%
{\DeclareFloatingEnvironment[fileext=#3,within=#1,name={#4}]{#2}}%
{\DeclareFloatingEnvironment[fileext=#3,name={#4}]{#2}}%
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later.

```
\cslet{listof#2s}\relax%
\cslet{listof#2es}\relax%
}
```

\newlistof [⟨*within*⟩] {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the \newfloat mechanism. Note that memoir uses a different syntax than tocloft for the name.

```
\RenewDocumentCommand{\newlistof}{o m m m}
{%
\IfValueTF{#1}
{\newlistentry[#1]{#2}{#3}{0}}
{\newlistentry{#2}{#3}{0}}
\@namedef{ext@#2}{#3}%
\@ifundefined{c@#3depth}{\newcounter{#3depth}}{}%
\setcounter{#3depth}{1}%
\@namedef{#3mark}{}%
\@namedef{#2}{\listof{#2}{#4}}
\@namedef{@cftmake#3title}{}
\@ifundefined{cftbefore#3titleskip}{
    \expandafter\newlength\csname cftbefore#3titleskip\endcsname
    \expandafter\newlength\csname cftafter#3titleskip\endcsname
}{}
\@namedef{cft#3titlefont}{}
\@namedef{cftafter#3title}{}
\@namedef{cft#3prehook}{}
\@namedef{cft#3posthook}{}
}
```

```
\renewcommand{\setfloatadjustment}[2]{}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTmemoir@marginfloat}{O{-1.2ex} m}
{% start
\LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
\captionsetup{type=#2}%
}
```

```
{%
\endLWR@BlockClassWP%
}

\DeclareDocumentEnvironment{marginfigure}{o}
  {\begin{KFLTmemoir@marginfloat}{figure}}
  {\end{KFLTmemoir@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
  {\begin{KFLTmemoir@marginfloat}{table}}
  {\end{KFLTmemoir@marginfloat}}

\renewcommand{\setmarginfloatcaptionadjustment}[2]{}
\renewcommand{\setmpjustification}[2]{}
\renewcommand*{\mpjustification}{}
\renewcommand*{\setfloatlocations}[2]{}
\DeclareDocumentCommand{\suppressfloats}{o}{}
\renewcommand*{\FloatBlock}{}
\renewcommand*{\FloatBlockAllowAbove}{}
\renewcommand*{\FloatBlockAllowBelow}{}
\renewcommand*{\setFloatBlockFor}{}

\renewcommand{\captiontitlefinal}[1]{}

\renewcommand{\flegtable}{\tablename}
\renewcommand{\flegfigure}{\figurename}
\renewcommand{\flegtoctable}{}
\renewcommand{\flegtocfigure}{}


\renewcommand{\subcaption}[2][]{%
\ifblank{#1}{\subfloat[#2]{}}{\subfloat[#1][#2]{}}%
}

\renewcommand{\contsubcaption}{\ContinuedFloat\subcaption}

\LetLtxMacro\subcaptionref\subref

\renewcommand*{\tightsubcaptions}{}
\renewcommand*{\loosesubcaptions}{}

\renewcommand*{\subcaptionsize}[1]{}
\renewcommand*{\subcaptionlabelfont}[1]{}
\renewcommand*{\subcaptionfont}[1]{}
\renewcommand*{\subcaptionstyle}[1]{}

\renewcommand*{\hangsubcaption}{}
\renewcommand*{\shortsubcaption}{}
\renewcommand*{\normalsubcaption}{}

\RenewDocumentEnvironment{sidecaption}{o m o}
{}
{
\IfValueTF{#1}{\caption[#1]{#2}}{\caption{#2}}%
\IfValueT{#3}{\label{#3}}%
```

```
}

% \newlength{\sidecapwidth}
% \newlength{\sidecapsep}
\renewcommand*{\setsidecaps}[2]{}
\renewcommand*{\sidecapmargin}[1]{}
% \newif\ifscapmargleft
\scapmargleftfalse
\renewcommand*{\setsidecappos}[1]{}

\RenewDocumentEnvironment{sidecontcaption}{m o}
{}
{%
\ContinuedFloat%
\caption{#1}%
```

Without \@captype, the section is referred to instead.

```
\IfValueT{#2}{\label[\@captype]{#2}}%
}
```

\sidenamedlegend does not appear to use the TOC argument.

```
\renewenvironment{sidenamedlegend}[2][]{
\begin{center}
\@nameuse{\@captype name}\CaptionSeparator#2
\end{center}
}
{}

\renewenvironment{sidelegend}[1]
{\begin{center}
#1

}
{\end{center}}

\renewcommand*{\sidecapstyle}{}
\renewcommand*{\overridescapmargin}[1]{}
% \newlength{\sidecapraise}
\renewcommand*{\sidecapfloatwidth}{\linewidth}

\LetLtxMacro\ctabular\tabular
\LetLtxMacro\endctabular\endtabular

\renewcommand{\autorows}[5][]{%
#5
}

\renewcommand{\autocols}[5][]{%
#5
}
```

§ 512.12 Page notes

```
\renewcommand*{\feetabovefloat}{}
\renewcommand*{\feetbelowfloat}{}
\renewcommand*{\feetatbottom}{}

\renewcommand*{\verbfootnote}[2][]{
\PackageError{lwarp,memoir}
{Verbatim footnotes are not yet supported by lwarp.}
{This may be improved some day.}
}

\renewcommand*{\plainfootnotes}{}
\renewcommand*{\twocolumnfootnotes}{}
\renewcommand*{\threecolumnfootnotes}{}
\renewcommand*{\paragraphfootnotes}{}
\renewcommand*{\footfudgefiddle}{}

\renewcommand*{\newfootnoteseries}[1]{
\PackageError{lwarp,memoir}
{Memoir footnote series are not yet supported by lwarp.}
{This may be improved some day.}
}

\renewcommand*{\plainfootstyle}[1]{}
\renewcommand*{\twocolumnfootstyle}[1]{}
\renewcommand*{\threecolumnfootstyle}[1]{}
\renewcommand*{\paragraphfootstyle}[1]{}

\renewcommand*{\footfootmark}{}
\renewcommand*{\footmarkstyle}[1]{}

% \newlength{\footmarkwidth}
% \newlength{\footmarksep}
% \newlength{\footparindent}

\renewcommand*{\foottextfont}{}

\renewcommand*{\marginparmargin}[1]{}
\renewcommand*{\sideparmargin}[1]{}

\LetLtxMacro\sidepar\marginpar
\renewcommand*{\sideparfont}{}
\renewcommand*{\sideparform}{}
\LWR@providelength{\sideparvshift}

\renewcommand*{\parnopar}{}

\renewcommand{\sidebar}[1]{\begin{quote}#1\end{quote}}
\renewcommand*{\sidebarmargin}[1]{}
\renewcommand*{\sidebarfont}{}
\renewcommand*{\sidebarform}{}
% \newlength{\sidebarhsep}
% \newlength{\sidebarvsep}
% \newlength{\sidebarwidth}
% \newlength{\sidebartopsep}
```

```
\renewcommand{\setsidebarheight}[1]{}
\renewcommand*{\setsidebars}[6]{}
\renewcommand*{\footnotesatfoot}{}
\renewcommand*{\footnotesinmargin}{}

\LetLtxMacro\sidefootnote\footnote
\LetLtxMacro\sidefootnotemark\footnotemark
\LetLtxMacro\sidefootnotetext\footnotetext

\renewcommand*{\sidefootmargin}[1]{}
% \newlength{\sidefoothsep}
% \newlength{\sidefootvsep}
% \newlength{\sidefootwidth}
% \newlength{\sidefootadjust}
% \newlength{\sidefootheight}
\renewcommand*{\setsidefootheight}[1]{}
% \renewcommand*{\sidefootfont}{}% in docs but not in the package
\renewcommand*{\setsidefeet}[6]{}
\renewcommand*{\sidefootmarkstyle}[1]{}
\renewcommand*{\sidefoottextfont}{}
\renewcommand*{\sidefootform}{}

\renewcommand*{\continuousnotenums}{\pncontopttrue}% from pagenote
\renewcommand*{\notepageref}{}
\renewcommand*{\prenotetext}{}
\renewcommand*{\postnotetext}{}
\renewcommand*{\idtextinnotes}[1]{}
\renewcommand*{\printpageinnotes}[1]{}
\renewcommand*{\printpageinnoteshyperref}[1]{}
\renewcommand*{\foottopagenote}{}
\renewcommand*{\pagetofootnote}{}
```

§ 512.13 Decorative text

```
\renewcommand*{\epigraphposition}[1]{}
\renewcommand*{\epigraphtextposition}[1]{}
\renewcommand*{\epigraphsourceposition}[1]{}
\renewcommand*{\epigraphfontsize}[1]{}
\renewcommand*{\epigraphforheader}[2][]{}
\renewcommand*{\epigraphpicture}{}
```

§ 512.14 Poetry

```
\renewcommand*{\vinphantom}{}
\renewcommand*{\vleftofline}[1]{#1}
% \let\linenumberfrequency\poemlines
% \renewcommand*{\linenumberfont}[1]{}

\DeclareDocumentCommand{\PoemTitle}{s o o m}{%
\IfValueTF{#2}%
{\poemtitle[#2]{#4}}%
{\poemtitle{#4}}%
}

\renewcommand*{\NumberPoemTitle}{}
```

```
\renewcommand*{\PlainPoemTitle}{}
\renewcommand*{\poemtitlepstyle}{}
\renewcommand*{\poemtitlestarmark}[1]{}
\renewcommand*{\poemtitlestarpstyle}{}
\renewcommand*{\PoemTitleheadstart}{}
\renewcommand*{\printPoemTitlenonum}{}
\renewcommand*{\printPoemTitlenum}{}
\renewcommand*{\afterPoemTitlenum}{}
\renewcommand*{\printPoemTitletitle}[1]{}
\renewcommand*{\afterPoemTitle}{}
\newlength{\midpoemtitleskip}
\renewcommand*{\PoemTitlenumfont}{}
\renewcommand*{\PoemTitlefont}{}
```

§ 512.15 Boxes, verbatims and files

```
\renewenvironment{qframe}{\framed}{\endframed}
\renewenvironment{qshade}{\shaded}{\endshaded}
```

Use the comment package:

```
\renewcommand*{\commentsoff}[1]{\includecomment{#1}}
\renewcommand*{\commentson}[1]{\excludecomment{#1}}
\LetLtxMacro\renewcomment\commentson

\renewcommand*{\setverbatimfont}[1]{}
\renewcommand*{\tabson}[1]{}
\renewcommand*{\tabsoff}{}
\renewcommand*{\wrappingon}{}
\renewcommand*{\wrappingoff}{}
\renewcommand*{\verbatimindent}{}
\renewcommand*{\verbatimbreakchar}[1]{}
```

```
\DefineVerbatimEnvironment{fboxverbatim}{Verbatim}{frame=single}
```

`boxedverbatim` is already defined by moreverb. `boxedverbatim*` does not appear to work at all, even in a minimal print memoir document.

```
\renewcommand*{\bvbox}{}
\renewcommand*{\bvtopandtail}{}
\renewcommand*{\bvsides}{}
\renewcommand*{\nobvbox}{}
% \newlength\bvboxsep
\renewcommand*{\bvtoprulehook}{}
\renewcommand*{\bvtopmidhook}{}
\renewcommand*{\bvendrulehook}{}
\renewcommand*{\bvleftsidehook}{}
\renewcommand*{\bvrightsidehook}{}
\renewcommand*{\bvperpagetrue}{}
\renewcommand*{\bvperpagefalse}{}
\renewcommand{\bvtopofpage}[1]{}
\renewcommand{\bvendofpage}[1]{}
\renewcommand*{\linenumberfrequency}[1]{}
\renewcommand*{\resetbvlinenumber}{}
\renewcommand*{\setbvlinenums}[2]{}
```

```
\renewcommand*{\linenumberfont}[1]{}
\renewcommand*{\bvnumbersinside}{}
\renewcommand*{\bvnumbersoutside}{}
```

§ 512.16 Cross referencing

```
\renewcommand*{\fref}[1]{\cref{#1}}
\renewcommand*{\tref}[1]{\cref{#1}}
\renewcommand*{\pref}[1]{\cpageref{#1}}
\renewcommand*{\Aref}[1]{\cref{#1}}
\renewcommand*{\Bref}[1]{\cref{#1}}
\renewcommand*{\Pref}[1]{\cref{#1}}
\renewcommand*{\Sref}[1]{\cref{#1}}
\renewcommand*{\figurerefname}{Figure}
\renewcommand*{\tablerefname}{Table}
\renewcommand*{\pagerefname}{page}
\renewcommand*{\bookrefname}{Book~}
\renewcommand*{\partrefname}{Part~}
\renewcommand*{\chapterrefname}{Chapter~}
\renewcommand*{\sectionrefname}{\S}
\renewcommand*{\appendixrefname}{Appendix~}
\LetLtxMacro\titleref\nameref
\renewcommand*{\headnameref}{}
\renewcommand*{\tocnameref}{}

\providecounter{LWR@currenttitle}

\renewcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}

\renewcommand*{\theTitleReference}[2]{}
\renewcommand*{\namerefon}{}
\renewcommand*{\namerefoff}{}
```

§ 512.17 Back matter

Redefined to write the `LWR@autoindex` counter instead of page. Note that memoir has two versions, depending on the use of hyperref.

```
\AtBeginDocument{

\def\@@wrindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
    {\string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}}%
    \endgroup
    \@esphack}%
```

\specialindex behaves like a regular \index, pointing to where \specialindex is used. If \specialindex is used inside a figure or table after the \caption, then the hyperlink will be given the name of that particular figure or table.

```
\def\@@wrspindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
    {%
%         \string\@@wrindexm@m{\@idxfile}{#1}{\@nameuse{the\@sptheidx}}%
        \string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}%
    }%
    \endgroup
    \@esphack}%

}% \AtBeginDocument
```

Patched to use _html filename and \BaseJobname:

```
\catcode`\_=12%
\renewcommand*{\makeindex}[1][\BaseJobname]{%
  \if@filesw
    \def\gindex{\@bsphack%
      \@ifnextchar [{\@index}{\@index[\BaseJobname]}}
    \def\specialindex{\@bsphack\@spindex}%
    \makememindexhook
    \expandafter\newwrite\csname #1@idxfile\endcsname
   \expandafter\immediate\openout \csname #1@idxfile\endcsname #1_html.idx\relax
    \typeout{Writing index file #1_html.idx }%
  \fi}
\catcode`\_=8%
```

Patched to use _html filename and \BaseJobname. This will later be patched by the lwarp core.

```
\catcode`\_=12%
\renewcommand{\printindex}[1][\BaseJobname]{\@input@{#1_html.ind}}
\catcode`\_=8%
```

```
\DeclareDocumentCommand{\newblock}{}{}
%
\renewcommand*{\showindexmarks}{}
\renewcommand*{\hideindexmarks}{}

\renewcommand*{\xindyindex}{}
```

§ 512.18 Miscellaneous

```
\renewcommand*{\changemarks}{}
\renewcommand*{\nochangemarks}{}
\renewcommand*{\added}[1]{}
\renewcommand*{\deleted}[1]{}
\renewcommand*{\changed}[1]{}

\renewcommand*{\showtrimsoff}{}
\renewcommand*{\showtrimson}{}
\renewcommand*{\trimXmarks}{}
\renewcommand*{\trimLmarks}{}
\renewcommand*{\trimFrame}{}
\renewcommand*{\trimNone}{}
\renewcommand*\trimmarkscolor{}
\renewcommand*{\trimmarks}{}
\renewcommand*{\tmarktl}{}
\renewcommand*{\tmarktr}{}
\renewcommand*{\tmarkbr}{}
\renewcommand*{\tmarkbl}{}
\renewcommand*{\tmarktm}{}
\renewcommand*{\tmarkmr}{}
\renewcommand*{\tmarkbm}{}
\renewcommand*{\tmarkml}{}
\renewcommand*{\trimmark}{}
\renewcommand*{\quarkmarks}{}
\renewcommand*{\registrationColour}[1]{}

\renewcommand*{\leavespergathering}[1]{}

\renewcommand*{\noprelistbreak}{}

\renewcommand*{\cleartorecto}{}
\renewcommand*{\cleartoverso}{}

\renewenvironment{vplace}[1][]{}{}
```

§ 512.19 ccaption emulation

```
\renewcommand*{\captiondelim}[1]{\renewcommand*{\CaptionSeparator}{#1}}
\renewcommand*{\captionnamefont}[1]{}
\renewcommand*{\captiontitlefont}[1]{}
\renewcommand*{\flushleftright}{}
\renewcommand*{\centerlastline}{}
\renewcommand*{\captionstyle}[2][]{}
\DeclareDocumentCommand{\captionwidth}{m}{}
\renewcommand*{\changecaptionwidth}{}
\renewcommand*{\normalcaptionwidth}{}
\renewcommand*{\hangcaption}{}
\renewcommand*{\indentcaption}[1]{}
\renewcommand*{\normalcaption}{}
\renewcommand{\precaption}[1]{}
\renewcommand{\postcaption}[1]{}
\renewcommand{\midbicaption}[1]{}
\renewcommand{\contcaption}[1]{%
```

```
% \ContinuedFloat%
% \caption{#1}%
\begin{LWR@figcaption}% later becomes \caption*
\LWR@isolate{\@nameuse{\@captype name}}~%
\thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#1}%
\end{LWR@figcaption}
}
```

```
\newlength{\abovelegendskip}
\setlength{\abovelegendskip}{0.5\baselineskip}
\newlength{\belowlegendskip}
\setlength{\belowlegendskip}{\abovelegendskip}
```

The extra \\ here forces a <br> in HTML when \legend is used in a \marginpar.

```
\renewcommand{\legend}[1]{\begin{center}#1\\\end{center}}

\renewcommand{\namedlegend}[2][]{
\begin{center}
\@nameuse{fleg\@captype}\CaptionSeparator#2\\
\end{center}
\@nameuse{flegtoc\@captype}{#1}
}

\renewcommand{\newfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
\renewcommand{\renewfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
\renewcommand{\providefixedcaption}[3][\caption]{%
  \providecommand{#2}{\def\@captype{#3}#1}}

\renewcommand{\bitwonumcaption}[6][]{%
\ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
\addtocounter{\@captype}{-1}%
\begingroup%
\csdef{\@captype name}{#4}%
\ifblank{#5}{\caption{#6}}{\caption[#5]{#6}}%
\endgroup%
\ifblank{#1}{}{\label{#1}}%
}

\LetLtxMacro\bionenumcaption\bitwonumcaption% todo

\renewcommand{\bicaption}[5][]{%
\ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
\begin{LWR@figcaption}% later becomes \caption*
\LWR@isolate{#4} \thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#5}%
\end{LWR@figcaption}
\ifblank{#1}{}{\label{#1}}%
}

\renewcommand{\bicontcaption}[3]{%
\contcaption{#1}%
\begingroup%
\csdef{\@captype name}{#2}%
\contcaption{#3}%
```

```
\endgroup%
}

% only in ccaption, not in memoir:
% \LetLtxMacro\longbitwonumcaption\bitwonumcaption%
% \LetLtxMacro\longbionenumcaption\bitwonumcaption%
% \LetLtxMacro\longbicaption\bicaption%

\RenewDocumentCommand{\subtop}{O{} O{} m}{%
\subfloat[#1][#2]{#3}%
}

\RenewDocumentCommand{\subbottom}{O{} O{} m}{%
\subfloat[#1][#2]{#3}%
}

\renewcommand{\contsubtop}{%
\ContinuedFloat\addtocounter{\@captype}{1}%
\subtop}

\renewcommand{\contsubbottom}{%
\ContinuedFloat\addtocounter{\@captype}{1}%
\subbottom}

\renewcommand{\subconcluded}{}

\let\subfigure\subbottom
\let\subtable\subtop

\let\contsubtable\contsubtop
\let\contsubfigure\contsubbottom

\newcommand{\newfloatentry}[4][\@empty]{TODO: newfloatentry}
\newcommand{\newfloatlist}[5][\@empty]{TODO: newfloatlist}
\newcommand{\newfloatenv}[4][\@empty]{TODO: newfloatenv}
\DeclareRobustCommand{\newfloatpagesoff}[1]{}
\DeclareRobustCommand{\newfloatpageson}[1]{}
\newcommand{\setnewfloatindents}[3]{}
```

§ 512.20 Final patchwork

```
\newlistof{tableofcontents}{toc}{\contentsname}
\newlistof{listoffigures}{lof}{\listfigurename}
\newlistof{listoftables}{lot}{\listtablename}
```

Change History

§ 513 Chg Hist

For the most recent changes, see page 1031.

v0.10
General: 2016/03/08 Initial version . . 1
v0.11
General: 2016/03/11 1
Added section: Operating-System portability. 211
Added section: Selecting the operating system. 121
Test Suite: MS-Windows in README.txt 1
Test Suite: limages and index in README.txt 1
v0.12
\LWR@newhtmlfile: Bugfix: TOC with numbered files. 355
General: 2016/03/14 1
Global: Uses \p@(type) in float captions. 1
Test Suite: Sub-figures 1
v0.13
\CaptionSeparator: Fix for newer babel package. 474
\LWR@LwarpStart: \up and \fup . . . 373
General: 2016/03/24 1
Fix dollar-redefined bug for newer package. 913
Removed package: subfig 1
Test Suite: Ordinals, Subcaption . . . 1
v0.14
\LWR@htmlsectionfilename: Fix: Links to home page. 317
General: 2016/03/31 1
floatrow: Added. 707
Docs: Commands for a successful HTML conversion. 124
Docs: Commands into a warpprint environment. 122
Docs: Newclude limitations. . . . 168
Docs: Table: Cross-referencing data structures. 460
Docs: Table: Float data structures. 470
Docs: Trademarks section. 192
Docs: Troubleshooting cross-references. 187
Test Suite: Assigned cleveref name for Test Float. 1
Test Suite: Floatrow 1
v0.15
General: 2016/04/06 1
Added. 712
Ampersand (&): Fixed handling when passed as an argument. . . 406
Docs: Added warning icons for items needing special attention. 195
Docs: Clarify print/HTML output. 121
Docs: Moved the supported features table to the introduction. 77
Files: lwarp_formal.css added. 1
Fix: steps counter 711
Fixed & handling. 710
Test Suite: test_suite_formal.css file added. 1
v0.16
General: 2016/04/11 1
\titlingpage: Improved print-output spacing. 381
xfrac: Adjusted for the use of any font: 969
Added XeLaTeX, LuaLaTeX support. 196
Docs: Font and UTF-8 support. . 108
Docs: Moved location of \usepackage{lwarp}. 110
Docs: Text not converting. 187
Lwarp no longer selects fonts. 108, 221
Removed package: suffix 1
Test Suite: Improved titlingpage. 381
Test Suite: Lwarp no longer selects fonts. 1
Test Suite: Supports XeLaTeX, LuaLaTeX. 1
v0.17
\LWR@htmlsectionfilename: Fix: Links when entire doc is one HTML page. 317
General: 2016/04/14 1
mdframed: Added. 793

Test Suite: Fix: Print-version front-matter page numbers. 1
Test Suite: Mdframed 1
v0.18
\LWR@includegraphicsb: Add: svgz file extension. 734
em, ex, %, px dimensions preserved. 734
Fix: \linewidth, \textwidth, \textheight inside a minipage. 734
Improved HTML output linebreaks. 734
\LWR@myshorttoc: Reorganize \HomeHTMLFilename logic. 478
\LWR@newhtmlfile: sideTOC after title, improving responsive design. . . 354
\LWR@requesttoc: Reorganize \HomeHTMLFilename logic. 375
\LWR@subhyperref: Improved HTML output linebreaks. 467
\LWR@subhyperrefclass: Improved HTML output linebreaks. 467
\LWR@subinlineimage: Suppress extra space. 469
\hspace: \hspace supported. 565
General: 2016/05/19 1
File: lwarp.css: Improved TOC outline display. 1
Files: lwarp.css and lwarp_formal.css: Improved responsive design. 1
Microtype disabled during HTML generation 221
PDF Unicode input characters. . 209
Test Suite: Verse package 1
lateximage: pdfcrop: --hires added. 522
Reorganize \HomeHTMLFilename logic. 522
Suppress extra space. 522
verse: Supports verse, memoir packages. 948
minipage: Fix: \linewidth, \textwidth, \textheight inside a minipage. 542
v0.19
\HTMLFilename: Docs: Escape filename underscores. 317
\HomeHTMLFilename: Docs: Escape filename underscores. 317
\LWR@LwarpStart: Enabled \\ equal to \newline. 372
\LWR@doequation: MathJax support. 509
\LWR@doubledollar: MathJax support. 503
\LWR@filestart: lwarp_mathjax.txt loaded. 370
\LWR@minipagestartpars: Suppresses paragraph tags between minipages. 563
\LWR@subsingledollar: MathJax support. 498
\LateximageFontSizeName: Add: User-adjustable math/lateximage font size. 518
\hspace: Fix: \hspace length computations. 565
\minipagefullwidth: Added: No width tag for the next minipage in HTML. 542
\warpHTMLonly: Added. 220
\warpprintonly: Replaces \rowprintedonly. 220
\xfracHTMLfontsize: Added. 969
General: 2016/06/08 1
CSS for table note item. 911
MathJax support added. 506, 512, 514
multirow: Added optional args. . 811
Adapts to tikz version. 913
Avoids MathJax. 496
cleveref: Loaded \AtEndPreamble. 537
Docs: Math options. 110
Docs: Table: Cross-referencing data structures, updated. 460
File: lwarp.css: tnoteitemheader added. 1
File: lwarp_mathjax.txt added. . . 1
Introduction: MathJax support mentioned. 74
Options: mathsvg and mathjax . 215
Supports colored \rule. 960
titleps: null \pagestyle and \thispagestyle for HTML. 914
v0.20
\BlockClassSingle: Renamed from "LWR@htmldivclassline". 330
\HTMLDescription: Added \NewHTMLdescription. (Renamed in v0.30.) 340
\HTMLFilename: No longer escape underscores. 317
\HomeHTMLFilename: No longer escape underscores. 317
\InlineClass: Renamed from "inlineclass". 330
\LWR@LwarpStart: Fix: math cross references. 374
\LWR@closeparagraph: \unskip extra spaces. 334
No break tags in the start/end of a tabular. 334
\LWR@endofline: Fix: \\ 563

\LWR@filestart: Adds meta description. 370
\LWR@htmldivclass: Added optional style. 328
\LWR@htmlelementclass: Added optional style. 328
\LWR@htmlsectionfilename: HTMLFilename: removed additional trailing '-', and may be empty. 317
Sections called "Index" or "index" have an underscore prepended to their filenames if no prefix. 317
\LWR@includegraphicsb: Fix: \linewidth in a floatrow. 734
Fix: Expands filename. 734
\LWR@longtabledatacaptiontag: Fix: Pars in captions. 443
\LWR@section: Combined higher-level sections together into files. 361
\LWR@setOSWindows: Auto-detects operating system. 213
\LWR@subhtmlelementclass: Factored code. 327
\SetHTMLFileNumber: Add: Control file numbers. 317
\cpagerefFor: User-redefinable word for page references. 538
\dotfill: Inserts an ellipsis. 563
\hfill: Inserts a \qquad. 563
\hrulefill: Inserts a short rule. . . 563
\hspace: Add: Supports HTML thin breakable space. 565
\hyperindexref: Print mode provided in case hyperref not used. 488
\pageref: Added. 466
\tracinglwarp: Added. 232
General: 2017/02/09 1
afterpage: Added. 585
alltt: Added. 590
bookmark: Added. 622
caption and subcaption supported. 1
cleveref and referencing patches: Applied \AfterEndPreamble. . . . 537
draftwatermark: Added. 673
eso-pic: Added. 685
everypage: Added. 686
extramarks: Added. 687
fancyhdr: Added. 693
float: Improved float caption type handling. 704
hyperref: Additional user macros. 746
keyfloat: Added. 762
letterspace: User-interface emulated. 771
listings: Added. 775
ltcaption: Added. 784
lwarp-newproject: Added. 244
microtype: User-interface emulated. 805
needspace: Added. 819
nowidow: Added. 823
placeins: Added. 848
ragged2e: Added. 855
setspace: Improved support. . . 874
textpos: Added. 905
titleps: Added. 914
titlesec: Added. 917
titletoc: Added. 919
titling: Improved compatibility. . 921
tocloft: Added. 929
wallpaper: Added. 954
wrapfig: Added. 955
xetexko-vertical: Added. 968
Added @, <, > columns. 401
Added single-expansion data arrays. 313
Code factored into independent lwarp_html files. 576
Docs: Examples for generating HTML file names. 119
Docs: Improved index. 1
Enhanced titling support. 380
File: lwarp.css: Minor fixes for validation. 1
File: lwarpmk used to compile print, HTML, indexes, and lateximages. 1
Fix: \linewidth in a floatrow. . . 710
Moved sidebar and example code to test suite. 1
Page geometry set to 6in wide with large margins. 222
Parallel versions of aux files for print/HTML. 1
Removed reliance on make, grep, gawk. 1
Tabular: \unskip extra spaces. . . 401
Test Suite: HTML meta descriptions. 1
verbatim: Added. 390
BlockClass: Added optional style. . 329
Renamed from "blockclass". . . . 329
LWR@nestspan: Fix: Minipages inside a span. 325
v0.21
\LWR@LwarpStart: Changed lateximages to a .txt file. 372

\LWR@filestart: Skip title if not given. 370
\LWR@newhtmlfile: Skip title if not given. 354
\marginpar: Fixed source listing. . . 347
\marginparBlock: Fixed source listing. 347
General: 2017/02/23 1
fontenc: Added. 717
lwarpmk: Fix: **lwarpmk again** for Windows. 293
lwarpmk: Fix: **lwarpmk limages** for Windows. 293
lwarpmk: Fix: *lwarpmk* uses lateximages text file instead of shell script. 293
Add: Errors for misplaced packages. 196
Docs: Added internet class. 83
Docs: Added TeX2page, GladTeX. . 83
Docs: Installing on Windows. . . . 89
File: lwarp_tutorial.txt added. . 93
v0.22
\LWR@parseDcolumn: Added tabular D column. 416
\LWR@parsebangcolumn: Added tabular ! column. 411
\LWR@parsetablecols: Unknown table column types become l. Added tabular D, !, X columns. . 418
\LWR@printmccoldata: Added tabular D, !, and X columns. 438
General: 2017/03/02 1
abstract: Added. 578
changepage: Added. 632
dcolumn: Added. 669
ftnright: Added. 723
geometry: Nullified commands. . 725
layout: Added. 768
lscape: Added. 783
mcaption: Added. 793
nameref: Added. 817
nextpage: Added. 819
parskip: Added. 839
showkeys: Added. 875
sidecap: Added. 876
tabularx: Added. 898
varioref: Supported. 133
verse: Added. 948
v0.23
\LWR@parsetablecols: Fix for vert bar column type. 418
\LWR@printmccoldata: Fix for vert bar column type. 438
General: 2017/03/02 1
v0.24
\LWR@htmlfileref: Fix: Index links while \tracinglwarp. 462
\hspace: Add: \hspace \fill converts to 2em 565
\hypertocfloat: List of floats responds to lofdepth, lotdepth. 484
General: 2017/03/15 1
floatrow: Support for subfig. . . . 707
subfig: Added. 891
tikz: For tikz v3.0.0 or later, auto-loads tikz babel library if necessary. 913
Docs: Filename underscore. 114, 127
Fix for inline images. 913
No longer preloads subcaption; conflicted with subfig. 224
picture: Fix for inline images. . . . 540
v0.25
\LWR@loadnever: Added the ability to prevent conflicting packages. . . 198
\addcontentsline: Handles theorems. 476
General: 2016/03/22 1
amsthm: Added. 597
ellipsis: Added. 676
emptypage: Added. 677
framed: Added. 721
lips: Added. 775
mdframed: Help avoid hyphenation. 795
ntheorem: Added. 824
showidx: Added. 875
theorem: Added. 906
Basic LaTeX theorems: improved css. 391
Docs: Adds credits for patched code. 1
Docs: Testing lwarp. 185
Fix: Allows XeLaTeX and LuaLaTeX to preload graphics and graphicx. 200
v0.26
General: 2017/03/31 1
lwarp.css: Improved responsive marginpar and marginblock. . . 251
cutwin: Added. 668
endnotes: Added. 678
floatflt: Added. 706
footmisc: Added. 717
footnotehyper: Added. 719
footnote: Added. 718
marginfix: Added. 791
marginnote: Added. 792
mparhack: Added. 808
pagenote: Supported as-is. 837

sidenotes: Added. 877
Docs: Improved MiKTEX install instructions. 88, 90
Dollar span avoided in a lateximage. 496
Footnotes now are LATEX boxes instead of pagenotes. 341
lateximage: Labels track page numbers of lateximages. 522
Print mode now uses a minipage of \linewidth. 522
picture: Fix for \makebox in picture. 540
v0.27
\LWR@@footnotetext: Fix for table footnote par tags. 343
General: 2017/04/04 1
lettrine: Added. 772
microtype: Fix with XeLATEX, LuaLATEX. 805
soul: Added. 884
ulem: Added. 943
Docs: Installing utilities for MACOS. 91
Docs: Limitations of saveboxes. . 127
Page geometry modified to reduce line overflow. 222
v0.28
\@wrindex: Improved indexing. . . . 486
\HTMLAuthor: Added \HTMLauthor. (Renamed in v0.30.) 340
\LWR@LwarpEnd: If FormatEPUB or FormatWP, no bottom nav. 375
\LWR@LwarpStart: FormatWordProcessor forces single-file output. 372
\LWR@filestart: Adds HTML meta author. 370
\LWR@forcenewpage: Forces new PDF page before major environments. 321
\LWR@htmlcomment: Breaks ligatures in HTML comments. 327
\LWR@includegraphicsb: Adapts to graphics syntax. 734
\LWR@newhtmlfile: If FormatEPUB or FormatWP: skips headers, footers, nav. 354
\LWR@parsetablecols: Added L, C, R, J column types. 418
\LWR@startref: Removed space. . . 464
\chapter: If EPUB, prints footnotes before each section. 367
\hyperindexref: Improved indexing. 488
\textup: Fixed span class. 553
General: 2017/04/14 1
glossaries: Added. 727
graphics: Added. 729
tabularx: Fix for optional pos. . . 898
tabulary: Added. 899
lwarpmk: Add: **printglossary** and **htmlglossary** commands. 293
Added boolean FormatEPUB. . . . 238
Added boolean FormatWP. 238
Added boolean HTMLDebugComments. 233
Added boolean HTMLMarkFloats, changed to WPMarkFloats as of v0.42. 238
Docs: Modfying lwarpmk and index processing. 185
File: lwarp_mathjax.txt: Updated CDN repository. 291
Forced oneside to maintain large right margin. 222
v0.29
\LWR@includegraphicsb: Fix: Error when no optional arguments. . . 734
General: 2017/04/15 1
*.lwarpmkconf: Add: language option for config files. 251
lwarpmk.conf: Add: language option for config files. 251
lwarpmk: Add: language option for config files. 293
Add: lwarpmklang option for lwarp. 216
Docs: Using a glossary 104
v0.30
\CSSFilename: Renamed from \NewCSS. 339
\HTMLAuthor: Renamed from \HTMLauthor. 340
\HTMLDescription: Renamed from \NewHTMLdescription. 340
\HTMLFirstPageTop: Renamed from \SetFirstPageTop. 338
\HTMLLanguage: Renamed from \MetaLanguage. 368
\HTMLPageBottom: Renamed from \SetPageBottom. 338
\HTMLPageTop: Renamed from \SetPageTop. 338
General: 2017/04/29 1
lwarp-newproject removed, and combined with lwarp. 244
lwarpmk: Add: xdyfile configuration option. 293
lwarpmk: Fix: *xindy* and *texindy* adjusted for *pdflatex*, *xelatex* and *lualatex*. 293

lwarpmk: Fix: *xindy* now used for print index generation with *latexmk*. 293
lwarpmk: language now used for both index and glossary generation. 293
File: lwarp_html.xdy renamed to lwarp.xdy. 290
Fix: *.css files only written in print mode. 251
Fix: lwarp.xdy only written in print mode. 290
Fix: lwarp_mathjax.txt: Only written in print mode. 291
Option lwarpmklang changed to IndexLanguage. 216
Option OSWindows replaces macro \warpOSwindows. 216
Option xdyFilename added. 216
Option *latexmk* replaces macro \UseLatexmk. 217
Options HomeHTMLFilename and HTMLFilename replace macros \HomeHTMLFilename and \HTMLFilename. 216
v0.31
General: 2017/05/15 1
keyfloat: Improved compatibility. 762
v0.32
\RequirePackage: Fix: Ignores blanks in package list. 228
General: 2016/06/09 1
glossaries: Prevent error with \glo@name not defined. 488
lwarpmk: Fix: **io.lines()** changed to **file:lines()** due to *luatex* changes. 293
v0.33
\HTMLAuthor: Fix: Provides empty default author if none given. . . . 340
\LWR@loadbefore: Fix: No \PackageError if already loaded. 198
\LWR@parseatcolumn: Fix: Column alignment with leftmost @. 410
\LWR@tabledatasinglecolumntag: Fix: Macros in tabular could cause extra data cell. 425
\LWR@vspace: Add: \vspace nullified. 566
\StartDefiningTabulars: Add: Avoids error: Misplaced alignment tab character &. . . 314
General: 2017/07/10 1
amsmath: Removed fleqn option. 590
fancyhdr: Fix: Optional args for \lhead, etc. 693
Add: Tabular at and bang columns now have their own HTML columns. 401
cleveref: Fix: Loaded \AtEndPreamble. 537
Fix: Incorrectly-inline math environments. 514
New handling of & to localize catcode changes. 401
v0.34
\@fnsymbol: Text symbols instead of math. 382
\InlineClass: Moved optional argument in front of mandatory. 330
\LWR@htmldivclass: Moved optional argument in front of mandatory. 328
\LWR@htmlelementclass: Moved optional argument in front of mandatory. 328
\LWR@htmlelementclassline: Moved optional argument in front of mandatory. 328
\LWR@htmlspanclass: Moved optional argument in front of mandatory. 326
\LWR@nullfonts: Improved font control. 554
\LWR@restoreorigformatting: booktabs: Works inside lateximage. 490
Improved font control. 490
\LWR@subhtmlelementclass: Moved optional argument in front of mandatory. 327
\LWR@tabledatacolumntag: booktabs: Works inside lateximage. 450
\fboxBlock: Added. 548
\makebox: Fix: Handles paren arg. . 546
General: 2017/08/08 1
babel-french: Adds fixed-width HTML spaces to punctuation. . . 323
balance: Added. 612
booktabs: Works inside lateximage. 453, 622
boxedminipage2e: Added. 624
crop: Added. 665
enumerate: Added. 679
enumitem: Added, no longer required. 679
everyshi: Added. 687
fancybox: Added. 689
fancyvrb: Added, no longer required. 695
figcaps: Added. 700

filecontents: Required. Patched for morewrites. 223
floatpag: Added. 707
flushend: Added. 712
fullpage: Added. 724
hyperxmp: Added. 751
idxlayout: Added. 752
marginfit: Added. 791
mdframed: Improved mdtheorem patch. 800
moreverb: Added. 807
paralist: Added. 838
pdflscape: Added. 840
pdfsync: Added. 844
prelim2e: Added. 849
rotfloat: Added. 862
savetrees: Added. 863
shadow: Added. 875
syntonly: Added. 897
titleps: No longer required. 914
titleref: Prevented. 917
xmpincl: Added. 972
Added. 964
Docs: Horizontal space limitations. 1
Docs: Misplaced alignment character. 187
File: lwarp_mathjax.txt: Version change. 291
File: README.txt: updated. 1
Fix: Added the eqnarray environments. 514
Improved font control. 551
Lists refactored to remove enumitem requirement. 392
Verbatim refactored to remove fancyvrb requirement. 388
tabular: booktabs: Works inside lateximage. 454
lateximage: Fix: lateximage with minipage, \parbox, \makebox, \fbox, \framebox, \raisebox, \scalebox, \reflectbox. 522
BlockClass: Moved optional argument in front of mandatory. 329
fminipage: Added. 549
LWR@nestspan: Fix: Minipages, BlocksClass, and lists inside a span. 325
v0.35
General: 2017/08/08 1
Fix: \textbf and related. 551
v0.36
\LWR@@footnotetext: Extra HTML source space after paragraphs. . 343
Force HTML superscripts. 343
\LWR@HTMLsanitize: Fix for babel-french. 519
\LWR@HTMLsanitizeexpand: Fix for babel-french. 519
\LWR@closeparagraph: Extra HTML source space after paragraphs. . 334
\LWR@currenttextcolor: Fix for \rule when xcolor not loaded. . 561
\LWR@nullfonts: Fix: Filenames while using MathJax. 554
\LWR@restoreorigformatting: siunitx: Improved super/subscripts in a lateximage. 490
\LWR@section: Improved spacing. . 361
\LWR@stoppars: Extra HTML source space after paragraphs. 336
\fbox: Fix: Uses \fboxrule and \fboxsep. 548
\framebox: Fix: Handles width and horiz position. 547
\makebox: Fix: Handles width and horiz position. 546
General: 2017/08/17 1
babel-french: Adjustements for French variants, load order, footnotes, ellipses. 323
footnote: Extra HTML source space after paragraphs. 718
siunitx: Fix for babel-french. . . . 530
siunitx: Improved symbol support. 879
transparent: Added. 939
upref: Added. 947
xcolor: Added \fcolorboxBlock, \colorboxBlock. 956
xcolor: Fix: Background none in print mode. 956
xcolor: Refactored \LWR@colorstyle. 960
xcolor: Uses \fboxrule and \fboxsep. 956
xcolor: \fcolorbox etc. now work inside lateximage. 956
Docs: Reorganized: Special cases and limitations. 124
Source: Improved formatting. 1
tabular: Fix for babel-french. 454
lateximage: Footnotes appear in regular text instead of the lateximage minipage. 522
v0.37
\include: Maintains independent aux files for HTML. 231
General: 2017/08/19 1
LaTeX accents: Added. 243

babel-french: Adjustment for load order. 323
color: Prevented. 662
comment: Maintains independent cutfiles for print, HTML. 220
siunitx: Improved symbol support. 879
textcomp: Improved support. . . 902
lwarpmk: Removes additional HTML aux files. 293
File handles reorganized. 230
v0.38
\@seccntformat: Added for appendix. 360
\ForceHTMLPage: Added. 358
\ForceHTMLTOC: Added. 358
\LWR@section: \part* starts a new HTML page, for appendix. 361
Modified spacing, uses \numberline. 361
\numberline: Added trailing \quad. 482
\part: Fix with article class. 366
General: 2017/08/27 1
appendix: Added. 601
arabicfront: Added. 603
chappg: Added. 634
color: Forces xcolor as well. 662
fix2col: Added. 702
fncychap: Added. 713
grffile: Added. 742
metalogo: Added. 802
nonumonpart: Added. 822
nopageno: Added. 822
pagenote: Option page disabled. 837
realscripts: Added. 856
relsize: Added. 858
romanbarpagenumber: Added. . 861
romanbar: Added. 861
scalefnt: Added. 863
siunitx: Removed from lwarp core. 879
textcomp: Removed from lwarp core. 902
tocbibind: Added. 926
xltxtra: Added. 971
lwarpmk: Added **print1** and **html1** actions. 293
Added \markboth, \sloppy, etc. . 321
Docs: Enhanced *Supported Features* table. 77
Docs: Index, tocbibind. 139
Docs: Starred sections. 135
v0.39
\@maketitle: titling version. 923
Native LaTeX version. 383
Removed minipages. 383, 923
Supports authblk with s of class oneauthor instead of tabular. 383, 923
\AddSubtitlePublished: Added. . . 385
\LWR@domulticolumn: Add: Optional vpos and # rows. 440
\LWR@restoreorigformatting: Appended with \appto instead of calling various macros. 490
\LWR@tabledatacolumntag: Don't start a data cell if see \TabularMacro. 450
\ResumeTabular: Added. 449
\TabularMacro: Added. 449
\multicolumnrow: Added. 447, 813
\printauthor: Removed minipages. 380
Supports authblk with s of class oneauthor instead of tabular. 380
\thanksmarkseries: Removed minipage footnotes. 925
General: 2017/09/05 1
a4wide: Added. 578
a4: Added. 577
a5comb: Added. 578
addlines: Added. 585
anysize: Added. 601
authblk: Added. 610
bigdelim: Added. 619
bigstrut: Added. 620
ebook: Added. 675
fullwidth: Added. 724
midpage: Added. 806
multirow: Add: New optional vpos argument. 811
multirow: Add: Supports left/right border for bigdelim. 811
multirow: Fix: Long text argument. 811
supertabular: Added. 896
textarea: Added. 901
titling: Improved compatibility. . 921
titling: Removed extraneous center environments. 922
typearea: Added. 942
xtabular: Added. 973
zwpagelayout: Added. 977
Docs: Reorganized tabular discussion. 160
Titlepage \published and \subtitle removed. \AddSubtitlePublished restores. 384
titlepage: Clear pending footnotes. 379
Removed minipages. 379
titlingpage: Clear pending footnotes. 921

v0.40
\@chapcntformat: Added for tocbibind, anonchap. 360
\LWR@HTMLhline: Added. 453
\LWR@includegraphicsb: Add: Full \graphicspath support. 734
\LWR@nullfonts: Fix: Long arguments for expandable command. 554
\LWR@restoreorigformatting: Improved LaTeX logos inside a lateximage. 490
Improved symbols inside a lateximage. 490
Nullified \InlineClass, etc. inside a lateximage. 490
\LWR@tabledatacolumntag: Fix for bigdelim: \ldelim, \rdelim. . . . 450
\chapter: Added support for quotchap. 367
\multicolumnrow: Fix: Adapts to older multirow and xparse. 447
\simplechapterdelim: Added for tocbibind, anonchap. 360
\underline: Added. 560
General: 2017/09/25 1
adjmulticol: Added. 584
anonchap: Added. 601
bigdelim: Improved documentation. 619
cuted: Added. 668
dblfnote: Added. 669
fnpos: Added. 714
graphics: Moved out of the lwarp core. 729
graphics: Restores \includegraphics and \DeclareGraphicsExtensions in a lateximage. 729
graphicx: Moved out of the lwarp core. 741
grffile: Directly supported. 742
midfloat: Added. 806
multirow: Improved bigdelim borders. 811
pfnote: Added. 846
quotchap: Added. 854
sectsty: Added. 872
stabular: Added. 888
tabls: Added. 898
textcomp: Additional symbols, improved XeLaTeX and LuaLaTeX support. 902
tocbibind: Improved for \simplechapter. 926
xfrac: No longer preloaded. 224
xltxtra: Fix for \showhyphens with XeLaTeX. 971
v0.41
\LWR@addcmidruletrim: Add: \cmidrule trims. 430
\LWR@clearmidrules: Add: \cmidrule trims. 427
\LWR@closetabledatacell: Add: Mute > for \bottomrule. 405
Fix: At/bang column with \multirow. 405
Fix: Cancel < for \multicolumn. . 405
\LWR@domulticolumn: Add: \cmidrule trims. 440
Added vertical rules. 441
\LWR@nullifyNoAutoSpacing: Fix: \NoAutoSpacing in a tabular with babel-french. 454
\LWR@parsebarcolumn: Added vertical rules. 413
\LWR@printatbang: Add: \cmidrule trims. 423
Add: Mute at and bang columns for \bottomrule. 423
\LWR@printbartag: Added vertical rules. 423
\LWR@subaddcmidruletrim: Added. 429
\LWR@subcmidrule: Add: \cmidrule trims. 428
\LWR@tabledatasinglecolumntag: Add: \cmidrule trims. 425
Add: Mute < for \bottomrule. . . 425
\LWR@tabularfinishrow: Unfinished tabular rows automatically filled. 407
\mcolrowcell: Added for \multicolumrow cells. 453
General: 2017/10/07 1
multirow: Add: \cmidrule trims. 811
Added vertical rules. 812
Fix: < spec. 812
Improved rules. 622
tabular: Fix: \NoAutoSpacing in a tabular with babel-french. 455
v0.42
\@ensuredmath: Improved \ensuremath. 505
\@textsubscript: Added. 560
\@textsuperscript: Added. 560
\LWR@HTMLhline: If FormatWP force explicit border. 453
\LWR@addformatwpalignment: If FormatWP add explicit style for cell alignment. 432
\LWR@addrulewidth: If FormatWP force explicit border. 430

\LWR@amsmathbody: Fix: Numbering and naming AMS math environments. 521
\LWR@amsmathbodynumbered: Fix: Numbering and naming AMS math environments. 521
\LWR@doequation: If FormatWP print LaTeX expression. 509
\LWR@domulticolumn: If FormatWP add cell alignment. 442
\LWR@doubledollar: If FormatWP print LaTeX expression. 503
Improved \ensuremath. 503
Improved line spacing with mathjax. 503
\LWR@floatbegin: If FormatWP add a text frame. 471
\LWR@floatend: If FormatWP add a text frame. 472
\LWR@htmlmathlabel: If FormatWP print LaTeX expression. 513
\LWR@includegraphicsb: Fix: Filename expansion. 734
If FormatWP, use explicit size. . . . 735
\LWR@remembertag: Fix: Numbering and naming AMS math environments. 521
\LWR@restoreorigformatting: Improved \ensuremath. 491
\LWR@subaddcmidruletrim: 0pt if no rule given. 429
\LWR@subsingledollar: If FormatWP print LaTeX expression. 498
\LWR@tabledatasinglecolumntag: If FormatWP add cell alignment. . . 425
\LaTeX: If FormatWP use explicit style. 570
\TeX: If FormatWP use explicit style. 570
\hspace: If FormatWP add \quads. . . 565
\listoffigures: Added boolean WPMarkLOFT. 480
\listoftables: Added boolean WPMarkLOFT. 480
\marginpar: If FormatWP emulate a wrapfig. 347
\marginparBlock: If FormatWP emulate a wrapfig. 347
\rule: If FormatWP add \quads. . . . 569
\tableofcontents: Added boolean WPMarkTOC. 479
\underline: If FormatWP, use explicit styles for \underline, etc. 560
General: 2017/10/30 1
\textbf and related: If FormatWP, use explicit styles for \textsc, etc. 551
algorithmicx: If FormatWP add \quads. 589
epigraph: If FormatWP add HTML styles. 680
fancybox: If FormatWP add HTML styles. 689
floatflt: Added width. 706
includegraphics: Fix: Class key. . 733
keyfloat: If FormatWP add explicit HTML style. 767
moreverb: Simplified formatting of listings. 807
multirow: If FormatWP add cell alignment. 812
overpic: Added. 836
realscripts: Fix for subscripts in a lateximage. 856
sidenotes: If FormatWP add explicit HTML style. 877
siunitx: Improved \ensuremath. . 879
soul: If FormatWP, add explicit styles. 884
textcomp: Improved \interrobangdown. 902
wrapfig: If FormatWP add explicit HTML style. 955
Added boolean WPMarkLOFT. . . . 239
Added boolean WPMarkMath. . . . 239
Added boolean WPMarkMinipages. 238
Added boolean WPMarkTOC. 238
Added boolean WPTitleHeading. 239
Docs: Added support page. 2
Docs: Improper \prevdepth. . . . 187
Docs: Reorganized math limitations 151
File: lwarp_mathjax.txt: Updated siunitx script. 291
Fix: Numbering and naming AMS math environments. 520
If FormatWP force explicit border. 622
If FormatWP, shift section headings. 239
tabbing: Added. 391
lateximage: Fix: Numbering and naming AMS math environments. 523
center: If FormatWP use explicit text-align. 527
minipage: Added boolean WPMarkMinipages. 544, 545
If FormatWP add a text frame. . . . 543
eqnarray: Fix: Numbering and naming AMS math environments. 515
If FormatWP print LaTeX expression. 514
LWR@BlockClassWP: Added to factor code. 330

LWR@figcaption: If FormatWP forces italic captions. 475
v0.43
\LWR@domulticolumn: Fix for vertical rules. 441
Fix: Multicolumn trim. 441
\LWR@maybeprintpendingfootnotes: Added FootnoteDepth. 346
\LWR@nullfonts: Fix: Nullify dollar inside filesnames. 554
\LWR@parsetablecols: Ignore spaces in col spec. 418
\LWR@printmccoltype: Added vertical rules. 436
\LWR@section: Fix: Expansion in comparison. 361
Fix: Math in section name. . 363, 365
Fix: Nullify fonts inside HTML comment. 362
\TabularMacro: \newcommand instead of \relax to fix supertabular and xtab. 449
\href: Made robust. 468
\nameref: Made robust. 466
\nolinkurl: Made robust. 468
\url: Made robust. 468
General: 2017/11/08 1
LWR@currentautosec: Added. . . . 361
breakurl: Added. 624
hyperref: Made robust. 746, 748, 750
hyperref: \Gauge added. 750
luatodonotes: Added. 786
todonotes: Added. 936
Added FootnoteDepth. 342
Docs: HTML settings table. 114
Docs: Reorganized HTML customization. 114
v0.44
\@currentlabelname: Adjustment for koma-script. 460
\HTMLTitle: Added. 340
\LWR@addformatwpalignment: Fix for multicolumn alignment if FormatWP. 432
\LWR@backgroundcolor: Added. . . . 960
\LWR@filestart: Add \HTMLTitle. . 371
Fix \HTMLAuthor. 370
\LWR@listitem: Added list and trivlist. 395
\LWR@patchlists: Added list and trivlist. 398
\LWR@strresult: Fix: \providecommand. 404
\LWR@textcurrentcolor: xcolor: Added \LWR@textcurrentcolor. 959
\addcontentsline: Automatic \LWR@newfloatanchor. 476
\chapter: Add preamble for koma-script. 367
\marginparBlock: Added. 347
\nopagecolor: xcolor: Fix for \nopagecolor. 961
\part: Add preamble for koma-script. 366
\title: Added \thetitle. 339
General: 2017/11/22 1
algorithmicx: Improved comment symbol. 589
atbegshi: Added. 607
cancel: Added. 627
changepage: Additional options. 633
easy-todo: Added. 674
fancyref: Added. 693
fixmetodonotes: Added. 703
fixme: Added. 702
fontenc: Allowed after lwarp. . . . 717
hang: Added. 743
ifoddpage: Added. 753
ltxtable: Added. 785
luatodonotes: Improved. 786
lwarp-patch-komascript: Added. 979
overpic: Fix: Groups for lateximages. 836
pdfsync: Fixes. 844
preview: Added. 850
scrextend: Added. 864
scrhack: Added. 867
scrlayer-notecolumn: Added. . . 869
scrlayer-scrpage: Added. 869
scrlayer: Added. 867
section: Added. 871
soulpos: Added. 885
soulutf8: Added. 886
supertabular: Fix for caption. . . 897
tikz: Fix: Groups for lateximages. 913
tocbasic: Added. 925
tocloft: Added \newlistentry. . 934
tocloft: Improved \newlistof. . . 934
tocstyle: Added. 935
todonotes: Improved. 936
todo: Added. 935
typearea: Added expert commands. 942
watermark: Added. 954
xcolor: Added \LWR@currenttextcolorstyle. . 959
xcolor: Added \LWR@findcurrenttextcolor. . . 959
xtab: Fix for caption. 974
Adjustment for koma-script. . . . 207

AMS environments: Fix: Groups for lateximages. 591
If pdfLaTeX, require T1 and UTF-8 encoding. 209
picture: overpic: Fix: Groups for lateximages. 540
list: Added list and trivlist. . . 395
LWR@nestspan: Added list and trivlist. 325
v0.45
\@currentHref: Added. 467
\@donoparitem: Modified for HTML. 393
\@item: Modified for HTML. 393
\@mklab: Modified for HTML. 393
\CSSFilename: Improved filenames with underscores. 339
\LWR@LwarpStart: Fix: Lateximages on incorrect pages with Mathjax. 374
\LWR@includegraphicsb: Improved URLs with underscores. 734
\LWR@newautoidanchor: Fix: No anchor if frozen autoid. 473
\LWR@notmemoirloadafter: Added. 197
\LWR@printpendingmpfootnotes: Added. 346
\LWR@startref: Fix: Labels with underscores. 465
\LWR@subhyperref: Improved URLs with underscores. 467
\LWR@subhyperrefclass: Improved URLs with underscores. 467
\LWR@sublabel: Fix: Labels with underscores. 463
\LWR@tabledatacolumntag: Fix: Empty line between rows. 452
\chapter: Add optional heading title for memoir. 367
\newpage: Added. 563
\nolinkurl: Fix: Underscore in URL. 468
\normalmarginpar: Added. 347
\reversemarginpar: Added. 347
\section: Add optional heading title for memoir. 367
\tableofcontents: Fix: Empty sidetoc. 479
Fix: Patch \AtBeginDocument. . . 479
\url: Improved URLs with underscores. 468
General: 2018/01/14 1
array: Added. 604
babel-french: Robust commands. 323
backref: Added. 612
breakurl: Fix: Underscore in URL. 624
changebar: Added. 632
cite: Added. 660
continue: Added. 664
endfloat: Added. 677
epigraph: Support for memoir. . 680
fancyvrb: Improvements. . . 695, 696
flafter: Added. 704
fltrace: Added. 712
footnpag: Added. 720
fwlw: Added. 725
hanging: Added. 744
hyperref: Fix: Underscore in URL. 746, 747
lwarp-patch-memoir: Added. . . . 981
memhfixc: Added. 802
memoir: Added. 573
natbib: Added. 817
pagesel: Added. 837
prettyref: Added. 850
subfigure: Added. 895
subfig: Fix for subcaption end tag. 894
subfig: Fix: Math in subcaptions. 892
textfit: Added. 905
titleref: Added. 917
turnthepage: Added. 941
Allows memoir's preloaded packages. 200
Docs: xparse warnings. 170
Docs: Fix for double hyphens. . . . 91
Docs: Improved install instructions. 92
Docs: Improved MiKTEX install instructions. 88
Docs: Moved table so doesn't interfere with install docs. 87
File: lwarp_mathjax.txt: Allow MATHJAX inside tabbing. 291
File: lwarp_mathjax.txt: Allow MATHJAX inside verse. 291
Fix: Empty sidetoc. 479
Improved: Robust \, \ , and \textellipsis commands. 562
Separate LWR@thisautoidWP for word processor s. 473
thebibliography: Patched to emphasize titles. 489
minipage: Fix: Improper \prevdepth. 542, 545
v0.46
\LWR@closeparagraph: Fix: Tabular empty lines. 335
\LWR@closeprevious: Fix: Stack unnesting. 321
\LWR@forcenewpage: Fix: Improper \prevdepth. 321
\LWR@lookforpackagename: Fix: Spaces in \usepackage. 227
\LWR@providelength: Added. 210

\LWRPrintStack: Name changed from \PrintStack. 320
\popclose: Fix: Stack unnesting. . . 312
\pushclose: Fix: Stack unnesting. . 312
General: 2018/01/23 1
LWR@tabularpardepth added. . . 403
amsthm: Adapted to trivlist changes. 599
mdframed: Fixes for SVG math or lateximage in title. 797
mdframed: Fixes for footnotes. . 797
ntheorem: Adapted to trivlist changes. 824
theorem: Adapt to trivlist changes. 908, 909
tabular: Fix: Tabular empty lines. 457, 458
list: Fix: Stack unnesting. 396
v0.47
\LWR@HTML@caption@begin: Fix: Argument passed to \LWR@origcaption@begin. 475
\LWR@LwarpStart: Fix for SVG math in \nameref. 375
\LWR@WPcell: Fix: Line wrap at HTML hyphen. 431
\LWR@createautosec: Fix: Line wrap at HTML hyphen. 359
\LWR@domulticolumn: Fix: Line wrap at HTML hyphen. 441
\LWR@floatbegin: Fix: Line wrap at HTML hyphen. 471
\LWR@htmlclosecomment: Add \mbox to prevent line breaks. 326
\LWR@newautoidanchor: Fix: Line wrap at HTML hyphen. 473
\LWR@printopenlist: Fix: Line wrap at HTML hyphen. 393
\LWR@startref: Fix: Line wrap at HTML hyphen. 464
\LWR@sublabel: Fix: Line wrap at HTML hyphen. 463
\LWR@subsingledollar: Added SVG math image baseline adjust and em sizing. 498
Fix: Line wrap at HTML hyphen. . 501
\captionlistentry: Fix: Line wrap at HTML hyphen. 476
\hypertoc: Fix: Line wrap at HTML hyphen. 483
\hypertocfloat: Fix: Line wrap at HTML hyphen. 484
General: 2018/01/30 1
adjmulticol: Fix: Line wrap at HTML hyphen. 584
blowup: Added. 621
caption: Added. 628
caption: Also loads lwarp-caption. 230
changepage: Fix for pagecheck macros. 633
endheads: Added. 677
epigraph: Fix: Line wrap at HTML hyphen. 680
hanging: Fix: Line wrap at HTML hyphen. 745
hang: Fix: Line wrap at HTML hyphen. 743
keyfloat: Fix for SVG math in captions. 764
midpage: Fix: Line wrap at HTML hyphen. 806
multirow: Fix: Line wrap at HTML hyphen. 811
multitoc: Added. 814
ntheorem: Fix: Line wrap at HTML hyphen. 828
realscripts: Fix: Line wrap at HTML hyphen. 856
scrextend: Fix: Line wrap at HTML hyphen. 864
sectionbreak: Added. 872
sidenotes: Fix for SVG math in captions. 877
subfig: Fix for SVG math in captions. 892
subfig: Fix: Support \nameref. . . 891
xurl: Added. 976
lwarpmk: *pdfcrop*: Removed hires option for improved crop accuracy. 293
lateximage: Added CSS style option. 522
Fix: Line wrap at HTML hyphen. . 526
center: Fix: Line wrap at HTML hyphen. 527
minipage: Fix: Line wrap at HTML hyphen. 543
flushleft: Fix: Line wrap at HTML hyphen. 528
flushright: Fix: Line wrap at HTML hyphen. 527
enumerate: Fix: Line wrap at HTML hyphen. 397
itemize: Fix: Line wrap at HTML hyphen. 396
LWR@BlockClassWP: Fix: Line wrap at HTML hyphen. 330
v0.48
\@@@setcpageref: Fix for new v0.21 of cleveref. 538

\@@@setcref: Fix for new v0.21 of cleveref. 537
\@@@setcrefrange: Fix for new v0.21 of cleveref. 538
\@biblabel: Improved bibliography label. 489
\@item: Honors \makelabel. 393
\@maketitle: Fix: Errors with IEEEtran class. 384
\LWR@LwarpStart: Adjusted space around captions. 373
\LWR@ProvidesPackageDrop: Fix: Options with braces. 229
\LWR@addtabularhrulecolor: colortbl: Added. 432
\LWR@addtabularrulecolors: colortbl: Added. 433
\LWR@closetabledatacell: colortbl: Added. 406
\LWR@includegraphicsb: Fix: Virtual page size limited to a group. 734, 737
\LWR@lookforpackagename: Fix: Parsing similar package names. . 226
\LWR@newautopagelabel: Fix: TOC, LOF, LOT links. 352
\LWR@newhtmlfile: Fix: TOC, LOF, LOT links. 356
\LWR@nullfonts: Fix: \newline in title. 554
\LWR@parsedrequirepackagenames: Fix: Parsing similar package names. 225
\LWR@parsetablecols: Fix: Ignore optional tabular column arguments. 419
\LWR@restoreorigformatting: Fix: Spacing in SVG math, lateximage, Ti*k*z. 490
\LWR@section: Fix: TOC, LOF, LOT links. 365
\LWR@tabledatasinglecolumntag: colortbl: Added. 426
\LWR@textcurrentfont: Added. Improves font control. 558
\bibliography: Fix: \BaseJobname for bibliography. 489
\centerline: Added. 529
\l@part: Adapts to classes without \part. 484
\leftline: Added. 529
\mbox: Nullified for HTML. 546
\rightline: Added. 529
\thempfootnote: Removed \itshape. 345
General: 2018/02/14 1
acronym: Added. 583
acro: Added. 581
chapterbib: Added. 634
colortbl: Added. 421, 432, 662
fancyref: Now directly supported. 693
hypcap: Added. 745
hypernat: Added. 746
hyperref: \texorpdfstring now uses the TEX string. 750
luatodonotes: Improved \todototoc. 787
siunitx: Changes fraction to symbol. 881
siunitx: Improved SVG math. 879, 881
siunitx: Improved color output. . 879
stfloats: Added. 889
todonotes: Improved \todototoc. 937
vmargin: Added. 950
xfrac: Fix: Added groups around super/subscripts to localize LWR@nestspan changes. 969
Docs: Converting an existing document. 107
Improved font control. 558
tabular: colortbl: Added. 456
lateximage: Print mode boxed to natural width. 527
abstract: Allow optional name. . . . 386
v0.49
\LWR@addtabularcellcolor: xcolor: Added tabular row colors. 435
\LWR@domulticolumn: xcolor: Added tabular row colors. 442
\LWR@printlength: Fix: Group printlen changes. 224
\affiliation: Fix: Adapts to classes which already provide. 379
\href: Fix: Adapt to classes. 468
\noalign: Fix: \noalign inside tabular. 453
\url: Fix: Adapt to classes. 468
General: 2018/02/19 1
amsmath: Fix: Patches for \eqref. 590
eso-pic: Fix for \AddToShipoutPicture. 686
figsize: Added. 701
fnlineno: Added. 714
hypdestopt: Added. 745
hyphenat: Added. 751
lineno: Added. 773
luacolor: Added. 786
pagegrid: Added. 837
pdfrender: Added. 843
resizegather: Added. 860
vertbars: Added. 950
vwcol: Added. 952

xcolor: Added tabular row colors. 421, 965
Fix: Adapt to classes. 562
v0.50
\@ensuredmath: Fix: Use lateximage even if MathJax. 505
Improved SVG math alt tags. . . . 505
\LWR@@footnotetext: Robustify macros. 343
\LWR@atbeginverbatim: Improved column alignment. 389
\LWR@doequation: Improved SVG math display. 509
\LWR@doubledollar: Improved SVG math alt tags. 503
Improved SVG math display. 503
\LWR@htmlrefsectionfilename: Fix: SVG math in a section name. . . 318
\LWR@newhtmlfile: Fix: SVG math in a section name. 355
\LWR@nullfonts: Fix: \underline in sectioning file name. 557
\LWR@overline: Added. 561
\LWR@subsingledollar: Fix: Use lateximage even if MathJax. . . . 498
Improved SVG math alt tags. . . . 498
MD5 hash avoids duplicate SVG math. 501
\LWR@vspace: Robustify macros. . . . 566
\newline: Robustify macros. 563
\textsubscript: Robustify macros. 560
\textsuperscript: Robustify macros. 560
General: 2018/03/03 1
lwarp.css: Improved SVG display math centering. 251
lwarp_one_limage.txt: Added. . 290
amsmath: Fix: Upright tags for SVGmath. 590
axodraw2: Added. 611
bytefield: Added. 627
dblfloatfix: Added. 669
diagbox: Added. 670
epstopdf: Added. 682
listings: Force flexible columns. . 776
morefloats: Added. 807
nonfloat: Added. 821
ntheorem: Fix: Not standard nor amsthm selected. 830
pbox: Added. 839
phfqit: Added. 846
schemata: Added. 863
siunitx: Fix: Loads xcolor. 879
siunitx: Improved SVG math alt tags. 881
siunitx: Improved units. 530, 879, 882
xy: Added. 976
lwarpmk: Error if lateximages.txt does not exist. 293
lwarpmk: Error if lwarpmk.conf points to lwarp. 293
lwarpmk: Improved error messages. 293
lwarpmk: MD5 hash avoids duplicate SVG math. 293
lwarpmk: Multiprocess support making lateximages. 293
AMS environments: Improved SVG math display. 591
Fix: Load fontspec if necessary. . 221
Robustify macros. 558
lateximage: Fix: SVG math in a section name. 525
MD5 hash avoids duplicate SVG math. 524, 526
eqnarray: Improved SVG math display. 515
v0.51
\@ensuredmath: Hashes \ensuremath. 505
\@item: Restored list label space. . . 394
\LWR@HTMLsanitize: Fix: Escapes double quotes. 519
\LWR@HTMLsanitizeexpand: Fix: Escapes double quotes. 519
\LWR@LwarpStart: MathJax: Nullifies \ensuremath. 375
\LWR@addbaselinemarker: Improved SVG math baseline. 496
\LWR@atbeginverbatim: Adds vertical offset. 389
\LWR@customizeMathJax: MathJax: Nullifies \ensuremath. 353
\LWR@doequation: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 509
\LWR@doubledollar: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 503
\LWR@findcurrenttextcolor: Added \LWR@findcurrenttextcolor when no xcolor. 561
\LWR@newautoidanchor: Fix: No autoid is inside a lateximage. . . 473
\LWR@newhtmlfile: MathJax: Nullifies \ensuremath. 357
\LWR@subsingledollar: Fix: \ensuredmath inside SVG image. 498
Fix: lateximage inside $\mathcal{AMS}$ \text. 499

Fix: Honors text font around SVG math. 499
Fix: SVG math with enclosed latexmage. 499
Improved SVG math baseline. . . . 500
SVG math baseline improved with invisible rule at corner. 502
Typeset SVG math only once during measurement. 499
\LWR@textcurrentcolor: xcolor: \LWR@textcurrentcolor if xcolor not loaded. 561
\addcontentsline: Add missing support for float mechanism if necessary. 477
No anchor ID if inside SVG image. 477
\displaymathnormal: Processing for complicated display math. 511
\displaymathother: Processing for complicated display math. 512
\textcolor: Fix: SVG math color. . . 961
General: 2018/03/24 1
HTML entity used for text dollar. . 496
lwarp_one_limage.txt: *pdftocairo* -noshrink added. 290
afterpackage: No longer required. 222
chemfig: Added. 635
chemformula: Added. 636
chemgreek: Added. 640
chemmacros: Added. 641
chemnum: Added. 659
epstopdf-base: Added. 682
fancybox: Fix: Optional tag for \item in a span. 691
grid: Added. 742
listings: Forces cleared options. . 776
ltxgrid: Added. 785
mhchem: Added. 803
tikz: Fix for \tikz macro. 913
tikz: Fix for tikz with optional argument. 913
titling: Fix for \thanks mark. . . . 923
lwarpmk: *pdfcrop*: Restored hires option. 293
lwarpmk: *pdftocairo* -noshrink added. 293
AMS environments: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 591
Docs: tikz limitations. 157
Docs: Multiple authors and affiliations. 135
Docs: Things to avoid. 125
Docs: Updated Converting an existing document. 107
Fix: Remember original \# in case is redefined. 241
latexmage: Added additional hashing option. 522
Fix: latexmage inside $\mathcal{AMS}$ \text. 523
Processing for complicated display math. 525
alignat: Fix: Added. 595
eqnarray: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 515
LWR@displaymathother: Processing for complicated display math. . . 506
LWR@equationother: Processing for complicated display math. 506
v0.52
\@ensuredmath: Improved hashing expansion. 505
\@mpfootnotetext: Fix: Paragraph handling. 345
\CustomizeMathJax: Added. 353
\LWR@@footnotetext: Fix: Paragraph handling. 344
\LWR@addbaselinemarker: Warnings if lwarp_baseline_marker.png is not present or if graphicx/s not loaded. 496
\LWR@customizedMathJax: Added. . 352
\LWR@doequation: Fix: equation* now based on equation instead of displaymath. 509
Fix: equation* with split. 509
\LWR@filenamenoblanks: Fix: \FileDepth with non-utf8 encoding. 351
\LWR@nullfonts: Fix: \texorpdfstring in section names. 557
\LWR@section: Fix: Footnote numbering: Limited HTML comment if starred. 362
Fix: Footnote numbering: Use short TOC entry for HTMLDebug comments. 362
\LWR@subsingledollar: Added user-adjustable SVG math font scaling. 500
\LateximageFontScale: Added user-adjustable SVG math font scaling. 518
\href: Fix: #, %, &, ~, _ in URL. . . . 468
\nolinkurl: Fix: #, %, &, ~, _ in URL. 468

\theHTMLTitleSeparator: Fix: \FileDepth with non-utf8 encoding. 369
\url: Fix: #, %, &, ~, _ in URL. 468
General: 2018/04/01 1
breakurl: Fix: #, %, &, ~, _ in URL. . 624
endfloat: Updated for v2.6. 677
fancyvrb: Initial support for \VerbatimFootnotes. 689, 695
hyperref: Fix: #, %, &, ~, _ in URL. 746–749
nicefrac: Added. 820
url: Added. 947
lwarpmk: Fix: Memory overflow when spawning tasks. 293
lwarpmk: Fix: Skip image generation if from page 0. 293
Changed FootnoteDepth default to \subsbusection. 342
Docs: Improved install instructions. 89
Fix: MathJax script line wraps. Reduced right margin. 222
If pdfLaTeX, allow other input encoding. 209
pkggraphics: Added defaults. 731, 732
pkggraphicx: Updated for v1.1a. . 732
pkggraphicx: Updated for v1.1b. . 732
Restore \kill in a lateximage. . 783
tabbing: Fix to allow inside lateximage. 391
lateximage: Fix for hash expansion. 524
v0.53
General: 2018/04/01 1
lwarpmk: Added **lwarpmk cleanlimages**. 293
lwarpmk: Added warning for corrupted images. 293
Docs: **lwarpmk cleanlimages**. . . 105
Docs: **lwarpmk pdftohtml**. 105
v0.54
\LWR@afterendverbatim: Added vspace argument. 390
\LWR@atbeginverbatim: Improved column alignment. 389
\LWR@earlyloadnever: Added. 199
\LWR@endfloatalignment: Honor \centering, etc. in floats. 473
\LWR@floatalignment: Honor \centering, etc. in floats. 473
\LWR@floatbegin: Honor \centering, etc. in floats. 471
\LWR@floatend: Honor \centering, etc. in floats. 472
\LateximageFontSizeName: Defaults to normalsize. 518
\centering: Added debug comment. 528
\raggedleft: Added debug comment. 528
\raggedright: Added debug comment. 528
General: 2018/04/22 1
*.lwarpmkconf: Option IndexLanguage changed to xindyLanguage. 251
*.lwarpmkconf: Option pdftotextEnc added. 251
*.lwarpmkconf: Option xdyFilename changed to xindyStyle. 251
*.lwarpmkconf: Option xindyCodepage added. 251
lwarp.css: Fix: Text-decoration-skip: auto. 251
lwarpmk.conf: Option IndexLanguage changed to xindyLanguage. 251
lwarpmk.conf: Option pdftotextEnc added. 251
lwarpmk.conf: Option xdyFilename changed to xindyStyle. 251
lwarpmk.conf: Option xindyCodepage added. 251
bibunits: Added. 618
chngpage: Added. 660
forest: Added. 720
glossaries: Fix when not using babel or polyglossia. 728
gridset: Added. 742
hyperref: Fix: \hyperref and \hyperlink with special chars in text. 748, 749
hyperref: Fix: \ref in \hyperref and \hyperlink caused nested link. 748, 749
lwarp-patch-memoir: Update for v3.7g. 986
magaz: Added. 788
ragged2e: Fix: \centering, etc. . 855
textcomp: Fix for \textperthousand. 902
tikz: Fixes for \pgfpicture, minipages, fit, align, font. 913
lwarpmk: Added pdftotextenc. . 293
lwarpmk: Added xindycodepage. 293
lwarpmk: Changed language to xindylanguage. 293
lwarpmk: Changed xdyfile to xindystyle. 293

lwarpmk: Improved error if configuration file does not exist. 293
lwarpmk: Increased prominence for error for an unknown command. 293
lwarpmk: Verifies HTML version exists before lwarpmk limages. . 293
lwarpmk: Verifies image references before lwarpmk limages. 293
Add: pdftotextEnc. 216
Add: xindyCodepage. 216
Added early check for disallowed packages. 199
Docs: BibTeX. 137
Docs: Macros in sectioning names. 125
Never load aecompl. 199
Option IndexLanguage changed to xindyLanguage. 216
Option xdyFilename changed to xindyStyle. 216
verse: Fix: Line spacing. 388
v0.55
\LWR@LwarpStart: Fix: Overfull boxes in lateximages. 373
\LWR@floatbegin: Fix: Float optional args. 471
\LWR@nullfonts: Removed extraneous space which appeared in file links. 557
\phantomsection: Fix: \ForceHTMLTOC with \phantomsection. 569
General: 2018/04/26 1
clrdblpg: Added. 661
Fix: \centering, etc. for koma-script. 471
Fix: QED symbols in lateximage. 600, 834
v0.56
\LWR@addcdashline: arydshln: Added. 431
\LWR@addmulticolvertrulecolor: Adds support for dashed vertical rules. 439
Adds support for double vertical rules. 439
\LWR@addtabularhrulecolor: Adds support for arydshln dashed rules. 432
Adds support for double \hlines and \midrules. 432
\LWR@addtabularrulecolors: Adds support for dashed vertical rules. 433
Adds support for double vertical rules. 433
\LWR@closeparagraph: Added support for parnotes. 335
\LWR@domulticolumn: Adds support for dashed vertical rules. 441
Adds support for double vertical rules. 441
\LWR@floatbegin: Adds a <class> per float package style. 471
\LWR@multicolpartext: Fix: \multicolumn parameters. 437
\LWR@openparagraph: Added support for parnotes. 333
\LWR@parsebarcolumn: Adds support for double vertical rules. 413
\LWR@parsecoloncolumn: arydshln: Added. 413
\LWR@parsesemicoloncolumn: arydshln: Added. 414
\LWR@parsetablecols: Added array W column. 420
\LWR@printmccoldata: Added array W column. 438
Fix: \multicolumn parameters. . . 438
\LWR@printmccoltype: Added array W column. 436
Adds support for dashed vertical rules. 436
Adds support for double vertical rules. 436
\LWR@tabledatacolumntag: Fix: \morecmidrules 451
\LWR@textcurrentfont: Added span.textbf, etc. 558
General: 2018/05/12 1
*.lwarpmkconf: Records --shell-escape. 251
lwarp.css: Added div.textbf, etc. 251
lwarp.css: Added span.textbf, etc. 251
lwarpmk.conf: Records --shell-escape. 251
arydshln: Added. 401, 604
lua-check-hyphen: Added. 785
paralist: Fixes for compactenum, compactitem, compactdesc. . . . 838
parnotes: Added. 838
quoting: Added. 855
tocenter: Added. 929
underscore: Added. 945
lwarpmk: Added lwarpmk pdftosvg. 293
lwarpmk: Supports --shell-escape. 293
Added \thinspace. 562

Docs: **lwarpmk pdftosvg**. 105
LWR@blocktextcurrentfont: Added div.textbf, etc. 558
v0.57
\BlockClassSingle: Improved print/HTML output selection. . . 330
\InlineClass: Improved print/HTML output selection. 330
\LWR@customizeMathJax: MathJax: Supports \footnote, \footnotemark. 353
\LWR@ref@ignorestar: subcaption: Fix: \subref. 466
\LWR@subhyperref: Fix: Text catcodes. 467
\LWR@subhyperreftext: Fix: Text catcodes. 467
\LWR@subsingledollar: Fix: Dynamic inline math expressions. 498, 499, 501
\LWR@vspace: Improved print/HTML output selection. 566
\StartDefiningMath: Added. 314
\boxframe: xcolor: Fix: Colored \boxframe. 965
\colorbox: xcolor: New system for switching print and HTML outputs. 961
\colorboxBlock: xcolor: New system for switching print and HTML outputs. 962
\fboxBlock: Improved print/HTML output selection. 548
\fcolorbox: xcolor: New system for switching print and HTML outputs. 962
\framebox: Improved print/HTML output selection. 547
\href: Fix: Text catcodes. 468
\inlinemathother: Added. 315
\listof: Fix: Provide \l@name if not defined. 481
\makebox: Improved print/HTML output selection. 546
\mathimagename: Added. 495
\mbox: Improved print/HTML output selection. 546
\multicolumnrow: multirow: Improved print/HTML output selection. 813
Improved print/HTML output selection. 447
\newfloat: rotfloat: Added float styles. 862
rotfloat: Fix for listof sideways floats. 862
\packagediagramname: Added. 495
\parbox: Improved print/HTML output selection. 545
\raisebox: Improved print/HTML output selection. 551
\reflectbox: Improved print/HTML output selection. 741
\resizebox: Improved print/HTML output selection. 741
\rotatebox: Improved print/HTML output selection. 739
\rule: Fix: Colored rules. 568
\scalebox: Improved print/HTML output selection. 740
\textcolor: xcolor: New system for switching print and HTML outputs. 961
General: 2018/06/06 1
lwarp.css: Added ruled, boxed, boxruled floats. 251
lwarp.css: Increased float vertical margins. 251
algorithm2e: Added. 585
bigdelim: Improved print/HTML output selection. 619
breakurl: Fix: Text catcodes. 624
colortbl: New system for switching print and HTML outputs. . . 662, 663
ellipsis: Added \midwordellipsis. 676
errata: Added. 684
float: Added float styles. 705
float: Fix: Do not pre-define \l@name. 705
ltablex: Added. 784
marginnote: Fix: Long optional argument. 792
multirow: Improved print/HTML output selection. 811
register: Added. 857
subcaption: Fix: \subref. 747
trimclip: Added. 939
vowel: Added. 951
xellipsis: Added. 967
xfrac: Improved print/HTML \scalebox control. 969
xltabular: Added. 971
xpiano: Added. 972
lwarpmk: Improved code factoring. 293
lwarpmk: Improved error handling. 293
Docs: Recompiling *lwarpmk* or CSS files. 185
Docs: Recreating the index for lwarp source. 182

New system for switching print and HTML outputs. 236
minipage: Improved print/HTML output selection. 542
BlockClass: Improved print/HTML output selection. 329
fminipage: Improved print/HTML output selection. 549
LWR@BlockClassWP: Improved print/HTML output selection. . . 330
v0.58
\LWR@HTML@caption@begin: Improved print/HTML output selection. . . 475
\LWR@HTML@caption@end: Improved print/HTML output selection. . . 476
\LWR@HTML@ref: Improved print/HTML output selection. 465
\LWR@doindexentry: Adds support for \see, \seealso, \emph, \textbf, etc. 487
\LWR@hyperindexrefnullified: Adds support for \see, \seealso, \emph, \textbf, etc. 487
\LWR@indexitem: Accepts optional arg for repeatindex. 486
\dotfill: Improved print/HTML output selection. 563
\hfill: Improved print/HTML output selection. 563
\hrulefill: Improved print/HTML output selection. 563
\hyperindexref: Adds support for \see, \seealso, \emph, \textbf, etc. 488
\printindex: Fix: Extra \newpage to flush pending \index writes. . . . 789
General: 2018/07/07 1
*.lwarpmkconf: Added option makeindexstyle. 251
*.lwarpmkconf: Added options makeindex and xindy. 251
*.lwarpmkconf: Generated \AtBeginDocument. 251
lwarp.xdy: Requires makeindex.xdy. 290
lwarp.xdy: Supports bold, italic. 290
lwarp_html.ist: Added. 289
lwarpmk.conf: Added option makeindexstyle. 251
lwarpmk.conf: Added options makeindex and xindy. 251
lwarpmk.conf: Generated \AtBeginDocument. 251
array: Improved print/HTML output selection. 604
attachfile2: Added. 608
attachfile: Added. 607
cases: Added. 631
imakeidx: Added. 754
index: Added. 757
intopdf: Added. 759
lwarp-patch-komascript: Modified indexing. 979
lwarp-patch-memoir: Fix for \specialindex. 1002
lwarp-patch-memoir: Fix for multiple indexes. 1002
makeidx: Added. Moved from lwarp core. 789
memoir: Fix for \firsthlline, \lasthline. 448
memoir: Fix for booktabs. 453
pdfpages: Added. 841
pdfx: Added. 845
repeatindex: Added. 860
splitidx: Added. 887
textcomp: Improved print/HTML output selection. 902
lwarpmk: Added makeindex and xindy options. 293
lwarpmk: Added -p option for project name. 293
lwarpmk: Added optional list of names for **lwarpmk printindex** and /cmdslwarpmk htmlindex. . 293
lwarpmk: Glossary generation now uses *makeglossaries*. 293
lwarpmk: **lwarpmk clean** removes all *.ind and *.idx files. 293
Added makeindex option. 217
Added xindy option. 217
Added option makeindexStyle. . 215
Docs: Index, *makeindex*, imakeidx. 139
Docs: Misplaced \omit. 187
Fix: memoir and ccaption. 200
Improved print/HTML output selection. 562
Replaced each \csuse with \@nameuse to force error if undefined. 1
tabbing: Improved print/HTML output selection. 391
v0.59
\LWR@addbaselinemarker: Uses .eps if DVI *latex*. 496
\LWR@includegraphicsb: Fix: Expand filename. 735
Now works with .pdf and .eps filename extensions. 734

\LWR@latexmkcmd: Fix: --shell-escape with *latexmk*. . 246
\LWR@writeconf: Compilation commands now preassigned by lwarp instead of being computed by *lwarpmk*. 250
\[: Fix with \displaymathnormal. . 504
General: 2018/09/07 1
Slunits: Added. 878
accsupp: Added. 581
amsmath: Moved from the lwarp core. 590
asymptote: Added. 606
axessibility: Added. 611
breqn: Added. 625
bxpapersize: Added. 627
canoniclayout: Added. 628
chemformula: Fix for \NMR. 656
draftcopy: Added. 672
epstopdf-base: Improved. 682
epstopdf: Improved. 682
fnbreak: Added. 713
nccfancyhdr: Added. 818
pdftricks: Added. 844
pst-eps: Added. 852
pstricks: Added. 853
units: Added support for MathJax. 945
xunicode: Added. 975
lwarpmk: Added **lwarpmk epstopdf**. 293
lwarpmk: Consolidated compiling options into printlatexcmd and HTMLlatexcmd. 293
lwarpmk: Double insead of single-dashed --shell-escape option. 293
lwarpmk: Error if lwarpmk.conf format changed. 293
lwarpmk: Warning if operating system changed. 293
Added option dvipdfmx. 218
Added option dvipdfm. 218
Added option dvips. 218
Docs: **lwarpmk epstopdf**. 105
File: lwarp_mathjax.txt: Fix: Removed chapter number from tagged non-numeric MathJax equations. 291
File: lwarp_mathjax.txt: Updated to MathJax v2.7.4. 291
picture: Added an alt tag. 540
v0.60
\LWR@clearmidrules: tabular: Fix for midrules. 427
\LWR@parsenormalcolumn: tabular: Improved memory management: Not using xstring. 414
\LWR@tabledatasinglecolumntag: tabular: Improved memory management: Not using xstring. 425
\LWR@tabularendofline: Fix: Slowdown for long tables. 410
General: 2018/09/19 1
tabular: Improved memory management: Global boolean. . 402
tabular: Improved memory management: Not using xstring. 404, 812
2up: Added. 577
booklet: Added. 621
bophook: Added. 623
diagbox: Fix for par tags. 671
draftfigure: Added. 673
fancytabs: Added. 694
fullminipage: Added. 724
grid-system: Added. 742
layaureo: Added. 768
leading: Added. 771
listings: Fix for HTML entities. . . 776
listings: Fix if inside a list. . . 776, 779
thumbs: Added. 912
thumb: Added. 912
widows-and-orphans: Added. . . 955
v0.61
\DeclareGraphicsExtensions: Fix: EPS for DVI LaTeX. 729
\LWR@HTMLLatexCmd: Added HTMLLatexCmd option. 250
Added PrintLatexCmd option. . . 250
\LWR@addcompilecmd: Removed spaces. 246
\LWR@closetabledatacell: Fix: Par tags in tabular. 405
\LWR@hyperindexrefnullified: Made robust, ... 487
\LWR@includegraphicsb: Fix: EPS for DVI LaTeX. 735
Set keys before using filename, for epsfig. 735
\LWRopseq: Added spaces. 213
\RequirePackage: Support up to 20 packages. 228
\inlinemathnormal: Changed name from \StopDynamicMath to \inlinemathnormal. 315
\inlinemathother: Changed name from \StartDynamicMath to \inlinemathother. 315
\listof: Fix: newfloat lists. 481

\lwarpsetup: Added. 214
General: 2018/10/13 1
lwarp.css: Footnotes text align left. 251
lwarp.css: Minipage table and footnotes: tighter margin. 251
chkfloat: Added. 660
cmdtrack: Added. 661
copyrightbox: Added. 664
dprogress: Added. 672
epsfig: Added. 681
lua-visual-debug: Added. 786
pdfprivacy: Added. 843
psfragx: Added. 851
psfrag: Added. 851
pstool: Added. 852
refcheck: Added. 857
srcltx: Added. 888
srctex: Added. 888
supertabular: Fix for caption w/o opt arg. 896
thinsp: Added. 910
threadcol: Added. 910
uspace: Added. 948
vpe: Added. 951
xbmks: Added. 956
xtab: Fix for caption w/o opt arg. 974
Added HTMLLatexCmd option. . . . 217
Added PrintLatexCmd option. . . 217
Docs: \tracinglwarp 232
Docs: HTML entities. 125
Docs: Compiling using custom shell commands. 171
Docs: Fonts. 108
Docs: HTMLDebugComments 114, 232
Docs: Multiple indexes. 192
Don't write configuration files if processing pstool image. 244
Spaces redefined \AtBeginDocument. 562
v0.62
\@partcntformat: Added for ctex. . 360
\@partnameformat: Added for ctex. 360
\InlineClass: Added optional word-processing style. Replaces \LWR@HTMLtextstyle. 330
\LWR@PreloadedPackage: Added. . . 529
\LWR@ProvidesPackagePass: Fix: Unknown option error. 229
\LWR@endofline: Extra space if optional arg. 563
\LWR@filestart: Refactored. 371
\LWR@includegraphicsb: Fix: FormatWP. 735
Fix: Filename expansion. 736
\LWR@isolate: Added. 211
\LWR@textcurrentfont: Added print version. 561
Tracks depth to avoid nesting repeated font changes. 558
\colorboxBlock: Fix: Horiz white space. 962
\fcolorbox: Fix: No longer requires xifthen. 534
\fcolorboxBlock: Fix: Horiz white space. 963, 964
\l@chapter: Don't define if no \chapter. Fix for algorithm2e. . 485
\slshape: Added. 559
\textup: Fixed WP span class. 553
\theHTMLSection: Added. 369
\theHTMLTitleSection: Added. . . . 369
\theHTMLTitleSeparator: Refactored. 369
General: 2018/11/19 1
\textbf and related: Improved font detection. 551
lwarp.css: Added css for xfrac, nicefrac. 251
lwarp.css: Fixed css for \textup. 251
lwarp.css: Reduced margins in titlepage. 251
lwarp_formal.css: Fix: Font for verse. 285
2in1: Added. 577
CJKutf8: Prevented unless xeCJK. 661
CJK: Prevented unless xeCJK. . . 661
asymptote: Improved alt tags. . 606
bitpattern: Added. 620
calc: Fix: Required for print version. 222
chngpage: Fix: Loads lwarp-chngpage. 660
ctexpatch: Added patch. 575
flippdf: Added. 704
musicography: Added. 814
nicefrac: Improved font control and css, honors nice, ugly. . . . 820
notespages: Added. 823
octave: Added. 835
pdfcomment: Added. 840
pdfmarginpar: Added. 840
register: Updated to v1.8. 857
rviewport: Added. 863
semantic-markup: Added. 873
textcomp: Fix conflict with xunicode. 903
tram: Added. 938
twoup: Added. 941

ulem: Improved compatibility with CJKulem. 943
ulem: Now works in a lateximage. 943
unitsdef: Added. 946
units: Improved font control and css, honors loose, tight. 945
xechangebar: Added. 967
xfrac: Improved css. 969
xunicode: Fix conflict with textcomp. 975
Added early checks for CJK, CJKutf8. 199
Docs: asymptote. 159
Docs: miktex-poppler-bin-* 92
Docs: *MiKTeX Console* 88
Docs: Improved MiKTEX install instructions. 88
Docs: UTF-8 locale. 174
File: lwarp_mathjax.txt: Removed inoperable siunitx extension. . . 291
Fix for \em. 554
Fix: Horiz white space. 964
Logos: CSS instead of <sup>, <sub>. 570
Logos: Fix for XƎTEX logo if graphics is not loaded. 572
Logos: Improved CSS. 570
Logos: Made robust. 570
fcolorminipage: Fix: Horiz white space. 964
Fix: No longer requires xifthen. . 535
fminipage: Fix: Horiz white space. . 550
LWR@blocktextcurrentfont: Added print version. 561
v0.63
\LWR@HTMLLatexCmd: ujarticle and related: Compile options. 250
\LWR@LwarpStart: Fixes for xeCJK. 372
\LWR@atbeginverbatim: Fix for xeCJK. 389
\LWR@checkloadbefore: Added. . . . 198
\LWR@checkloadfilename: Added to reduce number of lwarp-* files. 225
\LWR@checkloadnever: Added. 198
\LWR@compileuplatex: Added. 247
\LWR@createautosec: Fix for xeCJK. 359
\LWR@earlyclassloadnever: Added. 199
\LWR@filestart: Fix: Break ligature for luatexko. 371
\LWR@firstoffour: Added. 211
\LWR@htmlclosecomment: Fix: Break ligature for luatexko. 326
\LWR@isolate: Fix for xeCJK. 211
\LWR@notltjloadafter: Added more classes. 197
Added. 197
\LWR@subhtmlelementclass: Fix for xeCJK. 327
\LinkHome: Fix: Print version. 319
\linkhomename: Added. 319
General: 2018/12/03 1
lwarp.css: Added css for vertical writing. 251
lwarp.css: Improved css for mdframed. 251
amsthm, mdframed: Fix for enforced load order. 597
emumitem: v3.6: Nullifiy \DrawEnumitemLabel. 679
everyhook: Fix for bxjs* classes. . 223
geometry: Fix for bxjs* classes. . 222
mdframed: Avoid thin rules. . . . 795
mdframed: Improved font control. 798–800
stfloats: Adapted to ltj* classes. . 889
xpinyin: Added. 973
zhlineskip: Added. 977
Added pTEXsupport. 196
Docs: \linkhomename. 114
Docs: \sidetocname. 116
Fix: Default \LWR@mdfive. 208
Improved titles. 798
pTEX: Encoding. 209
pTEX: Load upquote. 210
pTEX: No newunicodechar. 210
LWR@BlockClassWP: Fix for xeCJK. . 330
v0.64
\LWR@HTMLLatexCmd: utarticle and related: Added. 250
\LWR@checkloadfilename: Prevented bitfield, doublespace, newthm, rplain, si. 225
\LWR@section: Support for ujarticle and related. 363
\enskip: Made robust. 564
\qquad: Made robust. 564
\quad: Made robust. 564
\theHTMLTitleSeparator: Added utarticle and related. 369
General: 2018/12/08 1
addlines: Updated to v0.3. 585
biblatex: Added patch for CTEX. . 617
bsheaders: Added. 626
gmeometric: Added. 728
marginal: Added. 791
rmpage: Added. 860
scrlayer-scrpage: Fixes. 869
scrlayer: Fixes. 868
scrpage2: Added. 870

ujarticle and related: Improved \today. 574
Added utarticle and related. . . . 574
v0.65
\LWR@LwarpEnd: Improved CSS for page layout. 376
\LWR@LwarpStart: Improved CSS for page layout. 374
\LWR@PreloadedPackage: \AtBeginDocument to avoid option clashes. 529
\LWR@hyperindexrefnullified: Added \textsi. 487
\LWR@includegraphicsb: graphics: Added \includegraphics alt key. 735, 737
\LWR@newhtmlfile: Error if duplicate file name. 355
Improved CSS for page layout. 354, 357
\LWR@nullfonts: Added \sishape. . 555
Added \textsi. 554
\LWR@restoreorigformatting: Added \sishape. 490
Fix: tabular*. 491
\enskip: Changed to Unicode EN SPACE. 564
\quad: Changed to Unicode EM SPACE. 564
\sishape: Added \sishape. 559
\textsi: Added. 553
General: 2018/12/22 1
lwarp.css: Added \sishape, \textsi. 251
lwarp.css: Improved CSS for page layout. 251
lwarp.css: Improved CSS for quotations. 251
lwarp.css: SideTOCto left for improved \marginpars. 251
lwarp_formal.css: SideTOCto left for improved \marginpars. 285
lwarp_sagebrush.css: SideTOCto left for improved \marginpars. . 280
bounddvi: Added. 624
embrac: Added. 676
footnoterange: Added. 719
gentombow: Added. 725
geometry: Fix for bxjs* classes. . 222
graphics: Added \includegraphics alt key. 533, 730, 731, 733
lltjext: Added. 780
multicolrule: Added. 810
multicol: Added \docolaction. . 810
plarydshln: Added. 848
plextarydshln: Added. 849
plextcolortbl: Added. 849
plext: Added. 848
pxatbegshi: Added. 853
pxeveryshi: Added. 853
pxftnright: Added. 853
pxjahyper: Added. 854
tascmac: Added. 899
versonotes: Added. 950
Added \sishape. 241
Added early checks for jarticle, tarticle, and related. 199
Fix for \rensuji. 574
Fix space between class and id. . 331
tabular: Added support for plext. . 454
Fix: tabular*. 454
Fix: Rule color. 456
minipage: Refactored to later allow Japanese <t/y> argument. 542
LWR@figcaption: Uses <figurecaption> instead of <figcaption>. 475
v0.66
\@mpfootnotetext: Improved HTML formatting. 344
\IgnoreMinipageWidths: Added, . . 542
\LWR@@footnotetext: Improved HTML formatting. 343
\LWR@LwarpStart: Fix: TOC, LOF, LOT links. 375
\LWR@checkloadfilename: Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 225
\LWR@closeparagraph: Fix: Combined span, tabular, and lateximage. 335
Improved HTML formatting. 334
\LWR@closeparagraph@br: Factored. 334
\LWR@fboxstyle: Use current text color. 548
\LWR@filenamenoblanks: Fix: Section names detokenized. 350
Fix: Section names with macros. 350
Fix: Section names with percent. 350
Improved file name generation. . 349
Limits filename length. 352
\LWR@findcurrenttextcolor: Fix: Color if xcolor not loaded. 561
\LWR@htmlfileref: No longer use zref. 462
\LWR@htmlsectionfilename: Sanitize underscores. 317
\LWR@includegraphicsb: Improved HTML formatting. 734
\LWR@indentHTML: Added. 324

\LWR@lateximagedepthref: No longer use zref. 462
\LWR@lateximagenumberref: No longer use zref. 462
\LWR@lwarplabel: No longer use zref. 462
\LWR@nameref: No longer use zref. . 462
\LWR@nullfonts: Logos. 557
\LWR@openparagraph: Improved HTML formatting. 333
\LWR@section: Fix: TOC, LOF, LOT links. 365
Improved HTML formatting. 365
\LWR@setexparray: Fix with \par. . 313
\LWR@setref: No longer use zref. . . 462
\LWR@simplifyname: Added. 349
\LWR@startref: No longer use zref. 464
\LWR@stoppars: Improved HTML formatting. 337
\LWR@subhtmlelementclass: Improved HTML formatting. . . . 327
\LWR@subhyperrefclass: Improved HTML formatting. 467
\LWR@subinlineimage: Improved HTML formatting. 469
\LWR@writeconf: Added ImagesDirectory and ImagesName. 250
\LinkHome: Fix: Document cross-references. 319
\UseMinipageWidths: Added, ... 542
\fbox: Fix: Removed extra space. . . 548
\hyperindexref: Fix: Long index entries. 488
\minipagefullwidth: Made \global. 542
\rotatebox: Improved HTML formatting. 739
\rule: Improved HTML formatting. . 568
\scalebox: Improved HTML formatting. 740
\textgreater: Made robust. 316
\textless: Made robust. 316
General: 2019/02/08 1
LWR@currentautosec: Fix for LOF, LOTfloat in home page. 361
lwarp.css: Added niceframe. . . 251
lwarp.css: Improved CSS for definition lists. 251
lwarp_formal.css: Improved CSS for table notes. 285
lwarp_one_limage.txt: Image directory and prefix. 290
acronym: Fix for acronym in caption. 583
acronym: No longer uses zref. . . 583
ar: Added. 602
caption: Fix for options clash. . . 230
ed: Added. 675
extramarks: Updated to v3.10. . . 687
fancyhdr: Updated to v3.10. . . . 693
kotexutf: Patch for references. . . 576
memoir: Docs re: version numbers. 166
multicolrule: Updated for v1.2. . 810
nameauth: Added. 816
register: Verified for v1.9. 857
subcaption: Added. 890
tocbasic: Updated to v3.26a. . . . 925
truncate: Added. 941
zref: No longer used. 224
lwarpmk: Added ImagesDirectory and ImagesName. 293
lwarpmk: Fix for **cleanlimages**. . 293
Added early checks for colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 199
Added option ImagesDirectory. 215
Added option ImagesName. 215
Added support for indentfirst. . . 338
Docs: Updated Converting an existing document. 107
Fix: Minipages inside multicols. 809
Improved HTML formatting. . 689, 696
Package dates added where possible. 577
Sanitize filenames. 219
tabular: Fix: Minipages inside tabular. 457
lateximage: Adds \BaseJobname for multiple projects. 522
Improved HTML formatting. 524
minipage: Honor \LWR@forceminipagefullwidth. 544
v0.67
\FilenameNullify: Added. . . . 558, 561
\FilenameSimplify: Added. . . 349, 353
\LWR@doequation: xfakebold: Added support. 510
\LWR@doubledollar: xfakebold: Added support. 504
\LWR@filenamenoblanks: Improved file name generation. 349
\LWR@lookforpackagename: easyReview: Supported. 227
\LWR@nullfonts: Add'l symbols. . . 555
\LWR@simplifycustom: Added. . . . 349
\LWR@subsingledollar: xfakebold: Added support. 498, 502
General: 2019/02/23 1
academicons: Added. 580

bbding: Added. 612
changes: Added. 633
color: Fix for version number. . . 662
dingbat: Added. 671
eurosym: Added. 686
fitbox: Added. 701
fontawesome5: Added. 716
fontawesome: Added. 715
foreign: Added. 720
gloss: Added. 726
karnaugh-map: Added. 759
marvosym: Added. 792
multicap: Added. 808
nomencl: Added. 821
notes: Added. 822
pifont: Added. 847
struktex: Added. 889
textcomp: Nullify in filenames. . 904
typicons: Added. 942
umoline: Added. 944
xfakebold: Added support. 496
xfakebold: Added. 968
xunicode: Nullify in filenames. . 975
AMS environments: Added xfakebold support. 591
`eqnarray`: xfakebold: Added support. 515, 516
v0.68
`\LWR@@footnotetext`: Factored for multiple foot boxes. 343
`\LWR@checkloadfilename`: Prevented alg, algorithmic, fncylab, pdfcprot. 225
`\LWR@printpendingfootnotes`: Factored for multiple footnote boxes. 346
`\LWR@tabular@warpprintonly`: Added. 454
General: 2019/03/05 1
bigfoot: Added. 619
fnpara: Added. 714
footnotebackref: Added. 719
hyperref: Fix for options with braces. 746
layouts: Added. 768
listings: Fix for listings v1.7. . . . 779
longtable: Improved error handling. 783
manyfoot: Added. 789
niceframe: Added. 820
perpage: Added. 845
showtags: Added. 876
tablefootnote: Added. 898
threeparttablex: Added. 911
threeparttable: Fix for caption type. 910
lwarpmk: Improved error handling if incomplete compile. 293
Prevented alg, algorithmic, fncylab, pdfcprot. 199
`tabular`: Fix: `\warpprintonly` inside `tabular`. 456
v0.69
`\LWR@maybetocdata`: Added support for tocdata. 482
`\framebox`: Fix: Handle paren arg. . 547
`\hypertoc`: Added support for tocdata. 483
`\hypertocfloat`: Added support for tocdata. 484
`\makebox`: Fix: Handle paren arg. . . 546
`\multicolumnrow`: multirow: Error if `\multirow` without `\mrowcell`. . 813
General: 2019/03/21 1
array: Fix for `\tabularnewline`. 604, 783
ctable: Added. 665
eqlist: Added. 683
eqparbox: Added. 683
ftcap: Added. 723
graphics: Warning if using `scale` option. 731
keyfloat: Updated for v2.00. 762
listliketab: Added. 779
minitoc: Added. 806
multirow: Error if `\multirow` without `\mrowcell`. 811
rotfloat: Requires graphicx. 861
supertabular: Fix: Clear caption after use. 897
tabularx: Require array. 898
tabulary: Require array. 899
tocdata: Added. 928
topcapt: Added. 938
xtab: Fix: Clear caption after use. 974
Error if used a tabular * column. 415
`tabular`: Error if `\multirow` without `\mrowcell`. 455, 457, 459
`lateximage`: Fix for *pdftotext* errors from font size change. 526
`fminipage`: Honors `\minipagefullwidth`. 550

Index of Objects

This is an index of macros, environments, booleans, counters, lengths, packages, classes, options, keys, files, and various other programming objects. Each is listed by itself, and also by category. In some cases, they are further subdivided by [class].

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

Symbols

\$ *496*
\& *316*, 7147
\(. 9616
*-images.txt (file) *522*
*_html.aux (file) *352*, *459*, *460*, *522*
*_html.lof (file) *474*
*_html.lot (file) *474*
*_html.tex (file) *245*
\, ... *126*
--shell-escape (option) *108*
\@@@setcpageref 10396
\@@@setcref 10359
\@@@setcrefrange 10373
\@author *377*
\@begintheorem 6811
\@biblabel 9274
\@captype 8889
\@chapcntformat 6014
\@currentHref 8724
\@currentlabelname 8583
\@date *377*
\@dlbfloat 8855
\@donoparitem 6837
\@endtheorem 6823
\@ensuredmath 9626
\@float 8855
\@fnsymbol 6600
\@footnotetext 5590
\@include 1090
\@item 6850
\@makecaption 8910
\@makefnmark 5557
\@makefntext 5556
\@maketitle 56, 6623
\@mklab 6831
\@mpfootnotetext 5592
\@nbitem 6917
\@opargbegintheorem 6817
\@partcntformat 6015
\@partnameformat 6016
\@rowc@lors 7479
\@rowcolors 7478
\@seccntformat 6012
\@starttoc 9023
\@textsubscript 11086
\@textsuperscript 11082
\@title *377*
\@wrglossary 9218
\@wrindex 9207
\[. 9616
\\ *563*
$ *503*
$$ *503*
2in1 (package) *577*
2up (package) *577*

A

a4 (package) *577*
a4wide (package) *578*
a5comb (package) *578*
abstract (environment) 6686
abstract (package) *136*, *578*
\abstractname *117*, 6685
academicons (package) *580*
accsupp (package) *581*
acro (package) *581*
acronym (package) *583*
\addcontentsline 8974
addlines (package) *585*
\AddSubtitlePublished 6651
adjmulticol (package) *584*
Adobe (program) *84*
\affiliation 6503
afterpage (package) *585*
algorithm2e (package) *585*
algorithmicx (package) *165*, *589*
align (environment) 131
align* (environment) 158
alignat (environment) 239
alignat* (environment) 266
alltt (package) *590*
\AmS 11374

amsmath (package) 590
amsthm (package) 597
\and 377
anonchap (package) 601
anysize (package) 601
appendix (package) 136, 601
ar (package) 602
arabicfront (package) 603
array (package) 603
\arrayrulecolor 7486
\arrayrulecolornexttoken 7486
arydshln (package) 604
AsciiDoc (program) 84
AsciiDoctor (program) 84
Asciidoctor-LaTeX (program) 84
asymptote (package) 159, 606
atbegshi (package) 607
attachfile (package) 607
attachfile2 (package) 608
\attrib 167, 387, 948
\attribution 6696
authblk (package) 136, 610
\author 123, 377
autosec 359
axessibility (package) 611
axodraw2 (package) 611

B

babel (package) 168
\backmatter 5990
backref (package) 612
balance (package) 612
\BaseJobname 4896
BaseJobname (option) 113, 215
bbding (package) 612
\bfseries 11065
biblatex (package) 617
\bibliography 9265
\BibTeX 11369
bibunits (package) 618
bigdelim (package) 164, 618
bigfoot (package) 619
bigstrut (package) 620
bitpattern (package) 620
BlockClass (environment) 5265
\BlockClassSingle 5279
blowup (package) 621
booklet (package) 621
bookmark (package) 622
booktabs (package) 622
boolean:
  CombineHigherDepths 116, 348
  FileSectionNames 117, 317
  FormatEPUB 175, 237
  FormatWP 177, 238
  HTMLDebugComments 117, 233
  LWR@amsmultline 512
  LWR@copiedsidetoc 479
  LWR@doingapar 332
  LWR@doingcmidrule 402
  LWR@doingstartpars 332
  LWR@doingtbrule 402
  LWR@dynamicmath 315
  LWR@emptyatbang 403
  LWR@exitingtabular 449
  LWR@forceminipagefullwidth 541
  LWR@foundmrowcell 403
  LWR@freezethisautoid 473
  LWR@indisplaymathimage 495
  LWR@infloatrow 733
  LWR@intabularmetadata 403
  LWR@isstartingequation 520
  LWR@mathmacro 314
  LWR@minipagefullwidth 541
  LWR@minipagethispar 542
  LWR@opttablecol 416
  LWR@origmathjax 214
  LWR@skipatbang 403
  LWR@skippingmcolrowcell 403
  LWR@skippingmrowcell 403
  LWR@starredlongtable 443
  LWR@startedrow 402
  LWR@tableparcell 402
  LWR@tabularcelladded 402
  LWR@tabularmutemods 450
  LWR@tracinglwarp 232
  LWR@usedmultirow 403
  LWR@validtablecol 416
  LWR@verbtags 389
  LWR@xfakebold 496
  mathjax 214
  usingOSWindows 213
  warpingHTML 214
  warpingprint 214
  WPMarkFloats 178, 238
  WPMarkLOFT 179, 239
  WPMarkMath 179, 239
  WPMarkMinipages 179, 238
  WPMarkTOC 179, 238
  WPTitleHeading 180, 239
bophook (package) 623
bounddvi (package) 624
boxedminipage2e (package) 624
\boxframe 190
breakurl (package) 624
breqn (package) 625
bsheaders (package) 626
BVerbatim (environment) 222
bxpapersize (package) 627
bytefield (package) 627

C

calc (package) 222
cancel (package) 627
canoniclayout (package) 628
capt-of (package) 477
caption (package) 165, 230, 477, 628
\caption@begin 8955
\caption@end 8955
\captionlistentry 8959
\captionof 8990
\CaptionSeparator 8909
cases (package) 631
center (environment) 10151
\centering 10175
\centerline 10194
changebar (package) 632
changepage (package) 632
changes (package) 633
chappg (package) 634
\chapter 6216
chapterbib (package) 634
chemfig (package) 634
chemformula (package) 636
chemgreek (package) 640
chemmacros (package) 641
chemnum (package) 659
chkfloat (package) 660
chngpage (package) 660
cite (package) 660
CJK (package) 661
CJKutf8 (package) 661
class (key) [Gin] 733
class:
  internet 83
  komascript 166
  memoir 166, 167, 949
\cleardoublepage 11246
\clearpage 11246
cleveref (package) 133, 537
clrdblpg (package) 661
cm-super (package) 108
cmap (package) 109
cmdtrack (package) 661
color (package) 157, 662
\colorbox 73
\colorboxBlock 86, 10256
colortbl (package) 164, 662
CombineHigherDepths (boolean) . . 116, 348
comment (package) 220
\ConTeXt 11366
continue (package) 664
copyrightbox (package) 664
counter:
  FileDepth 116, 348
  FootnoteDepth 117, 342
  footnoteReset 342
  lofdepth 483
  lotdepth 483
  LWR@cellcolordepth 435
  LWR@currentautosec 360
  LWR@externalfilecnt 495
  LWR@hdashedlines 402
  LWR@hlines 402
  LWR@htmlfilenumber 317
  LWR@latestautopage 475
  LWR@lateximagedepth 518
  LWR@lateximagenumber 517
  LWR@LIpage 518
  LWR@midrulecounter 427
  LWR@minipagedepth 541
  LWR@nextautoid 474
  LWR@nextautopage 474
  LWR@nextequation 506
  LWR@prevFileDepth 360
  LWR@previousautopagelabel 352
  LWR@spandepth 332
  LWR@startingequation 520
  LWR@tablecolspecindex 404
  LWR@tablecolspecwidth 404
  LWR@tableLaTeXcolindex 404
  LWR@tabletotalLaTeXcols 404
  LWR@tabletotalLaTeXcolsnext . . . 404
  LWR@tabularDepth 403
  LWR@tabularpardepth 403
  LWR@thisautoid 472
  LWR@thisautoidWP 473
  SideTOCDepth 116, 481
  tocdepth 116
\cpagerefFor 10395
crop (package) 665
\CSSFilename 117, 120, 5510
ctable (package) 665
\CustomizeMathJax 5834, 5859
cuted (package) 668
cutwin (package) 668

D

\date 123
dblfloatfix (package) 669
dblfnote (package) 669
dcolumn (package) 669
\DeclareGraphicsExtensions 2
dejavu (package) 108
description (environment) 6992
diagbox (package) 670
dingbat (package) 671
\displaymathnormal . . 154, 495, 511, 9809
\displaymathother . . . 154, 495, 511, 9820
ditaa (package) 174
\dotfill 11165
\doublerulesepcolor 7488

\doublerulesepcolornexttoken 7488
dprogress (package) *672*
draftcopy (package) *672*
draftfigure (package) *673*
draftwatermark (package) *673*
dvipdfm (option) *110*, *218*
dvipdfmx (option) *110*, *218*
dvips (option) *110*, *218*

E

easy-todo (package) *674*
ebook (package) *675*
ed (package) *675*
ellipsis (package) *676*
embrac (package) *676*
\emph 10764
emptypage (package) *677*
\end@dlbfloat 8872
\end@float 8872
endfloat (package) *677*
endheads (package) *677*
endnotes (package) *136*, *678*
\enlargethispage 11245
\enskip *564*, 11191
enumerate (environment) 6973
enumerate (package) *679*
enumitem (package) *679*
environ (package) *224*
environment:
  fminipage *129*
  lateximage *516*
  picture *540*
  titlepage *123*
  titlingpage *123*
  warpall *122*
  warpHTML *119*, *121*
  warpprint *119*, *122*
environments:
  abstract 6686
  align 131
  align* 158
  alignat 239
  alignat* 266
  BlockClass 5265
  BVerbatim 222
  center 10151
  description 6992
  enumerate 6973
  eqnarray 9869
  equation 9787
  equation* 9795
  fcolorminipage 166, 10297
  flalign 185
  flalign* 212
  flushleft 10167
  flushright 10159
  fminipage 10693
  gather 77
  gather* 104
  itemize 6967
  lateximage 10019, 10146
  list 6937
  longtable 4
  LWR@BlockClassWP 5306
  LWR@blocktextcurrentfont 11057, 11114
  LWR@displaymathnormal 9656
  LWR@displaymathother 9661
  LWR@equationother 9675
  LWR@figcaption 8924
  LWR@nestspan 5118
  math 9655
  minipage 10480
  multline 20
  multline* 48
  picture 10455
  quote 6712
  tabbing 6796
  tabular 8433
  thebibliography 9275
  theindex 9183
  titlepage 6520
  titlingpage 14
  verbatim 6786
  verse 2, 6727
  warpall 829
  warpHTML 830
  warpprint 830
epigraph (package) *680*
epsfig (package) *681*
epstopdf (package) *158*, *681*
epstopdf (program) *156*, *532*
epstopdf-base (package) *682*
eqlist (package) *683*
eqnarray (environment) 9869
eqparbox (package) *683*
equation (environment) 9787
equation* (environment) 9795
errata (package) *684*
eso-pic (package) *685*
\etalchar *137*
etoolbox (package) *196*
eurosym (package) *686*
everyhook (package) *223*
everypage (package) *686*
everyshi (package) *687*
expl3 (package) *223*
extramarks (package) *687*

F

fancybox (package) *130*, *688*
fancyhdr (package) *693*
fancyref (package) *693*

fancytabs (package) 694
fancyvrb (package) 695
\fbox 129, 10667
\fboxBlock 129, 10675
\fcolorbox 103, 10258
\fcolorboxBlock 126, 10295
fcolorminipage (environment) . 166, 10297
figcaps (package) 700
figsize (package) 701
file:
  *-images.txt 522
  *_html.aux 352, 459, 460, 522
  *_html.lof 474
  *_html.lot 474
  *_html.tex 245
  glyphtounicode.tex 109
  lwarp.css 121, 251
  lwarp.ist 148, 289
  lwarp.xdy 149, 289
  lwarp_baseline_marker.eps 496
  lwarp_baseline_marker.png 496
  lwarp_formal.css 285
  lwarp_mathjax.txt 291
  lwarp_one_limage.cmd 290
  lwarp_sagebrush.css 280
  lwarp_tutorial.txt 93
  lwarpmk.conf 251
  lwarpmk.lua 185
  project.css 121
  project.lwarpmkconf 251
  sample_project.css 121, 288
  tutorial.tex 93
filecontents (package) 223
FileDepth (counter) 116, 348
\FilenameLimit 117, 5700
\FilenameNullify 132, 11030, 11115
\FilenameSimplify 132, 5721, 5860
FileSectionNames (boolean) 117, 317
fitbox (package) 701
fix2col (package) 702
fixme (package) 169, 702
fixmetodonotes (package) 703
flafter (package) 704
\flagverse 949
flalign (environment) 185
flalign* (environment) 212
Flare (program) 84
flippdf (package) 704
float (package) 165, 704
floatflt (package) 706
floatpag (package) 707
floatrow (package) 165, 707
fltrace (package) 712
\flushbottom 5034
flushend (package) 712
flushleft (environment) 10167
flushright (environment) 10159
fminipage (environment) 129, 10693
fnbreak (package) 713
fncychap (package) 713
fnlineno (package) 714
fnpara (package) 714
fnpos (package) 714
fontawesome (package) 715
fontawesome5 (package) 716
fontenc (package) 109, 717
fontspec (package) 109
footmisc (package) 717
footnote (package) 718
footnotebackref (package) 719
FootnoteDepth (counter) 117, 342
footnotehyper (package) 719
footnoterange (package) 719
footnoteReset (counter) 342
footnpag (package) 720
\ForceHTMLPage 135, 5965
\ForceHTMLTOC 136, 5971
foreign (package) 720
forest (package) 720
FormatEPUB (boolean) 175, 237
FormatWP (boolean) 177, 238
\framebox 10643
framed (package) 721
FrameMaker (program) 84
\frontmatter 5987
ftcap (package) 723
ftnright (package) 723
fullminipage (package) 724
fullpage (package) 724
fullwidth (package) 724
\fup 11090
\fussy 5036
fwlw (package) 725

G

gather (environment) 77
gather* (environment) 104
GELLMU (program) 83
gentombow (package) 725
geometry (package) 222, 725
gettitlestring (package) 223
[Gin]:
  class (key) 733
GladTeX (program) 83
gloss (package) 137, 726
glossaries (package) 137, 726
GlossaryCmd (option) . . . 113, 137, 217, 726
glyphtounicode.tex (file) 109
gmeometric (package) 728
graphics (package) 155, 729
graphicx (package) 155, 741

grffile (package) *157*, *741*
grid (package) *742*
grid-system (package) *742*
gridset (package) *742*

H

hang (package) *743*
hanging (package) *744*
Hevea (program) *83*
\hfill 11161
\HomeHTMLFilename 4898
HomeHTMLFilename (option) . *110*, *114*, *216*
\href 8752
\hrulefill 11163
\hskip *126*
\hspace *126*, *564*, 11199, 11229, 11235
htlatex (program) *83*
\HTMLAuthor *118*, *124*, 5536
HTMLDebugComments (boolean) *117*, *233*
\HTMLDescription *118*, *124*, 5541
\HTMLentity 4880
\HTMLFilename 4897
HTMLFilename (option) *110*, *114*, *217*
\HTMLFirstPageTop *118*, 5498
htmlglossary (option) [lwarpmk] . *137*, *726*
HTMLIndexCmd (option) *112*, *217*
\HTMLLanguage *117*, 6286
HTMLLatexCmd (option) *110*, *171*, *217*
\HTMLleftmargini (length) *167*, *387*, *388*, *948*
\HTMLPageBottom *118*, *378*, 5504
\HTMLPageTop *118*, 5501
\HTMLTitle *117*, *124*, 5531
\HTMLTitleAfterSection *117*, 6309
\HTMLTitleBeforeSection *117*, 6304
\HTMLunicode 4888
\HTMLvleftskip (length) *167*, *387*, *388*, *948*
hypcap (package) *745*
hypdestopt (package) *745*
\hyperindexref 9243
hypernat (package) *746*
hyperref (package) *133*, *466*, *746*
\hypertoc 9120
\hypertocfloat 9143
hyperxmp (package) *751*
hyphenat (package) *751*

I

idxlayout (package) *752*
\if@titlepage 6498
ifoddpage (package) *753*
ifplatform (package) *196*
\IgnoreMinipageWidths . . . *128*, *541*, 10470
ImagesDirectory (option) *215*
ImagesName (option) *215*
imakeidx (package) *753*
\include 1090
\includegraphics 291
indentfirst (package) *338*
InDesign (program) *84*
index (package) *757*
\InlineClass 5290
\inlinemathnormal *154*, *494*, 4873
\inlinemathother *154*, *494*, 4869
inputenc (package) *109*
inputenx (package) *109*
internet (class) *83*
intopdf (package) *759*
itemize (environment) 6967
\itshape 11070

K

karnaugh-map (package) *759*
\kern *126*
key:
  [Gin]:
    class *733*
keyfloat (package) *166*, *762*
komascript (class) *166*
kotex (package) *170*
kvoptions (package) *214*

L

\l@chapter 9163
\l@figure 9174
\l@paragraph 9172
\l@part 9162
\l@section 9169
\l@subparagraph 9173
\l@subsection 9170
\l@subsubsection 9171
\l@table 9175
\LaTeX 11326
LaTeX2HTML (program) *83*
\LaTeXe 11326
lateximage (environment) *516*, 10019, 10146
\LateximageFontScale 9941
\LateximageFontSizeName 9940
latexmk (option) *110*, *114*, *217*
latexmk (program) *172*
LatexmkIndexCmd (option) *112*, *217*
LaTeXML (program) *83*
layaureo (package) *768*
layout (package) *768*
layouts (package) *768*
leading (package) *771*
\leftline 10193
length:
  \HTMLleftmargini . . *167*, *387*, *388*, *948*
  \HTMLvleftskip *167*, *387*, *388*, *948*
  \LWR@cmidrulewidth *427*
  \LWR@heavyrulewidth *427*
  \LWR@lightrulewidth *427*

\LWR@minipageheight 541
\LWR@minipagewidth 541
\LWR@tempheight 564
\LWR@tempraise 564
\LWR@tempwidth 564
\LWR@thiscmidrulewidth 427
\VerbatimHTMLWidth 388
\vleftmargini 167, 387, 948
\vleftskip 167, 387, 948, 949
letltxmacro (package) 196
letterspace (package) 771
lettrine (package) 772
LibreOffice (program) 84
\linebreak 11239
lineno (package) 773
\LinkHome 4956, 4961
\linkhomename 114, 4953
Linux (program) 121, 211
lips (package) 775
list (environment) 6937
listings (package) 775
listliketab (package) 779
\listof 9077
\listoffigures 9051
\listoftables 9064
lltjext (package) 780
lmodern (package) 108, 109
lofdepth (counter) 483
longtable (environment) 4
longtable (package) 162, 781
lotdepth (counter) 483
lscape (package) 783
ltablex (package) 784
ltcaption (package) 784
ltxgrid (package) 785
ltxtable (package) 785
lua-check-hyphen (package) 785
lua-visual-debug (package) 786
luacolor (package) 786
\LuaLaTeX 11355
LuaLaTeX (program) [requirement] 87
\LuaTeX 11355
luatodonotes (package) 169, 786
lwarp (package) 110
lwarp-patch-komascript (package) . . 978
lwarp-patch-memoir (package) 980
lwarp.css (file) 121, 251
lwarp.ist (file) 148, 289
lwarp.xdy (file) 149, 289
lwarp_baseline_marker.eps (file) 496
lwarp_baseline_marker.png (file) 496
lwarp_formal.css (file) 285
lwarp_mathjax.txt (file) 291
lwarp_one_limage.cmd (file) 290
lwarp_sagebrush.css (file) 280
lwarp_tutorial.txt (file) 93
[lwarpmk]:
htmlglossary (option) 137, 726
printglossary (option) 137, 726
lwarpmk (option) 113, 216, 293
lwarpmk (program) 185, 293
lwarpmk epstopdf (program) 156, 532
lwarpmk pdftosvg (program) 156, 532
lwarpmk.conf (file) 251
lwarpmk.lua (file) 185
\lwarpsetup 693
\LWR@@footnotetext 5560
\LWR@@makebox@align 10604
\LWR@@makebox@paren 10589
\LWR@@printpendingfootnotes 5625
\LWR@addbaselinemarker 9372
\LWR@addcdashline 7757
\LWR@addcmidruletrim 7723
\LWR@addcmidrulewidth 7754
\LWR@addcompilecmd 1469
\LWR@addformatwpalignment 7773
\LWR@addleftmostbartag 7558
\LWR@addmathjax 9724
\LWR@addmulticolvertrulecolor . . . 8032
\LWR@addrulewidth 7728
\LWR@addtabularcellcolor 7901
\LWR@addtabularhrulecolor 7801
\LWR@addtabularrowcolor 7786
\LWR@addtabularrulecolors 7847
\LWR@afterendverbatim 6769
\LWR@amsmathbody 10006
\LWR@amsmathbodynumbered 10012
LWR@amsmultline (boolean) 512
\LWR@applyxfakebold 9364
\LWR@atbeginverbatim 6750
\LWR@backgroundcolor 36
\LWR@beginhideamsmath 9854
LWR@BlockClassWP (environment) . . . 5306
LWR@blocktextcurrentfont (environment) 11057, 11114
\LWR@botnavigation 4979
LWR@cdashlines 427
LWR@cellcolordepth (counter) 435
\LWR@cellHTMLcolor 7483
\LWR@checkloadbefore 64
\LWR@checkloadfilename 937
\LWR@checkloadnever 83
\LWR@clearmidrules 7638
\LWR@closeparagraph 5404
\LWR@closeparagraph@br 5394
\LWR@closeprevious 5006
\LWR@closetabledatacell 7106
\LWR@cmidrulewidth (length) 427
LWR@colafterspec 405
LWR@colatspec 404

LWR@colbangspec 404
LWR@colbarspec 405
LWR@colbeforespec 405
\LWR@columnHTMLcolor 7481
\LWR@columnspeclookahead 7225
\LWR@compilecmd 1466
\LWR@compileuplatex 1498
\LWR@convertto 632
LWR@copiedsidetoc (boolean) 479
\LWR@copyfile 1125
\LWR@createautosec 5996
LWR@currentautosec (counter) 360
\LWR@currentcss 5509
\LWR@currenttextcolor 11101
\LWR@customizedMathJax 5833
\LWR@customizeMathJax 5839
\LWR@descitem 6979
LWR@displaymathnormal (environment) 9656
LWR@displaymathother (environment) 9661
\LWR@docdashline 7687
\LWR@docmidrule 7671
\LWR@doequation 9737
\LWR@doindexentry 9226
LWR@doingapar (boolean) 332
LWR@doingcmidrule (boolean) 402
LWR@doingstartpars (boolean) 332
LWR@doingtbrule (boolean) 402
\LWR@domulticolumn 8070
\LWR@doubledollar 9570
LWR@dynamicmath (boolean) 315
\LWR@earlyclassloadnever 104
\LWR@earlyloadnever 89
LWR@emptyatbang (boolean) 403
\LWR@endfloatalignment 8905
\LWR@endhideamsmath 9862
\LWR@endofline 11172
\LWR@ensuredoingapar 5370
LWR@equationother (environment) . . 9675
\LWR@equationtag 9992
LWR@exitingtabular (boolean) 449
\LWR@expandableformatted 1187
\LWR@expandableformattedenv 1212
LWR@externalfilecnt (counter) 495
\LWR@fboxstyle 10661
LWR@figcaption (environment) 8924
\LWR@filenamenoblanks 5732
\LWR@filestart 6318
\LWR@findcurrenttextcolor 11104
\LWR@findword 934
\LWR@firstoffour 647
\LWR@floatalignment 8891
\LWR@floatalignmentname 8890
\LWR@floatbegin 8823
\LWR@floatend 8857
\LWR@floatstyle 2
\LWR@footnotebox 5555
\LWR@footnotetext 5589
LWR@forceminipagefullwidth (boolean) 541
\LWR@forceminwidth 10650
\LWR@forcenewpage 5023
\LWR@formatted 1172
\LWR@formattedenv 1202
\LWR@formatting 1171
LWR@foundmrowcell (boolean) 403
\LWR@fourthoffour 647
LWR@freezethisautoid (boolean) 473
\LWR@futurenonspacelet 7051
\LWR@FVstyle 56
\LWR@getexparray 4842
\LWR@getmynexttoken 7058
LWR@hdashedlines (counter) 402
\LWR@heavyrulewidth (length) 427
\LWR@hidelatexequation 9710
LWR@hlines (counter) 402
\LWR@HTML@caption@begin 8934
\LWR@HTML@caption@end 8946
\LWR@HTML@Gin@setfile 122
\LWR@HTML@ref 8695
\LWR@htmlblockcomment 5204
\LWR@htmlblocktag 5206
\LWR@HTMLcline 8414
\LWR@htmlclosecomment 5176
\LWR@htmlcomment 5197
\LWR@htmldivclass 5242
\LWR@htmldivclassend 5245
\LWR@htmlelement 5255
\LWR@htmlelementclass 5229
\LWR@htmlelementclassend 5234
\LWR@htmlelementclassline 5248
\LWR@htmlelementend 5258
LWR@htmlfilenumber (counter) 317
\LWR@htmlfileref 8602
\LWR@HTMLhline 8397
\LWR@HTMLLatexCmd 1508
\LWR@htmlmathlabel 9839
\LWR@htmlmulticolumn 8119
\LWR@htmlopencomment 5176
\LWR@htmlrefsectionfilename 4943
\LWR@HTMLsanitize 9944
\LWR@HTMLsanitizeexpand 9961
\LWR@htmlsectionfilename 4908
\LWR@htmlspan 5153
\LWR@htmlspanclass 5161
\LWR@htmltag 5171
\LWR@htmltagc 5108
\LWR@hyperindexrefnullified 9231
\LWR@imagesizebox 121
\LWR@includegraphicsb 140
\LWR@indentHTML 5105
\LWR@indexitem 9195

\LWR@indexnameref 9225
\LWR@indexsubitem 9199
\LWR@indexsubsubitem 9203
LWR@indisplaymathimage (boolean) . . 495
LWR@infloatrow (boolean) 733
\LWR@instertatbangcols 7098
LWR@intabularmetadata (boolean) . . . 403
\LWR@isolate 638
LWR@isstartingequation (boolean) . . 520
\LWR@itemizeitem 6960
LWR@latestautopage (counter) 475
LWR@lateximagedepth (counter) 518
\LWR@lateximagedepthref 8605
LWR@lateximagenumber (counter) 517
\LWR@lateximagenumberref 8608
\LWR@lateximagesfile 1087
\LWR@latexmkcmd 1484
\LWR@latexmkdvipdfm 1489
\LWR@latexmkvar 1478
\LWR@lightrulewidth (length) 427
LWR@LIpage (counter) 518
\LWR@listitem 6922
\LWR@loadafter 23
\LWR@loadbefore 55
\LWR@loadnever 70
\LWR@longtabledatacaptiontag 8130
\LWR@lookforpackagename 979
\LWR@lwarpconfversion 1460
\LWR@LwarpEnd 6469, 11419
\LWR@lwarplabel 8611
\LWR@LwarpStart 6398, 11419
\LWR@maketitlesetup 33, 6592
LWR@mathmacro (boolean) 314
\LWR@maybenewtablerow 7490
\LWR@maybeprintpendingfootnotes . 5644
\LWR@maybetocdata 9119
LWR@midrulecounter (counter) 427
LWR@midrules 426
LWR@minipagedepth (counter) 541
LWR@minipagefullwidth (boolean) . . . 541
\LWR@minipageheight (length) 541
\LWR@minipagestartpars 11179
\LWR@minipagestoppars 11182
LWR@minipagethispar (boolean) 542
\LWR@minipagewidth (length) 541
\LWR@multicolother 7973
\LWR@multicolpartext 7967
\LWR@multicolskip 7979
\LWR@multirowborder 3
\LWR@mynexttoken 7050
\LWR@myshorttoc 9000
\LWR@nameref 8599
LWR@nestspan (environment) 5118
\LWR@new@label 8647
\LWR@newautoidanchor 8878
\LWR@newautopagelabel 5825
\LWR@newhtmlfile 5863
LWR@nextautoid (counter) 474
LWR@nextautopage (counter) 474
LWR@nextequation (counter) 506
\LWR@notltjloadafter 42
\LWR@notmemoirloadafter 39
\LWR@nullfonts 10889
\LWR@nullifycomment 928
\LWR@nullifyNoAutoSpacing 8420
\LWR@nulllistfills 6929
\LWR@opacity 120
\LWR@openparagraph 5376
LWR@opttablecol (boolean) 416
\LWR@orig@setBold 9362
\LWR@orig@unsetBold 9363
\LWR@origcolspec 7092
\LWR@originname 305
\LWR@originnames 312
LWR@origmathjax (boolean) 214
\LWR@overline 11096
\LWR@parseaftercolumn 7295
\LWR@parseatcolumn 7235
\LWR@parsebangcolumn 7261
\LWR@parsebarcolumn 7306
\LWR@parsebeforecolumn 7284
\LWR@parsecoloncolumn 7331
\LWR@parseDcolumn 7387
\LWR@parsedrequirepackagenames . . . 927
\LWR@parsenormalcolumn 7356
\LWR@parsepcolumn 7368
\LWR@parsesemicoloncolumn 7352
\LWR@parsestarcolumn 7377
\LWR@parsetablecols 7393
\LWR@parsewcolumn 7372
\LWR@patcherror 633
\LWR@patchlists 6998
\LWR@pdfencoding 589
\LWR@PreloadedPackage 10198
LWR@prevFileDepth (counter) 360
LWR@previousautopagelabel (counter) 352
\LWR@printatbang 7533
\LWR@printbartag 7523
\LWR@printcloselist 6829
\LWR@PrintLatexCmd 1508
\LWR@printlength 909
\LWR@printmccoldata 7982
\LWR@printmccoltype 7925
\LWR@printopenlist 6830
\LWR@printpendingfootnotes 5641
\LWR@printpendingmpfootnotes 5653
\LWR@printthetitle 6544
\LWR@providelength 629
\LWR@ProvidesPackageDrop 1064
\LWR@ProvidesPackagePass 1049

\LWR@pushoneclose 6002
\LWR@quickfile 1084
\LWR@ref@ignorestar 8703
\LWR@remembertag 9996
\LWR@replaceEPSSVG 129
\LWR@requesttoc 6462
\LWR@requirepackagenames 926
\LWR@restoreorigaccents 1417
\LWR@restoreorigformatting 9294
\LWR@restoreoriglists 7026
\LWR@rotboxorigin 304
\LWR@rotstyle 112
\LWR@rowHTMLcolor 7482
\LWR@ruleHTMLcolor 7484
\LWR@sanitize 764
\LWR@sanitized 763
\LWR@scalestyle 115
\LWR@secondoffour 647
\LWR@section 6019
\LWR@sectionumber 5993
\LWR@select@html@hspace 11199
\LWR@select@html@nohspace 11229
\LWR@select@print@hspace 11232
\LWR@setexparray 4833
\LWR@setlatestname 8585
\LWR@setOSWindows 681
\LWR@setref 8593
\LWR@shellescapecmd 1461
\LWR@sidetoc 9093
\LWR@simplifycustom 5720
\LWR@simplifyname 5709
\LWR@singledollar 9595
LWR@skipatbang (boolean) *403*
LWR@skippingmcolrowcell (boolean) . . *403*
LWR@skippingmrowcell (boolean) *403*
LWR@spandepth (counter) *332*
LWR@starredlongtable (boolean) *443*
LWR@startedrow (boolean) *402*
LWR@startingequation (counter) *520*
\LWR@startingequationtag 9991
\LWR@startnewdepth 6006
\LWR@startpars 5446
\LWR@startref 8660
\LWR@stoppars 5464
\LWR@stripperiod 8584
\LWR@strresult 7090
\LWR@subaddcmidruletrim 7710
\LWR@subaddtabularcellcolor 7895
\LWR@subcdashline 7674
\LWR@subcmidrule 7656
\LWR@subhtmlelementclass 5211
\LWR@subhyperref 8729
\LWR@subhyperrefclass 8742
\LWR@subhyperreftext 8737
\LWR@subinlineimage 8802
\LWR@sublabel 8624
\LWR@subnewref 8689
\LWR@subsingledollar 9408
\LWR@subtableofcontents 9013
\LWR@subtabularhtmlcolumns 8202
\LWR@syncmathjax 9690
LWR@tablecolspec *404*
LWR@tablecolspecindex (counter) . . . *404*
LWR@tablecolspecwidth (counter) . . . *404*
\LWR@tabledatacolumntag 8293
\LWR@tabledatasinglecolumntag . . . 7572
LWR@tableLaTeXcolindex (counter) . . . *404*
LWR@tableparcell (boolean) *402*
LWR@tabletotalLaTeXcols (counter) . . *404*
LWR@tabletotalLaTeXcolsnext (counter) *404*
\LWR@tabular@warpprintonly 8416
LWR@tabularcelladded (boolean) *402*
LWR@tabularDepth (counter) *403*
\LWR@tabularendofline 7205
\LWR@tabularfinishrow 7159
\LWR@tabularhtmlcolumns 8212
\LWR@tabularleftedge 7563
LWR@tabularmutemods (boolean) *450*
LWR@tabularpardepth (counter) *403*
\LWR@tdaddstyle 7698
\LWR@tdendstyles 7704
\LWR@tdstartstyles 7697
\LWR@tempcolor 11102
\LWR@tempcolortwo 11102
\LWR@tempheight (length) *564*
\LWR@tempraise (length) *564*
\LWR@tempwidth (length) *564*
\LWR@textcurrentcolor 19, 11107
\LWR@textcurrentfont 11036, 11113
\LWR@thirdoffour 647
LWR@thisautoid (counter) *472*
LWR@thisautoidWP (counter) *473*
\LWR@thiscmidrulewidth (length) *427*
\LWR@thiscolspec 7571
\LWR@thisfilename 5703
\LWR@thisnewfilename 5708
\LWR@titlingmaketitle 83, 6643
\LWR@topnavigation 4976
\LWR@traceinfo 1153
LWR@tracinglwarp (boolean) *232*
LWR@trimlrules *426*
LWR@trimrrules *427*
\LWR@unknownengine 1473
LWR@usedmultirow (boolean) *403*
LWR@validtablecol (boolean) *416*
LWR@verbtags (boolean) *389*
\LWR@vspace 11236
\LWR@WPcell 7769
\LWR@writeconf 1610
\LWR@xcolorrowHTMLcolor 7480

LWR@xfakebold (boolean) 496
\LWRopquote 676
\LWRopseq 677
\LWRPrintStack 4984
\LWRsetnextfloat 8918
\LyX 11387

M

Mac OS (program) 121, 211
Madcap (program) 84
magaz (package) 788
\mainmatter 5983
make (program) 174
\makebox 10613
makeidx (package) 150, 789, 926
\MakeIndex 11369
makeindex (option) 110, 114, 217
makeindex (program) 148
makeindexStyle (option) . . . 110, 148, 215
\makelabel 392
\maketitle 47, 123, 6604
manyfoot (package) 789
marginal (package) 791
marginfit (package) 791
marginfix (package) 791
marginnote (package) 792
\marginpar 127, 346, 5665
\marginparBlock 127, 346, 5676, 5693
\markboth 5031
\markright 5032
marvosym (package) 792
math (environment) 9655
\mathimagename 118, 9354
MathJax (program) 152, 153, 493
MathJax (program) [requirement] 87
mathjax (boolean) 214
mathjax (option) 110, 114, 215
mathsvg (option) 110, 114, 215
\mbox 10586
mcaption (package) 793
\mcolrowcell 8368
mdframed (package) 131, 793
\mdseries 11064
memhfixc (package) 802
memoir (class) 166, 167, 949
metalogo (package) 802
mhchem (package) 803
microtype (package) 221, 805
midfloat (package) 806
midpage (package) 806
\MiKTeX 11386
minipage (environment) 10480
\minipagefullwidth 10468
minitoc (package) 806
morefloats (package) 807
moreverb (package) 807
mparhack (package) 808
\mrowcell 8365
MS-Windows (program) 121, 212
multicap (package) 808
multicol (package) 809
multicolrule (package) 810
\multicolumnrow 40, 8235
\multirow 811
multirow (package) 810
multitoc (package) 814
multline (environment) 20
multline* (environment) 48
musicography (package) 814

N

nameauth (package) 816
\Nameref 8721
\nameref 8712
nameref (package) 817
natbib (package) 817
nccfancyhdr (package) 818
needspace (package) 819
newclude (package) 168
\newfloat 4
newfloat (package) 224
\newline 11170
\newpage 11167
\newtheorem 391
newtxmath (package) 155
newunicodechar (package) 109
nextpage (package) 819
nicefrac (package) 155, 820
niceframe (package) 820
\noalign 8386
\nolinebreak 11240
\nolinkurl 8768
nomencl (package) 138, 821
nonfloat (package) 821
nonumonpart (package) 822
\nopagebreak 11244
\nopagecolor 72
nopageno (package) 822
\normalfont 11078
\normalmarginpar 5690
notes (package) 822
notespages (package) 823
nowidow (package) 823
ntheorem (package) 154, 824
\numberline 9114
numindex (option) [tocbibind] 151, 926

O

octave (package) 835
OpenOffice (program) 84
option:
  --shell-escape 108

[lwarpmk]:
htmlglossary 137, 726
printglossary 137, 726
[tocbibind]:
numindex 151, 926
[tocloft]:
titles 136
BaseJobname 113, 215
dvipdfm 110, 218
dvipdfmx 110, 218
dvips 110, 218
GlossaryCmd 113, 137, 217, 726
HomeHTMLFilename 110, 114, 216
HTMLFilename 110, 114, 217
HTMLIndexCmd 112, 217
HTMLLatexCmd 110, 171, 217
ImagesDirectory 215
ImagesName 215
latexmk 110, 114, 217
LatexmkIndexCmd 112, 217
lwarpmk 113, 216, 293
makeindex 110, 114, 217
makeindexStyle 110, 148, 215
mathjax 110, 114, 215
mathsvg 110, 114, 215
OSWindows 113, 121, 212, 216
pdftotextEnc 113, 216
PrintIndexCmd 110, 217
PrintLatexCmd 110, 171, 217
warpHTML 113, 215
warpprint 113, 214
xindy 110, 114, 217
xindyCodepage 110, 216
xindyLanguage 110, 216
xindyStyle 110, 149, 216
\OSPathSymbol 680
OSWindows (option) 113, 121, 212, 216
overpic (package) 159, 836

P

package:
2in1 577
2up 577
a4 577
a4wide 578
a5comb 578
abstract 136, 578
academicons 580
accsupp 581
acro 581
acronym 583
addlines 585
adjmulticol 584
afterpage 585
algorithm2e 585
algorithmicx 165, 589
alltt 590
amsmath 590
amsthm 597
anonchap 601
anysize 601
appendix 136, 601
ar 602
arabicfront 603
array 603
arydshln 604
asymptote 159, 606
atbegshi 607
attachfile 607
attachfile2 608
authblk 136, 610
axessibility 611
axodraw2 611
babel 168
backref 612
balance 612
bbding 612
biblatex 617
bibunits 618
bigdelim 164, 618
bigfoot 619
bigstrut 620
bitpattern 620
blowup 621
booklet 621
bookmark 622
booktabs 622
bophook 623
bounddvi 624
boxedminipage2e 624
breakurl 624
breqn 625
bsheaders 626
bxpapersize 627
bytefield 627
calc 222
cancel 627
canoniclayout 628
capt-of 477
caption 165, 230, 477, 628
cases 631
changebar 632
changepage 632
changes 633
chappg 634
chapterbib 634
chemfig 634
chemformula 636
chemgreek 640
chemmacros 641
chemnum 659

chkfloat 660
chngpage 660
cite 660
CJK 661
CJKutf8 661
cleveref 133, 537
clrdblpg 661
cm-super 108
cmap 109
cmdtrack 661
color 157, 662
colortbl 164, 662
comment 220
continue 664
copyrightbox 664
crop 665
ctable 665
cuted 668
cutwin 668
dblfloatfix 669
dblfnote 669
dcolumn 669
dejavu 108
diagbox 670
dingbat 671
ditaa 174
dprogress 672
draftcopy 672
draftfigure 673
draftwatermark 673
easy-todo 674
ebook 675
ed 675
ellipsis 676
embrac 676
emptypage 677
endfloat 677
endheads 677
endnotes 136, 678
enumerate 679
enumitem 679
environ 224
epigraph 680
epsfig 681
epstopdf 158, 681
epstopdf-base 682
eqlist 683
eqparbox 683
errata 684
eso-pic 685
etoolbox 196
eurosym 686
everyhook 223
everypage 686
everyshi 687
expl3 223
extramarks 687
fancybox 130, 688
fancyhdr 693
fancyref 693
fancytabs 694
fancyvrb 695
figcaps 700
figsize 701
filecontents 223
fitbox 701
fix2col 702
fixme 169, 702
fixmetodonotes 703
flafter 704
flippdf 704
float 165, 704
floatflt 706
floatpag 707
floatrow 165, 707
fltrace 712
flushend 712
fnbreak 713
fncychap 713
fnlineno 714
fnpara 714
fnpos 714
fontawesome 715
fontawesome5 716
fontenc 109, 717
fontspec 109
footmisc 717
footnote 718
footnotebackref 719
footnotehyper 719
footnoterange 719
footnpag 720
foreign 720
forest 720
framed 721
ftcap 723
ftnright 723
fullminipage 724
fullpage 724
fullwidth 724
fwlw 725
gentombow 725
geometry 222, 725
gettitlestring 223
gloss 137, 726
glossaries 137, 726
gmeometric 728
graphics 155, 729
graphicx 155, 741
grffile 157, 741

grid 742
grid-system 742
gridset 742
hang 743
hanging 744
hypcap 745
hypdestopt 745
hypernat 746
hyperref 133, 466, 746
hyperxmp 751
hyphenat 751
idxlayout 752
ifoddpage 753
ifplatform 196
imakeidx 753
indentfirst 338
index 757
inputenc 109
inputenx 109
intopdf 759
karnaugh-map 759
keyfloat 166, 762
kotex 170
kvoptions 214
layaureo 768
layout 768
layouts 768
leading 771
letltxmacro 196
letterspace 771
lettrine 772
lineno 773
lips 775
listings 775
listliketab 779
lltjext 780
lmodern 108, 109
longtable 162, 781
lscape 783
ltablex 784
ltcaption 784
ltxgrid 785
ltxtable 785
lua-check-hyphen 785
lua-visual-debug 786
luacolor 786
luatodonotes 169, 786
lwarp 110
lwarp-patch-komascript 978
lwarp-patch-memoir 980
magaz 788
makeidx 150, 789, 926
manyfoot 789
marginal 791
marginfit 791
marginfix 791
marginnote 792
marvosym 792
mcaption 793
mdframed 131, 793
memhfixc 802
metalogo 802
mhchem 803
microtype 221, 805
midfloat 806
midpage 806
minitoc 806
morefloats 807
moreverb 807
mparhack 808
multicap 808
multicol 809
multicolrule 810
multirow 810
multitoc 814
musicography 814
nameauth 816
nameref 817
natbib 817
nccfancyhdr 818
needspace 819
newclude 168
newfloat 224
newtxmath 155
newunicodechar 109
nextpage 819
nicefrac 155, 820
niceframe 820
nomencl 138, 821
nonfloat 821
nonumonpart 822
nopageno 822
notes 822
notespages 823
nowidow 823
ntheorem 154, 824
octave 835
overpic 159, 836
pagegrid 837
pagenote 136, 837
pagesel 837
paralist 838
parnotes 838
parskip 839
pbox 839
pdfcomment 840
pdflscape 840
pdfmarginpar 840
pdfpages 841
pdfprivacy 843

pdfrender 843
pdfsync 844
pdftricks 158, 844
pdfx 845
perltex 173
perpage 845
pfnote 846
phfqit 846
pifont 847
placeins 848
plarydshln 848
plext 848
plextarydshln 849
plextcolortbl 849
polyglossia 168
prelim2e 849
prettyref 850
preview 850
printlen 224
psfrag 158, 850
psfragx 851
pst-eps 852
pstool 159, 852
pstricks 158, 853
pxatbegshi 853
pxeveryshi 853
pxftnright 853
pxjahyper 854
pythontex 173
quotchap 854
quoting 855
ragged2e 855
realscripts 856
refcheck 857
refcount 224
register 857
relsize 127, 858
repeatindex 859
resizegather 860
rmpage 860
romanbar 861
romanbarpagenumber 861
rotating 861
rotfloat 862
rterface 173
rviewport 863
sagetex 173
savetrees 863
scalefnt 863
schemata 863
scrextend 864
scrhack 867
scrlayer 867
scrlayer-notecolumn 868
scrlayer-scrpage 869
scrpage2 870
section 871
sectionbreak 872
sectsty 872
semantic-markup 873
setspace 874
shadow 875
showidx 875
showkeys 875
showtags 876
sidecap 876
sidenotes 877
SIunits 878
siunitx 155, 530, 879
soul 884
soulpos 885
soulutf8 886
splitidx 886
srcltx 888
srctex 888
stabular 888
stfloats 889
struktex 889
subcaption 165, 890
subfig 165, 891
subfigure 895
supertabular 163, 896
sympytex 173
syntonly 897
tablefootnote 898
tabls 898
tabularx 898
tabulary 899
tascmac 899
textarea 901
textcomp 109, 126, 901
textfit 905
textpos 905
theorem 906
thinsp 910
threadcol 910
threeparttable 910
threeparttablex 163, 911
thumb 912
thumbs 912
tikz 157, 913
titleps 914
titleref 917
titlesec 917
titletoc 919
titling 136, 921
tocbasic 925
tocbibind 150, 151, 926
tocdata 928
tocenter 929

tocloft 136, 151, 601, 929
tocstyle 935
todo 935
todonotes 169, 936
topcapt 938
tram 938
transparent 939
trimclip 939
trivfloat 165, 940
truncate 941
turnthepage 941
twoup 941
typearea 942
typicons 942
ulem 943
umoline 944
underscore 945
units 155, 945
unitsdef 946
upref 947
url 133, 947
uspace 948
varioref 133
varwidth 225
verbatim 223
verse 167, 948, 949
versonotes 950
vertbars 950
vmargin 950
vowel 951
vpe 951
vwcol 952
wallpaper 954
watermark 954
widows-and-orphans 955
wrapfig 955
xbmks 956
xcolor 157, 533, 956
xechangebar 967
xellipsis 967
xetexko-vertical 968
xfakebold 968
xfrac 969
xifthen 223
xltabular 971
xltxtra 971
xmpincl 972
xparse 170, 222
xpatch 196
xpiano 972
xpinyin 973
xstring 224
xtab 163, 973
xunicode 975
xurl 976
xy 976
zhlineskip 977
zwpagelayout 977
\packagediagramname 118, 9355
\pagebreak 11241
\pagecolor 71
pagegrid (package) 837
pagenote (package) 136, 837
\pagenumbering 5037
\pageref 8707
\pagerefPageFor 8706
pagesel (package) 837
\pagestyle 5029
Pandoc (program) 84
\paragraph 6268
paralist (package) 838
\parbox 10577
parnotes (package) 838
\parsemulticolumnalignment 8017
parskip (package) 839
\part 6203
pbox (package) 839
pdfcomment (package) 840
pdfcrop (program) [requirement] 87
pdfLaTeX (program) [requirement] 87
pdflscape (package) 840
pdfmarginpar (package) 840
pdfpages (package) 841
pdfprivacy (package) 843
pdfrender (package) 843
pdfseparate (program) [requirement] 87, 92
pdfsync (package) 844
pdftocairo (program) 156, 531
pdftocairo (program) [requirement] 87, 92
pdftotext (program) [requirement] . 87, 92
pdftotextEnc (option) 113, 216
pdftricks (package) 158, 844
pdfx (package) 845
perl (program) [requirement] 92
perltex (package) 173
perpage (package) 845
pfnote (package) 846
\phantomsection 11304
phfqit (package) 846
picture (environment) 540, 10455
pifont (package) 847
placeins (package) 848
plarydshln (package) 848
Plastex (program) 83
plext (package) 848
plextarydshln (package) 849
plextcolortbl (package) 849
\PN@parnotes@auto 5375
polyglossia (package) 168
\popclose 4806

\postchaptername 6187
\postpartname 6185
\postsectionname 6189
\prechaptername 6187
prelim2e (package) *849*
\prepartname 6185
\presectionname 6189
prettyref (package) *850*
preview (package) *850*
\printauthor *378*, 6552, 6571
\printdate *378*, 6563, 6573
printglossary (option) [lwarpmk] *137*, *726*
\printindex 2
PrintIndexCmd (option) *110*, *217*
PrintLatexCmd (option) *110*, *171*, *217*
printlen (package) *224*
\printthanks *377*, *379*
\printtitle *378*, 6536, 6570
program:
[requirement]:
LuaLaTeX *87*
MathJax *87*
pdfcrop *87*
pdfLaTeX *87*
pdfseparate *87*, *92*
pdftocairo *87*, *92*
pdftotext *87*, *92*
perl *92*
XeLaTeX *87*
Adobe *84*
AsciiDoc *84*
AsciiDoctor *84*
Asciidoctor-LaTeX *84*
epstopdf *156*, *532*
Flare *84*
FrameMaker *84*
GELLMU *83*
GladTeX *83*
Hevea *83*
htlatex *83*
InDesign *84*
LaTeX2HTML *83*
latexmk *172*
LaTeXML *83*
LibreOffice *84*
Linux *121*, *211*
lwarpmk *185*, *293*
lwarpmk epstopdf *156*, *532*
lwarpmk pdftosvg *156*, *532*
Mac OS *121*, *211*
Madcap *84*
make *174*
makeindex *148*
MathJax *152*, *153*, *493*
MS-Windows *121*, *212*
OpenOffice *84*
Pandoc *84*
pdftocairo *156*, *531*
Plastex *83*
TeX2page *83*
TeX4ht *83*
TeXMaths *179*
TtH *83*
Unix *121*, *211*
Windows *121*, *212*
Word *84*
xindy *149*
project.css (file) *121*
project.lwarpmkconf (file) *251*
psfrag (package) *158*, *850*
psfragx (package) *851*
pst-eps (package) *852*
pstool (package) *159*, *852*
pstricks (package) *158*, *853*
\pushclose 4779
pxatbegshi (package) *853*
pxeveryshi (package) *853*
pxftnright (package) *853*
pxjahyper (package) *854*
pythontex (package) *173*

Q

\qquad *564*, 11190
\quad *564*, 11185
quotchap (package) *854*
quote (environment) 6712
quoting (package) *855*

R

ragged2e (package) *855*
\raggedbottom 5033
\raggedleft 10181
\raggedright 10187
\raisebox 10755
realscripts (package) *856*
\ref 8695
refcheck (package) *857*
refcount (package) *224*
\reflectbox 366
register (package) *857*
relsize (package) *127*, *858*
repeatindex (package) *859*
[requirement]:
LuaLaTeX (program) *87*
MathJax (program) *87*
pdfcrop (program) *87*
pdfLaTeX (program) *87*
pdfseparate (program) *87*, *92*
pdftocairo (program) *87*, *92*
pdftotext (program) *87*, *92*
perl (program) *92*

XeLaTeX (program) 87
\RequirePackage 1011
\resizebox 375
resizegather (package) 860
\ResumeTabular 8280
\reversemarginpar 5689
\rightline 10195
\rmfamily 11066
rmpage (package) 860
romanbar (package) 861
romanbarpagenumber (package) 861
\rotatebox 324
rotating (package) 861
rotfloat (package) 862
\rowcolor 7485
\rownum 7477
rterface (package) 173
\rule 11248
rviewport (package) 863

S

sagetex (package) 173
sample_project.css (file) 121, 288
savetrees (package) 863
\sb 11080
\scalebox 347
scalefnt (package) 863
schemata (package) 863
scrextend (package) 864
scrhack (package) 867
scrlayer (package) 867
scrlayer-notecolumn (package) 868
scrlayer-scrpage (package) 869
scrpage2 (package) 870
\scshape 11071
\section 6242
section (package) 871
sectionbreak (package) 872
sectsty (package) 872
semantic-markup (package) 873
\SetHTMLFileNumber 4899
setspace (package) 874
\sffamily 11067
\sfrac 969
shadow (package) 875
showidx (package) 875
showkeys (package) 875
showtags (package) 876
sidecap (package) 876
sidenotes (package) 877
SideTOCDepth (counter) 116, 481
\sidetocname 116, 9090
\simplechapterdelim 6013
\sishape 11072
SIunits (package) 878
siunitx (package) 155, 530, 879
\sloppy 5035
\slshape 11077
soul (package) 884
soulpos (package) 885
soulutf8 (package) 886
\sp 11079
splitidx (package) 886
srcltx (package) 888
srctex (package) 888
stabular (package) 888
\StartDefiningMath 4857
\StartDefiningTabulars 4847
stfloats (package) 889
\StopDefiningMath 4861
\StopDefiningTabulars 4851
struktex (package) 889
subcaption (package) 165, 890
subfig (package) 165, 891
subfigure (package) 895
\subparagraph 6276
\subsection 6251
\subsubsection 6259
supertabular (package) 163, 896
sympytex (package) 173
syntonly (package) 897

T

tabbing (environment) 6796
tablefootnote (package) 898
\tableofcontents 118, 9032
tabls (package) 898
tabular (environment) 8433
\TabularMacro 8278
tabularx (package) 898
tabulary (package) 899
tascmac (package) 899
\TeX 11312
TeX2page (program) 83
TeX4ht (program) 83
TeXMaths (program) 179
textarea (package) 901
\textbf 10782
\textcolor 48
textcomp (package) 109, 126, 901
textfit (package) 905
\textgreater 4892
\textit 10827
\textless 4890
\textmd 10773
\textnormal 10874
textpos (package) 905
\textrm 10791
\textsc 10836
\textsf 10800
\textsi 10848
\textsl 10865

\textsubscript 11083
\textsuperscript 11081
\texttt 10809
\textup 10818
\tfl@chapter@fix *940*
\thanks *123*
\thanksmarkseries 91
\theauthor *378*
thebibliography (environment) 9275
\thedate *378*
\theHTMLSection 6315
\theHTMLTitleSection 6314
\theHTMLTitleSeparator 6291
theindex (environment) 9183
\thempfootnote 5622
theorem (package) *906*
\thetitle *378*
thinsp (package) *910*
\thispagestyle 5030
threadcol (package) *910*
threeparttable (package) *910*
threeparttablex (package) *163*, *911*
thumb (package) *912*
thumbs (package) *912*
tikz (package) *157*, *913*
\title *123*, 5520
titlepage (environment) *123*, 6520
titleps (package) *914*
titleref (package) *917*
titles (option) [tocloft] *136*
titlesec (package) *917*
titletoc (package) *919*
titling (package) *136*, *921*
titlingpage (environment) 14, *123*
tocbasic (package) *925*
[tocbibind]:
  numindex (option) *151*, *926*
tocbibind (package) *150*, *151*, *926*
tocdata (package) *928*
tocdepth (counter) *116*
tocenter (package) *929*
[tocloft]:
  titles (option) *136*
tocloft (package) *136*, *151*, *601*, *929*
tocstyle (package) *935*
todo (package) *935*
todonotes (package) *169*, *936*
topcapt (package) *938*
\tracinglwarp *190*, 1152
tram (package) *938*
transparent (package) *939*
trimclip (package) *939*
trivfloat (package) *165*, *940*
truncate (package) *941*
\ttfamily 11068
TtH (program) *83*
turnthepage (package) *941*
tutorial.tex (file) *93*
twoup (package) *941*
typearea (package) *942*
typicons (package) *942*

U

ulem (package) *943*
umoline (package) *944*
\underline 11091
underscore (package) *945*
units (package) *155*, *945*
unitsdef (package) *946*
Unix (program) *121*, *211*
\up 11089
upref (package) *947*
\upshape 11069
\url 8785
url (package) *133*, *947*
\UseMinipageWidths *128*, *541*, 10469
usingOSWindows (boolean) *213*
uspace (package) *948*

V

varioref (package) *133*
varwidth (package) *225*
verbatim (environment) 6786
verbatim (package) *223*
\VerbatimHTMLWidth (length) *388*
\verbatiminput 6778
verse (environment) 2, 6727
verse (package) *167*, *948*, *949*
versonotes (package) *950*
vertbars (package) *950*
\vleftmargini (length) *167*, *387*, *948*
\vleftskip (length) *167*, *387*, *948*, *949*
vmargin (package) *950*
vowel (package) *951*
vpe (package) *951*
vwcol (package) *952*

W

wallpaper (package) *954*
warpall (environment) *122*, 829
warpHTML (environment) *119*, *121*, 830
warpHTML (option) *113*, *215*
\warpHTMLonly *119*, *122*, 820
warpingHTML (boolean) *214*
warpingprint (boolean) *214*
warpprint (environment) . . . *119*, *122*, 830
warpprint (option) *113*, *214*
\warpprintonly *119*, *122*, 819
watermark (package) *954*
widows-and-orphans (package) *955*
Windows (program) *121*, *212*

Word (program) 84
WPMarkFloats (boolean) 178, 238
WPMarkLOFT (boolean) 179, 239
WPMarkMath (boolean) 179, 239
WPMarkMinipages (boolean) 179, 238
WPMarkTOC (boolean) 179, 238
WPTitleHeading (boolean) 180, 239
wrapfig (package) 955

X

xbmks (package) 956
xcolor (package) 157, 533, 956
xechangebar (package) 967
\XeLaTeX 11357
XeLaTeX (program) [requirement] 87
xellipsis (package) 967
\XeTeX 11357
xetexko-vertical (package) 968
xfakebold (package) 968
xfrac (package) 969
\xfracHTMLfontsize 3
xifthen (package) 223
xindy (option) 110, 114, 217
xindy (program) 149
xindyCodepage (option) 110, 216
xindyLanguage (option) 110, 216
xindyStyle (option) 110, 149, 216
xltabular (package) 971
xltxtra (package) 971
xmpincl (package) 972
xparse (package) 170, 222
xpatch (package) 196
xpiano (package) 972
xpinyin (package) 973
xstring (package) 224
xtab (package) 163, 973
xunicode (package) 975
xurl (package) 976
xy (package) 976

Z

zhlineskip (package) 977
zwpagelayout (package) 977

General Index

This is an index of instructions and concepts. Look here when wondering how to do something, and check the Troubleshooting Index when something goes wrong.

Symbols

\, ... 126
~ 126

A

accents
  in section & file names 357
adapting
  class 184
  document 107
  package 183
affiliation
  multiple authors 135
algorithmicx
  with newfloat, trivfloat 940
array
  mhchem 803
author
  HTML meta tag 124, 340
  multiple 135

B

baseline
  tabular 416
bibliography
  HTML page and TOC 135
bitmapped fonts 108
bugs 187

C

Calibre 175
chemistry
  Greek symbols 640
class
  modifying for lwarp 184
code listings 125
compiling
  custom 171
Computer Modern 108
converting
  class 184
  document 107
  package 183
CSS
  file selection 120
  lwarp.css 121
  per HTML page 120
  project-specific changes 121
ctable 164

D

danger icon 195
debugging 187
  HTML debug comments 232
  tracing log 232
Deja Vu 108
description
  HTML meta tag 124, 340
display math
  complicated objects 154
document
  convert existing 107
DVI LaTeX 103, 108
dynamic math 154
dynamic math expressions 314

E

endnotes
  HTML page and TOC 135
EPS image
  converting 105
  using 155, 531
EPUB
  conversion software 175
  HTML conversion settings 175, 238
error messages 187
export
  to word processor 177

F

FAQ 187
filename
  accent in 357
  hashed 497, 522
  international languages 167
  length 117
  simplify 132
  underscore in 114, 127
  unique 117
font
  Computer Modern 108
  Deja Vu 108

ligatures 109
packages 109
selection 108
size
lateximage 152, 492, 517
math, SVG 152, 492, 517
xfrac 969
type 1 vector 108
type 3 bitmapped 108
footnotes 340
numbering 133
foreign
section names 167
framed objects 129
Frequently Asked Questions 187

G

generator
HTML meta tag 370
GIF images 156, 532
gloss 137
glossaries
HTML page and TOC 135
language 137
options 137
processing 104
graphics
formats 155, 531
Greek
chemistry symbols 640

H

hash
SVG image filename 497, 522
heading, word processor 180
horizontal space 126
between minipages 563
HTML
conversion settings 114
debug comments 232
EPUB 175, 238
word processor 177, 238
conversion suggestions 124
entities, conversion 125
filename generation 119
headings 194
meta tag
author 124, 340
description 124, 340
generator 370
title 117, 124, 339, 340
viewport 371
selecting print/HTML definitions . . 233
tabular column conversion 417
verbatim, in 125
hyperref
and xindy 139

I

icon
warning 195
image
GIF 156, 532
graphicx package 531
hashed filename 497, 522
PDF or EPS
converting 105, 156, 532
using 155, 531
PNG and JPG 156, 532
processing 293
`\includegraphics`
using 155, 531
index
custom makeindex style file 148
custom xindy style file 149
custom display styles 150
formatting 487
HTML page and TOC 135
letter headings 753
placement and TOC options . . . 150, 926
processing 97, 98, 139
see, seealso, ranges 139
source code 139
table of contents 150, 926
UTF-8 109
xindy and hyperref 139
inline math
complicated objects 154
international
section names 167
item
empty 392

J

JAVASCRIPT
MATHJAX 151, 492
JPG images 156, 532

L

label
in HTML 374
math environment 513
language
glossaries 137
language HTML metadata 368
lateximage
font size 152, 492, 517
processing 293
Latin Modern font 108
LIBREOFFICE
conversion recommendations 180

import into 177
section headings 180
ligatures 109, 221
line numbers 195
list
empty item 392
filename 127
listings, program code 125
locale 174
LuaLaTeX
detection 196
file & section names 357
lwarp
loading 110
options 110
`lwarp.ist`
customizing 148
`lwarp.xdy`
customizing 149
lwarpmk
customizing 185

M

make utility 174
makeindex
customizing 148
margin
numbers 195
tags 195
markup languages 84
math
display with complicated objects . . 154
dynamic 154, 314
font size — SVG 152, 492, 517
inline with complicated objects . . . 154
MathJax custom functions . . . 153, 493
MathJax summary 152, 493
`mathjax` option 215
`mathsvg` option 215
mhchem 803
SVG summary 152, 492
word processor conversion 179
MathJax
custom functions 153, 493
`mathjax` option 215
summary 152, 493
`\mcolrowcell` 162
MD5 hash
SVG image filename 497, 522
memoir
verse 949
meta tag, HTML
author 124, 340
description 124, 340
generator 370
title 124, 339, 340
viewport 371
minipage
framed 129
horizontal space between 563
modifying
class 184
document 107
package 183
`\mrowcell` 162
`\multicolumn`
with `\multirow` 162
`\multirow`
with `\multicolumn` 162
multirow
`\mrowcell` and `\mcolrowcell` 162

N

newfloat
with trivfloat, algorithmicx 940
nomencl 138
numbers
left margin 195

P

package
modifying for lwarp 183
required 221
`\par`
hooks 336
PDF image
converting 105
using 155, 531
Perl 92
PNG images 156, 532
Poppler 87, 92
print
selecting print/HTML definitions . . 233
problems 187
program listings 125
programs
utility 86
`\published` 384

S

section
depths 194
file names 132
heading, word processor 180
international languages 167
settings
CSS project-specific 121
CSS selection 120
HTML conversion 114
lwarp package options 110
selecting output 121
title page 123
shell escape 108

siunitx
with *TeXMaths* 179
space
horizontal 126
between minipages 563
stack depths 194
\subtitle 384
SVG
converting from PDF or EPS 105
dynamic math 314
image processing 293
math summary 152, 492
mathsvg option 215

T

tabular
baseline 416
HTML colummn conversion 417
macros inside 160, 400
\multicolumn with \multirow 162
multirow \mrowcell and \mcolrowcell 162
tikz
catcodes 913
dollar redefined 913
title
HTML meta tag 124, 339, 340
titlepage
\subtitle and \published 384
tracing log 232
trivfloat
with newfloat, algorithmicx 940
troubleshooting 187
HTML debug comments 232
tracing log 232
type 1 vector fonts 108
type 3 bitmapped fonts 108

U

underscore
filename 114, 127
Unicode
enhanced coverage 108
file & section names 357
input characters 209
selection 108
UTF-8
enhanced coverage 108
file & section names 357
index 109
locale 174
selection 108
utility
programs 86

V

vector fonts 108
verbatim
code and HTML tags 125
viewport
HTML meta tag 371

W

warning icon 195
word processor
conversion recommendations 180
HTML conversion settings 177, 238
section headings 180

X

XeLaTeX
detection 196
file & section names 357
xindy
and hyperref 139
customizing 149
xparse
warnings 170

Troubleshooting Index

This index is a sorted reference of problems and solutions. In order to make it easier to locate a solution, the same issue may be addressed by more than one entry.

Entries with higher page numbers are often duplicates of entries with lower page numbers, as the same warning may occur within the user manual and again within the source code for a given package.

A

abstract
  missing TOC 136, 578
acronym
  multiply-defined labels 583
\AddSubtitlePublished 385
affiliation 378
alt tags 154, 188
AMSmath
  ntheorem
    numbering 155, 824
appendix
  incorrect TOC link 136, 601
array
  chemformula 169
authblk
  \theauthor 377, 378
  titling 136, 377, 610, 921
author
  affiliation 378
  formatting 123

B

babel
  French 168
backref 612
backref 133
bibliography
  HTML page and TOC 135
bibtex
  \etalchar 137
  Improper \prevdepth 137
bigdelim 164, 618
bigfoot 134, 789
boxes 127
breqn
  darray 625
  MATHJAX 625

C

Calibre
  EPUB conversion 175
caption
  numbering 165
  options 165
cases
  MATHJAX 631
chemfig 169
chemformula
  MATHJAX 169, 636
chemgreek
  fontspec mapping 640
  text-mode symbols 640
chemmacros
  \makepolymerdelims 641
  redox reactions 641
colortbl 164, 662
cross reference
  incorrect link 189
  missing 188
CSS 190
ctable 164

D

ditaa 174
duplcate filename 132

E

\endhead, etc. 162
endnotes
  HTML page and TOC 135
\ensuremath 187
epstopdf 158, 682
EPUB
  encoding 175
  page order 175
  search order 175
  section breaks 176
\etalchar 137

F

fancybox
  \VerbatimFootnotes . . . 134, 689, 695
fancyvrb
  \VerbatimFootnotes . . . 134, 689, 695

figure
macro in name 188
file
inaccessible 116
filename
accents 357
corrupted 132, 167
duplicate 132
international, UTF-8 167
Korean 170
macro in name 132
math in 107, 132, 151, 491
Missing $ inserted 187
fixme 169, 702
float
alignment 126, 164
out of sequence 189
floatrow
\FBwidth and \FBheight 165, 707
with subfig 165, 707
floatrow
\ttabbox 160, 399
font
ligatures 109
missing symbols 126, 901
monospace 109
package conflicts 108
selection 108
UTF-8 108
fontspec 108
footmisc 134, 341
footnote
displaymath 134, 689, 695
in math 134
in sectioning command 133
memoir 134, 341
numbering 133
paragraph tags 134, 689, 695
sectioning, footmisc 134, 341
sectioning, verbatim 134, 689, 695
title 377
verbatim 134
\VerbatimFootnotes . . . 134, 689, 695
forest 720
formatting
\bfseries etc. 125, 551
frames 129

G

gloss 137
glossaries
HTML page and TOC 135
makeglossaries not found . . . 137, 726
page numbers 138, 727
style 138, 727
graphics
\rotatebox, \scalebox, \reflectbox 157, 532
image format priorities 156, 532
images out of order 99, 189
optional arguments 156, 532
scale option 107, 155, 531
scaled 730
viewport 156, 532
Greek packages 640
grffile 157, 741

H

horizontal spacing 165, 891
HTML
&, <, > 125, 551
alt tags 154
author 340
corrupted 123, 127, 187, 190
entities 125, 551
image appear as HTML code . . . 99, 189
inaccessible pages 116, 118
starred section 135
invalid 125
missing pages
filename not unique 117
recompile 190
SideTOCDepth and FileDepth . . 116
SideTOCDepth and tocdepth . . . 116
page did not update 116, 190
settings
changed 114
undefined 187
validation 125
\HTMLAuthor 340
HTMLIndexCmd
filenames 112
hyperref
backref 133
comments between arguments . . . 133
incorrect link 189

I

image
appears as HTML code 99, 189
format priorities 156, 532
incorrect 99, 189
viewport 156, 532
Improper \prevdepth
bibtex 137
boxes 187
\includegraphics
optional arguments 156, 532
scale 107, 155, 531
index
empty 150

empty link 132, 188
formatting 487
HTML page and TOC 135
missing entries 139
numbers, not links 224
reference ranges 149
see and seealso 149
styling references 149
xindy and hyperref 149
xstring bug 224

K

keyfloat 166, 762

L

label
\nameref empty 132, 188
characters 132, 188
Label(s) may have changed 187
\LateximageFontSizeName 518
Leaders not followed by proper glue . . 187
LibreOffice
import 177
ligatures 109
LINUX 121, 211
list
empty item 127, 392
listings 189
lists
label formatting 392
locale 174
longtable
\endhead, etc. 162
ltxtable
numbering 785
luaLaTeX 108
\LWRbackslash 171
\LWRdollar 171
\LWRhash 171
\LWRopquote 171
\LWRopseq 171
\LWRpercent 171

M

MAC OS 121, 211
makeglossaries
not found 137, 726
\makelabel 392
manyfoot 134, 789
\marginpar 127, 346
math
alt tags 188
appears as HTML code 99, 189
chemformula 169
custom macros 188
dynamic 314
equation numbering
ntheorem 155, 824
file name 107, 132, 151, 491
footnote 134
in TeX boxes 152, 493
incorrect 99, 189, 314
non-math contents 188
section name 107, 132, 151, 491
slow or failed compile 188
subequations 153, 493
tabbing 159, 391
Ti*k*z 154
MATHJAX
breqn 625
cases 631
chemformula 169, 636
errors 154, 188, 314
mhchem 803
siunitx 153, 155, 494, 530, 879
subequations 153, 493
unsupported packages . . 153, 188, 494
\mcolrowcell 162
memoir
footmisc 134, 341
options clash 166, 981
version clash 166, 981
mhchem
MATHJAX 803
nested dollar signs 803
minipage
alignment 128, 541
horizontal space between 563
in a span 128, 540
inline 127, 540
multicols, width in 128, 541
size 128, 540
tabular, width in 128, 541
Misplaced \noalign 163, 781
tabular
rules 161, 400
Misplaced \omit
tabular 235
Misplaced alignment tab character &
ctable 164, 665
floatrow 165, 707
frames 129
supertabular 163, 896, 973
tabular
macros 160, 314, 399
Missing $ inserted
filename or URL 187
morewrites 187
morewrites 150
\mrowcell 162
MS-WINDOWS 121, 212

multiply-defined labels
acronym 583
\multirow and \multicolumn 162, 811
multirow
\mrowcell and \mcolrowcell 162

N

newclude 168
newtxmath 155
nicefrac 155
No room for a new \write 187
nomencl 138
ntheorem 824
font 154, 824
numbering 155, 824

O

operating system 121, 211
options clash
memoir 166, 981
overpic 159, 836

P

package
version numbers with memoir . 166, 981
page
inacessible 116
page counter
references 133
SVG images 99, 189
page numbers 133, 189, 537
pdftricks 158, 844
perltex 173
pfnote
numbering 134, 846
polyglossia
Undefined control sequence 168
poppler
Syntax Warning (ligature) 715
PrintIndexCmd 112
psfrag 158
pstool 159, 852
pstricks 158, 853
pythontex 173

R

reference
% character between arguments . . 189
empty link 132, 188
incorrect link 189
label characters 132, 188
missing or incorrect 188
page number 133, 189, 537
repeatindex 859
rterface 174

S

sample_projects.css
overwritten 120
scale (\includegraphics option) . . . .
. . . . . 107, 155, 531
sectioning
accents 357
duplicate name 132
international language 167
macro in name 132, 188
math in name 107, 132, 151, 491
missing 116
starred section 135
word processor import 180
siunitx
MathJax 155, 530, 879
with TeXMaths 179
siunitx 155, 530, 879
MathJax 153, 494
S column 161, 401
tabular S and s columns . 155, 530, 879
splitidx
\thepage and \AtWriteToIndex 140, 886
subcaption
numbering 165
subfig
options 165, 891
with floatrow 165, 707
SVG image
appears as HTML code 99, 189
incorrect 99, 189
math incorrect 314
out of order 99, 189
sympytex 174
Syntax Warning (ligature) 715

T

tabbing
math 159, 391
table
macro in name 188
numbering 785
Table of Contents
missing 118
tabular
* column specification 160, 400
baselines 416
corrupt rows 160, 399, 449
\endhead, \endfoot, \endlastfoot
. . . . . 162, 781
inside an environment . . 160, 399, 449
\kill 163, 781
macro inside 160, 400
Misplaced \noalign 161, 400
Misplaced alignment tab character &
macros 160, 399

rules 314
\multicolumn with \multirow 162
multirow \mrowcell and \mcolrowcell 162
\newcolumntype 161, 400
numbering 971
row corruption 160, 400
rules 161, 400
S column 161, 401
TeXMaths 179
text
&, <, > 125, 551
\bfseries etc. 125, 551
corrupted 108
textcomp
missing symbols 126, 901
\theauthor and authblk 377, 378
threeparttablex 163
tikz
in math 154
matrices, & 157, 913
title
affiliation 378
newlines 123
\thanks 377
titling
authblk 136, 377, 610, 921
hooks 385
tocloft
chapter titles 136, 151, 601, 929
todonotes 169, 786, 936
tracing lwarp 190
tram 938
transparent 939

U

Undefined control sequence
polyglossia 168
Unicode
fonts 108
UTF-8 locale 174
units 155
Unix 121, 211
URL
Missing $ inserted 187
UTF-8
locale 174

V

verbatim
footnote 134
framed 130, 688
VerbatimFootnotes 134, 689, 695
verse
spacing 168, 387, 948
version numbers
with memoir 166, 981
viewport 156, 532

W

warpall 187
warpHTML 122, 187
warpprint 122, 187
Windows 121, 212
word processor
import 177
sectioning headings 180

X

xeLaTeX 108
xfakebold 968
xfrac 969
xindy
hyperref 149
options
HTMLIndexCmd 112
LatexmkIndexCmd 112
PrintIndexCmd 112
xltabular
numbering 971
xparse 170
xstring 224
xy 976

Index of Indexes

C

Change History 1006

G

General Index 1052

I

Index of Objects 1032

T

Troubleshooting Index 1056