

# The `luatextra` package

Manuel Pégourié-Gonnard & Élie Roux  
Support: [lualatex-dev@tug.org](mailto:lualatex-dev@tug.org)

2010/10/10 v1.0

## Abstract

The `luatextra` package loads essential and useful packages for Lua<sup>L</sup>A<sub>T</sub>E<sub>X</sub>. It is meant as convenience for users who don't want to load them individually.

## Contents

<b>1 Documentation</b>	<b>1</b>
<b>2 Implementation</b>	<b>2</b>
<b>3 Test file</b>	<b>2</b>

## 1 Documentation

The following packages are loaded:

- `fontspec` — advanced font management, integrated in the L<sup>A</sup>T<sub>E</sub>X font selection scheme, with access to system fonts and opentype features;
- `luacode` — tools for easier integration of Lua code in L<sup>A</sup>T<sub>E</sub>X;
- `metalogo` — commands for logos, including \LuaTeX{} and \LuaLaTeX{};
- `fixltx2e` — various fixes and small enhancements for the L<sup>A</sup>T<sub>E</sub>X core;
- `luatexbase` — low-level management of LuaTeX's new and extended resources;
- `lualibs` — additional general-purpose Lua functions.

In case you are not yet familiar with the available Lua<sup>L</sup>A<sub>T</sub>E<sub>X</sub> packages, you might want to check the document `lualatex-doc.pdf` from the eponymous package.

## 2 Implementation

```
1 <*package>
  Identify.
2 \ProvidesPackage{luatextra}[2010/10/10 v1.0 Loading usual LuaLaTeX packages]
  Make sure LuaTeX is being used.
3 \RequirePackage{ifluatex}
4 \ifluatex\else
5   \PackageError{luatextra}{LuaTeX is required for this package. Aborting.}%
6   This package can only be used with the LuaTeX engine^^J%
7   (command 'lualatex' or 'luatex').^^J%
8   Package loading has been stopped to prevent additional errors.%
9   \expandafter\endinput
10 \fi
Load packages; luatexbase and lualibs are loaded (indirectly) by fontspec, but
just to be sure (in case it changes in the future).
11 \RequirePackage{fontspec}
12 \RequirePackage{luatexbase}
13 \RequireLuaModule{lualibs}
14 \RequirePackage{metalogo}
15 \RequirePackage{luacode}
16 \RequirePackage{fixltx2e}
17 </package>
```

## 3 Test file

Very minimal, just check that the package correctly loads. We have to use `\documentclass` to make `xkeyval` (loaded by `fontspec`) happy.

```
18 <*test>
19 \documentclass{minimal}
20 \usepackage{luatextra}
21 \stop
22 </test>
```